



US008182473B2

(12) **United States Patent**
Altshuler et al.

(10) **Patent No.:** **US 8,182,473 B2**

(45) **Date of Patent:** **May 22, 2012**

(54) **COOLING SYSTEM FOR A
PHOTOCOSMETIC DEVICE**

(58) **Field of Classification Search** None
See application file for complete search history.

(75) Inventors: **Gregory B. Altshuler**, Wilmington, MA
(US); **Joseph P. Caruso**, Reading, MA
(US); **Henry H. Zenzie**, Dover, MA
(US); **James G. Burke, III**,
Londonderry, NH (US); **Andrei V.
Erofeev**, N. Andover, MA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

853,033 A 5/1907 Roberts
(Continued)

FOREIGN PATENT DOCUMENTS

AT 400305 12/1995
(Continued)

OTHER PUBLICATIONS

A. V. Belikov et al., "Indentification of enamel and dentine under
tooth laser treatment," SPIE vol. 2623, Progress in Biomedical Optics
Europt Series, Proceedings of Medical Applications of Lasers III, pp.
109-116, Sep. 1995.

(Continued)

Primary Examiner — Henry M Johnson, III

Assistant Examiner — Lynsey Crandall

(74) *Attorney, Agent, or Firm* — Wilmer Cutler Pickering
Hale and Dorr LLP

(73) Assignee: **Palomar Medical Technologies**,
Burlington, MA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1400 days.

(21) Appl. No.: **11/603,712**

(22) Filed: **Nov. 22, 2006**

(65) **Prior Publication Data**

US 2007/0129711 A1 Jun. 7, 2007

Related U.S. Application Data

(63) Continuation of application No. 10/154,756, filed on
May 23, 2002, now Pat. No. 7,204,832, and a
continuation-in-part of application No. 10/052,474,
filed on Jan. 18, 2002, now Pat. No. 6,663,620, which
is a continuation of application No. 09/473,910, filed
on Dec. 28, 1999, now Pat. No. 6,517,532, and a
continuation-in-part of application No. 09/078,055,
filed on May 13, 1998, now Pat. No. 6,273,884, which
is a continuation-in-part of application No.
09/268,433, filed on Mar. 12, 1999, now Pat. No.

(Continued)


(51) **Int. Cl.**
A61B 18/18 (2006.01)

(52) **U.S. Cl.** **606/9; 607/89; 606/13**

ABSTRACT

Photocosmetic device for use in medical or non-medical envi-
ronments (e.g., a home, barbershop, or spa), which can be
used for a variety of tissue treatments. Radiation is delivered
to the tissue via optical systems designed to pattern the radi-
ation and project the radiation to a particular depth. The device
has a variety of cooling systems including phase change
cooling solids and liquids to cool treated skin and the radi-
ation sources. Contact sensors and motion sensor may be used
to enhance treatment. The device may be modular to facilitate
manufacture and replacement of parts.

16 Claims, 25 Drawing Sheets



Related U.S. Application Data

6,508,813, which is a continuation-in-part of application No. 08/759,036, filed on Dec. 2, 1996, now Pat. No. 6,015,404, and a continuation-in-part of application No. 08/759,136, filed on Dec. 2, 1996, now abandoned, which is a continuation-in-part of application No. 09/634,981, filed on Aug. 9, 2000, now Pat. No. 6,511,475, which is a continuation-in-part of application No. 09/847,043, filed on Apr. 30, 2001, now Pat. No. 6,653,618.

- (60) Provisional application No. 60/363,798, filed on Mar. 12, 2002, provisional application No. 60/115,447, filed on Jan. 8, 1999, provisional application No. 60/164,492, filed on Nov. 9, 1999, provisional application No. 60/046,542, filed on May 15, 1997, provisional application No. 60/077,794, filed on Jan. 8, 1999, provisional application No. 60/077,726, filed on Mar. 12, 1998, provisional application No. 60/200,431, filed on Apr. 28, 2000, provisional application No. 60/292,827, filed on May 23, 2001, provisional application No. 60/363,871, filed on Mar. 12, 2002.

(56)

References Cited

U.S. PATENT DOCUMENTS

1,590,283 A	6/1926	Catlin	4,601,753 A	7/1986	Soileau et al.
1,706,161 A	3/1929	Hollnagel	4,608,978 A	9/1986	Rohr
2,472,385 A	6/1949	Rollman	4,608,979 A	9/1986	Breidenthal et al.
2,669,771 A	2/1954	Burge et al.	4,617,926 A *	10/1986	Sutton 606/9
3,261,978 A	7/1966	Brennan	4,623,929 A	11/1986	Johnson et al.
3,327,712 A	6/1967	Kaufman et al.	4,653,495 A	3/1987	Nanaumi
3,486,070 A	12/1969	Engel	4,677,347 A	6/1987	Nakamura
3,527,932 A	9/1970	Thomas	4,686,986 A	8/1987	Fenyo et al.
3,538,919 A	11/1970	Meyer	4,695,697 A	9/1987	Kosa
3,597,652 A	8/1971	Gates, Jr.	4,710,677 A	12/1987	Halberstadt et al.
3,622,743 A	11/1971	Muncheryan	4,718,416 A	1/1988	Nanaumi et al.
3,653,778 A	4/1972	Freiling	4,733,660 A	3/1988	Itzkan
3,667,454 A	6/1972	Prince	4,736,745 A	4/1988	Gluckman
3,693,623 A	9/1972	Harte et al.	4,745,909 A	5/1988	Pelton et al.
3,818,914 A	6/1974	Bender	4,747,660 A	5/1988	Nishioka et al.
3,834,391 A	9/1974	Block	4,749,913 A	6/1988	Stuermer et al.
3,846,811 A	11/1974	Nakamura et al.	4,775,361 A	10/1988	Jacques et al.
3,857,015 A	12/1974	Clark et al.	4,779,173 A	10/1988	Carr et al.
3,890,537 A	6/1975	Park et al.	4,784,135 A	11/1988	Blum et al.
3,900,034 A	8/1975	Katz et al.	4,799,479 A	1/1989	Spears
3,909,649 A	9/1975	Arsena	4,808,789 A *	2/1989	Muncheryan 219/121.6
3,939,560 A	2/1976	Lyall	4,819,669 A	4/1989	Politzer et al.
3,977,083 A	8/1976	Leslie et al.	4,826,431 A	5/1989	Fujimura et al.
4,047,106 A	9/1977	Robinson	4,832,024 A	5/1989	Boussignac et al.
4,213,462 A	7/1980	Sato et al.	4,840,174 A	6/1989	Gluckman
4,232,678 A	11/1980	Skovajsa et al.	4,845,608 A	7/1989	Gdula
4,233,493 A	11/1980	Nath et al.	4,852,549 A	8/1989	Mori
4,269,067 A	5/1981	Tynan et al.	4,860,172 A	8/1989	Schlager et al.
4,273,109 A	6/1981	Enderby	4,860,744 A	8/1989	Johnson et al.
4,275,335 A	6/1981	Ishida et al.	4,862,903 A	9/1989	Campbell
4,298,005 A	11/1981	Mutzhass	4,871,479 A	10/1989	Bachelard et al.
4,316,467 A	2/1982	Muckerheide	4,884,560 A	12/1989	Kuracina
4,333,197 A	6/1982	Kuris	4,898,438 A	2/1990	Mori
4,335,726 A	6/1982	Kolstedt	4,905,690 A	3/1990	Ohshiro et al.
4,388,924 A	6/1983	Weissman et al.	4,914,298 A	4/1990	Quad et al.
4,409,479 A	10/1983	Sprague et al.	4,917,084 A	4/1990	Sinofsky
4,452,081 A	6/1984	Seppi	4,926,227 A	5/1990	Jensen
4,456,872 A	6/1984	Froeschle	4,928,038 A	5/1990	Nerone
4,461,294 A	7/1984	Baron	4,930,504 A	6/1990	Diamantopoulos et al.
4,504,727 A	3/1985	Melcher et al.	4,932,954 A	6/1990	Wondrazek et al.
4,512,197 A	4/1985	von Gutfeld et al.	4,945,239 A	7/1990	Wist et al.
4,524,289 A	6/1985	Hammond et al.	4,973,848 A	11/1990	Kolobanov et al.
4,539,987 A	9/1985	Nath et al.	4,976,308 A	12/1990	Faghri
4,553,546 A	11/1985	Javelle et al.	4,992,256 A	2/1991	Skaggs et al.
4,561,440 A	12/1985	Kubo et al.	5,000,752 A	3/1991	Hoskin et al.
4,566,271 A	1/1986	French et al.	5,030,090 A	7/1991	Maeda et al.
4,591,762 A	5/1986	Nakamura et al.	5,032,178 A	7/1991	Cornell
			5,046,494 A	9/1991	Searfoss et al.
			5,050,597 A	9/1991	Daikuzono
			5,057,104 A	10/1991	Chess
			5,059,192 A	10/1991	Zaiaas
			5,065,515 A *	11/1991	Iderosa 30/140
			5,066,293 A	11/1991	Furumoto
			5,071,417 A	12/1991	Sinofsky
			5,074,661 A	12/1991	Reynolds et al.
			5,074,861 A	12/1991	Schneider et al.
			5,099,910 A	3/1992	Walpole et al.
			5,108,388 A	4/1992	Trokel
			5,127,395 A	7/1992	Bontemps et al.
			5,133,102 A	7/1992	Sakuma
			5,137,530 A	8/1992	Sand
			5,140,984 A	8/1992	Dew et al.
			5,159,601 A	10/1992	Huber
			5,160,194 A	11/1992	Feldman
			5,171,564 A	12/1992	Nathoo et al.
			5,178,617 A	1/1993	Kuizenga et al.
			5,182,557 A	1/1993	Lang
			5,182,857 A *	2/1993	Simon 30/34.05
			5,192,278 A	3/1993	Hayes et al.
			5,196,004 A	3/1993	Sinofsky
			5,207,671 A	5/1993	Franken et al.
			5,220,804 A	6/1993	Tilton et al.
			5,222,907 A	6/1993	Katabuchi et al.
			5,225,926 A	7/1993	Cuomo et al.
			5,226,907 A	7/1993	Tankovich
			5,267,399 A	12/1993	Johnston
			5,281,211 A	1/1994	Parel et al.
			5,282,797 A	2/1994	Chess
			5,287,372 A	2/1994	Ortiz

5,287,380 A	2/1994	Hsia	5,679,113 A	10/1997	Caisey et al.
5,293,880 A	3/1994	Levitt	5,683,380 A	11/1997	Eckhouse et al.
5,300,097 A	4/1994	Lerner et al.	5,692,509 A	12/1997	Voss et al.
5,303,585 A	4/1994	Lichte	5,698,866 A	12/1997	Doiron et al.
5,304,170 A	4/1994	Green	5,707,401 A	1/1998	Talmore
5,304,173 A	4/1994	Kittrell et al.	5,707,403 A	1/1998	Grove et al.
5,306,143 A	4/1994	Levy	5,713,738 A	2/1998	Yarborough
5,306,274 A	4/1994	Long	5,714,119 A	2/1998	Kawagoe et al.
5,316,075 A	5/1994	Quon et al.	5,718,117 A	2/1998	McDunn et al.
5,320,618 A	6/1994	Gustafsson et al.	5,720,772 A	2/1998	Eckhouse et al.
5,334,191 A	8/1994	Poppas et al.	5,722,397 A	3/1998	Eppstein
5,334,193 A	8/1994	Nardella	5,725,522 A	3/1998	Sinofsky
5,336,217 A	8/1994	Buys et al.	5,728,090 A	3/1998	Martin et al.
5,342,358 A	8/1994	Daikuzono et al.	5,735,844 A	4/1998	Anderson et al.
5,344,418 A	9/1994	Ghaffari	5,735,884 A	4/1998	Thompson et al.
5,344,434 A	9/1994	Talmore et al.	5,738,678 A	4/1998	Patel et al.
5,348,551 A	9/1994	Spears et al.	5,742,392 A	4/1998	Anderson et al.
5,350,376 A	9/1994	Brown	5,743,901 A	4/1998	Grove et al.
5,353,020 A	10/1994	Schurmann	5,743,902 A	4/1998	Trost
5,353,790 A	10/1994	Jacques et al.	5,746,735 A	5/1998	Furumoto et al.
5,356,081 A	10/1994	Sellar	5,748,822 A	5/1998	Miura et al.
5,358,503 A	10/1994	Bertwell et al.	5,755,751 A	5/1998	Eckhouse et al.
5,360,426 A	11/1994	Muller et al.	5,759,200 A	6/1998	Azar et al.
5,369,831 A	12/1994	Bock	5,760,362 A	6/1998	Eloy
5,380,317 A	1/1995	Everett et al.	5,768,103 A	6/1998	Kobrinetz et al.
5,386,427 A	1/1995	Zayhowski	5,769,076 A	6/1998	Maekawa et al.
5,403,306 A	4/1995	Edwards et al.	5,782,249 A	7/1998	Weber et al.
5,405,368 A	4/1995	Eckhouse et al.	5,802,136 A	9/1998	Carol
5,409,446 A	4/1995	Rattner	5,810,801 A	9/1998	Anderson et al.
5,415,654 A	5/1995	Daikuzono et al.	5,812,567 A	9/1998	Jeon et al.
5,425,728 A	6/1995	Tankovich	5,813,855 A	9/1998	Crisio, Jr.
5,425,735 A	6/1995	Rosen et al.	5,814,008 A	9/1998	Chen et al.
5,425,754 A	6/1995	Braun et al.	5,814,040 A	9/1998	Nelson et al.
5,445,608 A	8/1995	Chen et al.	5,814,041 A	9/1998	Anderson et al.
5,445,611 A	8/1995	Eppstein et al.	5,817,089 A	10/1998	Tankovich et al.
5,454,807 A	10/1995	Lennox et al.	5,820,625 A	10/1998	Izawa et al.
5,458,140 A	10/1995	Eppstein et al.	5,820,626 A	10/1998	Baumgardner
5,464,436 A	* 11/1995	Smith 607/89	5,824,023 A	10/1998	Anderson
5,474,549 A	12/1995	Ortiz et al.	5,827,264 A	10/1998	Hohla et al.
5,486,170 A	1/1996	Winston et al.	5,828,803 A	10/1998	Eckhouse et al.
5,486,172 A	1/1996	Chess	5,830,208 A	11/1998	Muller
5,491,363 A	2/1996	Yoshikawa et al.	5,835,648 A	11/1998	Narciso, Jr. et al.
5,501,680 A	3/1996	Kurtz et al.	5,836,877 A	11/1998	Zavislan
5,502,582 A	3/1996	Larson et al.	5,836,999 A	11/1998	Eckhouse et al.
5,505,726 A	4/1996	Meserol	5,840,048 A	11/1998	Cheng et al.
5,505,727 A	4/1996	Keller	5,849,029 A	12/1998	Eckhouse et al.
5,519,534 A	5/1996	Smith et al.	5,851,181 A	12/1998	Talmer et al.
5,522,813 A	6/1996	Trelles et al.	5,853,407 A	12/1998	Miller
5,527,368 A	6/1996	Supkis et al.	5,860,967 A	1/1999	Zavislan et al.
5,531,739 A	7/1996	Trelles et al.	5,868,731 A	2/1999	Budnik et al.
5,531,740 A	7/1996	Black	5,871,480 A	2/1999	Tankovich
5,536,168 A	7/1996	Bourke	5,879,159 A	3/1999	Cipolla
5,549,660 A	8/1996	Mendes et al.	5,883,471 A	3/1999	Rodman et al.
5,558,667 A	9/1996	Yarborough et al.	5,885,211 A	3/1999	Eppstein et al.
5,561,881 A	10/1996	Klinger et al.	5,885,273 A	3/1999	Eckhouse et al.
5,571,098 A	11/1996	Domankevitz et al.	5,885,274 A	3/1999	Fullmer et al.
5,578,866 A	11/1996	DePoorter et al.	5,891,063 A	4/1999	Vigil
5,595,568 A	1/1997	Anderson et al.	5,893,828 A	4/1999	Uram
5,611,475 A	3/1997	Sim et al.	5,895,350 A	4/1999	Hori
5,611,793 A	3/1997	Wilson et al.	5,897,549 A	4/1999	Tankovich
5,616,140 A	4/1997	Prescott	5,906,609 A	5/1999	Assa et al.
5,618,284 A	4/1997	Sand	5,908,418 A	6/1999	Dority et al.
5,620,478 A	4/1997	Eckhouse et al.	5,913,883 A	6/1999	Alexander et al.
5,626,631 A	5/1997	Eckhouse et al.	5,916,211 A	6/1999	Quon et al.
5,628,744 A	5/1997	Coleman et al.	5,920,374 A	7/1999	Vaphiades et al.
5,630,811 A	5/1997	Miller	5,921,926 A	7/1999	Rolland et al.
5,634,711 A	6/1997	Kennedy et al.	5,928,222 A	7/1999	Kleinerman
5,649,972 A	7/1997	Hochstein	5,944,687 A	8/1999	Benett et al.
5,652,481 A	7/1997	Johnson et al.	5,944,748 A	8/1999	Mager et al.
5,653,706 A	8/1997	Zavislan et al.	5,947,957 A	9/1999	Morris
5,655,547 A	8/1997	Karni et al.	5,948,011 A	9/1999	Knowlton
5,657,760 A	8/1997	Ying et al.	5,949,222 A	9/1999	Buono
5,658,148 A	8/1997	Neuberger et al.	5,954,710 A	9/1999	Paolini et al.
5,658,323 A	8/1997	Miller	5,955,490 A	9/1999	Kennedy et al.
5,660,836 A	8/1997	Knowlton	5,957,915 A	9/1999	Trost
5,661,744 A	8/1997	Murakami et al.	5,964,749 A	10/1999	Eckhouse et al.
5,662,643 A	9/1997	Kung et al.	5,968,033 A	10/1999	Fuller et al.
5,662,644 A	9/1997	Swor	5,968,034 A	* 10/1999	Fullmer et al. 606/9
5,673,451 A	10/1997	Moore et al.	5,974,059 A	10/1999	Dawson

5,974,616 A	11/1999	Dreyfus	6,235,016 B1	5/2001	Stewart
5,977,723 A	11/1999	Yoon et al.	6,236,891 B1	5/2001	Ingle et al.
5,979,454 A	11/1999	Anvari et al.	6,239,442 B1	5/2001	Iimura
5,984,915 A	11/1999	Loeb et al.	6,240,306 B1	5/2001	Rohrscheib et al.
5,993,440 A *	11/1999	Ghassemi 606/9	6,245,093 B1	6/2001	Li et al.
6,007,219 A	12/1999	O'Meara	6,251,100 B1	6/2001	Flock et al.
6,015,404 A	1/2000	Altshuler et al.	6,251,127 B1	6/2001	Biel
6,022,316 A	2/2000	Eppstein et al.	6,254,388 B1	7/2001	Yarborough
6,026,828 A	2/2000	Altshuler	6,263,233 B1	7/2001	Zavislan et al.
6,027,495 A	2/2000	Miller	6,264,649 B1	7/2001	Whitcroft et al.
6,029,303 A	2/2000	Dewan	6,267,779 B1	7/2001	Gerdes
6,029,304 A	2/2000	Hulke et al.	6,267,780 B1	7/2001	Streeter
6,030,378 A	2/2000	Stewart	6,273,884 B1	8/2001	Altshuler et al.
6,030,399 A	2/2000	Ignatz et al.	6,273,885 B1	8/2001	Koop et al.
6,032,071 A	2/2000	Binder	6,280,438 B1	8/2001	Eckhouse et al.
RE36,634 E	3/2000	Ghaffari	6,283,956 B1	9/2001	McDaniel
6,036,684 A	3/2000	Tankovich et al.	6,287,549 B1	9/2001	Sumian et al.
6,044,514 A	4/2000	Kaneda et al.	6,290,496 B1	9/2001	Azar et al.
6,050,990 A	4/2000	Tankovich et al.	6,290,713 B1	9/2001	Russell
6,055,154 A	4/2000	Azar	6,306,130 B1 *	10/2001	Anderson et al. 606/27
D424,197 S	5/2000	Sydowski et al.	6,306,160 B1	10/2001	Nidetzky
6,056,548 A	5/2000	Neuberger et al.	6,315,772 B1	11/2001	Marchitto et al.
6,056,738 A	5/2000	Marchitto et al.	6,317,624 B1	11/2001	Kollias et al.
6,058,937 A	5/2000	Doiron et al.	6,319,274 B1	11/2001	Shaddock
6,059,820 A	5/2000	Baronov	6,325,769 B1	12/2001	Klopotek
6,063,108 A	5/2000	Salansky et al.	6,328,733 B1	12/2001	Trost
6,070,092 A	5/2000	Kazama et al.	6,331,111 B1	12/2001	Cao
6,071,239 A	6/2000	Cribbs et al.	6,340,495 B1	1/2002	Sumian et al.
6,074,382 A	6/2000	Asah et al.	6,343,400 B1	2/2002	Massholder et al.
6,080,146 A	6/2000	Altshuler et al.	6,343,933 B1	2/2002	Montgomery et al.
6,080,147 A	6/2000	Tobinick	6,350,261 B1	2/2002	Domankevitz et al.
6,083,217 A	7/2000	Tankovich	6,350,276 B1	2/2002	Knowlton
6,086,363 A	7/2000	Moran et al.	6,354,370 B1	3/2002	Miller et al.
6,086,580 A	7/2000	Mordon et al.	6,355,054 B1	3/2002	Neuberger
6,094,767 A	8/2000	Iimura	6,358,242 B1	3/2002	Cecchetti
6,096,029 A	8/2000	O'Donnell, Jr.	6,358,272 B1	3/2002	Wilden et al.
6,096,209 A	8/2000	O'Brien et al.	6,383,176 B1	5/2002	Connors et al.
6,099,521 A	8/2000	Shaddock	6,383,177 B1	5/2002	Balle-Petersen et al.
6,104,959 A	8/2000	Spartell	6,387,089 B1	5/2002	Kreindel et al.
6,106,293 A	8/2000	Wiesel	6,387,353 B1	5/2002	Jensen et al.
6,106,294 A	8/2000	Daniel	6,395,016 B1	5/2002	Oron et al.
6,110,195 A	8/2000	Xie et al.	6,400,011 B1	6/2002	Miki
6,113,559 A	9/2000	Klopotek	6,402,739 B1	6/2002	Neev
6,117,129 A	9/2000	Mukai et al.	6,406,474 B1	6/2002	Neuberger et al.
6,120,497 A	9/2000	Anderson et al.	6,409,665 B1	6/2002	Scott et al.
6,126,655 A	10/2000	Domankevitz et al.	6,413,267 B1	7/2002	Dumoulin-White et al.
6,129,723 A	10/2000	Anderson et al.	6,416,319 B1	7/2002	Cipolla
6,135,774 A	10/2000	Hack et al.	6,419,389 B1	7/2002	Fuchs et al.
6,142,650 A	11/2000	Brown et al.	6,424,852 B1	7/2002	Zavislan
6,142,939 A	11/2000	Eppstein et al.	6,425,912 B1	7/2002	Knowlton
6,149,644 A	11/2000	Xie	6,435,873 B1	8/2002	Burgio
6,149,895 A	11/2000	Kutsch	6,436,094 B1	8/2002	Reuter
6,159,236 A	12/2000	Biel	6,439,888 B1	8/2002	Boutousov et al.
6,162,055 A	12/2000	Montgomery et al.	6,440,155 B1	8/2002	Matsumae et al.
6,162,211 A	12/2000	Tankovich et al.	6,443,978 B1	9/2002	Zharov
6,162,212 A	12/2000	Kreindel et al.	6,451,007 B1	9/2002	Koop et al.
6,171,300 B1	1/2001	Adams	6,461,296 B1	10/2002	Desai
6,171,301 B1	1/2001	Nelson et al.	6,464,694 B1	10/2002	Massengill
6,171,302 B1	1/2001	Talpalriu et al.	6,471,712 B2	10/2002	Burres
6,171,332 B1	1/2001	Whitehurst	6,471,716 B1	10/2002	Pecukonis
6,173,202 B1	1/2001	Eppstein	6,475,211 B2	11/2002	Chess et al.
6,174,325 B1	1/2001	Eckhouse et al.	6,484,052 B1	11/2002	Visuri et al.
6,176,854 B1	1/2001	Cone	6,485,413 B1	11/2002	Boppert et al.
6,183,434 B1	2/2001	Eppstein	6,491,685 B2	12/2002	Visuri et al.
6,183,500 B1	2/2001	Kohler et al.	6,494,900 B1	12/2002	Salansky et al.
6,183,773 B1	2/2001	Anderson	6,497,702 B1	12/2002	Bernaz
6,187,001 B1	2/2001	Azar et al.	6,503,486 B2	1/2003	Xu et al.
6,187,029 B1	2/2001	Shapiro et al.	6,508,785 B1	1/2003	Eppstein
6,197,020 B1	3/2001	O'Donnell, Jr.	6,508,813 B1	1/2003	Altshuler
6,200,134 B1	3/2001	Kovac et al.	6,511,475 B1	1/2003	Altshuler et al.
6,200,309 B1	3/2001	Rice et al.	6,514,243 B1	2/2003	Eckhouse et al.
6,202,242 B1	3/2001	Salmon et al.	6,517,532 B1	2/2003	Altshuler et al.
6,203,540 B1	3/2001	Weber	6,519,376 B2	2/2003	Biagi et al.
6,210,425 B1	4/2001	Chen	6,525,819 B1	2/2003	Delawter et al.
6,214,034 B1	4/2001	Azar	6,527,764 B1	3/2003	Neuberger et al.
6,221,095 B1	4/2001	Van Zuylen et al.	6,530,915 B1	3/2003	Eppstein et al.
6,228,075 B1	5/2001	Furumoto	6,537,270 B1	3/2003	Elbrecht et al.
6,229,831 B1	5/2001	Nightingale et al.	6,547,780 B1	4/2003	Sinofsky
6,235,015 B1 *	5/2001	Mead et al. 606/9	6,551,346 B2	4/2003	Crossley

US 8,182,473 B2

Page 5

6,554,439	B1	4/2003	Teicher et al.	7,041,100	B2	5/2006	Kreindel
6,556,596	B1	4/2003	Kim et al.	7,044,959	B2	5/2006	Anderson et al.
6,558,372	B1	5/2003	Altshuler	7,060,061	B2	6/2006	Altshuler et al.
6,561,808	B2	5/2003	Neuberger	7,066,733	B2	6/2006	Logan et al.
6,569,155	B1	5/2003	Connors et al.	7,070,611	B2	7/2006	Biel
6,570,892	B1	5/2003	Lin et al.	7,077,840	B2	7/2006	Altshuler et al.
6,570,893	B1	5/2003	Libatique et al.	7,081,128	B2	7/2006	Hart et al.
6,572,634	B2	6/2003	Koo	7,097,639	B1	8/2006	Almeida
6,572,637	B1	6/2003	Yamazaki et al.	7,097,656	B1	8/2006	Akopov et al.
6,595,934	B1	7/2003	Hissong et al.	7,144,247	B2	12/2006	Black
6,600,951	B1	7/2003	Anderson	7,144,248	B2	12/2006	Irwin
6,602,245	B1	8/2003	Thiberg et al.	7,145,105	B2	12/2006	Gaulard
6,605,080	B1	8/2003	Altshuler et al.	7,145,108	B2	12/2006	Kanel et al.
6,605,083	B2	8/2003	Clement et al.	7,160,289	B2	1/2007	Cohen
6,606,755	B1	8/2003	Robinson et al.	7,182,760	B2	2/2007	Kubota
6,616,447	B1	9/2003	Rizoiu et al.	7,198,634	B2	4/2007	Harth et al.
6,616,451	B1	9/2003	Rizolu et al.	7,204,832	B2	4/2007	Altshuler et al.
6,618,531	B1	9/2003	Goto et al.	7,220,254	B2	5/2007	Altshuler et al.
6,623,272	B2	9/2003	Clemans	7,223,270	B2	5/2007	Altshuler et al.
6,623,513	B2	9/2003	Biel	7,223,281	B2	5/2007	Altshuler et al.
6,629,971	B2	10/2003	McDaniel	7,255,691	B2	8/2007	Tolkoff et al.
6,629,989	B2	10/2003	Akita et al.	7,274,155	B2	9/2007	Inochkin et al.
6,632,219	B1	10/2003	Baranov et al.	7,291,140	B2	11/2007	MacFarland et al.
6,635,075	B2	10/2003	Li et al.	7,309,335	B2	12/2007	Altshuler et al.
6,641,578	B2	11/2003	Mukai	7,311,722	B2	12/2007	Larsen
6,641,600	B1	11/2003	Kohler et al.	7,320,593	B2	1/2008	Ostler et al.
6,648,904	B2	11/2003	Altshuler et al.	7,322,972	B2	1/2008	Viator et al.
6,652,459	B2	11/2003	Payne et al.	7,329,273	B2	2/2008	Altshuler et al.
6,653,618	B2	11/2003	Zenzie	7,329,274	B2	2/2008	Altshuler et al.
6,659,999	B1	12/2003	Anderson et al.	7,331,964	B2	2/2008	Maricle et al.
6,660,000	B2	12/2003	Neuberger et al.	7,333,698	B2	2/2008	Israel
6,663,620	B2	12/2003	Altshuler et al.	7,351,252	B2	4/2008	Altshuler et al.
6,663,658	B1	12/2003	Kollias et al.	7,422,598	B2	9/2008	Altshuler et al.
6,663,659	B2	12/2003	McDaniel	7,423,767	B2	9/2008	Steinsiek et al.
6,666,856	B2	12/2003	Connors et al.	7,431,419	B2	10/2008	Turner et al.
6,675,425	B1	1/2004	Imura	7,431,719	B2	10/2008	Altshuler et al.
6,676,654	B1	1/2004	Balle-Petersen et al.	7,540,869	B2	6/2009	Altshuler et al.
6,679,837	B2	1/2004	Daikuzono	7,624,640	B2	12/2009	Maris et al.
6,685,639	B1	2/2004	Wang et al.	7,647,092	B2	1/2010	Motz et al.
6,685,699	B1	2/2004	Eppstein et al.	2001/0007068	A1	7/2001	Ota et al.
6,689,124	B1	2/2004	Thiberg et al.	2001/0008973	A1	7/2001	Van Zuylen et al.
6,699,040	B1	3/2004	Hahn et al.	2001/0023363	A1	9/2001	Harth et al.
6,706,035	B2	3/2004	Cense et al.	2001/0024777	A1	9/2001	Azar et al.
6,709,269	B1	3/2004	Altshuler	2001/0041886	A1	11/2001	Durkin et al.
6,709,446	B2	3/2004	Lundahl et al.	2001/0046652	A1	11/2001	Ostler et al.
6,723,090	B2	4/2004	Altshuler	2001/0048077	A1	12/2001	Afanassieva
6,743,222	B2	6/2004	Durkin et al.	2002/0004066	A1	1/2002	Stanley et al.
6,746,444	B2	6/2004	Key	2002/0005475	A1	1/2002	Zenzie
6,749,623	B1	6/2004	Hsi et al.	2002/0013572	A1	1/2002	Berlin
6,770,069	B1	8/2004	Hobart et al.	2002/0016587	A1	2/2002	Furumoto
6,790,205	B1	9/2004	Yamazaki et al.	2002/0018754	A1	2/2002	Sagel et al.
6,801,595	B2	10/2004	Grodzins et al.	2002/0019624	A1	2/2002	Clement et al.
6,808,331	B2	10/2004	Hall et al.	2002/0026225	A1	2/2002	Segal
6,808,532	B2	10/2004	Andersen et al.	2002/0029071	A1	3/2002	Whitehurst
RE38,670	E	12/2004	Asah et al.	2002/0035360	A1*	3/2002	Connors et al. 606/9
6,858,009	B2	2/2005	Kawata et al.	2002/0049483	A1	4/2002	Knowlton
6,860,879	B2	3/2005	Irion et al.	2002/0058890	A1	5/2002	Visuri et al.
6,862,771	B1	3/2005	Muller	2002/0071287	A1	6/2002	Haase
6,863,781	B2	3/2005	Nocera et al.	2002/0071827	A1	6/2002	Petersen et al.
6,868,436	B1	3/2005	Fleming, III	2002/0072676	A1	6/2002	Afanassieva
6,878,144	B2	4/2005	Altshuler et al.	2002/0081555	A1	6/2002	Wiesel
6,881,212	B1	4/2005	Clement et al.	2002/0091377	A1	7/2002	Anderson et al.
6,887,260	B1	5/2005	McDaniel	2002/0108193	A1	8/2002	Gruber
6,888,319	B2	5/2005	Inochkin et al.	2002/0111610	A1	8/2002	Nordquist
6,893,259	B1	5/2005	Reizenson	2002/0120256	A1	8/2002	Furuno et al.
6,902,397	B2	6/2005	Farrell et al.	2002/0123745	A1	9/2002	Svaasand et al.
6,902,563	B2	6/2005	Wilkens et al.	2002/0127224	A1	9/2002	Chen
6,936,046	B2	8/2005	Hissong et al.	2002/0128635	A1	9/2002	Altshuler et al.
6,942,658	B1	9/2005	Rizoiu et al.	2002/0128695	A1	9/2002	Harth et al.
6,953,341	B2	10/2005	Black	2002/0161357	A1	10/2002	Anderson et al.
6,974,451	B2	12/2005	Altshuler et al.	2002/0161418	A1	10/2002	Wilkens et al.
6,976,985	B2	12/2005	Altshuler et al.	2002/0173780	A1	11/2002	Altshuler et al.
6,989,023	B2	1/2006	Black	2002/0182563	A1	12/2002	Boutoussov et al.
6,991,644	B2	1/2006	Spooner et al.	2002/0183808	A1	12/2002	Biel
6,997,923	B2	2/2006	Anderson	2002/0198517	A1	12/2002	Alfano et al.
7,001,413	B2	2/2006	Butler	2003/0004499	A1	1/2003	McDaniel
7,006,223	B2	2/2006	Mullani	2003/0009158	A1	1/2003	Perricone
7,029,469	B2	4/2006	Vasily	2003/0009205	A1	1/2003	Biel
7,033,349	B2	4/2006	Key	2003/0018373	A1	1/2003	Eckhardt et al.

2003/0023235	A1	1/2003	Cense et al.	2005/0171581	A1	8/2005	Connors et al.
2003/0023283	A1	1/2003	McDaniel	2005/0177026	A1	8/2005	Hoeg et al.
2003/0023284	A1	1/2003	Gartstein et al.	2005/0182389	A1	8/2005	LaPorte et al.
2003/0028227	A1	2/2003	Neuberger et al.	2005/0197681	A1	9/2005	Barolet et al.
2003/0032900	A1	2/2003	Ella	2005/0215988	A1	9/2005	Altshuler et al.
2003/0032950	A1	2/2003	Altshuler et al.	2005/0220726	A1	10/2005	Pauly et al.
2003/0036680	A1	2/2003	Black	2005/0251118	A1	11/2005	Anderson et al.
2003/0040739	A1	2/2003	Koop	2006/0004306	A1	1/2006	Altshuler et al.
2003/0055414	A1	3/2003	Altshuler et al.	2006/0004347	A1	1/2006	Altshuler et al.
2003/0057875	A1	3/2003	Inochkin et al.	2006/0009750	A1	1/2006	Altshuler et al.
2003/0059738	A1	3/2003	Neuberger	2006/0020309	A1	1/2006	Altshuler et al.
2003/0065314	A1	4/2003	Altshuler et al.	2006/0047281	A1	3/2006	Kreindel
2003/0083649	A1	5/2003	Margaron et al.	2006/0058712	A1	3/2006	Altshuler et al.
2003/0084534	A1	5/2003	Kaizuka	2006/0079947	A1	4/2006	Tankovich et al.
2003/0097122	A1	5/2003	Ganz et al.	2006/0089687	A1	4/2006	Spooner et al.
2003/0100936	A1	5/2003	Altshuler et al.	2006/0094988	A1	5/2006	Tosaya et al.
2003/0104340	A1	6/2003	Clemans	2006/0122668	A1	6/2006	Anderson et al.
2003/0109787	A1	6/2003	Black	2006/0149343	A1	7/2006	Altshuler et al.
2003/0109860	A1	6/2003	Black	2006/0161143	A1	7/2006	Altshuler et al.
2003/0113684	A1	6/2003	Scott	2006/0194164	A1	8/2006	Altshuler et al.
2003/0129154	A1	7/2003	McDaniel	2006/0206103	A1	9/2006	Altshuler et al.
2003/0130709	A1	7/2003	D.C. et al.	2006/0253176	A1	11/2006	Caruso et al.
2003/0152528	A1	8/2003	Singh et al.	2006/0271028	A1	11/2006	Altshuler et al.
2003/0163884	A1	9/2003	Weihrauch	2006/0287646	A1	12/2006	Altshuler et al.
2003/0167080	A1	9/2003	Hart et al.	2007/0027440	A1	2/2007	Altshuler et al.
2003/0169433	A1	9/2003	Koele et al.	2007/0038206	A1	2/2007	Altshuler et al.
2003/0181896	A1	9/2003	Zvuloni et al.	2007/0049910	A1	3/2007	Altshuler et al.
2003/0187486	A1	10/2003	Savage et al.	2007/0060819	A1	3/2007	Altshuler et al.
2003/0195494	A1	10/2003	Altshuler et al.	2007/0067006	A1	3/2007	Altshuler et al.
2003/0199859	A1	10/2003	Altshuler et al.	2007/0073308	A1	3/2007	Anderson et al.
2003/0216795	A1	11/2003	Harth et al.	2007/0078501	A1	4/2007	Altshuler et al.
2003/0232303	A1	12/2003	Black	2007/0159592	A1	7/2007	Rylander et al.
2004/0006332	A1	1/2004	Black	2007/0185552	A1	8/2007	Masotti et al.
2004/0010298	A1	1/2004	Altshuler et al.	2007/0194717	A1	8/2007	Belikov
2004/0015156	A1	1/2004	Vasily	2007/0198004	A1	8/2007	Altshuler et al.
2004/0015158	A1	1/2004	Chen et al.	2007/0213696	A1	9/2007	Altshuler et al.
2004/0019990	A1	2/2004	Farrell et al.	2007/0213698	A1	9/2007	Altshuler et al.
2004/0024388	A1	2/2004	Altshuler	2007/0213792	A1	9/2007	Yaroslavsky et al.
2004/0030326	A1	2/2004	Altshuler et al.	2007/0219604	A1	9/2007	Yaroslavsky et al.
2004/0034319	A1	2/2004	Anderson et al.	2007/0219605	A1	9/2007	Yaroslavsky et al.
2004/0034341	A1	2/2004	Altshuler et al.	2007/0239142	A1	10/2007	Altshuler et al.
2004/0073079	A1	4/2004	Altshuler et al.	2007/0239143	A1	10/2007	Altshuler et al.
2004/0082940	A1	4/2004	Black et al.	2007/0255355	A1	11/2007	Altshuler et al.
2004/0085026	A1	5/2004	Inochkin et al.	2007/0288071	A1	12/2007	Rogers
2004/0093042	A1	5/2004	Altshuler et al.	2008/0009842	A1	1/2008	Manstein et al.
2004/0093043	A1	5/2004	Edel et al.	2008/0058783	A1	3/2008	Altshuler et al.
2004/0111132	A1	6/2004	Shenderova et al.	2008/0132886	A1	6/2008	Cohen et al.
2004/0116984	A1	6/2004	Spooner et al.	2008/0139901	A1	6/2008	Altshuler et al.
2004/0133251	A1	7/2004	Altshuler et al.	2008/0140164	A1	6/2008	Oberreiter et al.
2004/0143920	A1	7/2004	Nanda	2008/0172047	A1	7/2008	Altshuler et al.
2004/0147984	A1	7/2004	Altshuler et al.	2008/0183162	A1	7/2008	Altshuler et al.
2004/0156626	A1	8/2004	Thoms	2008/0183250	A1	7/2008	Tanojo et al.
2004/0161213	A1	8/2004	Lee	2008/0195183	A1	8/2008	Botchkareva et al.
2004/0162549	A1	8/2004	Altshuler	2008/0214988	A1	9/2008	Altshuler et al.
2004/0162596	A1	8/2004	Altshuler et al.	2008/0294150	A1	11/2008	Altshuler et al.
2004/0167500	A1 *	8/2004	Weckwerth et al. 606/9	2008/0306471	A1	12/2008	Altshuler et al.
2004/0176764	A1	9/2004	Dant	2009/0048557	A1	2/2009	Yeshurun et al.
2004/0191729	A1	9/2004	Altshuler et al.	2009/0069741	A1	3/2009	Altshuler et al.
2004/0193234	A1	9/2004	Butler				
2004/0193235	A1	9/2004	Altshuler et al.	FOREIGN PATENT DOCUMENTS			
2004/0193236	A1	9/2004	Altshuler et al.	AU	1851583		3/1984
2004/0199227	A1	10/2004	Altshuler et al.	AU	2002303863		12/2002
2004/0204745	A1	10/2004	Altshuler et al.	CN	2053926	U	3/1990
2004/0210276	A1	10/2004	Altshuler et al.	CN	1073607	A	6/1993
2004/0214132	A1	10/2004	Altshuler	CN	1182572	A	5/1998
2004/0225339	A1	11/2004	Yaroslavsky et al.	CN	1351483	A	5/2002
2004/0230258	A1	11/2004	Altshuler et al.	CN	1535126	A	10/2004
2004/0230260	A1	11/2004	MacFarland et al.	CN	1262249	C	7/2006
2004/0234460	A1	11/2004	Tarver et al.	DE	3304230	A1	8/1984
2005/0038418	A1	2/2005	Altshuler et al.	DE	3719561		1/1988
2005/0049467	A1	3/2005	Stamatas et al.	DE	3837248		5/1990
2005/0049582	A1	3/2005	DeBenedictis et al.	DE	9102407		8/1991
2005/0049658	A1	3/2005	Connors et al.	DE	19803460	C1	8/1999
2005/0063931	A1	3/2005	Paus et al.	DE	19944401	A1	3/2001
2005/0065531	A1	3/2005	Cohen	DE	10140715	A1	3/2002
2005/0085875	A1	4/2005	Van Zuylen	DE	10112289		9/2002
2005/0107849	A1	5/2005	Altshuler et al.	DE	10120787	A1	1/2003
2005/0168158	A1	8/2005	Inochkin et al.	EP	0142671		5/1985
2005/0171517	A1	8/2005	Altshuler et al.	EP	0 172 490		2/1986

US 8,182,473 B2

Page 7

EP	0565331	10/1993	WO	WO-9623447	8/1996
EP	0598984	6/1994	WO	WO-9625979	8/1996
EP	0724894	8/1996	WO	WO-96/28212	9/1996
EP	0726083	8/1996	WO	WO-9636396	11/1996
EP	0736308	10/1996	WO	WO-9641579	12/1996
EP	0743029	11/1996	WO	WO-9713458	4/1997
EP	0755698	1/1997	WO	WO-9713552	4/1997
EP	0763371	3/1997	WO	WO-97/22384 A1	6/1997
EP	0765673	4/1997	WO	WO-97/28752 A1	8/1997
EP	0765674	4/1997	WO	WO-98/05286 A1	2/1998
EP	0783904	7/1997	WO	WO-98/05380 A1	2/1998
EP	0 885 629	12/1998	WO	WO-98/06456 A1	2/1998
EP	0884066	12/1998	WO	WO-98/07379 A1	2/1998
EP	0885629	12/1998	WO	WO-9804317	2/1998
EP	1038505	9/2000	WO	WO-98/20937 A2	5/1998
EP	1057454	12/2000	WO	WO-9824507	6/1998
EP	1075854	2/2001	WO	WO-98/41158 A1	9/1998
EP	1138349	10/2001	WO	WO-9851235	11/1998
EP	1147785	10/2001	WO	WO-9852481	11/1998
EP	1219258	7/2002	WO	WO-9858595	12/1998
EP	1226787	7/2002	WO	WO-99/10046 A1	3/1999
EP	1238683 A1	9/2002	WO	WO-99/17668 A1	4/1999
EP	1250893	10/2002	WO	WO-9917666	4/1999
EP	1457234	9/2004	WO	WO-9917667	4/1999
EP	1495735 A1	1/2005	WO	WO-9927997	6/1999
EP	1512373	3/2005	WO	WO-9929243	6/1999
EP	1627662	2/2006	WO	WO-99/34867 A1	7/1999
EP	1839705 A1	10/2007	WO	WO-9938569 A2	8/1999
EP	1854505 A2	11/2007	WO	WO-9938569 A3	8/1999
EP	1535582	3/2009	WO	WO-99/43387 A1	9/1999
FR	2199453	4/1974	WO	WO-99/44638 A1	9/1999
FR	2591902	6/1987	WO	WO-9946005	9/1999
GB	1546625	5/1979	WO	WO-9949937	10/1999
GB	2044908	10/1980	WO	WO-99/62472 A1	12/1999
GB	2059053	4/1981	WO	WO-99/66988 A1	12/1999
GB	2059054	4/1981	WO	WO-0002491	1/2000
GB	2123287	2/1984	WO	WO-0003257	1/2000
GB	2239675 A	7/1991	WO	WO-00/07514 A1	2/2000
GB	2270159 A	3/1994	WO	WO-00/30714 A1	6/2000
GB	2356570	5/2001	WO	WO-0032272	6/2000
GB	2360461 A	9/2001	WO	WO-00/41278 A1	7/2000
GB	2360946	10/2001	WO	WO-0040266	7/2000
GB	2364376	1/2002	WO	WO-0043070	7/2000
GB	2368020	4/2002	WO	WO-0044294	8/2000
GB	2390021	12/2003	WO	WO-00/54649 A2	9/2000
GB	2397528	7/2004	WO	WO-00/54685	9/2000
JP	54129791 A	10/1979	WO	WO-0054685	9/2000
JP	03-066387	3/1991	WO	WO-0062700	10/2000
JP	10014661 A	1/1998	WO	WO-00/66226 A1	11/2000
JP	10165410 A	6/1998	WO	WO-0064537	11/2000
JP	11047146 A	2/1999	WO	WO-0071045	11/2000
JP	11081877 A	3/1999	WO	WO-0074583	12/2000
JP	2000037400	2/2000	WO	WO-0074781	12/2000
JP	2000300684 A	10/2000	WO	WO-0078242	12/2000
JP	2001029124 A	2/2001	WO	WO-0103257	1/2001
JP	2001145520	5/2001	WO	WO-01/14012 A1	3/2001
JP	2001343560 A	12/2001	WO	WO-0126573	4/2001
JP	2002506362 A	2/2002	WO	WO-01/34048	5/2001
JP	2002272861 A	9/2002	WO	WO-0134048	5/2001
JP	2003192809	7/2003	WO	WO-01/41872 A1	6/2001
JP	2005017796 A	1/2005	WO	WO-01/42671	6/2001
JP	2005027702 A	2/2005	WO	WO-0154606	8/2001
RU	2082337	6/1997	WO	WO-0154770	8/2001
RU	2089126	9/1997	WO	WO-0178830	10/2001
RU	2089127	9/1997	WO	WO-02/26147 A1	4/2002
RU	2096051	11/1997	WO	WO-02053050	7/2002
RU	2122848	12/1998	WO	WO-02069825	9/2002
WO	WO-8602783	5/1986	WO	WO-02/078559	10/2002
WO	WO-8804592	6/1988	WO	WO-02/094116	11/2002
WO	WO-9000420	1/1990	WO	WO-02094116	11/2002
WO	WO-9102562	3/1991	WO	WO-03/005883 A2	1/2003
WO	WO-9113652	9/1991	WO	WO-03/049633 A1	6/2003
WO	WO-9216338	10/1992	WO	WO-2004/000150 A1	12/2003
WO	WO-9219165	11/1992	WO	WO-2004/011848 A2	2/2004
WO	WO-9305920	4/1993	WO	WO-2004033040	4/2004
WO	WO-95/10243 A1	4/1995	WO	WO-2004/037068 A2	5/2004
WO	WO-9515725	6/1995	WO	WO-2004/037287 A2	5/2004
WO	WO-9532441	11/1995	WO	WO-2004/080279 A2	9/2004
WO	WO-96/22741 A1	8/1996	WO	WO-2004073537	9/2004

WO	WO-2004084752	10/2004
WO	WO-2004086947	10/2004
WO	WO-2005007003	1/2005
WO	WO-2005009266	2/2005
WO	WO-2005030317	4/2005
WO	WO-2005/046793 A2	5/2005
WO	WO-2005/065288 A2	7/2005
WO	WO-2005/092438 A1	10/2005
WO	WO-2005/096981 A2	10/2005
WO	WO-2005/099369 A2	10/2005
WO	WO-2005112815	12/2005
WO	WO-2006/006123 A1	1/2006
WO	WO-2006036968	4/2006
WO	WO-2006/066226 A1	6/2006
WO	WO-2006/089227 A2	8/2006
WO	WO-2006/101735 A1	9/2006
WO	WO-2006/116141 A1	11/2006
WO	WO-2007/035444	3/2007
WO	WO-2007/122611 A2	11/2007
WO	WO-2008/070747 A2	6/2008

OTHER PUBLICATIONS

A.J. Welch et al., "Evaluation of cooling techniques for the protection of the pidermis during HD-yag laser irradiation of the skin," Neodymium-Yag Laser in Medicine and Surgery, Elsevier Science Publishing Co., publisher, pp. 195-204, 1983.

Abstract Nos. 17-19, Lasers in Surgery and Medicine, ASLMS, Supplement 13, 2001.

Abstracts, Lasers in Surgery and Medicine, ASLMS, Twenty-First Annual Meeting, Sep. 13, 2001.

Abstracts, various.

Altshuler et al., "Acoustic Response of Hard Dental Tissues to Pulsed Laser Action", *SPIE* 2080:97-103 1993.

Altshuler et al., "Extended Theory of Selective Photothermolysis", *Lasers in Surgery and Medicine* 29:416-432 2001.

Anderson et al., "Selective Photothermolysis: Precise Microsurgery by Selective Absorption of Pulsed Radiation", *Science*, 220:524-527, 1983.

Anderson et al., "The Optics of Human Skin", *The Journal of Investigative Dermatology*, 77:13-19, 1981.

Bjerring et al., "Selective non-ablative wrinkle reduction by laser", *Journal of Cutaneous Laser Therapy* 2000; 2:9-15.

C.R. Taylor et al., "Treatment of tattoos by Q-switched ruby laser", *Arch. Dermatol.* vol. 126, pp. 893-899, Jul. 1990.

Doukas et al., "Transdermal Drug Delivery With a Pressure Wave", *Advanced Drug Delivery Reviews* 56, pp. 559-579, 2004.

Dover et al., "Pigmented Guinea Pig Skin Irradiated With Q-Switched Ruby Laser Pulses", *Arch Dermatol*, 125:43-49, 1989.

E. Klein et al., "Biological effects of laser radiation I.," Northeast Electronics Research and Engineering Meeting, NEREM Record, IEEE catalogue No. F-60, pp. 108-109, 1965.

E. Zeitler and M. L. Wolbarsht, "Laser Characteristics that Might be Useful in Biology," *Laser Applications in Medicine and Biology*, vol. I, M.L. Wolbarsht, editor, Plenum Press, publishers, Chapter 1, pp. 1-18, 1971.

Finkelstein et al., "Epilation of Hair-Bearing Urethral Grafts Using the Neodymium:Yag Surgical Laser", *The Journal of Urology*, 146:840-842, 1991.

Fiskerstrand, et al., "Hair Removal With Long Pulsed Diode Lasers: A Comparison Between Two Systems With Different Pulse Structures", *Lasers in Surgery and Medicine*, 32:399-404, 2003.

G.G. Riggle et al., "Laser effects on normal and tumor tissue," *Laser Applications in Medicine and Biology*, vol. I, M.L. Wolbarsht, editor, Plenum Press, publishers, Chapter 3, pp. 35-65, 1971.

Goldman et al., "Preliminary Investigation of Fat Embolization from Pulsed Ruby Laser Impacts of Bone", *Nature*, 221:361-363, 1969.

Goldman et al., "Effect of the Laser Beam on the Skin: III. Exposure of Cytological Preparations", *The Journal of Investigative Dermatology*, 42:247-251, 1964.

Goldman et al., "Impact of the Laser on Nevi and Melanomas", *Arch Dermatol*, 90:71-75, 1964.

Goldman et al., "Laser Action at the Cellular Level", *JAMA*, 198:641-644, 1966.

Goldman et al., "Laser Treatment of Tattoos", *JAMA*, 201:841-844, 1967.

Goldman et al., "Long-Term Laser Exposure of a Senile Freckle", *Arch Environ Health*, 22:401-403, 1971.

Goldman et al., "Pathology of the Effect of the Laser Beam on the Skin", *Nature*, 197:912-914, 1963.

Goldman et al., "Replica Microscopy and Scanning Electron Microscopy of Lower Impacts on the Skin", *The Journal of Investigative Dermatology*, 52:18-24, 1969.

Goldman et al., "The Effect of Repeated Exposures to Laser Beams", *Acta derm. venerol.* 44:264-268, 1964.

Goldman et al., "Treatment of Basal Cell Epithelioma by Laser Radiation", *JAMA*, 189:773-775, 1964.

Goldman, et al., "Effect of the Laser Beam on the Skin: Preliminary and Short Report", *The Journal of Investigative Dermatology*, 40:121-122, 1963.

Goldman, et al., "Radiation from a Q-Switched Ruby Laser. Effect of Repeated Impacts of Power Output of 10 Megawatts on a Tattoo of Men", *The Journal of Investigative Dermatology*, 44:69-71, 1965.

Goldman, et al., "The Biomedical Aspects of Lasers", *JAMA*, 188: 1967 (15 pgs).

Goldman, Leon, "Dermatologic Manifestations of Laser Radiation", *Federation of American Societies for Experimental Biology*, Suppl. 14:S-92-S-93, 1965.

Goldman, Leon, "Effects of New Laser Systems on the Skin", *Arch Dermatol*, 108:385-390, 1973.

Goldman, Leon, "Laser Surgery for Skin Cancer", *New York State Journal of Medicine*, 77:1897-1900, 1977.

Goldman, Leon, "Surgery by Laser for Malignant Melanoma", *J. Dermatol. Surg. Oncol.* 5:2:141-144, 1979.

Goldman, Leon, "The Skin", *Arch Environ Health*, 18:434-436, 1969.

Grossman et al., "Damage to Hair Follicles by Normal-Mode Ruby Laser Pulses", *Journal of the American Academy of Dermatology*, 35:889-894, 1996.

Grossman et al., "Laser Targeted at Hair Follicles", *American Society for Laser Medicine and Surgery*, Suppl. 7:221, 1995 (4 pgs).

J.A. Parrish, "Selective thermal effects with pulsed irradiation from lasers: From organ to organelle," *Journal of Investigative Dermatology*, vol. 80, No. 6 Supplement, pp. 75s-80s, 1983.

J.G. Kuhns et al., "Biological effects of laser radiation II Effects of laser irradiation on the skin," *NEREM Record*, pp. 152-153, 1965.

J.G. Kuhns et al., "Laser injury in skin," *Laboratory Investigation*, vol. 17, No. 1, pp. 1-13, Jul. 1967.

L. Goldman et al., "Effect of the laser beam on the skin, Preliminary report" *Journal of Investigative Dermatology*, vol. 40, pp. 121-122, 1963.

L. Goldman et al., "Laser treatment of tattoos, A preliminary survey of three year's clinical experience," *JAMA*, vol. 201, No. 11, pp. 841-844, Sep. 1967.

L. Goldman et al., The biomedical aspects of lasers, *JAMA*, vol. 188, No. 3, pp. 302-306, Apr. 1964.

L. Goldman, Biomedical Aspects of the Laser, Springer-Verlag New York Inc., publishers, Chaps. 1, 2, & 23, 1967.

L. Polla et al., "Melanosomes are a primary target of Q-switched ruby laser irradiation in guinea pig skin," *Journal of Investigative Dermatology*, vol. 89, No. 3, pp. 281-286, Sep. 1987.

Manstein et al., "Selective Photothermolysis of Lipid Rich Tissue", *American Society for Laser Medicine and Surgery Abstracts*, 2001 (2 pgs).

Margolis et al., "Visible Action Spectrum for Melanin-Specific Selective Photothermolysis", *Lasers in Surgery and Medicine* 9:389-397, 1989.

Ohshiro et al., "The Ruby and Argon Lasers in the Treatment of the Naevi," *Annals Academy of Medicine*, Apr. 1983, vol. 12, No. 2, pp. 388-395.

P. Bjerring et al., "Selective Non-Ablative Wrinkle Reduction by Laser," *J Cutan Laser Ther*, vol. 2, pp. 9-15, 2000.

S. Watanabe et al., "Comparative studies of femtosecond to microsecond laser pulses on selective pigmented cell injury in skin," *Photochemistry and Photobiology*, vol. 53, No. 6, pp. 757-762, 1991.

Shimbashi, et al., "Ruby Laser Treatment of Pigmented Skin Lesions", *Aesthetic Plastic Surgery*, 19:225-229, 1995.

- Storb et al., "Selective Mitochondrial Damage by a Ruby Laser Microbeam: An Electron Microscopic Study", *Science*, pp. 736-738, 1965.
- Stratton, et al., "Biological Effects of Laser Radiation II: ESR Studies of Melanin Containing Tissues after Laser Irradiation", *NEREM Record*, IEEE Catalogue No. F-60, pp. 150-151, 1965.
- Sumian et al., "Laser Skin Resurfacing Using a Frequency Doubled Nd:YAG Laser After Topical Application of an Exogenous Chromophore", *Lasers in Surgery and Medicine* 25:43-50, 1999.
- Sumian, C.C. et al., "A Preliminary Clinical and Histopathological Study of Laser Skin Resurfacing Using a Frequency-Doubled Nd:YAG Laser After Application of Chromofilm.RTM.," *Journal of Cutaneous Laser Therapy*, vol. 1, pp. 159-166, 1999.
- T. Shimbashi & T. Kojima, "Ruby laser treatment of pigmented skin lesions," *Aesth. Plast. Surg.*, vol. 19, pp. 225-229, 1995.
- Yules, et al., "The Effect of Q-Switched Ruby Laser Radiation on Dermal Tattoo Pigment in Man", *Arch Surg.*, 95:179-180, 1967.
- International Preliminary Examination Report, International Patent Application No. PCT/US02/16435, completed Sep. 24, 2003 (5 pages).
- International Search Report, International Patent Application No. PCT/US02/16435, mailed Sep. 26, 2002 (4 pages).
- PCT International Preliminary Report on Patentability dated Oct. 8, 2007 for International Application No. PCT/US2006/035927 (7 pages).
- Written Opinion from the International Preliminary Examining Authority, International Patent Application No. PCT/US02/16435, mailed May 22, 2003 (5 pages).
- Examination Report, Canadian Patent Application No. 2,448,385, dated Jul. 9, 2007 (5 pgs).
- Examination Report, Canadian Patent Application No. 2,448,385, dated Aug. 4, 2008 (4 pgs).
- Supplemental Partial European Search Report, European Patent Application No. 02731925, dated Oct. 13, 2005 (5 pgs).
- European Examination Report, European Patent Application No. 02731925, dated Apr. 5, 2007 (5 pgs).
- European Examination Report, European Patent Application No. 02731925, dated Sep. 1, 2008 (3 pgs).
- Examination Report, Australian Patent Application No. 2002303863, dated Apr. 27, 2005 (2 pgs).
- Examination Report, Australian Patent Application No. 2006246485, dated Mar. 27, 2007 (2 pgs).
- Japan Office Action, Japanese Patent Application No. 2002-590840, dated Jan. 24, 2008 (1 pg).
- Japan Office Action, Japanese Patent Application No. 2002-590840, dated Sep. 2, 2008 (1 pg).
- First Office Action, Chinese Patent Application No. 02814860.6, issued Apr. 22, 2005 (11 pgs).
- First Office Action, Chinese Patent Application No. 200610079270.1, issued Dec. 7, 2007 (2 pgs).
- Second Office Action, Chinese Patent Application No. 200610079270.1, issued Aug. 22, 2008 (17 pgs).
- First Office Action, Chinese Patent Application No. 200610093460.9, issued Dec. 7, 2007 (7 pgs).
- Second Office Action, Chinese Patent Application No. 200610093460.9, issued Aug. 22, 2008 (8 pgs).
- Marinelli et al., "Diode Laser Illuminated Automotive Lamp Systems", *SPIE*, 3285:170-177, 1998.
- Remillard, et al., "Diode Laser Illuminators for Night Vision Applications", *Proc. SPIE* 4285, 14-22, 2001.
- Remillard, et al., "Diode Laser Illuminated Automotive Brake Lamp Using Linear Fanout Diffractive Optical Element in Diffractive Optics and Micro-Optics", *OSA Technical Digest Series*, vol. 10, 192-194, 1998.
- Rhorer et al., Evaluating the Safety and Efficacy of a Novel Light Based Hair Removal System, ASLMS 2001 Convention, New Orleans, Apr. 2001 (2 pgs).
- Watanabe, et al., "The Effect of Pulse Duration on Selective Pigmented Cell Injury by Dye Lasers," *The Journal of Investigative Dermatology*, 88:523, 1987 (2 pgs).
- "Bioptron Light Therapy System," website print-out, accessed Jul. 13, 2006 (1 page).
- Altshuler et al., "Human Tooth as an Optical Device," *SPIE* vol. 1429 Holography Interferometry and Optical Pattern Recognition in Biomedicine, pp. 95-104, 1991. 10 pages.
- Altshuler et al., "Modern Optics and Dentistry," *Lasers in Dentistry*, pp. 283-297, 1995. 17 pages.
- Altshuler et al., "New Optical Effects in the Human Hard Tooth Tissues," *Lasers and Medicine*, *Proc. SPIE* vol. 1353, pp. 97-102, 1989. 6 pages.
- Amy, R.L. et al., "Selective mitochondrial damage by a ruby laser microbeam: An electron microscopic study," *Science*, vol. 150, pp. 756-758, Nov. 1965. 3 pages.
- Anderson, R.R. et al., "Selective photothermolysis: Precise microsurgery by selective absorption of pulsed radiation," *Science*, vol. 220, pp. 524-527, Apr. 1983. www.sciencemag.org, accessed Oct. 13, 2011, 4 pages.
- Apfelberg et al. "Analysis of Complications of Argon Laser Treatment for Port Wine Hemangiomas with Reference to Striped Technique," *Lasers in Surgery and Medicine*, 2:357-371 (1983). 16 pages.
- Apfelberg et al. "Dot or Pointillistic Method for Improvement in Results of Hypertrophic Scarring in the Argon Laser Treatment of Portwine Hemangiomas," *Lasers in Surgery and Medicine*, 6:552-558 (1987). 8 pages.
- Blankenau et al., "In Vivo Caries-Like Lesion Prevention with Argon Laser: Pilot Study," *Journal of Clinical Laser Medicine and Surgery*, vol. 17, No. 6, pp. 241-243, 1999.
- Chan, E.K., "Effects of Compression on Soft Tissue Optical Properties," *IEEE Journal of Selected Topics in Quantum Electronics*, vol. 2, No. 4, pp. 943-950 (Dec. 1996). 8 pages.
- Dabrowska, "Intravital Treatment of the Pulp with Stimulation Laser Biostimulation," *Rocz-Akad-Med-Bialymst*. 1997; 42(1): 168-76.— Abstract 10 pages.
- Dixon et al. "Hypertrophic Scarring in Argon Laser Treatment of Port-Wine Stains," *Plastic and Reconstructive Surgery*, 73:771-777 (1984). 8 pages.
- Forrest-Winchester et al., "The Effect of Infrared Laser Radiation on Dentine Permeability in vitro," *Department of Dentistry, University of Queensland Dental School*, pp. 1-8, 1992. 8 pages.
- Ginsbach et al. "New Aspects in the Management of Benign Cutaneous Tumors," *Laser 79 Opto-Electronics*, Munich Conference Proceedings, 344-347 (1979).
- Gottlieb, I., "Power Supplies, Switching Regulators, Inverters & Converters," 1976. 6 pages.
- Greenwald et al. "Comparative Histological Studies of the Tunable Dye (at 577 nm) Laser and Argon Laser: The Specific Vascular Effects of the Dye Laser," *The Journal of Investigative Dermatology*, 77:305-310 (1981). 7 pages.
- Grossman, et al., "780 nm Low Power Diode Laser Irradiation Stimulates Proliferation of Keratinocyte Cultures: Involvement of Reactive Oxygen Species," *Lasers in Surgery and Medicine* vol. 22, pp. 212-218, 1998. 8 pages.
- Hicks et al., "Enamel Caries Initiation and Progression Following Low Fluence (energy) and Argon Laser and Fluoride Treatment," *The Journal of Clinical Pediatric Dentistry*, vol. 20, No. 1 pp. 9-13, 1995. 6 pages.
- Hsu et al., "Combined Effects of Laser Irradiation/Solution Fluoride Ion on Enamel Demineralization," *Journal of Clinical Laser Medicine and Surgery*, vol. 16, No. 2 pp. 93-105, 1998. 13 pages.
- Hulsbergen Henning et al. "Clinical and Histological Evaluation of Portwine Stain Treatment with a Microsecond-Pulsed Dye-Laser at 577 NM," *Lasers in Surgery and Medicine*, 4:375-380 (1984). 7 pages.
- Hulsbergen Henning et al., "Port Wine Stain Coagulation Experiments with a 540-nm Continuous Wave Dye-Laser," *Lasers in Surgery and Medicine*, 2:205-210 (1983). 7 pages.
- IPG Data Sheet for TFL Thulium Laser, Jun. 2001. 2 pgs.
- Ivanov, A.P. et al., "Radiation Propagation in Tissues and Liquids with Close Particle Packing," *Zhurnal Prikladnoi Spektroskopii*, vol. 47, No. 4, pp. 662-668 (Oct. 1987). English Translation. 6 pages.
- Kalivradzhiyan et al., "The Usage of Low Intensity Laser Radiation for the Treatment of the Inflammatory processes of the Oral Cavity Mucosa after Applying Removable Plate Dentures," *SPIE* vol. 1984 pp. 225-230. (1995) 6 pages.

- Karu, "Cell Attachment to Extracellular Matrices is Modulated by Pulsed Radiation at 820 nm and Chemicals that Modify the Activity of Enzymes in the Plasma Membrane," *Lasers in Surgery and Medicine*, vol. 29, pp. 274-281, 2001. 9 pages.
- Karu, "Photobiological Fundamentals of Low-Power Laser Therapy," *IEEE Journal of Quantum Electronics*, vol. QE-23, No. 10, Oct. 1987, pp. 1703-1717. 15 pages.
- Kazmina et al., "Laser Prophylaxis and Treatment of Primary Caries," *SPIE* vol. 1984, pp. 231-233. (1995) 3 pages.
- Kozlov et al., "Laser in Diagnostics and Treatment of Microcirculation Disorders Under Parodontitis," *SPIE* vol. 1984, pp. 253-264. (1995) 12 pages.
- Kuhns, J.G. et al., "Biological effects of laser radiation II: Effects of laser irradiation on the skin," *NEREM Record*, pp. 152-153, 1965. 4 pages.
- Kuhns, J.G. et al., "Laser injury in skin," *Laboratory Investigation*, vol. 17, No. 1, pp. 1-13, Jul. 1967. 14 pages.
- Levin, G. et al., "Designing with hysteretic current-mode control," *EDN Magazine*, pp. 1-8, Apr. 11, 1996. www.edn.com/archives/1996/04/196/08df5.htm, accessed Oct. 3, 2011, 8 pages.
- Levin, G. et al., "Designing with hysteretic current-mode control," *EDN Magazine*, pp. 1-8, Apr. 28, 1994. www.edn.com/archives/1994/04/2894/09df3.htm, accessed Oct. 3, 2011, 8 pages.
- Maegawa, et al., "Effects of Near-Infrared Low-Level Laser Irradiation on Microcirculation," *Lasers in Surgery and Medicine*, vol. 27, pp. 427-437, 2000. 12 pages.
- Mamedova et al., "Microbiological Estimate of Parodontitis Laser Therapy Efficiency," *SPIE* vol. 1984, pp. 247-249. 1995. 3 pages.
- Mumford, "Effect of Soft Laser Treatment on Wound Healing in the Hamster Oral Mucosa," *Lasers in Surgery and Medicine*, Supplement 8, Abstracts, Abstract 25, pp. 6. 1996. 2 pages.
- McDaniel, et al., "Hexascan: A New Robotized Scanning Laser Handpiece," *Cutis*, 45:300-305 (1990). 7 pages.
- Nemeth, et al., "Copper vapor laser treatment of pigmented lesions," *Lasers Surg. Med. Supp.* 2:51 (1990). Abstract 214. 2 pages.
- Ohbayashi, "Stimulatory Effect of Laser Irradiation on Calcified Nodule Formation in Human Dental Pulp Fibroblasts," *J-Endod. Jan. 1999*; 25(1): 30-3. 5 pages.
- Oleinik, et al., "Automatized Securing Definition for Laser Therapy Indications in Case of Non-complicated Caries," *SPIE*, vol. 1984, pp. 238-244. 1995. 7 pages.
- Orchardson, "Effect of Pulsed Nd:YAG Laser Radiation on Action Potential Conduction in Nerve Fibres Inside Teeth in vitro," *J-Dent. Jul.-Aug. 1998*; 26(5-6): 421-6. 7 pages.
- Osigo et al., "Phase Transitions of Rat Stratum Corneum Lipids by an Electron Paramagnetic Resonance Study and Relationship of Phase States to Drug Penetration," *Biochimica et Biophysica Acta* 1301:97-104 (1996). 9 pages.
- Ozawa et al., "Stimulatory Effects of Low-Power Laser Irradiation on Bone Formation in vitro," *SPIE* vol. 1984, pp. 281-288. 1995. 8 pages.
- Petrishchev et al. "Clinical and Experimental Low-Intense Laser Therapy in Dentistry," *SPIE*, vol. 1984, pp. 212-214. 1995. 3 pages.
- Petrishchev et al., "Report on Low Intensity Laser Radiation Usage in Dentistry," *SPIE* vol. 1984, pp. 202-211. 1995. 10 pages.
- Powell, "Laser Dental Decay Prevention: does it have a future?" *SPIE* vol. 3192, pp. 2-5. 1997. 4 pages.
- Rohrer, "Evaluating the Safety and Efficacy of a Novel Light Based Hair Removal System," *Lasers. Surg. Med. Supp.* 13. Abstract 97, p. 24 (2001). 2 pages.
- Rotteleur, et al., "Robotized scanning laser handpiece for the treatment of port wine stains and other angiodysplasias," *Lasers Surg. Med.*, 8:283-287 (1998). 6 pages.
- Rubach et al., "Histological and Clinical Evaluation of Facial Resurfacing Using a Carbon Dioxide Laser With the Computer Pattern Generator," *Arch Otolaryngol Head Neck Surg.*, 123:929-934 (1997). 7 pages.
- Rylander, C.G. et al., "Mechanical Tissue Optical Clearing Devices: Enhancement of Light Penetration in Ex Vivo Porcine Skin and Adipose Tissue," *Lasers in Surgery and Medicine*, vol. 40, pp. 688-694 (2008). 7 pages.
- Sandford et al., "Thermal Effects During Desensitisation of Teeth with Gallium-Aluminum-Arsenide Lasers," *University of Queensland Dental School, Periodontology* 15: 25-30 (1994). 6 pages.
- Schindl, "Does Low Intensity Laser Irradiation Really Cause Cell Damage?" *Laser in Surgery and Medicine* vol. 29, pp. 105, 2001. 2 pages.
- Sheehan-Dare, et al., "Lasers in Dermatology," *British Journal of Dermatology*, 129:1-8 (1993). 10 pages.
- Shimizu et al., "Prospect of Relieving Pain Due to Tooth Movement During Orthodontic Treatment Utilizing a GA-AI-As Diode Laser," *SPIE* vol. 1984, pp. 275-280. 1995. 6 pages.
- Shumilovitch et al., "Influence of Low Intensity Laser Radiation Upon the Microflora of Carious Cavities and Root Canal," *SPIE* vol. 1984, pp. 215-220. 1995. 6 pages.
- Sing, "Electroacupuncture and Laser Stimulation Treatment: Evaluated by Somatosensory Evoked Potential in Conscious Rabbits," *AM-J-Chin-Med.* 1997; 25(3-4): 263-71. 9 pages.
- Sokolova et al., "Low-intense Laser Radiation in Complex Treatment of Inflammatory Diseases of Parodontium," *SPIE* vol. 1984, pp. 234-237. 1995. 4 pages.
- Sumian, C.C. et al., "A Preliminary Clinical and Histopathological Study of Laser Skin Resurfacing Using a frequency-Doubled Nd:YAG Laser After Application of Chromofilm®," *Journal of Cutaneous Laser Therapy*, vol. 1, pp. 159-166, 1999 8 pages.
- Unger, "Laser Hair Transplantation III. Computer-assisted Laser Transplanting," *Dermatol. Surg.*, 21:1047-1055 (1995). 10 pages.
- Van Bruegel, "Power Density and Exposure Time of He-Ne Irradiation Are More Important Than Total Energy Dose in Photo-Biomodulation of Human Fibroblasts in Vitro," *Lasers in Surgery and Medicine*, vol. 12 pp. 528-537, 1992. 11 pages.
- Walsh, "Laser "Curettage": a Critical Analysis," *Periodontology* 14:4-12, 1993. 9 pages.
- Walsh, "The Current Status of Low Level Laser Therapy in Dentistry. Part I. Soft Tissue Applications". *Australian Dental Journal*, 42(4):247-254 (1997) 8 pages.
- Watanabe, S. et al., "The Effect of Pulse Duration on Selective Pigmented Cell Injury by Dye Lasers," *The Journal of Investigative Dermatology*, 88:523, 1987. Abstract. 2 pages.
- Westerman et al., "Argon Laser Irradiation Effects on Sound Root Surfaces: In Vitro Scanning Electron Microscopic Observations," *Journal of Clinical Laser Medicine and Surgery*, vol. 16, No. 2, pp. 111-115, 1998. 6 pages.
- Yules, R.B. et al., "The effect of Q-switched ruby laser radiation on dermal tattoo pigment in man," *Arch Surg*, vol. 95, pp. 179-180, Aug. 1967. 3 pages.
- Zonios et al., "Skin Melanin, Hemoglobin, and Light Scattering Properties can be Quantitatively Assessed In Vivo Using Diffuse Reflectance Spectroscopy," *Journal of Investigative Dermatology*, 117:1452-1457 (Dec. 2001). 7 pages.
- US 6,230,044, 05/2001, Afanassieva et al. (withdrawn)

* cited by examiner

FIG. 1




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 15A




FIG. 15B




FIG. 16A




FIG. 16B




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18A




FIG. 18B




FIG. 19





FIG. 20

FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26A




FIG. 26B




FIG. 27





FIG. 28



1

COOLING SYSTEM FOR A PHOTOCOSMETIC DEVICE

RELATED APPLICATIONS

This application is a continuation of application Ser. No. 10/154,756 ("the '756 application"), filed May 23, 2002, which claims priority to provisional application Ser. No. 60/363,798, filed Mar. 12, 2002. The '756 application is also a continuation-in-part of application Ser. No. 10/052,474, filed Jan. 18, 2002, which application is a continuation of application Ser. No. 09/473,910, filed Dec. 28, 1999, which application claims priority to provisional application Ser. No. 60/115,447, filed Jan. 8, 1999, claims priority from provisional application Ser. No. 60/164,492, filed Nov. 9, 1999, and is a continuation-in-part of application Ser. No. 09/078,055, filed May 13, 1998, now U.S. Pat. No. 6,273,884, which application claims priority to provisional application Ser. No. 60/046,542, filed May 15, 1997 and provisional application Ser. No. 60/077,726, filed Mar. 12, 1998. The '756 application is also a continuation-in-part of application Ser. No. 09/268,433, filed Mar. 12, 1999, which application claims priority to provisional application Ser. No. 60/115,447, filed Jan. 8, 1999 and provisional application Ser. No. 60/077,794, filed Jan. 8, 1999 and is a continuation-in-part of application Ser. No. 08/759,036, filed Dec. 2, 1996, now U.S. Pat. No. 6,015,404, and is a continuation-in-part of application Ser. No. 08/759,136, filed Dec. 2, 1996, now abandoned, and is a continuation-in-part of application Ser. No. 09/078,055, filed May 13, 1998, now U.S. Pat. No. 6,273,884, which application claims priority to provisional application Ser. No. 60/046,542, filed May 15, 1997 and provisional application Ser. No. 60/077,726, filed Mar. 12, 1998. The '756 application is also a continuation-in-part of application Ser. No. 09/634,981, filed Aug. 9, 2000, which application is a continuation of application Ser. No. 09/078,055, filed May 13, 1998, now U.S. Pat. No. 6,273,884, which application claims priority to provisional application Ser. No. 60/046,542, filed May 15, 1997 and provisional application Ser. No. 60/077,726, filed Mar. 12, 1998. The '756 application is also a continuation-in-part of application Ser. No. 09/847,043, filed Apr. 30, 2001, which claims priority to provisional application Ser. No. 60/200,431, filed Apr. 28, 2000. The '756 application also claims priority to provisional application Ser. No. 60/292,827, filed May 23, 2001. The '756 application also claims priority to provisional application Ser. No. 60/363,871, filed Mar. 12, 2002. The contents of all of these prior application specifications are incorporated herein by reference.

BACKGROUND OF THE INVENTION

Related Art

There exists a variety of conditions treatable using photocosmetic procedures (also referred to herein as photocosmetic treatments), including light-based (e.g., using a laser or lamp) hair removal, treatment of various skin lesions, tattoo removal, facial resurfacing, and skin rejuvenation. Currently, photocosmetic procedures are performed using professional-grade devices that cause destructive heating of target structures located in the epidermis/dermis of a patient's skin.

To date, photocosmetic procedures have been performed in a dermatologist's office, partially because of the expense of the devices used to perform the procedures, partially because of safety concerns related to the devices, and partially because of the need to care for optically induced wounds on

2

the patient's skin. Such wounds may arise from damage to a patient's epidermis caused by the high-power radiation and may result in significant pain and/or risk of infection. While certain photocosmetic procedures, such as CO₂ laser facial resurfacing, will continue to be performed in the dermatologist's office for medical reasons (e.g., the need for post-operative wound care), there are a large number of photocosmetic procedures that could be performed in a non-medical environment (e.g., home, barber shop, or spa) if the consumer could perform the procedure in a safe and effective manner. Even for procedures performed in a medical environment, reduced skin damage would reduce recovery time.

Photocosmetic devices for use in medical or non-medical environments may benefit from following characteristics: (1) The device must be safe. For example, it is necessary to avoid eye and skin injuries. (2) Preferably the device is easy to use, thus allowing an operator to achieve acceptable cosmetic results after only reading a brief training period. (3) Preferably the device is robust and rugged enough to withstand abuse. (5) Preferably the device is easy to maintain. (6) Preferably the device is manufacturable in high volume. (7) Preferably the device is available at a reasonable price. (8) Preferably the device is small and easily stored, for example, in a bathroom. Currently available photocosmetic devices have limitations related to one or more of the above challenges.

SUMMARY OF THE INVENTION

A first aspect of the invention is a photocosmetic device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one source of electromagnetic radiation positioned within the treatment head and configured to project radiation onto the area of skin, a cooling surface thermally coupled to the at least one source, and a mechanism to direct a phase change substance onto the cooling surface. Optionally, the phase change substance comprises a liquid. Alternatively, the phase change substance comprises a solid.

In some embodiments of the first aspect, the surface has a texture. The texture may be a linear groove pattern or a concentric groove pattern. Alternatively, the texture is a plurality of projections. The mechanism may be a spray jet. The mechanism may further comprise a valve coupled to the spray jet, wherein the valve controls the amount of liquid projected onto the cooling surface. A heat sensor may be used to produce a signal indicative of the temperature of at least a portion of the area of skin, and a controller may be used to receive the signal from the heat sensor and control the valve in response to the temperature.

A container may be included to hold the substance. In some embodiments, the substance is a refrigerant. For example, the refrigerant comprises tetra fluoroethane. The solid may be ice or an organic compound, or an Ga/In alloy.

The cooling surface may be a thermally conductive electrode providing power to the source. Alternatively, the cooling surface may be a surface of a thermally conductive heat sink that is thermally coupled to the source. The cooling surface may have at least one channel therethrough to receive the phase change substance. Alternatively, the cooling surface has a plurality of channels therethrough to receive the phase change substance, the plurality of channels aligned along the length.

A second aspect of the invention is a photocosmetic device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one electromagnetic radiation source configured to project radiation through the treatment head onto the area of skin, and

3

a first mechanism coupled to the treatment head and configured to project a first substance onto the patient's skin. The electromagnetic radiation source may be positioned within the treatment head. The device may include an optical system to transmit radiation to the area of skin, the optical system having a surface configured to contact the patient's skin. The device may further comprise a cooling surface thermally coupled to the at least one source and said surface; and second mechanism to project a phase change substance onto the cooling surface, wherein the first mechanism is configured to use a gas formed by the phase change of the second substance to drive the first substance onto the patient's skin. The device may further comprising a cooling surface thermally coupled to the source and said surface, and a second mechanism configured to project a portion of the first substance onto the cooling surface.

The first substance may be a liquid and the portion of the first substance projected onto the skin is a gas resulting from a phase change of the first substance. Alternatively, the first substance is a solid and the portion of the first substance projected onto the skin is a liquid resulting from a phase change of the first substance. In yet another alternative, the first substance is a solid and the portion of the first substance projected onto the skin is a gas resulting from a phase change of the first substance.

The first substance may be a liquid, and the liquid may be a lotion. Alternatively, the first substance may be a gas, and the gas may be cooled air. The second substance may comprise a plurality of components. The cooling surface may be a surface of a thermally conductive electrode providing power to the source. The cooling surface may be a surface of a thermally conductive heat sink that is thermally coupled to the source. Optionally, the source is one of a diode laser bar, light emitting diode and lamp.

A third aspect of the invention is a device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one electromagnetic radiation source positioned in the treatment head and configured to project electromagnetic radiation onto the area of skin, a cooling surface thermally coupled to the at least one source of electromagnetic radiation and including at least one channel therethrough, and a mechanism to project a substance onto the cooling surface, and into the at least one channel.

The substance may be a liquid or a gas.

A fourth aspect of the invention is a device for use on an area of a patient's skin comprising at least one electromagnetic radiation source configured to project radiation onto the area of skin, a cooling surface thermally coupled to the at least one source, and a solid mass thermally coupled to the cooling surface, the solid mass changing phase in response to heat absorbed from the cooling surface.

In some embodiments the solid mass is ice or may be dry ice. The device may further comprise a mechanism to bring the solid mass into contact with the cooling surface. The device may further comprise a treatment head, wherein the source is positioned within the treatment head. The source may be one of a diode laser bar, light emitting diode and lamp.

The cooling surface is a surface of a thermally conductive electrode providing power to the source or a thermally conductive heat sink that is thermally coupled to the source.

A fifth aspect of the invention is a device for use on an area of a patient's skin comprising at least one electromagnetic radiation source configured to project electromagnetic radiation onto the area of skin, a cooling surface thermally coupled to the at least one source, a solid mass thermally coupled to the cooling surface, at least a portion of the mass becoming a liquid in response to absorption of heat from the cooling

4

surface, and an exhaust vent configured to receive a portion of the liquid and project the portion of the liquid onto the patient's skin.

The device may further comprise a mechanism for combining the liquid with a chemical substance and directing the liquid and chemical combination onto the patient's skin.

A sixth aspect of the invention is a device for use on an area of a patient's skin comprising at least one electromagnetic radiation source configured to project electromagnetic radiation onto the area of skin, a cooling surface thermally coupled to the at least one source, and a reaction chamber thermally coupled to the cooling surface and containing at least a first chemical compound and a second chemical compound, the first and second chemical compounds selected to provide an endothermic reaction within the reaction chamber.

The cooling surface may be a surface of a thermally conductive electrode providing power to the source, or the cooling surface may be a surface of a thermally conductive heat sink that is thermally coupled to the source.

A seventh aspect of the invention is a device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one source of electromagnetic radiation positioned in the treatment head and configured to project electromagnetic radiation onto the area of skin, and a cooling surface thermally coupled to the at least one source of electromagnetic radiation, the cooling surface having a channel therethrough to allow a low-boiling point liquid to flow onto a surface of the cooling surface.

The device may further comprise a valve connected to the channel to control the evaporation of the low-boiling point liquid. The device may also further comprise a heat sensor to produce a signal indicative of the temperature of the area of skin, and a controller to receive the signal from the heat sensor and control the valve in response to the signal. The device may have a pressure source is coupled to the channel to control the boiling of the low-boiling point liquid. The source is one of a laser diode bar, light emitting diode and lamp.

The eighth aspect of the invention is a device for use on an area of a patient's skin comprising a treatment head for use in close proximity to the patient's skin, at least one electromagnetic radiation source positioned in the treatment head and configured to project radiation onto the area of skin, a heat spreader thermally coupled to the at least one source, and a cooling surface thermally coupled to the heat spreader. The source may be one of a diode laser bar, light emitting diode and lamp. The cooling surface may be a surface of a thermally conductive electrode providing power to the source, or may be a surface of a thermally conductive heat sink that is thermally coupled to the source.

A ninth aspect of the invention is a cooling system for cooling a heat generating device a cooling surface thermally coupled to the heat generating device, and a nozzle configured to project a high pressure liquid, the liquid forming a flowing liquid on the cooling surface. The high pressure liquid may be projected such that the liquid forms a stream of liquid the entire distance between the nozzle and the cooling surface. The cooling surface may be textured. Optionally the cooling system may further comprise a cooling chamber to redirect the liquid to the cooling surface. The cooling chamber may include sidewalls and a cover. While many of the embodiments are described with reference to performing photocosmetic treatments in a non-medical environment, it is to be understood that the benefits of aspects of this invention apply to medical devices as well as non-medical devices, and the invention applies to either without limitation.

BRIEF DESCRIPTION OF THE DRAWINGS

Illustrative, non-limiting embodiments of the present invention will be described by way of example with reference

5

to the accompanying drawings, in which the same reference numeral is for the common elements in the various figures, and in which:

FIG. 1 is a schematic illustration of some basic elements of a photocosmetic device according to some aspects of the present invention;

FIG. 2A is a side view of one example of a radiation system according to some aspects of the present invention for use in performing a photocosmetic procedure on an area of a patient's skin;

FIG. 2B is a schematic top view of an irradiated area of a patient's skin taken along lines 2B-2B' of FIG. 2A;

FIG. 3 is a side view of an example of a radiation system that is capable of forming two areas of radiation on an area of a patient's skin;

FIG. 4 is a top view of one example of a system appropriate for formation of islands of treatment;

FIG. 5 is a schematic cross-sectional side view of one embodiment of a head according to aspects of the present invention;

FIG. 6A is a cross-sectional side view one example of one embodiment of a cooling system that uses evaporative cooling;

FIG. 6B is a cross-sectional side view of another embodiment of a cooling system utilizing a cooling liquid;

FIG. 6C is a schematic of another embodiment of a cooling system utilizing a cooling liquid and having a cooling chamber;

FIG. 6D is a cross-sectional side view of an embodiment a head utilizing a cooling liquid in which the exhaust vent is separated from the port through which cooling liquid enters chamber;

FIG. 7 is a cross-sectional side view of an embodiment of a cooling system having channels;

FIG. 8 is a cross-sectional side view of another embodiment of a head utilizing evaporative cooling of a liquid;

FIG. 9 is a cross-sectional side view of an embodiment of a cooling system using a solid phase-change material according to aspects of the present invention;

FIG. 10 is a cross-sectional side view of an embodiment of a cooling system using an endothermic chemical reaction for cooling;

FIG. 11 is a cross-sectional side view of an embodiment of a device having an exhaust vent to cool a patient's skin;

FIG. 12A is a side view of one example of an embodiment of a single-element optical system appropriate for use with photocosmetic devices according to some aspects of the present invention;

FIG. 12B is a ray trace of one example of an embodiment of an optical system as illustrated in FIG. 12A;

FIG. 13A is a side view of one example of an embodiment of a two-element cylindrical optical system appropriate for use with photocosmetic devices according to some aspects of the present invention;

FIG. 13B is a ray trace of one example of an embodiment of an optical system as illustrated in FIG. 13A;

FIG. 14A is a side view of another example of a embodiment of a two-element cylindrical optical system appropriate for use with photocosmetic devices according to some aspects of the present invention;

FIG. 14B is a ray trace of one example of an embodiment of an optical system as illustrated in FIG. 14A;

FIG. 15A is a side view of another example of a embodiment of a two-element cylindrical optical system appropriate for use with photocosmetic devices according to some aspects of the present invention;

6

FIG. 15B is a ray trace of one example of an embodiment of an optical system as illustrated in FIG. 15A;

FIG. 16A is a schematic illustration of an exemplary embodiment of a head for performing photocosmetic procedures;

FIG. 16B is a schematic illustration of an exemplary embodiment of a head for performing photocosmetic procedures that also provides the capability to perform muscle stimulation during a photocosmetic procedure;

FIG. 17A is a schematic of one example of one embodiment of an apparatus according to some aspects of the invention, which optically determines contact between an optical element and the surface of a patient's skin;

FIG. 17B is a schematic of one example of one embodiment of an apparatus according to some aspects of the invention, which optically determines contact between an optical element and the surface of a patient's skin;

FIG. 17C is a schematic of one example of one embodiment of an apparatus according to some aspects of the invention, which electrically determines contact between an optical element and the surface of a patient's skin;

FIG. 18A is a cutaway side view of one embodiment of a handpiece having a motion sensor;

FIG. 18B is a schematic of one example of an embodiment of a motion sensor system;

FIG. 19 is a schematic of another example of an apparatus having an optical motion sensor;

FIG. 20 is a schematic of one example of one embodiment of a handpiece illustrating some aspects of a self-contained photocosmetic device according to the present invention;

FIG. 21 is a schematic of one example of an embodiment of a handpiece docking station for docking a self-contained photocosmetic device;

FIG. 22 is a schematic of one example of one embodiment of a handpiece having a detachable head;

FIG. 23 is a schematic illustrating a modular handpiece having one or more components suitable for user-replacement;

FIG. 24 is a schematic illustrating a modular optical assembly having one or more components suitable for user-replacement;

FIG. 25 is a schematic of one example of a photocosmetic device illustrating some aspects of the present invention;

FIG. 26A is a schematic of one example of a photocosmetic head illustrating aspects of the present invention directed to treating a curved area of skin;

FIG. 26B is a schematic of one embodiment of two transmission systems of a head to treat a curved surface;

FIG. 27 is a schematic illustrating an embodiment of some aspects of handpiece 2700 according to the present invention; and

FIG. 28 is a schematic illustration of one embodiment of a photocosmetic device according to at least some aspects of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

FIG. 1 is a schematic illustration of some basic elements of a photocosmetic device 100 according to some aspects of the present invention. Area 110 is an area of a patient's skin on which a selected photocosmetic treatment is to be performed. Area of skin 110 has a basal layer 140 in between an epidermal layer 120 and a dermal layer 130. Typically, photocosmetic treatments involve treating a target area located within epidermal layer 120 or dermal layer 130. For example, in the case of hair removal, it may be desirable to heat a bulb 150 of a hair follicle 160. Alternatively, only a portion of bulb 150

may be heated, for example, the basement membrane **152** between the papilla and the follicle.

In some embodiments of the present invention, the major sub-systems of device **100** include a handpiece **170**, a base unit **120** and cord **126** to couple handpiece **170** to base unit **120**. Base unit **120** may include a power supply **124** to power control electronics **122** and electromagnetic radiation (EMR) source **125**. Power supply **124** can be coupled to handpiece **170** via cord **126**. Cord **126** is preferably lightweight and flexible. Alternatively, as described with reference to FIG. **21** below, cord **126** may be omitted and base unit **120** may be used as a charging station for a rechargeable power source (e.g., batteries or capacitors) located in handpiece **170**. In some embodiments, base unit **120** can be completely eliminated by including a rechargeable power source and an AC adapter in the handpiece **170**.

Handpiece **170** includes a treatment head **180** (also referred to simply as a head) configured to be in contact with a patient's skin, and a handle **190** that may be grasped by an operator to move head **180** in any direction across the patient's skin. For example, head **180** may be pushed across the skin in a forward direction **105** or pulled across the skin in a backward direction **106**. Typically, during a given stroke, contact will be maintained between head **180** and the patient's skin **110** while head **180** is moved. Handpiece **170** may be mechanically driven or hand-scanned across the skin surface of area **110**. Firm contact between head **180** and skin **110** is preferable to ensure good thermal and optical contact. As described in greater detail below, in some embodiments of the present invention, head **180** and/or area of skin **110** are cooled by a passive or active cooling apparatus to prevent damage to the head and reduce the occurrence of skin damage (e.g., wounds).

In an exemplary embodiment, source **125** is located in handpiece **170**, for example in head **180**. Alternatively, source **125** is located in base unit **120** and connected to head **180** via an optical fiber **128**. Optical fiber **128** may extend through handle **190**, or may be otherwise connected to head **180** for the purpose of delivering light to the patient's skin.

In some embodiments, controls **122** receive information from head **180** over lines **132**, for example information relating to contact of head **180** with skin **110**, the rate of movement of head **180** over the patient's skin, and/or skin temperature. Controls **122** may transmit control signals to head **180** over lines **132**. Lines **132** may be part of a cable that is also connected to head **180** through handle **190** or may be otherwise connected to the head. Controls **122** may also generate outputs to control the operation of source **125** and may also receive information from the source. Controls **122** may also control a selected output device **119**, for example an audio output device (e.g., buzzer), optical output device, a sensory output device (e.g., vibrator), or other feedback control to an operator. Depending on operator preference, other commonly used output devices may also be used. In some embodiments, output device **119** is located within handpiece **170**.

FIG. **2A** is a side view of one example of an illumination system **200** according to some aspects of the present invention for use in performing a photocosmetic procedure on an area of a patient's skin **110**. FIG. **2B** is a schematic top view of an irradiated area of a patient's skin **110** taken along lines **2B-2B'** of FIG. **2A**. In an exemplary embodiment of the invention, system **200**, including an EMR source **204**, is located in the head of a photocosmetic device (e.g., head **180** in FIG. **1**) such that the EMR source is located proximate the skin surface **110**.

Depending on the treatment to be performed, source **204** may be configured to emit at a single wavelength, multiple

wavelengths, or in a wavelength band. Source **204** may be a coherent light source, for example a ruby, alexandrite or other solid state laser, gas laser, diode laser bar, or other suitable laser light source. Alternatively source **204** may be an incoherent light source for example, an LED, arc lamp, flashlamp, fluorescent lamp, halogen lamp, halide lamp or other suitable lamp.

An optical system **206**, comprised of a plurality of optical elements, includes a surface **207** for transmitting radiation from an EMR source **204** and for contacting the patient's skin **110**. Further details of optical system **206**, are given below with reference to FIG. **12-16**. The phrase "optical system" is used herein to refer to a system for transmitting any type of optical radiation suitable for performing photocosmetic procedures.

In some embodiments, source **204** has an extended dimension in the x-direction (e.g., the light source is substantially linear). One of ordinary skill would understand that a plurality of point sources may be combined to form a substantially linear source. Additionally, relatively small linear sources may be combined to form a single, longer continuous linear source, or a longer linear source having one or more discontinuities. For example, source **204** may be a diode laser bar having a 1 cm long emission line and a few micron line width; optionally source **204** may include two or three bars placed in a line along the x-direction to create a 2 cm or 3 cm long emission line.

Alternatively, linear sources may be placed adjacent to one another in the y-direction to form a source having an increased line width. System **200** may include one or more additional sources **205**, similarly or differently configured than the one or more sources **204**. In embodiments having two sources, source **204** and source **205** may emit at the same or different wavelength ranges.

In embodiments having multiple EMR sources **204**, **205**, it may be desirable to activate only selected sources for a given treatment. For example, in embodiments having sources emitting at different wavelengths, for certain applications, for example, hair removal, it may be preferable to only activate a selected one or more sources and for certain other applications, for example, acne treatment or skin rejuvenation, to activate a selected one or more other sources. While sources are discussed as emitting radiation at a wavelength, one of ordinary skill would understand that any radiation source produces light over a finite range of wavelengths, accordingly a specified wavelength may be a part of a broader range.

Radiation source **204** may be a pulsed or continuous wave (CW) source. For applications that require coverage of large areas such as hair removal, CW diode laser bars may be preferable. A method of utilizing continuous wave (CW) light sources for the treatment of various dermatologic disorders is described in U.S. Pat. No. 6,273,884 B1 entitled "Methods and Apparatus for Dermatology Treatment," to Altshuler, et al., the substance of which is hereby incorporated by reference. Some aspects of that patent teach the use of a CW light source in combination with a contact optical delivery system that can be either hand scanned or mechanically driven across the skin surface to create a precise temperature rise in the targeted biological structures (i.e., using continuous contact scanning (CCS)).

Most commercial diode laser bars exhibit lifetimes of >5000 hours, but application according to the present invention may only require 10-100 hour lifetimes. Accordingly, in some embodiments of the present invention, a source **204** may be overdriven with current to increase radiation output, thus causing the diode laser to operate at a higher temperature, and thereby sacrificing lifetime.

Diode laser bars appropriate for use with the present invention include diode laser bars emitting at wavelengths of 790-980 nm or other suitable wavelengths. Examples of sources of diode laser bars appropriate for use with aspects of the present invention include Coherent Inc. of Santa Clara, Calif., or Spectra Physics of Mountain View, Calif. The above examples of sources **204**, **205** are exemplary and it should be understood that aspects of the present invention include devices and apparatus using any appropriate EMR source currently available or yet-to-be-developed.

For some embodiments of the present invention, for example those requiring either low power or for treatment of small areas of a patient's skin, LEDs may be used as light sources **204**, **205**. LEDs are available in a wide range of emission wavelengths. Similar to the diode laser sources discussed above, multiple LEDs emitting at different wavelengths could be used in a single optical system. Typical lifetimes for LEDs are in the 50,000-hour range; similar to laser diodes, it may be possible to overdrive an LED and sacrifice lifetime to generate higher optical power. For applications that require high power density, a reflective concentrator (e.g., a parabolic reflector) could be used to decrease the spot size at the skin surface.

Broadband sources (e.g., low-power halogen lamps, arc lamps and halide lamps) are another type of light source that could be used as sources **204**, **205**. One or more optical filters **240** and **242** can be used to provide a wavelength band of interest for a given application. Multiple lamps can be combined to produce high power, and, similar to the case of LEDs, a concentrator could be used to decrease the spot size at the skin surface. In some embodiments, several different types of light sources can be incorporated into a photocosmetic device (e.g., device **100** of FIG. 1).

In some embodiments of system **200**, a beam splitter **230** splits radiation from source **204** to form a first portion of EMR and a second portion of EMR. The first portion and second portion may be filtered by filters **240** and **242** respectively. After filtering, the portions may have the same or different wavelength ranges. The functions of the first and second portions may be the same or different. For example, the function of the second portion of EMR may be to preheat the patient's skin **110** in preparation for treatment by the first portion of EMR. Alternatively, both the first portion of EMR and the second portion of EMR may provide treatment.

Referring to FIG. 2B, in some embodiments, optical system **206** (visible in FIG. 2A) is configured to form a first area of radiation **210** along a first axis **211** on the patient's skin **110**. First area of radiation **210** is formed from at least a first portion of electromagnetic radiation from source **204** (visible in FIG. 2A). In some embodiments, a second area of radiation **220** along a second axis **221** is formed on the patient's skin **110**. Second area of radiation **220** may be formed from a second portion of electromagnetic radiation from the radiation source **204**; alternatively second area of radiation **220** may be formed from light from second radiation source **205** (visible in FIG. 2A).

In some aspects of the present invention, the first axis **211** and second axes **221** are parallel; however in other embodiments, the axes **211**, **221** are not parallel. System **206** may be configured to form the first area **210** a selected distance from the second area **220**, or may be configured such that the first portion of radiation overlaps at least a part of the second portion of radiation. Optionally, system **206** is configured to form (e.g., focus or collimate) the first portion and second portion substantially as lines. Optical system **200** may be configured to produce one or more lines of light at the skin surface, each having a length of 1-300 mm and a width of

0.1-10 mm. Astigmatism of the beam can be in the range 0.01-0.5. The term "astigmatism" is herein defined to mean the ratio of beam width to the beam length. Also, optionally, system **206** may be configured to form one or more additional areas of radiation along additional axes (not shown) on the patient's skin **110**, the additional areas of radiation formed from corresponding additional portions of electromagnetic radiation from the radiation source **204** or **205**, or radiation from one or more additional radiation sources.

FIG. 3 is a side view of another example of an illumination system **300** for use in performing photocosmetic procedures, that is capable of forming two areas of radiation **311**, **316** on an area of a patient's skin **110**. In system **300**, two optical systems **310**, **315**, instead of a single optical system **206** (FIG. 2), each generate a corresponding area of radiation **311**, **316** (e.g., areas of radiation **210**, **220**). The radiation used to generate the lines may be from two sources **304**, **305** or a single divided source as described above with reference to FIG. 2.

FIG. 4 is a top view of one example of an illumination system **400** appropriate for formation of islands of treatment. System **400** includes a plurality of sources **410** (e.g., a conventional laser diode emitting a line or circular spot of illumination), each having a corresponding optical system **415** to direct light onto an area of skin. The illustrated system may be used to create a square (or arbitrarily shaped) matrix of focal spots having islands of treatment within the area of skin. The term "island" as used here is defined to mean an area of specified treatment separated from other areas of the specified treatment, such that areas between two or more areas receive radiation in an amount below that necessary to achieve the specified treatment. Islands of illumination are discussed in greater detail in U.S. Provisional patent application Ser. No. 10/033,302, filed Dec. 27, 2001, by Anderson, entitled "Method and Apparatus for EMR Treatment" the substance of which is hereby incorporated by reference.

For embodiments of photocosmetic devices according to the present invention that utilize high-power sources, management of waste heat from the sources is important for avoiding wounds and other injuries to the consumer. For example, in the case of a photocosmetic device that includes diode laser bars in the handpiece, up to 60% of the electrical energy may be dissipated in non-optical waste heat. In addition to the removal of heat to avoid wounds, removal of heat may be important to prevent the source from overheating and shortening the lifetime of the source.

FIG. 5 is a schematic cross-sectional side view of one embodiment of a head **500** according to aspects of the present invention. Head **500** includes an illumination system including an EMR source (e.g., diode laser bar **510**) and an optical system **520**. Head **500** may be located in a housing to protect the optical components and to protect the operator of a photocosmetic device; the housing is omitted to avoid obfuscation. In FIG. 5, a diode laser bar **510** operates as the source of electromagnetic radiation (e.g., source **204** in FIG. 2) and may be used to form one or more areas of radiation (e.g., **210**, **220** in FIG. 2). Diode laser bar **510** is located between positive electrode **515** and negative electrode **516**. Electrodes **515**, **516** provide electrical power to diode laser bar **510**, and may be made of any suitable material having good electrical conductivity. In some embodiments, electrodes **515**, **516** are in thermal contact with diode laser bar **510**, and have good thermal conductivity to transfer waste heat away from diode laser bar **510**. For example, electrodes **515** and **516** may be made of aluminum or copper.

Optionally, waste heat from diode laser bar **510** may be transferred via electrodes **515** and **516** to a heatsink **530**. Heat

11

sink **530** may be made of any material having good thermal conductivity to transfer waste heat away from diode bar **510**. For example, heat sink **530** may be made of aluminum or copper. Heat sink **530** can be cooled by any appropriate, known method of cooling including a stream of air. Option-
 5 ally, cooling may be enhanced by adding fins (not shown) to heat sink **530**. Alternatively, heat sink **530** may be cooled by one or more of the heat removal methods discussed below with reference to FIGS. 6-11. Also optionally, a heat spreader **522** may be located between electrodes **515**, **516** and heatsink **530**. Heat spreader **522** is thermally coupled to electrodes **515**, **516** and heat sink **530**. Heat spreader **522** may be made of any suitable material having good thermal conductivity; preferably heat spreader **522** is electrically insulative. Dia-
 10 mond and carbon fiber are two examples of materials suitable for use as heat spreaders.

In some embodiments, electrodes **515**, **516** are configured to be heat sinks to conduct waste heat away from diode laser bar **510**. Accordingly, heat sink **530** and heat spreader **522** may be omitted. In such embodiments, electrodes **515** and **516** can be made of any material exhibiting good thermal and electrical conductivity. Optionally, one or more thermal sensors **524** (e.g. a thermocouple, a thermistor) may be used to monitor a temperature indicative of a patient's skin (e.g., the temperature at the interface of an optical system **520** and electrode **516**) for use in a cooling system as described below.

Diode laser bar **510** may be secured to electrodes **515** and **516** using any method capable of maintaining good electrical contact between bar **510** and electrodes **515**, **516**. In embodi-
 30 ments where transfer of waste heat is desired, any suitable method of achieving good thermal and electrical contact may be used. In one embodiment, diode laser bar **510** is clamped between the two electrodes **515** and **516**. A spring or other suitable device may be used to clamp diode laser bar **510** firmly between electrodes **515**, **516**. In another embodiment, diode laser bar **510** may also be glued in place with thermal/ electrical conductive epoxy. In another embodiment, diode laser bar **510** is soldered in place with a low-temperature solder (In or Au/Sn solder, etc.). Automated soldering may be achieved using an indium preform placed between diode laser bar **510** and electrodes **515** and **516**, and applying heat using a die bonder to heat, compress, and then cool the solder and diode bar. Optionally, a spacer **525**, made out of a material with high thermal and low electrical conductivity such as BeO, may be included to provide electrical insulation between the electrodes **515** and **516**.

According to some aspects of the present invention, optical system **520** couples light from diode laser bar **510** to a patient's skin. Optical system **520** may be separated from diode laser bar **510** by an air gap **511**. Exemplary optical systems **520** are described in greater detail below with reference to FIGS. 12-15. In embodiments according to some aspects of the present invention, optical system **520** is configured to contact an area of a patient's skin, and the optical surface **521** is cooled to provide cooling to the patient's skin.

In some embodiments, cooling of diode laser bar **510** and optical system **520** are achieved using a single cooling system. For example, electrodes **515**, **516** may be thermally coupled to optical system **520** along dimensions A; accordingly, both diode laser bar **510** and optical system **520** may be cooled by cooling the electrodes **515**, **516** directly or via cooling of a heat sink **530** that is thermally coupled to electrodes **515**, **516**. Dimensions A are typically both between roughly 1 and 10 mm. Further detail regarding simultaneous cooling of an optical source and an optical system are given in U.S. application Ser. No. 09/473,910, filed Dec. 28, 1999, the substance of which is hereby incorporated by reference.

12

Contact cooling of the skin may be used to protect a patient's epidermis during delivery of high-fluence radiation to the skin, for example at wavelengths where melanin exhibits significant absorption. In some embodiments of head **500**, optical system **520** includes a sapphire element configured to contact a patient's skin due to its good optical transmissivity and thermal conductivity. As described above, optical system **520** may be cooled to remove heat from the sapphire element during treatment. Optionally, prior to treatment with the photocosmetic device, a lotion that is transparent at the operative wavelength(s) may be applied on the skin. Preferably, the location is thermally conductive to enhance heat removal from the skin through optical surface **521**. Preferably, the lotion also facilitates the gliding motion of the optical system **520** over the skin surface and has a refractive index match between contact surface **520** and the skin **110** to provide efficient optical coupling of the radiation into the skin.

The lotion may also be used to show which skin areas have been treated by choosing a lotion with optical properties (e.g., color or reflectance) that are altered in response to irradiation by an EMR source (e.g., laser diode **510**). For example, if the lotion is initially a given color, after irradiation it would become transparent (or a different color). The ability to distinguish treated from untreated areas is particularly important for treatments such as hair removal that are performed over a large surface area.

FIG. 5 also illustrates one embodiment of a system for cooling diode bar **510** and optical system **520** via heat sink **530**. In FIG. 5, a heat absorptive liquid flows through a thermally conductive conduit **540** that is thermally coupled to heatsink **530**. For example, in one embodiment, water is used as the liquid. Optionally water may be provided by attaching a source of cold water, such as tap water; referring to FIG. 1, water may be provided through a handle **190** having suitable plumbing. Alternatively, a closed-circuit cooling loop having a heat exchanger (not shown) to remove heat from the liquid; the heat exchanger may be located in handle **190** or base unit **120**.

Referring again to FIG. 5, conduit **540** covers at least a portion of one or more surfaces, for example, surface **542** of heat sink **530**. A single planar conduit may cover the entirety of one or more surfaces of heat sink **530**. Alternatively, a plurality of conduits, each covering a portion of a surface heatsink **530**, may be used. Alternatively, one or more conduits **540** may cover at least a portion of electrodes **515**, **516**. Since cooling may be applied to either heat sink **530**, directly to electrodes **515**, **516**, a surface of a heatsink (e.g., surface **542**), a surface of an electrode, or any other appropriate surface from which heat is to be removed shall hereinafter be referred to as a "cooling surface." While a cooling surface is illustrated as an external surface, it is to be understood that a cooling surface may be an internal surface, such as a surface exposed to a conduit through a heat sink or an electrode.

FIG. 6A is a cross-sectional side view one example of one embodiment of a cooling system **600** that uses evaporative cooling. In FIG. 6, a phase change liquid is sprayed from one or more spray jets **610** and **620** onto the cooling surface **623**. The liquid can be any suitable evaporative liquid, such that the liquid evaporates in response to heat absorbed from the cooling surface. In some embodiments, the liquid is a low-temperature boiling-point liquid, directed on the heat sink such that as the liquid boils in response to heat absorbed from the cooling surface **623**. In some embodiments, the liquid is tetrafluoroethane (boiling point -26°C .), CO_2 (boiling point -78°C .) although any other suitable liquids (e.g., freon or liquid nitrogen) could also be used. In some embodiments, the liquid is atomized by spray jets **610** and **620**.

13

Optionally, the liquid can be contained in a container **625** located in the base unit or handle. Preferably, container **625** is conveniently accessible by a user so as to be user-replaceable. A conduit **626** is used to transport the liquid to spray jets **610** and **620**. The amount of coolant flow is regulated by valve **627**, which can be controlled manually or electrically using information regarding the amount of heat present in a system (e.g., system **500** of FIG. **5**). For example, a sensor (e.g., sensor **524** in FIG. **5**) can be used to control a feedback-controlled solenoid in valve **627**. Optionally, each spray jet **610** and **620** can be a combination valve and spray jet eliminating the need for a separate valve **627**.

Optionally, the cooling surface **623** from which evaporation occurs can be textured to increase the surface area from which the liquid can be evaporated. Although triangular texturing **615** of the evaporative surface is shown, any shape suitable for increasing surface area may be implemented. The illustrated triangular texturing **615** may be a part of a linear grooves pattern, a cross-sectional view of a concentric circular groove pattern or any other appropriate groove pattern. Other texturing includes a plurality of projections (e.g., hemispheres, cylinders, or pyramids projecting from the cooling surface). Optionally, a collar **630** may be used to surround spray jets **610**, **620** and heat sink **530** to contain the spray.

A phase change liquid may also be used to cool the electronics **644** used to power and/or control a photocosmetic device. In particular, power field effect transistors (FETs) used to control the power of a photocosmetic device generate a large amount of heat. Conventionally, power FETs have been cooled using a relatively large heat sink, and a fan to remove heat. Such systems tend to be large and heavy. Cooling systems according to the present invention provide an alternative method of cooling.

Optionally, a portion of the phase change liquid conduit **626** that provides liquid to remove heat generated by the EMR source may be configured to direct a portion of the phase change liquid to the spray jet **640**. Spray jet **640** directs a portion of the phase change liquid onto a cooling surface (e.g., a surface of a heat sink **642**). A heat sensor **646** (e.g., a thermistor) may be used to control the amount of liquid projected onto cooling surface, for example, by controlling a valve **650**.

FIG. **6B** is a schematic of another embodiment of a cooling system **650** for use in a head utilizing a flowing, cooling liquid **605**. In FIG. **6B**, a high-pressure liquid is maintained in a container **655** (e.g., tetrafluoroethane under 1 to 5 atmospheres of pressure) and projected through a nozzle **660** onto a cooling surface **665**. The projected liquid **607** from nozzle **660** may be in the form of droplets or stream of liquid. In some embodiments, the liquid is projected as a stream to overcome the poor aerodynamic properties (i.e., high drag) of droplets, thus improving the heat removal properties of cooling system **650**. As described above, cooling surface **665** may be any material that is a good conductor of heat (e.g., copper or silver). Preferably, cooling surface **665** is selected to have dimensions large enough such that the liquid **655** evaporates from surface **665** rather than drips off said surface.

Projected liquid **607** from nozzle **660** is projected onto cooling surface **665** to form a flowing liquid **605** on cooling surface **665**. Nozzle **660** and cooling surface **665** may be selected such that the liquid **607** projected from the nozzle **660** is a stream of liquid the entire distance between the nozzle **660**, and upon impinging surface **665** forms a flowing liquid at cooling surface **665**. Alternatively, nozzle **660** and cooling surface **665** may be selected such that the liquid **607** projected from nozzle **660** may form a spray of droplets between nozzle **660** and cooling surface **665** before aggregat-

14

ing to form a flowing liquid at cooling surface **665**. Because liquid projected from nozzle **660** is under high pressure, the flowing liquid on the cooling surface **665** flows across the cooling surface **665** at a relatively high speed *V*.

Forming a flowing liquid **605** on cooling surface **665** may be used to provide increased heat removal from surface **665** compared to conventional cooling system in which droplets (i.e., a non-flowing liquid) are formed on cooling surface **665**. For example, the improved heat removal may result from the fact that droplets (as formed in a conventional system) are not formed in sufficient number or density to achieve and maintain a selected amount of heat removal.

FIG. **6C** is a schematic of another embodiment of a cooling system **670** for use in a head, utilizing a cooling liquid **655** and having a cooling chamber **684**. Head **670** has sidewalls **675** and a cover **680** having a port **682** for entry of the liquid **655** from nozzle **660**. Sidewall **675** and cover **680** form chamber **684**. Port **682** may also serve as an exhaust vent for evaporated cooling liquid. As indicated by arrows **686**, sidewalls **675** and cover **680** redirect the liquid **655** from cover **680** back to the cooling surfaces **665**. The sidewalls **675** are preferably selected to be thermally coupled to the cooling surface **665** such that liquid contacting the sidewalls **675** may remove heat from the cooling surface **665**. Optionally, the side walls **675** may be integrated with cooling surface **665** such that liquid contacting the sidewall **675** may remove heat. In some embodiments, it may be preferable that cover **680** have poor thermal conductivity and poor wetting characteristics for the cooling liquid to improve the likelihood that the cooling liquid will reach the cooling surface **665**. For example, in some embodiments, cover **680** is made of a polymer or organic glass. Although chamber **684** is illustrated as having sidewalls and a cover forming an angle therebetween, the chamber may be formed having a continuous curvature.

Because port **682** operates as an exhaust vent from evaporated liquid **655**, the area *S* of port **682** determines the pressure maintained within chamber **684**. In some embodiments, port **682** is selected to have a area *S* large enough to prevent back pressure that slows the speed of the liquid projected on the cooling surface **665**; however, port **682** may be selected to be small enough to allow the cover **680** to redirect a significant portion of liquid back to the cooling surface **665**, and to maintain pressure in chamber **684** to keep the liquid from evaporating too quickly. For example, port area *S* may be approximately one hundred to two hundred times as large as the area *s* of nozzle **660**. In some embodiments, the cooling liquid is selected to be a liquid that has an boiling temperature (i.e., evaporation temperature) of less than -26 degrees Celsius for pressures less than or equal to atmospheric pressure.

FIG. **6D** is a cross-sectional side view of an embodiment a laser head **690** utilizing a cooling liquid in which the exhaust vent **692** is separated from the port **694** through which cooling liquid enters chamber **696**. Chamber **696** is bounded by a cooling surface **688**, side walls **693**, and a cover **695**. Cooling surface **688** is thermally coupled to source **525**, and optical system **520** via coupling plates (described in greater detail below). A cooling liquid from nozzle **698** is projected onto textured cooling surface **688**. A portion of the cooling liquid which does not contact cooling surface **688** directly is redirected by side walls **693** and cover **695** as indicated by arrows **686**.

Optionally, cover **695** may be selected to have a resonant frequency to enhance its ability to redirect the liquid to cooling surface **688**. Also, optionally a means to reduce the kinetic energy of the liquid (e.g., propeller, not shown) may be placed between the nozzle **698** and the cooling surface **688** to cool the liquid.

15

FIG. 7 is a cross-sectional side view of an embodiment of a head 700 for contacting skin surface 110. Head 700 has channels 730 and 731 in the electrodes 515, 516). Evaporative cooling may occur along the bottom surface of electrodes 515, 516 and along the surface of channels 730, 731, thus increasing the cooling surface area of head 700. Preferably, the location of channels 730 and 731 is proximate diode laser bar 510. In one embodiment, channels 730, 731 are located along the length of the diode laser bar 510 (i.e., along direction-x). In some embodiments, channels 730, 731 are located proximate a spray jet 610 to receive spray. Channels 730 and 731 may have a rectangular cross section or any other shape appropriate to improve cooling. For example, openings 740, 742 may be flared to receive spray from spray jet 610. As an alternative to a single channel extending along the length of the diode bar 510, a series of channels may be placed on one or both sides of diode laser bar 510 along the length of the diode laser bar.

FIG. 8 is a cross-sectional side view of another embodiment of a cooling system 800. In FIG. 8, a liquid is used to remove heat from cooling surface 823 but the liquid is not used in spray form. In the illustrated exemplary embodiment, liquid flows out of reservoir 825 into a plurality of channels 832 located within cooling surface 823. The length of each of the plurality of channels 832 extends in the direction of the length of source 510. The liquid is brought into thermal contact or physical contact with cooling surface 823.

Optionally, the liquid may be a low-boiling point liquid that evaporates in response to heat absorbed from cooling surface 823. A valve 833 may be used to control the liquid evaporation; when significant cooling is desired, valve 833 is opened and a pressure less than equilibrium is applied to the liquid to facilitate evaporation. The pressure drop causes the liquid to boil, which removes heat from cooling surface 823. Although channels 832 are illustrated as extending in a direction parallel to the length of light source 510, and the channels are illustrated as having rectangular cross sections, other shape of channels 832 aligned in one or more in various directions are possible and are within the scope of the present aspect of the invention. A feedback signal can be derived from a thermal sensor (e.g., sensor 524 in FIG. 5) to control a solenoid in control valve 833.

FIG. 9 is a cross-sectional side view of another exemplary embodiment of a head 900 for contacting a skin surface 110. Head 900 has a cooling system having a cooling surface 923 that is brought into physical contact with a solid mass (also referred to as a phase change solid). At least a portion of the solid mass 834 changes phase in response to heat absorbed from cooling surface 923. The phase change may be from a solid to liquid, or a solid to a gas. In some embodiments, the solid has a melting temperature between approximately -10°C and $+30^{\circ}\text{C}$; however, in some applications, materials undergoing a phase change outside this range, particularly below this range, may be utilized.

In some embodiments, the solid mass is conveniently located within a device handpiece (e.g. handpiece 170 in FIG. 1) so as to be user replaceable. In some embodiments, the solid mass is contained in an insulating sleeve to avoid contact with user's hands, and/or to minimize melting due to exposure to room temperature. In the illustrated embodiment, temperature control can be achieved by using a manually or electrically controlled solenoid or a spring 835 to bring the solid mass in and out of contact with cooling surface 923.

In one embodiment of the phase-change cooling system, the phase-change solid is ice. In this embodiment, a user could keep one or more frozen ice blocks in his/her freezer. When the user wanted to operate the photocosmetic device, a

16

frozen ice block could be inserted in the device. In another embodiment, dry ice, which has a significantly lower melting point than water, could also be used to achieve greater cooling capacity. It is to be understood that the ice block may contain water, or water with one or more additives to treat a user's skin.

In some embodiments, commercially available organic compounds (e.g., paraffin wax-based materials, fatty acids, cross-linked polyethylenes) may be used as phase change solids. Examples of appropriate paraffin wax materials include RT25 produced by Rubitherm GmbH. RT25 has a melting point of 27.7°C . In other embodiments, greases having melting points in the $20\text{--}35^{\circ}\text{C}$. range may be used as the phase change solid. In another embodiment, Ga or a Ga alloy (e.g., Ga/In, Ga/In/Sn, or Ga/In/Sn/Zn), which is tailored to exhibit a melting point in the $15\text{--}50^{\circ}\text{C}$. range, is used as the solid mass. In a Ga/In alloy, the relatively high thermal conductivity of Ga ($40.6\text{ W/m}\cdot\text{K}$) and In ($81.6\text{ W/m}\cdot\text{K}$) would help to spread the waste heat throughout the alloy volume. A disposable phase-change cooler cartridge may be used to contain the phase-change solid; for example, the phase change solid may be used either once and then discarded or may be rechargeable (i.e., resolidified one or more times).

FIG. 10 is an embodiment of a head 1000 having a cooling system in which an endothermic chemical reactions is used for cooling. Examples of appropriate reactions are ammonium nitrate (NH_4NO_3) or ammonium chloride (NH_4Cl) introduced into water causing an endothermic reaction. For example, if 200 ml of water is mixed with 200 g of ammonium nitrate, a temperature of approximately -5°C . can be achieved, thus allowing absorption of a heat.

In FIG. 10, an endothermic reaction is contained within a reaction chamber 1050, and the reaction chamber is thermally coupled to cooling surface 1023. In some embodiments, reaction chamber 1050 could be coupled to the cooling surface 1023 via a material having a good thermal conductivity. In some embodiments, the mechanism includes a thin membrane 1051 separating a first chamber of water and another chamber of ammonium chloride. In some embodiments, membrane 1051 can be broken to initiate the reaction and the reaction chamber could be a disposable container. For example, the user could apply force to a flexible plastic reaction chamber to break a membrane and thereby produce a reservoir of cold liquid prior to turning on the device. Alternatively, the membrane may be removed or otherwise manipulated according to any known means to allow contents of the first chamber and the second chamber to interact.

FIG. 11 is a cross-sectional side view of an embodiment of a device 1100 having a conduit 1110 and an exhaust vent 1120. In FIG. 11, a liquid or gas entering exhaust vent 1120 is directed to an area of skin 1130 so as to pre or post cool the area of skin 1130 during treatment. For example, a portion of the same cooling liquid that is sprayed onto cooling surface 530 or the gas resulting from the evaporation of the liquid may enter conduit 1110 and be sprayed onto skin by vent 1120. The portion of liquid may be condensed evaporate or simply excess liquid. If, as described above, tap water was utilized for cooling (or an ice phase-change cooler as described with reference to FIG. 9), it may be possible to divert a portion of the water after the water was used to cool the cooling surface 530. In some embodiments, the pressure from a gas resulting from a phase change cooling system may be used to drive a lotion onto a patient's skin. Although the illustrated embodiment illustrates diverting a portion of the cooling liquid after it is used to cool surface 530, in some embodiments a portion

17

of the cooling liquid may be directly projected onto the skin without being used to cool the cooling surface **530**.

Optionally, one or more additives may be added to the liquid via conduit **1112** (e.g., to form a cooling lotion) prior to spraying on the skin. The additives could be stored in a cartridge (not shown) in the handpiece or base unit. In some embodiments, to achieve a "shower effect," all of the water exiting the heatsink could be exhausted onto the skin. As an alternative to using the evaporative liquid, an alternative source of gas, liquid or lotion (i.e., independent of the cooling system) could be stored in a cartridge in the handpiece or the base unit and dispensed while the handpiece is moved across the skin surface.

To avoid obfuscation, the following exemplary embodiments of optical systems for use with aspects of the present invention will be described with reference to a single electromagnetic radiation source; however as described above, one or more sources may be used to form one or more areas of radiation. In the exemplary optical systems described below, each of the surfaces having optical power has optical power along a first axis (e.g., the y-axis) and zero optical power along an axis normal to the first axis (i.e., the x-axis). That is, the lenses are cylindrical. Although the embodiments discussed below have planar or cylindrical curvatures, other refractive or diffractive optical designs are within the scope of the present invention.

FIG. **12A** is a side view of one example of an embodiment of a single element optical system **1200** appropriate for use with photocosmetic devices according to some aspects of the present invention. Optical system **1200** includes an element **1210** for transmitting light from an electromagnetic radiation source **1220** (e.g., a laser diode bar) to a patient's skin **110**. Element **1210** has an input surface **1211** and an output surface **1212** configured to contact a patient's skin surface.

Source **1220** is closely coupled to input surface **1211** of the element **1210** (e.g., 1 mm separation); close coupling enables a large fraction of light along a highly divergent fast-axis of a laser diode source to be transmitted to a patient's skin. In some embodiments, input surface **1211** has an antireflective (AR) coating.

As described above, element **1210** is made of a material substantially transparent at the operative wavelength, and preferably made of a material that is thermally conductive to remove heat from a treated skin surface (e.g., sapphire). In some embodiments, the lateral sides **1213** of element **1210** are coated with a material reflective at the operative wavelength (e.g., copper, silver or gold). Additionally, the space **1221**, between source **1220** and input surface **1211**, may be surrounded with a reflective material to increase the strength of light incident on surface **1211**.

In one embodiment, optical element **1210** is a sapphire plate (i.e., surfaces **1211** and **1212** are planar, and have no optical power). In another embodiment of optical system **1200**, optical surface **1212** has a cylindrical curvature (as shown in FIG. **12**) and is selected to converge light incident on surface **1212**. For example, in one embodiment, surface **1212** has a radius of curvature of approximately 3 mm. This system can be used to treat skin structures that require high treatment fluence. For example, the lens system of FIG. **13** can be used to target stem cells of hair follicle, sebaceous gland, infratundibulum, vascular tissue, tattoos, or collagen.

In some embodiments, lateral surfaces **1213** have a length **L** approximately in the range 5-50 mm, and a cross-sectional width (measured in the x-direction) and height (measured in the y-direction) are selected to collect light from source **1220**. For example, for a source comprised of two 1 cm diode laser

18

bars close-coupled to element **1210**, the cross-sectional width is selected to be 2 cm, and the cross-sectional height is 2 cm.

As illustrated, optical element **1210** transmits a portion of light from source **1220** directly to surface **1212** with no reflections on lateral surfaces **1213** (e.g., exemplary ray **1230**) and a portion of light from source **1220** is reflected from lateral surfaces **1213** prior to reaching surface **1212** (e.g., exemplary ray **1232**). An element, such as element **1210**, that directs a portion of light from source to surface using total internal reflection is also referred herein to as a "waveguide."

Optionally, a tip reflector **1222** may be added to redirect light scattered out of the skin back into the skin (referred to as photon recycling). For wavelengths in the near-IR, between 40% and 80% of light incident on the skin surface is scattered out of the skin; as one of ordinary skill would understand the amount of scattering is partially dependant on skin pigmentation. By redirecting light scattered out of the skin back toward the skin using tip reflector **1222**, the effective fluence provided by system **1200** can be increased by more than a factor of two. In one embodiment, tip reflectors **1222** extend a total of 3 mm from the upper lateral surface and lower lateral surface of element **1210**. In some embodiments, tip reflectors **1222** have a copper, gold or silver coating to reflect light back toward the skin.

A reflective coating may be applied to any non-transmissive surfaces of the device that are exposed to the reflected/scattered light from the skin. As one of ordinary skill in the art would understand, the location and efficacy of these surfaces is dependent on the chosen focusing geometry and placement of the light source(s). Photon recycling is discussed further in U.S. application Ser. No. 09/634,981, filed Aug. 9, 2000, entitled "Heads for Dermatology Treatment," by Altshuler, et al., and application Ser. No. 09/268,433, filed Mar. 12, 1999; the substance of both is hereby incorporated by reference. FIG. **12B** is a ray trace of one example of an embodiment of such an optical system **1200** having a source **1220** and an element **1210** as illustrated in FIG. **12A**.

FIG. **13** is a side view of one example of an embodiment of a two-element cylindrical optical system **1300** appropriate for use with photocosmetic devices according to some aspects of the present invention, in which a collimator **1310** is used in conjunction with element **1210**. In FIG. **13**, a fast-axis collimator **1310** is very closely coupled to optical source **1220** (e.g., 0.09 mm). In one embodiment, collimator **1310** has a length 1.5 mm, a planar input surface **1311**, and an output surface **1312** having a curvature of to collimate the output of collimator **1310**. Element **1210** is located 0.1 mm from output surface **1312**. Collimator **1310** produces a beam of radiation that is substantially collimated in the y-dimension at output surface **1312**. For example, collimator **1310** may be a lens module number S-TIH53 produced by Limo GmbH of Dortmund, Germany.

The collimated beam is projected onto input surface **1211** of optical element **1210**. As described above, element **1210** may be a plate or may be weakly converging (e.g., output surface **1212** may have a radius of curvature equal to 3 mm) to compensate for scattering in the skin. This system can be used to treat skin structures that require high treatment fluence. For example, the lens system of FIG. **13** can be used to target stem cells of hair follicle, sebaceous gland, infratundibulum, vascular, tattoo, or collagen. FIG. **13B** is a ray trace of one example of an embodiment of such an optical system **1300** having a source **1220** and a collimator **1310** and an element **1210** as illustrated in FIG. **13A**.

FIG. **14A** is a side view of another example of an embodiment of a two-element cylindrical optical system **1400** appropriate for use with photocosmetic devices according to some

aspects of the present invention. In optical system **1400**, the fast-axis collimator **1310** of FIG. **13** is used in conjunction with an element **1420** located 0.1 mm from surface **1312** of collimator **1310** to project light from source **1220**. Element **1420** has an input surface **1421** with a curvature of 1 mm, a planar output surface **1422**, and a length of 1 mm. System **1400** focuses light at approximately 1 mm from surface **1422** (i.e., 1 mm below the skin surface for embodiments in which surface **1422** is configured to be in contact with a patient's skin). In one embodiment, the heights of elements **1310** and **1420** are selected to be 1.5 mm. In some embodiments, lens **1420** is made of sapphire. This system can be used to target shallow skin structures that require high treatment fluence. For example, the lens system of FIG. **14** can be used to target psoriasis, sebaceous glands, hair shafts, or hair stem cells. FIG. **14B** is a ray trace of one example of an embodiment of such an optical system **1400** having a source **1220** and a collimator **1310** and an element **1420** as illustrated in FIG. **14A**.

FIG. **15A** is a side view of another example of an embodiment of a two-element cylindrical optical system **1500** appropriate for use with photocosmetic devices according to some aspects of the present invention. FIG. **15** illustrates an optical system **1500** that can be used, for example, to focus the diode light deeper than the optical system **1400** in FIG. **14**. For example, optical system **1500** may focus the diode light approximately 2 mm below the skin surface (i.e., 2 mm from surface **1522**) to target deep structures (e.g. hair bulb, deeper blood vessels, subcutaneous fat) in the skin.

System **1500** is a two-element symmetrical lens system to project light from a source **1220**. A first element **1510** is located approximately 1.4 mm from source **1220** and has a input surface **1511** that is planar and an output surface **1512** having curvature of 2.5 mm; accordingly, lens **1510** quasi-collimates the light from light source **1522**. A second lens **1520** having an input surface **1521** with a curvature of 2.5 mm and a planar output surface **1522**; accordingly lens **1522** focuses the quasi-collimated light 2 mm below the skin surface. In the illustrated embodiment, aberrations in the optical system are balanced to achieve a substantially uniform (i.e., "flat top") spatial optical intensity profile at output surface **1522**. The flat top intensity profile is substantially determined by spherical aberration in a plane transverse to the cylindrical surface **1522**. In some embodiments, lenses **1510** and **1520** are made of sapphire. FIG. **15B** is a ray trace of one example of an embodiment of such an optical system **1500** having a source **1220** and an element **1510** and an element **1520** as illustrated in FIG. **15A**.

FIG. **16A** is a schematic illustration of an exemplary embodiment of a head **1600** for performing photocosmetic procedures. Head **1600** is illustrated without a housing to facilitate description. As described above head **1600** will be moved along an area of a patient's skin, typically in direction **1602** or direction **1604**.

Head **1600** includes an optical system **206** to transmit light from an EMR source **1630**. Electrodes **1620** activate an EMR source **1630**. An electric insulator **1650** may be located between electrodes **1620** to prevent electrical contact between electrodes **1620**. Electrodes **1620** may be tapered to reduce the region of contact with a patient's skin.

FIG. **16B** is a schematic illustration of an exemplary embodiment of a head **1650** for performing photocosmetic procedures that also provides the capability to perform muscle stimulation during a photocosmetic procedure. Electrical muscle stimulation is a well-known physical therapy procedure that may enhance the efficacy of some photocos-

metic procedures. For example, electrical muscle stimulation may be used to improve the efficacy of wrinkle treatment or cellulite treatment.

In one embodiment, two electrodes **1610** for delivering the electrical stimulation are located on opposite sides of optical system **206**, on a portion of head **1600** that is designed to be in contact with a patient's skin during a photocosmetic treatment (i.e., during the delivery of EMR by system **206**). One electrode **1610** contacts an area of a patient's skin prior to optical system **206** and the other electrode **1610** contacts an area of skin after optical system **206**.

A thermally conductive electric insulator **1615** (e.g., made of BeO or diamond or other suitable material) can be used to prevent electrical contact between electrodes **1610** which provide electrical stimulation, and electrodes **1620** which activate EMR source **1630**. An electric insulator **1650** may be located between electrodes **1620** to prevent electrical contact between electrodes **1620**.

By applying a constant (or pulsed) electrical current to a patient's skin via electrodes **1610** while the handpiece is scanned across the skin surface, simultaneous muscle stimulation and electromagnetic treatment can be achieved. In some embodiments, electrodes may provide radio frequency (RF) current through skin. Alternatively, electrodes, **1610** may provide a DC current or a microwave field. In some embodiments, skin can be scanned with a RF current or microwave field to selectively heat a portion of skin to be treated with EMR radiation. Preheating skin may enable the power of the EMR source **1630** to be decreased.

FIG. **17A** is a schematic of one example of one embodiment of an apparatus according to some aspects of the invention, which determines contact between an optical element **1704** (e.g., element **1210** of FIG. **12**) and the surface of a patient's skin **1701**. To provide eye safety, in some embodiments of photocosmetic devices, a contact sensor is used to enable an electromagnetic treatment source (e.g., source **510** of FIG. **5**) to activate only when the device is in contact with a patient's skin.

In FIG. **17A**, an illumination source **1702** (e.g., diode laser or LED, separate from the treatment source) is mounted a few millimeters (e.g., 5 mm) away from element **1704**, and directed toward skin surface **1701**. Optionally, illumination source **1702** may be mounted to direct light toward skin surface **1701** through element **1704**. Source **1702** may emit radiation at the same wavelength as the treatment source **510** but preferably emits radiation at a different wavelength than the treatment source **510**. A detector **1712** is located to detect light from the illumination source that is reflected or scattered from the surface of skin **1701**. Optionally, a filter **1708** may be added to selectively transmit light from source **1702**, and to eliminate wavelengths of light corresponding to the treatment source **510** and any other extraneous wavelengths of light.

In the case of poor or no skin contact, a relatively large amount of radiation light from source **1702** would reflect or scatter from the skin surface **1701** through the optical system **1704** to detector **1712**. As illustrated in FIG. **17B**, when element **1740** is in good contact with the skin surface **1701**, scattering and absorption in the skin would attenuate light from the illumination source **1702**, and a relatively small amount of radiation would reach detector **1712**. Thus, by using an electronic means (e.g., a comparator) to measure the output of detector **1712**, and selecting an appropriate threshold, the treatment source can be configured to activate only when the output of detector **1712** is below the threshold. Optionally, source **1702** and/or detector **1712** may be located in a base unit and one or more optical fibers may be used to couple light from the handpiece to the source or detector.

In another embodiment, detector 1712 detects light from the treatment source to determine contact between element 1740 and skin surface 1701. In such a system, light from source 510 is scattered and reflected by skin surface 1701 through element 1704 to detector 1712. A radiation filter 1708 may selectively transmit this scattered and reflected radiation to detector 1712. In this embodiment, the treatment source 510 is maintained at a low-power eye-safe mode until firm contact with the skin surface 1701 is made. When there is no or poor contact between skin surface 1701 and element 1704, the output of detector 1712 is relatively low. However, when element 1704 is in good contact with the skin surface 1701, the output of detector 1701 is relatively high. Thus, treatment source 510 would be configured to fire only when the output of detector 1712 was above a threshold level.

Alternatively, instead of source 1702 and detector 1712, a standard optical contact detector that is in an optical computer system mouse can be used, for example, the optical contact system in a CordLess Mouseman™ produced by Logitech of Fremont, Calif.

As an alternative to the optical methods of determining contact, electrical methods can be used to detect contact between element 1704 and a patient's skin 1701. FIG. 17C is a cross-sectional view of handpiece having two electrical contacts located in a portion of the handpiece such that when element 1704 is in contact with skin 1701, contacts 1720 are also in contact with skin 1701. Contact can be determined by measuring resistance (or capacitance) between the contacts. Treatment source 510 would be activated when resistance (or capacitance) between contacts 1720 was within a selected range (i.e., a range typical for skin). In another embodiment, contacts 1720 may be magnetic sensors to detect contact with skin surface 1701. In another alternative embodiment, contacts may be mechanical sensors to detect contact with skin surface 1701. For example, one or more spring-loaded pins or buttons may be located such that when the element 1704 is in contact with the skin the pin or button is depressed. Multiple sensors, pins, buttons, or other mechanical sensors located around the perimeter of element 1704 could be used to help ensure that the entire surface of element 1704 face was in good contact with skin. Alternatively, contacts 1720 can be conventional load cells to determine contact with skin surface 1701. Contacts, sensors, pins, buttons, or other mechanical sensors that allow for the measurement of resistance or capacitance may be preferred to ensure that the contact is with skin and not with another surface, for example, a mirror or countertop.

In another embodiment, one or more temperature sensors are used to determine contact with skin surface 1701. A typical skin surface temperature is in the 30-32° C. range; accordingly temperature sensors could be located near a surface of the device which contacts a patient's skin, and contact could be determined to occur when the measured temperatures were within a selected range (e.g., 23-27° C.). Alternatively, contact could be determined to have occurred when the temperature sensors measured a temperature versus time slope indicative of contact. In still another embodiment, where lotion is to be dispensed on the skin (described above with reference to FIG. 11), skin contact could be detected by using a pressure sensor within spray jet 1120. The pressure sensor would measure the pressure needed to eject the lotion onto the skin. Only when the handpiece was in good contact with the skin would relatively high pressure be provided to dispense the lotion.

Contact sensor designs are described in greater detail in U.S. application Ser. No. 09/847,043, by Henry Zenzie, filed Apr. 30, 2001, entitled "Contact Detecting Method and Appa-

ratus for an Optical Radiation Handpiece," the substance of which is hereby incorporated by reference.

A handpiece is preferably scanned across a patient's skin within a specified speed range. If the handpiece is moved too slowly (typical minimum speed limit would be between 5 and 25 mm/s depending on the application), the light dosage will be too high and undesired thermal damage may result. Correspondingly, if the handpiece is moved too quickly (typically the maximum speed limit would be between 50 and 500 mm/s depending on the application), the light dosage will be too low to achieve treatment efficacy. Thus, only when the handpiece is scanned within this speed range does the handpiece emit electromagnetic radiation for treatment. An exemplary speed range for operation of a photocosmetic hand piece for hair removal/growth delay is 10-500 mm/s which corresponds to the speed ranges with which is approximately equal to the speed which a typical razors passes over their skin.

FIG. 18A is a cutaway side view of one embodiment of a handpiece 1800 having a motion sensor 1820 for determining handpiece speed. Motion sensor 1820 may be used to prevent injury to skin 1810 by providing feedback control to a treatment source (e.g., source 510 in FIG. 2), such that if the handpiece remains motionless or if the movement across the skin 1810 is too slow or too fast, the intensity of source may be decreased or increased, respectively, or the source may be turned off. Optionally, the treatment source may be disabled instead of reduced in power. In one embodiment, a wheel 1821 is positioned to make physical contact with skin 1810, such that the wheel rotates as handpiece 1800 is moved relative the skin 1810, and handpiece speed can be determined.

Handpiece 1800 may be configured to inform the operator when the handpiece speed is inside or outside of an acceptable speed range. For example, a tactile indicator (e.g., a vibrator) could be configured to vibrate the handpiece when the handpiece speed is inside or outside the desired range. Alternatively, a visual indicator 1804 (e.g., an LED) or an audio indicator (e.g., a beeper) may be used to inform the operator that the handpiece speed is inside or outside the desired range. In some embodiments, multiple indicators 1806 (e.g., LEDs having different colors, or different sound indicators) may be used to inform the operator that the handpiece speed is either too high or too low or is within the desired range.

FIG. 18B is a schematic of one example of an embodiment of a motion sensor system having at least one wheel 1821. Preferably a second wheel 1821 is added and located on an opposite side of optical system 206 to ensure that the entire skin contacting surface of the optical system 206 moves at a rate of speed within the acceptable range to provide uniform illumination on a patient's skin.

In one embodiment, each external wheel 1821 is coupled to a corresponding auxiliary internal wheel 1822 having perforations around its perimeter. A source 1830 projects light in the direction of a corresponding detector 1832 so that as a wheel 1821 rotates, the perforations of auxiliary wheel 1822 alternately transmit and block light projected by source 1830; as a result, as handpiece 1800 (visible in FIG. 18A) moves across a patient's skin, detectors 1832 produce a signal having a chain of pulses.

One of ordinary skill would understand that the speed of the handpiece across a patient's skin is proportional to the rate at which the pulses occur. A controller 1834 correlates the pulse rate to the handpiece speed. The above-described perforated auxiliary wheel design is similar to a standard computer system mouse design, for example, a mouse wheel in the 3 Bth Wheel Mouse produced by Logitech Corporation of Fremont, Calif., which is just one example of an apparatus to measure handpiece speed, many other apparatus are possible

and are within the scope of this aspect of the invention. For example, in an alternative embodiment, a simple electric motor is coupled to wheel 1821 to generate a voltage that is proportional to handpiece speed.

FIG. 19 illustrates another optical apparatus 1900 having a motion sensor for determining handpiece speed. In apparatus 1900, a light source 1902 (e.g., an infrared LED) is coupled into the transmitting fiber 1904. A light detector 1910 (e.g., an inexpensive CCD camera or a diode sensor) is coupled to the end of a receiving fiber 1906. In apparatus 1900, the ends of the transmitting fiber 1904 and receiving fiber 1906 are coupled together to form a single fiber end 1909 that is in contact with the skin 1908. A portion of light projected onto skin surface 1908 by transmitting fiber 1904 through fiber end 1908 is reflected or scattered from the skin surface 1908 and received by receiving fiber 1906 through fiber end 1909 and detected by detector 1910. Because the skin surface 1908 has a semi-periodic structure (e.g., the distances between similar tissues such as hair follicle, vessels, glands are almost constant structure) detector output is modulated at a rate dependent on the handpiece speed. One of ordinary skill would understand that handpiece speed can be calculated from the modulated detector output. Optionally, a second transmitting fiber 1905 and receiving fiber 1907 coupled together through fiber end 1911 may be added, so that the first and second transmitting fiber/receiving fiber pairs are located on opposite sides of optical system 206 to ensure that the entire skin-contacting surface of optical system 206 moves across the skin with in the acceptable range to provide uniform illumination on a patient's skin.

In system 1900, each transmitting fibers 1904, 1905 is coupled to a corresponding receiving fiber 1906, 1907; alternatively, a transmitting fiber and corresponding receiving fiber, may contact the skin at distinct, separated points (i.e., the transmitting fiber and corresponding receiving fiber are not coupled at the skin); in such an embodiment, the ends of the fibers contacting the skin may be separated by any distance at which photons scattered by tissue layers can be reliably detected. In such embodiments, the upper bound on the fiber spacing occurs when the light coupled into receiving fiber is reduced to a point at which the amount of scattered photons generates a signal that is too small to be accurately detected.

Although optical apparatus for measuring handpiece speed have been described, it should be understood that other methods of speed measurement are within the scope of this aspect of the invention. For example, electromagnetic apparatuses that measure handpiece speed by recording the time dependence of electrical (capacitance and resistance)/magnetic properties of the skin as the handpiece is moved relative to the skin. Alternatively, the frequency spectrum or amplitude of sound emitted while an object is dragged across the skin surface can be measured and the resulting information used to calculate speed because the acoustic spectrum is dependent on speed. Another alternative is to use thermal sensors to measure handpiece speed, by using two sensors separated by a distance along the direction in which the handpiece is moved along the skin (e.g., one before the optical system and one after). In such embodiments, a first sensor monitors the temperature of untreated skin, which is independent of handpiece speed, and a second sensor monitors the post-irradiation skin temperature; the slower the handpiece speed, the higher the fluence delivered to a given area of the skin, which results in a higher skin temperature measured by the second detector. Therefore, the speed can be calculated based on the temperature difference between the two sensors.

An alternative system to measure handpiece speed using thermal characteristics uses a heat source (e.g., the treatment source or another means of heating an area of skin) located a selected distance from a thermal sensor along the direction in which the handpiece is moved along the skin. In such embodiments, the handpiece speed can be determined from the temperature measured by the thermal sensor. For a low handpiece speed, the heat would have sufficient time to propagate through the skin from the heat source to the thermal sensor; however, at high speed the heat would not have time to reach the thermal sensor. Thus, a high skin temperature measured by the thermal sensor would indicate low speed whereas a low skin temperature would indicate high speed.

In an alternative embodiment of a speed sensor, an optical apparatus is used to measure handpiece speed using Doppler-shift techniques. In such a system, the wavelength of light from a probe laser is projected onto the skin and the speed is determined by shifted frequency of a reflected portion of the light.

In any of the above embodiments, a speed sensor may be used in conjunction with a contact sensor (e.g., a contact sensor as described above with reference to FIGS. 17A-17C). In one embodiment of a handpiece, both contact and speed are determined by the same component. For example, an optical-mouse-type sensor such as is used on a conventional computer optical mouse may be used to determine both contact and speed. In such a system, a CCD (or CMOS) array sensor is used to continuously image the skin surface. By tracking the speed of a particular set of skin features as described above, the handpiece speed can be measured and because the strength of the optical signal received by the array sensor increases upon contact with the skin, contact can be determined by monitoring signal strength. Additionally, an optical sensor such as a CCD or CMOS device may be used to detect and measure skin pigmentation level or skin type based on the light that is reflected back from the skin; a treatment may be varied according to pigmentation level or skin type.

In some embodiments of the present invention, a motion sensor is used in conjunction with a feedback loop or look-up table to control the radiation source output. For example, the emitted laser power can be increased in proportion to the handpiece speed according to a lookup table. In this way, a fixed skin temperature can be maintained at a selected depth (i.e., by maintaining a constant flux at the skin surface) despite the fact that a handpiece is moved at a range of handpiece speeds. The power used to achieve a given skin temperature at a specified depth is described in greater detail in U.S. patent application Ser. No. 09/634,981, which was incorporated by reference herein above. Alternatively, the post-treatment skin temperature may be monitored, and a feedback loop used to maintain substantially constant fluence at the skin surface by varying the laser output power. Skin temperature can be monitored by using either conventional thermal sensors or a non-contact mid-infrared optical sensor. The above motion sensors are exemplary; motion sensing can be achieved by other means such as sound (e.g., using Doppler information).

Although the above embodiments were discussed with reference to a system monitoring handpiece speed as moved by an operator, the handpiece could be mounted on a translation stage to move the handpiece at controlled, predetermined speed across the skin surface. In such an embodiment, the apparatus would be positioned relative to the patient to treat a selected area of skin, and the translation stage could be moved to a subsequent area as necessary.

FIG. 20 is a schematic of one example of one embodiment of a handpiece 2000 illustrating some aspects of a self-con-

tained photocosmetic device. Handpiece **2000** includes an optical source **2055**, a power supply **2047**, an optical system **2044**, a cooling system **2046**, and a speed and/or contact sensor **2048**. The device is shown in contact with an area of skin **2043**. Optical system **2044** couples light from light source **2055** into the skin treatment area **2043**.

Cooling system **2046** can be a phase-change cooler or any other appropriate cooling system. In some embodiments cooling system **2046** is in good thermal contact with the heatsink **2045** (or electrodes or other cooling surface, not shown). A power supply **2047** (e.g., battery or capacitor) supplies electrical current to optical source **2055**. Contact and/or speed sensor **2048** ensures safe and effective treatment as described herein above. Although a contact and speed sensor is illustrated as a single component, it should be understood the contact and speed sensor may be different components and there may be multiple of each type of sensor as described above. Control electronics **2049** process data from contact/speed sensors **2048** or other sensors (e.g., thermal sensors) and control optical source **2055** and cooling system **2046**. Cooling system **2046** may be cooled prior to treatment via a thermal-contact plate **2050**. Power source **2047** may be charged via electrical contact **2051**. On/off button **2052** controls the electrical power. A housing **2053** may be used to enclose, protect, or mount one or more of the above parts.

Optionally, a hair removal device **2054** may be located to remove hair prior to irradiation by light from optical source **2055** to ensure that substantially no hair extends above the skin surface. For example, hair removal device **2054** may be a blade razor (e.g., a safety razor, a cartridge razor), an electric razor, a stripping device wherein the hair adheres to a surface and is pulled out as the handpiece is moved across a user's skin (e.g., a device like the Epilady™ produced by Happy Lady, Inc.), an abrasive device that grinds the hair, or a chemical compound that dissolves the hair. A hair removal device may be made disposable such that the hair removal device is easily replaceable by a user. In the instance of coarse hair, a razor having one or a plurality of blades may be used; however in the instance of fine hair, an abrasive paper may be used. A body location having coarse hair initially may have fine hair after one or more photocosmetic treatments; accordingly, a blade razor may be used for the first few treatments and an abrasive paper may be used for subsequent treatments. In some embodiments, the abrasive paper may be simply moved across the skin with a stroke of the photocosmetic device, and in other embodiments the paper may be vibrated by a vibrating mechanism (e.g., a motor).

FIG. **21** is a schematic of one example of an embodiment of a handpiece docking station **2100** for docking a handpiece **2000**. Docking station **2100** is contained in housing **2155**. Power supply **2156** charges battery/capacitor **2047** via electrical contact **2051**. Cooling material **2046** is cooled by chiller **2157** (e.g., a Peltier element). For example, chiller **2157** may be used to recharge a cooling system, by condensing a phase change liquid or freezing a phase change solid. Heatsink **2058** dissipates heat produced by chiller **2157**. Heatsink **2058** may utilize gas, liquid, or solid (phase change) media for heat removal or may simply be fins that are cooled by exposure to room temperature. Umbilical **2159** contains wires to supply electrical power to the docking station from an electrical outlet and may further include tubing for water cooling of heatsink **2058**. A self-contained photocosmetic device, and a handpiece docking station are described in greater detail in U.S. Application No. 60/292827, filed Dec. 28, 2000, by G. Altshuler et al., entitled "Method and Apparatus for EMR Treatment," the substance of which is hereby incorporated by reference.

For some embodiments of a photocosmetic device, it is advantageous to have one or more replaceable components. For example, in some embodiments, where the handpiece will likely be dropped or otherwise abused, it may be advantageous to make one or more optical systems removable from the handpiece. In addition, to achieve a variety of treatments that each require different optical sources or optical systems (e.g., treatment of pigmented lesion removal and treatment to achieve hair removal), interchangeable optical components would permit the user to perform different applications with the same handpiece. Additionally, for systems employing light sources or power sources having a limited lifetime, replacement of the light sources at the end of useful life may be desirable.

FIG. **22** is a schematic of one example of one embodiment of a handpiece **2200** having a detachable head **2210**. Handpiece **2200** has a handle **2220** coupled to a head **2210**. Handle **2220** may be coupled to head **2210** using any known method of fastening. Preferably head **2210** includes optical components (e.g., head **1600** of FIG. **16A**) to facilitate the use of replaceable components.

FIG. **23** is a schematic of one example of an embodiment of a modular handpiece **2300** having one or more components suitable for ease of manufacturability and/or user-replacement. For example, handpiece **2300** facilitates assembly and/or replacement of a head assembly **2310** (including an optical system), a cooling assembly **2320**, and a power assembly **2330**. Preferably, modular handpiece **2300** is configured such that when assembled, head assembly **2310** contacts a mating power plug of power assembly **2330**.

FIG. **24** is a schematic illustrating an optical assembly **2400** including a source **2410** (e.g., two diode-laser-bars). The source **2410** may be incorporated into a user-replaceable disposable cartridge, including electrodes **2412**, heat sink **2430**, optical system **2420** and coupling plates **2440**. Coupling plates **2440** may be used to fasten optical system **2420**, source **2410**, and heat sink **2430**. Preferably the fastening mechanism of source **2410** is configured to automatically align source **2410** to optical system **2420**. Also preferably, coupling plates are made of a material having a good thermal conductivity (e.g., copper) to conduct heat from the optical system **2420**. To simplify alignment of source **2410** and element **2420**, source **2412** may be fixedly mounted to optical system **2420**.

In addition to replacing the source **2410** at the end of its useable lifetime, it may also be desirable to facilitate the user-replacement of light sources **2410** for use for different cosmetic treatments without having to purchase multiple handpieces. Furthermore, it may be desirable to facilitate user-replacement of light sources **2410** based on skin type, hair type and/or on the location of the area of skin to be treated (e.g., underarm, bikini, leg, face).

FIG. **25** is a schematic of one example of a photocosmetic device **2500** illustrating some aspects of the present invention. Device **2500** has a head **2580** and a handle **2590**. Head **2580** has a first optical system **2510** (e.g., optical system **310** in FIG. **3**) to form a first area of radiation (e.g., area **311** in FIG. **3**), and a second optical system **2515** (e.g., optical system **315** in FIG. **3**) to form a second area of radiation (e.g., area **316** in FIG. **3**) on a patient's skin. As described above with reference to FIG. **3**, radiation to form the first area and the second area may be from a single divided source or two sources (sources not shown). Device **2500** also includes a motion sensor system having a wheel **2521** (e.g., corresponding to wheel **1821** of FIG. **18**), and a second wheel **2522** (e.g., corresponding to wheel **1822** of FIG. **18**) located on an opposite side of optical system **2510** to ensure that the entire skin

contacting surface of the optical element **2510** moves at a rate of speed within the acceptable range to provide substantially uniform illumination on a patient's skin.

FIG. **26A** is a schematic of one example of a photocosmetic head **2600** illustrating aspects of the present invention directed to a treating curved area of skin (e.g., a jaw, back or arm). Head **2600** includes two pivoting transmission systems **2610** and **2620** for delivering electromagnetic radiation. The components of head **2600** are substantially contained within a housing **2630** and coupled to a base unit (not shown) via cord **2640**. Housing **2630** is illustrated as a transparent wire frame to facilitate description. The size of components of head **2600** may be selected according to the body part with which they are to be used, and multiple heads may be connectable to cord **2640** to permit treatment of various body parts. Alternatively, each head may have a fixed cord such that each cord can be plugged into a base unit and removed.

FIG. **26B** is a schematic of one embodiment of two transmission systems **2610** and **2620** of a head to treat a curved surface. Transmission systems **2610** and **2620** are illustrated without a housing to illustrate their relative positioning. FIG. **26B** illustrates that transmission systems pivot in at least one rotational direction to facilitate maintenance of contact with a curved area of skin. For example, transmission systems **2610** and **2620** may be mounted at an angle relative to one another (e.g., 5-30 degrees) and mounted to enable rotation about axis X and X'.

FIG. **27** is a schematic illustrating an embodiment of some aspects of handpiece **2700** according to the present invention. Handpiece **2700** includes a housing **2710** having a handle **2702** and a head **2704**. Handpiece **2700** includes a head assembly **2710** (including an optical system), a cooling assembly **2720**, and a power assembly **2730**.

FIG. **28** is a schematic illustration of one embodiment of a photocosmetic device **2800** according to at least some aspects of the present invention. Device **2800** includes a handpiece **2810**, a base unit **2820**, a cord **2826** to couple handpiece **2810** to base unit **2820**. Handpiece **2810** may be grasped by an operator to move a head **2830** across a patient's skin (not shown). Head **2830** may be any head as described herein above or any other suitable head to achieve a photocosmetic treatment, for example, any of the treatments described below.

The following is a discussion of examples of treatments that can be achieved using apparatus and methods according to the present invention; however, the treatments discussed are exemplary and are not intended to be limiting. Apparatus and methods according to the present invention are versatile and may be applied to any known or yet-to-be-developed treatments.

Exemplary treatment mechanisms include absorption of light by a chromophore within a tissue responsible for the unwanted cosmetic condition or by a chromophore in proximity to the tissue. Treatment may be achieved by limited heating of the target tissue below temperature of irreversible damage or may be achieved by heating to cause irreversible damage (e.g., denaturation). Treatment may be achieved by direct stimulation of biological response to heat, or by induction of a cascade of phenomena such that a biological response is indirectly achieved by heat. A treatment may result from a combination of any of the above mechanisms. Optionally, cooling, DC or AC (RF) electrical current, physical vibration or other physical stimulus/action may be applied to a treatment area or adjacent area to increase the efficacy of a treatment. A treatment may result from a single session, or multiple sessions may be used to achieve a desired clinical effect.

A device according to one or more aspects of the invention may operate in a variety of optical ranges. For example, electromagnetic radiation delivered to the skin may have wavelength within the range 380-1900 nm. The power of the light delivered may be in the range 0.001-300 W/cm, and exemplary scan speeds include 0.1-500 mm/sec. The desired radiation characteristics may be achieved by any suitable LEDs, lamps, and diode lasers or any other suitable light source presently available or yet-to-be developed.

Radiation-induced hair removal is a cosmetic treatment that could be performed by apparatus and methods according to aspects of the present invention. In the case of hair removal, the principal target for thermal destruction is the hair bulb and preferably the hair matrix, hair papilla or basement membrane of the bulb. For hair removal treatments, melanin located in the hair shaft and follicle is the targeted chromophore. While the bulb contains melanin and can thus be thermally treated, the basement membrane, which provides the hair growth communication pathway between the papilla within the bulb and the matrix within the hair shaft, contains the highest concentration of melanin and may be selectively targeted.

Wavelengths between 0.6 and 1.2 μm are typically used for hair removal. By proper combination of power, speed, and focusing geometry, different hair related targets (e.g., bulb, matrix, basement membrane, stem cells) can be heated to the denaturation temperature while the surrounding dermis remains undamaged. Since the targeted hair follicle and the epidermis both contain melanin, a combination of epidermal contact cooling and long pulsewidth can be used to prevent epidermal damage. A more detailed explanation of hair removal is given in co-pending provisional patent application No. 60/363,871, entitled "METHOD AND APPARATUS FOR HAIR GROWTH CONTROL," by Rox Anderson, et al. filed Mar. 12, 2002, which is hereby incorporated herein by reference.

Hair removal is often required over large areas (e.g. back and legs), and the required power is therefore correspondingly large (on the order of 20-500 W) in order to achieve short treatment times. Current generation diode bars are capable of emitting 40-60 W at 800 nm, which makes them effective for use in some embodiments of photocosmetic device according to the present invention.

Exemplary methods of hair growth management may be achieved by combining low power irradiation of hair follicles with light and physical extraction of hair shaft, and/or complete or non-complete physical extraction of the hair follicle from the body. According to some embodiments irradiation is achieved by irradiating a portion of the skin containing the hair follicle with a light source emitting at a range of wavelengths absorbed by melanin or other endogenous or exogenous chromophores in the follicle. Physical extraction can be performed by mechanical, electromechanical or other suitable techniques. This treatment can be used for either temporary hair reduction or permanent hair reduction.

A first exemplary embodiment of a method of hair growth management according to the present invention includes first physically removing hair ("depilation") and then irradiating the skin as described above. According to some embodiments, the hair removal can be adjusted to remove mostly hair shafts from hair follicles; alternatively hair removal may be down to keratinized zone. This depilation can be done by electromechanical depilation or waxing.

Phototreatment can be performed, for example, using one of the embodiments of photocosmetic device described above. According to these embodiments, light is absorbed by

melanin in hair matrix and as a result of thermal injury hair growth is decelerated or completely arrested.

Optionally, after depilation but before irradiation, a topical lotion can be applied to the skin (e.g., via the handpiece) in a treatment area to fill empty hair follicles corresponding to the removed hair. In some embodiments, the transparent lotion is selected to have a refractive index in a range suitable to provide a waveguide effect to direct the light to a region of the skin to be irradiated. Preferably the index of refraction of the lotion is higher than the index of refraction of water (i.e., approximately 1.33 depending on chemical additives of the water). In some embodiments, the index of refraction of the lotion is higher than the index of refraction of the dermis (i.e., approximately 1.4). In some embodiments, the index of refraction of the lotion is higher than the index of refraction of the inner root sheath (i.e., approximately 1.55). In embodiments where the index of refraction is greater than the index of refraction of the inner root sheath, light incident on the surface of the skin can be delivered directly to hair matrix without significant attenuation.

The effective pulse length used to irradiate the skin is given by the beam size divided by the speed of scanning of the irradiation source. For example, a 2 mm beam size moved at a scanning speed of 50-100 mm/s provides an effective pulse length of 20-60 ms. For a power density of 250 W/cm the effective fluence is 5-10 J/cm², which approximately doubles the fluence of the light delivered by a device without the use of a high index lotion.

In some embodiments, the pH of the lotion can be adjusted to decrease the denaturation threshold of matrix cells. In such embodiments, lower power is required to injure the hair matrix and thus provide hair growth management. Optionally, the lotion can be doped by molecules or ions or atoms with significant absorption of light emitted by the source. Due to increased absorption of light in hair follicle due to the lotion, a lower power irradiation source may be used to provide sufficient irradiation to heat the hair matrix.

A second exemplary embodiment of a method of hair growth management according to the present invention includes first irradiating the skin, and then physically removing hair as described above. By first irradiating the skin, attachment of the hair shaft to the follicle or the hair follicle to dermis is weakened. Consequently, mechanical or electromechanical depilation may be more easily achieved (e.g., by using a soft waxing or electromechanical epilator) and pain may be reduced.

Irradiation can weaken attachment of hair bulb to skin or subcutaneous fat; therefore it is possible to pull out a significantly higher percentage of the hair follicle from the skin compared to the depilation alone. Because the diameter of the hair bulb is close to the diameter of the outer root sheath, pulling out hair with hair bulb can permanently destroy the entire hair follicle including stem cells. Accordingly, by first irradiating and then depilating, new hair growth can be delayed or terminated.

Treatment of cellulite is another example of a cosmetic problem that may be treated by apparatus and methods according to aspects of the present invention. The formation of characteristic cellulite dimples begins with poor blood and lymph circulation, which in turn inhibits the removal of cellular waste products. For example, unremoved dead cells in the intracellular space may leak lipid over time. Connective tissue damage and subsequent nodule formation occurs due to the continuing accumulation of toxins and cellular waste products.

The following are two exemplary treatments for cellulite, both of which aim to stimulate both blood flow and fibroblast

growth. In a first exemplary treatment, localized areas of thermal damage are created using a treatment source emitting in the near-infrared spectral range (e.g., at a wavelength in the range 650-1850 nm) in combination with an optical system designed to focus 2-10 mm beneath the skin surface. In one embodiment, light having a power density of 1-100 W/cm is delivered to the skin surface, and the apparatus is operated at a speed to create a temperature of 45 degrees Celsius at a distance 5 mm below the skin. Cooling may be applied to avoid or reduce damage to the epidermis to reduce wound formation. Further details of achieving a selected temperature a selected distance below the skin is given in U.S. patent application Ser. No. 09/634,691, filed Aug. 9, 2000, the substance of which was incorporated by reference herein above. The treatment may include compression of the tissue, massage of the tissue, or multipasses over the tissue.

In a second exemplary treatment, a treatment source emitting near-infrared light (e.g., a light emitting diode emitting at a wavelength in the range 700-1300 nm) is used to focus the light a distance 2-10 mm beneath the skin surface, to elevate the dermis/subcutaneous fat temperature to a point well below the thermal damage threshold (e.g., a temperature in the range 42-60 degree Celcius). According to the second exemplary treatment, heating may increase the rate of lipolysis (i.e., fat breakdown) and cause apoptosis (i.e., programmed cell death) of fat cells. Optionally, a topical lipolytic cream may be used in combination with the second exemplary treatment; the elevated temperature profile in the dermis/subcutaneous fat may enhance cream penetration and thus increase its efficacy. Due to very long thermal relaxation time of subcutaneous fat (i.e., longer than 1 minute), multiple scanning treatments of an area can achieve the desired heating of the fat, while maintaining normal skin surface temperature. The above exemplary treatments may be used for fat metabolism activation and fat reduction.

Acne is another very common skin disorder that can be treated using apparatus and methods according to aspects of the present invention. Acne results when sebum from the sebaceous gland cannot reach the skin surface via the hair follicle, and a bacterial infection occurs within the hair follicle. Photocosmetic treatment is an alternative to traditional treatments (e.g., topical and oral medications).

The following are exemplary methods of treating acne according to the present invention. In each of the exemplary methods, the actual treated area may be relatively small (assuming treatment of facial acne), thus a low-power CW source may be used. A first possible treatment is to selectively damage the sebaceous gland to prevent sebum production. The sebaceous glands are located approximately 1 mm below the skin surface. By creating a focal spot at this depth and using a wavelength selectively absorbed by lipids (e.g., in proximity of 0.92, 1.2, and 1.7 μ m), direct thermal destruction becomes possible. For example, to cause thermal denaturation, a temperature of 45-65 degrees Celsius may be generated at approximately 1 mm below the skin surface using any of the methods described in U.S. patent application Ser. No. 09/634,691, filed Aug. 9, 2000, the substance of which was incorporated by reference herein above.

Optionally, a linear matrix of focal spots (as described above with reference to FIG. 4) may be used to create islands of damage. Although the exact position of the sebaceous glands may not be known, each treatment with a matrix of focal spots will result in a certain number of sebaceous glands being damaged. Thus, by treating the area multiple times, a significant number of sebaceous glands will be damaged.

An alternative treatment for acne involves heating a sebaceous gland to a point below the thermal denaturation tem-

perature (e.g., to a temperature 45-65 degrees Celsius) to achieve a cessation of sebum production and apoptosis (programmed cell death). Such selective treatment may take advantage of the low thermal threshold of cells responsible for sebum production relative to surrounding cells. Another alternative treatment of acne is thermal destruction of the blood supply to the sebaceous glands (e.g., by heating the blood to a temperature 60-95 degrees Celsius).

For the above treatments of acne, the sebaceous gland may be sensitized to near-infrared radiation by using compounds such as indocyanine green (ICG, absorption near 800 nm) or methylene blue (absorption near 630 nm). Alternatively, non-thermal photodynamic therapy agents such as photofrin may be used to sensitize sebaceous glands. In some embodiments, biochemical carriers such as monoclonal antibodies (MABs) may be used to selectively deliver these sensitization compounds directly to the sebaceous glands.

Although the above procedures were described as treatments for acne, because the treatments involve damage/destruction of the sebaceous glands (and therefore reduction of sebum output), the treatments may also be used to treat excessively oily skin.

Another light-based method of treating acne involves thermally destruction of the bacteria (*P. acnes*) responsible for the characteristic inflammation associated with acne. Destruction of the bacteria may be achieved by targeting porphyrins stored in *P. Acnes* Porphyrines, such as protoporphyrins, coproporphyrins, and Zn-protoporphyrins are synthesized by anaerobic bacteria as their metabolic product. Porphyrins absorb light in the visible spectral region from 400-700 nm, with strongest peak of absorption around 415 nm. By providing light in the selected wavelength ranges in sufficient intensity heat resulting from absorption causes death of the bacteria. For example, the desired effect may be achieved using a treatment source emitting at a wavelength in the range 360-700 nm using an optical system designed to focus 0.2-1 mm beneath the skin surface and a power density of 0.01-10 W/cm at the skin surface.

Yet another technique for treating acne involves using light to expand the opening of an infected hair follicle to allow unimpeded sebum outflow. In one embodiment of the technique, a lotion that preferentially accumulates in the follicle opening (e.g., lipid consistent lotion with organic non organic dye or absorption particles) is applied to the skin surface. A treatment source wavelength is matched to an absorption band of the lotion. For example, in the case of ICG doped lotion the source wavelength is 790-810 nm. By using an optical system to generate a temperature of 45-100 degrees Celsius at the infundibulum/infrainfundibulum, for example, by generating a fluence of at skin surface (e.g., 1-100 W/cm), the follicle opening can be expanded and sebum is allowed to flow out of the hair follicle and remodeling of infrainfundibulum in order to prevent comedo (i.e., blackhead) formation.

Non-ablative wrinkle treatment, which is now used as an alternative to traditional ablative CO₂ laser skin resurfacing, is another cosmetic treatment that could be performed by apparatus and methods according to aspects of the present invention. Non-ablative wrinkle treatment is achieved by simultaneously cooling the epidermis and delivering light to the upper layer of the dermis to thermally stimulate fibroblasts to generate new collagen deposition.

In wrinkle treatment, because the primary chromophore is water, wavelengths ranging from 0.8-2 μ m appropriate wavelengths of treatment radiation. Since only wrinkles on the face are typically of cosmetic concern, the treated area is typically relatively small and the required coverage rate (cm²/sec) is correspondingly low, and a relatively low-power treatment

source may be used. An optical system providing sub-surface focusing in combination with epidermal cooling may be used to achieve the desired result. Precise control of the upper-dermis temperature is important; if the temperature is too high, the induced thermal damage of the epidermis will be excessive, and if the temperature is too low, the amount of new collagen deposition will be minimal. A speed sensor (in the case of a manually scanned handpiece) or a mechanical drive may be used to precisely control the upper-dermis temperature. Alternatively, a non-contact mid-infrared thermal sensor could be used to monitor dermal temperature.

Vascular lesions (e.g. port-wine stains, rosacea, spider veins) present another cosmetic problem that could be treated by apparatus and methods according to aspects of the present invention. For treatment of vascular lesions, the target chromophore is blood in these lesions. Exemplary treatment wavelengths range from 0.4-0.6 μ m for superficial vascular lesions and 0.6-1.3 for deep vascular lesions. In the case of treatment of spider veins, the relatively large size and corresponding long thermal relaxation time of the target tissue requires a large deposition of energy over a long time period to achieve thermal destruction and to preserve the epidermis. In addition, aggressive epidermal cooling (particularly for patients with darker skin type IV-VI) can be used to prevent epidermal damage. The use of CW sources is advantageous in the treatment of lesions because, similar to hair removal, part of the targeted structure (vein wall) contains little blood and must be damaged by thermal diffusion.

Pigmented lesions such as age spots can be removed by selectively targeting the cells containing melanin in these structures. These lesions are located using an optical system focusing at a depth of 100-200 μ m below the skin surface and can be targeted with wavelengths in the 0.4-1.1 μ m range. Since the individual melanin-bearing cells are small with a short thermal relaxation time, a shallow sub-surface focus is helpful to reach the denaturation temperature.

Elimination of underarm odor is another problem that could be treated by an apparatus and methods according to aspects of the present invention. In such a treatment, a source having a wavelength selectively absorbed by the eccrine/apocrine glands is used to thermally damage the eccrine/apocrine glands. Optionally, a sensitization compound may be used to enhance damage.

Tattoo removal is another procedure that can be achieved by apparatus and methods according to aspects of the present invention. Conventional devices for tattoo removal include short pulsed (10-50 ns) Q-switched ruby, alexandrite, Nd:YAG and frequency-doubled Nd:YAG for cosmetic tattoo removal. Typically, a source wavelength is selected based on the color of the tattoo to be removed (e.g., a green laser is used to remove a red portion of a tattoo). Since the ink particles are actually incorporated into individual cells, one embodiment of a thermal treatment for tattoo removal cause the rupture of the cells, thereby releasing the ink.

Exemplary embodiments of apparatus according to aspects of the present invention for use in tattoo removal use a CW source, and an optical system selected to tightly focus radiation from a treatment source at the depth where the cells containing the ink particles reside (e.g., 150-700 μ m) to rupture the ink-containing cells. Alternatively, it may also be possible to heat the cells below their thermal denaturation point and induce apoptosis. In the case of embodiments designed to cause apoptosis, healing may be enhanced by operating the radiation source in a quasi-continuous mode while the handpiece is continuously scanned across the skin surface to create areas in which cells are damaged and areas of non-irradiated areas in between. In some embodiments, feed-

back from a speed sensor could be used to control laser emission and create equally spaced lines of damage independent of handpiece speed. To completely remove the tattoo, multiple treatments would be required.

In some conventional, relatively expensive tattoo-removal apparatus, a Q-switched frequency-doubled Nd:YAG laser emitting at 0.532 μm is combined with an (Nd:YAG) emitting at 1.064 μm , and alexandrite laser emitting at 0.755 μm ; the lasers are selectively operated to target cells containing various tattoo ink colors. Embodiments of modular apparatus according to aspects of the present invention, provide a relatively low-cost alternative to the above system. For example, an embodiment of the present invention may be configured to allow the use of optical sources emitting at distinct wavelengths or wavelength bands or a single source and optical components to modify the wavelength of the light generated by a source. In particular, to achieve a wavelength close to the 0.755 μm wavelength, a 0.808 μm diode laser bar may be used; and a Nd:YAG crystal module could be inserted into the handpiece that would be pumped by the diode laser bar to produce a wavelength close to the 1.064 μm wavelength; and to produce a wavelength close to the 0.532- μm wavelength, an SHG crystal may be used to double the frequency of a laser diode emitting 1.064 μm wavelength radiation. Alternatively, a self-frequency-doubling crystal such as Nd:YCOB may be used.

Low-intensity therapy (LIT) is another procedure that can be achieved by apparatus and methods according to aspects of the present invention. LIT may be used to for treatment of wounds, carpal-tunnel syndrome treatment, or to stimulate hair growth, or to accelerate biochemical reactions. Power densities and wavelengths (630-820 nm) typically used for LITs may be achieved using diode lasers or LED treatment sources. Optionally one or more of the above treatments may be used for veterinary LIT applications.

Elimination of or reduction of the prominence of stretch marks and scars are procedures that may be achieved using apparatus and methods according to aspects of the present invention. Similar to the case of non-ablative skin resurfacing, to achieve the above procedures, it may be possible to stimulate collagen deposition and wound healing by creating a thin thermally damaged layer in the upper dermis.

Removal of warts is another procedure that can be achieved using apparatus and methods according to aspects of the present invention. Wart removal may be achieved using a source producing light in the region of blood absorption (0.5-0.8 μm). This wavelength is selectively absorbed by hemoglobin, which appears to shut off the wart's blood supply.

Psoriasis is skin disorder that can be treated using apparatus and methods according to aspects of the present invention. Exemplary, embodiments of the present invention configured to treat psoriasis emit at wavelengths near 800 nm. Optionally, one or more sensitization agents such as photodynamic drugs or ICG/Methylene blue may be used. Treatment may be applied several times per week, and may be delivered in several different ways including islands (or lines) of treatment. Additional application of apparatus and methods according to aspects of the present invention include facilitation of delivery of topical medications and cosmetic preparations into skin.

Having thus described the inventive concepts and a number of exemplary embodiments, it will be apparent to those skilled in the art that the invention may be implemented in various ways, and that modifications and improvements will readily occur to such persons. Thus, the examples given are not intended to be limiting. The invention is limited only as required by the following claims and equivalents thereto. The

invention is limited only as required by the following claims and equivalents thereto. Also, it is to be understood that the use of the terms "including," "comprising," or "having" is meant to encompass the items listed thereafter and equivalents thereof as well as additional items before, after, or in-between the items listed.

What is claimed is:

1. A dermatologic treatment apparatus that is cordless and sufficiently compact as to be hand-held, comprising: a self-contained housing configured for gripping by a person's hand for cordless manipulation in a dermatologic treatment procedure; a light source comprising one or more diode laser bars within the housing; an electrical circuit within the housing comprising one or more batteries and an electronic control circuit for energizing the light source to produce output light pulses; a light path within the housing including an aperture through which the output light pulses are propagated out of the housing having properties that provide efficacious treatment; and a heatsink for contacting a region of an epidermis of a person undergoing treatment, having one or more thermal characteristics that serve to remove heat from the epidermis, and wherein the temperature of the heatsink is maintained below a normal skin temperature, wherein a normal skin temperature is a temperature of the skin when not being treated with the device; wherein the cordless apparatus has a total weight and volume such that it is able to be hand-held.

2. The apparatus of claim 1, wherein the heatsink comprises a sapphire output window.

3. A dermatologic hair-regrowth-inhibiting apparatus that is cordless and sufficiently compact as to be hand-held, comprising: a self-contained housing configured for gripping by a person's hand for cordless manipulation in a hair-regrowth-inhibiting procedure; a light source comprising one or more diode laser bars within the housing; a direct drive electrical circuit within the housing comprising one or more batteries for energizing the light source to produce output light pulses; a light path within the housing including an aperture through which the output light pulses are propagated out of the housing having properties sufficient for at least temporary hair-regrowth inhibition; and a heatsink for contacting a region of an epidermis of a person undergoing treatment, having one or more thermal characteristics that serve to remove heat from the epidermis, and wherein the temperature of the heatsink is maintained below a normal skin temperature, wherein a normal skin temperature is a temperature of the skin when not being treated with the device.

4. The apparatus of claim 3, wherein the heatsink comprises a sapphire output window.

5. A dermatologic hair-regrowth-inhibiting apparatus that is cordless and sufficiently compact as to be hand-held, comprising: a self-contained housing configured for gripping with a person's hand for cordless manipulation in a hair-regrowth-inhibiting procedure; a light source within the housing containing one or more diode lasers; an electrical circuit within the housing comprising one or more batteries and an electronic control circuit for energizing the light source to produce output light pulses; a light path within the housing including an aperture through which the output light pulses are propagated out of the housing; and wherein a peak power, a pulse duration of a light pulse emitted by the apparatus, an output fluence of a light pulse emitted by the apparatus and a majority of the energy of a light pulse emitted by the apparatus are sufficient such that the light pulses propagated out of the housing inhibit hair-regrowth; and a heatsink for contacting a region of an epidermis of a person undergoing treatment, having one or more thermal characteristics that serve to remove heat from the epidermis, and wherein the temperature

35

of the heatsink is maintained below a normal skin temperature, wherein a normal skin temperature is an average temperature of the skin when not being treated with the device.

6. The apparatus of claim 5, wherein the heatsink comprises a sapphire output window.

7. A dermatologic hair-regrowth-inhibiting apparatus that is cordless and sufficiently compact as to be hand-held, comprising: a self-contained housing configured for gripping by a person's hand for cordless manipulation in a hair-regrowth-inhibiting procedure; a light source within the housing comprising one or more diode lasers a direct drive electrical circuit within the housing comprising one or more batteries for energizing the light source to produce output light pulses; a light path within the housing including an aperture through which the output light pulses are propagated out of the housing; and wherein a peak power, a pulse duration of a light pulse emitted by the apparatus, an output fluence of a light pulse emitted by the apparatus and a majority of the energy of a light pulse emitted by the apparatus are sufficient such that the light pulses propagated out of the housing inhibit hair-regrowth; and wherein the cordless apparatus has a total weight and volume such that it is able to be hand-held; light pulses are emitted at a pulse repetition frequency sufficient to produce lines of light at the skin surface to inhibit hair-regrowth; and a heatsink for contacting a region of an epidermis of a person undergoing treatment, having one or more thermal characteristics that serve to remove heat from the epidermis, and wherein the temperature of the heatsink is maintained below a normal skin temperature, wherein a normal skin temperature is a temperature of the skin when not being treated with the device.

8. The apparatus of claim 7, wherein the heatsink comprises a sapphire output window.

9. A dermatologic treatment apparatus that is cordless and able to be hand-held, comprising: a self-contained housing configured for grasping by a person's hand for cordless manipulation in a dermatologic treatment procedure; a light source comprising one to three diode laser bars within the housing; an electrical power source within the housing comprising one or more batteries and an electronic control for energizing the light source to produce output light pulses; a light path within the housing including an aperture through which the output light pulses are propagated out of the housing having properties that provide efficacious treatment; and a heatsink for contacting and cooling a region of an epidermis of a person undergoing treatment, by removing heat from the epidermis; wherein the cordless apparatus is of a size such that it may be hand-held.

10. The apparatus of claim 9, wherein the heatsink comprises a sapphire output window.

11. A dermatologic hair-growth-reduction apparatus that is cordless and able to be hand-held, comprising: a self-contained housing configured for grasping by a person's hand for cordless manipulation in a hair-growth-reduction procedure; a light source comprising one to three diode laser bars within the housing; an electrical power source within the housing comprising one or more batteries for energizing the light source to produce output light pulses; a light path within the housing including an aperture through which the output light pulses are propagated out of the housing to a patient's skin having properties sufficient for at least temporary hair-growth

36

reduction; and a heatsink for contacting a region of skin of a person undergoing treatment, and removing heat from the skin, and wherein the temperature of the heatsink is maintained below a normal skin temperature, wherein a normal skin temperature is a temperature of the skin when not being treated with the device.

12. The apparatus of claim 11, wherein the heatsink comprises a sapphire output window.

13. A dermatologic hair-growth-reducing apparatus that is cordless and able to be hand-held, comprising: a self-contained housing configured for grasping with a person's hand for cordless manipulation in a hair-growth-reducing procedure; a light source within the housing containing one to three diode lasers; an electrical power source within the housing comprising one or more batteries and a control for energizing the light source to produce output light pulses; a light path within the housing including an aperture through which the output light pulses are propagated out of the housing to the patient's skin surface; and wherein a peak power of a light pulse emitted by the apparatus is between 0.001-300 W/cm²; a pulse duration of a light pulse emitted by the apparatus is between 20 and 60 milliseconds; an output fluence of a light pulse emitted by the apparatus is between 5 J/cm² and 10 J/cm²; a majority of the energy of a light pulse emitted by the apparatus is contained within a spectral band of 790 nm to 900 nm; and a heatsink for contacting a region of skin of a person undergoing treatment, and removing heat from the skin, and wherein the temperature of the heatsink is maintained below a normal skin temperature, wherein a normal skin temperature is a temperature of the skin when not being treated with the device.

14. The apparatus of claim 13, wherein the heatsink comprises a sapphire output window.

15. A dermatologic hair-growth-reduction apparatus that is cordless and able to be hand-held, comprising: a self-contained housing configured for grasping by a person's hand for cordless manipulation in a hair-regrowth-inhibiting procedure; a light source within the housing comprising one to three diode laser bars an electrical power source within the housing comprising one or more batteries for energizing the light source to produce output light pulses; a light path within the housing including an aperture through which the output light pulses are propagated out of the housing; and wherein a peak power of a light pulse emitted by the apparatus is between 0.001-300 W/cm²; a pulse duration of a light pulse emitted by the apparatus is between 20-60 milliseconds; an output fluence of a light pulse emitted by the apparatus is between 5 J/cm² and 10 J/cm²; a majority of the energy of a light pulse emitted by the apparatus is contained within a spectral band of 790 nm to 900 nm; the cordless apparatus having a size such that it may be hand-held; wherein the lines of light emitted to the skin surface have a length of 1-300 mm and a width of 0.1-10 mm; and a heatsink for contacting a region of skin of a person undergoing treatment, and removing heat from the skin, and wherein the temperature of the heatsink is maintained below a normal skin temperature, wherein a normal skin temperature is a temperature of the skin when not being treated with the device.

16. The apparatus of claim 15, wherein the heatsink comprises a sapphire output window.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 8,182,473 B2
APPLICATION NO. : 11/603712
DATED : May 22, 2012
INVENTOR(S) : Gregory B. Altshuler et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title Page in the Related U.S. Application Data:


Item (63) should read:

Continuation of application No. 10/154,756, filed on May 23, 2002, now Pat. No. 7,204,832, and a continuation-in-part of application No. 10/052,474, filed on Jan. 18, 2002, now Pat. No. 6,663,620, which is a continuation of application No. 09/473,910, filed on Dec. 28, 1999, now Pat. No. 6,517,532, ~~and a continuation in part of application No. 09/078,055, filed on May 13, 1998, now Pat. No. 6,273,884, and said application No. 10/154,756, filed May 23, 2002, now Patent No. 7,204,832, which is a continuation-in-part of application No. 09/268,433 filed on Mar. 12, 1999, now Pat No. 6,508,813, which is a continuation in part of application No. 08/759,036, filed on Dec. 2, 1996, now Pat No. 6,015,404, and a continuation in part of application No. 08/759,136 filed on Dec. 2, 1996, now abandoned, which is a continuation in part of application No. 09/634,981, filed on Aug. 9, 2000, now Pat. No. 6,511,475, and which is a continuation-in-part of application No. 09/847,043, filed on Apr. 30, 2001, now Pat. No. 6,653,618.~~

Item (60) should read:

Provisional application No. 60/363,798, filed on Mar. 12, 2002, provisional application No. 60/115,447, filed on Jan. 8, 1999, provisional application No. 60/164,492, filed on Nov. 9, 1999, ~~provisional application No. 60/046,542, filed on May 15, 1997, provisional application No. 60/077,794, filed on Jan. 8, 1999, provisional application No. 60/077,726, filed on Mar. 12, 1998,~~ provisional application No. 60/200,431, filed on Apr. 28, 2000, provisional application No. 60/292,827, filed on May 23, 2001, provisional application No. 60/363,871, filed on Mar. 12, 2002.

Signed and Sealed this
Twenty-fourth Day of July, 2012



David J. Kappos
Director of the United States Patent and Trademark Office