



US008647308B2

(12) **United States Patent**
Solomon et al.

(10) **Patent No.:** **US 8,647,308 B2**
(45) **Date of Patent:** **Feb. 11, 2014**

(54) **DISINFECTING CAPS FOR MEDICAL MALE LUER CONNECTORS**

(71) Applicants: **Catheter Connections**, Salt Lake City, UT (US); **The University of Utah Research Foundation**, Salt Lake City, UT (US)

(72) Inventors: **Donald D. Solomon**, North Salt Lake, UT (US); **F. Mark Ferguson**, Salt Lake City, UT (US); **Robert Hitchcock**, Sandy, UT (US); **Steven Bandis**, South Jordan, UT (US); **James V. Mercer**, West Jordan, UT (US); **Michael W. Howlett**, Salt Lake City, UT (US)

(73) Assignee: **Catheter Connections, Inc.**, Salt Lake City, UT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/664,641**

(22) Filed: **Oct. 31, 2012**

(65) **Prior Publication Data**

US 2013/0072908 A1 Mar. 21, 2013

Related U.S. Application Data

(63) Continuation of application No. 13/281,404, filed on Oct. 25, 2011, now Pat. No. 8,328,767, which is a continuation of application No. 12/917,336, filed on Nov. 1, 2010, now Pat. No. 8,523,830, and a continuation-in-part of application No. 12/610,141, filed on Oct. 30, 2009, now Pat. No. 8,172,825, and a continuation-in-part of application No. 12/610,033, filed on Oct. 30, 2009, and a continuation-in-part of application No. 12/171,997, filed on Jul. 11, 2008, now Pat. No. 8,197,749, and a continuation-in-part of application No. 12/164,310, filed on Jun. 30, 2008,

(Continued)

(51) **Int. Cl.**
A61M 5/32 (2006.01)

(52) **U.S. Cl.**
USPC **604/199**; 604/263; 15/104.04; 134/6; 422/28; 422/292

(58) **Field of Classification Search**
USPC 604/192, 198, 263, 265, 533-539, 905, 604/199; 15/97.1, 104.04; 134/6; 422/28, 422/292, 294, 300-302; 206/205, 206, 207, 206/210

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,351,804 A 6/1944 Blum B65D 3/22
3,446,596 A 5/1969 Salivar et al. C12Q 1/10

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 462 355 A1 12/1991 A61M 39/00
WO WO 2006/099306 9/2006 A61M 25/16

(Continued)

OTHER PUBLICATIONS

U.S. Appl. No. 13/281,413, filed Oct. 25, 2011, Howlett.

(Continued)


Primary Examiner — Kami A Bosworth

(74) *Attorney, Agent, or Firm* — Sunstein Kann Murphy & Timbers LLP

(57) **ABSTRACT**

Disclosed herein are disinfecting caps that can be used to cover and disinfect a male luer post of a medical connector. The caps are configured to engage threads of the connector. The caps contain a disinfecting agent within an absorbent pad disposed in a chamber of the cap.

7 Claims, 58 Drawing Sheets



Related U.S. Application Data

now Pat. No. 8,177,761, said application No. 12/610,141 is a continuation-in-part of application No. 12/014,388, filed on Jan. 15, 2008, now abandoned, said application No. 12/610,033 is a continuation-in-part of application No. 12/014,388, filed on Jan. 15, 2008, now abandoned, said application No. 12/171,997 is a continuation-in-part of application No. 12/014,388, filed on Jan. 15, 2008, now abandoned, said application No. 12/164,310 is a continuation-in-part of application No. 12/014,388, filed on Jan. 15, 2008, now abandoned.

- (60) Provisional application No. 60/880,541, filed on Jan. 16, 2007.

(56) **References Cited**

U.S. PATENT DOCUMENTS

- 3,987,930 A 10/1976 Fuson A61M 39/20
 4,121,727 A * 10/1978 Robbins et al. 215/211
 4,232,677 A 11/1980 Leibensohn A61F 5/441
 4,324,239 A 4/1982 Gordon et al. A61M 39/26
 4,340,052 A 7/1982 Dennehey et al. A61M 3/00
 4,346,703 A 8/1982 Dennehey et al. A61J 1/100
 4,354,490 A 10/1982 Rogers A61M 1/28
 4,369,781 A 1/1983 Gilson et al. A61M 5/34
 4,402,691 A 9/1983 Rosenthal et al. A61M 39/16
 4,432,764 A 2/1984 Lopez A61M 1/28
 4,432,766 A 2/1984 Bellotti et al. A61M 39/16
 4,440,207 A 4/1984 Genatempo et al. A61L 31/16
 4,450,624 A 5/1984 Collier H01R 43/20
 4,624,664 A 11/1986 Peluso et al. 604/256
 4,671,306 A 6/1987 Spector I32/73
 4,778,447 A 10/1988 Velde et al. A61M 39/10
 4,838,875 A 6/1989 Somor A61J 1/05
 5,184,742 A 2/1993 DeCaprio et al. 215/356
 5,205,821 A 4/1993 Kruger et al. A61M 39/00
 5,242,425 A 9/1993 White et al. A61M 5/158
 5,466,219 A 11/1995 Lynn et al. A61B 5/15
 5,554,135 A 9/1996 Menyhay A61M 39/16
 5,694,978 A 12/1997 Heilmann et al. F16L 57/00
 5,792,120 A 8/1998 Menyhay A61M 39/16
 5,894,015 A 4/1999 Rechten A61M 5/00
 5,951,519 A 9/1999 Utterberg A61M 39/02
 5,954,957 A 9/1999 Chin-Loy et al. 210/232
 6,045,539 A 4/2000 Menyhay A61M 29/16
 6,171,287 B1 1/2001 Lynn et al. A61M 5/168
 6,932,795 B2 8/2005 Lopez et al. A61M 39/26
 6,960,191 B2 11/2005 Howlett et al. A61M 25/06
 7,040,598 B2 5/2006 Raybuck F16L 367/28
 7,198,611 B2 4/2007 Connell et al. A61M 1/00
 D547,446 S 7/2007 Racz et al.
 D550,355 S 9/2007 Racz et al.
 7,316,669 B2 1/2008 Ranalletta A61M 5/32
 D607,325 S 1/2010 Rogers et al.
 7,762,524 B2 7/2010 Cawthon et al. F16L 37/28
 7,780,794 B2 8/2010 Rogers et al. B08B 17/04
 7,922,701 B2 4/2011 Buchman 604/256
 7,985,302 B2 7/2011 Rogers et al. B08B 3/04
 2002/0093192 A1 7/2002 Matkovich A61J 1/05
 2003/0140441 A1 7/2003 Stafford A47L 13/12
 2003/0153865 A1 8/2003 Connell et al. A61M 1/16
 2003/0198502 A1 10/2003 Maloney et al. A47L 9/28
 2004/0201216 A1 10/2004 Segal et al. A61M 39/10
 2004/0214316 A1 10/2004 O'Connell C12M 1/30
 2004/0258560 A1 12/2004 Lake, Jr. et al. 422/28
 2005/0033267 A1 2/2005 Decaria A61J 15/00
 2005/0124970 A1 6/2005 Kunin et al. A61M 39/10
 2005/0147524 A1 7/2005 Bousquet 422/28
 2005/0183971 A1 * 8/2005 Petricca 206/210
 2005/0203460 A1 9/2005 Kim A61M 39/20
 2005/0245883 A1 11/2005 Baldwin A61M 39/22

- 2005/0266714 A1 12/2005 Higgins et al. H01R 13/52
 2006/0030827 A1 2/2006 Raulerson et al. A61M 25/00
 2007/0112333 A1 5/2007 Hoang et al. A61M 39/10
 2007/0202177 A1 8/2007 Hoang A61K 9/14
 2007/0287989 A1 12/2007 Crawford A61M 31/00
 2007/0293818 A1 12/2007 Stout et al. A61M 31/00
 2007/0293822 A1 12/2007 Crawford et al. A61M 5/00
 2008/0021381 A1 1/2008 Lurvey et al. A61M 25/00
 2008/0027399 A1 1/2008 Harding et al. A61M 25/00
 2008/0038167 A1 2/2008 Lynn A61L 2/18
 2008/0039803 A1 2/2008 Lynn A61M 39/16
 2008/0086091 A1 4/2008 Anderson et al. A61M 5/31
 2008/0095680 A1 4/2008 Steffens et al. A61L 2/18
 2008/0105704 A1 5/2008 Pritchard B67D 7/16
 2008/0107564 A1 5/2008 Sternberg et al. G01N 21/78
 2008/0132880 A1 6/2008 Buchman A61M 39/02
 2008/0147047 A1 6/2008 Davis et al. A61M 39/16
 2008/0177250 A1 7/2008 Howlett et al. A61M 39/16
 2008/0235888 A1 10/2008 Vaillancourt et al. B08B 9/00
 2009/0008393 A1 1/2009 Howlett et al. B65D 43/03
 2009/0062766 A1 3/2009 Howlett et al. A61B 19/02
 2009/0205151 A1 8/2009 Fisher et al. B08B 1/00
 2010/0047123 A1 2/2010 Solomon et al. A61L 2/18
 2010/0049170 A1 2/2010 Solomon et al.
 2010/0242993 A1 9/2010 Hoang et al. B08B 7/00
 2010/0306938 A1 12/2010 Rogers et al. B08B 1/00
 2010/0313366 A1 12/2010 Rogers et al. B08B 1/00
 2011/0044850 A1 2/2011 Solomon et al. A61L 2/16
 2011/0213341 A1 9/2011 Solomon et al. A61L 2/00
 2011/0217212 A1 9/2011 Solomon et al. A61L 2/18

FOREIGN PATENT DOCUMENTS

- WO WO 2008/089196 7/2008 A61M 39/16
 WO WO 2008/100950 8/2008 A61B 19/00
 WO WO 2010/002808 1/2010 F16L 21/00
 WO WO 2010/141508 12/2010 A61L 2/00
 WO WO 2011/053924 5/2011 A61M 5/14
 WO WO 2011/066565 6/2011 A61M 39/00
 WO WO 2011/066586 6/2011 A61M 39/20

OTHER PUBLICATIONS

- Unomedical Medical Products catalog, circa Jan. 2006, available at www.unomedical.net/au/section10/localssl/...%5Cpdf%5Cmedical.
 The Curo Port Protector. Simply Changing Infection Control, *Ivera Medical Corporation*, 2 pages, available at www.iveramed.com/curo-port-protector.com.
 Tego Connector product brochure, circa Nov. 2008, 2 pages, available at www.icumed.com/Docs-Tego/M1148%20TEGO%20Folder%20Brochure%20Rev.3.
 Ron Stoker, One Less Problem, *Managing Infection Control*, Jun. 2008, 4 pages, available at www.baxa.com/resources/docs/onelesspropaper.com.
 Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority issued Aug. 1, 2008 in International Application No. PCT/US2008/051087.
 Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority issued Jan. 6, 2011 in International Application No. PCT/US2010/054995.
 Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority issued Jan. 26, 2011 in International Application No. PCT/US2010/0548404.
 Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority issued Feb. 7, 2011 in International Application No. PCT/US2010/0548453.
 International Search Report with Written Opinion for International Application No. PCT/US2009/049094.
 International Search Report and Written Opinion for PCT/US2009/049094 dated Aug. 31, 2009.
 Maki, Dennis G., In Vitro Studies of a Novel Antimicrobial Luer-Activated Needleless Connector for Prevention of Catheter-Related Bloodstream Infection, *Clinical Infection Diseases*, Jun. 15, 2010, vol. 50, Issue 12, pp. 1580-1587.
 Hospira Male/Female Sterile Cap product packaging insert and brochure, circa Aug. 2004, 1 page.

(56)

References Cited**OTHER PUBLICATIONS**

Curos Port Protector web page from <http://www.iveramed.com> dated Jul. 11, 2008, 1 page.

Curos Port Protector product brochure, Jul. 11, 2008, www.iveramed.com, 1 page.

Curos Port Protector product brochure, circa Nov. 2008, 2 pages available at www.iveramed.com/docs/curos%20brochure-final.

Braun product catalog, circa Aug. 2008, 2 pages.

BD Q-Syte Luer Access Split Septum product brochure, circa Nov. 2008, 4 pages, available at www.bd.com/infusion/pdfs/D16333.

Baxa Corporation Patlock catalog page, 3 pages, copyright 2009, available at www.baxa.com/searchresults/productdetail?id=6452BFB9-3048-7B87-701697FB93902BA6.

Baxa Corporation Padlock Set Saver Specifications for Instructions and Use, copyright 2007, 2 pages, available at www.baxa.com/resources/docs/5300103905C.

Baxa Corporation Padlock product brochure, copyright 2007, 1 page, available at www.baxa.com/resources/docs/5300104405A.

Baxa Corporation Padlock Microbial Testing Paper, copyright 2007, 4 pages, available at www.baxa.com/resources/docs/technicalpapers.padlockmicrobialchallengepaper.

Baxa Corporation Launches PadLock Set Saver for IV Safety press release, Oct. 10, 2007, 2 pages, available at www.pr.com/press-release/55432.

Buchman, et al., A New Central Venous Catheter Cap: Decreased Microbial Growth and Risk for Catheter-Related Bloodstream Infection, *The Journal of Vascular Access*, 2009, 10: pp. 11-21.

International Searching Authority, International Search Report—International Application No. PCT/US2009/049094, dated Aug. 31, 2009, together with the Written Opinion of the International Searching Authority, 9 pages.

Ivera Medical Corporation, Curos™ Port Protector, web page from <http://www.iveramed.com>, dated Jul. 11, 2008, 1 page.

Ivera Medical Corporation, The Curos™ Port Protector. Simply Changing Infection Control Practice, Part No. 3005-1, IMC 005, Nov. 2008, 2 pages.

Ivera Medical Corporation, The Curos® Port Protector. Simply Changing Infection Control. <http://www.iveramed.com/curos-port-protector>, May 13, 2010, 2 pages.

Extended European Search Report, dated Mar. 6, 2012, Application No./Patent No. 08727689.5-2319/2125074; PCTUS2008051087, 7 pages.

* cited by examiner




FIG. 1




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 7B




FIG. 6




FIG. 7A




FIG. 8B




FIG. 8A




FIG. 9C




FIG. 9B




FIG. 9A




FIG. 9E




FIG. 9D






FIG. 10

FIG. 11



13
17
G
E

12
G
L




FIG. 15




FIG. 14




FIG. 17





FIG. 16






FIG. 19




FIG. 21




FIG. 20




FIG. 23

FIG. 22




FIG. 24




FIG. 25




FIG. 26




FIG. 28

FIG. 27





FIG. 29



SG 74




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36





FIG. 37



384




FIG. 39




FIG. 40





FIG. 41



42
G
L




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51

FIG. 52




FIG. 53




FIG. 54




FIG. 55




FIG. 56




FIG. 57






FIG. 58





66
G²
L







FIG. 61






FIG. 63A




FIG. 63B




FIG. 63C




FIG. 64




FIG. 65A




FIG. 65B





FIG. 66A







FIG. 66C







FIG. 67






FIG. 69

DISINFECTING CAPS FOR MEDICAL MALE LUER CONNECTORS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/281,404, filed Oct. 25, 2011, and a continuation of U.S. patent application Ser. No. 12/917,336, filed Nov. 1, 2010. Application Ser. No. 13/281,404 is a continuation-in-part of U.S. patent application Ser. No. 12/610,141, filed Oct. 30, 2009, which issued as U.S. Pat. No. 8,172,825 on May 8, 2012, U.S. patent application Ser. No. 12/610,033, filed Oct. 30, 2009, U.S. patent application Ser. No. 12/171,997, filed Jul. 11, 2008, which issued as U.S. Pat. No. 8,197,749 on Jun. 6, 2012, and U.S. patent application Ser. No. 12/164,310, filed Jun. 30, 2008, which issued as U.S. Pat. No. 8,177,761 on May 15, 2012, all of which are continuations-in-part of U.S. patent application Ser. No. 12/014,388, filed Jan. 15, 2008, which claims the benefit of U.S. Provisional Application No. 60/880,541, filed Jan. 16, 2007. All of these applications are incorporated herein by reference.

BACKGROUND

1. Technical Field

The present disclosure generally relates to caps for medical connectors and more specifically relates to caps that can be used to protect the sterility of unconnected medical connectors, such as connectors that may be used for fluid flow or for fluid delivery systems. Some embodiments are directed to caps for medical connectors that include elongated male portions.

2. Related Art

Bloodstream infections, such as may be caused by microorganisms that enter patients via intravascular catheters, are a significant cause of illness and excess medical costs. A substantial number of such infections occur in U.S. intensive care units annually. Additionally, a significant fraction of these infections result in death.

Guidelines from the Centers for Disease Control and Prevention describe various ways to limit bloodstream infections in hospital, outpatient, and home care settings. The guidelines address issues such as hand hygiene, catheter site care, and admixture preparation. However, despite these guidelines, such infections continue to plague healthcare systems at relatively unchanged rates.

Impregnating catheters with various antimicrobial agents is one approach for reducing these infections. Impregnated catheters, however, provide less than satisfactory results. Additionally, some microbes have developed resistance to the various antimicrobial agents used in the catheters. Other systems and approaches have also been developed, but these likewise suffer from a variety of limitations and drawbacks.

SUMMARY

Disclosed herein are disinfecting caps, and related systems and methods, that can reduce the threat of microorganisms entering the bloodstream of a patient via fluid flow or fluid delivery systems, such as, for example, needleless injection sites and/or fluid transfer devices having an elongated male portion or male protrusion, such as, for example, a male luer. In some embodiments, a cap is configured to couple with and disinfect a medical connector having a male protrusion. In further embodiments, the cap can include an antiseptic, and can be configured to create a seal with the male protrusion so

as prevent antiseptic from entering a lumen of the male protrusion. In some embodiments, the antiseptic may be contained within a pad prior to the coupling of the cap to the medical connector, and the act of coupling the cap to the medical connector can force at least a portion of the antiseptic from the pad and into contact with the male protrusion. Other or further features of various embodiments are also disclosed below and are set forth in the appended claims, which are hereby incorporated by reference in this summary section.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side elevation view of an embodiment of an assembly that includes an attached pair of medical caps;

FIG. 1A is an end perspective view of the caps of FIG. 1;

FIG. 1B is an end perspective view of the caps of FIG. 1 shown from a vantage point opposite of that shown in FIG. 1A;

FIG. 2 is an exploded side elevation view of the medical caps of FIG. 1;

FIG. 3 is a perspective view of a female medical cap from the assembly of FIG. 1, which shows internal threads;

FIG. 4 is a perspective view of the female cap of FIG. 3 and an associated medical connector about to be connected therewith;

FIG. 5 is a perspective view of male cap from the assembly of FIG. 1 and a luer lock connector to which the male cap may be affixed;

FIG. 6 is a side elevation view of an attached pair of medical caps, similar to the caps of FIG. 1, but having an embodiment of a sealing mechanism at connecting edges of the caps;

FIG. 7 is an exploded side elevation view of the cap assembly of FIG. 6;

FIG. 7A is a perspective view of one of the caps of FIG. 7 with a sealing mechanism disposed thereon;

FIG. 7B is a perspective view of the other cap of FIG. 7 with a sealing mechanism disposed thereon;

FIG. 8A is a side elevation view of the interconnected cap assembly of FIG. 6 with an embodiment of a seal partially displaced about connecting edges of the cap assembly;

FIG. 8B is a side elevation view of the interconnected cap assembly of FIG. 8A with the seal fully in place;

FIG. 9A is a side elevation view of the cap portion of FIG. 3 and an absorbent pad positioned above the cap portion;

FIG. 9B is a side elevation view of the cap portion and pad of FIG. 9A schematically showing the absorbent pad disposed within the cap portion;

FIG. 9C is a side elevation view of the cap portion and pad of FIG. 9B with a quantity of antiseptic material being dispensed into the cap and pad;

FIG. 9D is a perspective view of the cap portion containing the pad of FIGS. 9B and 9C affixed to an associated complementary cap;

FIG. 9E is a side elevation view of the cap portion of FIG. 5 and an absorbent pad disposed therein;

FIG. 10 is a cross-sectional perspective view of another embodiment of an assembly that includes a pair of caps, which are attached to each other via a threaded interface;

FIG. 11 is an exploded perspective view of the assembly of FIG. 10 showing the caps detached from each other;

FIG. 12 is a cross-sectional perspective view of another embodiment of an assembly that includes a pair of caps, which are attached to each other via a snapping interface;

FIG. 13 is a cross-sectional perspective view of another embodiment of an assembly that includes a pair of caps, which are attached to each other via a friction-fit interface;

3

FIG. 14 is a cross-sectional perspective view of another embodiment of an assembly that includes a pair of caps, which are attached to each other via a press-fit interface;

FIG. 15 is a cross-sectional perspective view of the assembly of FIG. 14 showing the caps detached from each other;

FIG. 16 is a cross-sectional perspective view of another embodiment of an assembly that includes a pair of caps, which are attached to each other via a welded interface;

FIG. 17 is a cross-sectional perspective view of the assembly of FIG. 16 showing the caps detached from each other;

FIG. 18 is a perspective view of another embodiment of an assembly that includes a pair of caps, which are attached to each other at least partially via a snapping interface;

FIG. 19 is a perspective view of the assembly of FIG. 18 showing the caps detached from each other;

FIG. 20 is a perspective view from a different angle of one of the caps of FIG. 18;

FIG. 21 is a perspective view from a different angle of another of the caps of FIG. 18;

FIG. 22 is a perspective view of another embodiment of an assembly that includes a pair of caps, which are attached to each other via a snapping interface;

FIG. 23 is a cross-sectional view of another embodiment of an assembly that includes a pair of caps and a sleeve, wherein the caps are shown attached to the sleeve;

FIG. 24 is a cross-sectional view of the assembly of FIG. 23, wherein the caps are shown detached from the sleeve;

FIG. 25 is a perspective view of another embodiment of an assembly that includes two cap portions integrally connected to each other;

FIG. 26 is an exploded perspective view of the assembly of FIG. 25;

FIG. 27 is a perspective view focusing on one cap portion of the assembly of FIG. 25, with covers removed from the assembly;

FIG. 28 is a perspective view focusing on the other cap portion of the assembly of FIG. 25, with covers removed from the assembly;

FIG. 29 is a cross-sectional view of the assembly of FIG. 28 taken along the view line 29-29;

FIG. 30 is a cross-sectional view of the assembly of FIG. 25 showing an early stage of coupling a cap portion of the assembly with a medical connector that has a male protrusion;

FIG. 31 is a cross-sectional view of the assembly of FIG. 25 showing a late stage of coupling the cap portion of the assembly with the medical connector that has a male protrusion;

FIG. 32 is a cross-sectional view of the assembly of FIG. 25 showing a late stage of coupling the other cap portion of the assembly with a first embodiment of a needleless injection site;

FIG. 33 is a cross-sectional view of the assembly of FIG. 25 showing a late stage of coupling the other cap portion of the assembly with a second embodiment of a needleless injection site;

FIG. 34 is a cross-sectional view of the assembly of FIG. 25 showing a late stage of coupling the other cap portion of the assembly with a third embodiment of a needleless injection site;

FIG. 35 is a cross-sectional view of another embodiment of an assembly that includes two cap portions integrally connected to each other, with covers removed from the assembly;

FIG. 36 is an exploded perspective view of another embodiment of an assembly that includes two cap portions integrally connected to each other;

FIG. 37 is a cross-sectional view of the assembly of FIG. 36 similar to the view shown in FIG. 29;

4

FIG. 38 is a cross-sectional view of the assembly of FIG. 36 showing an early stage of coupling a cap portion of the assembly with a medical connector that has a male protrusion;

FIG. 39 is a cross-sectional view of the assembly of FIG. 36 showing a late stage of coupling a cap portion of the assembly with a medical connector that has a male protrusion;

FIG. 40 is an exploded perspective view of another embodiment of a cap configured for coupling with a medical connector having a male protrusion;

FIG. 41 is a cross-sectional view of the assembled cap of FIG. 40 showing an early stage of coupling the cap with a medical connector that has a male protrusion in which the male protrusion has not yet contacted a sealing member of the cap;

FIG. 42 is a cross-sectional view such as that of FIG. 41 showing a later stage of coupling the cap with the medical connector in which the male protrusion forms a fluid-tight seal with the sealing member of the cap;

FIG. 43 is a cross-sectional view such as that of FIG. 41 showing a yet later stage of coupling the cap with the medical connector in which a pad is compressed so as to expel antiseptic therefrom through the sealing member and in which the male protrusion has not yet formed a fluid-tight seal with a sidewall of the medical connector;

FIG. 44 is a cross-sectional view such as that of FIG. 41 showing a yet later stage of coupling the cap with the medical connector in which the pad is compressed further so as to expel additional antiseptic therefrom through the sealing member and in which the male protrusion has not yet formed a fluid-tight seal with a sidewall of the medical connector;

FIG. 45 is a cross-sectional view such as that of FIG. 41 showing a yet later stage of coupling the cap with the medical connector in which that pad is compressed even further so as to expel additional antiseptic therefrom through the sealing member and in which the male protrusion forms a fluid-tight seal with a sidewall of the medical connector;

FIG. 46 is a cross-sectional view such as that of FIG. 41 showing another embodiment of cap coupled with a medical connector having a male protrusion;

FIG. 47 is a cross-sectional view of another embodiment of a cap configured for coupling with a medical connector having a male protrusion;

FIG. 48 is a cross-sectional view of yet another embodiment of a cap configured for coupling with a medical connector having a male protrusion;

FIG. 49 is a cross-sectional view of the cap of FIG. 48 coupled with a medical connector having a male protrusion;

FIG. 50 is an exploded perspective view of another embodiment of an assembly that includes a female cap and a male cap, which can be connected in a pre-use configuration via a sleeve;

FIG. 51 is a cross-sectional view of the female cap of FIG. 50 taken along the view line 51-51;

FIG. 52 is a cross-sectional view of the male cap of FIG. 49 taken along the view line 52-52;

FIG. 53 is a cross-sectional view of the sleeve of FIG. 49 taken along the view line 53-53;

FIG. 54 is an elevation view of the assembly of FIG. 50 shown in a pre-use configuration;

FIG. 55 is an exploded perspective view of another embodiment of an assembly that includes a female cap and a male cap, which can be connected in a pre-use configuration via a sleeve and that includes separation assists;

FIG. 56 is an elevation view of an embodiment of a cap that includes a seal inhibitor;

FIG. 57 is another elevation view of the cap of FIG. 56 showing a different face thereof;

5

FIG. 58 is an elevation view of the cap of FIG. 56 coupled with a removable cover;

FIG. 59 is a perspective view of another embodiment of an assembly that includes a female cap and a male cap, which can be connected in a pre-use configuration via a sleeve;

FIG. 60 is an exploded perspective view of the assembly of FIG. 59;

FIG. 61 is a perspective view of an embodiment of a sleeve that is compatible with the assembly of FIG. 59;

FIG. 62A is a top plan view of an embodiment of a housing portion of a female cap that is compatible with the assembly of FIG. 59;

FIG. 62B is a side elevation view of the housing portion of the female cap of FIG. 62A;

FIG. 62C is a front elevation view of the housing portion of the female cap of FIG. 62A;

FIG. 63A is a top plan view of an embodiment of a housing portion of a male cap that is compatible with the assembly of FIG. 59;

FIG. 63B is a side elevation view of the housing portion of the male cap of FIG. 63A;

FIG. 63C is a front elevation view of the housing portion of the male cap of FIG. 63A;

FIG. 64 is a cross-sectional view of the assembly of FIG. 59 taken along the view line 64-64 in FIG. 59;

FIG. 65A is a top plan view of the assembly of FIG. 59;

FIG. 65B is a top plan view of the assembly of FIG. 59 showing a male cap portion thereof having been rotated so as to assist in the release of the male cap from the assembly;

FIGS. 66A-66D depict various stages of an illustrative method for coupling a medical connector with the male cap of FIG. 65B;

FIG. 67 is a cross-sectional view of the female cap of FIG. 64 coupled with an embodiment of a needleless injection site;

FIG. 68 is a cross-sectional view of the female cap of FIG. 64 coupled with another embodiment of a needleless injection site; and

FIG. 69 is a cross-sectional view of the female cap of FIG. 64 coupled with another embodiment of a needleless injection site.

DETAILED DESCRIPTION

Disclosed herein are caps that can be used to protect and/or disinfect medical connectors. Systems and methods related to such caps are also disclosed. An example of medical connectors for which caps disclosed herein may be used are intravascular connectors associated with a fluid pathway, such as an IV line. Commonly, a fluid pathway is used to intermittently administer medications to a patient. For example, a fluid pathway, which communicates fluids with a patient's blood stream, may have one or more connectors associated therewith. Each of the fluid pathway connectors can be connected to other connectors, such as a connector associated with a central line. In such a situation, the medical connectors, such as luer lock connectors, are connected and disconnected at various times, and may remain disconnected for several minutes or hours. Medical connector caps are used to cover and protect the various medical connectors while the connectors are separated from one another. When the medical connectors are separated from each other, there are two connectors that each can benefit from being covered by a cap. Therefore, in some cases, it can be advantageous to have a single connector set that can be used to provide protection for both ends of a separated connection. In other or further embodiments, a cap can include an antiseptic for disinfecting a medical connector. In some cases, it can be advantageous

6

for the cap to form a seal with the medical connector to thereby prevent the antiseptic from exiting the cap into the fluid pathway.

Shown in FIGS. 1-1B, is a system, unit, or assembly 100 of a pair of separable caps 102 and 104, which are securely, but releasably, affixed one to the other across a common interface 106. When assembly 100 is in a pre-use or initially packaged state, the internal parts and surfaces thereof can be sterile, and these are able to reduce, prevent, or eliminate contamination of connectors with which caps 102, 104 can be coupled.

As further discussed below, in various embodiments, caps 102 and 104 can be distributed in a coupled state, such as that shown in FIGS. 1-1B, and may be decoupled by a user (e.g., a medical professional) and subsequently coupled with separate medical connectors. Caps 102 and 104 can include features to aid in such a decoupling action and/or in the coupling of caps 102, 104 with the respective connectors. For example, in the illustrated embodiment, each cap 102, 104 includes gripping features 103.

The gripping features 103 can comprise longitudinally extending lands or ridges 105 that taper from a relatively wide width near the interface 106 of the caps 102, 104 to a narrower width at or near an outer end of the cap 102, 104. The gripping features 103 can further include longitudinally extending depressions or grooves 107 between adjacent ridges 105. For example, as can be seen in FIGS. 1-8B, the grooves 107 can extend radially inwardly from an outer surface of the cap 102 that comprises the ridges 105, and the grooves 107 can also commence at a position near the interface 106 and can grow wider and deeper toward an outer end of the cap 102. The gripping features 103 can further include longitudinally extending bumps or protrusions 108 between adjacent ridges 105. As can be seen in FIGS. 1-8B, the protrusions 108 can extend radially outwardly from an outer surface of the cap 104 that comprises the ridges 105, and the protrusions 108 can also commence at a position near the interface 106 and can grow wider and taller toward an outer end of the cap 104. The uneven surfaces provided by the ridges 105 and the grooves 107 or protrusions 108 can facilitate rotational movement of the caps 102, 104 (e.g., rotational movement relative to each other), which can aid in decoupling the caps 102, 104 from each other and/or securing the caps 102, 104 to separated connectors. For example, the uneven surfaces may be easily gripped by the fingertips of a medical practitioner.

As can be seen, for example, in FIGS. 1A and 1B, the patterns of the ridges 105, grooves 107, and/or protrusions 108 can be different for the caps 102, 104. In the illustrated embodiment, cap 102 includes only ridges 105 and grooves 107, whereas cap 104 includes only ridges 105 and protrusions 108. Such differences can aid in distinguishing the caps 102, 104 from each other. Other features and methods for distinguishing the caps 102, 104 from each other are discussed further below.

Caps 102 and 104 are shown as separated from each other, or in a decoupled state, in FIG. 2, wherein cap 104 is shown as having an insertable or male section 109. Section 109 has an elongated portion 110 that ends at an exteriorly disposed threaded segment 112. Threaded segment 112 comprises threads 114 that are sized and shaped to be inserted and joined by threading into cap 102.

Cap 102, as shown in FIG. 3, has a closed, hollow interior 116, which may also be referred to as a disinfection cavity or chamber, which opens outwardly at a proximal end 118 to expose an interiorly disposed threaded segment 120 that includes threads 122. Threads 122 are of a size and pitch to complementarily engage threads 114 of cap 104 for a screw or push-on tight fit with cap 104.

As illustrated in FIG. 4, cap 102 has an interior surface 124, an opening edge 126 and an exterior surface 128, opening edge 126 being a common link between interior surface 124 and exterior surface 128. Further, threads 122 also have a size and pitch to engage a threadable segment 130 of a female connector, such as for example, female luer connector 132. Such connectors are generally and commonly used as catheter and other fluid-tight protective connectors in medical applications. As seen in FIG. 4, cap 102 provides a protective cover for connector 132 when encased about connector 132 (displaced in direction of arrow 134) whereupon threadable segment 130 engages and is drawn into a secure, but releasable connection with threads 122 of cap 102.

In some embodiments, the connector 132 comprises a needleless injection site, which may sometimes referred to as a needleless injection port, hub, valve, or device, or as a needleless access site, port, hub, valve, or device, and which can include such brands as, for example, Clave® (available from ICU Medical, Inc.), SmartSite® (available from Cardinal Health, Inc.), and Q-Syte™ (available from Becton, Dickinson and Company). Stated otherwise, in some embodiments, cap 102 can be suitably connected with any of a variety of different needleless injection sites, such as those previously listed. In certain embodiments, once cap 102 has been applied to or coupled with connector 132, it is unnecessary to disinfect (e.g. treat with an alcohol swab) the connector 132 prior to each reconnection of the connector 132 with another connector, as the connector 132 will be kept in an uncontaminated state while coupled with the cap 102. Use of the cap 102 thus can replace the standard swabbing protocol.

As seen in FIG. 5, threads 114 of cap 104 are of a size and pitch to engage threads 138 of a male luer-lock connector 136. For example, connector 136 can comprise the end of an IV tubing set that is disconnected from an IV catheter needleless injection site. Note that cap 104 has a medially disposed, elongated hole 140, which may also be referred to as a disinfection chamber, into which a male protrusion 141 of connector 136 may be facily and securely inserted when cap 104 is displaced in the direction of arrow 144 to engage connector 136. The male protrusion 141 may be of any suitable variety. The term "male protrusion" is used broadly herein, and includes any elongated structure. In the illustrated embodiment, the male protrusion 141 comprises a frustoconical luer 142.

Cap 104 also has a surface 146 which continues through to a circular edge 148. Further, distally displaced from circular edge 148, surface 146 abruptly ends at a circular ring shaped edge 150, which is therefrom joined to an outside surface 152. It may be noted that opening edge 126 (see FIG. 4) and ring shaped edge 150 combine to form common interface 106 (see FIG. 1) when cap 102 is affixed to cap 104 to construct assembly 100. It should also be noted that, in certain embodiments, surfaces of assembly 100, which contact internal surfaces of a connector, such as connector 132 or connector 136, are sufficiently sterile or aseptic to not contaminate the inner surfaces thereof.

Internal portions and associated edges of caps 102 and 104 can be pre-sterilized and so maintained until use. Caps 102 and 104 may be injection molded using polypropylene or other material that can be sterilized and which is impervious to contaminating agents while cap 102 is nested with cap 104, before being opened for use. Caps 102 and 104 can be impregnated or coated with an antimicrobial substance. As an example, each cap 102 and cap 104 may be individually sterilized by ethylene oxide (ETO) before final assembly and aseptically paired, or assembly 100 may be finally consolidated as a single unit and then sterilized, such as by radiation

(e.g. gamma). Assembly 100 can be kept intact until the time of use, with internal surfaces of nested parts 102 and 104 remaining clean and sterile until assembly 100 is opened for use.

Reference is now made to FIGS. 6 through 7B, wherein a seal, such as an O-ring, is disposed between surfaces 126 and 150 to provide yet another barrier against internal surface contamination of caps 102 and 104. As seen in FIG. 6, an O-ring 154 is disposed between surfaces 126 and 150 to provide a seal thereby. While O-ring 154 can be displaced from caps 102 and 104 as illustrated in FIG. 7, it is anticipated that O-ring 154 can be adapted to remain affixed to one of caps 102 and 104. For example, as illustrated in FIG. 7A, O-ring 154 can remain positioned adjacent surface 150 on cap 104 when caps 102 and 104 are disconnected from one another, rather than being separated when cap 104 is displaced from cap 102, as seen in FIG. 7.

Alternatively, O-ring 154 can be associated with cap 102, as seen in FIG. 7B. In particular, opening edge 126 of cap 102 can have an annular groove 156 for receiving O-ring 154 therein. Annular groove 156 can be sized and shaped such that O-ring 154 sealingly engages cap 104 or a medical connector when cap 102 is coupled thereto. It will be appreciated that annular groove 156 can be disposed in opening edge 126 toward the exterior of cap 102 as illustrated in FIG. 7B, or annular groove 126 can be disposed in opening edge 126 towards the interior of cap 102. In some exemplary embodiments, opening edge 126 of cap 102 does not have annular groove 126 therein. In such embodiments, O-ring 154 can be mounted directly to opening edge 126. O-ring 154 can be mounted on or to caps 102 or 104 in any suitable manner, including with the use of an adhesive, such as glue, a mechanical fastener, or a friction fitting.

While the seal between caps 102 and 104 has been described as being an O-ring mounted on one of caps 102 or 104, it will be appreciated that other seals are contemplated. For example, each of caps 102 and 104 can have an O-ring mounted thereon. In such a configuration, the two O-rings abut each other when caps 102 and 104 are coupled together, thereby forming a seal to antiseptically partition the internal and external surfaces of caps 102 and 104. In an alternate embodiment, an O-ring or other sealing mechanism can be mounted on surfaces 109a and 109b. Alternatively, one or both of caps 102 and 104 can be formed with a lip, bump, or groove that provides a sealing function when caps 102 and 104 are coupled to each other or to separated medical connectors. In one exemplary embodiment, one of caps 102 and 104 has a ridge extending around its interfacing surface, and the other cap has a corresponding groove in its interfacing surface into which the ridge is received to create the seal. In yet another exemplary embodiment, one or both of caps 102 and 104 can be overmolded or comolded using any known and suitable overmolding or comolding process. For example, one or both of caps 102 and 104, and associated surfaces 126 and 150, can be overmolded or comolded. Thus, caps 102 and 104 can be formed of a polymer, and surfaces 126 and 150 can be formed of a softer polymer that is comolded or overmolded to the rest of caps 102 or 104. Surfaces 126 and 150, formed of the softer polymer, are thus able to be compressed or deformed sufficiently to create an impermeable seal when caps 102 and 104 are coupled together or coupled to separated medical connectors. Other suitable seals or sealing mechanisms are also possible, such as those described below with respect to further embodiments.

As noted elsewhere herein, a sealing mechanism can be used to limit or prevent evaporation or loss of an antiseptic

agent disposed within caps **102** and **104** when caps **102** and **104** are coupled together. Additionally, a sealing mechanism, as described herein, can also limit or prevent evaporation or loss of an antiseptic agent disposed within caps **102** and **104** when caps **102** and **104** are coupled to separated medical connectors. Further, a sealing mechanism can limit or prevent microbial ingress within caps **102** and **104** when they are coupled to each other, or within caps **102** and **104** when caps **102** and **104** are individually coupled to separated medical connectors. Moreover, a sealing mechanism can be configured to maintain an antiseptic agent within caps **102** and **104** when caps **102** and **104** are either coupled to one another or to separated medical connectors for a predetermined amount of time. Thus, the seal may be adapted to limit or prevent microbial ingress, while also partially or completely preventing evaporation of an antiseptic agent disposed within caps **102** and **104** when caps **102** and **104** are coupled together or when caps **102** and **104** are coupled to separated medical connectors. Similarly, the seal may be configured to limit or prevent microbial ingress while not preventing evaporation of an antiseptic agent disposed within caps **102** and **104**. In yet other embodiments, no seal is provided between caps **102** and **104** when coupled together or between caps **102** and **104** when coupled to separated medical connectors.

Further safety in sealing against internal surface contamination may be provided by a sealing tape, or a planar or foil seal, such as tape **158** seen in FIG. **8A**. Tape **158** is disposed to fully cover exposed edges of surfaces **126** and **150**. Tape **158** may, for example, be of an impervious pliable material, such as a metallized-surface mylar. As seen in FIG. **8B**, tape **158** is wrapped about surfaces **126** and **150** to provide a secure seal. It is preferred that tape **158** frangibly divides when cap **102** is separated from cap **104** to facilitate separation of caps **102** and **104** and provide a visible indication that the seal is broken. Thus tape **158** provides both a seal to prevent microbial ingress and a mechanism for maintaining the secure connection between caps **102** and **104** prior to use. It will be appreciated, however, that any suitable sealing mechanism can be used to maintain the secure connection between caps **102** and **104** prior to use. For example, any sealing mechanism can be used that securely and selectively couples caps **102** and **104** together, requires deliberate action to break the seal, and provides a visual indication of whether the seal has been broken. By way of example and not limitation, a suitable sealing mechanism may include a heat stake, a frictional seal, a barbed seal, a ratchet seal, and the like.

When capping disconnected medical connectors, it can be desirable to do more than merely cover the connectors. For example, an absorbent pad, such as pad **160**, seen in FIG. **9A**, may be included within cap **102** (e.g., within the disinfection chamber **116**), such as by displacing pad **160** into cap **102** as indicated by arrow **162**. Pad **160** is seen disposed in cap **102** in FIG. **9B**. An antiseptic **164** can also be disposed within cap **102** as illustrated in FIG. **9C**. Antiseptic **164** can be in liquid or solid form. For example, alcohol or another stable liquid antiseptic may be added from a container **166** to be received within, wet, soak, or saturate pad **160** to a predetermined concentration level. Note that once assembly **100** is fully assembled, pad **160** will substantially remain at the predetermined concentration level due to the exterior seals provided for assembly **100** as described herein. Alternatively, or additionally, pad **160** may receive or be impregnated with a dry antiseptic, such as, for example, chlorhexidine gluconate.

Further note that once cap **104** is securely affixed to cap **102**, as seen in FIG. **9D**, pad **160** is disposed to contact at least circular edge **148** (see also FIG. **5**). (In FIG. **9D**, parts of cap **104** which are internal to assembly **100** are seen with hidden

or dashed lines.) Such contact provides a wiping action preferred to make contact with a surface before contact is made with an associated connector. Note also that residual antiseptic on associated internal surfaces of cap **104** may be transferred to related parts of the associated connector for cleaning and/or disinfecting purposes.

Pad **160** can be formed of a deformable, resilient material such that when cap **104** is coupled to cap **102**, elongated portion **110** can compress pad **160** within cap **102**, as illustrated in FIG. **9D**. Further, pad **160** can expand to its original shape when cap **104** is removed from cap **102**. Similarly, pad **160** can be compressed within cap **102** when cap **102** is coupled to a medical connector, such as medical connector **132**. More specifically, during the connection of cap **102** to a medical connector, cap **102** and pad **160** rotate relative to an opening edge of the medical connector, thereby drawing the medical connector into cap **102**. The rotation of cap **102** causes pad **160** to wipe or scrub the opening edge of the medical connector. Pad **160** and any antiseptic disposed within cap **102** can thus cleanse and disinfect the opening edges of the medical connector. Pad **160** can also be formed such that when a medical connector is coupled to cap **102**, pad **160** is deformed such that pad **160** extends around the opening edges and/or threads of the medical connector. For example, pad **160** can be formed such that as cap **102** is twisted onto medical connector **132**, pad **160** deforms around threads **130** and/or the opening edges of medical connector **132**, thereby scrubbing threads **130** and/or the opening edge of medical connector **132**.

Pad **160** can also provide additional functionality when a liquid antiseptic is disposed within cap **102**. In particular, pad **160** acts as a sponge to absorb or release the liquid antiseptic within cap **104**. More specifically, when pad **160** is compressed by elongate portion **110** of cap **104** (FIG. **9D**; see also elongate portion **268** compressing pad **160** in FIG. **14**) or the opening edges of a medical connector coupled to cap **102**, pad **160** releases at least a portion of the antiseptic so that the antiseptic can be transferred to elongate portion **110** or the opening edges of the medical connector. Conversely, when cap **102** or a medical connector is disconnected from cap **102**, pad **160** expands and absorbs excess antiseptic so that the antiseptic does not drip or spill out of cap **102**.

Similar to pad **160** and antiseptic **164** disposed within cap **102**, cap **104** may also have a pad and/or an antiseptic disposed therein. For example, as illustrated in FIG. **9E**, a pad **170** may be disposed within elongate hole **140** of cap **104**. An antiseptic can also be disposed within cap **104** in a manner similar to antiseptic **164** in cap **102**. Antiseptic can be in liquid or solid form. For example, alcohol or another stable liquid antiseptic may be added from a container to saturate pad **170** to a predetermined level. Alternatively, or additionally, pad **170** may be impregnated with a dry antiseptic, such as chlorhexidine gluconate. Once assembly **100** is fully assembled, an antiseptically saturated pad **170** disposed within cap **104** will substantially remain at the predetermined saturation level due to the exterior seals for assembly **100** as described above. Once caps **102** and **104** are disconnected from each other and connected to individual medical connectors, pad **170** disposed within cap **104** may scrub related parts of the associated connector for cleaning and/or disinfecting purposes. It will be appreciated, however, that in some embodiments, pad **170** may not contact a medical connector coupled to cap **104**. Additionally, the antiseptic disposed within cap **104** may be transferred to the related parts of the associated medical connector for cleaning and/or disinfecting purposes.

Additional embodiments of caps such as the caps **102**, **104** are provided in FIGS. **10-29** and the associated written

11

description of U.S. patent application Ser. No. 12/171,997, titled STERILITY-PROTECTING CAPS WITH FLUID RESERVOIR FOR SEPARATED CONNECTORS, which was filed on Jul. 11, 2008 and was published as U.S. Patent Application Publication No. 2009/0062766 on Mar. 5, 2009 ("the Publication"), which is hereby incorporated by reference herein. As indicated in the Publication, any suitable feature of the illustrative embodiments of FIGS. 16-29 of the Publication, which are described with respect to a female-type cap similar to the cap 102, may be applied to or incorporated within a male-type cap, similar to the cap 104. Likewise, the female-type caps described with reference to FIGS. 16-29 of the Publication can be coupled to a male-type cap in a manner similar to that described with reference to caps 102 and 104, in which the caps 102, 104 are nested with each other. In other embodiments, any suitable feature of the caps described with respect to FIGS. 1-29 of the Publication, whether of a male or female variety, can be formed and/or employed without being nested or otherwise associated with a complementary cap.

Discussed hereafter are additional embodiments of caps, which can have coupling arrangements and/or other features that differ in certain respects from those of the caps 102, 104 described above and other caps described in the Publication. Any suitable feature of such caps can be incorporated into the caps described hereafter, and vice versa.

FIGS. 10 and 11 depict a system or assembly 1000 that includes a first protective medical connector, shield, or cap 1002 and a second protective medical connector, shield, or cap 1004. As shown in FIG. 10, the caps 1002, 1004 are connected to each other when the assembly 1000 is in a shipping or pre-use state. As shown in FIG. 11, the caps 1002, 1004 can be separated from each other such that each may be coupled with a corresponding or complementary medical connector. For example, as with the cap 102, the cap 1002 can be configured to be coupled with a female connector, such as a female luer lock or a needleless injection site (see, e.g., FIG. 4). Accordingly, the cap 1002 may be referred to as a female cap. As with the cap 104, the cap 1004 can be configured to couple with a male connector, such as a male luer lock (see, e.g., FIG. 5). Accordingly, the cap 1004 and may be referred to as a male cap.

With continued reference to FIGS. 10 and 11, the cap 1002 can comprise a housing 1010. The housing 1010 can be elongated, and may define a cylinder or any other suitable shape. For example, in the illustrated embodiment, the housing 1010 includes a sidewall 1012 that defines a substantially cylindrical outer surface 1014. The outer surface can be smooth, as shown, which can enhance comfort to a patient if the cap 1002 contacts the patient when coupled with a medical connector. In other embodiments, the outer surface can include gripping features, which can aid in rotating the cap 1002 relative to the cap 1004 to permit separation of the caps 1002, 1004 and/or aid in rotating the cap 1002 relative to a medical connector. Such gripping features can include, for example, ridges, grooves, an/or protrusions similar to the ridges 105, grooves 107, and protrusions 108 described above and/or an elastomeric or other coating or layer having a relatively high coefficient of friction. The sidewall 1012 can define a sealing surface 1016 at one end thereof and can define a terminal edge 1018 at an opposite end thereof.

The housing 1010 can further include a transverse wall or partition 1020. In the illustrated embodiment, the partition 1020 defines a plane that is substantially perpendicular to a longitudinal axis of the sidewall 1012. A first portion of the sidewall 1012 can cooperate with one side of the partition 1020 to define a disinfection chamber 1022, which is closed at

12

one end by the partition 1020 and open at an opposite end thereof (e.g., the sealing surface 1016 can define an open end of the disinfection chamber 1022). Similarly, a second portion of the sidewall 1012 can cooperate with an opposite side of the partition 1020 to define a coupling chamber 1024, which likewise is closed at one end by the partition 1020 and open at an opposite end thereof (e.g., the terminal edge 1018 can define an open end of the coupling chamber 1024).

An interior surface of the sidewall 1012 can include a connecting geometry or connection interface 1030 in the region of the disinfection chamber 1022. The connection interface 1030 can comprise inwardly projecting threads 1031 similar to the threads 122 described above, and can be configured to complementarily engage a connection interface of a medical connector, such as, for example, outwardly projecting threads of a needleless injection site. The threaded connection interface 1030 thus can allow for selective coupling of the cap 1002 to a medical connector in a secure, yet selectively removable fashion. Other configurations of the connection interface 1030 may permit the cap 1002 to be coupled with a medical connector in a secure, yet selectively removable fashion, such as friction-fit, snap-fit, or other suitable interfacing arrangements.

The disinfection chamber 1022 can include a pad 1032 therein. The pad 1032 can resemble the pads 160, 170 described above. In various embodiments, the pad 1032 can be deformable, and can also be configured to retain an antiseptic 1033, such as, for example, the antiseptic 164 described above. In further embodiments, the pad 1032 can be resiliently deformable. For example, the pad 1032 can comprise any suitable sponge-like material, such as an elastomeric foam, any open-cell foam, felt, or non-woven fiber matrix, and can be configured to conform to the contours of a portion of a medical connector that is introduced into the disinfection chamber 1022 (e.g., uneven surfaces of an end of a needleless injection site; see also FIGS. 32-34 and the associated written description herein). The pad 1032 can also comprise any closed-cell foam, as well as a solid elastomeric foam such as silicone or the like.

The pad 1032 can have a series or network of openings or spaces therein that can retain the antiseptic 1033 when the pad 1032 is in an expanded state. For example, the antiseptic 1033 can be received within, occupy, fill (or partially fill), wet, soak, or saturate at least a fraction of the pad 1032, or stated otherwise, can fill the pad 1032 to a given concentration level. Compression of the pad 1032 can cause antiseptic 1033 to egress from the pad 1032 so as to contact the medical connector. Resilient expansion of the foam upon removal of a compressive force can allow the pad 1032 to soak up or absorb at least some of the antiseptic 1033 that had previously been forced from the pad 1032. In some embodiments, the antiseptic 1033 can comprise any liquid antiseptic, such as alcohol (e.g., isopropyl alcohol) at various concentrations ranging from 50-90%, ethanol at various concentrations ranging from 50-95%, and combinations of any alcohols with any antiseptics, or a dry material, such as chlorhexidine, ethylenediaminetetraacetic acid (EDTA), iodophors, or any suitable combination thereof. Accordingly, although the antiseptic 1033 is schematically depicted in FIG. 10 as a series of droplets, the antiseptic 1033 is not necessarily liquid and may fill the pad 1032 to a greater or lesser extent than what is shown. In the illustrated embodiment, when the disinfection chamber 1022 is in a sealed state (e.g., in its pre-use condition), the pad 1032 is in a relaxed, expanded, or uncompressed state in a longitudinal direction. It is noted that the pad 1032 may be uncompressed in one or more dimensions, yet compressed in one or more other dimensions, when the assembly

13

1000 is in the pre-use state. For example, the pad 1032 can be expanded or in a relaxed state in a longitudinal direction, yet compressed radially inwardly via the sidewall 1012, when the assembly 1000 is in the pre-use state. Such a lack of compression of the pad 1032 in the longitudinal direction can result from the fact that the cap 1004 does not interact with the connection interface 1030 of the cap 1002 to seal the cap 1002, and thus no portion of the cap 1004 contacts the pad 1032 when the caps 1002, 1004 are in the pre-use configuration.

In the illustrated embodiment, the pad 1032 is substantially cylindrical and defines an outer diameter that is approximately the same size as an inner diameter of the threads 1031. In other embodiments, the outer diameter of the pad 1032 can be larger than the inner diameter of the threads 1031 so as to be radially compressed and held tighter within the disinfection chamber 1022. In further embodiments, the pad 1032 can include threading that projects radially inwardly and that is complementary to the threads 1031 to thereby secure the pad 1032 within the chamber 1022.

The disinfection chamber 1022 can be sealed at the sealing surface 1016 via a cover 1034 that can span an open end of the disinfection chamber 1022. The cover 1034 can be secured to the housing 1010 in any suitable manner, such as, for example, via an adhesive. Preferably, the cover 1034 can be readily removed by a practitioner. For example, in some embodiments, the cover 1034 can include a tab 1035 and a practitioner can readily remove the cover 1034 by holding the housing 1010 in one hand and pulling the tab 1035 away from the housing 1010 with the other hand. The removable cover 1034 can be formed of any suitable material, such as, for example, an impervious pliable material (e.g., foil, plastic, metallized-surface mylar, and the like). The cover 1034 can provide a hermetic seal that can assist in maintaining the sterility of the disinfection chamber 1022 prior to use of the cap 1002 and/or can prevent evaporative loss of antiseptic 1033 from the disinfection chamber 1022.

When the cap 1002 is coupled with a medical connector, the coupling action can bring a portion of the medical connector into contact with the pad 1032 and can allow the pad 1032 to wipe or scrub the medical connector, as described above. Likewise, the antiseptic 1033 can be forced into contact with the medical connector during the coupling phase and can remain in contact with the medical connector, while the cap 1002 is coupled with the medical connector. The connection interface 1030 can cooperate with a connection interface of the medical connector to maintain the cap 1002 in an attached configuration relative to the connector. Moreover, the connection interface 1030 can couple with the medical connector, such as via complementary threading, so as to prevent antiseptic from leaking from the disinfection chamber 1022.

In some embodiments, such as where the pad 1032 is formed of a material that is not fully elastically resilient or that requires a relatively long relaxation time in which to transition from a compressed state to a relaxed or uncompressed state (e.g., in a longitudinal direction), pre-use storage in the relaxed or uncompressed state in at least one dimension can preserve or enhance the cleaning, scrubbing, or disinfection properties of the pad 1032. For example, as the cap 1002 is coupled with the medical connector (e.g., the medical connector 132 of FIG. 4), an end of the medical connector can come into contact with a proximal surface (e.g., the surface furthest from the partition 1020) of the pad 1032. Further advancement of the cap 1002 onto the medical connector can cause the pad 1032 to deform to complement a contour of the end of the medical connector as the pad 1032 is

14

compressed, which can permit a relatively tight or continuous contact between the pad 1032 and the medical connector. In the illustrated embodiment, the cap 1002 is rotated relative to the medical connector, as it is advanced onto the medical connector. This rotational motion causes the contoured surface of the pad 1032 to rub the medical connector. In certain embodiments, increasingly greater compression of the pad 1032 yields increasingly stronger rubbing of the medical connector, coupled with greater amounts of the antiseptic 1033 being expelled from the pad 1032. Accordingly, when the pad 1032 is uncompressed in at least one dimension (e.g., in a longitudinal direction) in a pre-use state, and thus is not plastically deformed or is not subject to time-consuming elastic recovery from pre-compression, the pad 1032 can be in disinfecting contact with the medical connector for a relatively greater portion of the coupling procedure. In some embodiments, a practitioner can more quickly couple the cap 1002 to the medical connector, as there is no need to first wait for the pad 1032 to relax to an uncompressed or expanded state to achieve better disinfection of the medical connector.

Various parameters can be adjusted to determine the amount of antiseptic 1033 that is expelled from the pad 1032 when the cap 1002 is coupled with a medical connector. For example, the depth to which the medical connector is received within the disinfection chamber 1022, the concentration of antiseptic 1033 within the pad 1032, and/or other parameters can be altered. In various embodiments, no less than about $\frac{1}{4}$, no less than about $\frac{1}{3}$, no less than about $\frac{1}{2}$, no less than about $\frac{2}{3}$, or no less than about $\frac{3}{4}$ of the antiseptic 1033 is expelled from the pad 1032 when the cap 1002 is coupled with a medical connector. In some embodiments, all, or substantially all, of the antiseptic 1033 is expelled from the pad 1032.

With reference to FIG. 10, an interior surface the sidewall 1012 can include another connecting geometry or connection interface 1040 in the region of the coupling chamber 1024. The connection interface 1040 can be configured to complementarily engage a connection interface 1042 of the cap 1004. For example, in the illustrated embodiment, the connection interface 1040 of the cap 1002 comprises inwardly projecting threads 1041, and the connection interface 1042 of the connector 1004 comprises outwardly projecting threads 1043 complementary thereto at an exterior surface of the cap 1004. The connection interfaces 1040, 1042 thus can allow the caps 1002, 1004 to be coupled to each other in a secure, yet selectively removable fashion. Other configurations of the connection interfaces 1040, 1042 may similarly permit the caps 1002, 1004 to be coupled with each other in a secure, yet selectively removable fashion, such as friction-fit, snap-fit, or other suitable interfacing arrangements, as discussed further below. The coupling chamber 1024 can further include a sealing member 1044, such as an elastomeric gasket described further below.

With reference to FIGS. 10 and 11, the male cap 1004 can comprise a housing 1050. The housing 1050 can be elongated, and may define a stepped, substantially cylindrical shape, or may define any other suitable shape. For example, in the illustrated embodiment, the housing 1050 includes a sidewall 1052, which is substantially cylindrical, and a base wall 1054 at one end of the sidewall 1052. A sealing end 1056 of the sidewall 1052 can be located opposite the base wall 1054, and can define an opening into a disinfection chamber 1058. The sidewall 1052 and the base wall 1054 thus can cooperate to define the disinfection chamber 1058.

In some embodiments, the housing 1050 includes a skirt 1060, which can extend radially outwardly from the sidewall 1052. In some embodiments, the skirt 1060 provides a convenient surface for manipulation of the cap 1004. For

15

example, in some embodiments, an outer diameter of the sidewall **1052** is smaller than an outer diameter of the sidewall **1012** of the cap **1002** such that the disparity between the outer diameters could complicate the gripping and rotation of the caps **1002**, **1004** relative to each other. Moreover, in some embodiments, the sidewall **1052** defines a relatively small outer surface area, which could make it difficult to grip the cap **1004**. The larger outer diameter and corresponding larger surface area of the skirt can facilitate gripping of the cap **1004**. The outer surface of the skirt **1060** can be smooth, as shown, or may include gripping features, which can aid in rotating the cap **1004** relative to the cap **1002** to permit separation of the caps **1002**, **1004** and/or aid in rotating the cap **1004** relative to a medical connector. Such gripping features can include, for example, ridges, grooves, and/or protrusions similar to the ridges **105**, grooves **107**, and protrusions **108** described above and/or an elastomeric or other coating having a relatively high coefficient of friction.

In some embodiments, a terminal edge **1062** of the skirt **1060** can be substantially coplanar with an outer surface of the base wall **1054**. In certain of such embodiments, the skirt **1060** can increase the stability of the assembly **1000**. For example, the assembly **1000** can stand uprightly on the base wall **1054**, and the skirt **1060** can inhibit tipping of the assembly **1000**.

With reference to FIG. **10**, the disinfection chamber **1058** can include a pad **1070** such as the pad **1032**. The pad **1070** can be deformable, so as to conform to the contours of a portion of a medical connector that is introduced into the disinfection chamber **1058** (e.g., an outer surface of a male luer). Compression and/or decompression of the pad **1070** can cause an antiseptic **1033** to exit from and/or be absorbed by the pad **1070**, respectively, in a manner such as described above with respect to the pad **1032** (it is noted that the antiseptic **1033** used with the pad **1070** need not necessarily be the same antiseptic as that used with the pad **1032**, although such is possible). Likewise, scrubbing or sanitization of a medical connector via the pad **1070** can proceed in a manner such as that described above with respect to the pad **1032**. In the illustrated embodiment, the pad **1070** is in a relaxed or uncompressed state in at least a longitudinal direction when the disinfection chamber **1058** is in a sealed or pre-use configuration.

As previously discussed, the cap **1004** can include the connection interface **1042**, which can interact with the connection interface **1040** of the cap **1002**. The connection interfaces **1040**, **1042** can cooperate to hold the cap **1004** tightly against the sealing member **1044**. For example, where the connection interfaces **1040**, **1042** comprise threading, appropriate rotation of the cap **1004** relative to the cap **1002** can draw the sealing end **1056** of the sidewall **1052** into abutment with the sealing member **1044**, and additional rotation in the same direction may deform the sealing member **1044**. The sealing end **1056** and the sealing member **1044** can form a hermetic seal that can assist in maintaining the sterility of the disinfection chamber **1058** prior to use of the cap **1004**, and can prevent evaporative loss of an antiseptic from the disinfection chamber **1058**. In further embodiments, a sealing tape (not shown), such as the sealing tape **158** (see FIGS. **8A** and **8B**), can be positioned about the caps **1002**, **1004** so as to contact a lower edge of the housing **1010** (e.g., an outer surface of the portion of the sidewall **1012** that defines the coupling chamber **1058**) and an outer surface of the skirt **1060** of the housing **1050**. The tape can aid in preventing evaporative loss of the antiseptic and/or can indicate whether the caps **1002**, **1004** have been separated or otherwise moved from

16

their initial or pre-use configuration. For example, in some embodiments, the tape can be frangible.

In the illustrated embodiment, the connection interface **1042** comprises outwardly projecting threads similar to the threads **114** described above, and can be configured to complementarily engage a connection interface of a medical connector, such as, for example, inwardly projecting threads of a skirt that surrounds a male luer. The threaded connection interface **1042** thus can allow for selective coupling of the cap **1004** to a medical connector in a secure, yet selectively removable fashion. Other configurations of the connection interface **1042** may permit the cap **1004** to be coupled with a medical connector in a secure, yet selectively removable fashion, such as friction-fit, snap-fit, or other suitable interfacing arrangements.

With continued reference to FIG. **10**, additional description of the illustrated embodiment of the assembly **1000** in the pre-use state will now be provided. As previously discussed, each disinfection chamber **1022**, **1058** can be defined by a separate housing **1012**, **1050**. The chambers **1022**, **1058** can be isolated from each other in the pre-use condition, or stated otherwise, no fluid communication may exist between the chambers **1022**, **1058**.

The caps **1002**, **1004** can cooperate to seal one of the chambers (e.g., the chamber **1058** in the illustrated embodiment) such that manipulation of the caps **1002**, **1004** away from their pre-use configuration can unseal the chamber **1058**, whereas the other chamber (e.g., the chamber **1022** in the illustrated embodiment) can remain in a sealed orientation independent of the relative orientations of the caps **1002**, **1004**. At least a portion of the housing **1050** of the cap **1004** can be received within, or can nest within, a portion of the housing **1010** of the cap **1002**. In the illustrated embodiment, the pad **1032** is free of any compression from the cap **1004** and the pad **1070** is free of any compression from the cap **1002** when the disinfection chambers **1022**, **1058**, in which the pads **1032**, **1070** are housed, are in a pre-use, sealed condition.

In the illustrated embodiment, the caps **1002**, **1004** are substantially coaxial with each other. As previously discussed, the disinfection chambers **1022**, **1058** defined by the caps **1002**, **1004** each can have an open end and a closed end, and in the pre-use configuration, the chambers **1022**, **1058** can be oriented such that their sealed open ends face in the same direction along the common axis of the caps **1002**, **1004**.

With reference to FIG. **11**, in order to prepare the cap **1004** for use with a medical connector (e.g., the connector **136** of FIG. **5**), the caps **1002**, **1004** are decoupled from each other. For example, in the illustrated embodiment, the caps **1002**, **1004** are rotated in opposite directions about a common longitudinal axis such that the connection interfaces **1040**, **1042** urge the caps **1002**, **1004** away from each other and are eventually released from each other. The cap **1004** can then be coupled with the medical connector via the connection interface **1042**, such as in a secure, yet selectively removable manner.

The cap **1002** can be prepared for use with a medical connector (e.g., the connector **132** of FIG. **4**) and connected to the medical connector independent of the coupling status of the caps **1002**, **1004** relative to each other. The cover **1034** can be removed from the cap **1002**, thereby permitting the cap **1002** to be coupled with the medical connector via the connection interface **1040**, such as in a secure, yet selectively removable manner.

The pre-use configuration of the system **1000**, in which the caps **1002**, **1004** are coupled with each other, can ease clinician handling of the system **1000**. As the caps **1002**, **1004** may

be used to cover female and male connectors, respectively, immediately upon decoupling of the female and male connectors from each other, having the caps **1002**, **1004** available in a coupled yet easily separable configuration can be convenient and time saving. Moreover, the system **1000** can include relatively few parts, which can reduce manufacturing costs. In some embodiments, the pre-use coupled configuration of the caps **1002**, **1004** likewise can reduce packaging costs of the system **1000**.

FIG. 12 illustrates another embodiment of an assembly **1100**, which can resemble the assembly **1000** described above in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "11." Relevant disclosure set forth above regarding similarly identified features thus may not be repeated hereafter. Moreover, specific features of the assembly **1100** may not be identified by a reference numeral in the drawings or specifically discussed in the written description that follows. However, such features may clearly be the same, or substantially the same, as features depicted in other embodiments and described with respect to such embodiments. Accordingly, the relevant descriptions of such features apply equally to the features of the assembly **1100**. Any suitable combination of the features and variations of the same described with respect to the assembly **1000** and components thereof can be employed with the assembly **1100** and components thereof, and vice versa. This pattern of disclosure applies equally to further embodiments depicted in subsequent figures and described hereafter.

As with the assembly **1000**, the assembly **1100** can include a female cap **1102** and a male cap **1104** that are coupled with each other when in a pre-use state and that can be removed from each other. The cap female **1102** can be configured to couple with a female connector, and the male cap **1104** can be configured to couple with a male connector. The female cap **1102** can include a housing **1110**, which can include a sidewall **1112** and a partition **1120**. A portion of the sidewall **1112** can cooperate with the partition **1120** to define a disinfection chamber **1122** such as the disinfection chamber **1022**. In the illustrated embodiment, the disinfection chamber **1122** is somewhat shorter than the disinfection chamber **1022** (see FIG. 10). The disinfection chamber **1122** can include a connection interface **1130**, which, in the illustrated embodiment, includes threading **1131**. The disinfection chamber **1122** can include a pad **1132**, such as the pad **1032**, and can be sealed via a removable cover **1134**.

Another portion of the sidewall **1112** can cooperate with the partition **1120** to define a coupling chamber **1124** that extends in a direction opposite the disinfection chamber **1122**. A terminal edge **1118** of the sidewall **1112** can define an opening of the disinfection chamber **1122**. The sidewall **1112** can define a connection interface **1140** that is configured to aid in coupling the caps **1102**, **1104** with each other, as described further below.

With continued reference to FIG. 12, the cap **1104** can include a housing **1150** that includes a sidewall **1152** and a base wall **1154**. The sidewall **1152** and the base wall **1154** can cooperate to define a disinfection chamber **1158**, which can include a pad **1170** therein. The disinfection chamber **1158** can be sealed at a sealing end **1156** of the sidewall **1152** via a removable cover **1136**, which can resemble the cover **1134**. A portion of the sidewall **1152** can define a connection interface **1142**, which includes one or more threads **1143** in the illustrated embodiment.

The housing **1150** can define a skirt **1160** that projects radially outwardly from the sidewall **1152**. The skirt **1160** can terminate at a terminal edge **1162**. In the illustrated embodi-

ment, the skirt **1160** is shorter than the skirt **1060** of the housing **1050** (see FIG. 10) and is spaced above a plane that is defined by an outer surface of the base wall **1154**. In some embodiments, the terminal edge **1162** contacts or is in close proximity to the terminal edge **1118** of the housing **1110** when the caps **1102**, **1104** are coupled with each other in a pre-use configuration, which can provide continuity to an outer surface of the assembly **1100** when it is in a pre-use configuration. The skirt **1160** can be rounded or beveled at the terminal edge **1162**, and an end of the sidewall **1112** can be rounded or beveled at the terminal edge **1118**, which can provide the system **1100** with an annular recess **1163** that can provide a visual and/or tactile indication of the transition from the skirt **1160** to the sidewall **1112**. The rounded ends can also enhance practitioner and/or patient comfort during use of the caps **1102**, **1104**.

In the illustrated embodiment, the sidewall **1152** of the housing **1150** defines a connection interface **1180** that is configured to couple with the connection interface **1140** of the housing **1110**. In particular, the connection interface **1180** includes an outward projection **1181** and the connection interface **1140** includes a recess **1144** that extends radially outwardly relative to the connection chamber **1124** and that is sized to receive the annular projection **1181** therein in a snap-fit engagement. In the illustrated embodiment, each of the projection **1181** and the recess **1144** is annular and extends about the cap **1104** and the cap **1102**, respectively, in its entirety. In other embodiments, the projection **1181** and/or the recess **1144** extend about only a portion of the caps **1102**, **1104**. In still other or further embodiments, the connection interface **1180** can include a recess in the sidewall **1152** and the connection interface **1140** can include an inward projection sized to fit within the recess in a snap-fit engagement. In still other or further embodiments, the connection interfaces **1140**, **1180** can include complementary threading, such as the connection interfaces **1040**, **1042** described above. Other coupling arrangements are also possible.

Features, usage, and operation of the assembly **1100** can resemble that of the assembly **1000** described above. For example, when the assembly **1100** is in the pre-use condition, each disinfection chamber **1122**, **1158** can be defined by a separate housing **1112**, **1150**, and the disinfection chambers **1122**, **1158** can be fluidly isolated from one another (e.g., no fluid communication may exist between the disinfection chambers **1122**, **1158**). Likewise, at least a portion of the housing **1150** of the cap **1104** can be received within, or can nest within, a portion of the housing **1110** of the cap **1102**. In the illustrated embodiment, each of the pads **1132**, **1170** is in an uncompressed or expanded state when each of the disinfection chambers **1122**, **1158** in which it is housed is in a pre-use, sealed condition.

However, certain differences can exist between the assembly **1100** and the assembly **1000**. For example, each of the disinfection chambers **1122**, **1158** can remain sealed independent of the coupling status of the caps **1102**, **1104**. Stated otherwise, the caps **1102**, **1104** do not cooperate to seal either of the chambers **1122**, **1158**. Accordingly, one or both of the caps **1102**, **1104** can be unsealed (e.g., the covers **1134**, **1136** can be removed) and coupled with a separate medical connector (e.g., via the connection interfaces **1130**, **1142**) without detaching the caps **1102**, **1104** from each other. Stated in yet another manner, either of the caps **1102**, **1104** can be installed on a medical connector without being detached from and/or without unsealing the other cap **1102**, **1104**. Alternatively, the caps **1102**, **1104** can be detached from each other, one or both of the caps **1102**, **1104** each can be connected with a separate medical connector (i.e., via the connection inter-

19

faces **1130**, **1142**), and the caps **1102**, **1104** can be reattached to each other (i.e., via the connection interfaces **1140**, **1180**), while remaining connected to the one or more medical connectors.

Moreover, in the illustrated embodiment, the caps **1102**, **1104** are substantially coaxial with each other, thus resembling the caps **1002**, **1004**. However, the disinfection chambers **1122**, **1158** are oriented such that their sealed open ends face away from each other (e.g., outwardly in opposite directions) along the common axis of the caps **1102**, **1104**, when the assembly **1100** is in the pre-use configuration.

FIG. 13 illustrates another embodiment of an assembly **1200**, which can resemble one or more of the assemblies described above in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "12." As with the assembly **1100**, the assembly **1200** can include a cap **1202** and cap **1204** that are coupled with each other, when in a pre-use state, and that can be removed from each other.

The caps **1202**, **1204** can differ from the caps **1102**, **1104** in the manner by which they are coupled with each other. In particular, the cap **1202** includes a housing **1210** that defines a connection chamber **1224** configured to receive a portion of a housing **1250** of the cap **1204**. The housing **1210** defines a connection interface **1240**, and the housing **1250** defines a connection interface **1280**. Rather than cooperating in a snap-fit engagement, however, the connection interfaces **1240**, **1280** cooperate with each other in a friction-fit engagement to provide a secure attachment between the caps **1202**, **1204** and yet to permit the caps **1202**, **1204** to be selectively removable from each other and to permit selective reattachment of the caps **1202**, **1204** to each other. Features, usage, and operation of the assembly **1200** can otherwise resemble that of the assembly **1100** described above.

FIGS. 14 and 15 illustrate another embodiment of an assembly **1300**, which can resemble one or more of the assemblies described above in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "13." The assembly **1300** can include a cap **1302** and cap **1304** that are coupled with each other when in a pre-use state and that can be removed from each other. However, as discussed further below, the caps **1302**, **1304** can include connection interfaces **1340**, **1380**, respectively, that attach the caps **1302**, **1304** to each other in a pre-use configuration, and that permit ready detachment of the caps **1302**, **1304** one from another, but that do not themselves permit reattachment of the caps **1302**, **1304**.

The cap **1302** can include a housing **1310**, which can include a sidewall **1312** and a base wall **1313**. The sidewall **1312** and the base wall **1313** can cooperate to define a disinfection chamber **1322** that can include a pad **1332** therein and that can be sealed via a removable cover **1334**. The base wall **1313** can include a terminal surface **1318** and can define the connection interface **1340**. In the illustrated embodiment, the connection interface **1340** includes a depression or recess **1345** that bows the terminal surface **1318** inwardly, or toward the disinfection chamber **1322**. The connection interface **1340** further includes a pin **1346** that extends outwardly, or away from the disinfection chamber **1322**.

With continued reference to FIGS. 14 and 15, the cap **1304** can include a housing **1350** that includes a sidewall **1352** and a base wall **1354**. The sidewall **1352** and the base wall **1354** can cooperate to define a disinfection chamber **1358**, which can include a pad **1370** therein. The disinfection chamber **1358** can be sealed via a removable cover **1336**. A portion of

20

the sidewall **1352** can define a connection interface **1342**, which includes one or more threads **1343** in the illustrated embodiment.

The housing **1350** can define a skirt **1360** that projects radially outwardly from the sidewall **1352**. The skirt **1360** can terminate at a terminal edge **1362**. In the illustrated embodiment, the skirt **1360** extends past a plane that is defined by an outer surface of the base wall **1354** and is sufficiently long to permit the terminal edge **1362** thereof to contact the terminal surface **1318** of the housing **1310** when the caps **1302**, **1304** are in a pre-use configuration. As with the skirt **1160** and the sidewall **1112**, the skirt **1360** can be rounded or beveled at its terminal edge **1362**, and the sidewall **1112** can be rounded or beveled at the terminal surface **1118**, which can provide the system **1300** with an annular recess **1363**.

The housing **1350** defines the connection interface **1380**, which is configured to couple with the connection interface **1340** of the housing **1310**. The connection interface **1380** includes a protrusion **1382** that extends from the base wall **1354** in a direction opposite the disinfection chamber **1358**. The protrusion **1382** is sized and shaped to receive therein at least a portion of the pin **1346**, and may be substantially annular. In various embodiments, the protrusion **1382** is joined to the pin in any suitable manner, such as, for example, press-fit or friction-fit engagement and/or any suitable adhesive.

In the illustrated embodiment, an additional protrusion **1384** is coaxial with and encircles the protrusion **1382**, and may also be substantially annular. The protrusion **1384** can contact the terminal surface **1318** of the housing **1310** when the caps **1302**, **1304** are in a pre-use configuration, and can provide stability to the connection interfaces **1340**, **1380** and assist in preventing premature separation of the caps **1302**, **1304**. The protrusion **1384** can be said to define a connection chamber **1324** in which the connection interface **1380** is located.

As shown in FIG. 15, the caps **1302**, **1304** can be separated from each other, which can facilitate coupling of the caps **1302**, **1304** to separate medical connectors by removing a constraint on the range of motion of the caps **1302**, **1304** relative to each other. In the illustrated embodiment, the pin **1346** can be sufficiently thin, sufficiently weak, or otherwise configured to break away from the housing **1310**, and can remain attached to the protrusion **1382** of the housing **1350**. In various embodiments, in order to break the pin **1346**, a practitioner can rotate the caps **1302**, **1304** relative to each other about their common longitudinal axis and/or can rotate one or more of the caps **1302**, **1304** about an axis perpendicular to its longitudinal axis so as to move the longitudinal axes of the caps **1302**, **1304** out of alignment with each other.

Breaking the pin **1346** can leave a nub **1347** on the housing **1310**. In certain embodiments, the nub **1347** can be fully below the terminal surface **1318** of the housing **1310** due to the recess **1345**, which can prevent or reduce contact with the nub **1347**, such as by a patient or practitioner.

In certain embodiments, the connection interfaces **1340**, **1380** are configured so as to not rejoin with each other once the caps **1302**, **1304** have been separated from the pre-use configuration. For example, once the pin **1346** has been broken, the caps **1302**, **1304** cannot readily be rejoined to each other via the pin **1346**. Accordingly, the caps **1302**, **1304** can be configured to be attached with each other in a pre-use configuration and readily separated from each other as desired, but not readily rejoined with each other once separated.

Features, usage, and operation of the assembly **1300** can resemble those of one or more of the assemblies described

21

above in other respects. For example, when the assembly **1300** is in the pre-use condition, each disinfection chamber **1322**, **1358** can be defined by a separate housing **1312**, **1350**, and the disinfection chambers **1322**, **1358** can be fluidly isolated from one another. Likewise, at least a portion of one of the housings **1310**, **1350** can be received within, or can nest within, a portion of the other housing **1310**, **1350**. To this end, it is noted that in other embodiments of the assembly **1300**, the housing **1350** of the cap **1304** may define the pin **1346** (or, more generally, the connection interface **1340**), and the housing **1310** of the cap **1302** may define the annular extension **1382** (or, more generally, the connection interface **1380**). In the illustrated embodiment, each of the pads **1332**, **1370** is in an uncompressed or expanded state when the disinfection chamber **1322**, **1358** in which it is housed is in a pre-use, sealed condition. Like the assemblies **1100**, **1200**, each of the disinfection chambers **1322**, **1358** can remain sealed independent of the coupling status of the caps **1302**, **1304**. One or both of the disinfection chambers **1322**, **1358** can be opened and used, while the caps **1302**, **1304** are connected with each other, or the caps **1302**, **1304** can be separated from each other and one or both of the disinfection chambers **1322**, **1358** can then be opened and each used with a separate medical connector.

FIGS. **16** and **17** illustrate another embodiment of an assembly **1400**, which can resemble the assembly **1300** described above in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to “14.” The assembly **1400** can include a cap **1402** and cap **1404** that are coupled with each other when in a pre-use state, and that can be removed from each other in a manner similar to the caps **1302**, **1304**. However, connection interfaces **1440**, **1480** of the caps differ from the connection interfaces **1340**, **1380** of the caps **1302**, **1304**.

The connection interface **1440** can be defined by a terminal surface **1418** of a housing **1410** of the cap **1402**. The connection interface **1440** can include a depression or recess **1448** that bows the terminal surface **1418** inwardly, or toward a disinfection chamber **1422**. The recess **1448** can be annular, although other shapes and configurations are possible.

A sidewall **1452** of the cap **1404** can be somewhat longer than the sidewall **1352** of the cap **1304**, and a base wall **1454** of the cap **1404** can be in close proximity with or adjacent to the terminal surface **1418** of the cap **1402**. A protrusion **1485** can extend outwardly from the base wall **1454**, or in a direction away from a disinfection chamber **1458**. The protrusion **1485** can be annular so as to be received within the annular recess **1448**, although other shapes and configurations are possible. The protrusion **1485** can be joined to the recess **1448** in any suitable manner, such as via an adhesive or via welding (e.g., spin, ultra-sonic, laser, radio frequency, thermal, etc.).

In the illustrated embodiment, the protrusion **1485** is welded to the recess **1448**, and the weld is configured to be broken to permit separation of the caps **1402**, **1404**. As shown in FIG. **17**, a weld edge **1486** can remain within the recess **1448** when the caps **1402**, **1404** are separated. In certain embodiments, the weld edge **1486** can be fully below the terminal surface **1418** of the housing **1410**, which can prevent or reduce contact with the weld edge **1486**, such as by a patient or practitioner. In order to break the weld, a practitioner can rotate the caps **1402**, **1404** relative to each other about their common longitudinal axis and/or can rotate one or more of the caps **1402**, **1404** about an axis perpendicular to its longitudinal axis, so as to move the longitudinal axes of the caps **1402**, **1404** out of alignment with each other. In other embodiments, the connection interfaces **1440**, **1480** can be

22

reversed such that the cap **1402** includes the protrusion **1485** and the cap **1404** can include the recess **1448**.

FIGS. **18-21** illustrate another embodiment of an assembly **1500**, which can resemble one or more of the assemblies described above in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to “15.” As can be seen in FIGS. **18** and **19**, and as discussed hereafter, the assembly **1500** can include a cap **1502** and cap **1504** that are coupled with each other when in a pre-use state and that can be removed from each other. The cap **1502** can be configured to couple with a female connector, and the cap **1504** can be configured to couple with a male connector. The caps **1502**, **1504** can be in a side-by-side arrangement when connected to each other in a pre-use configuration. In the illustrated embodiment, both caps **1502**, **1504** can be sealed shut in the pre-use configuration via a common cover **1537**.

The cap **1502** can include a housing **1510**, which can include a sidewall **1512** and a base wall **1513**. The sidewall **1512** can cooperate with the base wall **1513** to define a disinfection chamber **1522**. The disinfection chamber **1522** can include a connection interface **1530**, which, in the illustrated embodiment, includes threading **1531** disposed on an interior surface of the housing **1512**. The connection interface **1530** can be configured to attach the cap **1502** to a medical connector in a secure yet selectively removable manner. The disinfection chamber **1522** can include a pad **1532**.

The housing **1510** can further include a skirt **1561** that projects radially outwardly from the sidewall **1512** and that can also extend substantially parallel to the sidewall **1512**. The skirt **1561** can include one or more spacers or supports **1564** that can provide structural rigidity to the skirt **1561**. As shown in FIGS. **19** and **21**, the housing **1510** can define a connection interface **1540** that is configured to aid in coupling the caps **1502**, **1504** with each other in a pre-use configuration, as discussed further below. The connection interface **1540** can include a slot **1548** defined by the skirt **1561**, which can extend in a direction substantially parallel to a longitudinal axis of the disinfection chamber **1522**. The sidewall **1512** and the skirt **1561** can cooperate to define an open connection chamber **1524**, which is also discussed below. The slot **1548** can define a side opening of the connection chamber **1524**.

With reference to FIGS. **19** and **20**, the cap **1504** can include a housing **1550** that includes a sidewall **1552** and a base wall **1554**. The sidewall **1552** and the base wall **1554** can cooperate to define a disinfection chamber **1558**, which can include a pad **1570** therein. A portion of the sidewall **1552** can define a connection interface **1542**, which includes one or more threads **1543** in the illustrated embodiment. The connection interface **1542** can be configured to attach the cap **1504** to a medical connector in a secure yet selectively removable manner. The housing **1550** can define a skirt **1560** that projects radially outwardly from the sidewall **1552** and that can also extend substantially parallel to the sidewall **1552**. In the illustrated embodiment, the skirt **1560** extends about only a portion of the cap **1504**. The skirt **1560** can include one or more spacers or supports **1565** that can provide structural rigidity to the skirt **1560**.

The housing **1550** can further define a connection interface **1580** that is configured to interact with the connection interface **1540** of the housing **1510** to couple the caps **1502**, **1504**. The connection interfaces **1540** can maintain the caps **1502**, **1504** in a pre-use configuration, and can permit the caps **1502**, **1504** to be selectively removed from this configuration. In the illustrated embodiment, the connection interfaces **1540**, **1580** can further interact with each other to permit selective reattachment of the caps **1502**, **1504** to each other.

In the illustrated embodiment, the connection interface **1580** includes a locking member, snapping member, or radial extension **1585**. The extension **1585** projects radially from the sidewall **1552** and includes an enlarged region at its outermost end. The extension **1585** is configured to be received within the slot **1548** and the connection chamber **1524** of the cap **1502**. The enlarged portion of the extension **1585** can prevent the extension **1585** from moving out of the slot **1548** in a lateral direction. Although not shown, in some embodiments, the slot **1548** and the extension **1585** can include keying, such as a protrusion and recess that cooperate in a snapping fashion, which can selectively prevent the extension **1585** from moving out of the slot **1548** in a longitudinal direction in the absence of application of sufficient force by a practitioner. In other embodiments, the connection interfaces **1540**, **1580** can be reversed such that the cap **1402** includes the extension **1585** and the cap **1504** includes the slot **1548**.

In the illustrated embodiment, a terminal surface **1518** of the cap **1502** and a terminal surface **1562** of the cap **1504** are substantially coplanar when the system **1500** is in the pre-use configuration. This can contribute to the stability of the pre-use system **1500**, as the connected system **1500** can be set on a planar surface without a predisposition to tipping. Likewise, in the illustrated embodiment, a sealing end **1516** of the cap **1502** and a sealing end **1556** of the cap **1504** are substantially coplanar when the system **1500** is in the pre-use configuration. Each sealing end **1516**, **1556** can be sealed closed via a single or common removable cover **1537**. In the illustrated embodiment, the cover **1537** includes two tabs **1538** that can permit selective opening of just one of the caps **1502**, **1504**, or the opening both of the caps **1502**, **1504** by beginning with opening one of the caps **1502**, **1504** by removing a portion of the cover **1537** from that cap **1502**, **1504** and then continuing to remove the cover **1537** from the remaining cap **1502**, **1504**. Other arrangements are also possible.

The cover **1537** can assist in maintaining the caps **1502**, **1504** coupled with each other in the pre-use configuration, as it can be sufficiently tight to resist longitudinal movement of the caps **1502**, **1504** relative to each other. In various embodiments, the cover **1537** is removed from one or both of the caps **1502**, **1504** prior to removing the caps **1502**, **1504** from each other, as shown in FIG. 19. In other embodiments, the connection interfaces **1540**, **1580** of the caps **1502**, **1504** can be decoupled from each other prior to removing the cover **1537**.

Features, usage, and operation of the assembly **1500** can resemble that of one or more of the assemblies described above. For example, when the assembly **1500** is in the pre-use condition, each disinfection chamber **1522**, **1558** can be defined by a separate housing **1512**, **1550**, and the disinfection chambers **1522**, **1558** can be fluidly isolated from one another. Likewise, at least a portion of the housing **1550** of the cap **1504** can be received within, or can nest within, a portion of the housing **1510** of the cap **1502**. In the illustrated embodiment, each of the pads **1532**, **1570** is in an uncompressed or expanded state when the disinfection chamber **1522**, **1558** in which it is housed is in a pre-use, sealed condition.

However, certain differences can exist. For example, in the illustrated embodiment, the caps **1502**, **1504** are side-by-side, rather than coaxial, when in the pre-use configuration. Stated otherwise, each cap **1502**, **1504** can define a longitudinal axis, and the longitudinal axes can be substantially parallel with each other or non-collinear relative to each other when the caps **1502**, **1504** are in the pre-use configuration. In the illustrated embodiment, the disinfection chambers **1522**, **1558** are oriented such that their sealed open ends face in substantially the same direction when the assembly **1500** is in the pre-use configuration.

FIG. 22 illustrates another embodiment of an assembly **1600**, which can resemble one or more of the assemblies described above, particularly the assembly **1500**, in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "16." The assembly **1600** can include caps **1602**, **1604** such as the caps **1502**, **1504**. Rather than including a single cover **1537**, however, an individual cover **1634**, **1636** is provided to each of the caps **1602**, **1604**. Such an arrangement can, in some instances, facilitate removal of the caps **1602**, **1604** from each other while the caps **1602**, **1604** are maintained in a sealed configuration.

FIGS. 23 and 24 illustrate another embodiment of an assembly **1800**, which can resemble one or more of the assemblies described above in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "18." The assembly **1800** can include a cap **1802** and cap **1804** that are coupled with each other when in a pre-use state (FIG. 23) and that can be removed from each other (FIG. 24). In particular, the caps **1802**, **1804** can be coupled with each other via a sealing mechanism. In the illustrated embodiment, the caps **1802**, **1804** are coupled with each other via a sealing sleeve **1890**. The caps **1802**, **1804** can have open ends facing one another, and disinfection chambers **1822**, **1858** of the caps **1802**, **1804** can be in fluid communication with each other, when in the pre-use configuration.

The cap **1802** can include a housing **1810**, which can include a sidewall **1812** and a base wall **1813**. The sidewall **1812** can cooperate with the base wall **1813** to define the disinfection chamber **1822**. The disinfection chamber **1822** can include a connection interface **1830**, which, in the illustrated embodiment, includes threading **1831** disposed on an interior surface of the housing **1812**. The connection interface **1830** can be configured to attach the cap **1802** to a medical connector in a secure yet selectively removable manner. The disinfection chamber **1822** can include a pad **1832**.

An exterior surface of the sidewall **1812** can define a connection interface **1840** that is configured to couple the cap **1802** with a connection interface **1891** of the sleeve **1890**. In the illustrated embodiment, the connection interfaces **1840**, **1891** couple with each other via a friction-fit engagement. The friction fit can be sufficiently strong to provide a fluid-tight seal between the cap **1802** and the sleeve **1890**, yet can allow the cap **1802** to be removed from the sleeve **1890** via mere manipulation by a medical practitioner (e.g., without the use of ancillary tools). The fluid-tight seal can prevent evaporative loss of antiseptic from the pad **1832** and/or can maintain the sterility of the disinfection chamber **1822**. In other or further embodiments, the connection interfaces **1840**, **1891** can include threading or other suitable attachment features.

In the illustrated embodiment, the base wall **1813** protrudes slightly beyond an end of the sleeve **1890**, which can aid in manipulating the cap **1802** away from the sleeve **1890**. In other embodiments, the base wall **1813** can protrude even further, or can include one or more protrusions or gripping features, that can aid in removing the cap **1802** from the sleeve **1890**.

The cap **1802** can include a flange **1815** having an outer diameter larger than an inner diameter of the end of the sleeve **1890** that connects with the cap **1802**. The flange **1815** can prevent the cap **1802** from being inserted into the sleeve **1890** too deeply. In other or further embodiments, the flange **1815** can cooperate with an end surface of the sleeve **1890** to create a fluid-tight seal. For example, in some embodiments, a seal-

ing member, such as an O-ring, is included between the flange **1815** and the end of the sleeve **1890** to provide the fluid-tight seal.

The cap **1804** can include a housing **1850** that includes a sidewall **1852** and a base wall **1854**. The sidewall **1852** and the base wall **1854** can cooperate to define a disinfection chamber **1858**, which can include a pad **1870** therein. A portion of the sidewall **1852** can define a connection interface **1842**, which includes one or more threads **1843** in the illustrated embodiment. The connection interface **1842** can be configured to attach the cap **1804** to a medical connector in a secure yet selectively removable manner. Additionally, the connection interface **1842** can cooperate with a connection interface **1892** defined by the sleeve **1890** to couple the cap **1804** with the cap **1802**. The connection interface **1892** can include threading **1893** that is complementary to the threading **1843**. The interfaces **1842**, **1892**, when coupled with each other, can provide a fluid-tight seal between the cap **1804** and the sleeve **1890**. In other embodiments, the connection interfaces **1842**, **1890** can instead define a friction-fit seal, such as that provided by the illustrated embodiment of the connection interfaces **1840**, **1891** described above. In still other or further embodiments, a flange **1859** defined by the housing **1850** can cooperate with an end surface of the sleeve **1890** to create a fluid-tight seal, which can prevent evaporative loss of anti-septic from the pad **1870** and/or maintain the sterility of the disinfection chamber **1858**. For example, in some embodiments, a sealing member, such as an O-ring, is included between the flange **1859** and the end of the sleeve **1890** to provide the fluid-tight seal.

Features, usage, and operation of the assembly **1800** can resemble that of one or more of the assemblies described above. For example, when the assembly **1800** is in the pre-use condition, each disinfection chamber **1822**, **1858** can be defined by a separate housing **1812**, **1850**. Likewise, the caps **1802**, **1804** can be coaxial with each other, and the open ends of the caps **1802**, **1804** can face in opposite directions (e.g., towards each other). In the illustrated embodiment, each of the pads **1832**, **1870** is in an uncompressed or expanded state when the disinfection chamber **1822**, **1858** in which it is housed is in a pre-use, sealed condition.

However, certain differences can exist. For example, in the illustrated embodiment, the disinfection chambers **1822**, **1858** are in fluid communication with each other when the caps **1802**, **1804** are in the pre-use state. Moreover, in the illustrated embodiment, no portion of the housing **1850** of the cap **1804** is received within, or nested within, any portion of the housing **1810** of the cap **1802**.

FIGS. 25-29 illustrate another embodiment of an assembly **1900**, which can resemble one or more of the assemblies described above in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "19." As shown, for example, FIGS. 25 and 26, the assembly **1900** can include a female cap portion or female cap **1902** and a male cap portion or male cap **1904** that are integrally formed or otherwise permanently attached with each other. For example, the caps **1902**, **1904** can include a single, integrally molded housing **1910**. The female cap **1902** can be configured to couple with a female connector, and the male cap **1904** can be configured to couple with a male connector. In the illustrated embodiment, the caps **1902**, **1904** are in a coaxial arrangement. As shown, for example, in FIGS. 26 and 28, the assembly **1900** can include a pad **1970** that is received within one or more of the caps **1902**, **1904**. As shown, for example, in FIGS. 25 and 26, each cap **1902**, **1904** can be sealed shut in the pre-use configuration via a separate

cover **1934**, **1938**, respectively. Each cover **1934**, **1938** can include a tab **1935**, **1939**, respectively, that can aid in removal of the cover.

With continued reference to FIGS. 25-29, the housing **1910** can define at least a portion of each of the caps **1902**, **1904**. The housing **1910** includes a first sidewall **1912** that defines a first disinfection chamber **1922** and includes a second sidewall **1952** that defines a second disinfection chamber **1958**. As shown in FIG. 29, the first sidewall **1912** can define larger inner and outer diameters than those defined by the second sidewall **1952**. The housing **1910** can transition from the first sidewall **1912** and the first disinfection chamber **1922** to the second sidewall **1952** and the second disinfection chamber **1958** at a constriction or abutment **1920**. The housing **1910** can be substantially hollow such that the first and second disinfection chambers **1922**, **1958** are in fluid communication with each other. The housing **1910** can define another abutment **1921**, which is discussed further below.

As shown in FIGS. 26, 28, and 29, the female cap **1902** can include a connection interface **1930** that is configured to couple with a connection interface of a medical connector, such as a needleless injection site. The connection interface **1930** can include threading **1931**, which can be disposed at an interior of the sidewall **1912**. In some embodiments, the male cap **1902** includes one or more gripping features **1903** at an exterior surface of the sidewall **1912**. In the illustrated embodiment, the gripping features **1903** are raised areas. In other embodiments, the gripping features **1903** can include depressed areas. The gripping features **1903** can be formed in the shape of a company logo or any other suitable shape.

As shown in FIGS. 26, 27, and 29, the male cap **1904** can include a connection interface **1942** that is configured to couple with a connection interface of a medical connector, such as a medical attachment having a male luer. The connection interface **1942** can include threading **1943**, which can be disposed at an exterior surface of the sidewall **1952**. The cap **1904** can include one or more vents **1959**, which can be located at an end of the sidewall **1952**. The one or more vents can also extend along the length of sidewall **1952**. In the illustrated embodiment, a constriction, rim, or lip **1953** projects radially inwardly at the end of the sidewall **1952**, which can aid in maintaining the pad **1970** within the cap **1904**. In particular, the lip **1953** can define a smaller inner diameter than an outer diameter of the pad **1970** (see FIG. 29). The vents **1959** can comprise notches in the lip **1953**. The illustrated embodiment includes four vents **1959**, although more or fewer vents are possible.

With reference to FIG. 26, the pad **1970** can define a shape generally resembling a series of tiered cylinders. A rim **1971** can extend transversely, or radially outwardly, from a cylinder that has the smallest diameter. Another rim **1972** can extend transversely from a cylinder having an intermediate diameter. The largest cylinder can have a recess **1973** disposed therein. In certain embodiments, such as the illustrated embodiment, one or more extensions **1974** protrude from an end of the pad **1970** in a longitudinal direction. Each extension **1974** can include a groove **1975** therein, as discussed further below. In other embodiments, the one or more extensions **1974** are omitted.

With reference to FIG. 29, the pad **1970** can be secured within the housing **1910** in any suitable manner, and thus can resist translational movement in either direction that would cause the pad **1970** to exit the housing **1910** from either open end of the housing. For example, in the illustrated embodiment, interaction of the threads **1931** with a left end of the pad **1970** can prevent the pad **1970** from moving out of the housing **1910** in a leftward direction as a portion of a medical

connector (e.g., a male luer connector) is inserted into the housing 1910 from the right. As shown in FIG. 29, some portions of the pad 1970 can be compressed by the threads 1931, whereas the grooves 1975 of the extensions 1974 can accommodate the threads 1931. The enlarged tiered sections of the pad 1970, and the resultant interaction of the rims 1971, 1972 with the abutments 1920, 1921, respectively, can prevent the pad 1970 from moving out of the housing 1910 in the rightward direction as a portion of a medical connector (e.g., a needleless injection site) is advanced into the housing 1920 from the left. In other or further embodiments, the pad 1970 can be adhered to the housing 1910.

With reference to FIGS. 26 and 27, the cover 1938 can be secured to the housing 1910 in any suitable manner. For example, in some embodiments, an end of the cover 1938 is adhered or otherwise sealed to a sealing surface 1956 at an end of the sidewall 1952 so as to provide a hermetic seal. A side portion of the cover 1938 thus can cover the connection interface 1942 of the cap 1904. In other or further embodiments, a lower circumferential edge of the cover 1938 can be adhered or otherwise sealed to a sealing surface 1957 at a base end of the sidewall 1952 so as to provide a hermetic seal. With reference to FIGS. 26 and 28, the cover 1934 can be adhered or otherwise sealed to a sealing surface 1916 at an end of the sidewall 1912 of the housing 1910.

FIG. 30 illustrates an early stage of the coupling of a medical connector 2000 with the cap 1904. The medical connector 2000 can be of any suitable variety, and may be referred to as a male medical connector. The medical connector 2000 can include a housing 2005 that complies with ISO standards (e.g., ISO 594-1:1986 and ISO 594-2:1998). The housing 2005 can include a skirt 2010 that defines a connection interface 2012, which itself can include threading 2014. The housing 2005 can also include an elongated portion, a male projection, or male protrusion 2019, which can define a fluid passageway 2022. In the illustrated embodiment, the male protrusion 2019 is a male luer 2020.

Although the illustrated embodiment of the medical connector 2000 comprises a male luer-lock connector, it is to be understood that other embodiments of the cap 1904 can be compatible with other varieties of medical connectors 2000. For example, in some embodiments, the connection interface 2012 may comprise latches, prongs, or some other suitable attachment mechanism instead of (or in addition to) the threading 2014. In other or further embodiments, the male protrusion 2019 may be something other than a male luer. For example, the male protrusion 2019 may be a substantially cylindrical extension, or may define some other suitable shape.

In the illustrated embodiment, a tip of the male luer 2020 can contact an end surface of the pad 1970 prior to engagement of the connection interfaces 1942, 2012 (e.g., the threadings 1943, 2014) with each other. Accordingly, some compression of the pad 1970 may occur without assistance from the connection interfaces 1942, 2012. In other embodiments, the connection interfaces 1942, 2012 may engage one another prior to contact being made between the tip of the male luer 2020 and the end surface of the pad 1970, such as may occur when the pad 1970 is more recessed within the housing 1910 and/or the skirt 2010 and its connection interface 2012 are longer. In either case, in some embodiments, the connection interfaces 1942, 2012 can assist in the compression of the pad 1970. The desired antiseptic concentration level of the pad 1970 is determined by the volume required to fully coat and disinfect the medical connector 2000, while taking into consideration the evaporative loss that may occur during the shelf life of cap 1904.

FIG. 31 illustrates a later stage of the coupling of the medical connector 2000 with the cap 1904. As the male luer 2020 is advanced into the disinfection chamber 1958 of the cap 1904, it compresses the pad 1970 and causes antiseptic 1933 to egress therefrom. The pad 1970 can remain relatively fixed, rotationally, while the male luer 2020 is rotated and advanced further into the chamber 1958, which can effect a rubbing or scrubbing of the tip of the luer 2020, particularly as increased compression of the pad 1970 provides an increased force of the pad 1970 against the tip. The released antiseptic can fill an opening or volume of space between the sidewall 1952 of the housing 1910 and an outer surface of the male luer 2020, and can thereby disinfect the outer surface of the male luer 2020. Additionally, in the illustrated embodiment, the fluid passageway 2022 of the male luer 2020 is open such that antiseptic fluid 1933 may enter into it. In some instances, such as when the medical connector 2000 is connected to a fluid line 199 (see FIG. 5), it may be desirable to flush a portion of the fluid line after the cap 1904 has been disconnected from the medical connector 2000 so as to clear the male luer 2020 and any portion of the fluid line 199 into which antiseptic fluid 1933 has entered.

In certain embodiments, a seal can form between the lip 1953 and the male luer 2020 when the luer 2020 is advanced sufficiently far into the chamber 1958. The seal thus formed can be an interrupted seal, such that the seal is formed only at those regions where the luer 2020 and the lip 1953 are in contact with each other. Antiseptic 1933 can be permitted to exit from the chamber 1958 via the vents 1959. In some embodiments, the vents 1959 are sufficiently large to permit antiseptic 1933 to exit from the chamber 1958 freely once the antiseptic 1933 has been expelled from the pad 1970. Antiseptic 1933 that exits from the chamber 1958 through the vents 1959 can disinfect portions of the male luer 2020 that are proximal of the lip 1953.

In other embodiments, the vents 1959 are sufficiently small to prevent antiseptic 1933 from exiting from the chamber 1958 when a pressure within the chamber 1958 is the same or approximately the same as a pressure outside of the chamber 1958 (e.g., atmospheric pressure), and yet are sufficiently large to permit antiseptic 1933 to exit the chamber 1958 when the pressure within the chamber 1958 is significantly greater than the pressure outside of the chamber 1958, such as may result when the luer 2020 is being advanced deeper within the chamber 1958. The vents 1959 thus can permit selective egress of the antiseptic 1933 to aid in achieving the desired positioning of the male luer 2020, yet can maintain the antiseptic 1933 within the chamber 1958 in order to bathe a portion of the male luer 2020 once the male luer 2020 is positioned as desired. In still other embodiments, a fluid-tight seal is formed between the lip 1953 and the male luer 2020.

In certain embodiments, the pad 1970 may be recessed within the chamber 1958 to a greater degree when in the uncompressed state (e.g., when in the state shown in FIG. 30). Moreover, the threads 2014 of the connection interface 2012 and the threads 1943 of the connection interface 1942 can permit the antiseptic 1933 to pass through them, so as to provide additional venting of the chamber 1958. For example, threaded connection interfaces 2012, 1942 can permit antiseptic 1933 that has exited from the chamber 1958 to spiral about an outer surface of the second sidewall 1952 in a distal direction.

Each of FIGS. 32-34 illustrates the cap 1902 coupled with a separate needleless injection site 2040, 2060, 2080. As with other caps disclosed herein, the cap 1902 can be versatile so as to couple with a variety of different types of medical connectors in a secure fashion that disinfects each type of

29

medical connector. As can be seen in each of FIGS. 32-34, coupling of the needleless injection sites 2040, 2060, 2080 with the cap 1902 can effect compression of one end of the pad 1970 in a manner similar to that described above with respect to compression of the other end of the pad 1970. Compression of the pad 1970 and rotation of the needleless injection site 2040, 2060, 2080 can effect rubbing, swabbing, or scrubbing of the needleless injection site and disinfection thereof via the antiseptic 1933.

With reference to FIG. 32, the needleless injection site 2040 can comprise a Clave® port available from ICU Medical, Inc. The needleless injection site 2040 can include a housing 2042 that defines a connection interface 2044. The needleless injection site 2040 can further include an elastomeric seal 2046, which is shown in a closed configuration in which fluid access is not permitted into a fluid passageway 2048. Small crevices can exist between the housing 2042 and the elastomeric seal 2046 at an end of the needleless injection site 2040 that is inserted into disinfection chamber 1922. As the connection interface 2044 cooperates with the connection interface 1930 defined by the sidewall 1912 to draw the tip of the needleless injection site 2040 into the disinfection chamber 1922, the pad 1970 can be compressed so as to generally conform to the crevices. Compression of the pad 1970 likewise can expel antiseptic 1933, which, in some instances, can fill in portions of the crevices that the pad 1970 may not be able to contact directly. As the pad 1970 is compressed, the seal 2046 can remain closed so as to prevent antiseptic 1933 from entering the fluid passageway 2048. With reference again to FIG. 29, if present, the one or more extensions 1974, due to their positioning over the threads 1031, additionally can rub or scrub the side surfaces of the needleless injection site 2040. Thus, a thorough rubbing and disinfection of the needleless injection site 2040 can be accomplished via the cap 1902, and the performance of the cap 1902 in this regard can exceed that achieved via standard swabbing protocols and can be less susceptible to human error.

With reference to FIG. 33, the needleless injection site 2060 can comprise a Q-Syte® port available from Becton, Dickinson and Company. The needleless injection site 2060 can include a housing 2062 and an elastomeric seal 2066, which is shown in a closed configuration in which fluid access is not permitted into a fluid passageway 2068. As with the needleless injection site 2040, small crevices can exist between the housing 2062 and the elastomeric seal 2066. However, the crevices can exist at a side portion of the needleless injection site 2060, rather than at its tip. Nevertheless, as the needleless injection site 2060 is advanced into the cap 1902, the pad 1970 can be compressed so as to generally conform to these differently shaped crevices. Compression of the pad 1970 likewise can expel antiseptic 1933, which, in some instances, can fill in portions of the crevices that the pad 1970 may not be able to contact directly. The seal 2066 can be maintained in the closed position during the coupling procedure, so as to prevent any of the antiseptic 1933 from entering the fluid passageway 2068.

With reference to FIG. 34, the needleless injection site 2080 can comprise a SmartSite® port available from Cardinal Health, Inc. The needleless injection site 2080 can include a housing 2082 and an elastomeric seal 2086, which is shown in a closed configuration in which fluid access is not permitted into a fluid passageway 2088. As with the needleless injection sites 2040, 2060, small crevices can exist between the housing 2082 and the elastomeric seal 2086. However, these crevices can be in yet different positions than those of the needleless injection sites 2040, 2060. Nevertheless, as the needleless injection site 2080 is advanced into the cap 1902,

30

the pad 1970 can be compressed so as to generally conform to these differently shaped crevices. Compression of the pad 1970 likewise can expel antiseptic 1933, which, in some instances, can fill in portions of the crevices that the pad 1970 may not be able to contact directly. The seal 2086 can be maintained in the closed position during the coupling procedure so as to prevent any of the antiseptic 1933 from entering the fluid passageway 2088. Additionally, each of the needleless injection sites 2040, 2060, 2080 may advance into the cap 1902 by different amounts. The cap 1902 thus can be adaptable and versatile. Additional, non-limiting examples of needleless injection sites with which the cap 1902 can selectively couple include the Clearlink®. Site available from Baxter and the InVision-Plus® available from Rymed.

Features, usage, and operation of the assembly 1900 can resemble that of one or more of the assemblies described above. For example, in the illustrated embodiment, the pad 1970 is in an uncompressed or expanded state when the disinfection chambers 1922, 1958 in which it is housed are in a pre-use, sealed condition. Additionally, the caps 1902, 1904 are coaxial with each other with open ends that face in opposite directions. Likewise, the caps 1902, 1904 are connected to each other when the assembly 1900 is in a pre-use state.

However, certain differences can exist. For example, in the illustrated embodiment, the caps 1902, 1904 cannot be removed from each other. Moreover, the assembly 1900 includes a single pad 1970 that is used in both caps 1902, 1904. Although not shown in the drawings, it is understood that each cap 1902, 1904 can be coupled with a separate medical connector such that the pad 1970 is compressed from both ends when the caps 1902, 1904 are in a coupled state.

FIG. 35 illustrates another embodiment of an assembly 2100, which can resemble one or more of the assemblies described above, particularly the assembly 1900, in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "21." The assembly 2100 can include caps 2102, 2104, such as the caps 1902, 1904, that are fixedly, permanently, or integrally connected with each other. Covers such as the covers 1934, 1938, which are not shown in FIG. 35, can be used with the caps 2102, 2104. The assembly 2100 can include a single housing 2110 that defines two disinfection chambers 2122, 2158. The housing 2110 can include a partition 2120 that separates the disinfection chambers 2122, 2158 from each other such that the chambers 2122, 2158 are fluidly separated from one another. Each chamber 2122, 2158 can include a separate pad 2132, 2170 therein.

FIGS. 36 and 37 illustrate another embodiment of an assembly 2200, which can resemble one or more of the assemblies described above, particularly the assemblies 1900 and 2100, in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "22." The assembly 2200 can include a female cap 2202 and a male cap 2204 that are fixedly, permanently, or integrally connected with each other. The assembly can include a housing 2210, which can include a sidewall 2252 that defines a disinfection chamber 2258 and a connection interface 2242. Covers 2234, 2238, such as the covers 1934, 1938, can be used with the caps 2202, 2204.

The female cap 2202 can be substantially the same as the female cap 1902. However, the male cap 2204 can differ from the male cap 1904 in certain respects. For example, the cap 2204 can include a sealing member 2290. In the illustrated embodiment, the sealing member 2290 is shaped substantially as a conical disk. The sealing member 2290 can include a seal region 2292 which, in the illustrated embodiment, is rounded and projects toward an open end of the disinfection

31

chamber 2258 when situated therein. In other embodiments, the sealing member 2290 can define other shapes, such as, for example, square, oval, diamond, or other non-circular shapes. Further, the sealing member 2290 and the seal region 2292 may be a separate components that are integrally connected. The sealing member 2290 can include one or more ports 2294, which can define openings or channels 2293 that extend between opposing sides or faces of the sealing member 2290. Other configurations of the ports 2294 are also contemplated, such as, for example, self-sealing slits. In other configurations, such as some instances in which the sealing member 2290 is a non-circular shape, the ports can be eliminated since the antiseptic can flow around the sides of the sealing member 2290. In some embodiments, the sealing member 2290 can be relatively rigid so as to maintain a pre-formed shape, but may be configured to readily form a fluid-tight seal with a male luer of a medical connector. The sealing member 2290 can be formed of any suitable material, such as an elastomer or any thermoplastic such as polypropylene, polycarbonate, acrylonitrile butadiene styrene (ABS), polyvinyl chloride (PVC), or rigid or semi-rigid thermoset plastic. The sealing member 2290 can be formed in any suitable fashion, such as via molding or die cutting.

The sealing member 2290 can be coupled with a biasing element 2276, which can be configured to resist or oppose movement of the sealing member 2290. Stated otherwise, the biasing element 2276 can provide a bias to the sealing member 2290 in a direction of an initial position of the sealing member 2290, such as that shown in FIG. 37, once the sealing member 2290 has been displaced from that initial position. Accordingly, in the embodiment depicted in FIG. 37, the biasing element 2276 biases the sealing member 2290 in a proximal direction when the sealing member 2290 is displaced distally. The terms “proximal” and “distal,” when used herein relative to a cap, are such that a medical device is inserted into a proximal end of the cap and advanced toward a distal end of the cap. Accordingly, in the illustrated embodiment, the proximal ends of the caps 2202, 2204 are at opposite ends of the assembly 2200 and the distal ends of the caps 2202, 2204 are fixedly joined with each other.

The male cap 2204 can include a rim 2253, similar to the lip 1953, which can include one or more vents 2259. However, in the illustrated embodiment, the rim 2253 is more recessed from a proximal end of the cap 2204 (e.g., deeper within the cavity 2258). A portion of a pad 2270 that is positioned within the disinfection chamber 2258 can be shorter than a corresponding portion of the pad 1970, so as to more readily fit below the more recessed rim 2253. As shown in FIG. 37, the pad 2270 can be seated beneath the sealing member 2290, and the sealing member 2290 can be seated beneath the rim 2253 when the male cap is in the pre-use configuration. In some embodiments, the pad 2270 is in an uncompressed state (e.g., a longitudinally uncompressed state) when situated as shown in FIG. 37. The pad 2270 can include an antiseptic 2233 therein.

In the illustrated embodiment, the pad 2270 is resiliently compressible such that the biasing element 2276 comprises the pad 2270. Stated otherwise, compression of the pad 2270 gives rise to a biasing force that tends to restore the pad 2270 to its uncompressed state. The biasing force may increase with greater compression of the pad 2270. In some embodiments, the pad 2270 is fixedly secured to the sealing member 2290, such as by an adhesive or any suitable lamination technique. In other embodiments, the sealing member 2290 is not secured to the pad 2270, but movement of the sealing member 2290 within the disinfection chamber 2258 can nev-

32

ertheless be constrained by a proximal end of the pad 2270 and a distal edge of the rim 2253.

The sealing member 2290 can aid in maintaining the antiseptic 2233 within the pad 2270 when the cap 2204 is in a pre-use condition. For example, in some embodiments, only a small surface area of the proximal end of the pad 2270 that is directly beneath the ports 2294 of the sealing member 2290 is directly exposed to air when the proximal end of the cap 2204 is uncovered. Accordingly, evaporative loss of the antiseptic 2233 can be slowed. Moreover, in other or further embodiments, the ports 2294 may be defined by channels that are sufficiently small to prevent liquid antiseptic 2233 from passing through them when the pressure on both sides of the sealing member 2290 is balanced. However, the ports 2294 may permit liquid antiseptic 2233 to pass through them when the pressure on one side of the sealing member 2290 is greater than the pressure on the other side of the sealing member 2290, as discussed further below. The pad 2270 itself can also be configured to retain the antiseptic 2233 until it is compressed.

In some embodiments, an outer edge of the sealing member 2290 can form a fluid-tight seal with an inner surface of the sidewall 2252 when the cap 2204 is in the pre-use state. In further embodiments, the seal can be maintained as the sealing member 2290 is moved distally within the disinfection chamber 2258 such that liquid antiseptic 2233 is only permitted to bypass the sealing member 2290 through the ports 2294. In other embodiments, an outer edge of the sealing member 2290 may not form a fluid-tight seal with the sidewall 2252, whether initially or after having been moved from the pre-use condition, such that antiseptic 2233 can bypass the sealing member 2290 around its outer edge.

FIG. 38 illustrates an early stage of coupling a medical connector 2000 with the cap 2204. A tip 2021 of a male luer 2020 contacts the seal region 2292 of the sealing member 2290. In the illustrated embodiment, a portion of the sealing member 2290 extends into a lumen 2022 of the connector 2000 such that the contact is primarily between an inner edge of the tip 2021 and a thin band of the sealing member 2290. Such an arrangement can assist in forming a fluid-tight seal due to a relatively higher pressure that results between the tip 2021 and the sealing member 2290 when forces (e.g., an insertion force on the tip 2021 and an oppositely directed biasing force on the sealing member 2290) are distributed over relatively smaller areas. Such an arrangement likewise can allow antiseptic to contact much or all of an external surface of the luer 2020, including a distal surface of the tip 2021.

In the illustrated embodiment, contact between the tip 2021 and the sealing member 2290 occurs just prior to engagement of a connection 2012 of the connector 2000 with the connection interface 2242. In other embodiments, the connection interfaces 2012, 2242 can engage each other prior to contact between the tip 2021 and the sealing member 2290. In either case, as the connection interfaces 2012, 2242 cooperate with each other to connect the cap 2204 to the medical connector 2000 (e.g., as the cap 2204 is threaded onto the connector 2000), a fluid-tight seal is formed or maintained between the seal region 2292 of the sealing member 2290 and the tip 2021 of the male luer 2020.

FIG. 39 illustrates a late or final stage of coupling the medical connector 2000 with the cap 2204. To arrive at this stage, the cap 2204 is advanced over the male luer 2020 to a greater extent. As a result, the luer 2020 is advanced further into the disinfection chamber 2258, thereby moving the sealing member 2290 distally and compressing the pad 2270. Compression of the pad 2270 forces antiseptic 2233 out of the

33

pad 2270. Moreover, as the pad 2270 is compressed, the volume of the portion of the disinfection chamber 2258 that is on the distal side of the sealing member 2290 is reduced, thereby increasing the pressure in that portion of the disinfection chamber 2258. As a result, the antiseptic 2233 is forced through the ports 2294 into the portion of the disinfection chamber 2258 on the proximal side of the sealing member 2290. Due to the seal between the sealing member 2290 and the luer 2020, the antiseptic 2233 is prevented from entering the lumen 2022 of the luer 2020, and thus is prevented from contacting or mixing with medical fluid that may be within the lumen 2022 when the cap 2204 is coupled with the medical connector 2000 and/or that may flow through the lumen 2022 after the cap 2204 has been removed from the connector 2000. The antiseptic 2233 can fill the open region of the disinfection chamber 2258 on the proximal side of the sealing member 2290.

As the luer 2020 is advanced distally in the disinfection chamber 2258, another seal, or partial seal, can be formed between an outer surface of the luer 2020 and an inner surface of the rim 2253. Where present, the seal can be substantially fluid-tight. However, the vents 2259 can interrupt the seal so as to permit antiseptic 2233 to exit from the chamber 2258. In further embodiments, a proximal or distal surface of the rim 2253 can be covered with a covering, such as, for example, Tyvek® or other nonwoven material, which can filter microbes from the air entering the disinfection chamber 2258 via the vents 2259, yet can permit antiseptic 2233 to pass through it so as to exit from the disinfection chamber 2258. In other embodiments, the rim 2253 is uninterrupted (e.g., is free of vents 2259) such that an uninterrupted seal can be formed between the rim 2253 and the male luer 2020.

With continued reference to FIG. 39, when the cap 2204 is connected to the medical device 2000, antiseptic 2233 can fill the disinfection chamber 2258 between the seals formed by contact between the luer 2020 and the sealing member 2290 and between the luer 2020 and the rim 2253. An outer surface of the luer 2020 between these two sealed regions of the luer 2020 thus can be bathed in the antiseptic 2233 and disinfected thereby. As mentioned with respect to the assembly 1900, the rim 2253 can be positioned at a deeper or a more shallow position relative to the housing 2252, which can result in disinfection of a smaller or greater surface area of the luer 2020, respectively. In certain embodiments in which the proximal seal between the rim 2253 and the male luer 2020 is interrupted (e.g., where the rim 2253 includes vents 2259), antiseptic 2233 can be permitted to exit from the chamber 2258. In some embodiments, the vents 2259 are sufficiently large to permit antiseptic 2233 to exit from the chamber 2258 freely once the antiseptic 2233 has been expelled from the pad 2270. Antiseptic 2233 that exits from the chamber 2258 through the vents 2259 can disinfect portions of the male luer 2020 that are proximal of the rim 2253.

When the cap 2204 is removed from the medical device 2000, it can naturally or automatically return to the orientation shown in FIG. 37. In particular, the resiliently compressible pad 2270 can move the sealing member 2290 distally to its pre-use position. In so doing, the expanding portion of the disinfection chamber 2258 that is distal of the sealing member 2290 can have a decreased pressure such that antiseptic 2233 is forced back through the ports 2294 of the sealing member 2290 in a distal direction. The expanding pad 2270 can soak up or absorb the returned antiseptic 2233. The expanding pad 2270 can provide sufficient force to the sealing member 2290 to maintain the seal with the seal region 2292

34

such that antiseptic 2233 is prevented from entering into the lumen 2022 as the cap 2204 is decoupled from the medical device 2000.

In other embodiments, the caps 2202, 2204 can more closely resemble the caps 2102, 2104 described above. For example, the cap 2202 can have a separate pad, which is spaced from or separated from the pad 2270 by a partition. In still other embodiments, the caps 2202, 2204 can be readily disconnected from each other, and in further embodiments, may be configured for selective reconnection with each other in manners such as those described with respect to other caps herein.

FIGS. 40-45 illustrate another embodiment of a cap 2304, which can resemble one or more of the caps described above in certain respects. For example, the cap 2304 can replace or readily be altered to replace any of the caps 1004, 1104, 1204, 1304, 1404, 1504, 1604, 1804, 1904, 2104, 2204 in the systems 1000, 1100, 1200, 1300, 1400, 1500, 1600, 1800, 1900, 2100, 2200 described above. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "23."

The cap 2304 can include a housing 2350 having a sidewall 2352 and a base wall 2354 that define a disinfection chamber 2358. The housing 2350 can further include a coupling interface 2342. The cap 2304 can include a biasing member 2376, which can comprise a resiliently compressible pad 2370, which can in turn include an antiseptic 2333 therein. The cap 2304 can further include a sealing member 2390, which includes a sealing region 2392 and one or more ports 2394, which include channels 2393 that extend through the sealing member 2390.

The sidewall 2352 of the housing 2350 can be different from that of the illustrated embodiment of the cap 2204. In particular, at least a portion of an inner surface of the sidewall 2352 (e.g., a proximal region thereof) can be tapered so as to form a fluid-tight seal with a male luer. For example, at least a portion of the inner surface of the sidewall 2352 can comply with ISO standards (e.g., ISO 594-1:1986 and ISO 594-2:1998) for forming a seal with a male luer. In the illustrated embodiment, the sidewall 2352 is devoid of any inwardly projecting rims that could interrupt complementarities between the sidewall 2352 and a male luer.

FIGS. 41-45 illustrate consecutive stages of the cap 2304 being coupled with a medical device 2000. As shown in FIG. 41, a tip 2021 of a male luer 2020 can be received within the disinfection chamber 2358 prior to contacting the sealing member 2390. Stated otherwise, the sealing member 2390 can be recessed relative to a proximal end of the sidewall 2352 by a distance that is sufficiently great to permit at least a portion of the male luer 2020 to be received within the sidewall 2352 before the male luer contacts the sealing member 2390.

In FIG. 42, the luer 2020 has been advanced further within the disinfection chamber 2358 so as to contact the seal region 2392 of the sealing member 2390. In the illustrated embodiment, the connection interface 2342 of the cap 2304 engages a connection interface 2012 of the medical connector 2000 just prior to contact being made between the tip 2021 of the luer 2020 and the seal region 2392. The connection interfaces 2342, 2012 thus can assist in the creation of a fluid-tight seal between the luer 2020 and the sealing member 2390.

The sealing member 2390 can remain in the initial or pre-use position that is shown in both FIGS. 41 and 42 until the seal has been formed between the luer 2020 and the sealing member 2390. Further advancement of the luer 2020 into the disinfection chamber 2358 can strengthen the seal due to the spring force that arises as the pad 2370 is com-

35

pressed. When the sealing member **2390** is in the initial orientation, the ports **2394** can prevent antiseptic **2333** from passing through them. Also, the composition of the pad **2370** or the affinity of the pad **2370** to absorb antiseptic **2333** will determine the retention of the antiseptic **2333** in the pad **2370**.

In FIG. **43**, the luer **2020** has been advanced slightly further into the disinfection chamber **2358**, thereby compressing the pad **2370** somewhat and forcing antiseptic **2333** through the ports **2394**. As schematically shown by wavy lines, the antiseptic **2333** begins to fill the space between the sealing member **2390** and the tip **2021** of the luer **2020**. The antiseptic **2333** does not, however, enter into a lumen of the luer **2020** due to the seal between the luer **2020** and the sealing member **2390**.

In FIG. **44**, the luer **2020** has been advanced even further into the disinfection chamber **2358**, thereby compressing the pad **2370** to a greater extent and forcing additional antiseptic **2333** through the ports **2394**. Although the outer surface of the luer **2020** appears to be nearly parallel to and in contact with an inner surface of the tapered portion of the sidewall **2352**, a seal has not yet been formed in this area. Accordingly, the antiseptic **2333** can fill not only the space between the sealing member **2390** and the tip **2021** of the luer **2020**, but also the small amount of space between the luer **2020** and the sidewall **2352**. The luer **2020** thus can be covered in antiseptic **2333** and disinfected thereby. In some embodiments, the antiseptic **2333** remains within portions of the space between the luer **2020** and the sidewall **2352** only temporarily, as additional advancement of the luer **2020** can close this space to form a seal.

FIG. **45** illustrates a final or fully coupled stage, or an end-of-stroke orientation, in which the luer **2020** has been advanced even further into the disinfection chamber **2358** such that the luer **2020** forms a seal with the sidewall **2352**. Antiseptic **2333** can be retained in all open portions of the disinfection chamber **2358** that are between the seal formed by the luer **2020** and the sealing member **2390** and the seal formed by the luer **2020** and the sidewall **2352**. In the illustrated embodiment, only a small portion of the luer **2020**, which includes the tip **2021**, is in continual contact with the portion of the antiseptic **2333** thus retained. This portion of the luer **2020** can be bathed by the antiseptic **2333** and disinfected thereby. In other embodiments, larger portions of the luer **2020** can be bathed.

In some embodiments, the seal formed by the luer **2020** and the sealing member **2390**, and/or the seal formed by the luer **2020** and the sidewall **2352**, can be accomplished by appropriate sizing of the individual components. In certain embodiments, the sizing is subject to and based upon the standardized ISO luer taper specification, such as discussed elsewhere herein.

In certain instances, the a distance to which a particular luer **2020** is inserted into the chamber **2358** can vary from the distance to which a different luer **2020** may be inserted prior to sealing with the sidewall **2352**. Similarly, in certain manufacturing processes, the dimensions of the sidewall **2352** may vary slightly from one cap **2304** to another, within a tolerance range, such that a given luer **2020** may extend into the chamber **2358** of one cap **2304** to a greater or lesser extent than it may extend into the chamber **2358** of another cap **2304**.

For example, all manufactured components, such as the luer **2020** and the sidewall **2352** of the cap **2304**, can vary within tolerance limits that range between a maximum material condition and a minimum material condition. The maximum and minimum material conditions can correspond to large and small components, respectively. All combinations of maximum and minimum material conditions for interoper-

36

erable components can be considered to determine a maximum mating depth and a minimum mating depth for components that are within their respective tolerance ranges. Such maximum and minimum mating depths can represent the upper and lower values of an axial range of engagement.

For example, where both interoperable components (e.g., the luer **2020** and the sidewall **2352**) exhibit their respective minimum material conditions, the maximum mating depth may be achieved. This maximum mating depth may also be referred to as a maximum stroke. In other words, the minimum material condition corresponds to the loosest fit. Conversely, the maximum material condition corresponds to the tightest fit of the taper.

In some embodiments, the axial range of engagement for the sidewall **2352** of the cap **2304** with a luer **2020** that is within standard tolerances is about 2 millimeters. In certain of such embodiments, a minimum dispense stroke of about 1 millimeter indicates that the components have been dimensioned such that for the tightest fitting luer **2020** (i.e., maximum material condition), a minimum of about 1 millimeter dispense stroke will exist. Hence, in this example, for any luer **2020** within an acceptable tolerance range, a minimum of about 1 millimeter of movement of the seal member **2390** can exist prior to engagement between the luer **2020** and the sidewall **2352**. Other axial ranges of engagement, and other maximum and minimum dispense strokes, are also possible. For example, in various embodiments, an axial range of engagement for the cap **2304** can be no more than about 1, 2, 3, or 4 millimeters or no less than about 1, 2, 3, or 4 millimeters. In other or further embodiments, a minimum dispense stroke is no greater than about 0.5, 1.0, 1.5, or 2.0 millimeters.

FIG. **46** illustrates another embodiment of a cap **2304'** in an end-of-stroke orientation. The cap **2304'** is substantially the same as the cap **2304** just discussed. For example, a substantial portion of an interior surface of the sidewall **2352** is tapered so as to be complementary to the male luer **2020**. However, the sidewall **2352** includes one or more venting channels or vents **2353** therein that prevent the sidewall **2352** from fully sealing with the male luer **2020**. The illustrated vent **2353** extends from a proximal end of the sidewall **2352** in a longitudinal direction to a position just beyond (or distal of) an end-of-stroke position of the tip **2021** of the male luer **2020**. Accordingly, after liquid-imperious contact is established between the male luer **2020** and those portions of the sidewall **2352** having a taper complementary to the male luer **2020**, antiseptic **2333** can still exit the chamber **2358** via the vent **2353**. In certain embodiments, the coupled connection interfaces **2012**, **2342** can permit the antiseptic **2333** to pass through them so as to provide additional venting of the chamber **2358**. For example, threaded connection interfaces **2012**, **2342** can permit antiseptic **2333** that has exited from the chamber **2358** to spiral about an outer surface of the sidewall **2352** and/or otherwise seep in a distal direction.

In various embodiments, the cap **2304'** comprises one or more, two or more, three or more, or four or more vents **2353**. One or more of the vents **2353** can be substantially linear in a longitudinal direction (as shown) and/or can define alternate orientations. For example in some embodiments, one or more vents **2353** can be angled relative to a longitudinal axis of the cap **2304'** (e.g., can be helical), or can include a portion that is so angled. One or more of the vents **2353** can extend any suitable distance between the proximal end of the sidewall **2352** and the base wall **2354**. For example, in various embodiments, the vents **2353** extend no less than about 1/4, no less than about 1/3, no less than about 1/2, no less than about 2/3, or no less than about 3/4 the distance between the proximal end of the sidewall **2352** and the base wall **2354**. Where suitable, one

37

or more vents **2353** can be incorporated into embodiments of the caps described above, as well as those described hereafter.

FIG. **47** illustrates another embodiment of a cap **2404**, which can resemble one or more of the caps described above, particularly the caps **2304**, **2304'**, in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "24." The cap can include a housing **2450**, a biasing member **2476**, and a sealing member **2490**. The housing **2450** can have a sidewall **2452** and a base wall **2454** that define a disinfection chamber **2458**. The housing **2450** can further define one or more ports **2494**. In the illustrated embodiment, the port **2494** comprises a longitudinal channel or groove **2459** extending a distance along the sidewall **2452**. The longitudinal distance which the groove **2459** extends can be varied as desired. In some embodiments, the longitudinal distance is greater than or equal to a stroke length through which the sealing member **2490** is displaced when the cap **2404** is connected to a medical connector for reasons discussed hereafter, although such is not required.

The sealing member **2490** can be devoid of channels, and may act in a plunger-like fashion. The sealing member **2490** can form a liquid-impermeable seal with the sidewall **2452** when in the pre-use configuration shown in FIG. **47**. However, distal displacement of the sealing member **2490** can move a proximal end of the sealing member **2490** past a proximal end of the port **2494**, thereby opening the port **2494**. This can permit an antiseptic **2433** to be forced from a pad **2470** by the displaced sealing member **2490** and moved through the port **2494**, thereby entering the portion of the disinfection chamber **2458** which is proximal to the sealing member **2490**. In embodiments where the longitudinal length of a groove **2459** is greater than or equal to a stroke length through which the sealing member **2490** is displaced, antiseptic **2433** can be permitted to pass through the groove **2459** during all stages of the displacement. As can be appreciated from the foregoing, the port **2494** can comprise an opening, spacing, or gap that exists between a periphery or outermost perimeter of the sealing member **2490** and the sidewall **2452**. The groove **2459** thus can also be described as a gap.

In the illustrated embodiment, the biasing member **2476** includes a resiliently compressible pad **2477**, although additional or other components are possible (e.g., a compressible spring). The pad **2477** is separated from the pad **2470** by a barrier **2478**, which can comprise any suitable material capable of preventing passage of the antiseptic **2433**. For example, in some embodiments, the barrier **2478** comprises a plastic film or disk. The barrier **2478** thus can restrain the antiseptic **2433** to a predetermined portion of the disinfection chamber **2458** that is closest to the sealing member **2490**. Such an arrangement can permit the usage of less antiseptic **2433**, as a greater portion of the antiseptic **2433** can be expelled from the pad **2470**.

In some embodiments, both of the pads **2470**, **2477** comprise the same material, while in other embodiments different materials may be selected for desired properties. For example, the pad **2470** may comprise a more absorbent foam while the pad **2477** may comprise a springier foam. In some embodiments, both pads **2470**, **2477** can provide a bias to the sealing member **2490** when they are compressed such that the biasing member **2476** can be said to include both pads **2470**, **2477**. In still other or further embodiments, the biasing member **2476** can comprise a spring or other at least somewhat resiliently deformable element in place of the pad **2477**.

Although in the illustrated embodiment, the sealing member **2490** is devoid of ports, other embodiments can include ports in addition to or instead of the channels **2494** in the

38

sidewall **2452**. Likewise, it is understood that channels **2494** could be included in other embodiments of caps described herein in addition to or in place of ports through sealing members. Similar substitutions and rearrangements are possible with respect to other features of the cap **2404**, such as the two-part biasing member **2476** and the barrier **2478**.

FIGS. **48** and **49** illustrate another embodiment of a cap **2504**, which can resemble one or more of the caps described above, particularly the caps **2304**, **2304'**, **2404**, in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "25." The cap can include a housing **2550**, a biasing member **2576**, and a sealing member **2590**. The housing **2550** can have a sidewall **2552** that defines a disinfection chamber **2558**. The housing **2550** can further define a bathing recess **2555** within the disinfection chamber **2558**, which can be included in a tapered region at a proximal end of the sidewall **2552**. As shown in FIG. **49**, antiseptic **2533** can be retained within the bathing recess **2555** and maintained in contact with an outer surface of a male luer **2020**. Accordingly, a greater portion of the luer **2020** than just a tip **2021** thereof can be maintained in contact with the antiseptic **2533** when the luer **2020** is in an end-of-stroke position.

The housing **2550** can further define a vent **2598** having a cover **2599**. The vent **2598** can be defined by a channel that extends from an interior of the sidewall **2552** to an exterior thereof. A distal end of the vent **2598** can open into the bathing recess **2555**, and a proximal end of the vent **2598** can be at a proximal end of the sidewall **2552**. The vent **2598** can function in manners such as those described above with respect to other vents.

In some embodiments, the cover **2599** can comprise a material, such as, for example, Tyvek® or other nonwoven material, which can filter microbes from the air entering the disinfection chamber **2558** via the vent **2598** and can permit antiseptic **2533** to exit from the disinfection chamber **2558**.

With continued reference to FIGS. **48** and **49**, the antiseptic **2533** can be held within the disinfection chamber **2533** without pads. A biasing member **2576** can include a compression spring **2579**. A sealing member **2590** can form a fluid-tight seal with the sidewall **2552** to retain the antiseptic **2533** within a reservoir portion of the chamber **2533**. While the sealing member **2590** can resemble any of the sealing members discussed above, the illustrated embodiment includes ports **2594** that have two-way valves **2597** therein. In various embodiments, the two-way valves **2597** are formed of self-sealing slits and/or the two-way valves **2597** can be disposed within channels through the sealing member **2590**.

FIG. **50** illustrates another embodiment of an assembly **2600**, which can resemble one or more of the assemblies described above, particularly the assembly **1800**, in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "26." The assembly **2600** can include a cap **2602** and cap **2604** that are coupled with each other when in a pre-use state and that can be removed from each other. In particular, the caps **2602**, **2604** can be coupled with each other via a sealing mechanism **2689**. In the illustrated embodiment, the caps **2602**, **2604** are coupled with each other via a sealing sleeve **2691**.

With reference to FIG. **51**, the cap **2602** can include a housing **2610**, which can include a sidewall **2612** and a base wall **2613**. The housing **2610** can include a substantially cylindrical region toward a proximal end thereof, which can be flattened and taper toward the narrower base wall **2613**. Such a shape can provide a convenient handle at a distal end of the cap **2602**. A cavity **2623** can be formed at an interior of

the sidewall **2612** and the base wall **2613**, which can reduce material costs for the cap **2602**.

The sidewall **2612** can define a disinfection chamber **2622**, which can include a connection interface **2630** that includes threads **2631**. The connection interface **2630** can be configured to attach the cap **2602** to a medical connector in a secure yet selectively removable manner. The disinfection chamber **2622** can further include a pad **2632**.

A proximal surface **2624** of the sidewall **2612** can define a seal inhibitor **2625** that is configured to prevent the cap **2602** from forming a fluid-tight seal with a medical connector, such as a needleless injection site, when it is coupled therewith. For example, in the illustrated embodiment, the proximal surface **2624** of the sidewall **2612** is substantially castellated such that it defines a series of offset contact regions **2626** and venting regions **2627**. In the illustrated embodiment, each of the contact regions **2626** and venting regions **2627** includes a planar surface that is substantially perpendicular to a longitudinal axis of the cap **2602**. The contact regions **2626** are at a more proximal position than are the venting regions **2627**. Accordingly, when the cap **2602** is coupled with certain embodiments of needleless injection sites, the contact regions **2626** can come into contact with surfaces of the needleless injection sites that project radially outwardly, whereas the venting regions **2627** can avoid making any such contact.

For example, in arrangements such as those depicted in FIGS. **32** and **33**, the cap **2602** can be advanced onto a needleless injection site **2040**, **2060** sufficiently to bring the planar surfaces of the contact regions **2626** into contact with radially outwardly projecting planar surfaces of the needleless injection site **2040**, **2060**. However, in such a configuration, the venting regions **2627** would be spaced from the outwardly projecting planar surface of the needleless injection site **2040**, **2060** so as not to form a seal therewith. The cap **2602** thus would be permitted to vent via the venting regions **2627**. As further discussed below, other configurations of the seal inhibitor **2625** are also possible. Moreover, in some embodiments, the cap **2625** is devoid of a seal inhibitor **2625**.

With reference to FIGS. **51** and **53**, an exterior surface of the sidewall **2612** can define another connection interface **2640** that is configured to couple the cap **2602** with a connection interface **2695** of the sleeve **2691**. In the illustrated embodiment, the connection interfaces **2640**, **2695** couple with each other via a friction-fit engagement. The friction fit can be sufficiently strong to provide a fluid-tight seal between the cap **2602** and the sleeve **2691**, yet can allow the cap **2602** to be removed from the sleeve **2691** via mere manipulation by a medical practitioner (e.g., without the use of ancillary tools). The fluid-tight seal can prevent evaporative loss of antiseptic from the pad **2632** and/or can maintain the sterility of the disinfection chamber **2622**. In other or further embodiments, the connection interfaces **2640**, **2695** can include threads or other suitable attachment features.

The cap **2602** can include a flange **2615** having an outer diameter larger than an inner diameter of the end of the sleeve **2691** that connects with the cap **2602**. The flange **2615** can prevent the cap **2602** from being inserted into the sleeve **2691** too deeply. In other or further embodiments, the flange **2615** can cooperate with an end surface of the sleeve **2691** to create a fluid-tight seal (see FIG. **54**). For example, in some embodiments, a sealing member, such as an O-ring, is included between the flange **2615** and the end of the sleeve **2691** to provide the fluid-tight seal.

With reference to FIG. **52**, the cap **2604** can include a housing **2650** that includes a sidewall **2652** and a base wall **2654**, which can cooperate to define a cavity **2659** similar to the cavity **2623** described above. Likewise, the housing **2650**

can define a substantially cylindrical shape at a proximal end of the cap **2604**, which flattens and tapers toward the base wall **2654**.

The sidewall **2652** can define a disinfection chamber **2658**, which can include a sealing member **2690** and a biasing member **2676**. The sealing member **2690** and the biasing member **2676** can resemble any suitable combination of these components, and features thereof, described above. In the illustrated embodiment, the biasing member **2676** comprises a pad **2670**.

A portion of the sidewall **2652** can define a connection interface **2642**, which includes one or more threads **2643** in the illustrated embodiment. The connection interface **2642** can be configured to attach the cap **2604** to a medical connector in a secure yet selectively removable manner.

With reference to FIGS. **52** and **53**, the sidewall **2652** can define an additional connection interface **2680**, which can cooperate with a connection interface **2692** defined by the sleeve **2691** to couple the cap **2604** with the cap **2602**. The connection interface **2680** of the cap **2604** can include a groove **2683**, which may be substantially annular and extend about a periphery of the cap **2604**. The connection interface **2692** of the sleeve **2691** can include a complementary inward projection **2693**, which likewise can be substantially annular. The interfaces **2680**, **2692**, when coupled with each other, can provide a fluid-tight seal between the cap **2604** and the sleeve **2691**. In other embodiments, the connection interfaces **2680**, **2692** can instead define a friction-fit seal, such as that provided by the illustrated embodiment of the connection interfaces **2640**, **2695** described above. In still other or further embodiments, a flange **2661** defined by the housing **2650** can cooperate with an end surface of the sleeve **2691** to create a fluid-tight seal (see FIG. **54**), which can prevent evaporative loss of antiseptic from the pad **2670** and/or maintain the sterility of the disinfection chamber **2658**. For example, in some embodiments, a sealing member, such as an O-ring, is included between the flange **2659** and the end of the sleeve **2691** to provide the fluid-tight seal.

With reference to FIG. **54**, when the assembly **2600** is in a fully coupled or pre-use state, a proximal end of the sidewall **2652** of the cap **2604** is received within the cavity **2622** defined by the sidewall **2612** of the cap **2602**. In some embodiments, the sidewall **2652** of the cap **2604** does not contact any portion of the sidewall **2612** of the cap **2602** in this pre-use configuration, nor does the sidewall **2652** contact the pad **2632** that is within the cap **2602**. Such a configuration can result in a relatively compact assembly **2600** in which each cap **2602**, **2604** can be quickly prepared for use. In other embodiments, the sidewalls **2652**, **2612** may contact or couple with each other (e.g., via the connection interfaces **2642**, **2630**) and/or the sidewall **2652** may contact the pad **2632** in the pre-use configuration. In still other embodiments, the sidewalls **2652**, **2612** may be spaced from each other such that the sidewall **2652** is not received within the cavity **2622**.

FIG. **55** illustrates another embodiment of an assembly **2700**, which can resemble one or more of the assemblies described above, particularly the assemblies **1800**, **2600**, in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to "27." The assembly **2700** can include a cap **2702** and cap **2704** that are coupled with each other when in a pre-use state via a sealing sleeve **2791**.

The assembly **2700** can include one or more separation assists **2707**, **2708**, which can aid in removal of the cap **2702** and/or the cap **2704** from the sleeve **2791**. In the illustrated embodiment, the separation assists **2707**, **2708** each includes a complementary recess/protrusion pair. In particular, a

41

flange 2715 of the cap 2702 defines a recess 2716 that is sized and dimensioned to receive therein a protrusion 2799 that is defined by an edge 2798 of the sleeve 2791. The recess 2716 and the protrusion 2799 cooperate with each other as a separation assist 2707. Similarly, a flange 2761 of the cap 2704 defines a recess 2762 that is sized and dimensioned to receive therein a protrusion 2797 that is defined by an edge 2796 of the sleeve 2791. The recess 2762 and the protrusion 2797 cooperate with each other as a separation assist 2708.

Focusing now on the separation assist 2707, the recess 2716 can include two substantially planar surfaces that meet at a rounded base. The planar surfaces can be at an angle relative to a plane that is perpendicular to a longitudinal axis (or central axis) of the cap 2702 (e.g., a plane defined by portion of the flange 2715 that does not include the recess 2716, in the illustrated embodiment). For example, in the illustrated embodiment, each of the planar surfaces of the recess 2716 defines an angle of about 20 degrees relative to the perpendicular plane. Similarly, the protrusion 2799 can include two substantially planar surfaces that meet at a rounded apex. The planar surfaces can be at the same angle relative to the perpendicular plane as are the planar surfaces of the recess 2716. For example, in the illustrated embodiment, each of the planar surfaces of the protrusion 2799 defines an angle of about 20 degrees relative to a plane defined by the portion of the edge 2798 of the sleeve 2791 that does not include the protrusion 2799.

When the cap 2702 is joined with the sleeve 2791 in a pre-use configuration (similar to that shown in FIG. 54), the planar portions of the recess 2716 and of the protrusion 2799 can be in close proximity to each other or can contact each other. In order to separate the cap 2702 from the sleeve 2791, the cap 2702 can be rotated relative the sleeve 2791, which can cause opposing planar surfaces of the recess 2716 and the protrusion 2799 to contact each other and slide past each other. This interaction can convert the rotational movement of the cap 2702 about a common axis of the cap 2702 and the sleeve 2791 into translational movement of the cap 2702 away from the sleeve 2791 along the common axis. Due to the symmetry of the planar surfaces of each of the recess 2716 and the protrusion 2799 of the illustrated embodiment, the cap 2702 can be rotated in either direction to achieve the same lifting action via the separation assist 2707 that tends to move the cap 2702 away from the sleeve 2791.

In other embodiments, the separation assist 2707 can be configured to aid in separating the cap 2702 from the sleeve 2791 only when the cap 2702 is rotated in one predetermined direction (e.g., either clockwise or counterclockwise). For example, one planar surface may be at about 20 degrees relative to the perpendicular plane, whereas the other planar surface may be at a about 90 degrees relative to the perpendicular plane (i.e., approximately parallel to or extending through a central axis of the cap 2702). In other embodiments, one or more of the planar surfaces of the recess 2716 and/or the protrusion 2799 may be at larger or smaller angles relative to the perpendicular plane. For example, in various embodiments, a set of complementary planes may be at an angle of no more than about 15 degrees, no more than about 20 degrees, no more than about 30 degrees, no more than about 45 degrees, no more than about 60 degrees, or no more than about 75 degrees. Other configurations of the separation assist 2707 are also possible. For example, in some embodiments, the complementary surfaces of the recess 2716 and the protrusion 2799 can define angles as just described, but the surfaces may be rounded or otherwise non-planar.

The foregoing discussion regarding the separation assist 2707 applies equally to the separation assist 2708. In the

42

illustrated embodiment, the separation assist 2707 and the separation assist 2708 are substantially identical, such that the recess 2762 and the protrusion 2797 likewise include complementary planar surfaces that are at an angle of about 20 degrees relative to a plane oriented perpendicularly through a central axis of the cap 2704 and the sleeve 2791. In other embodiments, the arrangements of the separation assists 2707, 2708 may be different from each other. For example, the planar surfaces of the separation assist 2707 may be at a larger or smaller angle than those of the separation assist 2708 so as to provide a different amount of separation force. Moreover, in some embodiments, the assembly 2700 includes a number of separation assists 2707 equal to the number of separation assists 2708, whereas in other embodiments, the assembly 2700 may include more or fewer separation assists 2707 as compared with the number of separation assists 2708. For example, in the illustrated embodiment, the assembly 2700 includes one separation assist 2707 and two separation assists 2708.

In the illustrated embodiment, the two separation assists 2708 are at diametrically opposite positions. Such an orientation can aid in maintaining the cap 2704 and the sleeve 2791 in a substantially coaxial orientation as the cap 2704 is being removed, which can prevent an elongated sidewall 2752 from contacting an inner surface of the sleeve 2791 and thereby potentially complicating removal of the cap 2704. In other arrangements, additional separation assists 2708 may be used, and the separation assists 2708 may be equally spaced from each other about a perimeter of the sleeve 2791.

Other arrangements of the separation assists 2707, 2708 are contemplated. For example, in some embodiments, the caps 2702, 2704 include one or more of the protrusions 2799, 2797, respectively, whereas the sleeve 2791 includes one or more of the recesses 2716, 2762.

FIGS. 56 and 57 illustrate another embodiment of a cap 2802, which in some embodiments can be used in place of the cap 2602 in the assembly 2600. In other embodiments, the cap 2802 can be modified so as to be used in place of the cap 2702 in the assembly 2700, such as by altering a flange 2815 of the cap 2802 to include a recess.

The cap 2802 can include a seal inhibitor 2825 having a different arrangement from that shown with respect to the caps 2602, 2702. In the illustrated embodiment, the seal inhibitor 2825 is defined by a proximal surface 2824 of a sidewall 2812 of the cap 2802, which defines a rounded, sinusoidal contour. In particular, the proximal surface 2824 can define two contact regions 2826 and two venting regions 2827. In the illustrated embodiment, the contact regions 2826 are at diametrically opposite positions and the venting regions 2827 likewise are at diametrically opposite positions. The contact regions 2826 are at a more proximal position than are the venting regions 2827. As discussed above with respect to the cap 2602, the venting regions 2827 can prevent the cap 2802 from forming a seal with a medical connector, and can permit venting of the cap 2802 when it is coupled with the medical connector.

As shown in FIG. 58, the proximal surface 2824 of the cap 2802 can be well-suited for coupling with a removable cover 2834 such as the removable covers discussed above. Accordingly, various embodiments of the cap 2802 either can be readily fitted with a cover 2834 and distributed for individual use, or can be incorporated into an assembly, such as the assemblies 2600, 2700 described above, and distributed for use in a dual-cap system. Such versatility can reduce manufacturing costs, such as by eliminating tooling costs.

FIGS. 59-63 illustrate another embodiment of an assembly 3000, which can resemble one or more of the assemblies

described above, particularly the assemblies **2600** and **2700**, in certain respects. Accordingly, like features are designated with like reference numerals, with the leading digits incremented to “30,” and/or with identical or similar names.

As shown in FIG. **59**, the assembly **3000** can include a female cap **3002** and a male cap **3004** that are coupled with each other when in a pre-use state and that can be removed from each other. In particular, the female and male caps **3002**, **3004** can be coupled with each other via a sealing mechanism **3089**. In the illustrated embodiment, the sealing mechanism **3089** comprises a sealing sleeve **3091**. The terms “coupled” and variants thereof are used in their ordinary sense and include arrangements such as that illustrated in FIG. **1**, in which the connecting geometries, connection interfaces, or threads **122**, **114** of the caps **102**, **104** directly engage one another when the assembly **100** is in the assembled or pre-use state. The terms also include arrangements such as that illustrated in FIG. **59** where the caps **3002**, **3004** do not directly contact one another when the assembly **3000** is in the assembled or pre-use state, yet are securely held in a fixed relationship relative to one another. Stated otherwise, each of the caps **3002**, **3004** is separately secured to the sealing sleeve **3091**, and thus, although the caps **3002**, **3004** are spaced from one another, they nevertheless are indirectly secured to each other.

FIG. **60** is an exploded view of the assembly **3000**. The female cap **3002** can include a housing **3010** into which an antiseptic reservoir or pad **3032** is received. The male cap **3004** can include a housing **3050** into which a resilient support **3077**, an antiseptic reservoir or pad **3070**, and a sealing member **3090** are received. As further discussed below, the resilient support **3077** and the pad **3070** may be considered as a multi-part biasing member **3076** that is configured to urge the sealing member **3090** toward a proximal end of the male cap **3004**. As previously mentioned, the terms “proximal” and “distal,” when used herein relative to a cap, are used relative to the coupling of the cap with a medical device, such that the medical device is inserted into a proximal end of the cap and advanced toward a distal end of the cap. Accordingly, in the illustrated embodiment, the proximal ends of the caps **3002**, **3004** are directed toward each other and the distal ends of the caps **3002**, **3004** are directed away from each other when the assembly **3000** is in the pre-use configuration. The female cap **3002** can define one or more recesses **3016** and the male cap **3004** can define one or more recesses **3062** at positions that are between the proximal and distal ends of the caps **3002**, **3004**, respectively.

The sleeve **3091** can include end surfaces or edges **3096**, **3098** that are configured to interact with the male and female caps **3004**, **3002**, respectively. The sleeve **3091** can define one or more protrusions **3099** that are configured to be received in the one or more recesses **3016** of the female cap **3002**. Each protrusion **3099**/recess **3016** pair can cooperate as a decoupling feature, release mechanism, or separation assist **3007**. Similarly, the sleeve **3091** can define one or more protrusions **3097** that are configured to be received in the one or more recesses **3062** of the male cap **3004**. Each protrusion **3097**/recess **3062** pair can cooperate as a separation assist **3008**. The protrusions **3097**, **3099** and recesses **3016**, **3062** can have rounded edges (e.g., rounded or radiused valleys and apexes), which can facilitate their rotational movement relative to one another.

As shown in FIG. **61**, each protrusion **3099** can include a portion of the edge **3098** of the sleeve **3091**. Moreover, each protrusion **3099** can define a pair of faces **3099a**, **3099b** that are angled in opposite directions. Here, the term “angled” refers to any suitable non-zero, non-180-degree angle relative

to a transverse cross-sectional plane (not shown) that passes perpendicularly through a central axis of the sleeve **3091**. For a path that is traced along the edge **3098** in a clockwise direction (when looking toward the edge **3098**), the path moves away from the longitudinal center of the sleeve **3091** along the faces **3099a**, and the path moves toward the longitudinal center of the sleeve **3091** along the faces **3099b**.

Similarly, each protrusion **3097** can include a portion of the edge **3096** of the sleeve **3091**, and each protrusion **3097** can define a pair of oppositely angled faces **3097a**, **3097b**. For a path that is traced along the edge **3096** in a clockwise direction (when looking toward the edge **3096**), the path moves away from the longitudinal center of the sleeve **3091** along the faces **3097a**, and the path moves toward the longitudinal center of the sleeve along the faces **3097b**.

The protrusions **3097**, **3099** can be relatively flexible, as they extend a greater distance from the longitudinal center of the sleeve **3091**, and thus define longer moment arms relative thereto. In some embodiments, the sleeve **3091** includes a central band or reinforcing rib **3088** that can provide structural integrity to the sleeve **3091** and can prevent or inhibit large deformations of the sleeve **3091** during use and/or crushing of the sleeve **3091** after removal of one or more of the caps **3002**, **3004** therefrom. The illustrated reinforcing rib **3088** projects radially inwardly at a central region of the sleeve **3091**. In other embodiments, the reinforcing rib **3088** may extend outwardly or may be omitted. For example, in some embodiments, the sleeve **3091** may define a uniform thickness along its full length.

The sleeve **3091** defines an external surface **3082** and an internal surface **3083**, each of which extends away from the edges **3096**, **3098**. The internal surface **3083** can define a cavity, opening, or lumen **3084** into which proximal ends of the male and female caps **3004**, **3002** can be received. The terms “external surface” and “internal surface” are used relative to the assembly **3000** when it is in the pre-use state (e.g., the configuration shown in FIG. **59**). Accordingly, when the assembly **3000** is in an assembled state, the internal surface **3083** is at an interior of the assembly **3000**, so as not to be exposed to an environment that surrounds the assembly **3000**, and the external surface **3082** is at an exterior of the assembly, such that it is exposed to the environment and may be grasped or otherwise contacted by a user. It is noted that in the foregoing portion of the present specification, the terms “interior” and “exterior” may at times be used with respect to inwardly directed surfaces and outwardly directed surfaces of certain caps, without regard to whether any portion of these surfaces is in fact internal to an assembly that includes these caps when the assembly is in the pre-use state. The internal surface **3083** of the sleeve **3091** also can define a connection interface **3093** (FIG. **61**) and a connection interface **3095** by which the caps **3004**, **3002**, respectively, can be coupled to the sleeve **3091**, as discussed further below.

With reference to FIGS. **62A-62C** and **64**, the housing **3010** of the female cap **3002** can extend between a closed distal end and an open proximal end. The closed distal end does not permit any fluid flow therethrough and serves as a barrier between an interior of the housing **3010** and an exterior environment. The open proximal end of the housing **3010** is configured to receive at least a portion of a medical connector therein, such as any of the medical connectors described above with respect to female caps. The housing **3010** can include a sidewall **3012**, which defines the open proximal end, and a base wall **3013**, which defines at least a portion of the closed distal end.

The housing **3010** can include a body region **3036** near a proximal end thereof, which is substantially cylindrically

shaped in the illustrated embodiment. A handle **3037** can extend from the body region **3036** so as to be positioned at the distal end of the cap **3002**. The handle **3037** can comprise any suitable gripping features **3003**, such as any of the gripping features **103** discussed above. In the illustrated embodiment, the gripping features **3003** comprise opposing gripping regions or grasping recesses or platforms **3038** that are configured to provide a convenient surface against which a user can press so as to hold and/or twist the cap **3002**.

As shown in FIG. 62B, the illustrated grasping recesses or platforms **3038** are mirrored about a longitudinal plane LP that extends along a central longitudinal axis A (shown in FIG. 62A) of the housing **3010**. Each grasping recess or platform **3038** angles radially inwardly from the body region **3036** toward the longitudinal plane LP, in a proximal-to-distal direction. The grasping recesses or platforms **3038** are more steeply angled at their proximal ends than they are at their distal ends. The angled platforms **3038**, and particularly the steeply angled portions thereof, provide convenient surfaces to which forces may be applied in a distal-to-proximal direction. In the illustrated embodiment, the recesses or platforms **3038** define two substantially planar regions that are smoothly joined to each other at a rounded transition. The recesses or platforms **3038** can define a contour that is substantially complementary to fingertips that are pointed in the proximal direction.

As shown in FIG. 62A, the illustrated grasping platforms **3038** also taper inwardly toward the central longitudinal axis A of the housing **3010** in a proximal-to-distal direction. In the elevation view that is shown, the platforms **3038** are substantially ovoid. The platforms **3038** are sized and shaped to be held between the fingertips of a thumb and another finger (e.g., the index finger) of a user, although other grasping configurations may also be efficiently employed with the illustrated arrangement. The platforms **3038** provide convenient surfaces to which torque may be applied so as to rotate the cap **3002** about the longitudinal axis A.

With reference to FIGS. 62A-62C, the cap **3002** can include a lip, rim, or flange **3015** that extends radially inwardly at a proximal end of the body region **3036**. The flange **3015** can contact the edge **3098** of the sleeve **3091** to prevent the cap **3002** from being inserted into the sleeve **3091** too deeply. The flange **3015** can define the one or more recesses **3016** mentioned above.

With reference again to FIG. 62B, each recess **3016** can be at least partially defined by a pair of faces **3016a**, **3016b** of the flange **3015** that are angled in opposite directions. The angles can be any suitable non-zero, non-180-degree angles relative to a transverse cross-sectional plane TP that passes perpendicularly through the a central axis A of the housing **3010**. In particular, the faces **3016a** can define an angle .alpha. relative to the transverse plane TP, and the faces **3016b** can define an angle .beta. relative to the transverse plane TP. In the illustrated embodiment, the angles .alpha., .beta. are the same, although other arrangements are possible (as discussed further below). For a path is traced along the flange **3015** in a clockwise direction (when looking toward the flange **3015**), the path moves proximally along the faces **3016a** and the path moves distally along the faces **3016b**. The faces **3016a**, **3016b** can be substantially planar over at least a portion thereof, and can be configured to complementarily contact the faces **3099a**, **3099b**, respectively, of the sleeve **3091**. Additional discussion of the faces **3016a**, **3016b** is provided below with respect to FIGS. 65A-65B.

The housing **3010** defines an external surface **3018** and an internal surface **3019**, each of which extends away from the flange **3015**. The internal surface **3019** of the cap **3002** can

include an outwardly directed surface of the sidewall **3012**, a proximal end **3024** of the sidewall **3012**, and an inwardly directed surface of the sidewall **3012** (see FIGS. 62C and 64). The outwardly directed portion of the internal surface **3019** can define a connection interface **3040** that is configured to interact with or engage the connection interface **3095** of the sleeve **3091** so as to connect the cap **3002** to the sleeve **3091**. In the illustrated embodiment, the connection interfaces **3040**, **3095** couple with each other via a friction-fit engagement. For example, an inner diameter of the connection interface **3095** of the sleeve **3091** can be slightly smaller than an outer diameter of the connection interface **3040** of the cap **3002**. The friction fit can be sufficiently strong to provide a fluid-tight seal between the cap **3002** and the sleeve **3091**, yet can allow the cap **3002** to be removed from the sleeve **3091** via manipulation by a user (e.g., without the use of ancillary tools). The fluid-tight seal can prevent evaporative loss of antiseptic from an interior of the assembly **3000** when it is in the pre-use configuration and/or can maintain the sterility of the internal portions of the assembly **3000**. In other or further embodiments, the connection interfaces **3040**, **3095** can include threads and/or any other suitable attachment features. In the illustrated embodiment, a proximal portion of the connection interface **3095** includes a chamfer **3020**, which can assist in centering the cap **3002** relative to the sleeve **3091** when connecting the cap **3002** to the sleeve **3091**.

The proximal end **3024** of the housing **3010** (which is also a proximal end of the internal surface **3019**, or more generally, of the sidewall **3012**), can define a seal inhibitor **3025**, such as the seal inhibitor **2825** discussed above. In particular, the seal inhibitor **3025** can include one or more contact regions **3026** and one or more venting regions **3027**, such as the contact regions **2826** and the venting regions **2827** discussed above. In the illustrated embodiment, the seal inhibitor **3025** includes two contact regions **3026** that are diametrically opposite from each other, and also includes two venting regions **2827** that are diametrically opposite from each other and are angularly spaced from the contact regions. Other configurations of the seal inhibitor **3025** are also possible, such as, for example, the seal inhibitor **2625** discussed above.

With reference to FIGS. 62C and 64, the inwardly directed portion of the internal surface **3019** of the sidewall **3012** can define a disinfection chamber **3022**, which can include a connection interface **3030**. As discussed above, any suitable connection system may be used for the connection interface **3030**. In the illustrated embodiment, the connection interface includes threads **3031**. The connection interface **3030** can be configured to attach the cap **3002** to a medical connector in a secure yet selectively removable manner. For example, the cap **3002** can be connected in any suitable manner with any suitable medical connector, including those described above with respect to other embodiments of female caps. In other embodiments, the connection interface **3030** may include latches or prongs that are configured to snap over an outwardly extending rib of a connector, or may include one or more outwardly extending ribs over which one or more latches or prongs of the medical connector may snap.

A proximal portion of the disinfection chamber **3022** can be larger than a distal extension **3023** of the chamber. In the illustrated embodiment, the disinfection chamber **3022** defines three substantially frustoconical regions. The proximal region has a slightly tapered outer boundary that decreases in cross-sectional area in the distal direction; the intermediate region has a more pronounced tapered outer boundary that more rapidly decreases in cross-sectional area in the distal direction; and the distal region or distal extension **3023** has a slightly tapered outer boundary that decreases in

cross-sectional area in the distal direction at about the same rate as the proximal region. The intermediate and distal regions correspond with the proximal and distal regions, respectively, of the grasping platforms.

The constricted intermediate region of the disinfection chamber 3022 can provide a reactive force to a distal end of the pad 3032 when the cap 3002 is secured to a medical connector. The reactive force can be sufficient to prevent the pad 3032 from being forced into the distal extension 3023. In the illustrated embodiment, the threads 3031 also provide resistive forces. Axial compression of the pad 3032 as the cap 3002 is coupled to a medical connector can swab the connector and deliver antiseptic 3033 from the pad 3032 into contact with the medical connector in manners such as described above. In some embodiments, the pad 3032 may be resiliently deformable so as to regain a pre-use shape after a medical connector is decoupled from the cap 3002. In other embodiments, the pad 3032 may instead be plastically deformable.

In the illustrated embodiment, the pad 3032 is substantially square in cross-section along its full longitudinal length when the pad 3032 is in a relaxed orientation (see FIG. 60). Such an arrangement can facilitate and/or reduce material costs associated with the manufacture of the pad 3032. At least a portion of the pad 3032 (e.g., the corners thereof) may be compressed radially when the pad 3032 is positioned within the housing 3012. Other rectangular cross-sections are also possible for the pad 3032, and in other or further embodiments, the pad 3032 may define a rectangular cross-section along only a portion of the longitudinal length thereof. In other embodiments, at least a portion of the pad 3032 may define a round cross-section, such as a circular, elliptical, or other ovoid shape. For example, the pad 3032 can be cylindrical so as to have a circular cross-section. The pad 3032 may define any other suitable shape, and may or may not be radially compressed when the assembly 3000 is in the pre-use state.

With reference to FIGS. 63A-63C, the housing 3050 of the male cap 3004 can extend between a closed distal end and an open proximal end. The closed distal end does not permit any fluid flow therethrough and serves as a barrier between an interior of the housing 3050 and an exterior environment. The open proximal end of the housing 3050 is configured to receive at least a portion of a medical connector therein. In particular, the open proximal end of the housing 3050 is sized and shaped to receive at least a portion of a male protrusion of a medical connector. For example, the open proximal end of the housing 3050 can be configured to receive at least a portion of a male luer, such as the male luer 2020 described above. The housing 3050 can include a sidewall 3052, which defines the open proximal end, and a base wall 3054, which defines at least a portion of the closed distal end.

As viewed from the exterior (e.g., in FIGS. 63A and 63B), a shape and/or configuration of the distal end of the housing 3050 can be similar or identical to the distal end of the housing 3010 of the female cap 3002, which is discussed above. For example, in the illustrated embodiment, the housing 3050 includes a body region 3036 and a handle 3037 with grasping platforms 3038, which when viewed exteriorly, are identical to the identically numbered features of the cap 3002. Accordingly, as can be seen in FIGS. 59 and 64, when the assembly 3000 is in the pre-use state, an exterior thereof can be symmetrical about three mutually perpendicular planes. Other arrangements are also possible.

With continued reference to FIGS. 63A-63C, the housing 3050 can include a lip, rim, or flange 3061 that extends radially inwardly at a proximal end of the body region 3036. The flange 3061 can contact the edge 3096 of the sleeve 3091 to prevent the cap 3004 from being inserted into the sleeve

3091 too deeply. The flange 3061 can define the one or more recesses 3062 mentioned above.

With reference to FIG. 63B, each recess 3062 can be at least partially defined by a pair of faces 3062a, 3062b of the flange 3061 that are angled in opposite directions. The angles can be any suitable non-zero, non-180-degree angles relative to a transverse cross-sectional plane TP that passes perpendicularly through the a central axis of the cap 3004. In particular, the faces 3062a can define an angle .alpha.' relative to the transverse plane TP, and the faces 3062b can define an angle .beta.' relative to the transverse plane TP. In the illustrated embodiment, the angles .alpha.', .beta.' are the same, although other arrangements are possible (as discussed further below). Moreover, in the illustrated embodiment, the angles .alpha.', .beta.' are identical to the angles .alpha., .beta. defined by the faces 3016a, 3016b of the cap 3002. For a path is traced along the flange 3061 in a clockwise direction (when looking toward the flange 3061), the path moves proximally along the faces 3016a and the path moves distally along the faces 3016b. The faces 3016a, 3016b can be substantially planar over at least a portion thereof, and can be configured to complementarily contact the faces 3097a, 3097b, respectively, of the sleeve 3091.

The male cap 3004 defines an external surface 3065 and an internal surface 3066, each of which extends away from the flange 3061. The internal surface 3066 of the cap 3004 can include an outwardly directed surface of the sidewall 3052, a proximal end of the sidewall 3052, and an inwardly directed surface of the sidewall 3052 (see FIGS. 63C and 64). The outwardly directed portion of the internal surface 3066 can define a connection interface 3080 that is configured to interact with or engage the connection interface 3093 of the sleeve 3091 so as to connect the cap 3004 to the sleeve 3091. The connection interfaces 3080, 3093 can resemble the connection interfaces 3040, 3095 discussed above. In addition, a portion of the sidewall 3052 that is at a proximal end of the connection interface 3080 can include a chamfer 3067, which can assist in centering the cap 3004 relative to the sleeve 3091 during connection of these components.

The sidewall 3052 of the cap 3004 can define an extension, elongated portion, or projection 3055 that extends proximally from the connection interface 3080. The projection 3055 can be configured to couple with a medical connector that includes a male protrusion. The projection 3055 includes a connection interface 3042 that is configured to effect the coupling. In the illustrated embodiment, the projection 3055 is substantially cylindrical, and the connection interface 3042 comprises one or more threads 3043 that are positioned at an outwardly facing surface of the cylinder. Any other suitable connection interface 3042, such as any of those described above, is possible. As shown in FIG. 64, when the assembly 3000 is in the pre-use state, a proximal end of the projection 3055 can extend into a proximal end of the disinfection chamber 3022 of the female cap 3002 in a manner such as described above with respect to the assembly 2600. In the illustrated embodiment, the reinforcement rib 3088 of the sleeve 3091 can be at a longitudinal center of the assembly 3000, and the projection 3055 can extend through the reinforcement rib 3088.

With reference to FIGS. 63C and 64, an inwardly directed portion of the internal surface 3066 of the sidewall 3052 can define a disinfection chamber 3058, which can extend from the proximal end of the projection 3055 (i.e., the open proximal end of the cap 3004) to the base wall 3054. A proximal portion of the disinfection chamber 3058 can include a proximal seal region 3071, which can be configured to form a fluid-tight seal with the male protrusion portion of a medical

connector. For example, the seal region 3071 may be shaped complementarily to an outer surface of a male protrusion of a medical connector with which the male cap 3004 is configured to be used. In the illustrated embodiment, the proximal seal region 3071 comprises a substantially frustoconical surface 3072 that complies with ISO luer standards, as discussed above, such that a portion of a male luer can form a seal with the seal region 3071. The frustoconical surface 3072 can be tapered so as to decrease in diameter in a distal direction. In other embodiments, the proximal portion of the disinfection chamber 3058 may not be configured to form a fluid-tight seal with a male protrusion of a medical connector.

The disinfection chamber 3058 can further include an intermediate seal region 3073. In the illustrated embodiment, the intermediate seal region is formed by a rim, ridge, lip, or shelf 3074, which is defined by a short, substantially frustoconical portion of the sidewall 1052 that increases in diameter in the distal direction. An outer edge of a proximal surface of the sealing member 3090 can define a greater outer diameter than a minimum inner diameter of the shelf 3074 such that the shelf 3074 can maintain the sealing member 3090 within the chamber 3058. The shelf 3074 also can cooperate with the sealing member 3090 to seal the chamber 3058 when the assembly 3000 is in the pre-use state, as further discussed below.

In the illustrated embodiment, a long distal extension 3075 of the disinfection chamber 3022 can extend distally from the shelf 3074. The distal extension 3023 has a slightly tapered outer boundary that gradually decreases in cross-sectional area in the distal direction. The disinfection chamber 3022 can include a support post 3068 within a distal region thereof. The support post 3068 can be integrally formed with both the base wall 3054 and the sidewall 3052, and can provide a rigid surface against which the resilient support 3077 can rest. The support post 3068 can act as a stop that prevents the resilient support 3077 from moving distally within the chamber 3022 past a proximal end of the support post 3068. In some instances, however, a distal portion of the resilient support 3077 may deform so as to extend distally slightly past the proximal end of the support post 3068 when a medical connector is coupled with the cap 3004. The support post 3068 can reduce the amount of material that might otherwise be used to form the handle 3037 portion of the cap 3004.

The resilient support 3077, which may also be referred to as a post or a base element, can be configured to provide a base against which the antiseptic reservoir or pad 3070 can be compressed so as to force antiseptic 3033 therefrom. Accordingly, the resilient support 3077 can be harder, stiffer, or less compliant than the pad 3070, and can be configured to compress, under a given force, to a smaller extent than the pad 3070 does under the same force. For example, in various embodiments, the resilient support 3077 can be no less than about 2, 3, or 4 times harder than the pad 3070.

The resilient support 3077 can be elastically deformable such that compression of the support 3077 from a relaxed orientation gives rise to a restorative force. The resilient support 3077 can naturally return to the relaxed orientation upon removal of the compressive force. The resilient support 3077 can comprise any suitable elastically deformable material. In some embodiments, the resilient support 3077 comprises an elastomeric material, such as silicone. In certain embodiments, the resilient support 3077 comprises a closed configuration (e.g., closed cell foam) or is otherwise nonabsorbent such that little or no antiseptic 3033 that is expelled from the pad 3070 is received into the resilient support 3077. In other or further embodiments, the resilient support 3077 may comprise a spring (e.g., a compression coil spring).

In the illustrated embodiment, a distal end of the resilient support 3077 seats snugly against the inner surface 3066 of the sidewall 3052. The resilient support 3077 may form a fluid-tight seal with the sidewall 3052, which may prevent antiseptic 3033 that is expelled from the pad 3070 from migrating into the distal regions of the disinfecting chamber 3058. Rather, the antiseptic 3033 can be restrained to the proximal regions of the disinfecting chamber 3058 where it can be urged into contact with a male protrusion of a medical connector.

The pad 3070 can comprise any suitable material, such as those described above with respect to other pads (including plastically deformable materials, in some instances), and may be elastically or resiliently deformable. In some embodiments, the pad 3070 is attached to the resilient support 3077 via any suitable adhesive or other attachment mechanism, although in other embodiments, no such attachment mechanisms are used. For example, the pad 3070 and the resilient support 3077 may be maintained in contact with each other due to a slight longitudinal compression of one or more of these components once the cap 3004 is assembled (e.g., once the support 3077, the pad 3070, and the sealing member 3090 are positioned between the support post 3068 and the shelf 3074). Similarly, the pad 3070 may be attached to the sealing member 3090, or it may maintain a substantially fixed orientation relative to the sealing member 3090 without such attachment due to the resilience of the pad 3070 and/or the support 3077, which are in a slightly compressed state.

In the illustrated embodiment, the pad 3070 is substantially square in cross-section along its full longitudinal length when the pad 3070 is in a relaxed orientation (see FIG. 60). Such an arrangement can facilitate and/or reduce material costs associated with the manufacture of the pad 3070. At least a portion of the pad 3070 (e.g., the corners thereof) may be compressed radially when the pad 3070 is positioned within the housing 3052. Other rectangular cross-sections are also possible for the pad 3070, and in other or further embodiments, the pad 3070 may define a rectangular cross-section along only a portion of the longitudinal length thereof. In other embodiments, at least a portion of the pad 3070 may define a round cross-section, such as a circular, elliptical, or other ovoid shape. For example, the pad 3070 can be cylindrical so as to have a circular cross-section. The pad 3070 may define any other suitable shape, and may or may not be radially compressed when the assembly 3000 is in the pre-use state.

As previously mentioned, the pad 3070 and the support 3077 can, in some embodiments, cooperate as a two-part biasing member 3076. It is to be understood that any other suitable biasing member 3076 may be used, such as those described above. The biasing member 3076 can urge the sealing member 3090 in the proximal direction into sealing contact with the shelf 3074. The seal thus formed may be fluid-tight, and may prevent antiseptic 3033, whether in liquid or vapor form, from exiting the disinfecting chamber 3058 through the proximal end of the cap 3004 prior to coupling of the cap 3004 to a medical connector. This proximal seal may be in place when the assembly 3000 is in the pre-use configuration, as well as after the separation of the male and female caps 3004, 3002 when the assembly 3000 is opened.

The illustrated sealing member 3090 comprises unitary piece of material that includes a cylindrical region and a conical region. The conical region can be well-suited to form a seal with a tip of the projection of a male medical connector in manners such as described above. In some instances, an apex of the conical region can be received within a lumen 2022 of a luer 2020 when a medical connector is coupled with the cap 3004 (see, e.g., FIG. 66A). The sealing member 3090

51

can be formed of any suitable material, such as, for example, silicone and/or any of the materials discussed above with respect to other seals. In some embodiments, the sealing member 3090 can be harder, more rigid, and/or less compliant than the pad 3070.

FIGS. 65A and 65B illustrate stages in a method of removing the male cap 3004 from the assembly 3000. In some embodiments, it can be particularly advantageous to use the separation assists 3008 in the removal process. For example, in some instances, the fluid-tight seal between the cap 3004 and the sleeve 3091 can be relatively tight and/or a slight vacuum may be present within the assembly 3000 (and/or may arise as the cap 3004 is removed from the assembly 3000), such that the separation assists 3008 can facilitate removal of the cap 3004.

FIG. 65A illustrates the assembly 3000 in the pre-use state, with the faces 3062a, 3097a and 3062b, 3097b of the surfaces 3061, 3096 in contact with each other. Each paired set of surfaces constitutes a separation assist 3008. In the illustrated embodiment the assembly 3000 includes four separation assists 3008 rotationally spaced from each other at intervals of approximately 90 degrees. Focusing now on the upper separation assist 3008 that includes the faces 3062b, 3097b, the face 3062b can define an angle .beta.' (see FIG. 63B) of about 20 degrees. The face 3097b of the sleeve 3091 is at the same angle, although oppositely directed.

In order to separate the cap 3004 from the sleeve 3091, the cap 3004 can be rotated relative to the sleeve 3091. In the illustrated embodiment, the cap 3004 is rotated counterclockwise, which can cause the faces 3062b, 3097b to interact with each other and slide past each other. The cap 3004 thus cams relative to the sleeve 3091 as the rotational motion is converted into translational movement of the cap 3004 away from the sleeve 3091, as shown by the arrow in FIG. 65B.

Where the angles .alpha.', .beta.' (see FIG. 63B) of the surfaces 3062a, 3062b are identical, the same mechanical advantage may be present whether the cap 3004 is rotated in the clockwise or counterclockwise directions. In other embodiments, the separation assists 3008 can be configured to aid in separating the cap 3004 from the sleeve 3091 only when the cap 3004 is rotated in one predetermined direction (e.g., either clockwise or counterclockwise). For example, the pair of faces 3062a or the pair of faces 3062b may define an angle .alpha.' or .beta.', respectively, of 20 degrees so as to allow separation as shown in FIG. 63B, whereas the other pair of faces 3062a, 3062b may be at an angle of about 90 degrees (i.e., approximately parallel to or extending through a central axis of the cap 3004) so as to prevent rotation and separation of the cap 3004. In other embodiments, one or more of the faces 3062a, 3062b may be at larger or smaller angles .alpha.', .beta.'. For example, one or more of the angles .alpha.', .beta.' may be no more than about 15, 20, 30, 45, 60, or 75 degrees or no less than about 15, 20, 30, 45, 60, or 75 degrees. Other configurations of the separation assists 3008 are also possible. For example, in some embodiments, the complementary surfaces of the recess 3062 and the protrusion 3099 can define angles as just described, but the surfaces may be rounded or otherwise non-planar.

The foregoing discussion regarding the separation assists 3008 applies equally to the separation assists 3007. In the illustrated embodiment, the separation assists 3007, 3008 are substantially identical. The sleeve 3091 may be reversible, as either end thereof may connect with either cap 3002, 3004. In other embodiments, the arrangements of the separation assists 3007, 3008 may be different from each other. For example, the planar surfaces of the separation assist 3007 may be at a larger or smaller angle than those of the separation

52

assist 3008 so as to provide a different amount of separation force. Moreover, in some embodiments, the assembly 3000 includes a number of separation assists 3007 equal to the number of separation assists 3008, whereas in other embodiments, the assembly 3000 may include more or fewer separation assists 3007 as compared with the number of separation assists 3008. Other arrangements of the separation assists 3007, 3008 are contemplated, including those discussed above with respect to the assembly 2700. Other embodiments may be devoid of the separation assists 3007, 3008. Moreover, in some instances, a user may remove one or more of the caps 3002, 3004 from the assembly 3000 in a substantially longitudinal direction only (e.g., without rotating the caps 3002, 3004 relative to each other).

FIGS. 66A-66D illustrate consecutive stages of the cap 3004 being coupled with a medical device 2000 that includes a male protrusion 2019, which in the illustrated embodiment is a male luer 2020. As mentioned above, other arrangements of the male protrusion 2019 are also contemplated. A tip 2021 of the protrusion 2019, can be received within the disinfection chamber 3058 prior to contacting the sealing member 3090. Stated otherwise, the sealing member 3090 can be recessed relative to a proximal end of the sidewall 3052 by a distance that is sufficiently great to permit at least a portion of the male luer 2020 to be received within the sidewall 3052 before the male luer contacts the sealing member 3090.

In the illustrated stage of the procedure, the luer 2020 has been advanced sufficiently far into the disinfection chamber 3058 to contact the sealing member 3090 and to form a seal therewith. The connection interface 3042 of the cap 3004 has not yet engaged a connection interface 2012 of the medical connector 2000 at this stage, and the sealing member 3090 is just beginning to move distally within the disinfection chamber 3058 so as to break the proximal seal between the sealing member 3090 and the shelf 3074.

In FIG. 66B, the luer 2020 has been advanced slightly further into the disinfection chamber 3058, thereby compressing the pad 3070 somewhat and forcing antiseptic 3033 out of the pad 3070. The sealing member 3090 can define an outer diameter that is smaller than an inner diameter of this portion of the disinfection chamber 3058 such that a fluid path is present about an exterior of the sealing member 3090. Stated otherwise, the sealing member 3090 has been urged distally to a position where a periphery or outermost perimeter of the sealing member 3090 is spaced from the sidewall 3052 such that an opening, spacing, or gap that exists between the sealing member 2490 and the sidewall 2452. This opening may function as a fluid port.

Antiseptic 3033 thus can flow about the sealing member 3090 and/or any other portion of an open region that exists between the inner surface 3066 of the sidewall 3052 and the outer surfaces of the resilient support 3077, the pad 3070, the sealing member 3090, and the luer 2020. Further advancement of the luer 2020 into the disinfection chamber 3058 can cause the antiseptic 3033 to fill this open region. However, the antiseptic 3033 does not enter into the lumen 2022 of the luer 2020 due to the seal between the luer 2020 and the sealing member 3090. Further advancement of the luer 2020 into the disinfection chamber 3058 also can strengthen the seal between the luer 2020 and the sealing member 3090 due to the increasing restorative forces that arise as the pad 3070 is compressed.

As the pad 3070 is softer or more compliant than the resilient support 3077, the pad 3070 has been compressed to a much greater extent than the resilient support 3077 at this stage. Indeed, in some embodiments, the resilient support 3077 may compress only slightly or not at all at this stage.

In the illustrated embodiment, the interfaces **3042**, **2012** have not yet coupled with each other at this stage. However, in other embodiments, the interfaces **3042**, **2010** may already cooperate with each other at this or at a previous stage so as to draw the luer **2020** into the disinfection chamber **3058**.

In FIG. **66C**, the luer **2020** has been advanced even further into the disinfection chamber **3058**, thereby compressing the pad **3070** to a greater extent and forcing additional antiseptic **3033** into the interior regions of the disinfection chamber **3058**. In the illustrated embodiment, the resilient support **3077** is shown as having been slightly compressed relative to its configuration in the stage shown in FIG. **66C**, whereas the pad **3070** has been nearly completely compressed, such that all or nearly all of the antiseptic **3033** has been forced therefrom. Cooperation between the connection interfaces **3042**, **2012** can facilitate compression of the pad **3070** and/or the resilient support **3077**.

Although the outer surface of the luer **2020** appears to be nearly parallel to and in contact with the luer-tapered surface **3072** of the sidewall **3052**, a fluid-tight seal may not have formed yet in this area. Accordingly, the antiseptic **3033** may be permitted to cover the portion of the luer **2020** that is within the chamber **3058**, while in some embodiments, a small portion of antiseptic **3033** may also be permitted to exit from the disinfection chamber **3058**. The portion of the luer **2020** that is within the disinfection chamber **3058** thus may contact the antiseptic **3033** so as to be disinfected thereby.

FIG. **66D** illustrates a final or fully coupled stage, or an end-of-stroke orientation, in which the luer **2020** has been advanced even further into the disinfection chamber **3058** such that the luer **2020** forms a seal with the luer-tapered surface **3072** of the sidewall **3052**. Antiseptic **3033** can be retained in all open portions of the disinfection chamber **3058** that are between the seal formed by the luer **2020** and the sealing member **3090** and the seal formed by the luer **2020** and the sidewall **3052**. In the illustrated embodiment, a relatively large portion of the luer **2020**, which includes all or most of the tip **2021**, is in continual contact with the portion of the antiseptic **3033** thus retained. This portion of the luer **2020** can be bathed by the antiseptic **3033** and disinfected thereby. In other embodiments, larger portions of the luer **2020** can be bathed.

The deformable nature of the resilient support **3077** can allow for distal movement of the pad **3070**, even after the pad **3070** has been fully compressed. Such an arrangement can allow for a range of acceptable lengths for the luer **2020**. For example, shorter luers **2020** than that illustrated in the drawings may still be able to fully compress the pad **3070** so as to expel all antiseptic therefrom.

In other embodiments, the medical connector **2000** may include a male protrusion other than a luer **2020**, such as discussed above. In some embodiments, the surface **3072** may be shaped complementarily to the outer surface of such protrusions so as to form a seal therewith. In still other embodiments, the sidewall **3052** may not form a seal with the protrusion.

When the luer **2020** is removed from the chamber **3058**, the restoration forces of the pad **3070** and/or the resilient support **3077** (i.e., the biasing member **3076**) can maintain the seal between the luer **2020** and the sealing member **3090**, which can prevent antiseptic from entering into the lumen **2022** of the luer **2020**.

Each of FIGS. **67-69** illustrates the female cap **3002** coupled with a different needleless injection site **2040**, **2060**, **2080** in manners such as that described above with respect to the cap **1902** in FIGS. **32-34**. More generally, the female cap **3002** can be coupled with any of a variety of different types of

medical connectors in a secure fashion that disinfects each type of medical connector, such as in manners discussed above with respect to other female caps.

As shown in FIG. **68**, in some arrangements, a portion of the seal inhibitor **3025** can contact an outwardly projecting surface **2069** of a needleless injection site **2060**. In particular, the proximal end **3024** of the cap **3002** can contact the surface **2069** at two separate contact regions **3026** when the cap **3002** is fully coupled with the needleless injection site **2060**. In the venting regions **3027** (not shown in FIG. **68**, see FIGS. **62A** and **62B**), the proximal end **3024** of the cap **3002** can be spaced from the surface **2069**.

The caps described herein, and components thereof, can be formed of, or coated with various colored materials or coatings. In some embodiments, the caps each include the same color. In other embodiments, the caps include different colors. Coloring the caps can, in some instances, provide advantages, such as ready identification of the type of cap, ready matching of a particularly colored cap with a particular type of medical connector, and the like.

The foregoing disclosure recites various embodiments that include systems configured for use with a pair of separated medical connectors. Examples of first means for coupling a male cap with a first medical connector include the connection interfaces **1042**, **1142**, **1342**, **1542**, **1842**, **1942**, **2242**, **2342**, **2642**, and **3042** of the caps **1004**, **1104**, **1304**, **1504**, **1804**, **1904**, **2204**, **2304**, **2304'**, **2604**, and **3004**. Examples of first means for disinfecting a male luer of a first medical connector include the pads **1070**, **1170**, **1370**, **1570**, **1870**, **2170**, **2270**, **2370**, **2470**, **2670**, and **3070**. Examples of second means for coupling the female cap with a second medical connector include the connection interfaces **1030**, **1130**, **1530**, **1830**, **1930**, **2230**, **2630**, and **3030** of the caps **1002**, **1102**, **1502**, **1802**, **1902**, **2202**, **2602**, and **3002**. Examples of second means for disinfecting at least a portion of a second medical connector include the pads **1032**, **1132**, **1332**, **1532**, **1832**, **2132**, **2632**, **3032**. Examples of means for coupling the male and female caps in a pre-use configuration include the connection interfaces **1040** and **1042**; **1140** and **1180**; **1240** and **1280**; **1340** and **1380**; **1440** and **1480**; **1540** and **1580**; **1840** and **1891**, **1842** and **1892**; **2640** and **2695**, **2680** and **2692**; and **3040** and **3095**, **3080** and **3092**. Examples of means for sealing a lumen of a male luer include the sealing members **2290**, **2390**, **2490**, **2590**, **2690**, and **3090**. Examples of means for biasing a means for sealing a lumen of a male luer include the biasing members **2276**, **2376**, **2476**, **2576**, **2676**, and **3076**.

It will be understood by those having skill in the art that many changes may be made to the details of the above-described embodiments without departing from the underlying principles presented herein. For example, any suitable combination of features of the various embodiments of assemblies described above is contemplated.

Any methods disclosed herein comprise one or more steps or actions for performing the described method. The method steps and/or actions may be interchanged with one another. In other words, unless a specific order of steps or actions is required for proper operation of the embodiment, the order and/or use of specific steps and/or actions may be modified.

It should be appreciated that in the above description of embodiments, various features are sometimes grouped together in a single embodiment, figure, or description thereof for the purpose of streamlining the disclosure. This method of disclosure, however, is not to be interpreted as reflecting an intention that any claim require more features than those expressly recited in that claim. Rather, as the following claims reflect, inventive aspects lie in a combina-

55

tion of fewer than all features of any single foregoing disclosed embodiment. Thus, the claims following this Detailed Description are hereby expressly incorporated into this Detailed Description, with each claim standing on its own as a separate embodiment. This disclosure includes all permutations of the independent claims with their dependent claims.

References to approximations are made throughout this specification, such as by use of the terms “about” or “approximately.” For each such reference, it is to be understood that, in some embodiments, the value, feature, or characteristic may be specified without approximation. For example, where qualifiers such as “about,” “substantially,” and “generally” are used, these terms include within their scope the qualified words in the absence of their qualifiers. For example, where the term “substantially planar” is recited with respect to a feature, it is understood that in further embodiments, the feature can have a precisely planar orientation.

Recitation in the claims of the term “first” with respect to a feature or element does not necessarily imply the existence of a second or additional such feature or element. Elements recited in means-plus-function format are intended to be construed in accordance with 35 U.S.C. § 112 6. It will be apparent to those having skill in the art that changes may be made to the details of the above-described embodiments without departing from the underlying principles of the invention.

We claim:

1. A male-disinfecting cap for disinfecting a male luer-lock connector of the type including a post having a lumen through which fluid flows and an internally helically threaded skirt surrounding the post, the cap comprising:

a cap body having an outer surface defining a gripping portion and only one receiving portion and defining a longitudinal axis, the receiving portion defining one chamber having a single opening, said opening being in the receiving portion, into which the post of the male luer-lock connector can be received, wherein an exterior surface of the receiving portion near the opening of the chamber fits within the skirt of the male luer-lock connector when the post is received into the single opening of the chamber, the exterior surface of the receiving portion having protrusions shaped to engage helical threads of the internally helically threaded skirt; the chamber defining an interior portion extending within the gripping portion of the cap body, wherein the gripping portion extends the cap body longitudinally beyond

56

the skirt of the male luer-lock connector when the post is received into the chamber; and the gripping portion comprising at least one recess having a length and depth, wherein the depth varied monotonically along the length of the recess; and

an antiseptic agent disposed in the chamber.

2. A cap according to claim 1, further comprising a cover disposed over the opening of the chamber.

3. A cap according to claim 2, wherein the cover comprise an impervious pliable material.

4. A cap according to claim 3, wherein the impervious pliable material comprises plastic.

5. A cap according to claim 1, further comprising a taper extending along a portion of a wall of the chamber.

6. A cap according to claim 5, wherein the wall of the chamber is configured to engage with at least a portion of the post of the male luer-lock connector.

7. A male-disinfecting cap for disinfecting a male luer-lock connector of the type including a post having a lumen through which fluid flows and an internally helically threaded skirt surrounding the post, the cap comprising:

a cap body having an outer surface defining a gripping portion and only one receiving portion and defining a longitudinal axis, the receiving portion defining one chamber having a single opening, said opening being in the receiving portion, into which the post of the male luer-lock connector can be received, wherein an exterior surface of the receiving portion near the opening of the chamber fits within the skirt of the male luer-lock connector when the post is received into the single opening of the chamber, the exterior surface of the receiving portion having protrusions shaped to engage helical threads of the internally helically threaded skirt; the chamber defining an interior portion extending within the gripping portion of the cap body, wherein the gripping portion extends the cap body longitudinally and distally from the opening beyond the skirt of the male luer-lock connector when the post is received into the chamber; and the gripping portion comprising at least one recess having a bottom, the cap body having a cross sectional thickness at the bottom of the recess gradually increasing from a distal-most end of the cap body and towards the receiving portion; and

an antiseptic agent disposed in the chamber.

* * * * *