



US008192482B2

(12) **United States Patent**
Goicoechea et al.

(10) **Patent No.:** **US 8,192,482 B2**

(45) **Date of Patent:** ***Jun. 5, 2012**

(54) **ENDOLUMINAL STENT**

(75) Inventors: **George Goicoechea**, Grand Bahama (BS); **John Hudson**, Glenfield (GB); **Andrew H. Cragg**, Edina, MN (US); **Claude Mialhe**, Draguignan (FR); **Michael D. Dake**, Stanford, CA (US)

(73) Assignee: **Scimed Life Systems, Inc.**, Maple Grove, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1263 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **09/977,826**

(22) Filed: **Oct. 15, 2001**

(65) **Prior Publication Data**

US 2002/0019659 A1 Feb. 14, 2002

Related U.S. Application Data

(63) Continuation of application No. 09/313,593, filed on May 18, 1999, now Pat. No. 6,302,906, which is a continuation of application No. 08/662,484, filed on Jun. 13, 1996, now Pat. No. 5,916,263, which is a continuation of application No. 08/317,763, filed on Oct. 4, 1994, now Pat. No. 5,609,627, which is a continuation of application No. 08/312,881, filed on Sep. 27, 1994.

(30) **Foreign Application Priority Data**

Feb. 9, 1994 (EP) 94400284
Jun. 10, 1994 (EP) 94401306

(51) **Int. Cl.**
A61F 2/06 (2006.01)

(52) **U.S. Cl.** **623/1.16**

(58) **Field of Classification Search** 623/1.1, 623/1.11, 1.13, 1.15, 1.16, 1.22, 1.34, 1.35
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,304,557 A 2/1967 Polansky
3,500,820 A 3/1970 Almen
3,657,744 A 4/1972 Ersek
3,805,301 A 4/1974 Liebig
3,868,956 A 3/1975 Alfidi et al.

(Continued)

FOREIGN PATENT DOCUMENTS

AU PM 1537 4/1995

(Continued)

OTHER PUBLICATIONS

Search Report.

(Continued)


Primary Examiner — William H. Matthews

(74) *Attorney, Agent, or Firm* — Brooks, Cameron & Huebsch, PLLC

(57) **ABSTRACT**

A stent is provided comprising a plurality of hoops aligned along a common axis, wherein each of the hoops is oriented in a plane substantially perpendicular to the longitudinal axis of the stent. Each of the hoops includes a plurality of elongate elements joined to one another and forming apices that point in a direction along the axis of the stent. The stent also comprises means for securing an apex of one hoop to a juxtaposed apex of a neighboring hoop.

35 Claims, 23 Drawing Sheets



U.S. PATENT DOCUMENTS

3,878,565 A	4/1975	Sauvage	5,290,305 A	3/1994	Inoue
3,890,977 A	6/1975	Wilson	5,292,331 A	3/1994	Boneau
3,996,938 A	12/1976	Clark, III	5,304,200 A	4/1994	Spaulding
4,130,904 A	12/1978	Whalen	5,306,294 A	4/1994	Winston et al.
4,140,126 A	2/1979	Choudhury	5,314,472 A	5/1994	Fontaine
4,149,911 A	4/1979	Clabburn	5,330,500 A	7/1994	Song
4,202,349 A	5/1980	Jones	5,342,387 A	8/1994	Summers
4,214,587 A	7/1980	Sakura, Jr.	5,354,308 A	10/1994	Simon et al.
4,306,318 A	12/1981	Mano et al.	5,354,309 A	10/1994	Schnepp-Pesch
4,425,908 A	1/1984	Simon	5,360,443 A	11/1994	Barone et al.
4,494,531 A	1/1985	Gianturco	5,364,354 A	11/1994	Walker et al.
4,503,569 A	3/1985	Dotter	5,366,504 A	11/1994	Anderson et al.
4,512,338 A	4/1985	Balko et al.	5,370,683 A	12/1994	Fontaine
4,530,113 A	7/1985	Matterson	5,370,691 A	12/1994	Samson
4,545,082 A	10/1985	Hood	5,383,892 A	1/1995	Cardon
4,553,545 A	11/1985	Maass et al.	5,383,928 A	1/1995	Scott et al.
4,560,374 A	12/1985	Hammerslag	5,387,235 A	2/1995	Chuter
4,562,596 A	1/1986	Kornberg	5,389,106 A	2/1995	Tower
4,577,631 A	3/1986	Kreamer	5,395,349 A	3/1995	Quiachon et al.
4,580,568 A	4/1986	Gianturco	5,395,390 A	3/1995	Simon et al.
4,617,932 A	10/1986	Kornberg	5,397,345 A	3/1995	Lazarus
4,649,922 A	3/1987	Wiktor	5,405,377 A	4/1995	Cragg
4,655,771 A	4/1987	Wallsten	5,411,552 A *	5/1995	Andersen et al. 623/2.18
4,665,906 A	5/1987	Jervis	5,415,664 A	5/1995	Pinchuk
4,665,918 A	5/1987	Garza et al.	5,419,324 A	5/1995	Dillow
4,681,110 A	7/1987	Wiktor	5,429,144 A	7/1995	Wilk
4,728,328 A	3/1988	Hughes	5,443,496 A	8/1995	Schwartz
4,729,766 A	3/1988	Bergentz et al.	5,443,497 A	8/1995	Venbrux
4,732,152 A	3/1988	Wallsten et al.	5,443,498 A	8/1995	Fontaine
4,733,665 A	3/1988	Palmaz	5,456,713 A	10/1995	Chuter
4,739,762 A	4/1988	Palmaz	5,464,449 A	11/1995	Ryan et al.
4,762,128 A	8/1988	Rosenbluth	5,484,418 A	1/1996	Quiachon et al.
4,768,507 A	9/1988	Fischell et al.	5,489,295 A	2/1996	Piplani et al.
4,772,264 A	9/1988	Cragg	5,507,767 A	4/1996	Maeda
4,776,337 A	10/1988	Palmaz	5,507,771 A	4/1996	Gianturco
4,787,899 A	11/1988	Lazarus	5,522,880 A	6/1996	Barone et al.
4,795,463 A	1/1989	Gerow	5,540,712 A	7/1996	Kleshinski et al.
4,800,882 A	1/1989	Gianturco	5,562,724 A	10/1996	Vorwerk et al.
4,820,298 A	4/1989	Leveen et al.	5,562,726 A	10/1996	Chuter
4,830,003 A	5/1989	Wolff et al.	5,562,727 A	10/1996	Turk et al.
4,856,516 A	8/1989	Hillstead	5,562,728 A	10/1996	Lazarus et al.
4,878,906 A	11/1989	Lindemann et al.	5,571,170 A	11/1996	Palmaz et al.
4,886,062 A	12/1989	Wiktor	5,575,817 A	11/1996	Martin
4,886,065 A	12/1989	Collins, Jr.	5,609,605 A	3/1997	Marshall et al.
4,913,141 A	4/1990	Hillstead	5,609,627 A	3/1997	Goicoechea et al.
4,922,905 A	5/1990	Strecker	5,628,783 A	5/1997	Quiachon et al.
4,969,458 A	11/1990	Wiktor	5,632,772 A	5/1997	Alcime
4,969,890 A	11/1990	Sugita et al.	5,639,278 A	6/1997	Dereume et al.
4,994,032 A	2/1991	Sugiyama et al.	5,662,675 A	9/1997	Polanskyj Stockert et al.
4,994,071 A	2/1991	MacGregor	5,676,697 A	10/1997	McDonald
5,019,085 A	5/1991	Hillstead	5,683,448 A	11/1997	Cragg
5,019,090 A	5/1991	Pinchuk	5,683,450 A	11/1997	Goicoechea et al.
5,035,706 A	7/1991	Giantureo	5,693,086 A	12/1997	Goicoechea et al.
5,037,427 A	8/1991	Harada et al.	5,697,970 A	12/1997	Schmitt
5,041,126 A	8/1991	Gianturco	5,716,365 A	2/1998	Goicoechea et al.
5,047,050 A	9/1991	Arpesani	5,718,724 A	2/1998	Goicoechea et al.
5,057,092 A	10/1991	Webster, Jr.	5,725,572 A	3/1998	Lam
5,064,435 A	11/1991	Porter	5,741,332 A	4/1998	Schmitt
5,067,957 A	11/1991	Jervis	5,776,180 A	7/1998	Goicoechea et al.
5,078,726 A	1/1992	Kreamer	5,800,456 A *	9/1998	Maeda et al. 623/1.15
5,078,736 A	1/1992	Behl	5,800,508 A *	9/1998	Goicoechea et al. 623/1.15
5,085,635 A	2/1992	Cragg	5,824,039 A *	10/1998	Piplani et al. 623/1.11
5,104,399 A	4/1992	Lazarus	5,824,042 A	10/1998	Lombardi
5,104,404 A	4/1992	Wolff	5,871,536 A	2/1999	Lazarus
5,123,917 A	6/1992	Lee	5,876,432 A	3/1999	Lau et al.
5,133,732 A	7/1992	Wiktor	5,916,263 A	6/1999	Goicoechea et al.
5,135,536 A	8/1992	Hillstead	5,938,696 A	8/1999	Goicoechea et al.
5,151,105 A	9/1992	Kwan-Gett	6,051,020 A	4/2000	Goicoechea et al.
5,161,547 A	11/1992	Tower	6,090,137 A	7/2000	Schmitt
5,163,958 A	11/1992	Pinchuk	6,102,938 A	8/2000	Evans et al.
5,183,085 A	2/1993	Timmermans	6,117,167 A	9/2000	Goicoechea et al.
5,192,297 A	3/1993	Hull	6,123,722 A	9/2000	Fogarty et al.
5,192,310 A	3/1993	Herweck et al.	6,129,756 A	10/2000	Kugler et al.
5,201,901 A	4/1993	Harada et al.	6,156,063 A	12/2000	Douglas
5,207,695 A	5/1993	Trout	6,159,239 A	12/2000	Greenhalgh
5,236,446 A	8/1993	Dumon	6,162,246 A	12/2000	Barone
5,275,622 A	1/1994	Lazarus	6,165,213 A	12/2000	Goicoechea et al.
5,282,824 A	2/1994	Gianturco	6,176,875 B1	1/2001	Lenker et al.
			6,197,049 B1	3/2001	Shaolian et al.

6,200,339	B1	3/2001	Leschinsky et al.	EP	0 656 197	A2	6/1995
6,210,435	B1	4/2001	Piplani et al.	EP	0 657 147	A2	6/1995
6,221,099	B1	4/2001	Andersen et al.	EP	734 235		6/1995
6,221,102	B1	4/2001	Baker et al.	EP	0 662 307	A1	7/1995
6,235,050	B1	5/2001	Quiachon et al.	FR	1602513		1/1971
6,251,133	B1	6/2001	Richter et al.	FR	2 678 508	A1	1/1993
6,251,134	B1	6/2001	Alt et al.	FR	2678508		1/1993
6,261,316	B1	7/2001	Shaolian et al.	GB	1205743		9/1970
6,270,523	B1	8/2001	Herweck et al.	GB	1 491 202		11/1977
6,273,909	B1	8/2001	Kugler et al.	GB	2 106 190	A	4/1983
6,280,467	B1	8/2001	Leonhardt	GB	2269104		2/1994
6,283,991	B1	9/2001	Cox et al.	JP	H02-68052		3/1990
6,287,335	B1	9/2001	Drasler et al.	JP	H02-167178		6/1990
6,302,906	B1	10/2001	Goicoechea et al.	JP	03076554		4/1991
6,312,462	B1	11/2001	McDermott et al.	JP	3133446		6/1991
6,325,819	B1	12/2001	Pavcnik et al.	JP	3151983		6/1991
6,325,826	B1	12/2001	Vardi et al.	JP	4025755		1/1992
6,331,190	B1	12/2001	Shokoohi et al.	JP	H04-500328		1/1992
6,334,869	B1	1/2002	Leonhardt et al.	JP	H05-76554		3/1993
6,344,056	B1	2/2002	Dehdashtian	JP	5305092		11/1993
6,348,066	B1	2/2002	Pinchuk et al.	JP	H05-509008		12/1993
6,361,557	B1	3/2002	Gittings et al.	JP	H06-7454		1/1994
6,395,019	B2	5/2002	Chobotov	JP	6023031		2/1994
6,395,022	B1	5/2002	Piplani et al.	JP	7501476		2/1995
6,398,803	B1	6/2002	Layne et al.	WO	WO 83/03752		11/1983
6,398,807	B1	6/2002	Chouinard et al.	WO	WO89/08433		9/1989
6,409,750	B1	6/2002	Hyodoh et al.	WO	WO 90/15582		12/1990
6,409,756	B1	6/2002	Murphy	WO	WO91/07928		6/1991
6,416,542	B1	7/2002	Marcade et al.	WO	WO 91/17789		11/1991
6,428,565	B1	8/2002	Wisselink	WO	WO92/00043		1/1992
6,440,166	B1	8/2002	Kolluri	WO	WO 92/06734		4/1992
6,454,795	B1	9/2002	Chuter	WO	WO93/13825		7/1993
6,464,721	B1	10/2002	Marcade et al.	WO	WO93/19703		10/1993
6,485,524	B2	11/2002	Strecker	WO	WO94/17754		8/1994
6,517,572	B2	2/2003	Kugler et al.	WO	WO 95/01761		1/1995
6,524,336	B1	2/2003	Papazoligou et al.	WO	WO95/01761		1/1995
6,540,777	B2	4/2003	Stenzel	WO	WO 95/08966		4/1995
6,547,820	B1	4/2003	Staudenmeier	WO	WO 95/16406		6/1995
6,551,350	B1	4/2003	Thornton et al.	WO	WO 97/09008		3/1997
6,565,596	B1	5/2003	White et al.	WO	WO 98/27895		7/1998
6,576,007	B2	6/2003	Dehdashtian et al.				
6,576,009	B2	6/2003	Ryan et al.				
6,582,458	B1	6/2003	White et al.				
6,592,614	B2	7/2003	Lenker et al.				
6,645,242	B1	11/2003	Quinn				
6,652,567	B1	11/2003	Deaton				
6,682,541	B1	1/2004	Gifford, III et al.				

FOREIGN PATENT DOCUMENTS

CA	2086333	4/1991
CA	2158373	10/1994
CA	2 144 305 C	2/1995
DE	3 918 736 A1	12/1990
DE	43 03 181	2/1993
DE	93 19 267.3 U	4/1994
DE	4 303 181 A1	8/1994
EP	0 145 166 B1	6/1985
EP	0 346 564 A1	12/1989
EP	0 357 003 A2	3/1990
EP	0 421 729 A2	4/1991
EP	0 423 619 A1	4/1991
EP	0 423 916 A1	4/1991
EP	461 791 A1	12/1991
EP	0 464 755	1/1992
EP	0 466 518 B1	1/1992
EP	0 480 667 A1	4/1992
EP	0 508 473 A2	10/1992
EP	539 237 A1	4/1993
EP	0 540 290 A2	5/1993
EP	0 551 179 A1	7/1993
EP	0 556 850 A1	8/1993
EP	0 565 251 A1	10/1993
EP	0 579 523 A1	1/1994
EP	0 536 164 B1	3/1994
EP	0 481 365 B1	6/1994
EP	0 621 015 A1	10/1994
EP	0 621 016 A1	10/1994
EP	0 622 088 A1	11/1994
EP	0 646 365 A1	4/1995

OTHER PUBLICATIONS

- Dotter et al., "Transluminal Expandable Nitinol Coil Stent Grafting: Preliminary Report", Technical Developments and Instrumentation, *Radiology*, vol. 147, pp. 259-260 (Apr. 1983).
- Schetky, "Shape-Memory Alloys", pp. 74-82.
- K. Otsuka et al., "Shape-Memory Alloys—Pseudoelasticity", *Metals Forum*, vol. 4, No. 3, pp. 142-152 (1981).
- Cragg et al., "Nonsurgical Placement of Arterial Endoprostheses: A New Technique Using Nitinol Wire", *Radiology*, vol. 147, No. 1, pp. 261-263 (Apr. 1983).
- Cragg et al., "Percutaneous Arterial Grafting", *Radiology*, vol. 150, No. 1, pp. 45-49 (1984).
- Cragg et al., "Stents Vascular Stents", *Interventional Radiology*, pp. 686-692 (1990).
- T.W. Duerig et al., "An Engineer's Perspective of Pseudoelasticity", pp. 369-393.
- Office Action of Canadian Intellectual Property Office for Application No. 2,182,982 dated Jun. 14, 2004.
- Notice of Reasons of Rejection of Japan Patent Office Application No. H07-521275 dated May 18, 2004.
- Notice of Opposition by Scimed Life Sciences, Inc. to European Patent No. 0 676 937 B.
- Opposition by William Cook Aps to European Patent No. 0 676 937 B.
- Verlag, "Interventional Radiology," pp. 692-699 (1990).
- Yoshioka et al., "Self-Expanding Endovascular Graft: An Experimental Study in Dogs," *AJR* 15: pp. 673-676 (1988).
- U.S. Appl. No. 08/051,728.
- Official Action in Canadian Application No. 2,182,982, issued by the Canadian Intellectual Property Office on Mar. 30, 2006.
- Notice of Reasons for Rejection of Japan Patent Application No. 2004-335171 dated Apr. 24, 2007.

Notice of Reasons for Rejection of Japan Patent Application No. 2006-104574 dated May 15, 2007.

Notice of Reasons for Rejection of Japan Patent Application No. 2006-104577 dated May 15, 2007.

Decision from United States Court of Appeal for the Federal Circuit for *Boston Scientific Scimed, Inc. v. Medtronic Vascular, Inc. and Eric C. Martin* dated Aug. 8, 2007.

Video cassette allegedly showing operation conducted by Geoffrey H. White on Nov. 26, 1993.

Declaration of Geoffrey H. White executed Feb. 18, 2000.

Declaration of Ian L. Gordon executed Jun. 17, 2000.

Declaration of W. Davis dated Feb. 28, 2000.

Declaration of Mark Dehdashtian dated Jun. 16, 2000.

Communication of a Notice of Opposition dated Jan. 26, 2001 for EP 783 873 (including Notice of Opposition).

Communication of a Notice of Opposition dated Jan. 26, 2001 for EP 783 874 (including Notice of Opposition).

* cited by examiner

FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3




FIG. 4A




FIG. 4F




FIG. 4E




FIG. 4D




FIG. 4C




FIG. 4B




FIG. 5




FIG. 6




FIG. 7




FIG. 8A




FIG. 8B



FIG. 8C




FIG. 8D




FIG. 8E




FIG. 8F




FIG. 8G




FIG. 9




FIG. 10A





FIG. 10B






FIG. 12




FIG. 11




FIG. 14




FIG. 13




FIG. 16






FIG. 15







FIG. 20

FIG. 19

FIG. 21A




FIG. 21B




FIG. 21C




FIG. 23





FIG. 22






FIG. 24B





FIG. 24A






FIG. 27




FIG. 26

FIG. 28





FIG. 29






FIG. 31




FIG. 30

FIG. 34




FIG. 33





FIG. 32



1

ENDOLUMINAL STENT

This application is a continuation of Ser. No. 09/313,593, filed May 18, 1999, now U.S. Pat. No. 6,302,906, which is a continuation of Ser. No. 08/662,484, filed Jun. 13, 1996, now U.S. Pat. No. 5,916,263, which is a continuation of Ser. No. 08/317,763, filed Oct. 4, 1994, now U.S. Pat. No. 5,609,627, which is a continuation-in-part of Ser. No. 08/312,881, filed Sep. 27, 1994, now pending. This application is also a continuation-in-part of Ser. No. 08/312,881.

BACKGROUND OF THE INVENTION

The present invention relates to a bifurcated endoluminal prosthesis for use in a bifurcated blood vessel such, for example, as the infrarenal portion of a mammalian aortic artery where it bifurcates to the common iliac arteries. The present invention also embraces a stent connecting means for connecting a stent (e.g. a stent which forms part of an endoluminal prosthesis) to another stent, as well as apparatus and method for introducing prostheses to the vasculature and methods of treating angeological diseases.

A stent is used to provide a prosthetic intraluminal wall e.g. in the case of a stenosis to provide an unobstructed conduit for blood in the area of the stenosis. An endoluminal prosthesis comprises a stent which carries a prosthetic graft layer of fabric and is used e.g. to treat an aneurysm by removing the pressure on a weakened part of an artery so as to reduce the risk of embolism, or of the natural artery wall bursting. Typically, a stent or endoluminal prosthesis is implanted in a blood vessel at the site of a stenosis or aneurysm by so-called "minimally invasive techniques" in which the stent is compressed radially inwards and is delivered by a catheter to the site where it is required through the patient's skin or by a "cut down" technique in which the blood vessel concerned is exposed by minor surgical means. When the stent is positioned at the correct location, the catheter is withdrawn and the stent is caused or allowed to re-expand to a predetermined diameter in the vessel.

U.S. Pat. No. 4,886,062 discloses a vascular stent which comprises a length of sinuous or "zig-zag" wire formed into a helix; the helix defines a generally cylindrical wall which, in use, constitutes a prosthetic intraluminal wall. The sinuous configuration of the wire permits radial expansion and compression of the stent; U.S. Pat. No. 4,886,062 discloses that the stent can be delivered percutaneously and expanded in situ using a balloon catheter.

U.S. Pat. No. 4,733,665 discloses an expandable intraluminal graft which is constituted by a tubular member formed from a plurality of intersecting elongate members which permit radial expansion and compression of the stent.

EP-A-0556850 discloses an intraluminal stent which is constituted by a sinuous wire formed into a helix; juxtaposed apices of the wire are secured to one another so that each hoop of the helix is supported by its neighboring hoops to increase the overall strength of the stent and to minimize the risk of plaque herniation; in some embodiments the stent of EP-A-0556850 further comprises a tubular graft member to form an endoluminal prosthesis.

The prior art stents and prostheses mentioned above are generally satisfactory for the treatment of aneurysms, stenoses and other angeological diseases at sites in continuous un-biurcated portions of arteries or veins.

However, the prior art stents and prostheses are not wholly satisfactory for use where the site of desired application of the stent or prosthesis is juxtaposed or extends across a bifurcation in an artery or vein such, for example, as the bifurcation

2

in the mammalian aortic artery into the common iliac arteries. For example, in the case of an abdominal aortic aneurysm ("AAA") in the infrarenal portion of the aorta which extends into one of the common iliac arteries, the use of one of the prior art prostheses referred to above across the bifurcation into the one iliac artery will result in obstruction of the proximal end of the other common iliac artery; by-pass surgery is therefore required to connect the one iliac artery in juxtaposition with the distal end of the prosthesis to the other blocked iliac artery. It will be appreciated by a person skilled in the art that it is desirable to avoid surgery wherever possible; the requirement for by-pass surgery associated with the use of the prior art prosthesis in juxtaposition with a bifurcation in an artery therefore constitutes a significant disadvantage.

SUMMARY OF THE INVENTION

Throughout this specification, the term "proximal" shall mean "nearest to the heart," and the term "distal" shall mean "furthest from the heart."

According to one aspect of the present invention there is provided a stent connecting means for connecting two intraluminal stents one to the other to define a continuous lumen through the two stents, the stent connecting means including a first stent including a male engaging portion which can be compressed radially inwardly, and a second stent including a female cooperating portion. The male engaging portion may be entered into the female cooperating portion in a radially compressed state and thereafter caused or allowed to expand in the female cooperating portion; the arrangement being such that in service the interengagement of the male engaging portion and the female cooperating portion serves to resist longitudinal separation of the two stents one from the other.

Typically, the first stent may include a proximal male engaging portion; the second stent may include a distal female cooperation portion. The male engaging portion may be flared radially outwardly towards its extremity, and the female cooperating portion may be tapered radially inwardly towards its extremity. In some embodiments, the male engaging portion may comprise a frustoconical wall which flares outwardly towards its longitudinal extremity; the female engaging portion may comprise a frustoconical wall which tapers radially inwardly towards its longitudinal extremity.

Alternatively, said male engaging and female cooperating portions may be substantially untapered; they may be substantially cylindrical.

The male engaging portion of the first stent may be resiliently compressible in a radially inwards direction such that in the radially compressed state it is capable of self-reexpansion to engage in the female cooperating portion. Typically, each of said first and second stents may be resiliently compressible.

In use therefore the second stent may be delivered in a radially compressed state by using a catheter; when the second stent is located at the site of use, the catheter may be withdrawn thereby allowing the second stent to re-expand to engage the endoluminal surface of the blood vessel.

The first stent may then be delivered percutaneously or by a "cut down" technique to a site distal of the second stent such that the male engaging portion of the first stent in the radially compressed state is entered into the expanded female cooperating portion of the second stent; the catheter may then be withdrawn allowing the first stent to re-expand such that the male engaging portion engages in the female cooperating portion of the second stent.

In some embodiments of the present invention the second stent may have two transversely spaced distal female coop-

3

erating portions; the second stent may therefore constitute a bifurcated stent for use in juxtaposition with a bifurcation in a blood vessel.

Each of the two transversely spaced distal female cooperating portions may be adapted for connection to a first male stent which, in use, extends across the bifurcation into a respective one of the branched blood vessels.

In a particular aspect of the present invention there is provided a bifurcated intraluminal stent for use in juxtaposition with an aneological bifurcation; the bifurcated intraluminal stent comprising a proximal portion adapted to be positioned in service in a blood vessel in juxtaposition with a bifurcation, a first distal stent portion adapted to extend across the bifurcation into one of the branched blood vessels and a second distal stent portion adapted to allow blood to flow from the proximal portion into the other branched vessel. The first distal stent portion may be formed integrally with the proximal portion.

In some embodiments the second distal stent portion may comprise a female cooperating portion which is adapted to engage a male engaging portion of another stent adapted to extend in the other branched blood vessel such that, in use, the bifurcated stent can be connected in situ to the other stent. The bifurcated intraluminal stent may therefore constitute a second stent in accordance with the present invention comprising a distal female cooperating portion disposed intermediate the proximal and distal extremities of the stent; the other stent may constitute a first stent in accordance with the present invention.

Typically, the proximal end of said second stent may be flared radially outwardly towards its extremity to engage the endoluminal surface of the artery thereby to resist longitudinal movement of the second stent in service.

Each of the first and second stents may comprise a sinuous wire formed into a tubular configuration. The sinuous and tubular configurations may be imparted to the wire by winding it on a mandrel. Typically, each stent may be made from a shape memory nitinol (nickel-titanium) wire which may be wound on to the mandrel to form the stent in a tubular configuration of slightly greater diameter than the diameter of the blood vessel in which the stent is intended to be used. The stent may be annealed at an elevated temperature and then allowed to cool in air so that the nitinol wire "remembers" the configuration in which it was wound on the mandrel.

Said nitinol wire may be type "M" nitinol wire which is martensitic at temperatures below about 13° C. and is austenitic at temperatures above about 25° C.; it will be appreciated therefore that the type "M" wire will be austenitic at body temperature of 37° C. Typically, the annealing may be conducted at about 500° C. or more for at least about 60 minutes; after cooling the wire may be immersed in cold water to facilitate removal of the wire from the mandrel with the wire in its maleable martensitic form. Typically, the cold water may have temperature of less than about 10° C.; the wire may be immersed for about 5 minutes or more. An advantage of using nitinol wire to form the stent in accordance with the present invention is that the nitinol wire is "super elastic" in its austenitic state; the radial outward force exerted by the stent on the wall of the blood vessel in use is therefore substantially constant irrespective of the diameter of the vessel and the expanded stent.

In some embodiments the wire may have a helical configuration as disclosed in EP-A-0556850. Alternatively, the wire may be of an entirely novel configuration, namely one in which the wire forms a plurality of hoops such that the plane of the circumference of each hoop is substantially perpendicular to the longitudinal axis of the stent. Each hoop may

4

comprise a substantially complete turn of the wire having a sinuous configuration; optionally, as each hoop is completed, the point of winding the wire may be displaced longitudinally with respect to the winding axis to form the next hoop. When the next hoop is complete, the point of winding is moved further longitudinally with respect to the winding axes to the form the next succeeding hoop and so on.

It will be appreciated that an advantage of this novel arrangement is that the planes of the hoops are not skewed with respect to the longitudinal axis of the stent; the longitudinal ends of the stent are "square" to said longitudinal axis, so that when the stent is caused or allowed to expand in situ there is substantially no twisting of the stent as it shortens in length. It will be appreciated that this represents a significant advantage, as in areas of stenosis or aneurysm it is desirable to minimize the movement of the stent within the blood vessel so as to reduce the potential trauma to the patient. A stent of this configuration may be used, apart from the bifurcated embodiment otherwise taught herein, in any application in which stents generally have heretofore been used.

Typically, the stents of this invention whether of the helical or perpendicular variety, also comprise a securing means for securing an apex of the sinuous wire in one hoop to a juxtaposed apex of a neighboring hoop so that each hoop is supported by its neighbors. The securing means may comprise a loop element of a suture material, for example, to tie the juxtaposed apices together; the loop element may also comprise a loop formed of a thermoplastics material such, for example, as polypropylene. Alternatively, the securing means may be a bead formed of a thermoplastic material around juxtaposed apices. Also alternatively, the securing means may be a loop, ring, or staple formed of wire such as nitinol.

The male engaging portion and female cooperating portion, of the first and second interengaging stents of this invention, may be formed separately from the remainder of the respective nonengaging portions of these stents and then the engaging and non-engaging portions secured to one another by securing means.

In one embodiment of the present invention, the proximal and distal stent portions of the bifurcated stent in accordance with the present invention may be formed separately; the distal end of the proximal stent portion may be secured to the wider proximal end of a first intermediate frustoconical stent portion; the narrower distal end of the first intermediate frustoconical stent portion may be secured to the proximal end of the distal stent portion. The female cooperating portion of the bifurcated stent may be constituted by a second frustoconical stent portion which is secured to the distal end of the proximal stent portion in juxtaposition with the first frustoconical portion.

Alternatively the first and second frustoconical portions may be omitted; the proximal and distal stent portions may be secured directly one to the other.

The female cooperating portion may be constituted by a generally cylindrical stent portion secured to said proximal stent portion in transversely spaced relation to the distal portion.

Each of the first and second stents of the bifurcated form of the present invention may carry a tubular graft layer formed from a biocompatible fabric in juxtaposition with the stent; the combined stent and graft layer constituting an endoluminal prosthesis. Typically the graft layer may be disposed externally of the stent; it will be appreciated however that in some embodiments the graft layer may be disposed internally of the stent. In some embodiments the graft layer may be secured to the stent by loop elements such, for example, as loops of polypropylene. The biocompatible fabric may be a

5

polyester fabric or a polytetrafluoroethylene fabric; typically said fabric may be woven or a warp knitted polyester fabric. In some embodiments the woven or a warp knitted fabric may be formed in a seam-free bifurcated configuration as a sleeve for a bifurcated stent.

In some embodiments the male engaging portion of the first stent and the female cooperating portion of the second stent may be left uncovered. Alternatively, the fabric graft layer may extend to the proximal extremity on the external surface of the male engaging portion, and may be folded over the distal extremity of the female engaging portion to form an inner sleeve; in use the external fabric of the male engaging portion may butt against the folded over portion of the fabric internally of the female cooperating portion to form a substantially blood tight seal.

The present invention in one aspect therefore includes a bifurcated endoluminal prosthesis comprising a bifurcated stent in accordance with the invention and a tubular graft layer.

The first stent having the male engaging portion may also have a tubular graft layer. If required the first prosthesis may be introduced in a radially compressed state such that the male engaging portion of the first prosthesis is engaged in the intermediate female cooperating portion of the bifurcated prosthesis; the first prosthesis is then caused to be allowed to reexpand in situ such that the male engaging portion engages in the female cooperating portion to resist longitudinal separation of the two prosthesis in service.

The bifurcated prosthesis may be adapted for use in the infrarenal portion of a mammalian aorta in juxtaposition with the bifurcation of the common iliac arteries for the treatment of abdominal aortic aneurysms. In use the bifurcated endoluminal prosthesis may be introduced into the infrarenal portion of the aorta using a catheter such that the first distal stent portion extends into one of the branched iliac arteries; the catheter may then be withdrawn allowing the prosthesis to re-expand in situ.

It will be appreciated by a person skilled in the art that the prostheses may be introduced to the site of use percutaneously or by "cut down" techniques.

Any of the stents according to this invention may be provided on its external surface with circumferentially spaced wire barbs or hooks adapted to engage in the endoluminal surface of the host artery to resist longitudinal movement or slippage of the stent in use. Typically the barbs or hooks may be disposed on part of the stent which is provided with a fabric graft layer such that in use the points of the artery which are engaged by the barbs or hooks are covered by the fabric graft. It will be appreciated by a person skilled in the art that the trauma to the artery wall caused by the hooks or barbs may cause emboli; the provision of the fabric graft over the barbs or hooks in use will therefore help to prevent the introduction of such emboli into the blood stream.

The male engaging portion for the first stent may be provided with circumferentially spaced hooks or barbs on its external surface to engage the internal surface of said female cooperating means, thereby to reinforce the connecting means against longitudinal separation of the stents one from the other in the service.

The present invention therefore provides a connecting means for connecting two stents longitudinally one to the other. It will be appreciated that this represents a significant step forward in the art as it allows the provision of a bifurcated endoluminal prosthesis for use in juxtaposition e.g. with arterial bifurcations without requiring by-pass surgery to connect one of the branched arteries to the other branched artery.

6

In particular, the invention provides a bifurcated endoluminal prosthesis which can be positioned in an artery in juxtaposition with a bifurcation to extend into one of the branched arteries; the bifurcated prosthesis can be connected to another prosthesis which extends into the other branched artery. The prosthesis can be delivered percutaneously or by "cut down" methods and connected together in situ thereby to provide effective treatment of an angeological disease such, for example, as an aneurysm or a stenosis which extends across a bifurcation in a blood vessel without the need for by-pass surgery.

In another aspect, this invention provides an introducer for delivering, into the vasculature at an angeological bifurcation where a blood vessel branches into two branched vessels, a bifurcated endoluminal stent or prosthesis having a proximal portion adapted to be disposed in the blood vessel and a distal portion adapted to be disposed at least partially in one of the two branched vessels. The introducer comprises a tubular outer sheath, a proximal portion pusher disposed at least partially within the outer sheath, and a distal portion pusher disposed at least partially within the proximal portion pusher.

The present invention further provides an introducer for delivering into the vasculature at an angeological bifurcation where a blood vessel branches into two branched vessels, an endoluminal prosthesis having a proximal stent portion and a distal stent portion. The introducer comprises a tubular outer sheath, a proximal portion pusher disposed at least partially within the outer sheath and having a proximal end adapted to contact the proximal stent portion, a distal portion pusher disposed at least partially within the proximal portion pusher and having a proximal end adapted to contact the distal stent portion; and a balloon catheter, having a balloon attached thereto, disposed at least partially within the distal portion pusher.

This invention in another aspect provides a method for delivering a bifurcated endoluminal stent or prosthesis having a proximal portion and a first distal portion into the vasculature at an angeological bifurcation where a blood vessel branches into a first branched vessel and a second branched vessel. The method comprises inserting a first introducer containing the stent or prosthesis into the vasculature to a predetermined delivery location, the first introducer comprising an outer sheath, a proximal portion pusher, and a distal portion pusher; withdrawing the outer sheath of the first introducer while maintaining the proximal portion pusher in a fixed position until the proximal portion of the stent or prosthesis is deployed from the first introducer into the blood vessel; withdrawing the outer sheath and the proximal portion pusher while maintaining the distal portion pusher in a fixed position until the first distal portion of the stent or prosthesis is deployed from the first introducer at least partially into the first branched vessel; and withdrawing the first introducer from the vasculature.

This invention further provides a method for delivering, into the vasculature at an angeological bifurcation where a blood vessel branches into two branched vessels, an endoluminal prosthesis having a proximal stent portion, and a distal stent portion. The method comprises the steps of inserting an introducer containing the prosthesis into the vasculature to a predetermined delivery location, the introducer comprising an outer sheath, a proximal stent portion pusher, a distal stent portion pusher, and a balloon catheter having a balloon attached thereto; inflating the balloon to at least partially block blood flow in the blood vessel; withdrawing the outer sheath of the introducer while maintaining the proximal stent portion pusher in a fixed position until the proximal stent portion of the prosthesis is deployed from the introducer into

7

the blood vessel; withdrawing the outer sheath and the proximal stent portion pusher while maintaining the distal stent portion pusher in a fixed position until the distal stent portion of the prosthesis is deployed from the introducer into the blood vessel; and withdrawing the introducer from the vasculature.

In general, this invention provides a method of treating an aneological disease at a bifurcation site where a blood vessel branches into a first branched vessel and a second branched vessel comprising the steps of disposing in the blood vessel a proximal portion of an endoluminal stent; directing blood flow from the blood vessel into the first branched vessel through a first distal portion of the endoluminal stent, the first distal portion being connected to the proximal portion and extending into the first branched vessel; and directing blood flow from the blood vessel into the second branched vessel through a second distal portion of the endoluminal stent, the second distal portion being connected to the proximal portion and extending into the second branched vessel. This method may be applied to aneurysms, occlusions, or stenosis.

Following is a description by way of example only and with reference to the accompanying drawings of the present invention, including novel stent constructions and methods of manufacture and use thereof.

BRIEF DESCRIPTION OF THE DRAWINGS

The aspects, features and advantages of the present invention will be more readily understood from the following detailed description when read in conjunction with the accompanying drawings, in which:

FIG. 1a is a front view of a bifurcated intraluminal stent in accordance with the present invention constituting part of an endoluminal prosthesis.

FIG. 1b is a front view of another stent which is adapted to be connected to the bifurcated stent of FIG. 1a.

FIG. 2(a) is a side view of part of the bifurcated stent of FIG. 1a opened up to show its construction.

FIG. 2(b) is a side view of an exemplary mandrel used to form the part of the bifurcated stent shown in FIG. 2(a).

FIG. 3 is a side view of another part of the bifurcated stent of FIG. 1a opened up to show its construction.

FIG. 4(a) is a side view of yet another part of the bifurcated stent of FIG. 1a opened up to show its construction.

FIG. 4(b)-4(f) are partial exploded views of the exemplary stent of FIG. 4(a) illustrating alternative means for securing juxtaposed apices according to the present invention.

FIG. 5 is a schematic perspective view of a bifurcated endoluminal prosthesis in accordance with the present invention.

FIG. 6 is a schematic view of another bifurcated endoluminal prosthesis in accordance with the present invention.

FIG. 7 is a schematic view of yet another bifurcated endoluminal prosthesis in accordance with the present invention.

FIG. 8(a) is a cross-sectional view of an exemplary assembled introducer according to the present invention.

FIGS. 8(b)-8(e) are side views of the component parts of the introducer of FIG. 8(a).

FIG. 8(f) is a partial cross-sectional view of the introducer of FIG. 8(a).

FIG. 8(g) is a cross-sectional view of part of the introducer of FIG. 8(f) taken along the line A-A.

FIG. 9 is a side cross-sectional view of a portion an alternative embodiment of an introducer according to the present invention.

8

FIGS. 10(a) and 10(b) are side views of other alternative embodiments of an introducer according to the present invention.

FIGS. 11 through 20 are sequential cross-sectional views of the bifurcation of the abdominal aortic artery during introduction of an exemplary prosthesis according to the present invention.

FIGS. 21(a)-21(c) are cross-sectional views of alternative insertion apparatus according to the present invention.

FIGS. 22 and 23 are side views of alternative stents according to the present invention.

FIGS. 24(a), 24(b), 25, 26 and 27 are sequential cross-sectional views of the bifurcation of the abdominal aortic artery during introduction of an exemplary prosthesis according to the present invention.

FIGS. 28 and 29 are cross-sectional side views of alternative delivery apparatus according to the present invention.

FIGS. 30-34 are sequential cross-sectional views of the bifurcation of the abdominal aortic artery during introduction of an exemplary prosthesis according to the present invention.

DETAILED DESCRIPTION

The present invention includes apparatus and method for treating aneological diseases in any bifurcated blood vessel. One example of such a bifurcated blood vessel is the infrarenal portion of a mammalian aortic artery where it bifurcates to the common iliac arteries. Examples of diseases that can be treated using the apparatus and method of the present invention include aneurysm, stenosis, and occlusion.

A bifurcated stent in accordance with the present invention which is indicated at 10 in FIG. 1a comprises a wire skeleton which is constructed in four separate parts, namely a proximal part 12, a first frustoconical part 14, a first distal part 16 and a second frustoconical part 18. Said bifurcated stent 10 carries a fabric graft layer (FIGS. 5, 6, and 7) for use as an endoluminal prosthesis e.g. in the infrarenal portion of a mammalian aorta in juxtaposition with the bifurcation of the common iliac arteries. It will be appreciated, however, that bifurcated stents (with or without fabric graft layers) for use in different parts of the aneological system and for different mammals can be constructed in accordance with the invention by varying the dimensions of the stent accordingly.

Each of the four parts of the bifurcated stent 10 is made in substantially the same way by winding a shape memory nitinol wire, typically nitinol type M wire, onto a mandrel 46.

The construction of the exemplary proximal part 12 of the bifurcated stent 10 is shown in FIGS. 2(a) and 2(b); nitinol wire type M wire typically having a diameter of 0.46 mm (0.018") is wound around mandrel 46 to form a plurality of hoops 20. The winding surface of mandrel 46 is provided with a plurality of upstanding pins 47 disposed in a zig-zag pattern for each of the hoops 20 so that in each hoop 20 the nitinol wire follows a sinuous path to define a plurality of circumferentially spaced apices 22. Each hoop 20 is wound onto mandrel 46 such that the plane of the circumference of each hoop 20 is substantially perpendicular to the longitudinal axis of the mandrel.

When one hoop 20 e.g. the hoop indicated at 20a has been formed, the point of winding of the nitinol wire is displaced longitudinally with respect to the axis of mandrel 46 to form the next successive hoop 20b. The stent shown in FIG. 2(a) is the stent formed on mandrel 46 shown in FIG. 2(b) after cutting the stent longitudinally and rotating it 45 degrees to show the construction of the stent.

The proximal part of the exemplary bifurcated stent of FIG. 1a is formed on the mandrel with a diameter of about 24 mm

9

and a length in the longitudinal direction of about 55 mm. From FIGS. 1(a), 2(a), and 2(b) it will be noted that the proximal part 12 is constituted by three hoops 20 of unit width at the proximal end 24 of the proximal part 12, two intermediate hoops 25 of twice unit width and, at its distal end 26, by a single hoop 20 of unit width. In the illustrated embodiment, intermediate hoops 25 have a plurality of is offsets 25a. Offsets 25a are formed when the wire is passed around pins 47 on mandrel 46. Offsets 25a add stability to the stent. When the nitinol wire has been wound onto mandrel 46, the nitinol wire is annealed at an elevated temperature and then allowed to cool.

In this embodiment of the invention the wire is annealed at a temperature of about 500° C. for 60 minutes and is then allowed to cool in air. The purpose of the annealing is so that the nitinol wire in its austenitic form "remembers" its configuration as wound on mandrel 46; it will be appreciated therefore that other temperatures and durations for the annealing are included within the present invention provided the nitinol wire "remembers" its wound configuration.

After annealing and cooling, the wire is immersed in cold water at less than 10° C. for about 5 minutes; the wire is then removed from the mandrel, and juxtaposed apices 22 of neighboring hoops 20 are secured together by securing means 99 (see FIG. 4(a)), which are, in this example, 0.003" polypropylene filaments. Each apex 22 of each hoop 20 which has a juxtaposed apex of a neighboring hoop 20 is tied to the juxtaposed apex 22. It will be appreciated, however, that in other embodiments of the invention only some of the juxtaposed apices 22 may be secured in this way.

In addition to polypropylene filaments, the securing means may comprise a loop element 99a of a suture material, for example, to tie the juxtaposed apices together, as shown in FIG. 4(b). The securing means may also comprise bead 99b formed of a thermoplastic material around juxtaposed apices, as shown in FIG. 4(c). Also alternatively, the securing means may be a loop 99c, ring 99d, or staple 99e formed of wire such as nitinol, as shown in FIGS. 4(d), 4(e), and 4(f) respectively.

The exemplary first and second frustoconical parts 14, 18 of the skeleton shown in the figures are formed in substantially the same way as the proximal part 12 by winding nitinol wire onto a mandrel and then annealing the wire before removing it from the mandrel. As shown in FIG. 3, the first and second frustoconical parts 14, 18 are each constituted by three hoops 20 of unit width. The mandrel is tapered such that the proximal end of each of the exemplary frustoconical parts 14, 18 is formed with a diameter of about 12 mm and the distal end 32 of each is formed with a diameter of about 9 mm. The overall length of each of the exemplary frustoconical parts 14, 18 is about 18 mm. The wire used for the frustoconical parts 14, 18 is nitinol type M wire having a diameter of 0.28 mm (0.011"). Juxtaposed apices 22 of each of the exemplary frustoconical parts 14, 18 are tied together using 0.03" polypropylene filaments as described above. The first and second frustoconical parts 14, 18 are secured to the distal end 26 of the proximal part 12 of the stent 10 in transversely spaced relation as shown in FIG. 1a by securing the apices 22 of the hoop 20 forming the wider proximal end 30 of each of the frustoconical parts 14, 18 to juxtaposed apices 22 of the hoop 20 on the distal end 26 of the proximal part 12.

The exemplary first distal part 16 of the bifurcated stent 10 is formed by winding nitinol type M wire typically having a diameter of 0.28 mm (0.011") onto a mandrel to form twelve longitudinally spaced hoops 20 as shown in FIG. 4; the exemplary first distal part has an overall length of about 66 mm and a uniform diameter of about 9 mm. The proximal end 34 of the distal part 16 is secured to the narrower distal end 32 of the

10

first frustoconical part 14 by tying each apex 22 on the proximal end 34 of the first distal part 16 to a juxtaposed apex on the distal end 32 of the first frustoconical part 14 using, in this embodiment, 0.003" polypropylene filaments.

The proximal part 12, the first and second frustoconical parts 14, 18, and the first distal part 16 are each covered with a tubular graft layer of a biocompatible woven fabric (FIGS. 5, 6, and 7) such, for example, as a plain woven fabric made from 30 or 40 denier polyester. The tubular fabric layers may be attached to the proximal and distal parts 12, 16 of the stent 10 by stitching with, for example, 0.003" polypropylene filaments around the apices 22 of the underlying skeleton. The fabric covered stent constitutes one form of an endoluminal prosthesis.

The proximal part 12 of the wire skeleton may be provided with a plurality of circumferentially spaced hooks or barbs 43 which project through the tubular fabric layer to engage in the endoluminal surface of a host artery in service.

The sinuous configuration of each turn 20 of the wire skeleton of the stent 10 allows the prosthesis to be compressed resiliently radially inwards so that it can be received in a catheter e.g. a 16 or 18 French catheter for percutaneous or cut down delivery, e.g. to an intraluminal site in the infrarenal section of the aortic artery. Larger diameter catheters up to, e.g., 20 French, may be used to deliver the prosthesis using "cut down" procedures.

An x-ray opaque marker may be attached to one or more ends of a stent so that the delivery of the stent can be monitored using x-rays. As shown in FIG. 4(a), such a radiopaque marker may typically comprise a gold or platinum wire 17 crimped onto an end of stent 16. Alternatively, the radiopaque marker may be a tube 17a disposed around a length of wire on the stent, also as shown in FIG. 4(a). Typically, in the bifurcated stent the marker is secured to the stent in line with the distal stent portion so that the distal stent portion can be aligned with and inserted into one of the branched arteries in situ.

The bifurcated endoprosthesis is positioned in the infrarenal section of the aortic artery in juxtaposition with the bifurcation of the common iliac arteries such that the first distal part 16 of the prosthesis extends into one of the common iliac arteries. The catheter is then withdrawn allowing the stent 10 to re-expand towards its configuration as wound on the mandrel in which it was annealed until the stent engages the endoluminal surface of the host artery. The barbs or hooks engage the endoluminal surface of the host artery to resist longitudinal displacement or slipping of the prosthesis in use.

It will be appreciated that when the bifurcated prosthesis is positioned and re-expanded in the fitted position, blood can flow from the aortic artery into the proximal part 12 of the prosthesis from where it can flow into the one common iliac artery through the frustoconical part 14 and the first distal part 16 and also into the other common iliac artery through the second frustoconical part 18.

In cases where it is required to implant a prosthesis in the other common iliac artery a second prosthesis comprising a second stent 40 as shown in FIG. 1b can be used. The second stent 40 includes a wire skeleton comprising a proximal frustoconical part 42 and a distal part 44. The distal part 44 of the second stent 40 also may be covered with a tubular graft layer of a biocompatible fabric such, for example, as polyester or polytetrafluoroethylene fabric (FIGS. 5, 6, and 7).

The frustoconical proximal part 42 is constructed in the same way as the frustoconical parts 14, 18 of the bifurcated stent 10; the distal part 44 is constructed in the same way as the distal part 16 of the bifurcated stent 10. The distal end of the frustoconical proximal part 42 is secured to the proximal

11

end of the distal part **44** by securing juxtaposed apices using polypropylene filaments as described above.

In use, the second prosthesis is compressed radially inwards and is received in a catheter for percutaneous or "cut down" delivery to the other common iliac artery. The frustoconical proximal part **42** is guided, in the radially compressed state, into the second frustoconical part **18** of the bifurcated stent **10**. The catheter is then withdrawn allowing the second stent **40** to re-expand towards its remembered configuration, until the distal part **14** engages the endoluminal surface of the other common iliac artery, and the outer surface of the frustoconical proximal part **42** engages the interior surface of the second frustoconical part **18** of the bifurcated stent **10**.

As with other stents described herein, the frustoconical proximal part **42** may be formed with circumferentially spaced barbs or hooks **43**, as shown in FIG. **1b**, which engage in the wire skeleton of the second frustoconical part **18** of the bifurcated stent **10**. When barbs **43** are on proximal portion **12**, they engage the inner wall of the artery.

The tapered configurations of the second frustoconical part **18** of the bifurcated stent **10** and of the proximal frustoconical part **42** of the second stent **40** are such that in the fitted position as described, the prosthesis are locked together to resist longitudinal separation in service. Barbs or hooks on the second stent **40** and/or a frustoconical proximal part **42** help to resist such longitudinal separation.

In another example of the present invention a bifurcated endoluminal prosthesis **50** as shown in FIG. **5** includes a bifurcated stent comprising a proximal portion **52** which tapers radially inwardly from its proximal end **54** to its distal end **56**, and first and second transversely spaced frustoconical distal portions **58, 60** which are secured to the distal end **56** of the proximal portion **52**; the proximal portion **52** is covered with a tubular graft layer of a biocompatible fabric **62**.

In use the prosthesis is delivered percutaneously or by "cut down" methods to an artery in juxtaposition with an arterial bifurcation; blood can flow through the frustoconical proximal portion **52** into each of the branched arteries through the first and second distal frustoconical portions **58, 60**. If a prosthesis is required in one or both of the branched arteries, a separate prosthesis comprising a stent of the type shown in FIG. **1b** referred to above covered with fabric can be connected to the bifurcated prosthesis **50** by inserting and re-expanding the proximal end of such a separate prosthesis in one or both of the distal frustoconical portions **58, 60** of the prosthesis **50** for engagement therein.

Another variant of the present invention is shown in FIG. **6** which shows a bifurcated endoluminal prosthesis **70** having a proximal portion **72** which is secured at its distal end **74** to two transversely spaced frustoconical intermediate portions **76, 78**.

One of said frustoconical intermediate portions **76** is secured at its distal end to an elongate distal portion **80**. The proximal end **82** of the proximal portion **72** is flared radially outwards towards its proximal end **82** to engage the intraluminal surface of the host blood vessel in service. Save for this flared portion, the entire endoprosthesis is covered with a fabric graft layer as shown in FIG. **6**; said graft layer is carried externally of the wire skeleton and is folded over the distal extremity **84** of the other frustoconical intermediate portion **78** to form an internal lining in said other frustoconical intermediate portion **78**.

Said other frustoconical intermediate portion **78** constitutes a female cooperating portion in accordance with the present invention which is adapted to receive a male engaging portion of another prosthesis as indicated at **86** in FIG. **6**. Said other prosthesis **86** includes a frustoconical proximal portion

12

88 which constitutes the male engaging portion and an elongate distal portion **90**. The whole of the other prosthesis **86** is covered with a fabric graft layer as shown in FIG. **6**. In service, the male engaging portion **88** of the other prosthesis **86** is entered into and engaged with the female cooperating portion **78** of the bifurcated prosthesis **70** in situ in the manner herein before described. The fabric layer on the male engaging portion **88** butts face-to-face on the folded over portion of the fabric layer disposed internally of the female cooperating portion **78** to form a substantially blood-tight seal therewith.

Yet another example of the present invention is shown in FIG. **7** in which a bifurcated endoluminal prosthesis **91** has a generally cylindrical proximal portion **92**; said proximal portion **92** is connected at its distal end **93** to an elongate, generally cylindrical distal portion **94**. Said proximal portion **92** is also connected at its distal end **93** to a generally cylindrical intermediate portion **95** which is secured in transversely spaced relation to the elongate distal portion **94**. Said cylindrical intermediate portion **95** constitutes a female engaging portion which is adapted to receive a generally cylindrical male engaging portion of a second elongate prosthesis (not shown). The male engaging portion is equipped with circumferentially spaced external barbs to engage in the female cooperating portion in service. As shown in FIG. **7**, the whole of the bifurcated prosthesis **91** is covered with an external fabric graft layer save for a flared portion **96** towards the proximal end **97** of the proximal portion **92**.

Referring to FIGS. **8(a)-8(f)**, an exemplary embodiment of a delivery system according to the present invention will be described. This system is used to deploy the bifurcated stent **10** when it is covered with a fabric graft layer to create an endoluminal prosthesis. Introducer **100** includes outer sheath **101**. Outer sheath **101** is a cylindrical tube adapted to be inserted either percutaneously or by "cut-down" procedures into the vasculature from an entry point to the bifurcation site where the prosthesis is to be deployed.

Housed within outer sheath **101** is proximal portion pusher **102**. Proximal portion pusher **102** is a cylindrical tube having an outside diameter smaller than the inside diameter of outer sheath **101**. Proximal portion pusher **102** is preferably slidable throughout the length of outer sheath **101**.

Disposed within proximal portion pusher **102** is distal portion pusher **103**. Distal portion pusher **103** is a cylindrical tube slidably contained within distal portion pusher **102**. Distal portion pusher **103** is preferably adapted to slide throughout the entire length of proximal portion pusher **102**.

Disposed within distal portion **103** is balloon catheter **104**. Balloon catheter **104** is adapted to slide within distal portion pusher **103**. At the leading end **105** of balloon catheter **104** is nose cone **106**. Balloon **107** is attached to balloon catheter **104** between nose cone **106** and proximal end **115** of proximal portion pusher **102**.

As shown in FIG. **8(g)**, which is a cross-sectional view of balloon catheter **104** in the direction A-A of FIG. **8(f)**, balloon catheter **104** has a guide wire conduit **104a**. Guide wire conduit **104a** extends throughout the length of balloon catheter **104** for passing a guide wire (not shown) through introducer **100**. In the illustrated embodiment, balloon catheter **104** also includes injection orifice **109** and an injection conduit **109a**. Injection conduit **109a** connects injection orifice **109** to an injection site **108** at or near the distal end of balloon catheter **104** as shown in FIG. **8(e)**. Radiopaque liquid may be injected into injection site **108**, through injection conduit **109a**, out injection orifice **109**, and into the vasculature to monitor deployment of the prosthesis.

Also in the illustrated embodiment of FIGS. **8(f)** and **8(g)**, balloon catheter **104** has an inflation orifice **110** located at a

13

point where balloon **107** is attached to balloon catheter **104**. A balloon inflation conduit **110a** connects balloon inflation orifice **110** to balloon inflation site **111** (FIG. 8(e)). Balloon **107** may be inflated and deflated from balloon inflation site **111** during delivery of the prosthesis.

In an alternative embodiment illustrated in FIG. 9, seals **150**, **151** may be disposed around the distal ends **160**, **161** of outer sheath **10** and proximal portion pusher **102**. Seals **150**, **151** may be formed of silicone tubes.

FIG. 10(a) shows an alternative embodiment of introducer **100**. As shown in FIG. 10(a), wings **112** and **113** are provided at the distal end of introducer **100**. Wing **112** is connected to proximal portion pusher **102**, and wing **113** is connected to outer sheath **101**. Wings **112** and **113** indicate the rotational orientation of proximal portion pusher **102** and outer sheath **101**, respectively. This in turn indicates the orientation of proximal portion **12** within outer sheath **101** and distal portion **16** within proximal portion pusher **102**. Wings **112** and **113** in the illustrated embodiment are also provided with holes **112a** and **113a**.

As shown in FIG. 10(b), a rod **128** or other fixation device may be attached to wings **112** and **113** using e.g. bolts through holes **112a** and **113a** secured by wing nuts **129** or other securing means. Rod **128** prevents relative movement of proximal portion pusher **102** and outer sheath **101**. Wings may also be provided on distal portion pusher **103** and used to secure distal portion pusher **103** to either proximal portion pusher **102** or outer sheath **101** using a fixation device as described above.

Also shown in FIG. 10(a) as part of introducer **100** is hemostasis valve **114**. Hemostasis valve **114** is connected to distal portion pusher **103** and acts as a simple seal around balloon catheter **104**. Although it prevents fluid loss, hemostasis valve **114** allows balloon catheter **104** to slide within distal portion pusher **103**. Alternatively, a Touhy-Borst valve (not shown) may be used instead of hemostasis valve **114**. The Touhy-Borst valve is a device that may be manually tightened over balloon catheter **104**. Lightly tightening such a valve permits balloon catheter **104** to slide; firmly tightening such a valve clamps balloon catheter **104** in place.

In use, the prosthesis must first be loaded into introducer **100**. Outer sheath **101** is first removed from introducer **100**. Balloon catheter **104** is then threaded through distal portion **16** and proximal portion **12** of the prosthesis. The prosthesis is then cooled to a temperature of approximately 10° C. or below and radially compressed. For this purpose, the prosthesis may be immersed in cold water. The prosthesis should preferably remain in the water during the loading operation.

As supporting stent **10** is compressed beneath the fabric covering of the prosthesis, excess fabric is produced. This excess fabric may simply be pinched together and laid over the compressed prosthesis in longitudinal folds.

Distal portion **16** of the prosthesis in the radially compressed state is then inserted into proximal portion pusher **102**. Outer sheath **101** is then pulled over proximal portion **12** of the prosthesis and over proximal portion pusher **102**. A thread (not shown) may be attached to the proximal end of proximal portion **12** of the prosthesis and threaded through outer sheath **101**. This thread may then be used to pull proximal portion **12** through outer sheath **101**. During the loading process, it is important to keep proximal portion **12** and distal portion **16** of the prosthesis properly aligned with outer sheath **101** and proximal portion pusher **102**. Marks may be placed on the outside of outer sheath **101** and proximal portion pusher **102** to ensure proper alignment.

Referring again to FIG. 8(f), the prosthesis is inserted such that the outer surface of proximal portion **12** contacts and is

14

radially restrained by outer sheath **101**, and the outer surface of distal portion **16** contacts and is radially restrained by proximal portion pusher **102**. End **115** of proximal portion pusher **102** longitudinally engages proximal portion **12** of the prosthesis as shown in FIG. 8(f).

Balloon catheter **104** is positioned such that nose cone **106** just clears proximal end **117** of outer sheath **101**. The introducer is now in condition for insertion into the patient.

Referring to FIG. 11, introducer **100** is passed through an entry point (not shown) either in the patient's skin (percutaneous operation) or into the vasculature itself which has been surgically exposed ("cut-down" operation). Introducer **100** is inserted over a guide wire **170** into the vasculature from the entry point to the desired delivery location at an angiological bifurcation.

In the aorta, introducer **100** is positioned such that end **117** of outer sheath **101** is approximately level with renal arteries **180** as shown in FIG. 11. Balloon catheter **104** is then extended while maintaining outer sheath **101** in a fixed position. Balloon catheter **104** in this embodiment is extended until distal end **105** of nose cone **106** is approximately 35 mm above the proximal tip **117** of outer sheath **101**. Then, while maintaining proximal portion pusher **102** in a fixed position, outer sheath **101** is withdrawn until the proximal tip of the prosthesis is level with proximal tip **117** of outer sheath **101**. It will be noted that balloon catheter **104** does not move while outer sheath **101** is so withdrawn.

Introducer **100** is then repositioned to place the prosthesis in the desired deployment location. Proper placement may be facilitated with the use of radiopaque markers as described above. Balloon catheter **104** is then extended such that balloon **107** is above renal arteries **180**. Balloon **107** is then inflated to occlude the aorta as shown in FIG. 12.

While maintaining proximal portion pusher **102** in a fixed position, outer sheath **101** is withdrawn until the proximal end of the prosthesis emerges from outer sheath **101** as shown in FIG. 13. Using a radiopaque marker **120** disposed on proximal end of the prosthesis, the introducer is rotated until proper alignment of the prosthesis is obtained. In the illustrated embodiment, radiopaque marker **120** is a platinum wire twisted around an apex of the prosthesis in a "V" shape. To ensure proper alignment, the stent should be rotated until only the profile of the V is seen and shows up as a straight line rather than a "V".

Outer sheath **101** is further withdrawn while maintaining proximal portion pusher **102** fixed until proximal portion **12** is fully deployed from the end of outer sheath **101**, and the frustoconical portion **1** of the prosthesis just clears end **117**, as shown in FIG. 14.

Balloon **107** is then deflated to allow blood to flow through proximal portion **12** and out frustoconical portion **16** of the prosthesis. Balloon **107** is withdrawn into the prosthesis until the distal end **118** of nose cone **106** is just above the proximal end of the prosthesis.

Balloon **107** is then inflated to seat the prosthesis, which may be provided with barbs (not shown) at its proximal end, against the wall of the aorta, as shown in FIG. 15.

Distal portion pusher **103** is then maintained in a fixed position while outer sheath **101** is withdrawn. Once outer sheath **101** has been withdrawn to the point at which proximal end **117** of outer sheath **101** is flush with proximal end **115** of proximal portion pusher **102**, both outer sheath **101** and proximal portion pusher **102** are withdrawn, still maintaining distal portion pusher **103** in a fixed position. Outer sheath **101** and proximal portion pusher **102** are withdrawn until distal portion **16** of the prosthesis is deployed clear of proximal end **116** of distal portion pusher **103** as shown in

15

FIG. 16. Balloon 107 is slowly deflated to allow blood flow to be established through the proximal portion 12 of the prosthesis and out through frustoconical portion 18. Balloon 107 may be used to model distal portion 16 of the prosthesis as necessary by inflating balloon 107 where needed to expand distal portion 16. Balloon 107 is then deflated, and introducer 100 is withdrawn from the vasculature, leaving the guide wire 170 in place, as shown in FIG. 17.

FIG. 21(a) illustrates an exemplary second S introducer 300 used for deploying second distal part 44. Second introducer 300 of the illustrated embodiment comprises cylindrical outer sheath 301 and female Luer lock assembly 310. Second introducer 300 also has hemostasis valve 361 contained within a hub 362 thereof. Cartridge 311 shown in FIG. 21(b) is adapted to be attached to second introducer 300. Cartridge 311 has threaded male Luer lock assembly 312 provided on its proximal end. Cartridge 311 has outer tube 313 which houses inner tube 314.

In use, a thin-walled tube (not shown) is first threaded through distal portion 44. This tube serves as a guide wire guide, allowing a guide wire to be threaded straight through distal portion 44 as discussed below. Distal portion 44 containing the thin-walled tube is then cooled, radially compressed, and inserted into inner tube 314 of cartridge 311 in a manner similar to that described for inserting the bifurcated prosthesis into proximal portion pusher 102 and outer sheath 101. When distal portion 44 has been loaded into inner tube 314 of cartridge 311, the thin-walled tube serving as a guide wire guide extends out both ends of cartridge 311.

A guide wire 171 is then inserted into the vasculature to the bifurcation site and through distal stent portion 12 as shown in FIG. 18. A dilator 359 (FIG. 21(c)) having an outer diameter slightly less than the inner diameter of second introducer 300 is then inserted into second introducer 300 such that tapered end 360 extends out end 320 of second introducer 300. End 360 of dilator 359 has a hole therein that is just slightly larger than guide wire 171 and tapers gradually outward from the hole to the outer diameter of dilator 359.

Second introducer 300 is then inserted into the vasculature over guide wire 171 by passing guide wire 171 into and through dilator 359. Dilator 359 with tapered end 360 provides a smooth transition within the blood vessel from the diameter of guide wire 171 to the diameter of second introducer 300. Second introducer 300 is maneuvered such that outer sheath 301 is inside frustoconical portion 18 of proximal portion 12 by at least 20 mm in this embodiment, as shown in FIG. 19. Dilator 359 is then removed from second introducer 300 and from the vasculature and is discarded.

Cartridge 311 is then passed over guide wire 171 by passing guide wire 171 through the thin-walled guide wire guide within distal portion 44 contained in cartridge 311. The guide wire guide is then removed and discarded.

Cartridge 311 is then lockingly engaged with introducer 300 by mating male Luer lock assembly 310 with female Luer lock assembly 312. Such locking engagement prevents relative movement of cartridge 311 and introducer 300. Preventing relative movement lends stability and reliability to the insertion process that has not heretofore been achieved.

A pusher 315 is then inserted into inner tube 314 of cartridge 311 such that proximal end 317 of pusher 315 longitudinally contacts a distal end of distal portion 44 within inner tube 314. Pusher 315 pushes distal portion 44 through cartridge 311 and into outer sheath 301 of introducer 300. Distal portion 44 is pushed through outer sheath 301, which remains in a fixed position, until distal portion 44 is at proximal end

16

320 of outer sheath 301 (see FIG. 19). Again, radiopaque markers 120 may be used to align distal portion 44 properly with proximal portion 12.

Pusher 302 is held firmly in place, and outer sheath 301 is withdrawn approximately 2 cm. This deploys frustoconical part 42 of distal part 44 inside the frustoconical part 18 as shown in FIG. 19. The outer surface of frustoconical part 42 engages the inner surface of frustoconical part 18 such that distal portion 44 is connected to proximal portion 12 to resist longitudinal separation.

Cutter sheath 301 may then be withdrawn while maintaining pusher 302 in a fixed position to fully deploy distal portion 44, as shown in FIG. 20. If necessary, balloon catheter 104 may be inserted through sheath 301 in order to model distal portion 44. Introducer 301 and guide wires 170, 171 are then removed from the vasculature and the entry points are closed.

The delivery apparatus and method described above are particularly useful in treating an abdominal aortic aneurysm with a bifurcated prosthesis according to the present invention. Other diseases and alternative embodiments of the prosthesis and delivery method will now be described.

In the case of an abdominal aortic aneurysm confined to the aorta and not extending far enough to affect the iliac arteries, a straight (i.e. nonbifurcated) stent may be used. Preferably, for such applications, the straight stent comprises a composite of at least two axially aligned stent segments. Two embodiments of such straight stents are described herein, each comprising axially aligned stent segments, each of the segments comprising one or more adjacent hoops, perpendicular to a common axis, and each hoop being formed of wire in a sinuous or zigzag configuration with some or all of the juxtaposed apices in adjacent hoops secured to one another.

First, referring to FIG. 22, straight stent 400 comprises proximal stent portion (or segment) 401, distal stent portion 402, and an intermediate portion 403.

Proximal portion 401 is a ring formed of a number of longitudinally spaced hoops 20 as described in connection with the formation of stent 10 above. In the illustrated embodiment, two hoops 20 are used, each hoop 20 having a unit width.

Distal portion 402 is also a ring formed of longitudinally displaced hoops 20 in the manner described above. Distal ring 402 has two hoops 20 of unit width in the illustrated embodiment.

Intermediate portion 403 of straight stent 400 is formed of biocompatible woven fabric such as, for example, a plain woven fabric made from 30 or 40 denier polyester. In this embodiment, intermediate fabric section 403 does not cover a stent. Fabric portion 403 is attached at its proximal and distal ends to the proximal and distal stent portions, respectively, by stitching, for example, with 0.003 inch polypropylene filaments around apices 22 of the stent portions. Other than such connections at its longitudinal ends, intermediate fabric section 403 is unsupported by any stent.

The second embodiment of a straight stent that may be used according to this invention is illustrated in FIG. 23. Straight stent 450 includes stent portion 451, constructed of wire loops as described above with reference to stent portions 401 and 402. Stent portion 451 is partially covered by fabric 452. In this embodiment, fabric portion 451 covers and is supported by stent 451, whereas with stent 400, the fabric portion 403 is not supported by a stent.

To treat an abdominal aortic aneurysm that does not extend down over the walls of the iliac arteries, as shown in FIG. 24(a), straight stent 400 (or 450) is disposed as illustrated in FIG. 26. Proximal stent portion 401 engages the inner walls of the aorta above the aneurysm. Distal stent portion 402

17

engages the inner wall of the aorta below the aneurysm. Intermediate fabric portion **403** extends across the aneurysm, providing a strong, stable lumen for blood flow through the aorta.

FIG. **28** illustrates the delivery apparatus used to implant straight stent **400** in the vasculature. This apparatus is very similar to that described above for the delivery system to be used with the bifurcated stent or prosthesis. Accordingly, like reference numerals refer to the same components.

In the introducer **410** shown in FIG. **28**, proximal portion pusher **102** engages proximal stent portion **401**. Distal portion pusher **103** engages distal stent portion **402**.

In use, straight stent **400** is first charged into the introducer by cooling it to temperatures below 10° C., radially compressing it, and inserting it within outer sheath **101**, as described above in connection with the bifurcated stent or prosthesis. The remainder of introducer **410** is also assembled as described in connection with introducer **100**.

Introducer **410** is passed through an entry point (not shown) over guide wire **411** as shown in FIG. **24(a)**. This insertion may be accomplished using percutaneous or cut-down techniques. Introducer **410** is then inserted to the desired delivery location.

In the aorta, introducer **410** is positioned and balloon **107** is inflated above the renal arteries in the same manner as described above in connection with the bifurcated stent and as illustrated in FIG. **24(a)**.

While maintaining proximal portion pusher **102** in a fixed position, outer sheath **101** is withdrawn until proximal portion **401** of stent **400** emerges from outer sheath **101** as shown in FIG. **24(b)**. Using a radiopaque marker **420** disposed on the proximal end of the proximal portion **401**, stent **400** is optimally aligned within the aorta. Outer sheath **101** is further withdrawn until proximal portion **401** emerges therefrom, as shown in FIG. **25**. Outer sheath **101** is then further withdrawn until it is flush with proximal portion pusher **102**. Then both outer sheath **101** and proximal portion pusher **102** are withdrawn while maintaining distal portion pusher **103** in a fixed position. Distal portion **402** is thus deployed from the end of outer sheath **101**, as shown in FIG. **26**.

Balloon **107** is then deflated and withdrawn inside proximal portion **401** where balloon **107** is reinflated to seat the stent **400**, as shown in FIG. **27**. Balloon **107** is then withdrawn, along with the introducer **410** as described above, and the entry point is closed.

FIG. **29** illustrates the apparatus used to deploy straight stent **450**, shown in FIG. **23**, of the present invention. This apparatus is very similar to that described above for the delivery system to be used with the bifurcated stent or prosthesis. Accordingly, like reference numerals refer to the same components.

Proximal portion pusher **102** in this embodiment is glued to distal portion pusher **103** such that ends **115** and **116** are flush. These flush ends are adapted to engage stent **450** within outer sheath **101**.

In use, straight stent **450** is first charged into introducer **490** by cooling it to temperatures below 10° C., radially compressing it, and inserting it within outer sheath **101**, as described above in connection with the bifurcated stent or prosthesis. The remainder of introducer **490** is also assembled as described in connection with introducer **100**.

Introducer **490** is passed through an entry point (not shown) over a guide wire **411** as shown in FIG. **30**. This insertion may be accomplished using percutaneous or cut-down techniques. Introducer **490** is then inserted to the desired delivery location.

18

In the aorta, introducer **490** is positioned and balloon **107** is inflated above the renal arteries in the same manner as described above in connection with the bifurcated stent and as illustrated in FIG. **31**.

While maintaining attached proximal portion pusher **102** and distal portion pusher **103** in a fixed position, outer sheath **101** is withdrawn until proximal portion **451** of stent **450** emerges from outer sheath **101** as shown in FIG. **32**. Using a radiopaque marker **420** disposed on the proximal end of the proximal portion **451**, stent **450** is optimally aligned within the aorta. Outer sheath **101** is then completely withdrawn until stent **450** is deployed into the aorta as shown in FIG. **33**.

Balloon **107** is then deflated and withdrawn inside proximal portion **451** where balloon **107** is reinflated to seat the stent **450**, as shown in FIG. **34**. Balloon **107** is then withdrawn, along with the introducer **490** as described above, and the entry point is closed.

The angiological disease of occlusion is the blockage of an artery resulting from a buildup or clot of soft thrombus. There are two types of occlusions that can occur at the aorta-iliac bifurcation. The first is infrarenal occlusion. In this case, the blockage extends in the aorta from just below the renal arteries into the iliac arteries. The second type is an occlusion that is limited to the immediate area of the bifurcation.

To treat an infrarenal occlusion, a canalization is first made through the thrombus by methods known in the art. A bifurcated endoluminal prosthesis according to the present invention is then implanted at the bifurcation site to provide an unobstructed lumen extending from the aorta into each of the iliac arteries. Blood can thus flow freely from the aorta to the iliac arteries.

The bifurcated endoluminal prosthesis according to the present invention that is used to treat an occlusion must be fabric covered. This is necessary to prevent embolization from the thrombus remaining on the wall of the recanalized artery.

An occlusion at the bifurcation is treated by recanalizing the artery as above. A bifurcated endoluminal prosthesis according to the present invention may be implanted at the bifurcation. Because the occlusion is limited to the immediate bifurcation site, however, the proximal portion of the prosthesis may be shorter than that discussed above.

To implant the bifurcated endoluminal prosthesis to treat both types of occlusion, the delivery system comprising introducer **100** discussed above for delivering the bifurcated endoluminal prosthesis to treat an abdominal aortic aneurysm is used. The same delivery method discussed above for implanting the bifurcated endoluminal prosthesis to treat abdominal aortic aneurysms is used to implant the device to treat the occlusion.

Using the method and apparatus of this invention to treat occlusion provides an unobstructed lumen through which blood can flow from the aorta to the iliac arteries.

The angiological disease of stenosis is a narrowing of an artery caused by a buildup of hard calcified plaque. This is usually caused by a buildup of cholesterol. To treat such an angiological disease, angioplasty is performed on the plaque according to methods well known in the art. The bifurcated endoluminal stent according to the present invention is then implanted at the bifurcation site. This stent is the same as that described above for treatment of an abdominal aortic aneurysm. To treat the stenosis, however, it is not necessary to cover the stent with a fabric, thus creating a Prosthesis. Because restenosis is rare at the bifurcation site, there is no need to isolate the blood flowing in the lumen from the walls of the arteries.

19

The delivery system used to implant the bifurcated endoluminal stent used to treat stenosis is the same as that illustrated in FIG. 8 except that balloon 107 is not required. Because there is no fabric around the stent to be affected by blood flow in the arteries and cause migration of the bifurcated stent, it is not necessary to block the blood flow with the balloon. Otherwise, the delivery system for implanting the bifurcated stent to treat stenosis is the same as that for implanting the bifurcated prosthesis to treat abdominal aortic aneurysm.

Similarly, with the exception of the steps involving inflation of balloon 107 to block blood flow, the method of delivering the bifurcated endoluminal stent to treat stenosis is the same as that described above for delivering the bifurcated endoluminal prosthesis to treat abdominal aortic aneurysm.

What is claimed:

1. A stent comprising:
a plurality of hoops aligned along a common axis, each of said hoops being non-helical and oriented in a plane substantially perpendicular to the longitudinal axis of the stent, and each of said hoops including a plurality of elongate elements joined to one another and forming apices that point in a direction along the longitudinal axis of the stent, and wherein at least one elongate element in each hoop is a continuation of an elongate element of an adjacent hoop; and
means for securing an apex of one hoop to an abutting a juxtaposed apex of a neighboring hoop.
2. A stent as recited in claim 1 comprising at least one stent segment in combination with one or more additional stent segments.
3. A stent as recited in claim 2 wherein said one or more additional segments are axially aligned with one another.
4. A stent as recited in claim 3 wherein said axially aligned segments are connected to one another by a tubular fabric element.
5. A stent as recited in claim 2 wherein said one or more additional segments are secured to one another by connecting means connecting at least some of the apices of hoops at mating ends of said stent and said additional segments.
6. A stent as recited in claim 2 wherein adjacent hoops are of the same diameter.
7. A stent as recited in claim 2 wherein adjacent hoops are of a different diameter.
8. A stent as recited in claim 2 wherein a first additional segment is axially parallel to, but non-common co-axial with, said stent segment.
9. A stent as recited in claim 8 further comprising a second additional segment axially parallel to said stent segment, but non-co-axial with either said stent segment or said first additional stent segment.
10. A stent as recited in claim 9 wherein at least one of said first and second additional stent segments is of frustoconical shape and is further combined with a third an additional stent segment, one end of which includes a mating frustoconical shape.
11. A stent as recited in claim 10, wherein said mating frustoconical stent segments are adapted to be separately placed in a bifurcated artery and then, by expansion of one of said frustoconical stent segments, secured to one another.
12. A stent as recited in claim 2 wherein at least one of said additional stent segments comprises:
a plurality of hoops aligned along a common axis, each of said hoops oriented in a plane substantially perpendicular to the longitudinal axis of the additional stent segment, and each of said hoops including a plurality of elongate elements joined to one another and forming

20

apices that point in a direction along the longitudinal axis of the additional stent segment; and
means for securing an apex of one hoop to a juxtaposed apex of a neighboring hoop.

13. An endoluminal stent as claimed in claim 1 wherein said hoops are formed of a single continuous wire.

14. An endoluminal stent as claimed in claim 13 wherein said wire is nitinol.

15. An endoluminal stent as claimed in claim 1 wherein said securing means is a suture.

16. An endoluminal stent as claimed in claim 15 wherein said suture is a tied loop of thermoplastic material.

17. An endoluminal stent as claimed in claim 1 wherein said securing means is a staple.

18. An endoluminal stent as claimed in claim 1 wherein said securing means is wire twisted into loop.

19. An endoluminal stent as claimed in claim 18 wherein said wire is nitinol.

20. An endoluminal stent as claimed in claim 1 wherein said securing means is bead of thermoplastic material.

21. An endoluminal stent as claimed in claim 1 wherein each longitudinal end of the stent is substantially perpendicular square to the longitudinal axis of the stent.

22. An endoluminal stent as claimed in claim 1 wherein said stent is at least partially covered in fabric.

23. An endoluminal stent as claimed in claim 1 further comprising a radiopaque marker disposed on at least one end of the stent.

24. An endoluminal stent as claimed in claim 23 wherein said radiopaque marker comprises a radiopaque element attached to one end of said stent.

25. An endoluminal stent as claimed in claim 24 wherein said element is a platinum wire.

26. An endoluminal stent as claimed in claim 24 wherein said element is a gold wire.

27. An endoluminal stent as claimed in claim 23 wherein said radiopaque marker comprises a radiopaque tube disposed around a part of said stent.

28. An endoluminal stent as claimed in claim 27 wherein said tube is platinum.

29. An endoluminal stent as claimed in claim 27 wherein said tube is gold.

30. A stent comprising a tubular member having a plurality of hoops aligned adjacent one another along the longitudinal axis of said tubular member, each of said hoops comprising a plurality of elongate elements, with pairs of said elongate elements meeting one another and forming vertices axially pointing in a direction along the longitudinal axis of the stent, wherein at least some of said vertices axially abut and are individually connected to oppositely pointed vertices of elongate elements of an adjacent hoop, wherein the vertices of each hoop pointed in the axial direction lie in a common plane perpendicular to the longitudinal axis of the tubular member, and wherein at least one elongate element in each hoop is a continuation of an elongate element of an adjacent hoop.

31. A prosthesis for placement in a body lumen comprising a tubular graft supported and adapted to be retained in said lumen by a stent as recited in claim 30.

32. A method of reinforcing a body vessel using a tubular sheath disposed between an entry location in a body and an implantation location, said method comprising the steps of:

- a. providing a stent as recited in claim 30;
- b. compressing the stent into its compressed configuration;
- c. inserting the compressed stent into the tubular sheath;
- d. delivering the compressed stent through the tubular sheath to the implantation location; and

21

e. withdrawing the sheath while holding the stent at the implantation location within the vessel and expanding the stent within the implantation location as the sheath is withdrawn by permitting the self-expandable stent, as the constraint of the sheath is removed to return to said expanded configuration;

whereby the stent is securely disposed in the implanted state against said body vessel.

33. A method according to claim **32**, wherein said stent is comprised of a shape memory material.

22

34. A method according to claim **33**, wherein said shape memory material is nitinol and step (b) is performed at low temperature.

35. A method according to claim **32**, wherein at least one elongate element in each hoop is a continuation of an elongate element of an adjacent hoop.

* * * * *