US008616431B2

(12) **United States Patent**
Timm et al.

(10) **Patent No.: US 8,616,431 B2**
(45) **Date of Patent: Dec. 31, 2013**

(54) **SHIFTABLE DRIVE INTERFACE FOR ROBOTICALLY-CONTROLLED SURGICAL TOOL**

(75) Inventors: **Richard W. Timm**, Cincinnati, OH (US); **Frederick E. Shelton, IV**, Hillsboro, OH (US)

(73) Assignee: **Ethicon Endo-Surgery, Inc.**, Cincinnati, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/369,578**

(22) Filed: **Feb. 9, 2012**

(65) **Prior Publication Data**

US 2012/0132450 A1 May 31, 2012

Related U.S. Application Data

(63) Continuation of application No. 13/118,223, filed on May 27, 2011, which is a continuation-in-part of application No. 13/020,053, filed on Feb. 3, 2011, now Pat. No. 8,196,796, which is a continuation of application No. 11/810,015, filed on Jun. 4, 2007, now Pat. No. 7,905,380.

(51) **Int. Cl.**
A61B 19/00 (2006.01)
B25J 19/00 (2006.01)

(52) **U.S. Cl.**
USPC **227/178.1**; 227/175.1; 227/180.1; 606/130; 606/167; 606/219

(58) **Field of Classification Search**
USPC 227/175.1, 178.1, 180.1; 606/130, 167, 606/219; 74/490.01
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

66,052	A	6/1867	Smith
662,587	A	11/1900	Blake
951,393	A	3/1910	Hahn
2,037,727	A	4/1936	La Chapelle
2,132,295	A	10/1938	Hawkins
2,161,632	A	6/1939	Nattenheimer
2,211,117	A	8/1940	Hess
2,214,870	A	9/1940	West

(Continued)

FOREIGN PATENT DOCUMENTS

CA	2458946	A1	3/2003
CA	2512960	A1	1/2006

(Continued)

OTHER PUBLICATIONS

Disclosed Anonymously, "Motor-Driven Surgical Stapler Improvements," Research Disclosure Database No. 526041, Published: Feb. 2008.

(Continued)

Primary Examiner — Michelle Lopez

(57) **ABSTRACT**

A surgical instrument including an end effector that has a selectively reciprocatable implement movably supported therein. The implement is selectively advanceable in a distal direction upon application of a rotary actuation motion thereto and retractable in a proximal direction upon application of a rotary retraction motion thereto. An elongate shaft assembly is coupled to the end effector and is configured to transmit the rotary actuation motion and rotary retraction motion to the reciprocatable implement from a robotic system that is configured to generate the rotary actuation motion and said rotary retraction motion.

26 Claims, 120 Drawing Sheets



IS 1001

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,441,096 A 5/1948 Happe
2,526,902 A 10/1950 Rublee
2,674,149 A 4/1954 Benson
2,804,848 A 9/1957 O'Farrell et al.
2,808,482 A 10/1957 Zanichkowsky et al.
2,853,074 A 9/1958 Olson
3,032,769 A 5/1962 Palmer
3,075,062 A 1/1963 Iaccarino
3,078,465 A 2/1963 Bobrov
3,166,072 A 1/1965 Sullivan, Jr.
3,266,494 A 8/1966 Brownrigg et at
3,269,630 A 8/1966 Fleischer
3,357,296 A 12/1967 Lefever
3,490,675 A 1/1970 Green et al.
3,551,987 A 1/1971 Wilkinson
3,598,943 A 8/1971 Barrett
3,643,851 A 2/1972 Green et al.
3,662,939 A 5/1972 Bryan
3,717,294 A 2/1973 Green
3,734,207 A 5/1973 Fishbein
3,740,994 A 6/1973 DeCarlo, Jr.
3,744,495 A 7/1973 Johnson
3,746,002 A 7/1973 Haller
3,751,902 A 8/1973 Kingsbury et al.
3,819,100 A 6/1974 Noiles et al.
3,821,919 A 7/1974 Knohl
3,851,196 A 11/1974 Hinds
3,885,491 A 5/1975 Curtis
3,892,228 A 7/1975 Mitsui
3,894,174 A 7/1975 Cartun
3,940,844 A 3/1976 Colby et al.
RE28,932 E 8/1976 Noiles et al.
4,060,089 A 11/1977 Noiles
4,129,059 A 12/1978 Van Eck
4,169,990 A 10/1979 Lerdman
4,198,982 A 4/1980 Fortner et al.
4,207,898 A 6/1980 Becht
4,213,562 A 7/1980 Garrett et al.
4,250,436 A 2/1981 Weissman
4,261,244 A 4/1981 Becht et al.
4,272,662 A 6/1981 Simpson
4,275,813 A 6/1981 Noiles
4,289,133 A 9/1981 Rothfuss
4,305,539 A 12/1981 Korolkov et al.
4,317,451 A 3/1982 Cerwin et al.
4,321,002 A 3/1982 Froehlich
4,331,277 A 5/1982 Green
4,340,331 A 7/1982 Savino
4,347,450 A 8/1982 Colligan
4,349,028 A 9/1982 Green
4,353,371 A 10/1982 Cosman
4,379,457 A 4/1983 Gravener et al.
4,380,312 A 4/1983 Landrus
4,383,634 A 5/1983 Green
4,393,728 A 7/1983 Larson et al.
4,396,139 A 8/1983 Hall et al.
4,402,445 A 9/1983 Green
4,408,692 A 10/1983 Siegel et al.
4,415,112 A 11/1983 Green
4,428,376 A 1/1984 Mericle
4,429,695 A 2/1984 Green
4,434,796 A 3/1984 Karapetian et al.
4,442,964 A 4/1984 Becht
4,451,743 A 5/1984 Suzuki et al.
4,454,887 A 6/1984 Krüger
4,467,805 A 8/1984 Fukuda
4,473,077 A 9/1984 Noiles et al.
4,475,679 A 10/1984 Fleury, Jr.
4,485,816 A 12/1984 Krumme
4,489,875 A 12/1984 Crawford et al.
4,500,024 A 2/1985 DiGiovanni et al.
4,505,273 A 3/1985 Braun et al.
4,505,414 A 3/1985 Filipi
4,506,671 A 3/1985 Green
4,520,817 A 6/1985 Green
4,522,327 A 6/1985 Korthoff et al.
4,526,174 A 7/1985 Froehlich
4,527,724 A 7/1985 Chow et al.
4,530,453 A 7/1985 Green
4,531,522 A 7/1985 Bedi et al.
4,532,927 A 8/1985 Miksza, Jr.
4,548,202 A 10/1985 Duncan
4,565,189 A 1/1986 Mabuchi
4,566,620 A 1/1986 Green et al.
4,571,213 A 2/1986 Ishimoto
4,573,468 A 3/1986 Conta et al.
4,573,469 A 3/1986 Golden et al.
4,573,622 A 3/1986 Green et al.
4,576,167 A 3/1986 Noiles et al.
4,580,712 A 4/1986 Green
4,589,416 A 5/1986 Green
4,591,085 A 5/1986 Di Giovanni
4,604,786 A 8/1986 Howie, Jr.
4,605,001 A 8/1986 Rothfuss et al.
4,605,004 A 8/1986 Di Giovanni et al.
4,606,343 A 8/1986 Conta et al.
4,607,638 A 8/1986 Crainich
4,608,981 A 9/1986 Rothfuss et al.
4,610,250 A 9/1986 Green
4,610,383 A 9/1986 Rothfuss et al.
4,619,262 A 10/1986 Taylor
4,629,107 A 12/1986 Fedotov et al.
4,632,290 A 12/1986 Green et al.
4,633,874 A 1/1987 Chow et al.
4,641,076 A 2/1987 Linden
4,646,722 A 3/1987 Silverstein et al.
4,655,222 A 4/1987 Florez et al.
4,663,874 A 5/1987 Sano et al.
4,664,305 A 5/1987 Blake, III et al.
4,665,916 A 5/1987 Green
4,667,674 A 5/1987 Korthoff et al.
4,671,445 A 6/1987 Barker et al.
4,676,245 A 6/1987 Fukuda
4,693,248 A 9/1987 Failla
4,709,120 A 11/1987 Pearson
4,715,520 A 12/1987 Roehr, Jr. et al.
4,719,917 A 1/1988 Barrows et al.
4,728,020 A 3/1988 Green et al.
4,728,876 A 3/1988 Mongeon et al.
4,729,260 A 3/1988 Dudden
4,730,726 A 3/1988 Holzwarth
4,741,336 A 5/1988 Failla et al.
4,743,214 A 5/1988 Tai-Cheng
4,752,024 A 6/1988 Green et al.
4,754,909 A 7/1988 Barker et al.
4,767,044 A 8/1988 Green
4,773,420 A 9/1988 Green
4,777,780 A 10/1988 Holzwarth
4,787,387 A 11/1988 Burbank, III et al.
4,790,225 A 12/1988 Moody et al.
4,805,617 A 2/1989 Bedi et al.
4,805,823 A 2/1989 Rothfuss
4,809,695 A 3/1989 Gwathmey et al.
4,817,847 A 4/1989 Redtenbacher et al.
4,819,853 A 4/1989 Green
4,821,939 A 4/1989 Green
4,827,911 A 5/1989 Broadwin et al.
4,844,068 A 7/1989 Arata et al.
4,869,414 A 9/1989 Green et al.
4,869,415 A 9/1989 Fox
4,880,015 A 11/1989 Nierman
4,890,613 A 1/1990 Golden et al.
4,892,244 A 1/1990 Fox et al.
4,915,100 A 4/1990 Green
4,930,503 A 6/1990 Pruitt
4,930,674 A 6/1990 Barak
4,932,960 A 6/1990 Green et al.
4,938,408 A 7/1990 Bedi et al.
4,941,623 A 7/1990 Pruitt
4,944,443 A 7/1990 Oddsen et al.
4,955,959 A 9/1990 Tompkins et al.
4,978,049 A 12/1990 Green
4,986,808 A 1/1991 Broadwin et al.
4,988,334 A 1/1991 Hornlein et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,002,553	A	3/1991	Shiber
5,009,661	A	4/1991	Michelson
5,014,899	A	5/1991	Presty et al.
5,015,227	A	5/1991	Broadwin et al.
5,027,834	A	7/1991	Pruitt
5,031,814	A	7/1991	Tompkins et al.
5,040,715	A	8/1991	Green et al.
5,042,707	A	8/1991	Taheri
5,061,269	A	10/1991	Muller
5,062,563	A	11/1991	Green et al.
5,065,929	A	11/1991	Schulze et al.
5,071,052	A	12/1991	Rodak et al.
5,071,430	A	12/1991	de Salis et al.
5,074,454	A	12/1991	Peters
5,080,556	A	1/1992	Carreno
5,083,695	A	1/1992	Foslien et al.
5,084,057	A	1/1992	Green et al.
5,088,979	A	2/1992	Filipi et al.
5,088,997	A	2/1992	Delahuerga et al.
5,094,247	A	3/1992	Hernandez et al.
5,100,420	A	3/1992	Green et al.
5,104,025	A	4/1992	Main et al.
5,106,008	A	4/1992	Tompkins et al.
5,111,987	A	5/1992	Moeinzadeh et al.
5,116,349	A	5/1992	Aranyi
5,122,156	A	6/1992	Granger et al.
5,129,570	A	7/1992	Schulze et al.
5,137,198	A	8/1992	Nobis et al.
5,139,513	A	8/1992	Segato
5,141,144	A	8/1992	Foslien et al.
5,142,932	A	9/1992	Moya et al.
5,156,315	A	10/1992	Green et al.
5,156,614	A	10/1992	Green et al.
5,158,567	A	10/1992	Green
D330,699	S	11/1992	Gill
5,163,598	A	11/1992	Peters et al.
5,171,247	A	12/1992	Hughett et al.
5,171,249	A	12/1992	Stefanchik et al.
5,188,111	A	2/1993	Yates et al.
5,190,517	A	3/1993	Zieve et al.
5,195,968	A	3/1993	Lundquist et al.
5,197,648	A	3/1993	Gingold
5,200,280	A	4/1993	Karasa
5,205,459	A	4/1993	Brinkerhoff et al.
5,207,697	A	5/1993	Carusillo et al.
5,209,747	A	5/1993	Knoepfler
5,211,649	A	5/1993	Kohler et al.
5,217,457	A	6/1993	Delahuerga et al.
5,217,478	A	6/1993	Rexroth
5,219,111	A	6/1993	Bilotti et al.
5,221,036	A	6/1993	Takase
5,221,281	A	6/1993	Klicek
5,222,963	A	6/1993	Brinkerhoff et al.
5,222,975	A	6/1993	Crainich
5,222,976	A	6/1993	Yoon
5,223,675	A	6/1993	Taft
5,234,447	A	8/1993	Kaster et al.
5,236,440	A	8/1993	Hlavacek
5,239,981	A	8/1993	Anapliotis
5,240,163	A	8/1993	Stein et al.
5,242,457	A	9/1993	Akopov et al.
5,244,462	A	9/1993	Delahuerga et al.
5,246,156	A	9/1993	Rothfuss et al.
5,246,443	A	9/1993	Mai
5,253,793	A	10/1993	Green et al.
5,258,009	A	11/1993	Conners
5,258,012	A	11/1993	Luscombe et al.
5,259,366	A	11/1993	Reydel et al.
5,260,637	A	11/1993	Pizzi
5,263,629	A	11/1993	Trumbull et al.
5,263,973	A	11/1993	Cook
5,268,622	A	12/1993	Philipp
5,271,543	A	12/1993	Grant et al.
5,271,544	A	12/1993	Fox et al.
RE34,519	E	1/1994	Fox et al.
5,275,323	A	1/1994	Schulze et al.
5,275,608	A	1/1994	Forman et al.
5,281,216	A	1/1994	Klicek
5,282,806	A	2/1994	Haber et al.
5,282,829	A	2/1994	Hermes
5,297,714	A	3/1994	Kramer
5,304,204	A	4/1994	Bregen
5,307,976	A	5/1994	Olson et al.
5,309,927	A	5/1994	Welch
5,312,023	A	5/1994	Green et al.
5,312,329	A	5/1994	Beaty et al.
5,314,424	A	5/1994	Nicholas
5,318,221	A	6/1994	Green et al.
5,330,502	A	7/1994	Hassler et al.
5,332,142	A	7/1994	Robinson et al.
5,333,422	A	8/1994	Warren et al.
5,333,772	A	8/1994	Rothfuss et al.
5,334,183	A	8/1994	Wuchinich
5,336,232	A	8/1994	Green et al.
5,339,799	A	8/1994	Kami et al.
5,341,724	A	8/1994	Vatel
5,341,810	A	8/1994	Dardel
5,342,395	A	8/1994	Jarrett et al.
5,342,396	A	8/1994	Cook
5,344,060	A	9/1994	Gravener et al.
5,350,391	A	9/1994	Iacovelli
5,350,400	A	9/1994	Esposito et al.
5,352,229	A	10/1994	Goble et al.
5,352,235	A	10/1994	Koros et al.
5,352,238	A	10/1994	Green et al.
5,354,303	A	10/1994	Spaeth et al.
5,356,006	A	10/1994	Alpern et al.
5,358,510	A	10/1994	Luscombe et al.
5,359,231	A	10/1994	Flowers et al.
D352,780	S	11/1994	Glaeser et al.
5,360,428	A	11/1994	Hutchinson, Jr.
5,364,003	A	11/1994	Williamson, IV
5,366,134	A	11/1994	Green et al.
5,366,479	A	11/1994	McGarry et al.
5,368,015	A	11/1994	Wilk
5,370,645	A	12/1994	Klicek et al.
5,372,596	A	12/1994	Klicek et al.
5,372,602	A	12/1994	Burke
5,374,277	A	12/1994	Hassler
5,376,095	A	12/1994	Ortiz
5,379,933	A	1/1995	Green et al.
5,381,782	A	1/1995	DeLaRama et al.
5,382,247	A	1/1995	Cimino et al.
5,383,880	A	1/1995	Hooven
5,383,881	A	1/1995	Green et al.
5,383,888	A	1/1995	Zvenyatsky et al.
5,383,895	A	1/1995	Holmes et al.
5,389,098	A	2/1995	Tsuruta et al.
5,391,180	A	2/1995	Tovey et al.
5,392,979	A	2/1995	Green et al.
5,395,030	A	3/1995	Kuramoto et al.
5,395,033	A	3/1995	Byrne et al.
5,395,312	A	3/1995	Desai
5,397,046	A	3/1995	Savage et al.
5,397,324	A	3/1995	Carroll et al.
5,403,312	A	4/1995	Yates et al.
5,405,072	A	4/1995	Zlock et al.
5,405,073	A	4/1995	Porter
5,405,344	A	4/1995	Williamson et al.
5,407,293	A	4/1995	Crainich
5,409,498	A	4/1995	Braddock et al.
5,411,508	A	5/1995	Bessler et al.
5,413,267	A	5/1995	Solyntjes et al.
5,413,268	A	5/1995	Green et al.
5,413,272	A	5/1995	Green et al.
5,415,334	A	5/1995	Williamson, IV et al.
5,415,335	A	5/1995	Knodell, Jr.
5,417,361	A	5/1995	Williamson, IV
5,421,829	A	6/1995	Olichney et al.
5,422,567	A	6/1995	Matsunaga
5,423,809	A	6/1995	Klicek
5,425,745	A	6/1995	Green et al.
5,431,322	A	7/1995	Green et al.
5,431,668	A	7/1995	Burbank, III et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,433,721 A 7/1995 Hooven et al.
5,438,302 A 8/1995 Goble
5,439,479 A 8/1995 Shichman et al.
5,441,193 A 8/1995 Gravener
5,441,494 A 8/1995 Ortiz
5,445,304 A 8/1995 Plyley et al.
5,445,644 A 8/1995 Pietrafitta et al.
5,447,417 A 9/1995 Kuhl et al.
5,447,513 A 9/1995 Davison et al.
5,449,355 A 9/1995 Rhum et al.
5,449,365 A 9/1995 Green et al.
5,452,836 A 9/1995 Huitema et al.
5,452,837 A 9/1995 Williamson, IV et al.
5,454,827 A 10/1995 Aust et al.
5,456,401 A 10/1995 Green et al.
5,458,579 A 10/1995 Chodorow et al.
5,462,215 A 10/1995 Viola et al.
5,464,300 A 11/1995 Crainich
5,465,894 A 11/1995 Clark et al.
5,465,895 A 11/1995 Knodel et al.
5,465,896 A 11/1995 Allen et al.
5,466,020 A 11/1995 Page et al.
5,467,911 A 11/1995 Tsuruta et al.
5,470,006 A 11/1995 Rodak
5,470,007 A 11/1995 Plyley et al.
5,470,009 A 11/1995 Rodak
5,472,132 A 12/1995 Savage et al.
5,472,442 A 12/1995 Klicek
5,473,204 A 12/1995 Temple
5,474,057 A 12/1995 Makower et al.
5,474,566 A 12/1995 Alesi et al.
5,476,206 A 12/1995 Green et al.
5,476,479 A 12/1995 Green et al.
5,478,003 A 12/1995 Green et al.
5,478,354 A 12/1995 Tovey et al.
5,480,089 A 1/1996 Blewett
5,480,409 A 1/1996 Riza
5,482,197 A 1/1996 Green et al.
5,484,095 A 1/1996 Green et al.
5,484,398 A 1/1996 Stoddard
5,484,451 A 1/1996 Akopov et al.
5,485,947 A 1/1996 Olson et al.
5,485,952 A 1/1996 Fontayne
5,487,499 A 1/1996 Sorrentino et al.
5,487,500 A 1/1996 Knodel et al.
5,489,058 A 2/1996 Plyley et al.
5,489,256 A 2/1996 Adair
5,496,312 A 3/1996 Klicek
5,496,317 A 3/1996 Goble et al.
5,497,933 A 3/1996 DeFonzo et al.
5,503,320 A 4/1996 Webster et al.
5,503,635 A 4/1996 Sauer et al.
5,503,638 A 4/1996 Cooper et al.
5,505,363 A 4/1996 Green et al.
5,507,426 A 4/1996 Young et al.
5,509,596 A 4/1996 Green et al.
5,509,916 A 4/1996 Taylor
5,511,564 A 4/1996 Wilk
5,514,129 A 5/1996 Smith
5,514,157 A 5/1996 Nicholas et al.
5,518,163 A 5/1996 Hooven
5,518,164 A 5/1996 Hooven
5,520,678 A 5/1996 Heckele et al.
5,520,700 A 5/1996 Beyar et al.
5,522,817 A 6/1996 Sander et al.
5,527,320 A 6/1996 Carruthers et al.
5,529,235 A 6/1996 Boiarski et al.
D372,086 S 7/1996 Grasso et al.
5,531,744 A 7/1996 Nardella et al.
5,533,521 A 7/1996 Granger
5,533,581 A 7/1996 Barth et al.
5,533,661 A 7/1996 Main et al.
5,535,934 A 7/1996 Boiarski et al.
5,535,935 A 7/1996 Vidal et al.
5,535,937 A 7/1996 Boiarski et al.
5,540,375 A 7/1996 Bolanos et al.
5,541,376 A 7/1996 Ladtkow et al.
5,542,594 A 8/1996 McKean et al.
5,543,119 A 8/1996 Sutter et al.
5,547,117 A 8/1996 Hamblin et al.
5,549,621 A 8/1996 Bessler et al.
5,549,628 A 8/1996 Cooper et al.
5,549,637 A 8/1996 Crainich
5,551,622 A 9/1996 Yoon
5,553,675 A 9/1996 Pitzen et al.
5,553,765 A 9/1996 Knodel et al.
5,554,169 A 9/1996 Green et al.
5,556,416 A 9/1996 Clark et al.
5,558,665 A 9/1996 Kieturakis
5,558,671 A 9/1996 Yates
5,560,530 A 10/1996 Bolanos et al.
5,560,532 A 10/1996 DeFonzo et al.
5,562,239 A 10/1996 Boiarski et al.
5,562,241 A 10/1996 Knodel et al.
5,562,682 A 10/1996 Oberlin et al.
5,562,701 A 10/1996 Huitema et al.
5,562,702 A 10/1996 Huitema et al.
5,564,615 A 10/1996 Bishop et al.
5,569,161 A 10/1996 Ebling et al.
5,569,284 A 10/1996 Young et al.
5,571,090 A 11/1996 Sherts
5,571,100 A 11/1996 Goble et al.
5,571,116 A 11/1996 Bolanos et al.
5,571,285 A 11/1996 Chow et al.
5,573,543 A 11/1996 Akopov et al.
5,574,431 A 11/1996 McKeown et al.
5,575,789 A 11/1996 Bell et al.
5,575,799 A 11/1996 Bolanos et al.
5,575,803 A 11/1996 Cooper et al.
5,577,654 A 11/1996 Bishop
5,579,978 A 12/1996 Green et al.
5,580,067 A 12/1996 Hamblin et al.
5,582,611 A 12/1996 Tsuruta et al.
5,582,617 A 12/1996 Klieman et al.
5,584,425 A 12/1996 Savage et al.
5,586,711 A 12/1996 Plyley et al.
5,588,579 A 12/1996 Schnut et al.
5,588,580 A 12/1996 Paul et al.
5,588,581 A 12/1996 Conlon et al.
5,591,170 A 1/1997 Spievack et al.
5,591,187 A 1/1997 Dekel
5,597,107 A 1/1997 Knodel et al.
5,599,151 A 2/1997 Daum et al.
5,599,344 A 2/1997 Paterson
5,599,350 A 2/1997 Schulze et al.
5,601,224 A 2/1997 Bishop et al.
5,603,443 A 2/1997 Clark et al.
5,605,272 A 2/1997 Witt et al.
5,605,273 A 2/1997 Hamblin et al.
5,607,094 A 3/1997 Clark et al.
5,607,095 A 3/1997 Smith et al.
5,607,450 A 3/1997 Zvenyatsky et al.
5,609,285 A 3/1997 Grant et al.
5,609,601 A 3/1997 Kolesa et al.
5,611,709 A 3/1997 McAnulty
5,613,966 A 3/1997 Makower et al.
5,618,294 A 4/1997 Aust et al.
5,618,303 A 4/1997 Marlow et al.
5,618,307 A 4/1997 Donlon et al.
5,620,289 A 4/1997 Curry
5,620,452 A 4/1997 Yoon
5,624,452 A 4/1997 Yates
5,626,587 A 5/1997 Bishop et al.
5,626,595 A 5/1997 Sklar et al.
5,628,446 A 5/1997 Geiste et al.
5,628,743 A 5/1997 Cimino
5,630,539 A 5/1997 Plyley et al.
5,630,540 A 5/1997 Blewett
5,630,782 A 5/1997 Adair
5,632,432 A 5/1997 Schulze et al.
5,632,433 A 5/1997 Grant et al.
5,634,584 A 6/1997 Okorocha et al.
5,636,779 A 6/1997 Palmer
5,636,780 A 6/1997 Green et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,639,008 A 6/1997 Gallagher et al.
5,643,291 A 7/1997 Pier et al.
5,645,209 A 7/1997 Green et al.
5,647,526 A 7/1997 Green et al.
5,647,869 A 7/1997 Goble et al.
5,649,937 A 7/1997 Bito et al.
5,651,491 A 7/1997 Heaton et al.
5,653,373 A 8/1997 Green et al.
5,653,374 A 8/1997 Young et al.
5,653,677 A 8/1997 Okada et al.
5,653,721 A 8/1997 Knodel et al.
5,655,698 A 8/1997 Yoon
5,657,921 A 8/1997 Young et al.
5,658,281 A 8/1997 Heard
5,658,300 A 8/1997 Bito et al.
5,662,258 A 9/1997 Knodel et al.
5,662,260 A 9/1997 Yoon
5,662,662 A 9/1997 Bishop et al.
5,665,085 A 9/1997 Nardella
5,667,517 A 9/1997 Hooven
5,667,526 A 9/1997 Levin
5,667,527 A 9/1997 Cook
5,669,544 A 9/1997 Schulze et al.
5,669,904 A 9/1997 Platt, Jr. et al.
5,669,907 A 9/1997 Platt, Jr. et al.
5,669,918 A 9/1997 Balazs et al.
5,673,840 A 10/1997 Schulze et al.
5,673,841 A 10/1997 Schulze et al.
5,673,842 A 10/1997 Bittner et al.
5,678,748 A 10/1997 Plyley et al.
5,680,981 A 10/1997 Mililli et al.
5,680,982 A 10/1997 Schulze et al.
5,680,983 A 10/1997 Plyley et al.
5,683,349 A 11/1997 Makower et al.
5,685,474 A 11/1997 Seeber
5,688,270 A 11/1997 Yates et al.
5,690,269 A 11/1997 Bolanos et al.
5,692,668 A 12/1997 Schulze et al.
5,693,042 A 12/1997 Boiarski et al.
5,693,051 A 12/1997 Schulze et al.
5,695,494 A 12/1997 Becker
5,695,504 A 12/1997 Gifford, III et al.
5,695,524 A 12/1997 Kelley et al.
5,697,543 A 12/1997 Burdorff
5,697,943 A 12/1997 Sauer et al.
5,700,270 A 12/1997 Peyser et al.
5,702,387 A 12/1997 Arts et al.
5,702,408 A 12/1997 Wales et al.
5,702,409 A 12/1997 Rayburn et al.
5,704,087 A 1/1998 Strub
5,704,534 A 1/1998 Huitema et al.
5,706,997 A 1/1998 Green et al.
5,706,998 A 1/1998 Plyley et al.
5,707,392 A 1/1998 Kortenbach
5,709,334 A 1/1998 Sorrentino et al.
5,709,680 A 1/1998 Yates et al.
5,711,472 A 1/1998 Bryan
5,713,128 A 2/1998 Schrenk et al.
5,713,505 A 2/1998 Huitema
5,713,895 A 2/1998 Lontine et al.
5,713,896 A 2/1998 Nardella
5,715,987 A 2/1998 Kelley et al.
5,715,988 A 2/1998 Palmer
5,716,366 A 2/1998 Yates
5,718,359 A 2/1998 Palmer et al.
5,718,360 A 2/1998 Green et al.
5,718,548 A 2/1998 Cotellessa
5,720,744 A 2/1998 Eggleston et al.
D393,067 S 3/1998 Geary et al.
5,725,536 A 3/1998 Oberlin et al.
5,725,554 A 3/1998 Simon et al.
5,728,121 A 3/1998 Bimbo et al.
5,730,758 A 3/1998 Allgeyer
5,732,871 A 3/1998 Clark et al.
5,732,872 A 3/1998 Bolduc et al.
5,735,445 A 4/1998 Vidal et al.
5,735,848 A 4/1998 Yates et al.
5,735,874 A 4/1998 Measamer et al.
5,738,474 A 4/1998 Blewett
5,738,648 A 4/1998 Lands et al.
5,743,456 A 4/1998 Jones et al.
5,747,953 A 5/1998 Philipp
5,749,889 A 5/1998 Bacich et al.
5,749,893 A 5/1998 Vidal et al.
5,752,644 A 5/1998 Bolanos et al.
5,752,965 A 5/1998 Francis et al.
5,755,717 A 5/1998 Yates et al.
5,758,814 A 6/1998 Gallagher et al.
5,762,255 A 6/1998 Chrisman et al.
5,762,256 A 6/1998 Mastri et al.
5,766,188 A 6/1998 Igaki
5,766,205 A 6/1998 Zvenyatsky et al.
5,769,892 A 6/1998 Kingwell
5,772,379 A 6/1998 Evensen
5,772,578 A 6/1998 Heimberger et al.
5,772,659 A 6/1998 Becker et al.
5,776,130 A 7/1998 Buysse et al.
5,779,130 A 7/1998 Alesi et al.
5,779,131 A 7/1998 Knodel et al.
5,779,132 A 7/1998 Knodel et al.
5,782,396 A 7/1998 Mastri et al.
5,782,397 A 7/1998 Koukline
5,782,749 A 7/1998 Riza
5,782,859 A 7/1998 Nicholas et al.
5,784,934 A 7/1998 Izumisawa
5,785,232 A 7/1998 Vidal et al.
5,785,647 A 7/1998 Tompkins et al.
5,787,897 A 8/1998 Kieturakis
5,792,135 A * 8/1998 Madhani et al. 606/1
5,792,165 A 8/1998 Klieman et al.
5,794,834 A 8/1998 Hamblin et al.
5,796,188 A 8/1998 Bays
5,797,536 A 8/1998 Smith et al.
5,797,537 A 8/1998 Oberlin et al.
5,797,538 A 8/1998 Heaton et al.
5,797,906 A 8/1998 Rhum et al.
5,797,959 A 8/1998 Castro et al.
5,799,857 A 9/1998 Robertson et al.
5,807,376 A 9/1998 Viola et al.
5,807,378 A * 9/1998 Jensen et al. 606/1
5,807,393 A 9/1998 Williamson, IV et al.
5,809,441 A 9/1998 McKee
5,810,811 A 9/1998 Yates et al.
5,810,855 A 9/1998 Rayburn et al.
5,813,813 A 9/1998 Daum et al.
5,814,057 A 9/1998 Oi et al.
5,817,084 A 10/1998 Jensen
5,817,091 A 10/1998 Nardella et al.
5,817,093 A 10/1998 Williamson, IV et al.
5,817,109 A 10/1998 McGarry et al.
5,817,119 A 10/1998 Klieman et al.
5,820,009 A 10/1998 Melling et al.
5,823,066 A 10/1998 Huitema et al.
5,826,776 A 10/1998 Schulze et al.
5,827,271 A 10/1998 Buysse et al.
5,829,662 A 11/1998 Allen et al.
5,833,690 A 11/1998 Yates et al.
5,833,695 A 11/1998 Yoon
5,833,696 A 11/1998 Whitfield et al.
5,836,503 A 11/1998 Ehrenfels et al.
5,836,960 A 11/1998 Kolesa et al.
5,839,639 A 11/1998 Sauer et al.
5,843,132 A 12/1998 Ilvento
5,846,254 A 12/1998 Schulze et al.
5,849,011 A 12/1998 Jones et al.
5,855,311 A 1/1999 Hamblin et al.
5,855,583 A * 1/1999 Wang et al. 606/139
5,860,975 A 1/1999 Goble et al.
5,865,361 A 2/1999 Milliman et al.
5,868,760 A 2/1999 McGuckin, Jr.
5,871,135 A 2/1999 Williamson, IV et al.
5,873,885 A 2/1999 Weidenbenner
5,876,401 A 3/1999 Schulze et al.
5,878,193 A 3/1999 Wang et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,878,937 A 3/1999 Green et al.
5,878,938 A 3/1999 Bittner et al.
5,891,160 A 4/1999 Williamson, IV et al.
5,893,506 A 4/1999 Powell
5,894,979 A 4/1999 Powell
5,897,562 A 4/1999 Bolanos et al.
5,899,914 A 5/1999 Zirps et al.
5,901,895 A 5/1999 Heaton et al.
5,902,312 A 5/1999 Frater et al.
5,904,693 A 5/1999 Dicesare et al.
5,906,625 A 5/1999 Bito et al.
5,908,402 A 6/1999 Blythe
5,908,427 A 6/1999 McKean et al.
5,911,353 A 6/1999 Bolanos et al.
5,915,616 A 6/1999 Viola et al.
5,918,791 A 7/1999 Sorrentino et al.
5,919,198 A 7/1999 Graves, Jr. et al.
5,928,256 A 7/1999 Riza
5,931,847 A 8/1999 Bittner et al.
5,931,853 A 8/1999 McEwen et al.
5,937,951 A 8/1999 Izuchukwu et al.
5,938,667 A 8/1999 Peyser et al.
5,941,442 A 8/1999 Geiste et al.
5,944,172 A 8/1999 Hannula
5,944,715 A 8/1999 Goble et al.
5,948,030 A 9/1999 Miller et al.
5,951,552 A 9/1999 Long et al.
5,951,574 A 9/1999 Stefanchik et al.
5,954,259 A 9/1999 Viola et al.
5,964,774 A 10/1999 McKean et al.
5,971,916 A 10/1999 Koren
5,988,479 A 11/1999 Palmer
6,003,517 A 12/1999 Sheffield et al.
6,004,319 A 12/1999 Goble et al.
6,010,054 A 1/2000 Johnson et al.
6,012,494 A 1/2000 Balazs
6,013,076 A 1/2000 Goble et al.
6,015,406 A 1/2000 Goble et al.
6,017,322 A 1/2000 Snoke et al.
6,017,356 A 1/2000 Frederick et al.
6,022,352 A 2/2000 Vandewalle
6,024,741 A 2/2000 Williamson, IV et al.
6,024,748 A 2/2000 Manzo et al.
6,027,501 A 2/2000 Goble et al.
6,032,849 A 3/2000 Mastri et al.
6,033,378 A 3/2000 Lundquist et al.
6,033,399 A 3/2000 Gines
6,033,427 A 3/2000 Lee
6,039,733 A 3/2000 Buysse et al.
6,039,734 A 3/2000 Goble
6,045,560 A 4/2000 McKean et al.
6,050,472 A 4/2000 Shibata
6,053,390 A 4/2000 Green et al.
6,056,746 A 5/2000 Goble et al.
6,063,097 A 5/2000 Oi et al.
6,063,098 A 5/2000 Houser et al.
6,066,132 A 5/2000 Chen et al.
6,068,627 A 5/2000 Orszulak et al.
6,071,233 A 6/2000 Ishikawa et al.
6,074,386 A 6/2000 Goble et al.
6,077,286 A 6/2000 Cuschieri et al.
6,079,606 A 6/2000 Milliman et al.
6,082,577 A 7/2000 Coates et al.
6,083,234 A 7/2000 Nicholas et al.
6,083,242 A 7/2000 Cook
6,086,600 A 7/2000 Kortenbach
6,090,106 A 7/2000 Goble et al.
6,093,186 A 7/2000 Goble
6,099,537 A 8/2000 Sugai et al.
6,099,551 A 8/2000 Gabbay
6,102,271 A 8/2000 Longo et al.
6,109,500 A 8/2000 Alli et al.
6,117,148 A 9/2000 Ravo et al.
6,117,158 A 9/2000 Measamer et al.
6,119,913 A 9/2000 Adams et al.
6,120,433 A 9/2000 Mizuno et al.
6,123,241 A 9/2000 Walter et al.
H1904 H 10/2000 Yates et al.
6,126,058 A 10/2000 Adams et al.
6,126,670 A 10/2000 Walker et al.
6,131,789 A 10/2000 Schulze et al.
6,132,368 A 10/2000 Cooper
6,139,546 A 10/2000 Koenig et al.
6,155,473 A 12/2000 Tompkins et al.
6,156,056 A 12/2000 Kearns et al.
6,159,146 A 12/2000 El Gazayerli
6,159,200 A 12/2000 Verdura et al.
6,162,208 A 12/2000 Hipps
6,165,175 A 12/2000 Wampler et al.
6,165,184 A 12/2000 Verdura et al.
6,168,605 B1 1/2001 Measamer et al.
6,171,316 B1 1/2001 Kovac et al.
6,171,330 B1 1/2001 Benchetrit
6,174,308 B1 1/2001 Goble et al.
6,174,309 B1 1/2001 Wrublewski et al.
6,179,776 B1 1/2001 Adams et al.
6,181,105 B1 1/2001 Cutolo et al.
6,193,129 B1 2/2001 Bittner et al.
6,197,042 B1 3/2001 Ginn et al.
6,202,914 B1 3/2001 Geiste et al.
6,214,028 B1 4/2001 Yoon et al.
6,220,368 B1 4/2001 Ark et al.
6,223,835 B1 5/2001 Habedank et al.
6,228,081 B1 5/2001 Goble
6,228,084 B1 5/2001 Kirwan, Jr.
6,231,565 B1 5/2001 Tovey et al.
6,234,178 B1 5/2001 Goble et al.
6,241,139 B1 6/2001 Milliman et al.
6,241,723 B1 6/2001 Heim et al.
6,249,076 B1 6/2001 Madden et al.
6,250,532 B1 6/2001 Green et al.
6,258,107 B1 7/2001 Balázs et al.
6,261,286 B1 7/2001 Goble et al.
6,264,086 B1 7/2001 McGuckin, Jr.
6,264,087 B1 7/2001 Whitman
6,270,508 B1 8/2001 Klieman et al.
6,273,897 B1 8/2001 Dalessandro et al.
6,277,114 B1 8/2001 Bullivant et al.
6,293,942 B1 9/2001 Goble et al.
6,296,640 B1 10/2001 Wampler et al.
6,302,311 B1 10/2001 Adams et al.
6,306,134 B1 10/2001 Goble et al.
6,309,403 B1 10/2001 Minor et al.
6,315,184 B1 11/2001 Whitman
6,320,123 B1 11/2001 Reimers
6,324,339 B1 11/2001 Hudson et al.
6,325,799 B1 12/2001 Goble
6,325,810 B1 12/2001 Hamilton et al.
6,330,965 B1 12/2001 Milliman et al.
6,331,181 B1 * 12/2001 Tierney et al. 606/130
6,331,761 B1 12/2001 Kumar et al.
6,334,860 B1 1/2002 Dorn
6,336,926 B1 1/2002 Goble
6,338,737 B1 1/2002 Toledano
6,346,077 B1 2/2002 Taylor et al.
6,352,503 B1 3/2002 Matsui et al.
6,358,224 B1 3/2002 Tims et al.
6,364,877 B1 4/2002 Goble et al.
6,364,888 B1 4/2002 Niemeyer et al.
6,373,152 B1 4/2002 Wang et al.
6,387,113 B1 5/2002 Hawkins et al.
6,387,114 B2 5/2002 Adams
6,391,038 B2 5/2002 Vargas et al.
6,398,781 B1 6/2002 Goble et al.
6,398,797 B2 6/2002 Bombard et al.
6,402,766 B2 6/2002 Bowman et al.
6,406,440 B1 6/2002 Stefanchik
6,409,724 B1 6/2002 Penny et al.
H2037 H 7/2002 Yates et al.
6,416,486 B1 7/2002 Wampler
6,416,509 B1 7/2002 Goble et al.
6,419,695 B1 7/2002 Gabbay
RE37,814 E 8/2002 Allgeyer
6,428,070 B1 8/2002 Takanashi et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,429,611 B1 8/2002 Li
6,436,097 B1 8/2002 Nardella
6,436,107 B1 8/2002 Wang et al.
6,436,110 B2 8/2002 Bowman et al.
6,436,122 B1 8/2002 Frank et al.
6,439,446 B1 8/2002 Perry et al.
6,440,146 B2 8/2002 Nicholas et al.
6,443,973 B1 9/2002 Whitman
6,450,391 B1 9/2002 Kayan et al.
6,468,275 B1 10/2002 Wampler et al.
6,471,106 B1 10/2002 Reining
6,482,200 B2 11/2002 Shippert
6,485,490 B2 11/2002 Wampler et al.
6,488,196 B1 12/2002 Fenton, Jr.
6,488,197 B1 12/2002 Whitman
6,491,201 B1 12/2002 Whitman
6,491,690 B1 12/2002 Goble et al.
6,491,701 B2 12/2002 Tierney et al.
6,492,785 B1 12/2002 Kasten et al.
6,494,896 B1 12/2002 D'Alessio et al.
6,503,257 B2 1/2003 Grant et al.
6,503,259 B2 1/2003 Huxel et al.
6,505,768 B2 1/2003 Whitman
6,510,854 B2 1/2003 Goble
6,511,468 B1 1/2003 Cragg et al.
6,517,535 B2 2/2003 Edwards
6,517,565 B1 2/2003 Whitman et al.
6,517,566 B1 2/2003 Hovland et al.
6,522,101 B2 2/2003 Malackowski
6,543,456 B1 4/2003 Freeman
6,547,786 B1 4/2003 Goble
6,550,546 B2 4/2003 Thurler et al.
6,551,333 B2 4/2003 Kuhns et al.
6,554,861 B2 4/2003 Knox et al.
6,558,379 B1 5/2003 Batchelor et al.
6,565,560 B1 5/2003 Goble et al.
6,569,085 B2 5/2003 Kortenbach et al.
6,569,171 B2 5/2003 DeGuillebon et al.
6,578,751 B2 6/2003 Hartwick
6,582,427 B1 6/2003 Goble et al.
6,588,643 B2 7/2003 Bolduc et al.
6,589,164 B1 7/2003 Flaherty
6,592,597 B2 7/2003 Grant et al.
6,596,432 B2 7/2003 Kawakami et al.
D478,665 S 8/2003 Isaacs et al.
D478,986 S 8/2003 Johnston et al.
6,601,749 B2 8/2003 Sullivan et al.
6,602,252 B2 8/2003 Mollenauer
6,605,078 B2 8/2003 Adams
6,605,669 B2 8/2003 Awokola et al.
6,616,686 B2 9/2003 Coleman et al.
6,619,529 B2 9/2003 Green et al.
6,620,166 B1 9/2003 Wenstrom, Jr. et al.
6,626,834 B2 9/2003 Dunne et al.
6,629,630 B2 10/2003 Adams
6,629,974 B2 10/2003 Penny et al.
6,629,988 B2 10/2003 Weadock
6,636,412 B2 10/2003 Smith
6,638,108 B2 10/2003 Tachi
6,638,285 B2 10/2003 Gabbay
6,638,297 B1 10/2003 Huitema
RE38,335 E 11/2003 Aust et al.
6,641,528 B2 11/2003 Torii
6,644,532 B2 11/2003 Green et al.
6,646,307 B1 11/2003 Yu et al.
6,648,816 B2 11/2003 Irion et al.
D484,243 S 12/2003 Ryan et al.
D484,595 S 12/2003 Ryan et al.
D484,596 S 12/2003 Ryan et al.
6,656,193 B2 12/2003 Grant et al.
6,666,875 B1 12/2003 Sakurai et al.
6,669,073 B2 12/2003 Milliman et al.
6,671,185 B2 12/2003 Duval
D484,977 S 1/2004 Ryan et al.
6,676,660 B2 1/2004 Wampler et al.
6,679,410 B2 1/2004 Würsch et al.
6,681,978 B2 1/2004 Geiste et al.
6,681,979 B2 1/2004 Whitman
6,682,527 B2 1/2004 Strul
6,682,528 B2 1/2004 Frazier et al.
6,685,727 B2 2/2004 Fisher et al.
6,692,507 B2 2/2004 Pugsley et al.
6,695,199 B2 2/2004 Whitman
6,698,643 B2 3/2004 Whitman
6,699,235 B2 3/2004 Wallace et al.
6,704,210 B1 3/2004 Myers
6,705,503 B1 3/2004 Pedicini et al.
6,712,773 B1 3/2004 Viola
6,716,223 B2 4/2004 Leopold et al.
6,716,232 B1 4/2004 Vidal et al.
6,716,233 B1 4/2004 Whitman
6,722,552 B2 4/2004 Fenton, Jr.
6,723,087 B2 4/2004 O'Neill et al.
6,723,091 B2 4/2004 Goble et al.
6,726,697 B2 4/2004 Nicholas et al.
6,740,030 B2 5/2004 Martone et al.
6,747,121 B2 6/2004 Gogolewski
6,749,560 B1 6/2004 Konstorum et al.
6,752,768 B2 6/2004 Burdorff et al.
6,752,816 B2 6/2004 Culp et al.
6,755,195 B1 6/2004 Lemke et al.
6,755,338 B2 6/2004 Hahnen et al.
6,758,846 B2 7/2004 Goble et al.
6,761,685 B2 7/2004 Adams et al.
6,767,352 B2 7/2004 Field et al.
6,767,356 B2 7/2004 Kanner et al.
6,769,590 B2 8/2004 Vresh et al.
6,769,594 B2 8/2004 Orban, III
6,773,438 B1 8/2004 Knodel et al.
6,777,838 B2 8/2004 Miekka et al.
6,780,151 B2 8/2004 Grabover et al.
6,780,180 B1 8/2004 Goble et al.
6,783,524 B2 8/2004 Anderson et al.
6,786,382 B1 9/2004 Hoffman
6,786,864 B2 9/2004 Matsuura et al.
6,786,896 B1 9/2004 Madhani et al.
6,790,173 B2 9/2004 Saadat et al.
6,793,652 B1 9/2004 Whitman et al.
6,805,273 B2 10/2004 Bilotti et al.
6,806,808 B1 10/2004 Watters et al.
6,808,525 B2 10/2004 Latterell et al.
6,814,741 B2 11/2004 Bowman et al.
6,817,508 B1 11/2004 Racenet et al.
6,817,509 B2 11/2004 Geiste et al.
6,817,974 B2 11/2004 Cooper et al.
6,821,273 B2 11/2004 Mollenauer
6,821,284 B2 11/2004 Sturtz et al.
6,827,725 B2 12/2004 Batchelor et al.
6,828,902 B2 12/2004 Casden
6,830,174 B2 12/2004 Hillstead et al.
6,832,998 B2 12/2004 Goble
6,834,001 B2 12/2004 Myono
6,835,199 B2 12/2004 McGuckin, Jr. et al.
6,843,403 B2 1/2005 Whitman
6,843,789 B2 1/2005 Goble
6,846,307 B2 1/2005 Whitman et al.
6,846,308 B2 1/2005 Whitman et al.
6,846,309 B2 1/2005 Whitman et al.
6,849,071 B2 2/2005 Whitman et al.
RE38,708 E 3/2005 Bolanos et al.
6,866,178 B2 3/2005 Adams et al.
6,872,214 B2 3/2005 Sonnenschein et al.
6,874,669 B2 4/2005 Adams et al.
6,877,647 B2 4/2005 Green et al.
6,878,106 B1 4/2005 Herrmann
6,889,116 B2 5/2005 Jinno
6,893,435 B2 5/2005 Goble
6,905,057 B2 6/2005 Swayze et al.
6,905,497 B2 6/2005 Truckai et al.
6,913,608 B2 7/2005 Liddicoat et al.
6,913,613 B2 7/2005 Schwarz et al.
6,923,803 B2 8/2005 Goble
6,929,641 B2 8/2005 Goble et al.
6,931,830 B2 8/2005 Liao

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,936,042 B2 8/2005 Wallace et al.
6,939,358 B2 9/2005 Palacios et al.
6,942,662 B2 9/2005 Goble et al.
6,945,444 B2 9/2005 Gresham et al.
6,953,138 B1 10/2005 Dworak et al.
6,953,139 B2 10/2005 Milliman et al.
6,959,851 B2 11/2005 Heinrich
6,959,852 B2 11/2005 Shelton, IV et al.
6,960,163 B2 11/2005 Ewers et al.
6,960,220 B2 11/2005 Marino et al.
6,964,363 B2 11/2005 Wales et al.
6,966,907 B2 11/2005 Goble
6,966,909 B2 11/2005 Marshall et al.
6,972,199 B2 12/2005 Lebouitz et al.
6,974,462 B2 12/2005 Sater
6,978,921 B2 12/2005 Shelton, IV et al.
6,978,922 B2 12/2005 Bilotti et al.
6,981,628 B2 * 1/2006 Wales 227/178.1
6,981,941 B2 1/2006 Whitman et al.
6,981,978 B2 1/2006 Gannoe
6,984,203 B2 1/2006 Tartaglia et al.
6,984,231 B2 1/2006 Goble et al.
6,986,451 B1 1/2006 Mastri et al.
6,988,649 B2 1/2006 Shelton, IV et al.
6,988,650 B2 1/2006 Schwemberger et al.
6,990,796 B2 1/2006 Schnipke et al.
6,994,708 B2 2/2006 Manzo
6,997,931 B2 2/2006 Sauer et al.
7,000,818 B2 2/2006 Shelton, IV et al.
7,000,819 B2 2/2006 Swayze et al.
7,001,380 B2 2/2006 Goble
7,001,408 B2 2/2006 Knodel et al.
7,008,435 B2 3/2006 Cummins
7,018,390 B2 3/2006 Turovskiy et al.
7,025,743 B2 4/2006 Mann et al.
7,029,435 B2 4/2006 Nakao
7,032,798 B2 4/2006 Whitman et al.
7,032,799 B2 4/2006 Viola et al.
7,033,356 B2 4/2006 Latterell et al.
7,036,680 B1 5/2006 Flannery
7,037,344 B2 5/2006 Kagan et al.
7,044,352 B2 5/2006 Shelton, IV et al.
7,044,353 B2 5/2006 Mastri et al.
7,048,687 B1 5/2006 Reuss et al.
7,052,494 B2 5/2006 Goble et al.
7,055,730 B2 6/2006 Ehrenfels et al.
7,055,731 B2 6/2006 Shelton, IV et al.
7,056,284 B2 6/2006 Martone et al.
7,056,330 B2 6/2006 Gayton
7,059,331 B2 6/2006 Adams et al.
7,059,508 B2 6/2006 Shelton, IV et al.
7,063,712 B2 6/2006 Vargas et al.
7,066,879 B2 6/2006 Fowler et al.
7,066,944 B2 6/2006 Laufer et al.
7,070,083 B2 7/2006 Jankowski
7,070,559 B2 7/2006 Adams et al.
7,071,287 B2 7/2006 Rhine et al.
7,075,770 B1 7/2006 Smith
7,077,856 B2 7/2006 Whitman
7,080,769 B2 7/2006 Vresh et al.
7,081,114 B2 7/2006 Rashidi
7,083,073 B2 8/2006 Yoshie et al.
7,083,075 B2 8/2006 Swayze et al.
7,083,571 B2 8/2006 Wang et al.
7,083,615 B2 8/2006 Peterson et al.
7,087,071 B2 8/2006 Nicholas et al.
7,090,637 B2 8/2006 Danitz et al.
7,090,673 B2 8/2006 Dycus et al.
7,090,683 B2 8/2006 Brock et al.
7,090,684 B2 8/2006 McGuckin, Jr. et al.
7,094,202 B2 8/2006 Nobis et al.
7,094,247 B2 8/2006 Monassevitch et al.
7,097,089 B2 8/2006 Marczyk
7,098,794 B2 8/2006 Lindsay et al.
7,104,741 B2 9/2006 Krohn
7,108,695 B2 9/2006 Witt et al.
7,108,701 B2 9/2006 Evens et al.
7,108,709 B2 9/2006 Cummins
7,111,769 B2 9/2006 Wales et al.
7,112,214 B2 9/2006 Peterson et al.
RE39,358 E 10/2006 Goble
7,114,642 B2 10/2006 Whitman
7,118,582 B1 10/2006 Wang et al.
7,121,446 B2 10/2006 Arad et al.
7,122,028 B2 10/2006 Looper et al.
7,128,253 B2 10/2006 Mastri et al.
7,128,254 B2 10/2006 Shelton, IV et al.
7,128,748 B2 10/2006 Mooradian et al.
7,131,445 B2 11/2006 Amoah
7,133,601 B2 11/2006 Phillips et al.
7,140,527 B2 11/2006 Ehrenfels et al.
7,140,528 B2 11/2006 Shelton, IV
7,143,923 B2 12/2006 Shelton, IV et al.
7,143,924 B2 12/2006 Scirica et al.
7,143,925 B2 12/2006 Shelton, IV et al.
7,143,926 B2 12/2006 Shelton, IV et al.
7,147,138 B2 12/2006 Shelton, IV
7,147,139 B2 12/2006 Schwemberger et al.
7,147,637 B2 12/2006 Goble
7,147,650 B2 12/2006 Lee
7,150,748 B2 12/2006 Ebbutt et al.
7,153,300 B2 12/2006 Goble
7,156,863 B2 1/2007 Sonnenschein et al.
7,159,750 B2 1/2007 Racenet et al.
7,160,299 B2 1/2007 Baily
7,161,036 B2 1/2007 Oikawa et al.
7,168,604 B2 1/2007 Milliman et al.
7,172,104 B2 2/2007 Scirica et al.
7,179,223 B2 2/2007 Motoki et al.
7,179,267 B2 2/2007 Nolan et al.
7,182,239 B1 2/2007 Myers
7,188,758 B2 3/2007 Viola et al.
7,189,207 B2 3/2007 Viola
7,195,627 B2 3/2007 Amoah et al.
7,204,835 B2 4/2007 Latterell et al.
7,207,233 B2 4/2007 Wadge
7,207,471 B2 4/2007 Heinrich et al.
7,207,472 B2 4/2007 Wukusick et al.
7,208,005 B2 4/2007 Frecker et al.
7,210,609 B2 5/2007 Leiboff et al.
7,211,081 B2 5/2007 Goble
7,211,084 B2 5/2007 Goble et al.
7,213,736 B2 5/2007 Wales et al.
7,214,224 B2 5/2007 Goble
7,217,285 B2 5/2007 Vargas et al.
7,220,260 B2 5/2007 Fleming et al.
7,220,272 B2 5/2007 Weadock
7,225,963 B2 6/2007 Scirica
7,225,964 B2 6/2007 Mastri et al.
7,234,624 B2 6/2007 Gresham et al.
7,235,089 B1 6/2007 McGuckin, Jr.
7,235,302 B2 6/2007 Jing et al.
7,237,708 B1 7/2007 Guy et al.
7,238,195 B2 7/2007 Viola
7,241,288 B2 7/2007 Braun
7,246,734 B2 7/2007 Shelton, IV
7,247,161 B2 7/2007 Johnston et al.
7,252,660 B2 8/2007 Kunz
7,255,696 B2 8/2007 Goble et al.
7,258,262 B2 8/2007 Mastri et al.
7,260,431 B2 8/2007 Libbus et al.
7,265,374 B2 9/2007 Lee et al.
7,267,679 B2 9/2007 McGuckin, Jr. et al.
7,273,483 B2 9/2007 Wiener et al.
7,278,562 B2 10/2007 Mastri et al.
7,278,563 B1 10/2007 Green
7,278,994 B2 10/2007 Goble
7,282,048 B2 10/2007 Goble et al.
7,295,907 B2 11/2007 Lu et al.
7,296,724 B2 11/2007 Green et al.
7,297,149 B2 11/2007 Vitali et al.
7,300,450 B2 11/2007 Vleugels et al.
7,303,106 B2 12/2007 Milliman et al.
7,303,107 B2 12/2007 Milliman et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,303,108 B2 12/2007 Shelton, IV
7,303,556 B2 12/2007 Metzger
7,308,998 B2 12/2007 Mastri et al.
7,322,975 B2 1/2008 Goble et al.
7,324,572 B2 1/2008 Chang
7,328,828 B2 2/2008 Ortiz et al.
7,328,829 B2 2/2008 Arad et al.
7,330,004 B2 2/2008 DeJonge et al.
7,334,717 B2 2/2008 Rethy et al.
7,334,718 B2 2/2008 McAlister et al.
7,336,184 B2 2/2008 Smith et al.
7,338,513 B2 3/2008 Lee et al.
7,341,591 B2 3/2008 Grinberg
7,343,920 B2 3/2008 Toby et al.
7,348,763 B1 3/2008 Reinhart et al.
7,351,258 B2 4/2008 Ricotta et al.
7,354,447 B2 4/2008 Shelton, IV et al.
7,357,287 B2 4/2008 Shelton, IV et al.
7,364,060 B2 4/2008 Milliman
7,364,061 B2 4/2008 Swayze et al.
7,377,928 B2 5/2008 Zubik et al.
7,380,695 B2 6/2008 Doll et al.
7,380,696 B2 6/2008 Shelton, IV et al.
7,388,217 B2 6/2008 Buschbeck et al.
7,396,356 B2 7/2008 Mollenauer
7,397,364 B2 7/2008 Govari
7,398,907 B2 7/2008 Racenet et al.
7,398,908 B2 7/2008 Holsten et al.
7,401,721 B2 7/2008 Holsten et al.
7,404,508 B2 7/2008 Smith et al.
7,404,509 B2 7/2008 Ortiz et al.
7,407,075 B2 8/2008 Holsten et al.
7,407,078 B2 8/2008 Shelton, IV et al.
7,410,086 B2 8/2008 Ortiz et al.
7,416,101 B2 8/2008 Shelton, IV et al.
7,418,078 B2 8/2008 Blanz et al.
7,419,080 B2 9/2008 Smith et al.
7,422,136 B1 9/2008 Marczyk
7,422,139 B2 9/2008 Shelton, IV et al.
7,424,965 B2 9/2008 Racenet et al.
7,431,188 B1 10/2008 Marczyk
7,431,189 B2 10/2008 Shelton, IV et al.
7,431,694 B2 10/2008 Stefanchik et al.
7,431,730 B2 10/2008 Viola
7,434,715 B2 10/2008 Shelton, IV et al.
7,434,717 B2 10/2008 Shelton, IV et al.
7,438,209 B1 10/2008 Hess et al.
7,439,354 B2 10/2008 Lenges et al.
7,441,684 B2 10/2008 Shelton, IV et al.
7,441,685 B1 10/2008 Boudreaux
7,442,201 B2 10/2008 Pugsley et al.
7,448,525 B2 11/2008 Shelton, IV et al.
7,455,208 B2 11/2008 Wales et al.
7,455,676 B2 11/2008 Holsten et al.
7,455,682 B2 11/2008 Viola
7,461,767 B2 12/2008 Viola et al.
7,464,846 B2 12/2008 Shelton, IV et al.
7,464,847 B2 12/2008 Viola et al.
7,464,849 B2 12/2008 Shelton, IV et al.
7,467,740 B2 12/2008 Shelton, IV et al.
7,467,849 B2 12/2008 Silverbrook et al.
7,472,814 B2 1/2009 Mastri et al.
7,472,815 B2 1/2009 Shelton, IV et al.
7,473,253 B2 1/2009 Dycus et al.
7,479,608 B2 1/2009 Smith
7,481,347 B2 1/2009 Roy
7,481,349 B2 1/2009 Holsten et al.
7,481,824 B2 1/2009 Boudreaux et al.
7,485,133 B2 2/2009 Cannon et al.
7,490,749 B2 2/2009 Schall et al.
7,494,039 B2 2/2009 Racenet et al.
7,494,499 B2 2/2009 Nagase et al.
7,500,979 B2 3/2009 Hueil et al.
7,501,198 B2 3/2009 Barlev et al.
7,506,790 B2 3/2009 Shelton, IV
7,506,791 B2 3/2009 Omaits et al.
7,510,107 B2 3/2009 Timm et al.
7,524,320 B2 4/2009 Tierney et al.
7,530,985 B2 5/2009 Takemoto et al.
7,546,940 B2 6/2009 Milliman et al.
7,547,312 B2 6/2009 Bauman et al.
7,549,563 B2 6/2009 Mather et al.
7,549,564 B2 6/2009 Boudreaux
7,552,854 B2 6/2009 Wixey et al.
7,556,186 B2 7/2009 Milliman
7,559,450 B2 7/2009 Wales et al.
7,559,452 B2 7/2009 Wales et al.
7,563,862 B2 7/2009 Sieg et al.
7,566,300 B2 7/2009 Devierre et al.
7,568,603 B2 8/2009 Shelton, IV et al.
7,568,604 B2 8/2009 Ehrenfels et al.
7,568,619 B2 8/2009 Todd et al.
7,575,144 B2 8/2009 Ortiz et al.
7,588,175 B2 9/2009 Timm et al.
7,588,176 B2 9/2009 Timm et al.
7,597,229 B2 10/2009 Boudreaux et al.
7,600,663 B2 10/2009 Green
7,604,150 B2 10/2009 Boudreaux
7,604,151 B2 10/2009 Hess et al.
7,607,557 B2 10/2009 Shelton, IV et al.
7,611,038 B2 11/2009 Racenet et al.
7,615,003 B2 11/2009 Stefanchik et al.
7,624,902 B2 12/2009 Marczyk et al.
7,631,793 B2 12/2009 Rethy et al.
7,635,074 B2 12/2009 Olson et al.
7,637,409 B2 12/2009 Marczyk
7,641,092 B2 1/2010 Kruszynski et al.
7,641,093 B2 1/2010 Doll et al.
7,641,095 B2 1/2010 Viola
7,644,848 B2 1/2010 Swayze et al.
7,648,519 B2 1/2010 Lee et al.
7,651,017 B2 1/2010 Ortiz et al.
7,651,498 B2 1/2010 Shifrin et al.
7,656,131 B2 2/2010 Embrey et al.
7,658,311 B2 2/2010 Boudreaux
7,658,312 B2 2/2010 Vidal et al.
7,665,646 B2 2/2010 Prommersberger
7,665,647 B2 2/2010 Shelton, IV et al.
7,669,746 B2 3/2010 Shelton, IV
7,669,747 B2 3/2010 Weisenburgh, II et al.
7,670,334 B2 3/2010 Hueil et al.
7,673,780 B2 3/2010 Shelton, IV et al.
7,673,781 B2 3/2010 Swayze et al.
7,673,782 B2 3/2010 Hess et al.
7,673,783 B2 3/2010 Morgan et al.
7,674,255 B2 3/2010 Braun
7,682,307 B2 3/2010 Danitz et al.
7,686,826 B2 3/2010 Lee et al.
7,688,028 B2 3/2010 Phillips et al.
7,691,098 B2 4/2010 Wallace et al.
7,699,204 B2 4/2010 Viola
7,699,859 B2 4/2010 Bombard et al.
7,708,180 B2 5/2010 Murray et al.
7,708,758 B2 5/2010 Lee et al.
7,714,239 B2 5/2010 Smith
7,717,312 B2 5/2010 Beetel
7,721,930 B2 5/2010 McKenna et al.
7,721,931 B2 5/2010 Shelton, IV et al.
7,721,934 B2 5/2010 Shelton, IV et al.
7,721,936 B2 5/2010 Shelton, IV et al.
7,722,610 B2 5/2010 Viola et al.
7,726,537 B2 6/2010 Olson et al.
7,726,538 B2 6/2010 Holsten et al.
7,731,072 B2 6/2010 Timm et al.
7,735,703 B2 6/2010 Morgan et al.
7,738,971 B2 6/2010 Swayze et al.
7,740,159 B2 6/2010 Shelton, IV et al.
7,743,960 B2 6/2010 Whitman et al.
7,744,627 B2 6/2010 Orban, III et al.
7,753,245 B2 7/2010 Boudreaux et al.
7,753,904 B2 7/2010 Shelton, IV et al.
7,766,209 B2 8/2010 Baxter, III et al.
7,766,210 B2 8/2010 Shelton, IV et al.
7,766,821 B2 8/2010 Brunnen et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

7,770,775 B2 8/2010 Shelton, IV et al.
7,771,396 B2 8/2010 Stefanchik et al.
7,772,720 B2 8/2010 McGee et al.
7,776,060 B2 8/2010 Mooradian et al.
7,780,054 B2 8/2010 Wales
7,780,055 B2 8/2010 Scirica et al.
7,780,663 B2 8/2010 Yates et al.
7,780,685 B2 8/2010 Hunt et al.
7,784,662 B2 8/2010 Wales et al.
7,793,812 B2 9/2010 Moore et al.
7,794,475 B2 9/2010 Hess et al.
7,798,386 B2 9/2010 Schall et al.
7,799,039 B2 9/2010 Shelton, IV et al.
7,803,151 B2 9/2010 Whitman
7,806,891 B2 10/2010 Nowlin et al.
7,810,692 B2 10/2010 Hall et al.
7,810,693 B2 10/2010 Broehl et al.
7,815,092 B2 10/2010 Whitman et al.
7,815,565 B2 10/2010 Stefanchik et al.
7,819,296 B2 10/2010 Hueil et al.
7,819,297 B2 10/2010 Doll et al.
7,819,298 B2 10/2010 Hall et al.
7,819,299 B2 10/2010 Shelton, IV et al.
7,823,592 B2 11/2010 Bettuchi et al.
7,824,401 B2 11/2010 Manzo et al.
7,828,189 B2 11/2010 Holsten et al.
7,828,794 B2 11/2010 Sartor
7,828,808 B2 11/2010 Hinman et al.
7,832,408 B2 11/2010 Shelton, IV et al.
7,832,611 B2 11/2010 Boyden et al.
7,832,612 B2 11/2010 Baxter, III et al.
7,836,400 B2 11/2010 May et al.
7,837,080 B2 11/2010 Schwemberger
7,837,081 B2 11/2010 Holsten et al.
7,845,533 B2 12/2010 Marczyk et al.
7,845,534 B2 12/2010 Viola et al.
7,845,537 B2 12/2010 Shelton, IV et al.
7,846,149 B2 12/2010 Jankowski
7,850,642 B2 12/2010 Moll et al.
7,857,185 B2 12/2010 Swayze et al.
7,857,186 B2 12/2010 Baxter, III et al.
7,861,906 B2 1/2011 Doll et al.
7,866,527 B2 1/2011 Hall et al.
7,870,989 B2 1/2011 Viola et al.
7,871,418 B2 1/2011 Thompson et al.
7,887,530 B2 2/2011 Zemlok et al.
7,900,805 B2 3/2011 Shelton, IV et al.
7,905,380 B2 3/2011 Shelton, IV et al.
7,905,381 B2 3/2011 Baxter, III et al.
7,909,191 B2 3/2011 Baker et al.
7,909,221 B2 3/2011 Viola et al.
7,913,891 B2 3/2011 Doll et al.
7,914,543 B2 3/2011 Roth et al.
7,918,376 B1 4/2011 Knodel et al.
7,918,377 B2 4/2011 Measamer et al.
7,918,848 B2 4/2011 Lau et al.
7,922,061 B2 4/2011 Shelton, IV et al.
7,922,063 B2 4/2011 Zemlok et al.
7,934,630 B2 5/2011 Shelton, IV et al.
7,938,307 B2 5/2011 Bettuchi
7,941,865 B2 5/2011 Seman, Jr. et al.
7,942,303 B2 5/2011 Shah
7,942,890 B2 5/2011 D'Agostino et al.
7,944,175 B2 5/2011 Mori et al.
7,950,560 B2 5/2011 Zemlok et al.
7,954,682 B2 6/2011 Giordano et al.
7,954,684 B2 6/2011 Boudreaux
7,954,686 B2 6/2011 Baxter, III et al.
7,959,050 B2 6/2011 Smith et al.
7,959,051 B2 6/2011 Smith et al.
7,963,963 B2 6/2011 Francischelli et al.
7,966,799 B2 6/2011 Morgan et al.
7,967,180 B2 6/2011 Scirica
7,980,443 B2 7/2011 Scheib et al.
7,997,469 B2 8/2011 Olson et al.
8,002,795 B2 8/2011 Beetel
8,006,889 B2 8/2011 Adams et al.
8,011,551 B2 9/2011 Marczyk et al.
8,011,555 B2 9/2011 Tarinelli et al.
8,016,177 B2 9/2011 Bettuchi et al.
8,020,743 B2 9/2011 Shelton, IV
8,025,199 B2 9/2011 Whitman et al.
8,028,883 B2 10/2011 Stopek
8,034,077 B2 10/2011 Smith et al.
8,038,045 B2 10/2011 Bettuchi et al.
8,038,046 B2 10/2011 Smith et al.
8,056,787 B2 11/2011 Boudreaux et al.
8,062,330 B2 11/2011 Prommersberger et al.
8,066,167 B2 11/2011 Measamer et al.
D650,074 S 12/2011 Hunt et al.
8,083,119 B2 12/2011 Prommersberger
8,083,120 B2 12/2011 Shelton, IV et al.
8,091,756 B2 1/2012 Viola
8,097,017 B2 1/2012 Viola
8,100,310 B2 1/2012 Zemlok
8,108,072 B2 1/2012 Zhao et al.
8,113,410 B2 2/2012 Hall et al.
8,123,103 B2 2/2012 Milliman
8,123,767 B2 2/2012 Bauman et al.
8,128,645 B2 3/2012 Sonnenschein et al.
8,136,712 B2 3/2012 Zingman
8,141,762 B2 3/2012 Bedi et al.
8,152,041 B2 4/2012 Kostrzewski
8,157,145 B2 4/2012 Shelton, IV et al.
8,157,152 B2 4/2012 Holsten et al.
8,157,153 B2 4/2012 Shelton, IV et al.
8,161,977 B2 4/2012 Shelton, IV et al.
8,167,185 B2 5/2012 Shelton, IV et al.
8,167,895 B2 5/2012 D'Agostino et al.
8,172,124 B2 5/2012 Shelton, IV et al.
8,186,555 B2 5/2012 Shelton, IV et al.
8,186,560 B2 5/2012 Hess et al.
8,192,460 B2 6/2012 Orban, III et al.
8,196,795 B2 6/2012 Moore et al.
8,196,796 B2 6/2012 Shelton, IV et al.
8,201,721 B2 6/2012 Zemlok et al.
8,205,781 B2 6/2012 Baxter, III et al.
8,210,411 B2 7/2012 Yates et al.
8,210,414 B2 7/2012 Bettuchi et al.
8,211,125 B2 7/2012 Spivey
8,215,531 B2 7/2012 Shelton, IV et al.
8,220,468 B2 7/2012 Cooper et al.
8,225,799 B2 7/2012 Bettuchi
8,241,271 B2 8/2012 Millman et al.
8,245,898 B2 8/2012 Smith et al.
8,245,901 B2 8/2012 Stopek
8,256,654 B2 9/2012 Bettuchi et al.
8,257,391 B2 9/2012 Orban, III et al.
8,276,802 B2 10/2012 Kostrzewski
8,328,802 B2 12/2012 Deville et al.
8,348,127 B2 1/2013 Marczyk
8,348,972 B2 1/2013 Soltz et al.
8,353,437 B2 1/2013 Boudreaux
8,353,438 B2 1/2013 Baxter, III et al.
8,353,439 B2 1/2013 Baxter, III et al.
8,365,973 B1 2/2013 White et al.
8,372,094 B2 2/2013 Bettuchi et al.
2002/0022836 A1 2/2002 Goble et al.
2002/0029036 A1 3/2002 Goble et al.
2002/0072736 A1* 6/2002 Tierney et al. 606/1
2002/0117534 A1 8/2002 Green et al.
2002/0134811 A1 9/2002 Napier et al.
2002/0165541 A1* 11/2002 Whitman 606/48
2003/0093103 A1 5/2003 Malackowski et al.
2003/0105478 A1 6/2003 Whitman et al.
2003/0130677 A1 7/2003 Whitman et al.
2003/0139741 A1 7/2003 Goble et al.
2003/0153908 A1 8/2003 Goble et al.
2003/0195387 A1 10/2003 Kortenbach et al.
2003/0205029 A1 11/2003 Chapolini et al.
2003/0216732 A1 11/2003 Truckai et al.
2003/0220660 A1 11/2003 Kortenbach et al.
2004/0002726 A1 1/2004 Nunez et al.
2004/0006335 A1 1/2004 Garrison

(56) **References Cited**

U.S. PATENT DOCUMENTS

2004/0006340 A1 1/2004 Latterell et al.
2004/0006372 A1 1/2004 Racenet et al.
2004/0030333 A1 2/2004 Goble
2004/0034357 A1 2/2004 Beane et al.
2004/0034369 A1 2/2004 Sauer et al.
2004/0044364 A1 3/2004 DeVries et al.
2004/0068161 A1 4/2004 Couvillon, Jr.
2004/0068307 A1 4/2004 Goble
2004/0070369 A1 4/2004 Sakakibara
2004/0078037 A1 4/2004 Batchelor et al.
2004/0093024 A1 5/2004 Lousararian et al.
2004/0094597 A1 5/2004 Whitman et al.
2004/0097987 A1 5/2004 Pugsley et al.
2004/0098040 A1 5/2004 Taniguchi et al.
2004/0101822 A1 5/2004 Wiesner et al.
2004/0108357 A1 6/2004 Milliman et al.
2004/0111081 A1 6/2004 Whitman et al.
2004/0115022 A1 6/2004 Albertson et al.
2004/0116952 A1 6/2004 Sakurai et al.
2004/0147909 A1 7/2004 Johnston et al.
2004/0164123 A1 8/2004 Racenet et al.
2004/0167572 A1 8/2004 Roth et al.
2004/0173659 A1 9/2004 Green et al.
2004/0181219 A1 9/2004 Goble et al.
2004/0186470 A1 9/2004 Goble et al.
2004/0193189 A1 9/2004 Kortenbach et al.
2004/0222268 A1 11/2004 Bilotti et al.
2004/0230214 A1 11/2004 Donofrio et al.
2004/0232201 A1 11/2004 Wenchell et al.
2004/0243151 A1 12/2004 Demmy et al.
2004/0243163 A1 12/2004 Casiano et al.
2004/0243176 A1 12/2004 Hahnen et al.
2004/0254566 A1* 12/2004 Plicchi et al. 606/1
2004/0254608 A1 12/2004 Huitema et al.
2004/0260315 A1 12/2004 Dell et al.
2004/0267310 A1 12/2004 Racenet et al.
2005/0032511 A1 2/2005 Malone et al.
2005/0033357 A1 2/2005 Braun
2005/0054946 A1 3/2005 Krzyzanowski
2005/0059997 A1 3/2005 Bauman et al.
2005/0070929 A1 3/2005 Dalessandro et al.
2005/0075561 A1 4/2005 Golden
2005/0080454 A1 4/2005 Drews et al.
2005/0085693 A1 4/2005 Belson et al.
2005/0090817 A1 4/2005 Phan
2005/0096683 A1 5/2005 Ellins et al.
2005/0103819 A1 5/2005 Racenet et al.
2005/0107814 A1 5/2005 Johnston et al.
2005/0107824 A1 5/2005 Hillstead et al.
2005/0113820 A1 5/2005 Goble et al.
2005/0119525 A1 6/2005 Takemoto
2005/0119669 A1 6/2005 Demmy
2005/0124855 A1 6/2005 Jaffe et al.
2005/0125009 A1 6/2005 Perry et al.
2005/0131173 A1 6/2005 McDaniel et al.
2005/0131211 A1 6/2005 Bayley et al.
2005/0131390 A1* 6/2005 Heinrich et al. 606/1
2005/0131436 A1 6/2005 Johnston et al.
2005/0131437 A1 6/2005 Johnston et al.
2005/0131457 A1 6/2005 Douglas et al.
2005/0137454 A1 6/2005 Saadat et al.
2005/0137455 A1 6/2005 Ewers et al.
2005/0143759 A1 6/2005 Kelly
2005/0145675 A1 7/2005 Hartwick et al.
2005/0154258 A1 7/2005 Tartaglia et al.
2005/0165419 A1 7/2005 Sauer et al.
2005/0165435 A1 7/2005 Johnston et al.
2005/0169974 A1 8/2005 Tenerz et al.
2005/0171522 A1 8/2005 Christopherson
2005/0177181 A1 8/2005 Kagan et al.
2005/0182298 A1 8/2005 Ikeda et al.
2005/0184121 A1 8/2005 Heinrich
2005/0187545 A1 8/2005 Hooven et al.
2005/0187572 A1 8/2005 Johnston et al.
2005/0187576 A1 8/2005 Whitman et al.
2005/0189397 A1 9/2005 Jankowski
2005/0192609 A1 9/2005 Whitman et al.
2005/0192628 A1 9/2005 Viola
2005/0203550 A1 9/2005 Laufer et al.
2005/0216055 A1 9/2005 Scirica et al.
2005/0222554 A1* 10/2005 Wallace et al. 606/1
2005/0228224 A1 10/2005 Okada et al.
2005/0240222 A1 10/2005 Shipp
2005/0245965 A1 11/2005 Orban, III et al.
2005/0251128 A1 11/2005 Amoah
2005/0256452 A1 11/2005 DeMarchi et al.
2005/0256522 A1 11/2005 Francischelli et al.
2005/0261676 A1 11/2005 Hall et al.
2005/0261677 A1 11/2005 Hall et al.
2005/0263563 A1 12/2005 Racenet et al.
2005/0267455 A1 12/2005 Eggers et al.
2005/0274768 A1 12/2005 Cummins et al.
2006/0004407 A1 1/2006 Hiles et al.
2006/0008787 A1 1/2006 Hayman et al.
2006/0011699 A1 1/2006 Olson et al.
2006/0015009 A1 1/2006 Jaffe et al.
2006/0020247 A1 1/2006 Kagan et al.
2006/0020258 A1 1/2006 Strauss et al.
2006/0020336 A1 1/2006 Liddicoat
2006/0025811 A1 2/2006 Shelton, IV
2006/0025812 A1 2/2006 Shelton, IV
2006/0025813 A1 2/2006 Shelton et al.
2006/0041188 A1 2/2006 Dirusso et al.
2006/0047275 A1 3/2006 Goble
2006/0047303 A1 3/2006 Ortiz et al.
2006/0047307 A1 3/2006 Ortiz et al.
2006/0049229 A1 3/2006 Milliman et al.
2006/0052825 A1 3/2006 Ransick et al.
2006/0060630 A1 3/2006 Shelton, IV et al.
2006/0064086 A1 3/2006 Odom
2006/0079735 A1 4/2006 Martone et al.
2006/0085031 A1 4/2006 Bettuchi
2006/0085033 A1 4/2006 Criscuolo et al.
2006/0086032 A1 4/2006 Valencic et al.
2006/0100643 A1 5/2006 Laufer et al.
2006/0108393 A1 5/2006 Heinrich et al.
2006/0111711 A1 5/2006 Goble
2006/0111723 A1 5/2006 Chapolini et al.
2006/0122636 A1 6/2006 Bailly et al.
2006/0142772 A1 6/2006 Ralph et al.
2006/0149163 A1 7/2006 Hibner et al.
2006/0161185 A1 7/2006 Saadat et al.
2006/0173470 A1 8/2006 Oray et al.
2006/0180634 A1 8/2006 Shelton, IV et al.
2006/0183246 A1 8/2006 Wiesner et al.
2006/0200123 A1 9/2006 Ryan
2006/0212069 A1 9/2006 Shelton, IV
2006/0217729 A1 9/2006 Eskridge et al.
2006/0226196 A1 10/2006 Hueil et al.
2006/0235469 A1 10/2006 Viola
2006/0241655 A1 10/2006 Viola
2006/0241692 A1 10/2006 McGuckin, Jr. et al.
2006/0244460 A1 11/2006 Weaver
2006/0245971 A1 11/2006 Burns et al.
2006/0258904 A1 11/2006 Stefanchik et al.
2006/0259073 A1 11/2006 Miyamoto et al.
2006/0264927 A1 11/2006 Ryan
2006/0264929 A1 11/2006 Goble et al.
2006/0271042 A1 11/2006 Latterell et al.
2006/0271102 A1 11/2006 Bosshard et al.
2006/0278680 A1 12/2006 Viola et al.
2006/0278681 A1 12/2006 Viola et al.
2006/0289602 A1 12/2006 Wales et al.
2006/0291981 A1 12/2006 Viola et al.
2007/0023476 A1 2/2007 Whitman et al.
2007/0023477 A1 2/2007 Whitman et al.
2007/0027468 A1 2/2007 Wales et al.
2007/0027469 A1 2/2007 Smith et al.
2007/0027472 A1 2/2007 Hiles et al.
2007/0034668 A1 2/2007 Holsten et al.
2007/0055219 A1 3/2007 Whitman et al.
2007/0060879 A1* 3/2007 Weitzner et al. 604/95.04
2007/0070574 A1 3/2007 Nerheim et al.
2007/0073341 A1 3/2007 Smith

(56) **References Cited**

U.S. PATENT DOCUMENTS

2007/0078484 A1 4/2007 Talarico et al.
2007/0083193 A1 4/2007 Werneth et al.
2007/0084897 A1 4/2007 Shelton, IV et al.
2007/0102472 A1 5/2007 Shelton, IV
2007/0106113 A1 5/2007 Ravo
2007/0106317 A1 5/2007 Shelton, IV et al.
2007/0114261 A1 5/2007 Ortiz et al.
2007/0118175 A1 5/2007 Butler et al.
2007/0129605 A1 6/2007 Schaaf
2007/0135803 A1 6/2007 Belson
2007/0158358 A1 7/2007 Mason, II et al.
2007/0170225 A1 7/2007 Shelton, IV et al.
2007/0173806 A1 7/2007 Orszulak et al.
2007/0173813 A1 7/2007 Odom
2007/0175949 A1 8/2007 Shelton, IV et al.
2007/0175950 A1 8/2007 Shelton, IV et al.
2007/0175951 A1 8/2007 Shelton, IV et al.
2007/0175955 A1 8/2007 Shelton, IV et al.
2007/0181632 A1 8/2007 Milliman
2007/0194079 A1 8/2007 Hueil et al.
2007/0194081 A1 8/2007 Hueil et al.
2007/0194082 A1 8/2007 Morgan et al.
2007/0203510 A1 8/2007 Bettuchi
2007/0213750 A1 9/2007 Weadock
2007/0221700 A1 9/2007 Ortiz et al.
2007/0221701 A1 9/2007 Ortiz et al.
2007/0225562 A1 9/2007 Spivey et al.
2007/0239028 A1 10/2007 Houser et al.
2007/0246505 A1 10/2007 Pace-Floridia et al.
2007/0249999 A1 10/2007 Sklar et al.
2007/0260278 A1 11/2007 Wheeler et al.
2007/0270784 A1 11/2007 Smith et al.
2007/0270884 A1 11/2007 Smith et al.
2007/0288044 A1 12/2007 Jinno et al.
2007/0295780 A1 12/2007 Shelton et al.
2007/0299427 A1 12/2007 Yeung et al.
2008/0015598 A1 1/2008 Prommersberger
2008/0029570 A1 2/2008 Shelton et al.
2008/0029573 A1 2/2008 Shelton et al.
2008/0029574 A1 2/2008 Shelton et al.
2008/0029575 A1 2/2008 Shelton et al.
2008/0030170 A1 2/2008 Dacquay et al.
2008/0035701 A1 2/2008 Racenet et al.
2008/0041916 A1 2/2008 Milliman et al.
2008/0041917 A1 2/2008 Racenet et al.
2008/0078800 A1 4/2008 Hess et al.
2008/0078802 A1 4/2008 Hess et al.
2008/0078803 A1 4/2008 Shelton et al.
2008/0078804 A1 4/2008 Shelton et al.
2008/0078806 A1 4/2008 Omaits et al.
2008/0078807 A1 4/2008 Hess et al.
2008/0078808 A1 4/2008 Hess et al.
2008/0082114 A1 4/2008 McKenna et al.
2008/0082125 A1 4/2008 Murray et al.
2008/0082126 A1 4/2008 Murray et al.
2008/0083813 A1 4/2008 Zemlok et al.
2008/0114385 A1 5/2008 Byrum et al.
2008/0129253 A1 6/2008 Shiue et al.
2008/0140115 A1 6/2008 Stopek
2008/0167522 A1 7/2008 Giordano et al.
2008/0167672 A1 7/2008 Giordano et al.
2008/0169328 A1 7/2008 Shelton
2008/0169329 A1 7/2008 Shelton et al.
2008/0169330 A1 7/2008 Shelton et al.
2008/0169331 A1 7/2008 Shelton et al.
2008/0169332 A1 7/2008 Shelton et al.
2008/0169333 A1 7/2008 Shelton et al.
2008/0172087 A1 7/2008 Fuchs et al.
2008/0172088 A1 7/2008 Smith et al.
2008/0183193 A1 7/2008 Omori et al.
2008/0185419 A1 8/2008 Smith et al.
2008/0197167 A1 8/2008 Viola et al.
2008/0200835 A1 8/2008 Monson et al.
2008/0200949 A1 8/2008 Hiles et al.
2008/0228029 A1 9/2008 Mikkaichi et al.
2008/0245841 A1 10/2008 Smith et al.
2008/0251568 A1 10/2008 Zemlok et al.
2008/0251569 A1 10/2008 Smith et al.
2008/0255413 A1 10/2008 Zemlok et al.
2008/0262654 A1 10/2008 Omori et al.
2008/0283570 A1 11/2008 Boyden et al.
2008/0287944 A1 11/2008 Pearson et al.
2008/0290134 A1 11/2008 Bettuchi et al.
2008/0296346 A1 12/2008 Shelton, IV et al.
2008/0297287 A1 12/2008 Shachar et al.
2008/0308602 A1 12/2008 Timm et al.
2008/0308603 A1 12/2008 Shelton, IV et al.
2008/0308608 A1 12/2008 Prommersberger
2008/0314960 A1 12/2008 Marczyk et al.
2009/0001121 A1 1/2009 Hess et al.
2009/0001122 A1 1/2009 Prommersberger et al.
2009/0001124 A1 1/2009 Hess et al.
2009/0001130 A1 1/2009 Hess et al.
2009/0005807 A1 1/2009 Hess et al.
2009/0005808 A1 1/2009 Hess et al.
2009/0005809 A1 1/2009 Hess et al.
2009/0012534 A1 1/2009 Madhani et al.
2009/0012556 A1 1/2009 Boudreaux et al.
2009/0020958 A1 1/2009 Soul
2009/0045242 A1* 2/2009 Viola 227/177.1
2009/0048589 A1 2/2009 Takashino et al.
2009/0054908 A1 2/2009 Zand et al.
2009/0057369 A1 3/2009 Smith et al.
2009/0078736 A1 3/2009 Van Lue
2009/0088774 A1 4/2009 Swarup et al.
2009/0090763 A1 4/2009 Zemlok et al.
2009/0093728 A1 4/2009 Hyde et al.
2009/0108048 A1 4/2009 Zemlok et al.
2009/0112229 A1 4/2009 Omori et al.
2009/0114701 A1 5/2009 Zemlok et al.
2009/0143805 A1 6/2009 Palmer et al.
2009/0149871 A9 6/2009 Kagan et al.
2009/0157067 A1 6/2009 Kane et al.
2009/0206125 A1 8/2009 Huitema et al.
2009/0206126 A1 8/2009 Huitema et al.
2009/0206131 A1 8/2009 Weisenburgh, II et al.
2009/0206132 A1 8/2009 Hueil
2009/0206133 A1 8/2009 Morgan et al.
2009/0206137 A1 8/2009 Hall et al.
2009/0206139 A1 8/2009 Hall et al.
2009/0206141 A1 8/2009 Huitema et al.
2009/0206142 A1 8/2009 Huitema et al.
2009/0206143 A1 8/2009 Huitema et al.
2009/0209946 A1 8/2009 Swayze et al.
2009/0209979 A1 8/2009 Yates et al.
2009/0209990 A1 8/2009 Yates
2009/0213685 A1 8/2009 Mak et al.
2009/0218384 A1 9/2009 Aranyi
2009/0242610 A1 10/2009 Shelton, IV et al.
2009/0255974 A1 10/2009 Viola
2009/0255975 A1 10/2009 Zemlok et al.
2009/0255976 A1 10/2009 Marczyk et al.
2009/0255977 A1 10/2009 Zemlok
2009/0255978 A1 10/2009 Viola et al.
2009/0292283 A1 11/2009 Odom
2009/0308907 A1 12/2009 Nalagatla et al.
2010/0012704 A1 1/2010 Tarinelli Racenet et al.
2010/0023024 A1 1/2010 Zeiner et al.
2010/0049084 A1 2/2010 Nock et al.
2010/0057087 A1 3/2010 Cha
2010/0069942 A1 3/2010 Shelton, IV
2010/0072254 A1 3/2010 Aranyi et al.
2010/0076475 A1 3/2010 Yates et al.
2010/0087840 A1 4/2010 Ebersole et al.
2010/0089970 A1 4/2010 Smith et al.
2010/0089972 A1 4/2010 Marczyk
2010/0096431 A1 4/2010 Smith et al.
2010/0108740 A1 5/2010 Pastorelli et al.
2010/0108741 A1 5/2010 Hessler et al.
2010/0127042 A1 5/2010 Shelton, IV
2010/0133317 A1 6/2010 Shelton, IV et al.
2010/0133318 A1 6/2010 Boudreaux
2010/0145146 A1 6/2010 Melder
2010/0147922 A1 6/2010 Olson

(56) **References Cited**

U.S. PATENT DOCUMENTS

2010/0163598 A1 7/2010 Belzer
2010/0179382 A1 7/2010 Shelton, IV et al.
2010/0186219 A1 7/2010 Smith
2010/0193566 A1 8/2010 Scheib et al.
2010/0193567 A1 8/2010 Scheib et al.
2010/0193568 A1 8/2010 Scheib et al.
2010/0193569 A1 8/2010 Yates et al.
2010/0198220 A1 8/2010 Boudreaux et al.
2010/0200637 A1 8/2010 Beetel
2010/0213241 A1 8/2010 Bedi et al.
2010/0222901 A1 9/2010 Swayze et al.
2010/0224669 A1 9/2010 Shelton, IV et al.
2010/0230465 A1 9/2010 Smith et al.
2010/0243707 A1 9/2010 Olson et al.
2010/0243708 A1 9/2010 Aranyi et al.
2010/0243709 A1 9/2010 Hess et al.
2010/0258611 A1 10/2010 Smith et al.
2010/0264193 A1 10/2010 Huang et al.
2010/0264194 A1 10/2010 Huang et al.
2010/0268030 A1 10/2010 Viola et al.
2010/0276471 A1 11/2010 Whitman
2010/0294827 A1 11/2010 Boyden et al.
2010/0294829 A1 11/2010 Giordano et al.
2010/0301095 A1 12/2010 Shelton, IV et al.
2010/0305552 A1 12/2010 Shelton, IV et al.
2010/0308100 A1 12/2010 Boudreaux
2010/0312261 A1 12/2010 Suzuki et al.
2010/0331880 A1 12/2010 Stopek
2011/0003528 A1 1/2011 Lam
2011/0006099 A1 1/2011 Hall et al.
2011/0006101 A1 1/2011 Hall et al.
2011/0006103 A1 1/2011 Laurent et al.
2011/0011914 A1 1/2011 Baxter, III et al.
2011/0011915 A1 1/2011 Shelton, IV
2011/0011916 A1 1/2011 Levine
2011/0017801 A1 1/2011 Zemlok et al.
2011/0022032 A1 1/2011 Zemlok et al.
2011/0024477 A1 2/2011 Hall et al.
2011/0024478 A1 2/2011 Shelton, IV
2011/0024479 A1 2/2011 Swensgard et al.
2011/0036887 A1 2/2011 Zemlok et al.
2011/0036890 A1 2/2011 Ma
2011/0042441 A1 2/2011 Shelton, IV et al.
2011/0060363 A1 3/2011 Hess et al.
2011/0068145 A1 3/2011 Bedi et al.
2011/0068148 A1 3/2011 Hall et al.
2011/0084112 A1 4/2011 Kostrzewski
2011/0084115 A1 4/2011 Bedi et al.
2011/0087276 A1 4/2011 Bedi et al.
2011/0087279 A1 4/2011 Shah et al.
2011/0095068 A1 4/2011 Patel
2011/0101065 A1 5/2011 Milliman
2011/0114697 A1 5/2011 Baxter, III et al.
2011/0114698 A1 5/2011 Baxter, III et al.
2011/0114699 A1 5/2011 Baxter, III et al.
2011/0114700 A1 5/2011 Baxter, III et al.
2011/0118754 A1 5/2011 Dachs, II et al.
2011/0118761 A1 5/2011 Baxter, III et al.
2011/0125176 A1 5/2011 Yates et al.
2011/0125177 A1 5/2011 Yates et al.
2011/0132963 A1 6/2011 Giordano et al.
2011/0132964 A1 6/2011 Weisenburgh, II et al.
2011/0132965 A1 6/2011 Moore et al.
2011/0144430 A1 6/2011 Spivey et al.
2011/0147433 A1 6/2011 Shelton, IV et al.
2011/0147434 A1 6/2011 Hueil et al.
2011/0155780 A1 6/2011 Boudreaux
2011/0155781 A1 6/2011 Swensgard et al.
2011/0155785 A1 6/2011 Laurent et al.
2011/0155787 A1 6/2011 Baxter, III et al.
2011/0163147 A1 7/2011 Laurent et al.
2011/0174861 A1 7/2011 Shelton, IV et al.
2011/0174863 A1 7/2011 Shelton, IV et al.
2011/0178536 A1 7/2011 Kostrzewski
2011/0192882 A1 8/2011 Hess et al.
2011/0210156 A1 9/2011 Smith et al.
2011/0226837 A1 9/2011 Baxter, III et al.
2011/0233258 A1 9/2011 Boudreaux
2011/0275901 A1 11/2011 Shelton, IV
2011/0276083 A1 11/2011 Shelton, IV et al.
2011/0278343 A1 11/2011 Knodel et al.
2011/0288573 A1 11/2011 Yates et al.
2011/0290851 A1 12/2011 Shelton, IV
2011/0290853 A1 12/2011 Shelton, IV et al.
2011/0290854 A1 12/2011 Timm et al.
2011/0290855 A1 12/2011 Moore et al.
2011/0290856 A1 12/2011 Shelton, IV et al.
2011/0290857 A1 12/2011 Shelton, IV et al.
2011/0295242 A1 12/2011 Spivey et al.
2011/0295269 A1 12/2011 Swensgard et al.
2011/0295270 A1 12/2011 Giordano et al.
2011/0295295 A1 12/2011 Shelton, IV et al.
2012/0022523 A1 1/2012 Smith et al.
2012/0024934 A1 2/2012 Shelton, IV et al.
2012/0024935 A1 2/2012 Shelton, IV et al.
2012/0024936 A1 2/2012 Baxter, III et al.
2012/0029272 A1 2/2012 Shelton, IV et al.
2012/0029544 A1 2/2012 Shelton, IV et al.
2012/0029547 A1 2/2012 Shelton, IV et al.
2012/0046692 A1 2/2012 Smith et al.
2012/0061448 A1 3/2012 Zingman
2012/0071711 A1 3/2012 Shelton, IV et al.
2012/0071866 A1 3/2012 Kerr et al.
2012/0074196 A1 3/2012 Shelton, IV et al.
2012/0074198 A1 3/2012 Huitema et al.
2012/0074200 A1 3/2012 Schmid et al.
2012/0074201 A1 3/2012 Baxter, III et al.
2012/0080332 A1 4/2012 Shelton, IV et al.
2012/0080333 A1 4/2012 Woodard, Jr. et al.
2012/0080334 A1 4/2012 Shelton, IV et al.
2012/0080335 A1 4/2012 Shelton, IV et al.
2012/0080336 A1 4/2012 Shelton, IV et al.
2012/0080337 A1 4/2012 Shelton, IV et al.
2012/0080338 A1 4/2012 Shelton, IV et al.
2012/0080339 A1 4/2012 Shelton, IV et al.
2012/0080340 A1 4/2012 Shelton, IV et al.
2012/0080344 A1 4/2012 Shelton, IV
2012/0080345 A1 4/2012 Morgan et al.
2012/0080475 A1 4/2012 Smith et al.
2012/0080477 A1 4/2012 Leimbach et al.
2012/0080478 A1 4/2012 Morgan et al.
2012/0080479 A1 4/2012 Shelton, IV
2012/0080480 A1 4/2012 Woodard, Jr. et al.
2012/0080481 A1 4/2012 Widenhouse et al.
2012/0080482 A1 4/2012 Schall et al.
2012/0080483 A1 4/2012 Riestenberg et al.
2012/0080484 A1 4/2012 Morgan et al.
2012/0080485 A1 4/2012 Woodard, Jr. et al.
2012/0080486 A1 4/2012 Woodard, Jr. et al.
2012/0080487 A1 4/2012 Woodard, Jr. et al.
2012/0080488 A1 4/2012 Shelton, IV et al.
2012/0080489 A1 4/2012 Shelton, IV et al.
2012/0080490 A1 4/2012 Shelton, IV et al.
2012/0080491 A1 4/2012 Shelton, IV et al.
2012/0080493 A1 4/2012 Shelton, IV et al.
2012/0080496 A1 4/2012 Schall et al.
2012/0080498 A1 4/2012 Shelton, IV et al.
2012/0080499 A1 4/2012 Schall et al.
2012/0080500 A1 4/2012 Morgan et al.
2012/0080501 A1 4/2012 Morgan et al.
2012/0080502 A1 4/2012 Morgan et al.
2012/0080503 A1 4/2012 Woodard, Jr. et al.
2012/0083833 A1 4/2012 Shelton, IV et al.
2012/0083834 A1 4/2012 Shelton, IV et al.
2012/0083835 A1 4/2012 Shelton, IV et al.
2012/0083836 A1 4/2012 Shelton, IV et al.
2012/0138658 A1 6/2012 Ullrich et al.
2012/0138660 A1 6/2012 Shelton, IV
2012/0150192 A1 6/2012 Dachs, II et al.
2012/0160721 A1 6/2012 Shelton, IV et al.
2012/0175399 A1 7/2012 Shelton et al.
2012/0187179 A1 7/2012 Gleiman
2012/0199630 A1 8/2012 Shelton, IV et al.
2012/0199631 A1 8/2012 Shelton, IV et al.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2012/0199632	A1	8/2012	Spivey et al.
2012/0199633	A1	8/2012	Shelton, IV et al.
2012/0203247	A1	8/2012	Shelton, IV et al.
2012/0205421	A1	8/2012	Shelton, IV
2012/0211546	A1	8/2012	Shelton, IV
2012/0234890	A1	9/2012	Aronhalt et al.
2012/0234891	A1	9/2012	Aronhalt et al.
2012/0234892	A1	9/2012	Aronhalt et al.
2012/0234893	A1	9/2012	Schuckmann et al.
2012/0234895	A1	9/2012	O'Connor et al.
2012/0234896	A1	9/2012	Ellerhorst et al.
2012/0234897	A1	9/2012	Shelton, IV et al.
2012/0234898	A1	9/2012	Shelton, IV et al.
2012/0234899	A1	9/2012	Scheib et al.
2012/0234900	A1	9/2012	Swayze
2012/0238823	A1	9/2012	Hagerty et al.
2012/0238824	A1	9/2012	Widenhouse et al.
2012/0238826	A1	9/2012	Yoo et al.
2012/0238829	A1	9/2012	Shelton, IV et al.
2012/0239009	A1	9/2012	Mollere et al.
2012/0239010	A1	9/2012	Shelton, IV et al.
2012/0239012	A1	9/2012	Laurent et al.
2012/0239075	A1	9/2012	Widenhouse et al.
2012/0239082	A1	9/2012	Shelton, IV et al.
2012/0241491	A1	9/2012	Aldridge et al.
2012/0241492	A1	9/2012	Shelton, IV et al.
2012/0241493	A1	9/2012	Baxter, III et al.
2012/0241496	A1	9/2012	Mandakolathur Vasudevan et al.
2012/0241497	A1	9/2012	Mandakolathur Vasudevan et al.
2012/0241498	A1	9/2012	Gonzalez et al.
2012/0241499	A1	9/2012	Baxter, III et al.
2012/0241500	A1	9/2012	Timmer et al.
2012/0241501	A1	9/2012	Swayze et al.
2012/0241502	A1	9/2012	Aldridge et al.
2012/0241503	A1	9/2012	Baxter, III et al.
2012/0241505	A1	9/2012	Alexander, III et al.
2012/0248169	A1	10/2012	Widenhouse et al.
2012/0253298	A1	10/2012	Henderson et al.
2012/0265230	A1	10/2012	Yates et al.
2012/0273551	A1	11/2012	Shelton, IV et al.
2012/0283707	A1	11/2012	Giordano et al.
2012/0283748	A1	11/2012	Ortiz et al.
2012/0286019	A1	11/2012	Hueil et al.
2012/0292367	A1	11/2012	Morgan et al.
2012/0292370	A1	11/2012	Hess et al.
2012/0298719	A1	11/2012	Shelton, IV et al.
2012/0325892	A1	12/2012	Kostrzewski
2013/0012931	A1	1/2013	Spivey et al.
2013/0012957	A1	1/2013	Shelton, IV et al.
2013/0018361	A1	1/2013	Bryant
2013/0020376	A1	1/2013	Shelton, IV et al.
2013/0023861	A1	1/2013	Shelton, IV et al.
2013/0026208	A1	1/2013	Shelton, IV et al.
2013/0026210	A1	1/2013	Shelton, IV et al.
2013/0037596	A1	2/2013	Bear et al.
2013/0041371	A1	2/2013	Yates et al.
2013/0048697	A1	2/2013	Shelton, IV et al.
2013/0056518	A1	3/2013	Swensgard
2013/0056520	A1	3/2013	Swensgard
2013/0056521	A1	3/2013	Swensgard
2013/0056522	A1	3/2013	Swensgard
2013/0075443	A1	3/2013	Giordano et al.
2013/0075448	A1	3/2013	Schmid et al.
2013/0075449	A1	3/2013	Schmid et al.
2013/0075450	A1	3/2013	Schmid et al.
2013/0105551	A1	5/2013	Zingman
2013/0126581	A1	5/2013	Yates et al.
2013/0126582	A1	5/2013	Shelton, IV et al.
2013/0126583	A1	5/2013	Hueil et al.
2013/0146641	A1	6/2013	Shelton, IV et al.
2013/0146642	A1	6/2013	Shelton, IV et al.
2013/0146643	A1	6/2013	Schmid et al.
2013/0193189	A1	8/2013	Yates

FOREIGN PATENT DOCUMENTS

CA	2514274	A1	1/2006
CN	2488482	Y	5/2002
CN	1634601	A	7/2005
CN	1868411	A	11/2006
CN	1915180	A	2/2007
CN	101011286	A	8/2007
CN	101095621	A	1/2008
DE	273689	C	5/1914
DE	1775926	A	1/1972
DE	3036217	A1	4/1982
DE	3210466	A1	9/1983
DE	3709067	A1	9/1988
DE	9412228	U	9/1994
DE	19509116	A1	9/1996
DE	19851291	A1	1/2000
DE	19924311	A1	11/2000
DE	69328576	T2	1/2001
DE	10052679	A1	5/2001
DE	20112837	U1	10/2001
DE	20121753	U1	4/2003
DE	10314072	A1	10/2004
DE	202007003114	U1	6/2007
EP	0122046	A1	10/1984
EP	0070230	B1	10/1985
EP	0156774	A2	10/1985
EP	0387980	81	10/1985
EP	0033548	B1	5/1986
EP	0129442	B1	11/1987
EP	0276104	A2	7/1988
EP	0178940	B1	1/1991
EP	0178941	B1	1/1991
EP	0248844	B1	1/1993
EP	0545029	A1	6/1993
EP	0277959	B1	10/1993
EP	0233940	B1	11/1993
EP	0261230	B1	11/1993
EP	0639349	A2	2/1994
EP	0324636	B1	3/1994
EP	0593920	A1	4/1994
EP	0594148	A1	4/1994
EP	0427949	B1	6/1994
EP	0523174	B1	6/1994
EP	0600182	A2	6/1994
EP	0310431	B1	11/1994
EP	0375302	B1	11/1994
EP	0376562	B1	11/1994
EP	0630612	A1	12/1994
EP	0634144	A1	1/1995
EP	0646356	A2	4/1995
EP	0646357	A1	4/1995
EP	0653189	A2	5/1995
EP	0669104	A1	8/1995
EP	0511470	B1	10/1995
EP	0674876	A2	10/1995
EP	0679367	A2	11/1995
EP	0392547	B1	12/1995
EP	0685204	A1	12/1995
EP	0364216	B1	1/1996
EP	0699418	A1	3/1996
EP	0702937	A1	3/1996
EP	0705571	A1	4/1996
EP	0711611	A2	5/1996
EP	0484677	B2	6/1996
EP	0541987	B1	7/1996
EP	0667119	B1	7/1996
EP	0708618	B1	3/1997
EP	0770355	A1	5/1997
EP	0503662	B1	6/1997
EP	0447121	B1	7/1997
EP	0625077	B1	7/1997
EP	0633749	B1	8/1997
EP	0710090	B1	8/1997
EP	0578425	B1	9/1997
EP	0625335	B1	11/1997
EP	0552423	B1	1/1998
EP	0592244	B1	1/1998
EP	0648476	B1	1/1998

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

EP	0649290	B1	3/1998
EP	0598618	B1	9/1998
EP	0676173	B1	9/1998
EP	0678007	B1	9/1998
EP	0603472	B1	11/1998
EP	0605351	B1	11/1998
EP	0878169	A1	11/1998
EP	0879742	A1	11/1998
EP	0695144	B1	12/1998
EP	0722296	B1	12/1998
EP	0760230	B1	2/1999
EP	0623316	B1	3/1999
EP	0650701	B1	3/1999
EP	0537572	B1	6/1999
EP	0923907	A1	6/1999
EP	0843906	B1	3/2000
EP	0552050	B1	5/2000
EP	0833592	B1	5/2000
EP	0830094	B1	9/2000
EP	1034747	A1	9/2000
EP	1034748	A1	9/2000
EP	0694290	B1	11/2000
EP	1050278	A1	11/2000
EP	1053719	A1	11/2000
EP	1053720	A1	11/2000
EP	1055399	A1	11/2000
EP	1055400	A1	11/2000
EP	1080694	A1	3/2001
EP	1090592	A1	4/2001
EP	1095627	A1	5/2001
EP	1256318	B1	5/2001
EP	0806914	B1	9/2001
EP	0768840	B1	12/2001
EP	0908152	B1	1/2002
EP	0872213	B1	5/2002
EP	0862386	B1	6/2002
EP	0949886	B1	9/2002
EP	1238634	A2	9/2002
EP	0858295	B1	12/2002
EP	0656188	B1	1/2003
EP	0717960	B1	2/2003
EP	1284120	A1	2/2003
EP	1287788	A1	3/2003
EP	0717966	B1	4/2003
EP	0869742	B1	5/2003
EP	0829235	B1	6/2003
EP	0887046	B1	7/2003
EP	0852480	B1	8/2003
EP	0891154	B1	9/2003
EP	0813843	B1	10/2003
EP	0873089	B1	10/2003
EP	0856326	B1	11/2003
EP	1374788	A1	1/2004
EP	0741996	B1	2/2004
EP	0814712	B1	2/2004
EP	1402837	A1	3/2004
EP	0705570	B1	4/2004
EP	0959784	B1	4/2004
EP	1407719	A2	4/2004
EP	1086713	B1	5/2004
EP	0996378	B1	6/2004
EP	1426012	A1	6/2004
EP	0833593	B2	7/2004
EP	1442694	A1	8/2004
EP	0888749	B1	9/2004
EP	0959786	B1	9/2004
EP	1459695	A1	9/2004
EP	1254636	B1	10/2004
EP	1473819	A1	11/2004
EP	1477119	A1	11/2004
EP	1479345	A1	11/2004
EP	1479347	A1	11/2004
EP	1479348	A1	11/2004
EP	0754437	B2	12/2004
EP	1025807	B1	12/2004
EP	1001710	B1	1/2005
EP	1520521	A1	4/2005
EP	1520522	A1	4/2005
EP	1520523	A1	4/2005
EP	1520525	A1	4/2005
EP	1522264	A1	4/2005
EP	1523942	A2	4/2005
EP	1550408	A1	7/2005
EP	1557129	A1	7/2005
EP	1064883	B1	8/2005
EP	1067876	B1	8/2005
EP	0870473	B1	9/2005
EP	1157666	B1	9/2005
EP	0880338	B1	10/2005
EP	1158917	B1	11/2005
EP	1344498	B1	11/2005
EP	1330989	B1	12/2005
EP	0771176	B2	1/2006
EP	1621138	A2	2/2006
EP	1621139	A2	2/2006
EP	1621141	A2	2/2006
EP	1621145	A2	2/2006
EP	1621151	A2	2/2006
EP	1034746	B1	3/2006
EP	1632191	A2	3/2006
EP	1065981	B1	5/2006
EP	1082944	B1	5/2006
EP	1652481	A2	5/2006
EP	1382303	B1	6/2006
EP	1253866	B1	7/2006
EP	1032318	B1	8/2006
EP	1045672	B1	8/2006
EP	1617768	B1	8/2006
EP	1693015	A2	8/2006
EP	1400214	B1	9/2006
EP	1702567	A2	9/2006
EP	1129665	B1	11/2006
EP	1400206	B1	11/2006
EP	1721568	A1	11/2006
EP	1256317	B1	12/2006
EP	1285633	B1	12/2006
EP	1728473	A1	12/2006
EP	1728475	A2	12/2006
EP	1479346	B1	1/2007
EP	1484024	B1	1/2007
EP	1754445	A2	2/2007
EP	1759812	A1	3/2007
EP	1767163	A1	3/2007
EP	1769756	A1	4/2007
EP	1769758	A1	4/2007
EP	1581128	B1	5/2007
EP	1780825	A1	5/2007
EP	1785097	A2	5/2007
EP	1790293	A2	5/2007
EP	1800610	A1	6/2007
EP	1300117	B1	8/2007
EP	1813199	A1	8/2007
EP	1813201	A1	8/2007
EP	1813202	A1	8/2007
EP	1813203	A2	8/2007
EP	1813207	A1	8/2007
EP	1813209	A1	8/2007
EP	1487359	B1	10/2007
EP	1599146	B1	10/2007
EP	1839596	A1	10/2007
EP	2110083	A2	10/2007
EP	1857057	A2	11/2007
EP	1402821	B1	12/2007
EP	1872727	A1	1/2008
EP	1897502	A1	3/2008
EP	1908417	A2	4/2008
EP	1330201	B1	6/2008
EP	1702568	B1	7/2008
EP	1943955	A2	7/2008
EP	1943957	A2	7/2008
EP	1943964	A1	7/2008
EP	1943976	A2	7/2008
EP	1593337	B1	8/2008
EP	1970014	A1	9/2008

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

EP	1980213	A2	10/2008
EP	1759645	B1	11/2008
EP	1990014	A2	11/2008
EP	1693008	B1	12/2008
EP	1759640	B1	12/2008
EP	2000102	A2	12/2008
EP	2005894	A2	12/2008
EP	2008595	A2	12/2008
EP	1736104	B1	3/2009
EP	1749486	B1	3/2009
EP	2039316	A2	3/2009
EP	1721576	B1	4/2009
EP	1733686	B1	4/2009
EP	2044890	A1	4/2009
EP	1550409	A1	6/2009
EP	1550413	B1	6/2009
EP	1745748	B1	8/2009
EP	2090237	A1	8/2009
EP	2090241	A1	8/2009
EP	2090244	A2	8/2009
EP	2090245	A1	8/2009
EP	2090256	A2	8/2009
EP	2095777	A2	9/2009
EP	2098170	A2	9/2009
EP	2110082	A1	10/2009
EP	2111803	A2	10/2009
EP	1813208	B1	11/2009
EP	1908426	B1	11/2009
EP	2116195	A1	11/2009
EP	1607050	B1	12/2009
EP	1815804	B1	12/2009
EP	1566150	B1	4/2010
EP	1813206	B1	4/2010
EP	1769754	B1	6/2010
EP	1854416	B1	6/2010
EP	1535565	B1	10/2010
EP	1702570	B1	10/2010
EP	1785098	B1	10/2010
EP	2005896	B1	10/2010
EP	2030578	B1	11/2010
EP	1627605	B1	12/2010
EP	2286738	A2	2/2011
EP	1690502	B1	3/2011
EP	1769755	B1	4/2011
EP	1813205	B1	6/2011
EP	2090243	B1	6/2011
EP	2329773	A1	6/2011
EP	1908414	B1	11/2011
EP	1785102	B1	1/2012
EP	2090253	B1	3/2012
EP	2005895	B1	8/2012
EP	2090248	B1	8/2012
EP	1884206	B1	3/2013
FR	999646	A	2/1952
FR	1112936	A	3/1956
FR	2598905	A1	11/1987
FR	2765794	A	1/1999
GB	939929	A	10/1963
GB	1210522	A	10/1970
GB	1217159	A	12/1970
GB	1339394	A	12/1973
GB	2109241	A	6/1983
GB	2272159	A	5/1994
GB	2284242	A	5/1995
GB	2336214	A	10/1999
GB	2425903	A	11/2006
JP	58500053	A	1/1983
JP	61-98249	A	5/1986
JP	S 61502036	A	9/1986
JP	63-203149		8/1988
JP	3-12126	A	1/1991
JP	5-212039	A	8/1993
JP	6007357	A	1/1994
JP	H 6-30945	A	2/1994
JP	H 6-121798	A	5/1994
JP	7051273	A	2/1995
JP	7-124166	A	5/1995
JP	7-255735	A	10/1995
JP	8-33642	A	2/1996
JP	8033641	A	2/1996
JP	8-164141	A	6/1996
JP	8229050	A	9/1996
JP	2000-14632		1/2000
JP	2000033071	A	2/2000
JP	2000171730	A	6/2000
JP	2000287987	A	10/2000
JP	2000325303	A	11/2000
JP	2001-514541	A	9/2001
JP	2001286477	A	10/2001
JP	2002143078	A	5/2002
JP	2002369820	A	12/2002
JP	2003-500153	A	1/2003
JP	2003-521301	A	7/2003
JP	2004-329624	A	11/2004
JP	2004-344663		12/2004
JP	2005-028147	A	2/2005
JP	2005-028149	A	2/2005
JP	2005-505309	A	2/2005
JP	2005505322	T	2/2005
JP	2005103293	A	4/2005
JP	2005131163	A	5/2005
JP	2005131164	A	5/2005
JP	2005131173	A	5/2005
JP	2005131211	A	5/2005
JP	2005131212	A	5/2005
JP	2005137423	A	6/2005
JP	2005152416	A	6/2005
JP	2005-523105	A	8/2005
JP	2005524474	A	8/2005
JP	2006-034975	A	2/2006
JP	2006-034980	A	2/2006
JP	2006-218297	A	8/2006
JP	2006-281405	A	10/2006
JP	2007-098130	A	4/2007
JP	2007-117725	A	5/2007
JP	2007-203057	A	8/2007
JP	2007-229448	A	9/2007
JP	2008-283459	A	11/2008
RU	2008830	C1	3/1994
RU	2141279	C1	11/1999
RU	2187249	C2	8/2002
RU	2225170	C2	3/2004
SU	189517	A	1/1967
SU	328636	A	9/1972
SU	886900	A1	12/1981
SU	1009439	A	4/1983
SU	1333319	A2	8/1987
SU	1377053	A1	2/1988
SU	1561964	A1	5/1990
SU	1722476	A1	3/1992
WO	WO 82/02824	A1	9/1982
WO	WO 91/15157	A1	10/1991
WO	WO 92/20295	A1	11/1992
WO	WO 92/21300	A1	12/1992
WO	WO 93/08755	A1	5/1993
WO	WO 93/13718	A1	7/1993
WO	WO 93/14690	A1	8/1993
WO	WO 93/15648	A1	8/1993
WO	WO 93/15850	A1	8/1993
WO	WO 93/19681	A1	10/1993
WO	WO 94/00060	A1	1/1994
WO	WO 94/11057	A1	5/1994
WO	WO 94/12108	A1	6/1994
WO	WO 94/18893	A1	9/1994
WO	WO 94/22378	A1	10/1994
WO	WO 94/23659	A1	10/1994
WO	WO 95/02369	A1	1/1995
WO	WO 95/03743	A1	2/1995
WO	WO 95/06817	A1	3/1995
WO	WO 95/09576	A1	4/1995
WO	WO 95/09577	A1	4/1995
WO	WO 95/14436	A1	6/1995
WO	WO 95/17855	A1	7/1995
WO	WO 95/18383	A1	7/1995

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	WO 95/18572 A1	7/1995
WO	WO 95/19739 A1	7/1995
WO	WO 95/20360 A1	8/1995
WO	WO 95/23557 A1	9/1995
WO	WO 95/24865 A1	9/1995
WO	WO 95/25471 A3	9/1995
WO	WO 95/26562 A1	10/1995
WO	WO 95/29639 A1	11/1995
WO	WO 96/04858 A1	2/1996
WO	WO 96/18344 A2	6/1996
WO	WO 96/19151 A1	6/1996
WO	WO 96/19152 A1	6/1996
WO	WO 96/20652 A1	7/1996
WO	WO 96/21119 A1	7/1996
WO	WO 96/22055 A1	7/1996
WO	WO 96/23448 A1	8/1996
WO	WO 96/24301 A1	8/1996
WO	WO 96/27337 A1	9/1996
WO	WO 96/31155 A1	10/1996
WO	WO 96/35464 A1	11/1996
WO	WO 96/39085 A1	12/1996
WO	WO 96/39086 A1	12/1996
WO	WO 96/39087 A1	12/1996
WO	WO 96/39088 A1	12/1996
WO	WO 96/39089 A1	12/1996
WO	WO 97/00646 A1	1/1997
WO	WO 97/00647 A1	1/1997
WO	WO 97/06582 A1	2/1997
WO	WO 97/10763 A1	3/1997
WO	WO 97/10764 A1	3/1997
WO	WO 97/11648 A2	4/1997
WO	WO 97/11649 A1	4/1997
WO	WO 97/15237 A1	5/1997
WO	WO 97/24073 A1	7/1997
WO	WO 97/24993 A1	7/1997
WO	WO 97/30644 A1	8/1997
WO	WO 97/34533 A1	9/1997
WO	WO 97/37598 A1	10/1997
WO	WO 97/39688 A2	10/1997
WO	WO 98/17180 A1	4/1998
WO	WO 98/27880 A1	7/1998
WO	WO 98/30153 A1	7/1998
WO	WO 98/47436 A1	10/1998
WO	WO 99/03407 A1	1/1999
WO	WO 99/03408 A1	1/1999
WO	WO 99/03409 A1	1/1999
WO	WO 99/12483 A1	3/1999
WO	WO 99/12487 A1	3/1999
WO	WO 99/12488 A1	3/1999
WO	WO 99/15086 A1	4/1999
WO	WO 99/15091 A1	4/1999
WO	WO 99/23933 A2	5/1999
WO	WO 99/23959 A1	5/1999
WO	WO 99/25261 A1	5/1999
WO	WO 99/29244 A1	6/1999
WO	WO 99/34744 A1	7/1999
WO	WO 99/45849 A1	9/1999
WO	WO 99/48430 A1	9/1999
WO	WO 99/51158 A1	10/1999
WO	WO 00/24322 A1	5/2000
WO	WO 00/24330 A1	5/2000
WO	WO 00/41638 A1	7/2000
WO	WO 00/48506 A1	8/2000
WO	WO 00/53112 A2	9/2000
WO	WO 00/54653 A1	9/2000
WO	WO 00/057796 A1	10/2000
WO	WO 00/64365 A1	11/2000
WO	WO 00/72762 A1	12/2000
WO	WO 00/72765 A1	12/2000
WO	WO 01/03587 A1	1/2001
WO	WO 01/05702 A1	1/2001
WO	WO 01/10482 A1	2/2001
WO	WO 01/35845 A1	5/2001
WO	WO 01/54594 A1	8/2001
WO	WO 01/58371 A1	8/2001
WO	WO 01/62158 A2	8/2001
WO	WO 01/62161 A1	8/2001
WO	WO 01/62162 A1	8/2001
WO	WO 01/62164 A2	8/2001
WO	WO 01/62169 A2	8/2001
WO	WO 01/78605 A2	10/2001
WO	WO 01/91646 A1	12/2001
WO	WO 02/07608 A2	1/2002
WO	WO 02/07618 A1	1/2002
WO	WO 02/17799 A1	3/2002
WO	WO 02/19920 A1	3/2002
WO	WO 02/19932 A1	3/2002
WO	WO 02/30297 A2	4/2002
WO	WO 02/32322 A2	4/2002
WO	WO 02/36028 A1	5/2002
WO	WO 02/43571 A2	6/2002
WO	WO 02/058568 A1	8/2002
WO	WO 02/060328 A1	8/2002
WO	WO 02/067785 A2	9/2002
WO	WO 02/098302 A1	12/2002
WO	WO 03/000138 A2	1/2003
WO	WO 03/001329 A2	1/2003
WO	WO 03/013363 A1	2/2003
WO	WO 03/015604 A2	2/2003
WO	WO 03/020106 A2	3/2003
WO	WO 03/020139 A2	3/2003
WO	WO 03/024339 A1	3/2003
WO	WO 03/079909 A3	3/2003
WO	WO 03/030743 A2	4/2003
WO	WO 03/037193 A1	5/2003
WO	WO 03/047436 A3	6/2003
WO	WO 03/055402 A1	7/2003
WO	WO 03/057048 A1	7/2003
WO	WO 03/057058 A1	7/2003
WO	WO 03/063694 A1	8/2003
WO	WO 03/077769 A1	9/2003
WO	WO 03/079911 A1	10/2003
WO	WO 03/082126 A1	10/2003
WO	WO 03/086206 A1	10/2003
WO	WO 03/088845 A2	10/2003
WO	WO 03/090630 A2	11/2003
WO	WO 03/094743 A1	11/2003
WO	WO 03/094745 A1	11/2003
WO	WO 03/094746 A1	11/2003
WO	WO 03/094747 A1	11/2003
WO	WO 03/101313 A1	12/2003
WO	WO 03/105698 A2	12/2003
WO	WO 03/105702 A2	12/2003
WO	WO 2004/006980 A2	1/2004
WO	WO 2004/011037 A2	2/2004
WO	WO 2004/019769 A1	3/2004
WO	WO 2004/021868 A2	3/2004
WO	WO 2004/028585 A2	4/2004
WO	WO 2004/032754 A2	4/2004
WO	WO 2004/032760 A2	4/2004
WO	WO 2004/032762 A1	4/2004
WO	WO 2004/032763 A2	4/2004
WO	WO 2004/034875 A2	4/2004
WO	WO 2004/047626 A1	6/2004
WO	WO 2004/047653 A2	6/2004
WO	WO 2004/049956 A2	6/2004
WO	WO 2004/052426 A2	6/2004
WO	WO 2004/056276 A1	7/2004
WO	WO 2004/056277 A1	7/2004
WO	WO 2004/062516 A1	7/2004
WO	WO 2004/078050 A2	9/2004
WO	WO 2004/078051 A2	9/2004
WO	WO 2004/086987 A1	10/2004
WO	WO 2004/096015 A2	11/2004
WO	WO 2004/096057 A2	11/2004
WO	WO 2004/103157 A2	12/2004
WO	WO 2004/105593 A1	12/2004
WO	WO 2004/105621 A1	12/2004
WO	WO 2004/112618 A2	12/2004
WO	WO 2004/112652 A2	12/2004
WO	WO 2005/027983 A2	3/2005
WO	WO 2005/037329 A2	4/2005
WO	WO 2005/044078 A2	5/2005
WO	WO 2005/055846 A1	6/2005

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	WO 2005/072634	A2	8/2005
WO	WO 2005/078892	A1	8/2005
WO	WO 2005/079675	A2	9/2005
WO	WO 2005/096954	A2	10/2005
WO	WO 2005/112806	A2	12/2005
WO	WO 2005/112808	A1	12/2005
WO	WO 2005/115251	A2	12/2005
WO	WO 2005/115253	A2	12/2005
WO	WO 2005/117735	A1	12/2005
WO	WO 2005/122936	A1	12/2005
WO	WO 2006/023486	A1	3/2006
WO	WO 2006/027014	A1	3/2006
WO	WO 2006/044490	A2	4/2006
WO	WO 2006/044581	A2	4/2006
WO	WO 2006/044810	A2	4/2006
WO	WO 2006/051252	A1	5/2006
WO	WO 2006/059067	A1	6/2006
WO	WO 2006/083748	A1	8/2006
WO	WO 2006/092563	A1	9/2006
WO	WO 2006/092565	A1	9/2006
WO	WO 2006/115958	A1	11/2006
WO	WO 2006/125940	A1	11/2006
WO	WO 2006/132992	A1	12/2006
WO	WO 2007/002180	A2	1/2007
WO	WO 2007/016290	A2	2/2007
WO	WO 2007/018898	A2	2/2007
WO	WO 2007/098220	A2	8/2007
WO	WO 2007/121579	A1	11/2007
WO	WO 2007/131110	A2	11/2007
WO	WO 2007/137304	A2	11/2007
WO	WO 2007/139734	A2	12/2007
WO	WO 2007/142625	A2	12/2007
WO	WO 2007/147439	A1	12/2007
WO	WO 2008/021969	A2	2/2008
WO	WO 2008/039249	A1	4/2008
WO	WO 2008/039270	A1	4/2008
WO	WO 2008/045383	A2	4/2008
WO	WO 2008/070763	A1	6/2008
WO	WO 2008/089404	A2	7/2008
WO	WO 2008/101080	A1	8/2008
WO	WO 2008/109125	A1	9/2008
WO	WO 2008/124748	A1	10/2008
WO	WO 2009/0137761	A2	11/2009
WO	WO 2010/030434	A1	3/2010
WO	WO 2010/063795	A1	6/2010
WO	WO 2010/098871	A2	9/2010
WO	WO 2012/021671	A1	2/2012
WO	WO 2012/044844	A2	4/2012

OTHER PUBLICATIONS

C.C. Thompson et al., "Peroral Endoscopic Reduction of Dilated Gastrojejunal Anastomosis After Roux-en-Y Gastric Bypass: A Possible New Option for Patients with Weight Regain," Surg Endosc (2006) vol. 20, pp. 1744-1748.

B.R. Coolman, DVM, MS et al., "Comparison of Skin Staples With Sutures for Anastomosis of the Small Intestine in Dogs," Abstract; http://www.blackwell-synergy.com/doi/abs/10.1053/jvet.2000.7539?cookieSet=1&journalCode=vsu which redirects to http://www3.interscience.wiley.com/journal/119040681/abstract?CRETRY=1&SRETRY=0; [online] accessed: Sep. 22, 2008 (2 pages).

The Sodem Aseptic Battery Transfer Kit, Sodem Systems, (2000), 3 pages.

"Biomedical Coatings," Fort Wayne Metals, Research Products Corporation, obtained online at www.fwmetals.com on Jun. 21, 2010 (1 page).

Van Meer et al., "A Disposable Plastic Compact Wrist for Smart Minimally Invasive Surgical Tools," LAAS/CNRS (Aug. 2005).

Breedveld et al., "A New, Easily Miniaturized Sterrable Endoscope," IEEE Engineering in Medicine and Biology Magazine (Nov./Dec. 2005).

D. Tuite, Ed., "Get the Lowdown on Ultracapacitors," Nov. 15, 2007; [online] URL: http://electronicdesign.com/Articles/Print.cfm?ArticleID=17465, accessed Jan. 15, 2008 (5 pages).

Datasheet for Panasonic TK Relays Ultra Low Profile 2 A Polarized Relay, Copyright Matsushita Electric Works, Ltd. (Known of at least as early as Aug. 17, 2010), 5 pages.

ASTM procedure D2240-00, "Standard Test Method for Rubber Property-Durometer Hardness," (Published Aug. 2000).

ASTM procedure D2240-05, "Standard Test Method for Rubber Property-Durometer Hardness," (Published Apr. 2010).

U.S. Appl. No. 12/031,368, filed Feb. 14, 2008.

U.S. Appl. No. 12/031,542, filed Feb. 14, 2008.

U.S. Appl. No. 12/031,556, filed Feb. 14, 2008.

U.S. Appl. No. 12/031,573, filed Feb. 14, 2008.

U.S. Appl. No. 13/118,241, filed May 27, 2011.

U.S. Appl. No. 13/488,903, filed Jun. 5, 2012.

U.S. Appl. No. 13/310,107, filed Dec. 2, 2011.

U.S. Appl. No. 13/369,561, filed Feb. 9, 2012.

U.S. Appl. No. 13/369,629, filed Feb. 9, 2012.

U.S. Appl. No. 13/372,195, filed Feb. 13, 2012.

U.S. Appl. No. 13/486,175, filed Jun. 1, 2012.

U.S. Appl. No. 13/480,263, filed May 24, 2012.

International Search Report for PCT/US2012/026995, dated Jun. 19, 2012 (4 pages).

Written Opinion for PCT/US2012/026995, dated Jun. 19, 2012 (5 pages).

International Search Report for PCT/US2012/039296, dated Aug. 29, 2012 (5 pages).

Written Opinion for PCT/US2012/039296, dated Aug. 29, 2012 (12 pages).

Covidien Brochure, "Endo GIA™ Reloads with Tri-Staple™ Technology," (2010), 1 page.

Covidien Brochure, "Endo GIA™ Reloads with Tri-Staple™ Technology and Endo GIA™ Ultra Universal Staplers," (2010), 2 pages.

Covidien Brochure, "Endo GIA™ Black Reload with Tri-Staple™ Technology," (2012), 2 pages.

Covidien Brochure, "Endo GIA™ Curved Tip Reload with Tri-Staple™ Technology," (2012), 2 pages.

Covidien Brochure, "Endo GIA™ Reloads with Tri-Staple™ Technology," (2010), 2 pages.

Covidien Brochure, "Endo GIA™ Ultra Universal Stapler," (2010), 2 pages.

* cited by examiner



FIG. 1


58
62
63
154
59
146
57
61
66
84
65
80
65
97
99
156
64
95
96
88
147
145
144
57
149
106
154
150
176
107
152
82
151
148
79
87
81
77
86
142
78
83
138
141
140
143

FIG. 2


52
88
164
136
130
135
132
190
92
196
170
134
194
69
67
174
119
172
195
73
68
71
102
114
115
122
192
112
117
118
76
128
124
72
110
111
166
168
116
108
100
90
160
70
54
180
169
182
162
163
184
55
186
183
188
126
164
85

FIG. 3


52
107
130
190
194
196
195
174
114
193
108
110
116
118
132
172
106
102
120
A
166
176
76
69
100
73
128
70
124
67
68
71
126
164
106
160
72
90
82
87
53
54
57
78

FIG. 4


50
105
107
136
130
132
112
114
135
119
113
196
168
108
110
134
118
122
116
176
111
109
172
120
76
68
72
100
182
106
166
184
164
186
169
163
162
160
87
79
138

FIG. 5


50
130
132
135
136
107
114
112
113
110
119
196
111
109
118
122
116
76
108
110
182
184
72
68
55
71
186
164
164
162
160

FIG. 6


130
107
132
136
135
114
119
112
196
113
68
108
69
110
109
118
122
111
194
116
164
71
164
162
68
72
72
100
55
50
138
57
54

FIG. 7


132
136
174
171
69
90
68
100
92
166
163
162
106
50
119
196
194
122
72
164
67
76
54
124
126
140
138
142
147
145
144
79
83
81
148
146
57
64
62
66
FIRST HANDLE STROKE COMPRESSION

FIG. 8


52
160
164
166
162
169
106
70
186
188
180
92
73
69
68
170
184
182
172
191
179
176
192
193
166
168
132
194
195
173
135
134
119
115
174
136
132
107
130

FIG. 9



FIG. 11



FIG. 10


132
136
174
171
69
68
90
92
166
163
162
106
146
138
142
147
144
145
140
54
126
124
100
55
67
164
72
122
194
196
119
76
65
57
59
63
96
97
64
62
61
66
81
83
79
148
146
57
FIRST HANDLE STROKE RELEASE

FIG. 12


132
130
136
196
192
191
194
122
119
164
174
68
72
67
171
172
176
100
90
92
166
163
162
106
138
124
126
54
146
145
140
147
144
57
59
79
83
96
64
81
97
148
146
62
66
61
Knife 1/3
SECOND HANDLE STROKE COMPRESSION

FIG. 13


132
130
119
119
196
194
136
135
131
122
76
174
114
69
68
67
171
164
176
70
72
124
172
100
92
166
126
54
163
162
83
90
138
106
81
140
142
145
144
147
57

FIG. 14



THIRD HANDLE STROKE COMPRESSION

FIG. 15


130
119
196
194
118
122
76
132
136
114
68
72
164
67
171
192
176
172
90
100
92
166
160
106
54
146
138
140
65
145
57
142
59
79
83
63
147
64
81
144
62
148
96
146
97
57
66
61

FIG. 16


130
132
136
114
174
171
192
172
92
196
194
122
68
72
100
67
55
128
124
126
54
164
166
162
106
138
140
145
142
147
79
83
81
144
148
146
57
146
57
65
59
63
64
62
96
97
61
66

FIG. 17


130
132
136
174
171
172
100
90
92
166
196
194
122
69
68
72
67
54
124
126
164
162
106
138
145
140
146
147
144
57
59
63
96
97
64
62
61
66
83
81
148
146
57

FIG. 18


57
138
106
160
92
69
68
172
174
134
130
132
107
136
115
196
191
192
179
176
173
180
54

FIG. 19



FIG. 20



FIG. 21



FIG. 22



FIG. 23


154
58
51
146
207
63
62
217
84
80
65
156
96
97
97
95
147
64
145
88
144
232
149
206
207
154
150
152
148
151
138
232
86
142
140
141
143

FIG. 24


202
212
234
218
240
236
204
210
224
220
242
214
222
226
219
228
250
201
216
211
206
205
218
215
209
203
230

FIG. 25


148
206
230
250
210
207
203
201
228
222
214
242
226
220
219
232
236
204
240
234
238
212
202

FIG. 26


212
234
219
210
240
236
201
222
228
220
224
226
242
203
204
250
215
205
232

FIG. 27


140
206
205
232
203
204
222
228
250
242
212
234
236
238
240
219
201

FIG. 28


228
222
220
224
219
201
226
242
213
250
209
204
200
205
203
211
215
206
207
150
154
148
146
96

FIG. 29


96
146
200
154
148
207
206
205
203
242
226
250
204
234
240
236
238
219
201

FIG. 30


287
284
285
282
280
283
300
293
292
290
297
299
294
298
288
296
295
281
301
302
286

FIG. 31


280
282
284
285
283
300
293
290
297
290
292
292
291
291
299
294
298
281
302
301
286

FIG. 32


234
212
210
222
279
278
277
204
277
274
218
270
X1
275
X2
272
276
218

FIG. 33



FIG. 34



FIG. 35


1116
1108
1120
1106
1120
1106
1108
1108
1114
1110
1200
LTI
1112C
1108
1122
1208
LTI
1112b
1112a

FIG. 36



FIG. 37



FIG. 38


1230
1244
1256'
1247
1252
1245
1250
1240
1256'
1252
1241
1247
1252
1256'
1250
1248
1250
1252
1256'
1250
1256'
1252
1256'
1246
1010
1274
1270
1272
1272
1271
1276
1272
1276

FIG. 39


1240
1244
1246
1241
1247
1243
1245

FIG. 40


1240
1250
1243
1247
1239
1250
1256'
1252
1260
1252
1245
1248
1252
1242
1252
1245
1243
1250
1256'
1252
1250
1246

FIG. 41



FIG. 42


1300
1302
1304
1306
1307
1208
1200
1240
1246
1242
1250
1256'
1248
1230
2012
2024
2034
2022

FIG. 43


LT
2253b
2250b
2251b
PD
2052
AA
SD
AA
FD
2250a
2253a
2251a
2011
DD
2050
2040
2042
2008
2045
2027
2044
2024
LT

FIG. 44


1300
2206
LT
1302
2274
2270
1230
2268
2267
2330
2100
2070
2074
2069
1301
2220
2260
2104
2228
2226
2062
1309
2120
2010
2118
2116
2060
2008
1240
2040
2044
2045
2025
2011
2042
2027
1200
2012
2024
2022
2034
LT

FIG. 45


2024
2012
2022
2034
LT
DD
2025
2045
2042
2011
2044
2008
PD
R
2044
2040
2062
2060
1309
2070
2074
2118
2116
2100
2120
2106
2228
2226
2224
1300
2264
2220
2230
2206
2260
LT
1240
2210
1302
2272
2270
2274
2072
1230

FIG. 46


LT
2206
2210
2220
2230
2228
2226
2224
2120
2110
2118
2114
2099
1230
2116
2264
2260
2272
2100
2062
2074
2070
1300
2106
2060
1240
1309
1302
2040
R
2008
PD
2042
2045
2027
2012
2024
LT
2022
2034
2025
DD
2011

FIG. 47


2024
LT
2012
2034
2042
2027
PD
2025
2044
DD
1309
1230
2060
1300
2062
2074
2110
2114
2118
2116
2274
2206
2120
1305
2102
1240
2106
2099
2112
2100
2104
2260
2210
2222
1302
2230
LT
2220
2228
2226
2224

FIG. 48


1300
2220
2206
2210
1245
1243
2204
2068
1240
2062
2040
1241
1200
1302
2250a
2250b
DD
2044
2011
PD
2042
2050
2044
2200
2045
2027
2025
2202
2033
2032
2012
2022
2034

FIG. 49


1300
2206
2210
2220
2230
1243
2254
2260
2264
2266
2267
1240
2068
2204
2101
2100
2062
2060
2040
2008
2052
2250a
1309
1302
1241
2200

FIG. 50


1300
2056
2057
2210
1302
2206
2204
2252
2254
2254
2262
2268
1305
2102
2264
2267
2266
2260
2249
2063
2062
2100
2200
2207
2060
2250a
2040
1200
2052
2053

FIG. 51


1302
2210
2254
2252
2057
2256
2068
2250a
1305
2012
2100
2058
2264
2267
2266
2262
2260
2207
2249
2062
2060
2040

FIG. 52



FIG. 53



FIG. 54


1230
2462
2340
2460
2300
2308
2325
2345
2327
2324
2334
2322
2312

FIG. 55


2353
2351
LT
2440
2355
2442
DD
2401
2357
2450
2444
PD
2308
2340
2350
2400
2390
2384
2412
2388
2386
2392
2372
2418
2410
2416
2402
2380
2415
2374
2385
2426
2424
2485
2300
2430
2383
2354
2414
2382
2420
2312
2360
2345
2432
2434
2327
2325
2370
D
2336
2324
2334
2333
2332
LT

FIG. 56


LT
2442
2440
2450
2444
DD
2308
2340
2390
2384
2412
2416
2388
2392
2387
2418
2415
2402
2380
2370
2372
2374
2426
2385
2424
D
2430
2354
2414
2383
2382
2420
2360
2434
2345
2432
2327
2325
2312
PD
2324
2333
2332
2334
LT
2336
2300

FIG. 57


LT
2442
2440
2450
2350
2444
2400
2308
2340
2390
2402
2386
2387
2388
2384
2392
2416
2380
2412
2418
2410
2385
2426
2414
2372
2374
2430
2370
2432
2383
2420
2382
2360
2434
PD
DD
2312
D
2327
2354
2336
2345
2300
2324
2332
2334
2333
LT

FIG. 58


2375
LT
2490'
2490
2491
2493
2481
2482
2480
2492
2443
2460
2470
2484
2440
2359
2483
2472
2462
2474
2345
2341
2343
2465
2340
PD
2353
DD
2300
2308
LT

FIG. 59



FIG. 60


2508
2529
2523
2552
2554
2500
2550
2555
2527
2525
2582
2524
2512
DD
PD
D
2540
2541
2580
LT
2562
2570
2564
2560
2527
2532
2534
2522

FIG. 61


2508
2523
2541
2540
2580
LT
2562
2570
2564
2529
2500
2552
2560
2527
2554
2550
2555
2525
2582
2512
2524
2532
2534
2522

FIG. 62



FIG. 63


2600
2654
2650
2653
2656
2658
2644
2640
2622
2624
2623
2620
2652
2605
2642
2628
2630
2626
2610
2612
2614
2603
2544
2542
2602
2580
2500
2540

FIG. 64



FIG. 65


2740
2780
2800
2790
2792
2793
2762
2770
2794
2729
2727
2791
2723
2802
2760
2708
2752
2764
2804
PD
D
2754
2761
DD
2700
2727
2725
2750
2782
2712
2732
2724
2734
2722

FIG. 66


2740
2780
2800
2791
2793
2762
2770
2790
2792
2723
PD
2729
2794
2727
2802
2708
2760
68
2764
2804
2752
2761
2754
DD
2725
2727
2782
2700
2750
2732
2712
2724
2734
2722

FIG. 67



FIG. 68



FIG. 69


2900
2943
2944
2940
2946
LT
2786
2922
2920
2906
2924
2942
2948
2784
2808
2928
2923
70B
2902
2904
2926
2912
2806
2744
2914
2742
2742
2910
2740
2780
2903
2700
2708
2800
LT

FIG. 70



FIG. 70A



FIG. 70B


2740
2800
2792
2723
2770
2760
2708
2752
2804
2700'
2761
2727
2725
2712
2750
2782
2732
2724
2722
2734

FIG. 71


2740
2791
2708
2792
2760
2770
2804
2700'
2761
2752
2727
2725
2732
2750
2724
2722
2734

FIG. 72


3020
3022
1240
1000
3024
3026
3028
3014
3030
3011
3034
3010
1258
1270
3032
3012
3036
3031
3038
3013
DD
PD
3000
3003
D
3002

FIG. 73


3020
3022
1240
1000
3028
3024
3026
3014
3012
3030
3011
3034
1258
1270
3032
3031
3040
3046
3013
3042
3044
3000'
3003
3002

FIG. 74


PD
DD
3200
3208
3343
3340
3341
3342
3235
3232
3245
3225
3227
3229
3212
3209
3223
3224
3222
3234
3314
3322
3324
3320
3352
3354
3350
3356
3326
3328
3330
3358
3333
3310
3332
3360
3334
3363
3365
3362
3302
3335
3339
3368
3364
3336
3337
3367
3305
3338
3340
3235
3300

FIG. 75


3200'
3341
3343
3342
3208
3345
PD
3225
3229
3227
3245
3223
3209
3212'
DD
3222
3224

FIG. 76


3200''
3341
3343
3342
3347
3235'
3345
3225
3229
3223
DD
3212''
3234
3222

FIG. 77



FIG. 78



FIG. 80



FIG. 79


3408
3420
3410
3400
3442
3418
3416
3412
3450
3422
3525
3523
3445
3430
3527
3529
3432
3412
3524
3522
3534

FIG. 81


3408
3420
3400
3410
3442
3440
3418
3412
3416
3424
3450
3422
3523
3525
3527
3529
3445
3430
3432

FIG. 82


3420
3408
3410
3400
3418
3412
3424
3416
3440
3442
3422
3450
3529
3523
3430
3445
3527
3525
3432
3522
3412
3524

FIG. 83


3420
3408
3410
3400
3418
3414
3412
3424
3416
3442
3440
3450
3523
3422
3430
3522
3412
3445
3529
3527
3525
3432

FIG. 84


3500
3484
3480
3486
3494
LT
3490
3482
3488
3492
3472
3470
3474
3460
3462
3504
3420
3502
3408
3410
3400
LT

FIG. 85


LT
3751
3750
3710
3700
3678
3676
3677
3600
3692
3612
3662
3640
3630
AA
3620
LT

FIG. 86


3640
3620
3630
3658
3650
3612
3662
3676
3678
3676
3692

FIG. 87


3692
LT
3678
3676
3676
3662
AA
3658
3650
3650
3620
3640
3630
LT

FIG. 88


3676
3676
3612
3689
3620
3630

FIG. 89


3678
3692
3676
3676
3612
3689
3620
3630

FIG. 90


3664
3660
3666
3658
3652
3662
3650
3691
3670
3656
3684
3691
3676
3682
3654
3679
3689
3656
3678
3676
3680
3685
3694
3664
3660
3687
3672
3686
3674
3690
3692
3574

FIG. 91


3612
3702
3712
3692
3710
3700
3704
94
B
D
3730
3732

FIG. 92


3612
3712
3702
3692
3704
3710
3700
95
A
B
C
D
3730
3732

FIG. 93


3721
3734
3678
3730
C
3720

FIG. 94


3700
3720
3734
3721
3678
D
3730
3703
B
3676
3676
3720
3722
3612

FIG. 95



FIG. 96


3613
3690
3700''
3720'
3681
3612''
3680'
3710
3721
3740
3741

FIG. 97


3690
3613
3680'
3680'
3740
3721
3710
3700''
3720'

FIG. 98


3765
3764
3762
3766
3760
3763
3774
3767
3775
2720
3778
3770
3772
3757
3756
3753
3751
3776
3755
3754
3750
3752
3701
PD
3771
3700
DD
3600
2720

FIG. 99


3800
3808
PD
3850
3870
3841
3840
3825
3812
3824
3822
3814
3834
DD
3912
3910
3914
3916
3918
1240
3922
3904
3920
3900
3902
1000

FIG. 100


3808
3809
3811
3840
3872b
3870
3871
3874b
C
Z
3875
3865
3874a
3872a
3863
3873
Y
3868
3825
3864
3869
3860
3866
3867
3862
3824
3827
3823
3823
3822
3834
3835
3814

FIG. 101



FIG. 102



FIG. 103



FIG. 104



FIG. 105



FIG. 106



FIG. 107



FIG. 108



FIG. 109



FIG. 110



FIG. 111



FIG. 112


4100
4084
4080
4086
4094
LT
4090
4082
4088
4092
4013
4072
4070
4074
4060
4062
4104
4020
4011
4102
4008
4010
4000
LT

FIG. 113


5000
5200
5204
5207
5172
5170
5174
5176
5164
5140
5141
5144
5143
5115
5112
5152
5150
5145
5142
5154
5206
5114
5120
5110
5012
5122
5162
5160
5138
5137
5117
5110
5171
5070
5020
5044
5042
5030
5038
5040
5080
5130
R
PD
5108
5160
DD

FIG. 114



FIG. 115



FIG. 116


5012
120
120
5134
5136
5132
5130
5088
5098
5088
5098
5088
5084
5098
5088
5088
5040
5098
5044
5030
5044
5042
5098
5082
5086
5096
5094
5086
5092
5090
5086
5080
5098
5086
5026
5088
5062
5098
5026
5088
5060
5026
5098
5088
5026
5028
5026
5022

FIG. 117


5134
5022
5136
5130
5026
DD
5132
5026
5088
5098
5098
5026
5088
5088
5060
5062
5050
5098
5056
5052
5042
5034
5044
5032
5030
5054
5038
5026
5098
5088

FIG. 118



FIG. 120



FIG. 119



FIG. 121



FIG. 122



FIG. 123



FIG. 124



FIG. 125



FIG. 126


5000'
5088b
5022
5088a
5026,5028
5060'
5053
5026,5028
5030'
5026,5028
5052',5054'
5055
5056'

FIG. 127


5312
5330
5322
5333
DD
5336
5334
5350
5332
5352
5362
5364
5380
5388
5360
5392
5386
5346
5344
5342
5340

FIG. 128


5312
5350
5352
5334
5322
5333
5368
DD
5394
5362
5366
5364
5368
5312

FIG. 129



FIG. 130


5340
5332
5342
5330
5346
5344
5312
5360
5336
5380
5392
5394
5334

FIG. 131


5312
5332
5334
5362
5360
5364
5360
5362
5364
5364
5362
5360
5364
5364
5360
5392
5364
5364
5360
5394
5362
5364
5360
5360
5364
5364
5360
5362
5360
5364
5364
5370
5362
5372

FIG. 132



FIG. 133


2008
1100
1001
1200
2012
5520
5504
2037a
2024
2034a
2037a
2022
2034a
2037a
2034b
2034a
2035
2037a
5532
2035a
5514
5530
5540
5512
2035a
5512
2035
2035a
5512
5510
5500
5502

FIG. 134


2008
1200
2012
2022
2024
2034b
5534
5540
5530
5520
5532
5504
2034a
5502
5512
5512
5512
5514
5500
5512
5514
5510
5512

FIG. 135


2008
1100
1000
1001
1200
2024
2022
2034b
5504
5534
5530
2035
5532
5534
5520
5500
5502

FIG. 136


2008
1100
1000
1001
1200
U
2022
2024
5504
2034b
5534
2035
5520
5530
5534
5532
5500
5502

FIG. 137


1100
1000
1001
2008
1200
2024
5540
2022
5514
2034a
5500
5512
2035
5502
5510

FIG. 138


5664
3612
3612
5600
5650
5652
5664
5664
5653
5620
5666
5658
5653
5654
5625
5660
5624
5660
5680
5612
5644
5642
5610
5644
5649
5644
5626
1100
5640
5630
5626
5648
1003
1000
1001

FIG. 139



FIG. 140



FIG. 141


5600
5666
5666
5658
5664
5650
5652
5653
5653
5620
5654
5625
5668
5662
5624
5670
5660
5680
5660
5612
5644
5642
5649
5628
5644
5640
5626
5630

FIG. 142


3676
3676
3612
5664
5666
5662
5660
5668
3662
3680
3689
5670
3640
3630
3620
5669
5672

FIG. 143


LT
6030
6202
6200
6040
PD
6100
DD
6009
6000
6042
6008
6043
6034
6045
6027
6022
6012
6024
LT

FIG. 144


LT
6146
6150
6152
6110
6102
6144
6030
6126
6146
D
TA2
L
TA1
R
6122
6125
6144
6124
6123
6120
6150
6124
6010
6127
TA2
U
LT
TA1

FIG. 145



FIG. 146



FIG. 147


6550
6564
6560
6570
6572
6568
6574
6566
6562
6540
LT
6352
6142
6322
6351
6542
6534
6300
6370
6324
6372
6362
6371
6375
6374
6342
6180
6140
6182
6332
6192
S
6160
6172
6174
6166
6164
6167
6162
6190
6361
6330
6344
6350
6512
6516
6522
6520
6169
6168
6144
6412
6320
6166
6414
6150
6410
6049
6048
6524
6518
6510
6514
6202
6402
6041
6148
6400
6040
6205
6200
6144
6110
6532
6147
6150
6530
6008
LT
6000

FIG. 148


6322
6324
6350
6330
6300
LT
6380
6371
6332
S
6142
6370
6374
6372
6342
6364
VA
6361
6362
6320
6340
6344
6192
6375
6190
6110
6365
6162
6167
6170
6174
6164
6180
6181
6166
6153
6159
6166
HA
6182
6172
6169
6155
6150
6152
6160
6166
6151
6153
6140
6154
6149
6168
6110
6144
6147
6144
LT
6146
6148

FIG. 149



FIG. 150



FIG. 151

SHIFTABLE DRIVE INTERFACE FOR ROBOTICALLY-CONTROLLED SURGICAL TOOL

CROSS-REFERENCE TO RELATED APPLICATIONS

This non-provisional patent application is a continuation patent application of and claims the benefit from U.S. patent application Ser. No. 13/118,223, filed May 27, 2011, entitled "Robotically-Controlled Shaft Based Rotary Drive Systems For Surgical Instruments", which is a continuation-in-part of and claims the benefit of U.S. patent application Ser. No. 13/020,053, entitled "Shaft Based Rotary Drive System for Surgical Instruments", filed Feb. 3, 2011, now U.S. Pat. No. 8,196,796 which is a continuation patent application of and claims the benefit from U.S. patent application Ser. No. 11/810,015, filed Jun. 4, 2007, entitled "Surgical Instrument Having a Multiple Rate Directional Switching Mechanism", now U.S. Pat. No. 7,905,380, the entire disclosures of which are herein incorporated by reference and which are related to the following commonly-owned U.S. Patent Applications and which are hereby incorporated by reference in their entirety:

(1) U.S. patent application Ser. No. 11/810,016, entitled SURGICAL INSTRUMENT HAVING A DIRECTIONAL SWITCHING MECHANISM, now U.S. Pat. No. 7,832,408; and

(2) U.S. patent application Ser. No. 11/809,935, entitled SURGICAL INSTRUMENT HAVING A COMMON TRIGGER FOR ACTUATING AN END EFFECTOR CLOSING SYSTEM AND A STAPLE FIRING SYSTEM, now U.S. Pat. No. 7,819,299.

BACKGROUND

1. Field of the Invention

The present invention generally relates to surgical stapling instruments and, more particularly, to surgical staplers having an end effector closing system and a firing system for deploying staples.

2. Description of the Related Art

As known in the art, surgical staplers are often used to deploy staples into soft tissue to reduce or eliminate bleeding from the soft tissue, especially as the tissue is being transected, for example. Surgical staplers, such as an endocutter, for example, often comprise an end effector which is configured to secure the soft tissue between first and second jaw members. The first jaw member often includes a staple cartridge which is configured to removably store staples therein and the second jaw member often includes an anvil. In use, the staples are typically deployed from the staple cartridge by a driver which traverses a channel in the staple cartridge and causes the staples to be deformed against the anvil and secure layers of the soft tissue together. Often, as known in the art, the staples are deployed in several staple lines, or rows, in order to more reliably secure the layers of tissue together. The end effector may also include a cutting member, such as a knife, for example, which is advanced between two rows of the staples to resect the soft tissue after the layers of the soft tissue have been stapled together.

After the driver and the cutting member have been advanced within the end effector, it is often necessary to retract the driver and/or cutting member to their starting positions. Previous surgical staplers have included a return spring which retracts the cutting member relative to the staple cartridge after a release button or toggle switch on the surgical stapler has been actuated by the surgeon. Such staplers, however, are unable to partially retract the cutting member and, as a result, the cutting member must be fully retracted before it can be readvanced. Other previous surgical staplers have included a plurality of triggers which are operatively engaged with systems for closing a jaw member and for advancing and/or retracting the driver and cutting member. Such devices, while suitable for their intended purposes, often require a surgeon to release a trigger operably engaged with the closing system and reposition their hand to grasp a different trigger which is operatively engaged with a system for advancing the staple driver and cutting member. While previous surgical staplers have been developed which have a single trigger for both closing the jaw member and advancing the driver and cutting member, such devices perform both functions upon the initial actuation of the trigger. While suitable in some circumstances, devices which perform both functions in the same trigger actuation are often exceedingly difficult to operate owing to the high degree of force required to actuate the trigger. Furthermore, such devices, as they close the jaw member and deploy staples in the same trigger actuation, do not afford the surgeon with an opportunity to evaluate the position of the closed jaw member and reposition the jaw member before the staples are deployed into the soft tissue. What is needed is an improvement over the foregoing.

SUMMARY

In at least one form of the invention, a surgical instrument can include a switching mechanism which can allow a surgeon, or other clinician, to selectively advance or retract a staple driver and/or cutting member within a staple cartridge. In various embodiments, the surgical instrument can include a handle, a trigger operatively coupled to the handle, a firing drive, and an end effector. In at least one embodiment, the firing drive can include a first ratchet assembly configured to advance a cutting member in the end effector and a second ratchet assembly configured to retract the cutting member. In various embodiments, the trigger can include first and second pawls pivotably mounted thereon which are configured to be selectively engaged with the first and second ratchet assemblies, respectively. In at least one such embodiment, the trigger can be configured to slide between a first position in which the first pawl is engaged with the first ratchet assembly and a second position in which the second pawl is engaged with the second ratchet assembly. In such embodiments, a surgeon can quickly and conveniently select between advancing and retracting motions of the cutting member.

In at least one form of the invention, a surgical instrument can include a drive mechanism configured to advance a staple driver and/or cutting member at a first rate and retract the staple driver and/or cutting member at a different rate. In at least one embodiment, the rate at which the driver and cutting member are advanced and/or retracted is the distance that the driver and cutting member are translated per actuation, or stroke, of a trigger, for example. Accordingly, in such embodiments, a first rate is considered to be faster than a second rate if the trigger advances or retracts the cutting member a greater distance per actuation. In various embodiments, the cutting member can be retracted at a faster rate as compared to the rate in which it is advanced. In such embodiments, the surgical instrument can, owing to the slower advancing rate, provide a greater torque or advancing force to the cutting member while, owing to the faster retracting rate, reduce the time required for the surgeon to retract the cutting member. In various embodiments, as described above, the surgical instrument can include a switching mechanism configured to selectively engage one of a first drive system and a

second drive system with a rotatable drive shaft. In at least one such embodiment, the first drive system can include a first gear having a first pitch radius and the second drive system can include a second gear having a different pitch radius where the first and second gears can rotate the drive shaft at different rates.

In at least one form of the invention, a surgical instrument can include a trigger which can be configured to close a jaw member onto soft tissue, for example, upon a first actuation of the trigger and advance a staple driver and/or cutting member upon a subsequent, or second, actuation of the trigger. In various embodiments, such a surgical instrument can allow a surgeon to position the surgical instrument in a surgical site and close the jaw member with an initial actuation of the trigger without deploying any staples into, or incising, the tissue. In such embodiments, as a result, the surgeon can manipulate the position of the surgical instrument and then actuate the trigger a second time to deploy staples into, and/or incise, the tissue. In at least one such embodiment, the first actuation of the trigger which closes the jaw member can also unlock a firing drive configured to advance the staple driver and cutting member during the second actuation of the trigger. In various embodiments, the surgical instrument can include a switching mechanism which can allow the surgeon to reopen the jaw member and, if they so choose, to reposition the jaw member in a more suitable position.

In accordance with another general aspect of at least one embodiment of the present invention, there is provided a surgical instrument that includes an end effector that has a selectively reciprocatable implement movably supported therein. The implement is selectively advanceable in a distal direction upon application of a rotary actuation motion thereto and retractable in a proximal direction upon application of a rotary retraction motion thereto. The surgical instrument further comprises an elongate shaft assembly that is coupled to the end effector and is configured to transmit the rotary actuation motion and rotary retraction motion to the reciprocatable implement from a robotic system that is configured to generate the rotary actuation motion and the rotary retraction motion. The surgical instrument further comprises a firing drive that includes a first rotary drive assembly that operably interfaces with a first corresponding drive portion of the robotic system. The first rotary drive assembly selectively interfaces with the elongate shaft assembly and is configured to apply the rotary actuation motion thereto when activated. A second rotary drive assembly operably interfaces with a second corresponding drive portion of the robotic system. The second rotary drive assembly interfaces with the elongate shaft assembly and is configured to apply the rotary retraction motion thereto when the first rotary drive assembly is deactivated and the second rotary drive assembly is activated.

In accordance with yet other general aspects of various embodiments of the present invention, there is provided a surgical instrument that includes an elongate shaft assembly that is coupled to a remotely actuatable system that is capable of generating a plurality of control motions. The elongate shaft assembly is operably engaged with a first drive member and a second drive member. An end effector is coupled to the elongate shaft assembly. In various embodiments, the end effector comprises an elongate channel that is configured to operably support a staple cartridge therein. An anvil is movably coupled to the elongate channel and a cutting member is operably supported within the elongate channel. The cutting member is operably engaged with the elongate shaft assembly such that when the remotely actuatable system is engaged with the first drive member, a first actuation advances said cutting member a first distance and wherein, when the remotely actuatable system is engaged with the second drive member, a second actuation retracts the cutting member a second distance. In various embodiments, the second distance is greater than the first distance.

BRIEF DESCRIPTION OF THE DRAWINGS

The above-mentioned and other features and advantages of the various embodiments of this invention, and the manner of attaining them, will become more apparent and the invention itself will be better understood by reference to the following description of embodiments of the invention taken in conjunction with the accompanying drawings, wherein:

FIG. **1** is a perspective view of a surgical instrument in accordance with an embodiment of the present invention;

FIG. **2** is an exploded view of a shaft portion and end effector of the surgical instrument of FIG. **1**;

FIG. **3** is an exploded view of a handle portion of the surgical instrument of FIG. **1**;

FIG. **4** is partial side view of the handle portion of FIG. **3** with some components of the surgical instrument removed;

FIG. **5** is a top view of the handle portion of FIG. **3** with some components of the surgical instrument removed illustrating the surgical instrument in a configuration for advancing a cutting member in the end effector;

FIG. **6** is a bottom view of the handle portion of FIG. **3** with some components of the surgical instrument removed illustrating the surgical instrument in a configuration for advancing a cutting member in the end effector;

FIG. **7** is a partial perspective view of the handle portion of FIG. **3** with some components of the surgical instrument removed;

FIG. **8** is a perspective view of the surgical instrument of FIG. **1** illustrating the configuration of the surgical instrument upon the first actuation of the trigger;

FIG. **9** is a partial perspective view of the surgical instrument of FIG. **1** in the configuration illustrated in FIG. **8** with some components of the surgical instrument removed;

FIG. **10** is a perspective view of a cam of the end effector closure system of the surgical instrument of FIG. **1**;

FIG. **11** is an elevational view of the cam of FIG. **10** illustrating various relative positions of a lock of the anvil closure system;

FIG. **12** is a perspective view of the surgical instrument of FIG. **1** illustrating the configuration of the surgical instrument after the trigger has been released after the first actuation of the trigger;

FIG. **13** is a perspective view of the surgical instrument of FIG. **1** illustrating the configuration of the surgical instrument upon the second actuation of the trigger;

FIG. **14** is a partial perspective view of the surgical instrument of FIG. **1** in the configuration illustrated in FIG. **13**;

FIG. **15** is a perspective view of the surgical instrument of FIG. **1** illustrating the configuration of the surgical instrument upon the third actuation of the trigger;

FIG. **16** is a perspective view of the surgical instrument of FIG. **1** illustrating the configuration of the surgical instrument upon the fourth actuation of the trigger;

FIG. **17** is a perspective view of the surgical instrument of FIG. **1** illustrating the configuration of the surgical instrument after the trigger has been released after the fourth actuation of the trigger and the switching mechanism of the surgical instrument has been operated;

FIG. **18** is a perspective view of the surgical instrument of FIG. **1** illustrating the configuration of the surgical instrument upon the seventh actuation of the trigger with the cutting member fully retracted;

FIG. **19** is a partial elevational view of the surgical instrument of FIG. **1** illustrated in the configuration of FIG. **18** with components of the surgical instrument removed;

FIG. **20** is a partial perspective view of the housing of the surgical instrument of FIG. **1** illustrating the interaction of the firing drive and the housing after the seventh actuation of the trigger;

FIG. **21** is a perspective view of a gear reduction mechanism for a surgical instrument in accordance with an alternative embodiment of the present invention with a portion of the gear reduction housing disassembled;

FIG. **22** is an exploded view of the gear reduction mechanism of FIG. **21**;

FIG. **23** is a perspective view of a surgical instrument in accordance with an alternative embodiment of the present invention;

FIG. **24** is an exploded view of the end effector and shaft assembly of the surgical instrument of FIG. **23**;

FIG. **25** is an exploded view of the handle portion of the surgical instrument of FIG. **23**;

FIG. **26** is an exploded view of the surgical instrument of FIG. **23** with components of the surgical instrument removed;

FIG. **27** is a perspective view of the surgical instrument of FIG. **23** with components of the surgical instrument removed;

FIG. **28** is a second perspective view of the surgical instrument of FIG. **23** with components of the surgical instrument removed;

FIG. **29** is a side view of the surgical instrument of FIG. **23** configured to advance a cutting member within the end effector;

FIG. **30** is a side view of the surgical instrument of FIG. **23** configured to retract the cutting member within the end effector;

FIG. **31** is a perspective view of a directional switching mechanism in accordance with an alternative embodiment of the present invention with some components disassembled and other components illustrated in cross-section;

FIG. **32** is a plan view of the directional switching mechanism of FIG. **31** with some components removed and other components illustrated in cross-section;

FIG. **33** is a diagram of a bistable compliant mechanism in accordance with an alternative embodiment of the present invention;

FIG. **34** is a perspective view of one robotic controller embodiment;

FIG. **35** is a perspective view of one robotic surgical arm cart/manipulator of a robotic system operably supporting a plurality of surgical tool embodiments of the present invention;

FIG. **36** is a side view of the robotic surgical arm cart/manipulator depicted in FIG. **35**;

FIG. **37** is a perspective view of an exemplary cart structure with positioning linkages for operably supporting robotic manipulators that may be used with various surgical tool embodiments of the present invention;

FIG. **38** is a perspective view of a surgical tool embodiment of the present invention;

FIG. **39** is an exploded assembly view of an adapter and tool holder arrangement for attaching various surgical tool embodiments to a robotic system;

FIG. **40** is a side view of the adapter shown in FIG. **39**;

FIG. **41** is a bottom view of the adapter shown in FIG. **39**;

FIG. **42** is a top view of the adapter of FIGS. **39** and **40**;

FIG. **43** is a partial bottom perspective view of the surgical tool embodiment of FIG. **38**;

FIG. **44** is a partial exploded view of a portion of an articulatable surgical end effector embodiment of the present invention;

FIG. **45** is a perspective view of the surgical tool embodiment of FIG. **43** with the tool mounting housing removed;

FIG. **46** is a rear perspective view of the surgical tool embodiment of FIG. **43** with the tool mounting housing removed;

FIG. **47** is a front perspective view of the surgical tool embodiment of FIG. **43** with the tool mounting housing removed;

FIG. **48** is a partial exploded perspective view of the surgical tool embodiment of FIG. **47**;

FIG. **49** is a partial cross-sectional side view of the surgical tool embodiment of FIG. **43**;

FIG. **50** is an enlarged cross-sectional view of a portion of the surgical tool depicted in FIG. **49**;

FIG. **51** is an exploded perspective view of a portion of the tool mounting portion of the surgical tool embodiment depicted in FIG. **43**;

FIG. **52** is an enlarged exploded perspective view of a portion of the tool mounting portion of FIG. **51**;

FIG. **53** is a partial cross-sectional view of a portion of the elongated shaft assembly of the surgical tool of FIG. **43**;

FIG. **54** is a side view of a half portion of a closure nut embodiment of a surgical tool embodiment of the present invention;

FIG. **55** is a perspective view of another surgical tool embodiment of the present invention;

FIG. **56** is a cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of the surgical tool embodiment of FIG. **55** with the anvil in the open position and the closure clutch assembly in a neutral position;

FIG. **57** is another cross-sectional side view of the surgical end effector and elongated shaft assembly shown in FIG. **56** with the clutch assembly engaged in a closure position;

FIG. **58** is another cross-sectional side view of the surgical end effector and elongated shaft assembly shown in FIG. **56** with the clutch assembly engaged in a firing position;

FIG. **59** is a top view of a portion of a tool mounting portion embodiment of the present invention;

FIG. **60** is a perspective view of another surgical tool embodiment of the present invention;

FIG. **61** is a cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of the surgical tool embodiment of FIG. **60** with the anvil in the open position;

FIG. **62** is another cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of the surgical tool embodiment of FIG. **60** with the anvil in the closed position;

FIG. **63** is a perspective view of a closure drive nut and portion of a knife bar embodiment of the present invention;

FIG. **64** is a top view of another tool mounting portion embodiment of the present invention;

FIG. **65** is a perspective view of another surgical tool embodiment of the present invention;

FIG. **66** is a cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of the surgical tool embodiment of FIG. **65** with the anvil in the open position;

FIG. **67** is another cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of the surgical tool embodiment of FIG. **66** with the anvil in the closed position;

FIG. **68** is a cross-sectional view of a mounting collar embodiment of a surgical tool embodiment of the present invention showing the knife bar and distal end portion of the closure drive shaft;

FIG. **69** is a cross-sectional view of the mounting collar embodiment of FIG. **68**;

FIG. **70** is a top view of another tool mounting portion embodiment of another surgical tool embodiment of the present invention;

FIG. **70**A is an exploded perspective view of a portion of a gear arrangement of another surgical tool embodiment of the present invention;

FIG. **70**B is a cross-sectional perspective view of the gear arrangement shown in FIG. **70**A;

FIG. **71** is a cross-sectional side view of a portion of a surgical end effector and elongated shaft assembly of another surgical tool embodiment of the present invention employing a pressure sensor arrangement with the anvil in the open position;

FIG. **72** is another cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of the surgical tool embodiment of FIG. **71** with the anvil in the closed position;

FIG. **73** is a side view of a portion of another surgical tool embodiment of the present invention in relation to a tool holder portion of a robotic system with some of the components thereof shown in cross-section;

FIG. **74** is a side view of a portion of another surgical tool embodiment of the present invention in relation to a tool holder portion of a robotic system with some of the components thereof shown in cross-section;

FIG. **75** is a side view of a portion of another surgical tool embodiment of the present invention with some of the components thereof shown in cross-section;

FIG. **76** is a side view of a portion of another surgical end effector embodiment of a portion of a surgical tool embodiment of the present invention with some components thereof shown in cross-section;

FIG. **77** is a side view of a portion of another surgical end effector embodiment of a portion of a surgical tool embodiment of the present invention with some components thereof shown in cross-section;

FIG. **78** is a side view of a portion of another surgical end effector embodiment of a portion of a surgical tool embodiment of the present invention with some components thereof shown in cross-section;

FIG. **79** is an enlarged cross-sectional view of a portion of the end effector of FIG. **78**;

FIG. **80** is another cross-sectional view of a portion of the end effector of FIGS. **78** and **79**;

FIG. **81** is a cross-sectional side view of a portion of a surgical end effector and elongated shaft assembly of another surgical tool embodiment of the present invention with the anvil in the open position;

FIG. **82** is an enlarged cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of the surgical tool embodiment of FIG. **81**;

FIG. **83** is another cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of FIGS. **81** and **82** with the anvil thereof in the closed position;

FIG. **84** is an enlarged cross-sectional side view of a portion of the surgical end effector and elongated shaft assembly of the surgical tool embodiment of FIGS. **81-83**;

FIG. **85** is a top view of a tool mounting portion embodiment of a surgical tool embodiment of the present invention;

FIG. **86** is a perspective assembly view of another surgical tool embodiment of the present invention;

FIG. **87** is a front perspective view of a disposable loading unit arrangement that may be employed with various surgical tool embodiments of the present invention;

FIG. **88** is a rear perspective view of the disposable loading unit of FIG. **87**;

FIG. **89** is a bottom perspective view of the disposable loading unit of FIGS. **87** and **88**;

FIG. **90** is a bottom perspective view of another disposable loading unit embodiment that may be employed with various surgical tool embodiments of the present invention;

FIG. **91** is an exploded perspective view of a mounting portion of a disposable loading unit depicted in FIGS. **87-89**;

FIG. **92** is a perspective view of a portion of a disposable loading unit and an elongated shaft assembly embodiment of a surgical tool embodiment of the present invention with the disposable loading unit in a first position;

FIG. **93** is another perspective view of a portion of the disposable loading unit and elongated shaft assembly of FIG. **92** with the disposable loading unit in a second position;

FIG. **94** is a cross-sectional view of a portion of the disposable loading unit and elongated shaft assembly embodiment depicted in FIGS. **92** and **93**;

FIG. **95** is another cross-sectional view of the disposable loading unit and elongated shaft assembly embodiment depicted in FIGS. **92-94**;

FIG. **96** is a partial exploded perspective view of a portion of another disposable loading unit embodiment and an elongated shaft assembly embodiment of a surgical tool embodiment of the present invention;

FIG. **97** is a partial exploded perspective view of a portion of another disposable loading unit embodiment and an elongated shaft assembly embodiment of a surgical tool embodiment of the present invention;

FIG. **98** is another partial exploded perspective view of the disposable loading unit embodiment and an elongated shaft assembly embodiment of FIG. **97**;

FIG. **99** is a top view of another tool mounting portion embodiment of a surgical tool embodiment of the present invention;

FIG. **100** is a side view of another surgical tool embodiment of the present invention with some of the components thereof shown in cross-section and in relation to a robotic tool holder of a robotic system;

FIG. **101** is an exploded assembly view of a surgical end effector embodiment that may be used in connection with various surgical tool embodiments of the present invention;

FIG. **102** is a side view of a portion of a cable-driven system for driving a cutting instrument employed in various surgical end effector embodiments of the present invention;

FIG. **103** is a top view of the cable-driven system and cutting instrument of FIG. **102**;

FIG. **104** is a top view of a cable drive transmission embodiment of the present invention in a closure position;

FIG. **105** is another top view of the cable drive transmission embodiment of FIG. **104** in a neutral position;

FIG. **106** is another top view of the cable drive transmission embodiment of FIGS. **104** and **93** in a firing position;

FIG. **107** is a perspective view of the cable drive transmission embodiment in the position depicted in FIG. **104**;

FIG. **108** is a perspective view of the cable drive transmission embodiment in the position depicted in FIG. **105**;

FIG. **109** is a perspective view of the cable drive transmission embodiment in the position depicted in FIG. **106**;

FIG. **110** is a perspective view of another surgical tool embodiment of the present invention;

FIG. **111** is a side view of a portion of another cable-driven system embodiment for driving a cutting instrument employed in various surgical end effector embodiments of the present invention;

FIG. **112** is a top view of the cable-driven system embodiment of FIG. **111**;

FIG. **113** is a top view of a tool mounting portion embodiment of another surgical tool embodiment of the present invention;

FIG. **114** is a top cross-sectional view of another surgical tool embodiment of the present invention;

FIG. **115** is a cross-sectional view of a portion of a surgical end effector embodiment of a surgical tool embodiment of the present invention;

FIG. **116** is a cross-sectional end view of the surgical end effector of FIG. **115** taken along line **116-116** in FIG. **115**;

FIG. **117** is a perspective view of the surgical end effector of FIGS. **115** and **116** with portions thereof shown in cross-section;

FIG. **118** is a side view of a portion of the surgical end effector of FIGS. **115-117**;

FIG. **119** is a perspective view of a sled assembly embodiment of various surgical tool embodiments of the present invention;

FIG. **120** is a cross-sectional view of the sled assembly embodiment of FIG. **119** and a portion of the elongated channel of FIG. **118**;

FIGS. **121-126** diagrammatically depict the sequential firing of staples in a surgical tool embodiment of the present invention;

FIG. **127** is a partial perspective view of a portion of a surgical end effector embodiment of the present invention;

FIG. **128** is a partial cross-sectional perspective view of a portion of a surgical end effector embodiment of a surgical tool embodiment of the present invention;

FIG. **129** is another partial cross-sectional perspective view of the surgical end effector embodiment of FIG. **128** with a sled assembly axially advancing therethrough;

FIG. **130** is a perspective view of another sled assembly embodiment of another surgical tool embodiment of the present invention;

FIG. **131** is a partial top view of a portion of the surgical end effector embodiment depicted in FIGS. **128** and **129** with the sled assembly axially advancing therethrough;

FIG. **132** is another partial top view of the surgical end effector embodiment of FIG. **131** with the top surface of the surgical staple cartridge omitted for clarity;

FIG. **133** is a partial cross-sectional side view of a rotary driver embodiment and staple pusher embodiment of the surgical end effector depicted in FIGS. **128** and **129**;

FIG. **134** is a perspective view of an automated reloading system embodiment of the present invention with a surgical end effector in extractive engagement with the extraction system thereof;

FIG. **135** is another perspective view of the automated reloading system embodiment depicted in FIG. **134**;

FIG. **136** is a cross-sectional elevational view of the automated reloading system embodiment depicted in FIGS. **134** and **135**;

FIG. **137** is another cross-sectional elevational view of the automated reloading system embodiment depicted in FIGS. **134-136** with the extraction system thereof removing a spent surgical staple cartridge from the surgical end effector;

FIG. **138** is another cross-sectional elevational view of the automated reloading system embodiment depicted in FIGS. **134-137** illustrating the loading of a new surgical staple cartridge into a surgical end effector;

FIG. **139** is a perspective view of another automated reloading system embodiment of the present invention with some components shown in cross-section;

FIG. **140** is an exploded perspective view of a portion of the automated reloading system embodiment of FIG. **139**;

FIG. **141** is another exploded perspective view of the portion of the automated reloading system embodiment depicted in FIG. **140**;

FIG. **142** is a cross-sectional elevational view of the automated reloading system embodiment of FIGS. **139-141**;

FIG. **143** is a cross-sectional view of an orientation tube embodiment supporting a disposable loading unit therein;

FIG. **144** is a perspective view of another surgical tool embodiment of the present invention;

FIG. **145** is a partial perspective view of an articulation joint embodiment of a surgical tool embodiment of the present invention;

FIG. **146** is a perspective view of a closure tube embodiment of a surgical tool embodiment of the present invention;

FIG. **147** is a perspective view of the closure tube embodiment of FIG. **146** assembled on the articulation joint embodiment of FIG. **145**;

FIG. **148** is a top view of a portion of a tool mounting portion embodiment of a surgical tool embodiment of the present invention;

FIG. **149** is a perspective view of an articulation drive assembly embodiment employed in the tool mounting portion embodiment of FIG. **148**;

FIG. **150** is a perspective view of another surgical tool embodiment of the present invention; and

FIG. **151** is a perspective view of another surgical tool embodiment of the present invention.

Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate preferred embodiments of the invention, in one form, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION

Applicant of the present application also owns the following patent applications that were filed on May 27, 2011 and which are each herein incorporated by reference in their respective entireties:

- U.S. patent application Ser. No. 13/118,259, entitled "Surgical Instrument With Wireless Communication Between a Control Unit of a Robotic System and Remote Sensor";
- U.S. patent application Ser. No. 13/118,210, entitled "Robotically-Controlled Disposable Motor Driven Loading Unit";
- U.S. patent application Ser. No. 13/118,194, entitled "Robotically-Controlled Endoscopic Accessory Channel";
- U.S. patent application Ser. No. 13/118,253, entitled "Robotically-Controlled Motorized Surgical Instrument";
- U.S. patent application Ser. No. 13/118,278, entitled "Robotically-Controlled Surgical Stapling Devices That Produce Formed Staples Having Different Lengths";
- U.S. patent application Ser. No. 13/118,190, entitled "Robotically-Controlled Motorized Cutting and Fastening Instrument";
- U.S. patent application Ser. No. 13/118,263, entitled "Robotically-Controlled Surgical Instrument Having Recording Capabilities";
- U.S. patent application Ser. No. 13/118,272, entitled "Robotically-Controlled Surgical Instrument With Force Feedback Capabilities";

U.S. patent application Ser. No. 13/118,246, entitled "Robotically-Driven Surgical Instrument With E-Beam Driver"; and

U.S. patent application Ser. No. 13/118,241, entitled "Surgical Stapling Instruments With Rotatable Staple Deployment Arrangements".

Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the various embodiments of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

Uses of the phrases "in various embodiments," "in some embodiments," "in one embodiment", or "in an embodiment", or the like, throughout the specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics of one or more embodiments may be combined in any suitable manner in one or more other embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

Certain exemplary embodiments will now be described to provide an overall understanding of the principles of the structure, function, manufacture, and use of the devices and methods disclosed herein. One or more examples of these embodiments are illustrated in the accompanying drawings. Those of ordinary skill in the art will understand that the devices and methods specifically described herein and illustrated in the accompanying drawings are non-limiting exemplary embodiments and that the scope of the various embodiments of the present invention is defined solely by the claims. The features illustrated or described in connection with one exemplary embodiment may be combined with the features of other embodiments. Such modifications and variations are intended to be included within the scope of the present invention.

In various embodiments, a surgical instrument in accordance with the present invention can include systems for inserting surgical staples into soft tissue, for example. In at least one embodiment, the surgical instrument can include a staple cartridge configured to removably store staples therein and an anvil for deforming the staples as they are deployed from the staple cartridge. In order to deploy the staples, the surgical instrument can include a staple driver configured to traverse the staple cartridge and a firing drive for advancing the staple driver within the staple cartridge. In various embodiments, the firing drive can include a drive bar which is translated in a substantially linear direction by a trigger operably engaged therewith. In other embodiments, the firing drive can include a drive shaft which is rotated by the trigger. In such embodiments, the surgical instrument can include a shaft assembly which can convert the rotary motion of the drive shaft into linear motion and translate the staple driver within the staple cartridge. While the exemplary embodiment illustrated in FIGS. **1-20** and described below includes a firing drive having a rotary drive shaft, the present invention is not so limited. Furthermore, while a general description of a firing drive having a rotary drive shaft is provided below, other such devices are described and illustrated in greater detail in the commonly-owned, co-pending U.S. patent application Ser. No. 11/475,412, entitled MANUALLY DRIVEN SURGICAL CUTTING AND FASTENING INSTRUMENT and filed on Jun. 27, 2006, the entire disclosure of which is hereby incorporated by reference herein.

Referring to FIG. **1**, surgical instrument **50** can include handle portion **52**, trigger **54**, elongate shaft assembly **56**, and end-effector **58**. In various embodiments, end-effector **58** can include anvil **62** and staple cartridge channel **64**, where channel **64** can be configured to receive staple cartridge **66** and anvil **62** can be pivotably connected to channel **64**. In at least one embodiment, at least one of anvil **62** and channel **64** can be operably connected to trigger **54** such that, upon an actuation of trigger **54**, anvil **62** can be rotated into a closed position as illustrated in FIG. **8**. In various embodiments, referring to FIGS. **2-4**, trigger **54** can be operably engaged with a closure drive system configured to translate both anvil **62** and channel **64** relative to outer sheath **57** of elongate shaft assembly **56**. Referring primarily to FIG. **4**, the closure drive can include cam **68** operably engaged with trigger **54** such that a first actuation of trigger **54** can rotate cam **68** about pin **70** and drive closure links **72** in a substantially linear direction. More particularly, trigger **54** can include lift pin **55** (FIG. **3**) extending therefrom which can be configured to contact surface **71** of cam **68** and lift cam **68** into the position illustrated in FIG. **8**. Cam **68** can further include cam slot **69** where, when cam **68** is rotated from its position illustrated in FIG. **4** to its position illustrated in FIG. **8**, the side walls of cam slot **69** can engage closure link pin **76** and, in the present embodiment, slide closure links **72** in a direction illustrated by arrow A (FIG. **4**).

Referring to FIGS. **2** and **4**, surgical instrument **50** can further include a spine assembly within elongate shaft assembly **56** (FIG. **1**), where the spine assembly can include proximal channel portion **78** and distal channel portion **80**. In various embodiments, channel portions **78** and **80** can be interconnected by the cooperative engagement of projection, or tongue, **84** and groove **86**. More particularly, referring to FIG. **2**, proximal channel portion **78** can include, in various embodiments, first half **77** and second half **79** which can be assembled to distal channel portion **80** such that projection **84** is secured within groove **86**. In at least one embodiment, proximal channel portion halves **77** and **79** can include projections **81** and/or apertures **83** configured to provide a snap-fit or press-fit engagement between proximal channel portion halves **77** and **79**. In various other embodiments, channel portions **78** and **80** can be interconnected by any suitable means and, in at least one embodiment, although not illustrated, portions **78** and **80** can be integrally formed. Similar to the above, referring to FIG. **2**, distal channel portion **80** can include distal end **88** which can be connected to staple cartridge channel **64**. More particularly, distal channel portion **80** and staple cartridge channel **64** can include cooperating tongue and groove features, for example, which can provide a press-fit or snap-fit interconnection therebetween, although any other suitable interconnection therebetween can be used.

Referring to FIG. **4**, proximal end **82** of channel portion **78** can be coupled to closure links **72** by pin **53** such that, when closures links **72** are translated by cam **68**, channel portion **78** is translated within elongate shaft assembly **56**. In at least one embodiment, channel portion **78** can further include projections **87** extending therefrom which can be configured to slide within recesses **85** (FIG. **3**) in housing portions **90** and substantially limit the translation of channel portion **78** along an axis. As staple cartridge channel **64** is connected to proximal channel portion **78** via distal channel portion **80**, channel **64**,

and anvil **62** pivotably connected thereto, can be moved in direction A when cam **68** is rotated by trigger **54** as described above. In at least one embodiment, referring to FIG. **2**, proximal end **63** of anvil **62** can be configured to abut outer sheath **57** of elongate shaft assembly **56** when channel **64** and anvil **62** are translated relative to sheath **57**. After proximal end **63** of anvil **62** contacts outer sheath **57**, anvil **62** can be configured to rotate toward channel **64** and staple cartridge **66** in order to close anvil **62** as illustrated in FIG. **8**. In various embodiments, referring to FIG. **2**, channel **64** can include slots **65** therein which can be configured to guide anvil **62** as it is pivoted relative to channel **64**. Once anvil **62** is closed, the surgical instrument can further include a lock which holds anvil **62** in its closed position. In various embodiments, referring to FIGS. **9-11**, surgical instrument **50** can include spring lock **92** mounted to housing **90**, where spring lock **92** can be configured to releasably hold cam **68** in position which, as a result, locks closure links **72**, channel portions **78** and **80**, channel **64**, and anvil **62** in position until a surgeon desires to open anvil **62** as described in detail further below.

In various embodiments, after anvil **62** has been placed into its closed position, trigger **54** can be actuated a second time to operate a firing drive which advances cutting member **96** within end effector **58**. In at least one embodiment, the firing drive can be disengaged from trigger **54** prior to the first actuation of trigger **54**. In such embodiments, the first actuation of trigger **54** can operably engage trigger **54** with the firing drive and/or release a component of the firing drive such that the firing drive becomes operably engaged with trigger **54**. In the illustrated embodiment, referring to FIGS. **3** and **4**, the firing drive can include trigger gear portion **100** extending from trigger **54**, gear train **102**, gear carriage **130**, and rotatable drive shaft **106** which can be configured to advance cutting member **96** within end effector **58** as described in greater detail below. As illustrated in FIGS. **3-7**, gear train **102** can include ratchet gear **108**, main drive gear **110**, bevel drive gear **112**, and bevel gear **114** where, prior to the first actuation of trigger **54**, cam **68** can be configured to bias ratchet gear **108** out of engagement with main drive gear **110**. More particularly, referring to FIG. **3**, ratchet gear **108** can include shaft **116** and collar **118** where cam **68** can be configured to contact collar **118** and bias ratchet gear **108** away from main drive gear **112** such that ratchet face **109** on ratchet gear **108** is not engaged with ratchet face **111** on main drive gear **110**.

Upon the first actuation of trigger **54**, as described above, cam **68** can be rotated into the position illustrated in FIG. **8** and, as a result of such rotation, groove **120** (FIGS. **4** and **5**) in cam **68** can be configured to release ratchet gear **108**. More particularly, referring to FIGS. **5-7**, groove **120** can be dimensioned such that, when the rotation of cam **68** aligns groove **120** with collar **118**, collar **118** can slide past cam **68** and allow ratchet spring **122** to bias ratchet gear **108** into operative engagement with main drive gear **110**. Thereafter, trigger **54** can be released and then returned to its starting position by trigger spring **124** where trigger spring **124** can be connected to pin **126** extending from housing **90** and pin **128** extending from trigger **54**. Notably, even though trigger **54** can be returned to its starting position, cam **68** can remain locked in its second position by lock **92**, as described above, thereby maintaining the alignment between groove **120** and collar **118**. With ratchet gear **108** now operably engaged with drive gear **110**, a second actuation of trigger **54** can advance cutting member **96** and the staple driver within end effector **58**.

Referring primarily to FIGS. **3** and **4**, an actuation of trigger **54** can rotate trigger gear portion **100** about an axis defined by pin **70**. Trigger gear portion **100** can include gear teeth extending along the perimeter thereof which can, referring to FIGS. **5** and **6**, be engaged with gear teeth extending around the circumference, for example, of ratchet gear **108**. In use, as a result, the actuation, or rotation, of trigger **54** can rotate ratchet gear **108** about an axis defined by shaft **116** and pin **117** (FIG. **3**). As described above, ratchet gear **108** can, referring to FIGS. **5** and **6**, include ratchet face **109** which can be configured to engage ratchet face **111** of main drive gear **110**. In at least one embodiment, ratchet faces **109** and **111** can be configured to transmit the rotational motion of trigger **54** to main drive gear **110** upon the second actuation, or other subsequent actuation, of trigger **54** but also permit relative sliding movement therebetween when trigger **54** is released and returned to its unactuated position. In effect, ratchet faces **109** and **111** can be configured to transmit rotational motion to main drive gear **110** when ratchet gear **108** is rotated in one direction but not transmit rotational motion to main drive gear **110** when ratchet gear **108** is rotated in the opposite direction. Although a ratchet mechanism has been described and illustrated herein, any other suitable mechanism for transmitting motion between trigger **54** and main drive gear **110** can be used. Furthermore, although trigger **54** has been described and illustrated as a lever, any other suitable device can be used to motivate the firing and closing drives described herein.

Referring primarily to FIGS. **5-7**, main drive gear **110** can include gear teeth extending around the circumference thereof, for example, which can be engaged with gear teeth extending around the perimeter, for example, of bevel drive gear **112**. In use, as a result, the rotational motion transmitted to main drive gear **110** from ratchet gear **108**, for example, can be transmitted to bevel drive gear **112**. In various embodiments, bevel drive gear **112** can be mounted to or integrally formed with shaft **113**, where shaft **113** can define an axis about which bevel drive gear **112** can be rotated. In at least one embodiment, referring to FIG. **3**, surgical instrument **50** can further include bracket **115** about which bevel drive gear **112** and shaft **113** can be rotated. As described in greater detail below, bracket **115** can also include supports **119** which can be configured to slidably support at least a portion of gear carriage **130**. In various embodiments, referring to FIGS. **5-7**, bevel gear **114** can be attached to bevel drive gear **112** or, alternatively, bevel gear **114** can be mounted to or integrally formed with shaft **113**. In either event, the rotational motion transmitted to bevel drive gear **112** can be transmitted to bevel gear **114**.

In various embodiments, although not illustrated, bevel gear **114** could be directly engaged with drive shaft **106** via cooperating bevel gear teeth. In at least one such embodiment, bevel gear **114** could rotate drive shaft **106** in a clockwise direction, for example, and advance cutting member **96** within end effector **58** as described below. In such embodiments, the actuation of trigger **54** could advance cutting member **96** within end effector **58**, however, cutting member **96** would have to be retracted either manually or via an additional retraction system. In the illustrated embodiment of the present invention, referring to FIGS. **3** and **5-7**, surgical instrument **50** can further include a switching mechanism which can allow drive shaft **106** to be rotated in either a clockwise or counter-clockwise direction and, correspondingly, allow cutting member **96** to be advanced or retracted via the actuation of trigger **54**. In various embodiments, referring primarily to FIGS. **5** and **6**, the switching mechanism can include gear carriage **130** which can be shifted between a first position in which the rotational motion of bevel gear **114** rotates drive shaft **106** in a clockwise direction, for example, and a second position in which the rotational motion of bevel gear **114** rotates drive shaft **106** in a counter-clockwise direction.

In various embodiments, referring to FIGS. **5-7**, gear carriage **130** can include housing **132**, forward gear **134**, and reversing gear **136** where forward gear **134** and reversing gear **136** can be rotatably mounted to housing **132**. In at least one embodiment, drive shaft **106** can include substantially hex-shaped end **107**, for example, which can be received within apertures (not illustrated) in forward gear **134** and reversing gear **136** such that gears **134** and **134** are rotatably engaged with drive shaft **106**. In other various embodiments, end **107** can include any other suitable shape or configuration such that gears **134** and **136** are rotatably engaged with drive shaft **106**. In either event, referring to FIG. **5**, gear carriage **130** can be slid along end **107** such that either forward gear **134** or reversing gear **136** can be engaged with bevel gear **114**. In use, when forward gear **134** is engaged with bevel gear **114**, for example, the rotational motion of bevel gear **114** can be transmitted to forward gear **134** and, owing to cooperating geometries of end **107** and the aperture in forward gear **134**, the rotational motion of gear **134** can be transmitted to drive shaft **106**. In order to rotate drive shaft in the opposite direction, gear carriage **130** can be slid proximally, or rearward, such that reversing gear **136** engages bevel gear **114**. A mechanism for motivating gear carriage **130** in this manner is described further below.

In various embodiments, when forward gear **134** is engaged with bevel gear **114**, as illustrated in FIG. **5**, reversing gear **136** can be disengaged from bevel gear **114** such that reversing gear **136** is free to rotate with drive shaft **106**. In at least one embodiment, gear carriage **130** can further include spacer **135** which can be configured to rotatably support and align gears **134** and **136** yet permit gears **134** and **136** to rotate independent of one another. In some embodiments, gear carriage **130** can be placed in a position intermediate the forward and rearward positions such that both gears **134** and **136** engage bevel gear **114** and hold drive shaft **106** in a 'locked-out' condition such that trigger **54** cannot be actuated. In other various embodiments, gear carriage **130** can be placed in an intermediate position such that neither gears **134** and **136** engage bevel gear **114**. In such embodiments, the firing drive is in a 'free' condition and the rotational motion of bevel gear **114** is not transmitted to drive shaft **106**.

In various embodiments, referring primarily to FIG. **2**, drive shaft **106** can further include threaded drive portion **138** which can be operably engaged with firing nut **140**. In at least one embodiment, threaded drive portion **138** can be configured to slidably advance and/or retract firing nut **140** in response to rotational motion of drive shaft **106**. More particularly, firing nut **140** can include threaded aperture **141** which can be configured to threadably receive threaded drive portion **138** such that the rotation of drive shaft **106** produces a reactional force which advances firing nut **140** distally. In at least one embodiment, firing nut **140** can include projection **142** extending therefrom which can be configured to extend through a slot defined between proximal channel portion halves **77** and **79** in order to constrain the movement of firing nut **140** along an axis. In effect, the slot can prevent firing nut **140** from rotating with drive shaft **106** and can define a path for projection **142** as firing nut **140** is translated within channel portion **78**.

In various embodiments, referring to FIG. **2**, cutting member **96** can be operably engaged with firing nut **140** such that the translation of firing nut **140**, as described above, can result in the translation of cutting member **96** within end effector **58**. In at least one embodiment, surgical instrument **50** can further include firing rod **144** connected to firing nut **140**, drive bar **146** connected to cutting member **96**, and adapter **148** configured to connect drive bar **146** to firing rod **144**. In various embodiments, firing rod **144** can include proximal end **145** which can include an aperture configured to receive at least a portion of firing nut **140** in a press-fit manner. In at least one embodiment, proximal end **145** of firing rod **144** can include deformable member **147** which can be configured to engage recess **143** in firing nut **140** after deformable member **147** has been depressed or deformed inwardly toward recess **143**. In either event, firing rod **144** can further include distal end **149** which can be configured to receive plug **150** in a press-fit manner, for example, where plug **150** can include projection **152** extending therefrom which can be received within slot **154** in adapter **148**. In various embodiments, adapter **148** can further include slot **151**, where slot **151** can be configured to receive connector tab **154** of drive bar **146** such that, when adapter **148** is translated by firing rod **144**, drive bar **146** can be translated within distal retainer section **80**. In at least one embodiment, drive bar **146** can further include distal end **156** which can be configured to engage recess **97** in cutting member **96** and advance and/or retract cutting member **96** within end effector **58**. As described above, cutting member **96** can include knife **99** which can be configured to incise tissue positioned between anvil **62** and staple cartridge **66** as cutting member **96** is advanced within end effector **58**. Further, as described above, cutting member **96** can include portion **95**, where portion **95** can be configured to push a staple driver (not illustrated) within staple cartridge **66** to deploy staples (not illustrated) removably stored therein.

In various embodiments, the surgical instrument can be configured to advance cutting member **96** a desired distance upon a single actuation of trigger **54**, i.e., the second overall actuation of trigger **54** in embodiments where the first actuation of trigger **54** closes anvil **62** as described above. In other embodiments, however, more than one actuation of trigger **54** can be used to advance cutting member **96** a desired distance. In at least one such embodiment, referring to FIGS. **12-16**, trigger **54** can be actuated three times to advance cutting member **96** from proximal end **59** to distal end **61** of end effector **58**. The quantity of such actuations in other embodiments, however, will depend largely upon the overall distance that cutting member **96** is to be displaced and the displacement of cutting member **96** as a result of each actuation. Notably, prior to the second actuation of trigger **54**, cutting member **96** can be positioned in proximal end **59** of end effector **58** and firing nut **140** can be positioned in its most proximal position. Upon the second actuation of trigger **54**, referring to FIGS. **13** and **14**, cutting member **96** can be advanced approximately one-third of the distance between proximal end **59** and distal end **61** and, similarly, firing nut **140** can be advanced distally along drive shaft **106**. Thereafter, referring to FIG. **15**, cutting member can be advanced an additional one-third of the distance between proximal end **59** and distal end **61** upon the third actuation of trigger **54** and, similarly, referring to FIG. **16**, cutting member **96** can be advanced into distal end **61** of end effector **58** upon the fourth actuation of trigger **54**.

In various embodiments, in order to assist a surgeon in monitoring the amount of times that trigger **54** has been actuated, surgical instrument **50** can include a counting mechanism which can be configured to display the amount of times that trigger **54** has been actuated and/or the amount of actuations remaining to deploy all of the staples in the staple cartridge. In either event, referring primarily to FIGS. **3** and **9**, one embodiment of counting mechanism **170** can include indicator nut **172**, indicator plate **174**, and indicator window **171** (FIG. **1**) in housing **90**. In at least one embodiment, indicator plate **174** can include indicia thereon which can communicate to the surgeon the amount of times that trigger

54 has been actuated to advance cutting member 96. In such embodiments, indicator plate 174 can include blank portion 173 which is visible through window 171 before and after the first actuation of trigger 54, i.e., the actuation of trigger 54 which closes anvil 62 as described above. Upon the second actuation of trigger 54, the rotation of drive shaft 106 can advance indicator nut 172 and indicator plate 174, which is mounted to indicator nut 172, distally such that the numeral "1" or other appropriate indicia on indicator plate 174 can be seen through indicator window 171. Accordingly, such an indicium can indicate to the surgeon that cutting member 96 has been advanced by one actuation of trigger 54. Similar to firing nut 140, indicator nut 172 can include a threaded aperture which can be threadably engaged with threaded portion 176 of drive shaft 106 such that the rotation of drive shaft 106 applies a reactional force to indicator nut 172 and advances it distally. Subsequent actuations of trigger 54 can move the numerals '2' and '3' beneath indicator window 171.

In order to retract cutting member 96, as outlined above, gear carriage 130 can be shifted such that forward gear 134 is disengaged from bevel gear 114 and, referring to FIGS. 17 and 18, reversing gear 136 is engaged with bevel gear 114. Thereafter, subsequent actuations of trigger 54 can rotate drive shaft 106 in the opposite direction and translate firing nut 140 proximally. More particularly, owing to the threaded engagement between firing nut 140 and threaded portion 138 of drive shaft 106, the rotation of shaft 106 in the opposite direction applies a reactional force to firing nut 140 which displaces firing nut 140 in the proximal direction. Accordingly, firing rod 144, drive bar 146 and cutting member 96, which can be connected to firing nut 140 as described above, are also displaced in the proximal direction thereby retracting cutting member 96 within end effector 58. Similarly, the rotation of shaft 106 in the opposite direction can displace indicator nut 172 of indicator assembly 170 proximally as well. More particularly, the first actuation of trigger 54 after gear carriage 130 has been shifted, i.e., the fifth overall actuation of trigger 54, can cause drive shaft 106 to apply a reactional force to indicator nut 172 and move nut 172 proximally. In such circumstances, indicator nut 172 can move indicator plate 174 relative to window 171 such that the numeral '2' is visible through indicator window 171 which can remind the surgeon that two more actuations of trigger 54 are required to fully retract cutting member 96.

Although trigger 54 is actuated three times to advance and/or retract cutting member 96 in the present embodiment, the actuations required to advance cutting member 96 can be different than the actuations required to retract cutting member 96 in other embodiments. Exemplary embodiments including features for advancing and retracting cutting member 96 at different rates are described in detail further below. Furthermore, in at least one embodiment, portion 95 of cutting member 96 can be engaged with the staple driver such the retraction of cutting member 96 also retracts the staple driver. In other embodiments, however, the staple driver can be left behind in the staple cartridge and only the cutting member 96 is retracted. Such embodiments may be utilized where a spent staple cartridge assembly is replaced with a new staple cartridge assembly which includes its own staple driver therein and, as a result, it may be desirable to leave the used staple driver in the spent cartridge.

In order to motivate gear carriage 130 as described above, surgical instrument 50 can include, referring to FIGS. 3-5, switching mechanism 160. In at least one embodiment, switching mechanism 160 can include shaft switch 162, shifter handles 164 extending therefrom, and shifter link 166, where shifter link 166 can be connected to shaft 162 via shifter pin 169 and gear carriage housing 132 via pin 168. In order to slide gear carriage 130 relative to drive shaft 106 as described above, shifter handles 164 can be configured to rotate shaft 162 such that crank arm 163 extending from shaft 162 displaces shifter link 166 and drives gear carriage 130 along axis 105 of drive shaft 106. In the illustrated embodiment, when shifter handles 164 are oriented in a substantially downward direction, as illustrated in FIG. 8, crank arm 163 is oriented in a substantially upward direction. In this configuration, referring to FIG. 5, gear carriage 130 is positioned in its most rearward, or proximal, position such that forward gear 134 is operably engaged with bevel gear 114. In order to shift surgical instrument 50 into a configuration in which cutting member 96 is retracted, shifter handles 164 can be rotated upwardly, as illustrated in FIG. 17, to rotate crank arm 163 forward, or distally. Correspondingly, crank arm 163 can be configured to displace link arm 166 distally and pull gear carriage 130 into its most distal position, thereby engaging reversing gear 136 with bevel gear 114. In the event that the surgeon desires to advance cutting member 96 after at least partially retracting cutting member 96, the surgeon can rotate shifter handles 164 downwardly and re-engage forward gear 134 with bevel gear 114.

In various embodiments, referring to FIGS. 3 and 5, surgical instrument 50 can further include a bistable compliant mechanism for biasing switching mechanism 160 into a configuration where one of gears 134 or 136 is engaged with bevel gear 114. Stated another way, the bistable compliant mechanism can cause switching mechanism 160 to become dynamically unstable when a surgeon only partially rotates shifter handles 164. In such circumstances, the bistable compliant mechanism can bias switching mechanism 160 into one of two configurations where it is stable, i.e., the forward and reversing configurations. In various embodiments, bistable compliant mechanism 180, referring primarily to FIG. 3, can include receiver 182, spring 184, plunger 186 and toggle pin 188. In at least one embodiment, toggle pin 188 can connect plunger 186 to switch shaft 162 and receiver 182 can be connected to projection 183 extending from housing 90. In use, spring 184 can be configured to apply a biasing force to shaft 162 via plunger 186 and can be configured to rotate shaft 162 in the event that shaft 162 is only partially rotated between its forward and reversing orientations.

In various embodiments, once cutting member 96 has been fully retracted, the end effector closing system and the staple firing system can be reset so that the spent staple cartridge can be removed from surgical instrument 50, a new staple cartridge 66 can be positioned within staple cartridge channel 64, and surgical instrument 50 can be used to further staple and cut tissue as described above. In the illustrated embodiment, cam 68 can be released from lock 92 to open anvil 62 and reset the end effector closure system. Similarly, ratchet gear 108 can be disengaged from main drive gear 110 to disengage trigger 54 from gear train 102 and reset the staple firing system. In at least one embodiment, cam 68 and ratchet gear 108 can be manually reset, however, referring primarily to FIGS. 3-5, 9, 10, 19 and 20, surgical instrument 50 can include a reset system which can automatically reset the end effector closure system and staple firing system described above. In various embodiments, the final return actuation of trigger 54 can reset these systems as described in detail below.

As outlined above, the first actuation of trigger 54 can rotate cam 68 into the position illustrated in FIG. 8 and spring lock 92 can be configured to hold cam 68 in place as the firing drive is operated by subsequent actuations of trigger 54. As also illustrated in FIG. 8, surgical instrument 50 can further include cam spring 67 which can be configured to bias cam 68

downwardly and, referring to FIGS. **9** and **10**, hold cam lock arm **73** extending from cam **68** against spring lock **92**. In such embodiments, cam lock arm **73** can include recess **74** which can be configured to receive at least a portion of spring lock **92**. In order to assist cam spring **67** in keeping cam **68** from lifting upwardly during subsequent actuations of trigger **54** and becoming disengaged from cam spring **92**, indicator nut **174** can be configured to contact cam rail **75** and hold cam lock arm **73** against spring lock **92**. More particularly, as indicator nut **174** is advanced distally, as described above, indicator nut **174** can be slid along contact rail **75** providing a positive stop against which cam **68** cannot rotate. Once indicator nut **174** is returned to its most proximal position, however, indicator nut **174** can become aligned with ramp **89** and, as a result, the third return actuation of trigger **54** can cause cam **68** to rotate upward slightly, thereby disengaging lock arm **73** from spring lock **92** as illustrated in FIG. **10**.

After cam **68** has been released from lock **92**, cam return spring **67** can be configured to rotate cam **68** downwardly and return it to its original position. As cam **68** is rotated downwardly, the walls of cam slot **69** can be configured to drive closure links **72** distally and, correspondingly, drive channel portions **78** and **80** and staple cartridge channel **64** distally as well. In at least one embodiment, end effector **58** can further include a spring (not illustrated) configured to bias anvil **62** upwardly as staple cartridge channel **64** is slid distally, i.e., away from outer sheath **57** of elongate shaft assembly **56**. In other various embodiments, although not illustrated, surgical instrument **50** can further include an actuator in which a surgeon can operate to pull or push anvil **62** into an open position. In either event, in at least one embodiment, cam return spring **67** can assert a force sufficient for cam **68** to displace ratchet gear **108** out of engagement with main drive gear **110** and, as a result, reset the firing drive. In other various embodiments, cam return spring **67** may not be strong enough to pull cam **68** downwardly with sufficient force to disengage ratchet gear **108** from main drive gear **110**. In at least one such embodiment, surgical instrument **50** can further include, referring to FIGS. **3-5** and **19**, a toggle switch assembly which can selectively bias ratchet gear **108** away from main drive gear **110**.

In various embodiments, referring primarily to FIGS. **3**, **4**, and **9**, toggle switch assembly **190** can include toggle actuator **192** mounted to drive shaft **106**, where toggle actuator **192** can include toggle arm **193** extending therefrom. Upon the final return actuation of trigger **54**, in at least one embodiment, indicator nut **172** can contact toggle actuator **192** and rotate it about drive shaft **106** such that toggle arm **193** is rotated toward ratchet gear **108**. In at least one such embodiment, referring to FIG. **9**, indicator nut **172** can further include ramp **179** which can be configured to engage projection **191** extending from toggle actuator **192** and rotate toggle actuator **192** clockwise about drive shaft **106**. In various embodiments, toggle arm **193** can be configured to contact ratchet gear **108** as it is rotated about drive shaft **106** and displace ratchet gear **108** away from main drive gear **110**. In at least one embodiment, ratchet gear **108** can be sufficiently displaced away from drive gear **110** to allow cam return spring **67** to position cam **68** adjacent collar **118**. Thereafter, cam **68** can hold ratchet gear **108** in this position until cam **68** is rotated upwardly as described above.

Although the above-described mechanisms can reset cam **68** and ratchet gear **108** into their initial positions, toggle arm **193** of toggle actuator **192**, at least in the illustrated embodiment, can remain positioned against collar **118** of ratchet gear **108**. Accordingly, even if cam **68** is rotated upwardly such that groove **120** is aligned with collar **118** upon the first actuation of trigger **54**, ratchet gear **108** may not be released to engage main drive gear **110** as described above. In view of this, in at least one embodiment, surgical instrument **50** can include a reset mechanism for rotating toggle arm **193** out of engagement with ratchet gear **108**. Such a mechanism can, in various embodiments, be manually operated and/or automatically operated in response to an actuation of trigger **54**, for example. In at least one embodiment, as illustrated in FIG. **20**, housing **90** can include projection **91** extending therefrom which can be configured to rotate toggle actuator **192** about drive shaft **106** and return it to its original, unactuated position as illustrated in FIG. **9**. More particularly, in various embodiments, projection **91** can be configured to engage toggle link **194** (FIG. **3**) as gear carriage **130** is moved from its distal position in which reversing gear **136** is engaged with bevel gear **114** to its proximal position in which forward gear **134** is engaged with bevel gear **114**. Such movement can be effected by switching mechanism **160** when shifter handles **164** are rotated downwardly to move gear carriage **130** proximally and place surgical instrument **50** in its 'advancing' configuration described above. As a result of the contact between toggle link **194** and projection **91**, toggle link **194** can be rotated about pin **195** such that toggle link **194** contacts actuator arm **193** and rotates toggle actuator **192** counterclockwise about drive shaft **106**. In various embodiments, toggle switch assembly **190** can further include bistable compliant mechanism **196**, which can assist in assuring that toggle switch assembly **190** does not become stuck in an intermediate configuration.

As described above, surgical instruments in accordance with the present invention can include a single trigger for actuating both an end effector closure system and a staple firing system. While the above-described features were described in connection with such single trigger surgical instruments, several of the features described above can be used in surgical instruments having a first trigger for actuating an end effector closure system and a second trigger for actuating a staple firing system. Referring to FIGS. **23-30**, for example, surgical instrument **200** can include trigger **201** for actuating an end effector closure system and trigger **204** for actuating a staple firing system. In various embodiments, referring to FIG. **25**, the end effector closure system can include closure link **203** operably engaged with closure trigger **201** via pin **209**. The end effector closure system can further include slider **205** and closure tube **207** (FIG. **23**), where closure tube **207** can be operably connected to closure link **203** via slider **205** and pin **211**. More particularly, referring to FIG. **29**, closure tube **207** can include flange **213** at its most proximal end which can be configured to be received within slot **215** in slider **205** such that the sliding motion of slider **205** is transmitted to closure tube **207**.

In use, referring primarily to FIGS. **29** and **30**, the actuation of trigger **201** can translate closure link **203** distally and, correspondingly, translate slider **205** and closure tube **207** distally as well. In various embodiments, closure tube **207** can include features which are cooperatively engaged with anvil **62** such that translation of closure tube **207** causes anvil **62** to rotate toward staple cartridge channel **64**. More particularly, referring to FIG. **24**, anvil **62** can include projection **51** extending therefrom which can be received within aperture **217** of closure tube **207** such that sidewalls of aperture **217** can abut projection **51** and rotate anvil **62** downwardly. To guide anvil **62**, as outlined above, staple cartridge channel **64** can include slots **65** which can define a path for anvil **62** as it is rotated. Surgical instrument **200** can further include lock **219** which can be configured to hold trigger **201** in an actuated position thereby holding anvil **62** in a closed position. To open

anvil **62**, lock **219** (FIG. **28**) can be disengaged from trigger **201** such that trigger **201** can be returned to its unactuated position. As trigger **201** is returned to its unactuated position, trigger **201** can drive slider **205** and closure tube **207** proximally and, owing to the operative engagement between projection **51** and aperture **217**, rotate anvil **62** upwardly.

As indicated above, surgical instruments in accordance with the present invention can include a firing drive which can be configured to advance a cutting member, for example, at a first rate and retract the cutting member at a different rate. In various embodiments, referring to FIGS. **23-30**, surgical instrument **200** can include firing drive **202** which can comprise trigger **204**, drive shaft **206**, first ratchet assembly **210**, and second ratchet assembly **212**. In at least one embodiment, ratchet assemblies **210** and **212** can be configured to rotate drive shaft **206** in clockwise and counter-clockwise directions, respectively, in order to advance or retract cutting member **96** within end effector **58**. In various embodiments, referring to FIG. **25**, trigger **204** can be selectively engageable with ratchet assemblies **210** and **212** such that, when trigger **204** is actuated, only one of ratchet assemblies **210** and **212** is driven by trigger **204**. In at least one such embodiment, trigger **204** can be slidable along pin **214** in order to engage trigger **204** with one of ratchet assemblies **210** and **212**. In the illustrated embodiment, pin **214** can be rotatably received in apertures **216** in housing portions **218** and provide an axis of rotation for trigger **204**.

In various embodiments, referring to FIG. **27**, trigger **204** can be positioned such that pawl **220**, which can be pivotably mounted to trigger **204**, is engaged with ratchet wheel **222** and, upon the actuation of trigger **204**, ratchet wheel **222** is rotated about pin **214** by pawl **220**. Upon the release of trigger **204**, pawl **220** can slide over ratchet teeth **224** of ratchet wheel **222** permitting relative movement therebetween. In at least one embodiment, ratchet assembly **210** can further include a pawl spring (not illustrated) configured to bias pawl **220** into engagement with ratchet teeth **224** and re-engage pawl **220** with ratchet teeth **224** when trigger **204** is reactuated. In order to transmit the rotation of ratchet wheel **222** to drive shaft **206**, drive shaft **206** can include forward gear **226** connected thereto. More particularly, in at least one embodiment, ratchet wheel **222** can further include gear teeth **228** which can be operably engaged with forward gear **226** such that the rotation of ratchet wheel **222** rotates forward gear **226** and drive shaft **206** about axis **230** (FIG. **25**). In various embodiments, forward gear **226** can be press-fit, for example, onto drive shaft **206** or, in other various embodiments, forward gear **226** can be integrally formed with drive shaft **206**.

In various embodiments, similar to the surgical instruments described above, drive shaft **206** can, referring to FIG. **24**, be operably engaged with firing nut **140** in order to translate firing nut **140** within proximal retainer portion **232**. As also described above, the translation of firing nut **140** can be transmitted to cutting member **96** via drive bar **146** in order to advance cutting member **96** within end effector **58**. In order to retract cutting member **96** within end effector **58**, in at least one embodiment, trigger **204** can be slid into engagement with second ratchet assembly **212** such that drive shaft **206** is rotated in the opposite direction when trigger **204** is actuated. Similar to ratchet assembly **210**, referring to FIG. **28**, ratchet assembly **212** can include ratchet wheel **234** and pawl **236** where pawl **236** can be pivotably mounted to trigger **204** and can be operatively engaged with ratchet wheel **234** via ratchet teeth **238**. Similar to ratchet wheel **222**, ratchet wheel **234** can include gear teeth **240** which can be operably engaged with reversing gear **242** mounted to drive shaft **206**. As ratchet wheels **222** and **234** engage drive shaft **206** on substantially opposite sides, ratchet wheels **222** and **234** can rotate drive shaft **206** in opposite directions, i.e. clockwise and counter-clockwise directions, respectively. Thus, in order to select whether cutting member **96** is advanced or retracted within end effector **58**, trigger **204** can be slid into operative engagement with either first ratchet assembly **210** or second ratchet assembly **212**.

In various embodiments, although not illustrated, first ratchet wheel **222** and second ratchet wheel **234** can have substantially the same diameter, or pitch radius. Stated another way, the distance between the center, or axis of rotation, of the ratchet wheels and the gear teeth of the ratchet wheels can be the same. In such embodiments, the distance that cutting member **96** is advanced per actuation of trigger **204** will be substantially the same distance that cutting member **96** is retracted per actuation of trigger **204**. While suitable in some circumstances, such embodiments may require a surgeon to actuate trigger **204** several times before cutting member **96** is completely retracted. In view of the above, in various embodiments, first ratchet wheel **222** can have a pitch radius which is different than the pitch radius of second ratchet wheel **234**. In at least one embodiment, second ratchet wheel **234** can have a larger pitch radius than first ratchet wheel **222** such that cutting member **96** is retracted a distance per actuation of trigger **204** which is greater than the distance that cutting member **96** is advanced per actuation of trigger **204**. Stated another way, second ratchet assembly **212** can, at least in these embodiments, retract cutting member **96** at a rate which is greater than which it is advanced. In such embodiments, first ratchet assembly **210** can, owing to the slower advancing rate, provide a greater torque or advancing force to cutting member **96** while second ratchet assembly **212** can, owing to the faster retracting rate, reduce the time required for the surgeon to retract the cutting member.

While the term 'rate', as used above, is used to describe the distance that cutting member **96** can be advanced or retracted per actuation of trigger **204**, the term 'rate' is not so limited. In at least one embodiment, the term 'rate' can be used to describe the velocity and/or acceleration in which the cutting member is moved. In such embodiments, it may be desirable to have a cutting member which is advanced at a lower velocity and/or acceleration to better control the cutting member and retracted at a greater velocity and/or acceleration to reduce the time required to retract the cutting member. Furthermore, while the illustrated embodiments include ratchet assemblies for providing the different advancing and retracting rates, the invention is not so limited. On the contrary, other embodiments are envisioned which include spur gear trains, bevel gears, and/or other motion transmission devices.

In various embodiments, surgical instruments in accordance with the present invention may include a gearbox for increasing or decreasing the rotational speed of the drive shaft. In at least one embodiment, referring to FIG. **25**, surgical instrument **200** can further include gearbox **250** which can be operably positioned intermediate drive shaft **206** and ratchet assemblies **210** and **212**. In various embodiments, gearbox **250** can be used to 'gear down' the speed of drive shaft **206** such that shaft **206** turns at a slower speed than if gearbox **250** were not utilized. In alternative embodiments, a gearbox can be used to 'gear up' the speed of drive shaft **206** such that drive shaft **206** turns at a faster speed. In at least one embodiment, gearbox **250** can include at least one set of planetary gears for changing the speed of drive shaft **206**. In other various embodiments, a gearbox, such as gearbox **252** illustrated in FIGS. **21** and **22**, can include housing **253**, input gear **254** mounted to input shaft **256**, pinion gears **258**, and output gear **260** mounted to output shaft **262**. In such embodi-

ments, owing to the different pitch radii of input gear **254** and output gear **260**, input shaft **256** and output shaft **262** will rotate at different speeds. To facilitate the rotational movement of gears **254**, **258**, and **260** within housing **253**, gearbox **252** can further include various support plates **264**, spacers **266**, and pins **268** as illustrated in FIG. **22**. In addition to the above, gearbox **252** can also be used to convert the clockwise motion of input shaft **256**, for example, into counter-clockwise motion of output shaft **262**.

In various embodiments described above, trigger **204** of surgical instrument **200** can be slid between a first position in which it is operatively engaged with first ratchet assembly **210** and a second position in which it is operatively engaged with second ratchet assembly **212**. In at least one embodiment, firing drive **202** can be configured such that first pawl **220**, for example, is disengaged from first ratchet wheel **222** before second pawl **236** is engaged with second ratchet wheel **234**. In such embodiments, trigger **204** may be positioned in an intermediate position where it is not operably engaged with either first ratchet assembly **210** or second ratchet assembly **212**. In various embodiments, as a result, firing drive **202** can be in a 'free' state where the actuation of trigger **204** does not result in the rotation of drive shaft **206**. In alternative embodiments, firing drive **202** can be configured such that second pawl **236**, for example, is engaged with second ratchet wheel **234** before first pawl **220** is operatively disengaged from first ratchet wheel **222**. In such embodiments, trigger **204** may be positioned in an intermediate 'locked' state where trigger **204** cannot be actuated, thereby indicating to the surgeon that trigger **204** is not completely engaged with either one of the ratchet assemblies and trigger **204** requires further adjustment.

In various embodiments, surgical instrument **200** can include a device which biases trigger **204** into engagement with one of first ratchet assembly **210** and second ratchet assembly **212**. In at least one embodiment, referring to FIG. **33**, surgical instrument **200** can further include bistable compliant mechanism **270** which can bias trigger **204** out of an intermediate position described above and into engagement with either first ratchet assembly **210** and second ratchet assembly **212**. In various embodiments, bistable compliant mechanism **270** can include spring **272** and link **274**, where spring **272** can apply a biasing force to trigger **204** via link **274** such that the biasing force acts to move trigger **204** out of its intermediate position illustrated in FIG. **33** and into engagement with either first ratchet wheel **222** or second ratchet wheel **234**. More particularly, when trigger **204** is positioned in its intermediate position, spring **272** can be stretched to a length X**1** and, owing to the resiliency of spring **272**, spring **272** can seek to shorten itself to its unstretched length, or at least a length shorter than X**1**, such as length X**2** for example. In order for spring **272** to shorten itself to length X**2**, spring **272** can rotate link **274** about pin **275** where pin **275** can extend from and pivotably mount link **274** to surgical instrument housing **218**. More particularly, as the first end of spring **272** is mounted to pin **276** extending from housing **218** and the second end of spring **272** is mounted to pin **277** extending from link **274**, spring **272** can shorten itself by moving pin **277** closer to pin **276** which is most easily accomplished by rotating link **274** about pin **275**. As link **274** is rotated about pin **275**, the side walls of slot **278** in link **274** can be configured to engage pin **279** extending from trigger **204** and slide trigger **204** into engagement with first ratchet wheel **222** or second ratchet wheel **234**. In effect, the intermediate position of trigger **204** illustrated in FIG. **33** represents a dynamically unstable position and the positions of trigger **204** where trigger **204** is engaged with ratchet wheels **222** and **234** represent the dynamically stable positions of the firing drive system.

In various embodiments, as described above, surgical instruments in accordance with the present invention can include devices for rotating a drive shaft in a first direction in which the drive shaft advances a cutting member within an end effector, for example, and a second direction in which the drive shaft retracts the cutting member. In at least one embodiment, referring to FIGS. **31** and **32**, a surgical instrument can include transmission **280**, for example, which can allow a surgeon to select whether the drive shaft advances or retracts the cutting member. In various embodiments, transmission **280** can include housing **282**, internal input shaft **284**, external input shaft **285**, output drive shaft **286**, and switching mechanism **288**, where switching mechanism **288** can be configured to selectively engage internal input shaft **284** and external input shaft **285** with output shaft **286**. Although not illustrated, the surgical instrument can further include a trigger, for example, which is operatively engaged with external drive shaft **285** in order to rotate drive shaft **285** about axis **287** in a clockwise direction, for example. In at least one embodiment, transmission **280** can include pinion gears **292** rotatably mounted within housing **282**, input gear **293** fixedly mounted to external input shaft **285**, and output gear **294** mounted to output drive shaft **286**, where input gear **293** can be operably engaged with outer gear teeth **290** of pinion gears **292** such that the rotation of external shaft **285** is transmitted to pinion gears **292**.

In a first configuration of transmission **280**, output gear **294** can be operatively engaged with inner gear teeth **291** of pinion gears **292** such that the rotation of pinion gears **292** is transmitted to output drive shaft **286**. More particularly, output gear **294** can be operably engaged with output drive shaft **286** via splined end **296** such that output gear **294** drives output drive shaft **286** about axis **287**. In this first configuration, a clockwise rotation of external input shaft **285**, for example, can be converted into a counter-clockwise motion of output drive shaft **286**. In a second configuration of transmission **280**, output gear **294** can be disengaged from pinion gears **292** such that the rotation of external input shaft **285** is not transmitted to output drive shaft **286** via pinion gears **292**. In order to disengage output gear **294** from pinion gears **292**, internal drive shaft **284** can be slid relative to external drive shaft **285** such that input gear **297** contacts recess **298** in output gear **294** and pushes output gear **294** away from pinion gears **292**. In at least one embodiment, recess **298** can include teeth **299** which can be operatively engaged with input gear **297** of internal input shaft **284** such that the rotation of internal input shaft **284** is transmitted to output drive shaft **286**. In this second configuration of transmission **280**, a clockwise rotation of internal input shaft **284** can be directly transmitted to output drive shaft **286** such that output shaft **286** rotates in a clockwise direction as well. In order to reengage output gear **294** with pinion gears **292**, internal input gear **284** can be disengaged from output gear **294** to allow spring **281** to slide output gear **294** along splined end **296**.

In the embodiments described above, a surgeon can selectively move internal input shaft **284** relative to external input shaft **285** to place transmission **280** in either a forward or reversing configuration. In order to move input shaft **284**, in various embodiments, the surgical instrument can further include an actuator or trigger configured to translate internal input shaft **284**. In at least one embodiment, the surgical instrument can include a first actuator or trigger for rotating external input shaft **285** and a second actuator or trigger for translating internal shaft **284** relative to external shaft **285**. In

such embodiments, internal input shaft **284** can include splines **283** which can be slidably engaged with external input shaft **285** such that the rotation of external shaft **285** is transmitted to internal shaft **284** yet sliding motion is permitted therebetween. In at least one embodiment, transmission **280** can further include bearing **300** which can rotatably support input gear **293** and, when compressed between input gear **293** and housing **282**, provide a biasing force to keep input gear **293** operably engaged with pinion gears **292**. In various embodiments, output shaft **286** can include member **302** extending therefrom which can be configured to be received within recess **301** of housing **282** in order to reduce, or even eliminate, relative movement between output shaft **286** and housing **282**. In at least one embodiment, although not illustrated, transmission **280** may only have one pinion gear **292** and still operate in the manner described above.

In various embodiments, transmission **280** can also be configured to advance cutting member **96**, for example, at a different rate than which it is retracted. In at least one embodiment, referring to FIGS. **31** and **32**, the operative engagement between internal input shaft **284** and output shaft **286** can be used to advance cutting member **96** and, owing to the direct engagement between input gear **297** and output gear **294**, internal input shaft **284** and output shaft **286** can rotate in a 1:1 ratio, i.e., for every rotation of internal input shaft **284**, output shaft **286** is rotated once. In various embodiments, the operative engagement between external input shaft **285** and output shaft **286** can be used to retract cutting member **96** and, owing to the different pitch radii of input gear **293** and output gear **294** and their operative engagement with pinions **292**, external input shaft **285** and output shaft **286** can rotate in a ratio different than 1:1. In the illustrated embodiment, output shaft **286** can rotate at a faster speed than external input shaft **285** when they are mated via pinions **292**. In various embodiments, as a result, cutting member **96** can be translated at a faster rate when external input shaft **285** is operably engaged with output shaft **286** than when internal input shaft **284** is operably engaged with output shaft **286**.

The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

Preferably, the invention described herein will be processed before surgery. First, a new or used instrument is obtained and if necessary cleaned. The instrument can then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK bag. The container and instrument are then placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, or high-energy electrons. The radiation kills bacteria on the instrument and in the container. The sterilized instrument can then be stored in the sterile container. The sealed container keeps the instrument sterile until it is opened in the medical facility.

While this invention has been described as having exemplary designs, the present invention may be further modified within the spirit and scope of the disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles. Further, this application is intended to cover such departures from the present disclosure as come within known or customary practice in the art to which this invention pertains.

Over the years a variety of minimally invasive robotic (or "telesurgical") systems have been developed to increase surgical dexterity as well as to permit a surgeon to operate on a patient in an intuitive manner. Many of such systems are disclosed in the following U.S. patents which are each herein incorporated by reference in their respective entirety: U.S. Pat. No. 5,792,135, entitled "Articulated Surgical Instrument For Performing Minimally Invasive Surgery With Enhanced Dexterity and Sensitivity", U.S. Pat. No. 6,231,565, entitled "Robotic Arm DLUS For Performing Surgical Tasks", U.S. Pat. No. 6,783,524, entitled "Robotic Surgical Tool With Ultrasound Cauterizing and Cutting Instrument", U.S. Pat. No. 6,364,888, entitled "Alignment of Master and Slave In a Minimally Invasive Surgical Apparatus", U.S. Pat. No. 7,524,320, entitled "Mechanical Actuator Interface System For Robotic Surgical Tools", U.S. Pat. No. 7,691,098, entitled Platform Link Wrist Mechanism", U.S. Pat. No. 7,806,891, entitled "Repositioning and Reorientation of Master/Slave Relationship in Minimally Invasive Telesurgery", and U.S. Pat. No. 7,824,401, entitled "Surgical tool With Writed Monopolar Electrosurgical End Effectors". Many of such systems, however, have in the past been unable to generate the magnitude of forces required to effectively cut and fasten tissue.

FIG. **34** depicts one version of a master controller **1001** that may be used in connection with a robotic arm slave cart **1100** of the type depicted in FIG. **35**. Master controller **1001** and robotic arm slave cart **1100**, as well as their respective components and control systems are collectively referred to herein as a robotic system **1000**. Examples of such systems and devices are disclosed in U.S. Pat. No. 7,524,320 which has been herein incorporated by reference. Thus, various details of such devices will not be described in detail herein beyond that which may be necessary to understand various embodiments and forms of the present invention. As is known, the master controller **1001** generally includes master controllers (generally represented as **1003** in FIG. **34**) which are grasped by the surgeon and manipulated in space while the surgeon views the procedure via a stereo display **1002**. The master controllers **1001** generally comprise manual input devices which preferably move with multiple degrees of freedom, and which often further have an actuatable handle for actuating tools (for example, for closing grasping saws, applying an electrical potential to an electrode, or the like).

As can be seen in FIG. **35**, in one form, the robotic arm cart **1100** is configured to actuate a plurality of surgical tools, generally designated as **1200**. Various robotic surgery systems and methods employing master controller and robotic arm cart arrangements are disclosed in U.S. Pat. No. 6,132,368, entitled "Multi-Component Telepresence System and Method", the full disclosure of which is incorporated herein by reference. In various forms, the robotic arm cart **1100** includes a base **1002** from which, in the illustrated embodiment, three surgical tools **1200** are supported. In various forms, the surgical tools **1200** are each supported by a series of manually articulatable linkages, generally referred to as set-up joints **1104**, and a robotic manipulator **1106**. These

structures are herein illustrated with protective covers extending over much of the robotic linkage. These protective covers may be optional, and may be limited in size or entirely eliminated in some embodiments to minimize the inertia that is encountered by the servo mechanisms used to manipulate such devices, to limit the volume of moving components so as to avoid collisions, and to limit the overall weight of the cart **1100**. Cart **1100** will generally have dimensions suitable for transporting the cart **1100** between operating rooms. The cart **1100** may be configured to typically fit through standard operating room doors and onto standard hospital elevators. In various forms, the cart **1100** would preferably have a weight and include a wheel (or other transportation) system that allows the cart **1100** to be positioned adjacent an operating table by a single attendant.

Referring now to FIG. **36**, in at least one form, robotic manipulators **1106** may include a linkage **1108** that constrains movement of the surgical tool **1200**. In various embodiments, linkage **1108** includes rigid links coupled together by rotational joints in a parallelogram arrangement so that the surgical tool **1200** rotates around a point in space **1110**, as more fully described in issued U.S. Pat. No. 5,817,084, the full disclosure of which is herein incorporated by reference. The parallelogram arrangement constrains rotation to pivoting about an axis **1112***a*, sometimes called the pitch axis. The links supporting the parallelogram linkage are pivotally mounted to set-up joints **1104** (FIG. **35**) so that the surgical tool **1200** further rotates about an axis **1112***b*, sometimes called the yaw axis. The pitch and yaw axes **1112***a*, **1112***b* intersect at the remote center **1114**, which is aligned along a shaft **1208** of the surgical tool **1200**. The surgical tool **1200** may have further degrees of driven freedom as supported by manipulator **1106**, including sliding motion of the surgical tool **1200** along the longitudinal tool axis "LT-LT". As the surgical tool **1200** slides along the tool axis LT-LT relative to manipulator **1106** (arrow **1112***c*), remote center **1114** remains fixed relative to base **1116** of manipulator **1106**. Hence, the entire manipulator is generally moved to re-position remote center **1114**. Linkage **1108** of manipulator **1106** is driven by a series of motors **1120**. These motors actively move linkage **1108** in response to commands from a processor of a control system. As will be discussed in further detail below, motors **1120** are also employed to manipulate the surgical tool **1200**.

An alternative set-up joint structure is illustrated in FIG. **37**. In this embodiment, a surgical tool **1200** is supported by an alternative manipulator structure **1106'** between two tissue manipulation tools. Those of ordinary skill in the art will appreciate that various embodiments of the present invention may incorporate a wide variety of alternative robotic structures, including those described in U.S. Pat. No. 5,878,193, entitled "Automated Endoscope System For Optimal Positioning", the full disclosure of which is incorporated herein by reference. Additionally, while the data communication between a robotic component and the processor of the robotic surgical system is primarily described herein with reference to communication between the surgical tool **1200** and the master controller **1001**, it should be understood that similar communication may take place between circuitry of a manipulator, a set-up joint, an endoscope or other image capture device, or the like, and the processor of the robotic surgical system for component compatibility verification, component-type identification, component calibration (such as off-set or the like) communication, confirmation of coupling of the component to the robotic surgical system, or the like.

An exemplary non-limiting surgical tool **1200** that is well-adapted for use with a robotic system **1000** that has a tool drive assembly **1010** (FIG. **39**) that is operatively coupled to a master controller **1001** that is operable by inputs from an operator (i.e., a surgeon) is depicted in FIG. **38**. As can be seen in that Figure, the surgical tool **1200** includes a surgical end effector **2012** that comprises an endocutter. In at least one form, the surgical tool **1200** generally includes an elongated shaft assembly **2008** that has a proximal closure tube **2040** and a distal closure tube **2042** that are coupled together by an articulation joint **2011**. The surgical tool **1200** is operably coupled to the manipulator by a tool mounting portion, generally designated as **1300**. The surgical tool **1200** further includes an interface **1230** which mechanically and electrically couples the tool mounting portion **1300** to the manipulator. One form of interface **1230** is illustrated in FIGS. **39-43**. In various embodiments, the tool mounting portion **1300** includes a tool mounting plate **1302** that operably supports a plurality of (four are shown in FIG. **43**) rotatable body portions, driven discs or elements **1304**, that each include a pair of pins **1306** that extend from a surface of the driven element **1304**. One pin **1306** is closer to an axis of rotation of each driven elements **1304** than the other pin **1306** on the same driven element **1304**, which helps to ensure positive angular alignment of the driven element **1304**. Interface **1230** includes an adaptor portion **1240** that is configured to mountingly engage the mounting plate **1302** as will be further discussed below. The adaptor portion **1240** may include an array of electrical connecting pins **1242** (FIG. **41**) which may be coupled to a memory structure by a circuit board within the tool mounting portion **1300**. While interface **1230** is described herein with reference to mechanical, electrical, and magnetic coupling elements, it should be understood that a wide variety of telemetry modalities might be used, including infrared, inductive coupling, or the like.

As can be seen in FIGS. **39-42**, the adapter portion **1240** generally includes a tool side **1244** and a holder side **1246**. In various forms, a plurality of rotatable bodies **1250** are mounted to a floating plate **1248** which has a limited range of movement relative to the surrounding adaptor structure normal to the major surfaces of the adaptor **1240**. Axial movement of the floating plate **1248** helps decouple the rotatable bodies **1250** from the tool mounting portion **1300** when the levers **1303** along the sides of the tool mounting portion housing **1301** are actuated (See FIG. **38**). Other mechanisms/arrangements may be employed for releasably coupling the tool mounting portion **1300** to the adaptor **1240**. In at least one form, rotatable bodies **1250** are resiliently mounted to floating plate **1248** by resilient radial members which extend into a circumferential indentation about the rotatable bodies **1250**. The rotatable bodies **1250** can move axially relative to plate **1248** by deflection of these resilient structures. When disposed in a first axial position (toward tool side **1244**) the rotatable bodies **1250** are free to rotate without angular limitation. However, as the rotatable bodies **1250** move axially toward tool side **1244**, tabs **1252** (extending radially from the rotatable bodies **1250**) laterally engage detents on the floating plates so as to limit angular rotation of the rotatable bodies **1250** about their axes. This limited rotation can be used to help drivingly engage the rotatable bodies **1250** with drive pins **1272** of a corresponding tool holder portion **1270** of the robotic system **1000**, as the drive pins **1272** will push the rotatable bodies **1250** into the limited rotation position until the pins **1234** are aligned with (and slide into) openings **1256'**. Openings **1256** on the tool side **1244** and openings **1256'** on the holder side **1246** of rotatable bodies **1250** are configured to accurately align the driven elements **1304** (FIG. **43**) of the

tool mounting portion **1300** with the drive elements **1271** of the tool holder **1270**. As described above regarding inner and outer pins **1306** of driven elements **1304**, the openings **1256**, **1256'** are at differing distances from the axis of rotation on their respective rotatable bodies **1250** so as to ensure that the alignment is not **180** degrees from its intended position. Additionally, each of the openings **1256** is slightly radially elongated so as to fittingly receive the pins **1306** in the circumferential orientation. This allows the pins **1306** to slide radially within the openings **1256**, **1256'** and accommodate some axial misalignment between the tool **1200** and tool holder **1270**, while minimizing any angular misalignment and backlash between the drive and driven elements. Openings **1256** on the tool side **1244** are offset by about **90** degrees from the openings **1256'** (shown in broken lines) on the holder side **1246**, as can be seen most clearly in FIG. **42**.

Various embodiments may further include an array of electrical connector pins **1242** located on holder side **1246** of adaptor **1240**, and the tool side **1244** of the adaptor **1240** may include slots **1258** (FIG. **42**) for receiving a pin array (not shown) from the tool mounting portion **1300**. In addition to transmitting electrical signals between the surgical tool **1200** and the tool holder **1270**, at least some of these electrical connections may be coupled to an adaptor memory device **1260** (FIG. **41**) by a circuit board of the adaptor **1240**.

A detachable latch arrangement **1239** may be employed to releasably affix the adaptor **1240** to the tool holder **1270**. As used herein, the term "tool drive assembly" when used in the context of the robotic system **1000**, at least encompasses various embodiments of the adapter **1240** and tool holder **1270** and which has been generally designated as **1010** in FIG. **39**. For example, as can be seen in FIG. **39**, the tool holder **1270** may include a first latch pin arrangement **1274** that is sized to be received in corresponding clevis slots **1241** provided in the adaptor **1240**. In addition, the tool holder **1270** may further have second latch pins **1276** that are sized to be retained in corresponding latch clevises **1243** in the adaptor **1240**. See FIG. **41**. In at least one form, a latch assembly **1245** is movably supported on the adapter **1240** and is biasable between a first latched position wherein the latch pins **1276** are retained within their respective latch clevis **1243** and an unlatched position wherein the second latch pins **1276** may be into or removed from the latch clevises **1243**. A spring or springs (not shown) are employed to bias the latch assembly into the latched position. A lip on the tool side **1244** of adaptor **1240** may slidably receive laterally extending tabs of tool mounting housing **1301**.

Turning next to FIGS. **43-50**, in at least one embodiment, the surgical tool **1200** includes a surgical end effector **2012** that comprises in this example, among other things, at least one component **2024** that is selectively movable between first and second positions relative to at least one other component **2022** in response to various control motions applied thereto as will be discussed in further detail below. In various embodiments, component **2022** comprises an elongated channel **2022** configured to operably support a surgical staple cartridge **2034** therein and component **2024** comprises a pivotally translatable clamping member, such as an anvil **2024**. Various embodiments of the surgical end effector **2012** are configured to maintain the anvil **2024** and elongated channel **2022** at a spacing that assures effective stapling and severing of tissue clamped in the surgical end effector **2012**. As can be seen in FIG. **49**, the surgical end effector **2012** further includes a cutting instrument **2032** and a sled **2033**. The cutting instrument **2032** may be, for example, a knife. The surgical staple cartridge **2034** operably houses a plurality of surgical staples (not show) therein that are supported on movable staple drivers (not shown). As the cutting instrument **2032** is driven distally through a centrally-disposed slot (not shown) in the surgical staple cartridge **2034**, it forces the sled **2033** distally as well. As the sled **2033** is driven distally, its "wedge-shaped" configuration contacts the movable staple drivers and drives them vertically toward the closed anvil **2024**. The surgical staples are formed as they are driven into the forming surface located on the underside of the anvil **2024**. The sled **2033** may be part of the surgical staple cartridge **2034**, such that when the cutting instrument **2032** is retracted following the cutting operation, the sled **2033** does not retract. The anvil **2024** may be pivotably opened and closed at a pivot point **2025** located at the proximal end of the elongated channel **2022**. The anvil **2024** may also include a tab **2027** at its proximal end that interacts with a component of the mechanical closure system (described further below) to facilitate the opening of the anvil **2024**. The elongated channel **2022** and the anvil **2024** may be made of an electrically conductive material (such as metal) so that they may serve as part of an antenna that communicates with sensor(s) in the end effector, as described above. The surgical staple cartridge **2034** could be made of a nonconductive material (such as plastic) and the sensor may be connected to or disposed in the surgical staple cartridge **2034**, as was also described above.

As can be seen in FIGS. **43-50**, the surgical end effector **2012** is attached to the tool mounting portion **1300** by an elongated shaft assembly **2008** according to various embodiments. As shown in the illustrated embodiment, the shaft assembly **2008** includes an articulation joint generally indicated as **2011** that enables the surgical end effector **2012** to be selectively articulated about an articulation axis AA-AA that is substantially transverse to a longitudinal tool axis LT-LT. See FIG. **44**. In other embodiments, the articulation joint is omitted. In various embodiments, the shaft assembly **2008** may include a closure tube assembly **2009** that comprises a proximal closure tube **2040** and a distal closure tube **2042** that are pivotably linked by a pivot links **2044** and operably supported on a spine assembly generally depicted as **2049**. In the illustrated embodiment, the spine assembly **2049** comprises a distal spine portion **2050** that is attached to the elongated channel **2022** and is pivotally coupled to the proximal spine portion **2052**. The closure tube assembly **2009** is configured to axially slide on the spine assembly **2049** in response to actuation motions applied thereto. The distal closure tube **2042** includes an opening **2045** into which the tab **2027** on the anvil **2024** is inserted in order to facilitate opening of the anvil **2024** as the distal closure tube **2042** is moved axially in the proximal direction "PD". The closure tubes **2040**, **2042** may be made of electrically conductive material (such as metal) so that they may serve as part of the antenna, as described above. Components of the main drive shaft assembly (e.g., the drive shafts **2048**, **2050**) may be made of a nonconductive material (such as plastic).

In use, it may be desirable to rotate the surgical end effector **2012** about the longitudinal tool axis LT-LT. In at least one embodiment, the tool mounting portion **1300** includes a rotational transmission assembly **2069** that is configured to receive a corresponding rotary output motion from the tool drive assembly **1010** of the robotic system **1000** and convert that rotary output motion to a rotary control motion for rotating the elongated shaft assembly **2008** (and surgical end effector **2012**) about the longitudinal tool axis LT-LT. In various embodiments, for example, the proximal end **2060** of the proximal closure tube **2040** is rotatably supported on the tool mounting plate **1302** of the tool mounting portion **1300** by a forward support cradle **1309** and a closure sled **2100** that is also movably supported on the tool mounting plate **1302**. In at

least one form, the rotational transmission assembly **2069** includes a tube gear segment **2062** that is formed on (or attached to) the proximal end **2060** of the proximal closure tube **2040** for operable engagement by a rotational gear assembly **2070** that is operably supported on the tool mounting plate **1302**. As can be seen in FIG. **46**, the rotational gear assembly **2070**, in at least one embodiment, comprises a rotation drive gear **2072** that is coupled to a corresponding first one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **1302** when the tool mounting portion **1300** is coupled to the tool drive assembly **1010**. See FIG. **43**. The rotational gear assembly **2070** further comprises a rotary driven gear **2074** that is rotatably supported on the tool mounting plate **1302** in meshing engagement with the tube gear segment **2062** and the rotation drive gear **2072**. Application of a first rotary output motion from the tool drive assembly **1010** of the robotic system **1000** to the corresponding driven element **1304** will thereby cause rotation of the rotation drive gear **2072**. Rotation of the rotation drive gear **2072** ultimately results in the rotation of the elongated shaft assembly **2008** (and the surgical end effector **2012**) about the longitudinal tool axis LT-LT (represented by arrow "R" in FIG. **46**). It will be appreciated that the application of a rotary output motion from the tool drive assembly **1010** in one direction will result in the rotation of the elongated shaft assembly **2008** and surgical end effector **2012** about the longitudinal tool axis LT-LT in a first direction and an application of the rotary output motion in an opposite direction will result in the rotation of the elongated shaft assembly **2008** and surgical end effector **2012** in a second direction that is opposite to the first direction.

In at least one embodiment, the closure of the anvil **2024** relative to the staple cartridge **2034** is accomplished by axially moving the closure tube assembly **2009** in the distal direction "DD" on the spine assembly **2049**. As indicated above, in various embodiments, the proximal end **2060** of the proximal closure tube **2040** is supported by the closure sled **2100** which comprises a portion of a closure transmission, generally depicted as **2099**. In at least one form, the closure sled **2100** is configured to support the closure tube **2009** on the tool mounting plate **1320** such that the proximal closure tube **2040** can rotate relative to the closure sled **2100**, yet travel axially with the closure sled **2100**. In particular, as can be seen in FIG. **51**, the closure sled **2100** has an upstanding tab **2101** that extends into a radial groove **2063** in the proximal end portion of the proximal closure tube **2040**. In addition, as can be seen in FIGS. **51** and **52**, the closure sled **2100** has a tab portion **2102** that extends through a slot **1305** in the tool mounting plate **1302**. The tab portion **2102** is configured to retain the closure sled **2100** in sliding engagement with the tool mounting plate **1302**. In various embodiments, the closure sled **2100** has an upstanding portion **2104** that has a closure rack gear **2106** formed thereon. The closure rack gear **2106** is configured for driving engagement with a closure gear assembly **2110**. See FIG. **48**.

In various forms, the closure gear assembly **2110** includes a closure spur gear **2112** that is coupled to a corresponding second one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **1302**. See FIG. **43**. Thus, application of a second rotary output motion from the tool drive assembly **1010** of the robotic system **1000** to the corresponding second driven element **1304** will cause rotation of the closure spur gear **2112** when the tool mounting portion **1300** is coupled to the tool drive assembly **1010**. The closure gear assembly **2110** further includes a closure reduction gear set **2114** that is supported in meshing engagement with the closure spur gear **2112**. As can be seen in FIGS. **47** and **48**, the closure reduction gear set **2114** includes a driven gear **2116** that is rotatably supported in meshing engagement with the closure spur gear **2112**. The closure reduction gear set **2114** further includes a first closure drive gear **2118** that is in meshing engagement with a second closure drive gear **2120** that is rotatably supported on the tool mounting plate **1302** in meshing engagement with the closure rack gear **2106**. Thus, application of a second rotary output motion from the tool drive assembly **1010** of the robotic system **1000** to the corresponding second driven element **1304** will cause rotation of the closure spur gear **2112** and the closure transmission **2110** and ultimately drive the closure sled **2100** and closure tube assembly **2009** axially. The axial direction in which the closure tube assembly **2009** moves ultimately depends upon the direction in which the second driven element **1304** is rotated. For example, in response to one rotary output motion received from the tool drive assembly **1010** of the robotic system **1000**, the closure sled **2100** will be driven in the distal direction "DD" and ultimately drive the closure tube assembly **1009** in the distal direction. As the distal closure tube **2042** is driven distally, the end of the closure tube segment **2042** will engage a portion of the anvil **2024** and cause the anvil **2024** to pivot to a closed position. Upon application of an "opening" out put motion from the tool drive assembly **1010** of the robotic system **1000**, the closure sled **2100** and shaft assembly **2008** will be driven in the proximal direction "PD". As the distal closure tube **2042** is driven in the proximal direction, the opening **2045** therein interacts with the tab **2027** on the anvil **2024** to facilitate the opening thereof. In various embodiments, a spring (not shown) may be employed to bias the anvil to the open position when the distal closure tube **2042** has been moved to its starting position. In various embodiments, the various gears of the closure gear assembly **2110** are sized to generate the necessary closure forces needed to satisfactorily close the anvil **2024** onto the tissue to be cut and stapled by the surgical end effector **2012**. For example, the gears of the closure transmission **2110** may be sized to generate approximately 70-120 pounds.

In various embodiments, the cutting instrument **2032** is driven through the surgical end effector **2012** by a knife bar **2200**. See FIGS. **49** and **51**. In at least one form, the knife bar **2200** may be fabricated from, for example, stainless steel or other similar material and has a substantially rectangular cross-sectional shape. Such knife bar configuration is sufficiently rigid to push the cutting instrument **2032** through tissue clamped in the surgical end effector **2012**, while still being flexible enough to enable the surgical end effector **2012** to articulate relative to the proximal closure tube **2040** and the proximal spine portion **2052** about the articulation axis AA-AA as will be discussed in further detail below. As can be seen in FIGS. **52** and **53**, the proximal spine portion **2052** has a rectangular-shaped passage **2054** extending therethrough to provide support to the knife bar **2200** as it is axially pushed therethrough. The proximal spine portion **2052** has a proximal end **2056** that is rotatably mounted to a spine mounting bracket **2057** attached to the tool mounting plate **1032**. See FIG. **51**. Such arrangement permits the proximal spine portion **2052** to rotate, but not move axially, within the proximal closure tube **2040**.

As shown in FIG. **49**, the distal end **2202** of the knife bar **2200** is attached to the cutting instrument **2032**. The proximal end **2204** of the knife bar **2200** is rotatably affixed to a knife rack gear **2206** such that the knife bar **2200** is free to rotate relative to the knife rack gear **2206**. See FIG. **51**. As can be seen in FIGS. **45-50**, the knife rack gear **2206** is slidably supported within a rack housing **2210** that is attached to the tool mounting plate **1302** such that the knife rack gear **2206** is

retained in meshing engagement with a knife gear assembly **2220**. More specifically and with reference to FIG. **48**, in at least one embodiment, the knife gear assembly **2220** includes a knife spur gear **2222** that is coupled to a corresponding third one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **1302**. See FIG. **43**. Thus, application of another rotary output motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding third driven element **1304** will cause rotation of the knife spur gear **2222**. The knife gear assembly **2220** further includes a knife gear reduction set **2224** that includes a first knife driven gear **2226** and a second knife drive gear **2228**. The knife gear reduction set **2224** is rotatably mounted to the tool mounting plate **1302** such that the firs knife driven gear **2226** is in meshing engagement with the knife spur gear **2222**. Likewise, the second knife drive gear **2228** is in meshing engagement with a third knife drive gear **2230** that is rotatably supported on the tool mounting plate **1302** in meshing engagement with the knife rack gear **2206**. In various embodiments, the gears of the knife gear assembly **2220** are sized to generate the forces needed to drive the cutting element **2032** through the tissue clamped in the surgical end effector **2012** and actuate the staples therein. For example, the gears of the knife drive assembly **2230** may be sized to generate approximately 40 to 100 pounds. It will be appreciated that the application of a rotary output motion from the tool drive assembly **1010** in one direction will result in the axial movement of the cutting instrument **2032** in a distal direction and application of the rotary output motion in an opposite direction will result in the axial travel of the cutting instrument **2032** in a proximal direction.

In various embodiments, the surgical tool **1200** employs and articulation system **2007** that includes an articulation joint **2011** that enables the surgical end effector **2012** to be articulated about an articulation axis AA-AA that is substantially transverse to the longitudinal tool axis LT-LT. In at least one embodiment, the surgical tool **1200** includes first and second articulation bars **2250***a*, **2250***b* that are slidably supported within corresponding passages **2053** provided through the proximal spine portion **2052**. See FIGS. **51** and **53**. In at least one form, the first and second articulation bars **2250***a*, **2250***b* are actuated by an articulation transmission generally designated as **2249** that is operably supported on the tool mounting plate **1032**. Each of the articulation bars **2250***a*, **2250***b* has a proximal end **2252** that has a guide rod protruding therefrom which extend laterally through a corresponding slot in the proximal end portion of the proximal spine portion **2052** and into a corresponding arcuate slot in an articulation nut **2260** which comprises a portion of the articulation transmission. FIG. **52** illustrates articulation bar **2250***a*. It will be understood that articulation bar **2250***b* is similarly constructed. As can be seen in FIG. **52**, for example, the articulation bar **2250***a* has a guide rod **2254** which extends laterally through a corresponding slot **2058** in the proximal end portion **2056** of the distal spine portion **2050** and into a corresponding arcuate slot **2262** in the articulation nut **2260**. In addition, the articulation bar **2250***a* has a distal end **2251***a* that is pivotally coupled to the distal spine portion **2050** by, for example, a pin **2253***a* and articulation bar **2250***b* has a distal end **2251***b* that is pivotally coupled to the distal spine portion **2050** by, for example, a pin **2253***b*. In particular, the articulation bar **2250***a* is laterally offset in a first lateral direction from the longitudinal tool axis LT-LT and the articulation bar **2250***b* is laterally offset in a second lateral direction from the longitudinal tool axis LT-LT. Thus, axial movement of the articulation bars **2250***a* and **2250***b* in opposing directions will result in the articulation of the distal spine portion **2050** as well as the surgical end effector **2012** attached thereto about the articulation axis AA-AA as will be discussed in further detail below.

Articulation of the surgical end effector **2012** is controlled by rotating the articulation nut **2260** about the longitudinal tool axis LT-LT. The articulation nut **2260** is rotatably journaled on the proximal end portion **2056** of the distal spine portion **2050** and is rotatably driven thereon by an articulation gear assembly **2270**. More specifically and with reference to FIG. **46**, in at least one embodiment, the articulation gear assembly **2270** includes an articulation spur gear **2272** that is coupled to a corresponding fourth one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **1302**. See FIG. **43**. Thus, application of another rotary input motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding fourth driven element **1304** will cause rotation of the articulation spur gear **2272** when the interface **1230** is coupled to the tool holder **1270**. An articulation drive gear **2274** is rotatably supported on the tool mounting plate **1302** in meshing engagement with the articulation spur gear **2272** and a gear portion **2264** of the articulation nut **2260** as shown. As can be seen in FIGS. **51** and **52**, the articulation nut **2260** has a shoulder **2266** formed thereon that defines an annular groove **2267** for receiving retaining posts **2268** therein. Retaining posts **2268** are attached to the tool mounting plate **1302** and serve to prevent the articulation nut **2260** from moving axially on the proximal spine portion **2052** while maintaining the ability to be rotated relative thereto. Thus, rotation of the articulation nut **2260** in a first direction, will result in the axial movement of the articulation bar **2250***a* in a distal direction "DD" and the axial movement of the articulation bar **2250***b* in a proximal direction "PD" because of the interaction of the guide rods **2254** with the spiral slots **2262** in the articulation gear **2260**. Similarly, rotation of the articulation nut **2260** in a second direction that is opposite to the first direction will result in the axial movement of the articulation bar **2250***a* in the proximal direction "PD" as well as cause articulation bar **2250***b* to axially move in the distal direction "DD". Thus, the surgical end effector **2012** may be selectively articulated about articulation axis "AA-AA" in a first direction "FD" by simultaneously moving the articulation bar **2250***a* in the distal direction "DD" and the articulation bar **2250***b* in the proximal direction "PD". Likewise, the surgical end effector **2012** may be selectively articulated about the articulation axis "AA-AA" in a second direction "SD" by simultaneously moving the articulation bar **2250***a* in the proximal direction "PD" and the articulation bar **2250***b* in the distal direction "DD." See FIG. **44**.

The tool embodiment described above employs an interface arrangement that is particularly well-suited for mounting the robotically controllable medical tool onto at least one form of robotic arm arrangement that generates at least four different rotary control motions. Those of ordinary skill in the art will appreciate that such rotary output motions may be selectively controlled through the programmable control systems employed by the robotic system/controller. For example, the tool arrangement described above may be well-suited for use with those robotic systems manufactured by Intuitive Surgical, Inc. of Sunnyvale, Calif., U.S.A., many of which may be described in detail in various patents incorporated herein by reference. The unique and novel aspects of various embodiments of the present invention serve to utilize the rotary output motions supplied by the robotic system to generate specific control motions having sufficient magnitudes that enable end effectors to cut and staple tissue. Thus, the unique arrangements and principles of various embodi-

ments of the present invention may enable a variety of different forms of the tool systems disclosed and claimed herein to be effectively employed in connection with other types and forms of robotic systems that supply programmed rotary or other output motions. In addition, as will become further apparent as the present Detailed Description proceeds, various end effector embodiments of the present invention that require other forms of actuation motions may also be effectively actuated utilizing one or more of the control motions generated by the robotic system.

FIGS. **55-59** illustrate yet another surgical tool **2300** that may be effectively employed in connection with the robotic system **1000** that has a tool drive assembly that is operably coupled to a controller of the robotic system that is operable by inputs from an operator and which is configured to provide at least one rotary output motion to at least one rotatable body portion supported on the tool drive assembly. In various forms, the surgical tool **2300** includes a surgical end effector **2312** that includes an elongated channel **2322** and a pivotally translatable clamping member, such as an anvil **2324**, which are maintained at a spacing that assures effective stapling and severing of tissue clamped in the surgical end effector **2312**. As shown in the illustrated embodiment, the surgical end effector **2312** may include, in addition to the previously-mentioned elongated channel **2322** and anvil **2324**, a cutting instrument **2332** that has a sled portion **2333** formed thereon, a surgical staple cartridge **2334** that is seated in the elongated channel **2322**, and a rotary end effector drive shaft **2336** that has a helical screw thread formed thereon. The cutting instrument **2332** may be, for example, a knife. As will be discussed in further detail below, rotation of the end effector drive shaft **2336** will cause the cutting instrument **2332** and sled portion **2333** to axially travel through the surgical staple cartridge **2334** to move between a starting position and an ending position. The direction of axial travel of the cutting instrument **2332** depends upon the direction in which the end effector drive shaft **2336** is rotated. The anvil **2324** may be pivotably opened and closed at a pivot point **2325** connected to the proximate end of the elongated channel **2322**. The anvil **2324** may also include a tab **2327** at its proximate end that operably interfaces with a component of the mechanical closure system (described further below) to open and close the anvil **2324**. When the end effector drive shaft **2336** is rotated, the cutting instrument **2332** and sled **2333** will travel longitudinally through the surgical staple cartridge **2334** from the starting position to the ending position, thereby cutting tissue clamped within the surgical end effector **2312**. The movement of the sled **2333** through the surgical staple cartridge **2334** causes the staples therein to be driven through the severed tissue and against the closed anvil **2324**, which turns the staples to fasten the severed tissue. In one form, the elongated channel **2322** and the anvil **2324** may be made of an electrically conductive material (such as metal) so that they may serve as part of the antenna that communicates with sensor(s) in the end effector, as described above. The surgical staple cartridge **2334** could be made of a nonconductive material (such as plastic) and the sensor may be connected to or disposed in the surgical staple cartridge **2334**, as described above.

It should be noted that although the embodiments of the surgical tool **2300** described herein employ a surgical end effector **2312** that staples the severed tissue, in other embodiments different techniques for fastening or sealing the severed tissue may be used. For example, end effectors that use RF energy or adhesives to fasten the severed tissue may also be used. U.S. Pat. No. 5,709,680, entitled "Electrosurgical Hemostatic Device" to Yates et al., and U.S. Pat. No. 5,688,270, entitled "Electrosurgical Hemostatic Device With Recessed And/Or Offset Electrodes" to Yates et al., which are incorporated herein by reference, discloses cutting instruments that use RF energy to fasten the severed tissue. U.S. patent application Ser. No. 11/267,811 to Morgan et al., now U.S. Pat. No. 7,673,783 and U.S. patent application Ser. No. 11/267,383 to Shelton et al., now U.S. Pat. No. 7,607,557 which are also incorporated herein by reference, disclose cutting instruments that use adhesives to fasten the severed tissue. Accordingly, although the description herein refers to cutting/stapling operations and the like, it should be recognized that this is an exemplary embodiment and is not meant to be limiting. Other tissue-fastening techniques may also be used.

In the illustrated embodiment, the surgical end effector **2312** is coupled to an elongated shaft assembly **2308** that is coupled to a tool mounting portion **2460** and defines a longitudinal tool axis LT-LT. In this embodiment, the elongated shaft assembly **2308** does not include an articulation joint. Those of ordinary skill in the art will understand that other embodiments may have an articulation joint therein. In at least one embodiment, the elongated shaft assembly **2308** comprises a hollow outer tube **2340** that is rotatably supported on a tool mounting plate **2462** of a tool mounting portion **2460** as will be discussed in further detail below. In various embodiments, the elongated shaft assembly **2308** further includes a distal spine shaft **2350**. Distal spine shaft **2350** has a distal end portion **2354** that is coupled to, or otherwise integrally formed with, a distal stationary base portion **2360** that is non-movably coupled to the channel **2322**. See FIGS. **56-58**.

As shown in FIG. **56**, the distal spine shaft **2350** has a proximal end portion **2351** that is slidably received within a slot **2355** in a proximal spine shaft **2353** that is non-movably supported within the hollow outer tube **2340** by at least one support collar **2357**. As can be further seen in FIGS. **56** and **57**, the surgical tool **2300** includes a closure tube **2370** that is constrained to only move axially relative to the distal stationary base portion **2360**. The closure tube **2370** has a proximal end **2372** that has an internal thread **2374** formed therein that is in threaded engagement with a transmission arrangement, generally depicted as **2375** that is operably supported on the tool mounting plate **2462**. In various forms, the transmission arrangement **2375** includes a rotary drive shaft assembly, generally designated as **2381**. When rotated, the rotary drive shaft assembly **2381** will cause the closure tube **2370** to move axially as will be describe in further detail below. In at least one form, the rotary drive shaft assembly **2381** includes a closure drive nut **2382** of a closure clutch assembly generally designated as **2380**. More specifically, the closure drive nut **2382** has a proximal end portion **2384** that is rotatably supported relative to the outer tube **2340** and is in threaded engagement with the closure tube **2370**. For assembly purposes, the proximal end portion **2384** may be threadably attached to a retention ring **2386**. Retention ring **2386**, in cooperation with an end **2387** of the closure drive nut **2382**, defines an annular slot **2388** into which a shoulder **2392** of a locking collar **2390** extends. The locking collar **2390** is non-movably attached (e.g., welded, glued, etc.) to the end of the outer tube **2340**. Such arrangement serves to affix the closure drive nut **2382** to the outer tube **2340** while enabling the closure drive nut **2382** to rotate relative to the outer tube **2340**. The closure drive nut **2382** further has a distal end **2383** that has a threaded portion **2385** that threadably engages the internal thread **2374** of the closure tube **2370**. Thus, rotation of the closure drive nut **2382** will cause the closure tube **2370** to move axially as represented by arrow "D" in FIG. **57**.

Closure of the anvil **2324** and actuation of the cutting instrument **2332** are accomplished by control motions that are transmitted by a hollow drive sleeve **2400**. As can be seen in FIGS. **56** and **57**, the hollow drive sleeve **2400** is rotatably and slidably received on the distal spine shaft **2350**. The drive sleeve **2400** has a proximal end portion **2401** that is rotatably mounted to the proximal spine shaft **2353** that protrudes from the tool mounting portion **2460** such that the drive sleeve **2400** may rotate relative thereto. See FIG. **56**. As can also be seen in FIGS. **56-58**, the drive sleeve **2400** is rotated about the longitudinal tool axis "LT-LT" by a drive shaft **2440**. The drive shaft **2440** has a drive gear **2444** that is attached to its distal end **2442** and is in meshing engagement with a driven gear **2450** that is attached to the drive sleeve **2400**.

The drive sleeve **2400** further has a distal end portion **2402** that is coupled to a closure clutch **2410** portion of the closure clutch assembly **2380** that has a proximal face **2412** and a distal face **2414**. The proximal face **2412** has a series of proximal teeth **2416** formed thereon that are adapted for selective engagement with corresponding proximal teeth cavities **2418** formed in the proximal end portion **2384** of the closure drive nut **2382**. Thus, when the proximal teeth **2416** are in meshing engagement with the proximal teeth cavities **2418** in the closure drive nut **2382**, rotation of the drive sleeve **2400** will result in rotation of the closure drive nut **2382** and ultimately cause the closure tube **2370** to move axially as will be discussed in further detail below.

As can be most particularly seen in FIGS. **56** and **57**, the distal face **2414** of the drive clutch portion **2410** has a series of distal teeth **2415** formed thereon that are adapted for selective engagement with corresponding distal teeth cavities **2426** formed in a face plate portion **2424** of a knife drive shaft assembly **2420**. In various embodiments, the knife drive shaft assembly **2420** comprises a hollow knife shaft segment **2430** that is rotatably received on a corresponding portion of the distal spine shaft **2350** that is attached to or protrudes from the stationary base **2360**. When the distal teeth **2415** of the closure clutch portion **2410** are in meshing engagement with the distal teeth cavities **2426** in the face plate portion **2424**, rotation of the drive sleeve **2400** will result in rotation of the drive shaft segment **2430** about the stationary shaft **2350**. As can be seen in FIGS. **56-58**, a knife drive gear **2432** is attached to the drive shaft segment **2430** and is meshing engagement with a drive knife gear **2434** that is attached to the end effector drive shaft **2336**. Thus, rotation of the drive shaft segment **2430** will result in the rotation of the end effector drive shaft **2336** to drive the cutting instrument **2332** and sled **2333** distally through the surgical staple cartridge **2334** to cut and staple tissue clamped within the surgical end effector **2312**. The sled **2333** may be made of, for example, plastic, and may have a sloped distal surface. As the sled **2333** traverses the elongated channel **2322**, the sloped forward surface of the sled **2333** pushes up or "drive" the staples in the surgical staple cartridge **2334** through the clamped tissue and against the anvil **2324**. The anvil **2324** turns or "forms" the staples, thereby stapling the severed tissue. As used herein, the term "fire" refers to the initiation of actions required to drive the cutting instrument and sled portion in a distal direction through the surgical staple cartridge to cut the tissue clamped in the surgical end effector and drive the staples through the severed tissue.

In use, it may be desirable to rotate the surgical end effector **2312** about the longitudinal tool axis LT-LT. In at least one embodiment, the transmission arrangement **2375** includes a rotational transmission assembly **2465** that is configured to receive a corresponding rotary output motion from the tool drive assembly **1010** of the robotic system **1000** and convert that rotary output motion to a rotary control motion for rotating the elongated shaft assembly **2308** (and surgical end effector **2312**) about the longitudinal tool axis LT-LT. As can be seen in FIG. **59**, a proximal end **2341** of the outer tube **2340** is rotatably supported within a cradle arrangement **2343** attached to the tool mounting plate **2462** of the tool mounting portion **2460**. A rotation gear **2345** is formed on or attached to the proximal end **2341** of the outer tube **2340** of the elongated shaft assembly **2308** for meshing engagement with a rotation gear assembly **2470** operably supported on the tool mounting plate **2462**. In at least one embodiment, a rotation drive gear **2472** is coupled to a corresponding first one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **2462** when the tool mounting portion **2460** is coupled to the tool drive assembly **1010**. See FIGS. **43** and **59**. The rotation drive assembly **2470** further comprises a rotary driven gear **2474** that is rotatably supported on the tool mounting plate **2462** in meshing engagement with the rotation gear **2345** and the rotation drive gear **2472**. Application of a first rotary output motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding driven element **1304** will thereby cause rotation of the rotation drive gear **2472** by virtue of being operably coupled thereto. Rotation of the rotation drive gear **2472** ultimately results in the rotation of the elongated shaft assembly **2308** (and the end effector **2312**) about the longitudinal tool axis LT-LT (primary rotary motion).

Closure of the anvil **2324** relative to the staple cartridge **2034** is accomplished by axially moving the closure tube **2370** in the distal direction "DD". Axial movement of the closure tube **2370** in the distal direction "DD" is accomplished by applying a rotary control motion to the closure drive nut **2382**. To apply the rotary control motion to the closure drive nut **2382**, the closure clutch **2410** must first be brought into meshing engagement with the proximal end portion **2384** of the closure drive nut **2382**. In various embodiments, the transmission arrangement **2375** further includes a shifter drive assembly **2480** that is operably supported on the tool mounting plate **2462**. More specifically and with reference to FIG. **59**, it can be seen that a proximal end portion **2359** of the proximal spine portion **2353** extends through the rotation gear **2345** and is rotatably coupled to a shifter gear rack **2481** that is slidably affixed to the tool mounting plate **2462** through slots **2482**. The shifter drive assembly **2480** further comprises a shifter drive gear **2483** that is coupled to a corresponding second one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **2462** when the tool mounting portion **2460** is coupled to the tool holder **1270**. See FIGS. **43** and **59**. The shifter drive assembly **2480** further comprises a shifter driven gear **2478** that is rotatably supported on the tool mounting plate **2462** in meshing engagement with the shifter drive gear **2483** and the shifter rack gear **2482**. Application of a second rotary output motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding driven element **1304** will thereby cause rotation of the shifter drive gear **2483** by virtue of being operably coupled thereto. Rotation of the shifter drive gear **2483** ultimately results in the axial movement of the shifter gear rack **2482** and the proximal spine portion **2353** as well as the drive sleeve **2400** and the closure clutch **2410** attached thereto. The direction of axial travel of the closure clutch **2410** depends upon the direction in which the shifter drive gear **2483** is rotated by the robotic system **1000**. Thus, rotation of the shifter drive gear **2483** in a first rotary direction will result in the axial movement of the closure clutch **2410** in the proximal direction "PD" to bring the proximal teeth **2416** into meshing engagement with the proximal teeth cavities **2418** in the closure drive nut **2382**. Conversely, rotation of the shifter

drive gear **2483** in a second rotary direction (opposite to the first rotary direction) will result in the axial movement of the closure clutch **2410** in the distal direction "DD" to bring the distal teeth **2415** into meshing engagement with corresponding distal teeth cavities **2426** formed in the face plate portion **2424** of the knife drive shaft assembly **2420**.

Once the closure clutch **2410** has been brought into meshing engagement with the closure drive nut **2382**, the closure drive nut **2382** is rotated by rotating the closure clutch **2410**. Rotation of the closure clutch **2410** is controlled by applying rotary output motions to a rotary drive transmission portion **2490** of transmission arrangement **2375** that is operably supported on the tool mounting plate **2462** as shown in FIG. **59**. In at least one embodiment, the rotary drive transmission **2490** includes a rotary drive assembly **2490'** that includes a gear **2491** that is coupled to a corresponding third one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **2462** when the tool mounting portion **2460** is coupled to the tool holder **1270**. See FIGS. **43** and **59**. The rotary drive transmission **2490** further comprises a first rotary driven gear **2492** that is rotatably supported on the tool mounting plate **2462** in meshing engagement with a second rotary driven gear **2493** and the rotary drive gear **2491**. The second rotary driven gear **2493** is coupled to a proximal end portion **2443** of the drive shaft **2440**.

Rotation of the rotary drive gear **2491** in a first rotary direction will result in the rotation of the drive shaft **2440** in a first direction. Conversely, rotation of the rotary drive gear **2491** in a second rotary direction (opposite to the first rotary direction) will cause the drive shaft **2440** to rotate in a second direction. As indicated above, the drive shaft **2440** has a drive gear **2444** that is attached to its distal end **2442** and is in meshing engagement with a driven gear **2450** that is attached to the drive sleeve **2400**. Thus, rotation of the drive shaft **2440** results in rotation of the drive sleeve **2400**.

A method of operating the surgical tool **2300** will now be described. Once the tool mounting portion **2462** has been operably coupled to the tool holder **1270** of the robotic system **1000** and oriented into position adjacent the target tissue to be cut and stapled, if the anvil **2334** is not already in the open position (FIG. **56**), the robotic system **1000** may apply the first rotary output motion to the shifter drive gear **2483** which results in the axial movement of the closure clutch **2410** into meshing engagement with the closure drive nut **2382** (if it is not already in meshing engagement therewith). See FIG. **57**. Once the controller **1001** of the robotic system **1000** has confirmed that the closure clutch **2410** is meshing engagement with the closure drive nut **2382** (e.g., by means of sensor(s)) in the surgical end effector **2312** that are in communication with the robotic control system), the robotic controller **1001** may then apply a second rotary output motion to the rotary drive gear **2492** which, as was described above, ultimately results in the rotation of the rotary drive nut **2382** in the first direction which results in the axial travel of the closure tube **2370** in the distal direction "DD". As the closure tube **2370** moved in the distal direction, it contacts a portion of the anvil **2323** and causes the anvil **2324** to pivot to the closed position to clamp the target tissue between the anvil **2324** and the surgical staple cartridge **2334**. Once the robotic controller **1001** determines that the anvil **2334** has been pivoted to the closed position by corresponding sensor(s) in the surgical end effector **2312** in communication therewith, the robotic system **1000** discontinues the application of the second rotary output motion to the rotary drive gear **2491**. The robotic controller **1001** may also provide the surgeon with an indication that the anvil **2334** has been fully closed. The surgeon may then initiate the firing procedure. In alternative embodiments, the firing procedure may be automatically initiated by the robotic controller **1001**. The robotic controller **1001** then applies the primary rotary control motion **2483** to the shifter drive gear **2483** which results in the axial movement of the closure clutch **2410** into meshing engagement with the face plate portion **2424** of the knife drive shaft assembly **2420**. See FIG. **58**. Once the controller **1001** of the robotic system **1000** has confirmed that the closure clutch **2410** is meshing engagement with the face plate portion **2424** (by means of sensor(s)) in the end effector **2312** that are in communication with the robotic controller **1001**), the robotic controller **1001** may then apply the second rotary output motion to the rotary drive gear **2492** which, as was described above, ultimately results in the axial movement of the cutting instrument **2332** and sled portion **2333** in the distal direction "DD" through the surgical staple cartridge **2334**. As the cutting instrument **2332** moves distally through the surgical staple cartridge **2334**, the tissue clamped therein is severed. As the sled portion **2333** is driven distally, it causes the staples within the surgical staple cartridge to be driven through the severed tissue into forming contact with the anvil **2324**. Once the robotic controller **1001** has determined that the cutting instrument **2324** has reached the end position within the surgical staple cartridge **2334** (by means of sensor(s)) in the end effector **2312** that are in communication with the robotic controller **1001**), the robotic controller **1001** discontinues the application of the second rotary output motion to the rotary drive gear **2491**. Thereafter, the robotic controller **1001** applies the secondary rotary output motion to the rotary drive gear **2491** which ultimately results in the axial travel of the cutting instrument **2332** and sled portion **2333** in the proximal direction "PD" to the starting position. Once the robotic controller **1001** has determined that the cutting instrument **2324** has reached the staring position by means of sensor(s) in the surgical end effector **2312** that are in communication with the robotic controller **1001**, the robotic controller **1001** discontinues the application of the secondary rotary output motion to the rotary drive gear **2491**. Thereafter, the robotic controller **1001** applies the primary rotary output motion to the shifter drive gear **2483** to cause the closure clutch **2410** to move into engagement with the rotary drive nut **2382**. Once the closure clutch **2410** has been moved into meshing engagement with the rotary drive nut **2382**, the robotic controller **1001** then applies the secondary output motion to the rotary drive gear **2491** which ultimately results in the rotation of the rotary drive nut **2382** in the second direction to cause the closure tube **2370** to move in the proximal direction "PD". As can be seen in FIGS. **56-58**, the closure tube **2370** has an opening **2345** therein that engages the tab **2327** on the anvil **2324** to cause the anvil **2324** to pivot to the open position. In alternative embodiments, a spring may also be employed to pivot the anvil **2324** to the open position when the closure tube **2370** has been returned to the starting position (FIG. **56**).

FIGS. **60-64** illustrate yet another surgical tool **2500** that may be effectively employed in connection with the robotic system **1000**. In various forms, the surgical tool **2500** includes a surgical end effector **2512** that includes a "first portion" in the form of an elongated channel **2522** and a "second movable portion" in the form of a pivotally translatable clamping member, such as an anvil **2524**, which are maintained at a spacing that assures effective stapling and severing of tissue clamped in the surgical end effector **2512**. As shown in the illustrated embodiment, the surgical end effector **2512** may include, in addition to the previously-mentioned elongated channel **2522** and anvil **2524**, a "third movable portion" in the form of a cutting instrument **2532**, a sled (not shown), and a surgical staple cartridge **2534** that is removably seated in the

elongated channel **2522**. The cutting instrument **2532** may be, for example, a knife. The anvil **2524** may be pivotably opened and closed at a pivot point **2525** connected to the proximate end of the elongated channel **2522**. The anvil **2524** may also include a tab **2527** at its proximate end that is configured to operably interface with a component of the mechanical closure system (described further below) to open and close the anvil **2524**. When actuated, the knife **2532** and sled travel longitudinally along the elongated channel **2522**, thereby cutting tissue clamped within the surgical end effector **2512**. The movement of the sled along the elongated channel **2522** causes the staples of the surgical staple cartridge **2534** to be driven through the severed tissue and against the closed anvil **2524**, which turns the staples to fasten the severed tissue. In one form, the elongated channel **2522** and the anvil **2524** may be made of an electrically conductive material (such as metal) so that they may serve as part of the antenna that communicates with sensor(s) in the surgical end effector, as described above. The surgical staple cartridge **2534** could be made of a nonconductive material (such as plastic) and the sensor may be connected to or disposed in the surgical staple cartridge **2534**, as described above.

It should be noted that although the embodiments of the surgical tool **2500** described herein employ a surgical end effector **2512** that staples the severed tissue, in other embodiments different techniques for fastening or sealing the severed tissue may be used. For example, end effectors that use RF energy or adhesives to fasten the severed tissue may also be used. U.S. Pat. No. 5,709,680, entitled "Electrosurgical Hemostatic Device" to Yates et al., and U.S. Pat. No. 5,688,270, entitled "Electrosurgical Hemostatic Device With Recessed And/Or Offset Electrodes" to Yates et al., which are incorporated herein by reference, discloses cutting instruments that use RF energy to fasten the severed tissue. U.S. patent application Ser. No. 11/267,811 to Morgan et al. and U.S. patent application Ser. No. 11/267,383 to Shelton et al., which are also incorporated herein by reference, disclose cutting instruments that use adhesives to fasten the severed tissue. Accordingly, although the description herein refers to cutting/stapling operations and the like, it should be recognized that this is an exemplary embodiment and is not meant to be limiting. Other tissue-fastening techniques may also be used.

In the illustrated embodiment, the elongated channel **2522** of the surgical end effector **2512** is coupled to an elongated shaft assembly **2508** that is coupled to a tool mounting portion **2600**. As shown in FIG. **60**, the elongated shaft assembly **2508** may include an articulation joint **2511** of the type and construction described herein to permit the surgical end effector **2512** to be selectively articulated about an axis that is substantially transverse to the tool axis LT-LT. Other embodiments, however, may lack an articulation joint arrangement. In at least one embodiment, the elongated shaft assembly **2508** comprises a hollow spine tube **2540** that is non-movably coupled to a tool mounting plate **2602** of the tool mounting portion **2600**. As can be seen in FIGS. **61** and **62**, the proximal end **2523** of the elongated channel **2522** comprises a hollow tubular structure configured to be attached to the distal end **2541** of the spine tube **2540**. In one embodiment, for example, the proximal end **2523** of the elongated channel **2522** is welded or glued to the distal end of the spine tube **2540**.

As can be further seen in FIGS. **61** and **62**, in at least one non-limiting embodiment, the surgical tool **2500** further includes an axially movable actuation member in the form of a closure tube **2550** that is constrained to move axially relative to the elongated channel **2522** and the spine tube **1540**. The closure tube **2550** has a proximal end **2552** that has an internal thread **2554** formed therein that is in threaded engagement with a rotatably movable portion in the form of a closure drive nut **2560**. More specifically, the closure drive nut **2560** has a proximal end portion **2562** that is rotatably supported relative to the elongated channel **2522** and the spine tube **2540**. For assembly purposes, the proximal end portion **2562** is threadably attached to a retention ring **2570**. The retention ring **2570** is received in a groove **2529** formed between a shoulder **2527** on the proximal end **2523** of the elongated channel **2522** and the distal end **2541** of the spine tube **1540**. Such arrangement serves to rotatably support the closure drive nut **2560** within the elongated channel **2522**. Rotation of the closure drive nut **2560** will cause the closure tube **2550** to move axially as represented by arrow "D" in FIG. **61**.

Extending through the spine tube **2540** and the closure drive nut **2560** is a drive member which, in at least one embodiment, comprises a knife bar **2580** that has a distal end portion **2582** that is rotatably coupled to the cutting instrument **2532** such that the knife bar **2580** may rotate relative to the cutting instrument **2582**. As can be seen in FIG. **61-63**, the closure drive nut **2560** has a slot **2564** therein through which the knife bar **2580** can slidably extend. Such arrangement permits the knife bar **2580** to move axially relative to the closure drive nut **2560**. However, rotation of the knife bar **2580** about the longitudinal tool axis LT-LT will also result in the rotation of the closure drive nut **2560**. The axial direction in which the closure tube **2550** moves ultimately depends upon the direction in which the knife bar **2580** and the closure drive nut **2560** are rotated. As the closure tube **2550** is driven distally, the distal end thereof will contact the anvil **2524** and cause the anvil **2524** to pivot to a closed position. Upon application of an opening rotary output motion from the robotic system **1000**, the closure tube **2550** will be driven in the proximal direction "PD" and pivot the anvil **2524** to the open position by virtue of the engagement of the tab **2527** with the opening **2555** in the closure tube **2550**.

In use, it may be desirable to rotate the surgical end effector **2512** about the longitudinal tool axis LT-LT. In at least one embodiment, the tool mounting portion **2600** is configured to receive a corresponding first rotary output motion from the robotic system **1000** and convert that first rotary output motion to a rotary control motion for rotating the elongated shaft assembly **2508** about the longitudinal tool axis LT-LT. As can be seen in FIG. **64**, a proximal end **2542** of the hollow spine tube **2540** is rotatably supported within a cradle arrangement **2603** attached to a tool mounting plate **2602** of the tool mounting portion **2600**. Various embodiments of the surgical tool **2500** further include a transmission arrangement, generally depicted as **2605**, that is operably supported on the tool mounting plate **2602**. In various forms the transmission arrangement **2605** include a rotation gear **2544** that is formed on or attached to the proximal end **2542** of the spine tube **2540** for meshing engagement with a rotation drive assembly **2610** that is operably supported on the tool mounting plate **2602**. In at least one embodiment, a rotation drive gear **2612** is coupled to a corresponding first one of the rotational bodies, driven discs or elements **1304** on the adapter side of the tool mounting plate **2602** when the tool mounting portion **2600** is coupled to the tool holder **1270**. See FIGS. **43** and **64**. The rotation drive assembly **2610** further comprises a rotary driven gear **2614** that is rotatably supported on the tool mounting plate **2602** in meshing engagement with the rotation gear **2544** and the rotation drive gear **2612**. Application of a first rotary output motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding driven rotational body **1304** will thereby cause rotation of the rotation drive gear **2612** by virtue of

being operably coupled thereto. Rotation of the rotation drive gear **2612** ultimately results in the rotation of the elongated shaft assembly **2508** (and the end effector **2512**) about the longitudinal tool axis LT-LT.

Closure of the anvil **2524** relative to the surgical staple cartridge **2534** is accomplished by axially moving the closure tube **2550** in the distal direction "DD". Axial movement of the closure tube **2550** in the distal direction "DD" is accomplished by applying a rotary control motion to the closure drive nut **2382**. In various embodiments, the closure drive nut **2560** is rotated by applying a rotary output motion to the knife bar **2580**. Rotation of the knife bar **2580** is controlled by applying rotary output motions to a rotary closure system **2620** that is operably supported on the tool mounting plate **2602** as shown in FIG. **64**. In at least one embodiment, the rotary closure system **2620** includes a closure drive gear **2622** that is coupled to a corresponding second one of the driven rotatable body portions discs or elements **1304** on the adapter side of the tool mounting plate **2462** when the tool mounting portion **2600** is coupled to the tool holder **1270**. See FIGS. **43** and **64**. The closure drive gear **2622**, in at least one embodiment, is in meshing driving engagement with a closure gear train, generally depicted as **2623**. The closure gear drive rain **2623** comprises a first driven closure gear **2624** that is rotatably supported on the tool mounting plate **2602**. The first closure driven gear **2624** is attached to a second closure driven gear **2626** by a drive shaft **2628**. The second closure driven gear **2626** is in meshing engagement with a third closure driven gear **2630** that is rotatably supported on the tool mounting plate **2602**. Rotation of the closure drive gear **2622** in a second rotary direction will result in the rotation of the third closure driven gear **2630** in a second direction. Conversely, rotation of the closure drive gear **2483** in a secondary rotary direction (opposite to the second rotary direction) will cause the third closure driven gear **2630** to rotate in a secondary direction.

As can be seen in FIG. **64**, a drive shaft assembly **2640** is coupled to a proximal end of the knife bar **2580**. In various embodiments, the drive shaft assembly **2640** includes a proximal portion **2642** that has a square cross-sectional shape. The proximal portion **2642** is configured to slideably engage a correspondingly shaped aperture in the third driven gear **2630**. Such arrangement results in the rotation of the drive shaft assembly **2640** (and knife bar **2580**) when the third driven gear **2630** is rotated. The drive shaft assembly **2640** is axially advanced in the distal and proximal directions by a knife drive assembly **2650**. One form of the knife drive assembly **2650** comprises a rotary drive gear **2652** that is coupled to a corresponding third one of the driven rotatable body portions, discs or elements **1304** on the adapter side of the tool mounting plate **2462** when the tool mounting portion **2600** is coupled to the tool holder **1270**. See FIGS. **43** and **64**. The rotary driven gear **2652** is in meshing driving engagement with a gear train, generally depicted as **2653**. In at least one form, the gear train **2653** further comprises a first rotary driven gear assembly **2654** that is rotatably supported on the tool mounting plate **2602**. The first rotary driven gear assembly **2654** is in meshing engagement with a third rotary driven gear assembly **2656** that is rotatably supported on the tool mounting plate **2602** and which is in meshing engagement with a fourth rotary driven gear assembly **2658** that is in meshing engagement with a threaded portion **2644** of the drive shaft assembly **2640**. Rotation of the rotary drive gear **2652** in a third rotary direction will result in the axial advancement of the drive shaft assembly **2640** and knife bar **2580** in the distal direction "DD". Conversely, rotation of the rotary drive gear **2652** in a tertiary rotary direction (opposite to the third rotary direction) will cause the drive shaft assembly **2640** and the knife bar **2580** to move in the proximal direction.

A method of operating the surgical tool **2500** will now be described. Once the tool mounting portion **2600** has been operably coupled to the tool holder **1270** of the robotic system **1000**, the robotic system **1000** can orient the surgical end effector **2512** in position adjacent the target tissue to be cut and stapled. If the anvil **2524** is not already in the open position (FIG. **61**), the robotic system **1000** may apply the second rotary output motion to the closure drive gear **2622** which results in the rotation of the knife bar **2580** in a second direction. Rotation of the knife bar **2580** in the second direction results in the rotation of the closure drive nut **2560** in a second direction. As the closure drive nut **2560** rotates in the second direction, the closure tube **2550** moves in the proximal direction "PD". As the closure tube **2550** moves in the proximal direction "PD", the tab **2527** on the anvil **2524** interfaces with the opening **2555** in the closure tube **2550** and causes the anvil **2524** to pivot to the open position. In addition or in alternative embodiments, a spring (not shown) may be employed to pivot the anvil **2354** to the open position when the closure tube **2550** has been returned to the starting position (FIG. **61**). The opened surgical end effector **2512** may then be manipulated by the robotic system **1000** to position the target tissue between the open anvil **2524** and the surgical staple cartridge **2534**. Thereafter, the surgeon may initiate the closure process by activating the robotic control system **1000** to apply the second rotary output motion to the closure drive gear **2622** which, as was described above, ultimately results in the rotation of the closure drive nut **2382** in the second direction which results in the axial travel of the closure tube **2250** in the distal direction "DD". As the closure tube **2550** moves in the distal direction, it contacts a portion of the anvil **2524** and causes the anvil **2524** to pivot to the closed position to clamp the target tissue between the anvil **2524** and the staple cartridge **2534**. Once the robotic controller **1001** determines that the anvil **2524** has been pivoted to the closed position by corresponding sensor(s) in the end effector **2512** that are in communication therewith, the robotic controller **1001** discontinues the application of the second rotary output motion to the closure drive gear **2622**. The robotic controller **1001** may also provide the surgeon with an indication that the anvil **2524** has been fully closed. The surgeon may then initiate the firing procedure. In alternative embodiments, the firing procedure may be automatically initiated by the robotic controller **1001**.

After the robotic controller **1001** has determined that the anvil **2524** is in the closed position, the robotic controller **1001** then applies the third rotary output motion to the rotary drive gear **2652** which results in the axial movement of the drive shaft assembly **2640** and knife bar **2580** in the distal direction "DD". As the cutting instrument **2532** moves distally through the surgical staple cartridge **2534**, the tissue clamped therein is severed. As the sled portion (not shown) is driven distally, it causes the staples within the surgical staple cartridge **2534** to be driven through the severed tissue into forming contact with the anvil **2524**. Once the robotic controller **1001** has determined that the cutting instrument **2532** has reached the end position within the surgical staple cartridge **2534** by means of sensor(s) in the surgical end effector **2512** that are in communication with the robotic controller **1001**, the robotic controller **1001** discontinues the application of the second rotary output motion to the rotary drive gear **2652**. Thereafter, the robotic controller **1001** applies the secondary rotary control motion to the rotary drive gear **2652** which ultimately results in the axial travel of the cutting

instrument **2532** and sled portion in the proximal direction "PD" to the starting position. Once the robotic controller **1001** has determined that the cutting instrument **2524** has reached the staring position by means of sensor(s) in the end effector **2512** that are in communication with the robotic controller **1001**, the robotic controller **1001** discontinues the application of the secondary rotary output motion to the rotary drive gear **2652**. Thereafter, the robotic controller **1001** may apply the secondary rotary output motion to the closure drive gear **2622** which results in the rotation of the knife bar **2580** in a secondary direction. Rotation of the knife bar **2580** in the secondary direction results in the rotation of the closure drive nut **2560** in a secondary direction. As the closure drive nut **2560** rotates in the secondary direction, the closure tube **2550** moves in the proximal direction "PD" to the open position.

FIGS. **65-70**B illustrate yet another surgical tool **2700** that may be effectively employed in connection with the robotic system **1000**. In various forms, the surgical tool **2700** includes a surgical end effector **2712** that includes a "first portion" in the form of an elongated channel **2722** and a "second movable portion" in on form comprising a pivotally translatable clamping member, such as an anvil **2724**, which are maintained at a spacing that assures effective stapling and severing of tissue clamped in the surgical end effector **2712**. As shown in the illustrated embodiment, the surgical end effector **2712** may include, in addition to the previously-mentioned channel **2722** and anvil **2724**, a "third movable portion" in the form of a cutting instrument **2732**, a sled (not shown), and a surgical staple cartridge **2734** that is removably seated in the elongated channel **2722**. The cutting instrument **2732** may be, for example, a knife. The anvil **2724** may be pivotably opened and closed at a pivot point **2725** connected to the proximal end of the elongated channel **2722**. The anvil **2724** may also include a tab **2727** at its proximal end that interfaces with a component of the mechanical closure system (described further below) to open and close the anvil **2724**. When actuated, the knife **2732** and sled to travel longitudinally along the elongated channel **2722**, thereby cutting tissue clamped within the surgical end effector **2712**. The movement of the sled along the elongated channel **2722** causes the staples of the surgical staple cartridge **2734** to be driven through the severed tissue and against the closed anvil **2724**, which turns the staples to fasten the severed tissue. In one form, the elongated channel **2722** and the anvil **2724** may be made of an electrically conductive material (such as metal) so that they may serve as part of the antenna that communicates with sensor(s) in the surgical end effector, as described above. The surgical staple cartridge **2734** could be made of a nonconductive material (such as plastic) and the sensor may be connected to or disposed in the surgical staple cartridge **2734**, as described above.

It should be noted that although the embodiments of the surgical tool **2500** described herein employ a surgical end effector **2712** that staples the severed tissue, in other embodiments different techniques for fastening or sealing the severed tissue may be used. For example, end effectors that use RF energy or adhesives to fasten the severed tissue may also be used. U.S. Pat. No. 5,709,680, entitled "Electrosurgical Hemostatic Device" to Yates et al., and U.S. Pat. No. 5,688,270, entitled "Electrosurgical Hemostatic Device With Recessed And/Or Offset Electrodes" to Yates et al., which are incorporated herein by reference, discloses cutting instruments that use RF energy to fasten the severed tissue. U.S. patent application Ser. No. 11/267,811 to Morgan et al. and U.S. patent application Ser. No. 11/267,383 to Shelton et al., which are also incorporated herein by reference, disclose cutting instruments that use adhesives to fasten the severed tissue. Accordingly, although the description herein refers to cutting/stapling operations and the like, it should be recognized that this is an exemplary embodiment and is not meant to be limiting. Other tissue-fastening techniques may also be used.

In the illustrated embodiment, the elongated channel **2722** of the surgical end effector **2712** is coupled to an elongated shaft assembly **2708** that is coupled to a tool mounting portion **2900**. Although not shown, the elongated shaft assembly **2708** may include an articulation joint to permit the surgical end effector **2712** to be selectively articulated about an axis that is substantially transverse to the tool axis LT-LT. In at least one embodiment, the elongated shaft assembly **2708** comprises a hollow spine tube **2740** that is non-movably coupled to a tool mounting plate **2902** of the tool mounting portion **2900**. As can be seen in FIGS. **66** and **67**, the proximal end **2723** of the elongated channel **2722** comprises a hollow tubular structure that is attached to the spine tube **2740** by means of a mounting collar **2790**. A cross-sectional view of the mounting collar **2790** is shown in FIG. **69**. In various embodiments, the mounting collar **2790** has a proximal flanged end **2791** that is configured for attachment to the distal end of the spine tube **2740**. In at least one embodiment, for example, the proximal flanged end **2791** of the mounting collar **2790** is welded or glued to the distal end of the spine tube **2740**. As can be further seen in FIGS. **66** and **67**, the mounting collar **2790** further has a mounting hub portion **2792** that is sized to receive the proximal end **2723** of the elongated channel **2722** thereon. The proximal end **2723** of the elongated channel **2722** is non-movably attached to the mounting hub portion **2792** by, for example, welding, adhesive, etc.

As can be further seen in FIGS. **66** and **67**, the surgical tool **2700** further includes an axially movable actuation member in the form of a closure tube **2750** that is constrained to move axially relative to the elongated channel **2722**. The closure tube **2750** has a proximal end **2752** that has an internal thread **2754** formed therein that is in threaded engagement with a rotatably movable portion in the form of a closure drive nut **2760**. More specifically, the closure drive nut **2760** has a proximal end portion **2762** that is rotatably supported relative to the elongated channel **2722** and the spine tube **2740**. For assembly purposes, the proximal end portion **2762** is threadably attached to a retention ring **2770**. The retention ring **2770** is received in a groove **2729** formed between a shoulder **2727** on the proximal end **2723** of the channel **2722** and the mounting hub **2729** of the mounting collar **2790**. Such arrangement serves to rotatably support the closure drive nut **2760** within the channel **2722**. Rotation of the closure drive nut **2760** will cause the closure tube **2750** to move axially as represented by arrow "D" in FIG. **66**.

Extending through the spine tube **2740**, the mounting collar **2790**, and the closure drive nut **2760** is a drive member, which in at least one embodiment, comprises a knife bar **2780** that has a distal end portion **2782** that is coupled to the cutting instrument **2732**. As can be seen in FIGS. **66** and **67**, the mounting collar **2790** has a passage **2793** therethrough for permitting the knife bar **2780** to slidably pass therethrough. Similarly, the closure drive nut **2760** has a slot **2764** therein through which the knife bar **2780** can slidably extend. Such arrangement permits the knife bar **2780** to move axially relative to the closure drive nut **2760**.

Actuation of the anvil **2724** is controlled by a rotary driven closure shaft **2800**. As can be seen in FIGS. **66** and **67**, a distal end portion **2802** of the closure drive shaft **2800** extends through a passage **2794** in the mounting collar **2790** and a

closure gear **2804** is attached thereto. The closure gear **2804** is configured for driving engagement with the inner surface **2761** of the closure drive nut **2760**. Thus, rotation of the closure shaft **2800** will also result in the rotation of the closure drive nut **2760**. The axial direction in which the closure tube **2750** moves ultimately depends upon the direction in which the closure shaft **2800** and the closure drive nut **2760** are rotated. For example, in response to one rotary closure motion received from the robotic system **1000**, the closure tube **2750** will be driven in the distal direction "DD". As the closure tube **2750** is driven distally, the opening **2745** will engage the tab **2727** on the anvil **2724** and cause the anvil **2724** to pivot to a closed position. Upon application of an opening rotary motion from the robotic system **1000**, the closure tube **2750** will be driven in the proximal direction "PD" and pivot the anvil **2724** to the open position. In various embodiments, a spring (not shown) may be employed to bias the anvil **2724** to the open position (FIG. **66**).

In use, it may be desirable to rotate the surgical end effector **2712** about the longitudinal tool axis LT-LT. In at least one embodiment, the tool mounting portion **2900** is configured to receive a corresponding first rotary output motion from the robotic system **1000** for rotating the elongated shaft assembly **2708** about the tool axis LT-LT. As can be seen in FIG. **70**, a proximal end **2742** of the hollow spine tube **2740** is rotatably supported within a cradle arrangement **2903** and a bearing assembly **2904** that are attached to a tool mounting plate **2902** of the tool mounting portion **2900**. A rotation gear **2744** is formed on or attached to the proximal end **2742** of the spine tube **2740** for meshing engagement with a rotation drive assembly **2910** that is operably supported on the tool mounting plate **2902**. In at least one embodiment, a rotation drive gear **2912** is coupled to a corresponding first one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **2602** when the tool mounting portion **2600** is coupled to the tool holder **1270**. See FIGS. **43** and **70**. The rotation drive assembly **2910** further comprises a rotary driven gear **2914** that is rotatably supported on the tool mounting plate **2902** in meshing engagement with the rotation gear **2744** and the rotation drive gear **2912**. Application of a first rotary control motion from the robotic system **1000** through the tool holder **1270** and the adapter **1240** to the corresponding driven element **1304** will thereby cause rotation of the rotation drive gear **2912** by virtue of being operably coupled thereto. Rotation of the rotation drive gear **2912** ultimately results in the rotation of the elongated shaft assembly **2708** (and the end effector **2712**) about the longitudinal tool axis LT-LT (primary rotary motion).

Closure of the anvil **2724** relative to the staple cartridge **2734** is accomplished by axially moving the closure tube **2750** in the distal direction "DD". Axial movement of the closure tube **2750** in the distal direction "DD" is accomplished by applying a rotary control motion to the closure drive nut **2760**. In various embodiments, the closure drive nut **2760** is rotated by applying a rotary output motion to the closure drive shaft **2800**. As can be seen in FIG. **70**, a proximal end portion **2806** of the closure drive shaft **2800** has a driven gear **2808** thereon that is in meshing engagement with a closure drive assembly **2920**. In various embodiments, the closure drive system **2920** includes a closure drive gear **2922** that is coupled to a corresponding second one of the driven rotational bodies or elements **1304** on the adapter side of the tool mounting plate **2462** when the tool mounting portion **2900** is coupled to the tool holder **1270**. See FIGS. **43** and **70**. The closure drive gear **2922** is supported in meshing engagement with a closure gear train, generally depicted as **2923**. In at least one form, the closure gear rain **2923** comprises a first driven closure gear **2924** that is rotatably supported on the tool mounting plate **2902**. The first closure driven gear **2924** is attached to a second closure driven gear **2926** by a drive shaft **2928**. The second closure driven gear **2926** is in meshing engagement with a planetary gear assembly **2930**. In various embodiments, the planetary gear assembly **2930** includes a driven planetary closure gear **2932** that is rotatably supported within the bearing assembly **2904** that is mounted on tool mounting plate **2902**. As can be seen in FIGS. **70** and **70**B, the proximal end portion **2806** of the closure drive shaft **2800** is rotatably supported within the proximal end portion **2742** of the spine tube **2740** such that the driven gear **2808** is in meshing engagement with central gear teeth **2934** formed on the planetary gear **2932**. As can also be seen in FIG. **70**A, two additional support gears **2936** are attached to or rotatably supported relative to the proximal end portion **2742** of the spine tube **2740** to provide bearing support thereto. Such arrangement with the planetary gear assembly **2930** serves to accommodate rotation of the spine shaft **2740** by the rotation drive assembly **2910** while permitting the closure driven gear **2808** to remain in meshing engagement with the closure drive system **2920**. In addition, rotation of the closure drive gear **2922** in a first direction will ultimately result in the rotation of the closure drive shaft **2800** and closure drive nut **2760** which will ultimately result in the closure of the anvil **2724** as described above. Conversely, rotation of the closure drive gear **2922** in a second opposite direction will ultimately result in the rotation of the closure drive nut **2760** in an opposite direction which results in the opening of the anvil **2724**.

As can be seen in FIG. **70**, the proximal end **2784** of the knife bar **2780** has a threaded shaft portion **2786** attached thereto which is in driving engagement with a knife drive assembly **2940**. In various embodiments, the threaded shaft portion **2786** is rotatably supported by a bearing **2906** attached to the tool mounting plate **2902**. Such arrangement permits the threaded shaft portion **2786** to rotate and move axially relative to the tool mounting plate **2902**. The knife bar **2780** is axially advanced in the distal and proximal directions by the knife drive assembly **2940**. One form of the knife drive assembly **2940** comprises a rotary drive gear **2942** that is coupled to a corresponding third one of the rotatable bodies, driven discs or elements **1304** on the adapter side of the tool mounting plate **2902** when the tool mounting portion **2900** is coupled to the tool holder **1270**. See FIGS. **43** and **70**. The rotary drive gear **2942** is in meshing engagement with a knife gear train, generally depicted as **2943**. In various embodiments, the knife gear train **2943** comprises a first rotary driven gear assembly **2944** that is rotatably supported on the tool mounting plate **2902**. The first rotary driven gear assembly **2944** is in meshing engagement with a third rotary driven gear assembly **2946** that is rotatably supported on the tool mounting plate **2902** and which is in meshing engagement with a fourth rotary driven gear assembly **2948** that is in meshing engagement with the threaded portion **2786** of the knife bar **2780**. Rotation of the rotary drive gear **2942** in one direction will result in the axial advancement of the knife bar **2780** in the distal direction "DD". Conversely, rotation of the rotary drive gear **2942** in an opposite direction will cause the knife bar **2780** to move in the proximal direction. Tool **2700** may otherwise be used as described above.

FIGS. **71** and **72** illustrate a surgical tool embodiment **2700** that is substantially identical to tool **2700** that was described in detail above. However tool **2700'** includes a pressure sensor **2950** that is configured to provide feedback to the robotic controller **1001** concerning the amount of clamping pressure experienced by the anvil **2724**. In various embodiments, for example, the pressure sensor may comprise a spring biased

contact switch. For a continuous signal, it would use either a cantilever beam with a strain gage on it or a dome button top with a strain gage on the inside. Another version may comprise an off switch that contacts only at a known desired load. Such arrangement would include a dome on the based wherein the dome is one electrical pole and the base is the other electrical pole. Such arrangement permits the robotic controller **1001** to adjust the amount of clamping pressure being applied to the tissue within the surgical end effector **2712** by adjusting the amount of closing pressure applied to the anvil **2724**. Those of ordinary skill in the art will understand that such pressure sensor arrangement may be effectively employed with several of the surgical tool embodiments described herein as well as their equivalent structures.

FIG. **73** illustrates a portion of another surgical tool **3000** that may be effectively used in connection with a robotic system **1000**. The surgical tool **3003** employs on-board motor(s) for powering various components of a surgical end effector cutting instrument. In at least one non-limiting embodiment for example, the surgical tool **3000** includes a surgical end effector in the form of an endocutter (not shown) that has an anvil (not shown) and surgical staple cartridge arrangement (not shown) of the types and constructions described above. The surgical tool **3000** also includes an elongated shaft (not shown) and anvil closure arrangement (not shown) of the types described above. Thus, this portion of the Detailed Description will not repeat the description of those components beyond that which is necessary to appreciate the unique and novel attributes of the various embodiments of surgical tool **3000**.

In the depicted embodiment, the end effector includes a cutting instrument **3002** that is coupled to a knife bar **3003**. As can be seen in FIG. **73**, the surgical tool **3000** includes a tool mounting portion **3010** that includes a tool mounting plate **3012** that is configured to mountingly interface with the adaptor portion **1240'** which is coupled to the robotic system **1000** in the various manners described above. The tool mounting portion **3010** is configured to operably support a transmission arrangement **3013** thereon. In at least one embodiment, the adaptor portion **1240'** may be identical to the adaptor portion **1240** described in detail above without the powered rotation bodies and disc members employed by adapter **1240**. In other embodiments, the adaptor portion **1240'** may be identical to adaptor portion **1240**. Still other modifications which are considered to be within the spirit and scope of the various forms of the present invention may employ one or more of the mechanical motions (i.e., rotary motion(s)) from the tool holder portion **1270** (as described hereinabove) to power/actuate the transmission arrangement **3013** while also employing one or more motors within the tool mounting portion **3010** to power one or more other components of the surgical end effector. In addition, while the end effector of the depicted embodiment comprises an endocutter, those of ordinary skill in the art will understand that the unique and novel attributes of the depicted embodiment may be effectively employed in connection with other types of surgical end effectors without departing from the spirit and scope of various forms of the present invention.

In various embodiments, the tool mounting plate **3012** is configured to at least house a first firing motor **3011** for supplying firing and retraction motions to the knife bar **3003** which is coupled to or otherwise operably interfaces with the cutting instrument **3002**. The tool mounting plate **3012** has an array of electrical connecting pins **3014** which are configured to interface with the slots **1258** (FIG. **42**) in the adapter **1240'**. Such arrangement permits the controller **1001** of the robotic system **1000** to provide control signals to the electronic control circuit **3020** of the surgical tool **3000**. While the interface is described herein with reference to mechanical, electrical, and magnetic coupling elements, it should be understood that a wide variety of telemetry modalities might be used, including infrared, inductive coupling, or the like.

Control circuit **3020** is shown in schematic form in FIG. **73**. In one form or embodiment, the control circuit **3020** includes a power supply in the form of a battery **3022** that is coupled to an on-off solenoid powered switch **3024**. Control circuit **3020** further includes an on/off firing solenoid **3026** that is coupled to a double pole switch **3028** for controlling the rotational direction of the motor **3011**. Thus, when the controller **1001** of the robotic system **1000** supplies an appropriate control signal, switch **3024** will permit battery **3022** to supply power to the double pole switch **3028**. The controller **1001** of the robotic system **1000** will also supply an appropriate signal to the double pole switch **3028** to supply power to the motor **3011**. When it is desired to fire the surgical end effector (i.e., drive the cutting instrument **3002** distally through tissue clamped in the surgical end effector, the double pole switch **3028** will be in a first position. When it is desired to retract the cutting instrument **3002** to the starting position, the double pole switch **3028** will be moved to the second position by the controller **1001**.

Various embodiments of the surgical tool **3000** also employ a gear box **3030** that is sized, in cooperation with a firing gear train **3031** that, in at least one non-limiting embodiment, comprises a firing drive gear **3032** that is in meshing engagement with a firing driven gear **3034** for generating a desired amount of driving force necessary to drive the cutting instrument **3002** through tissue and to drive and form staples in the various manners described herein. In the embodiment depicted in FIG. **73**, the driven gear **3034** is coupled to a screw shaft **3036** that is in threaded engagement with a screw nut arrangement **3038** that is constrained to move axially (represented by arrow "D"). The screw nut arrangement **3038** is attached to the firing bar **3003**. Thus, by rotating the screw shaft **3036** in a first direction, the cutting instrument **3002** is driven in the distal direction "DD" and rotating the screw shaft in an opposite second direction, the cutting instrument **3002** may be retracted in the proximal direction "PD".

FIG. **74** illustrates a portion of another surgical tool **3000'** that is substantially identical to tool **3000** described above, except that the driven gear **3034** is attached to a drive shaft **3040**. The drive shaft **3040** is attached to a second driver gear **3042** that is in meshing engagement with a third driven gear **3044** that is in meshing engagement with a screw **3046** coupled to the firing bar **3003**.

FIG. **75** illustrates another surgical tool **3200** that may be effectively used in connection with a robotic system **1000**. In this embodiment, the surgical tool **3200** includes a surgical end effector **3212** that in one non-limiting form, comprises a component portion that is selectively movable between first and second positions relative to at least one other end effector component portion. As will be discussed in further detail below, the surgical tool **3200** employs on-board motors for powering various components of a transmission arrangement **3305**. The surgical end effector **3212** includes an elongated channel **3222** that operably supports a surgical staple cartridge **3234**. The elongated channel **3222** has a proximal end **3223** that slidably extends into a hollow elongated shaft assembly **3208** that is coupled to a tool mounting portion **3300**. In addition, the surgical end effector **3212** includes an anvil **3224** that is pivotally coupled to the elongated channel **3222** by a pair of trunnions **3225** that are received within corresponding openings **3229** in the elongated channel **3222**. A distal end portion **3209** of the shaft assembly **3208** includes

an opening **3245** into which a tab **3227** on the anvil **3224** is inserted in order to open the anvil **3224** as the elongated channel **3222** is moved axially in the proximal direction "PD" relative to the distal end portion **3209** of the shaft assembly **3208**. In various embodiments, a spring (not shown) may be employed to bias the anvil **3224** to the open position.

As indicated above, the surgical tool **3200** includes a tool mounting portion **3300** that includes a tool mounting plate **3302** that is configured to operably support the transmission arrangement **3305** and to mountingly interface with the adaptor portion **1240'** which is coupled to the robotic system **1000** in the various manners described above. In at least one embodiment, the adaptor portion **1240'** may be identical to the adaptor portion **1240** described in detail above without the powered disc members employed by adapter **1240**. In other embodiments, the adaptor portion **1240'** may be identical to adaptor portion **1240**. However, in such embodiments, because the various components of the surgical end effector **3212** are all powered by motor(s) in the tool mounting portion **3300**, the surgical tool **3200** will not employ or require any of the mechanical (i.e., non-electrical) actuation motions from the tool holder portion **1270** to power the surgical end effector **3200** components. Still other modifications which are considered to be within the spirit and scope of the various forms of the present invention may employ one or more of the mechanical motions from the tool holder portion **1270** (as described hereinabove) to power/actuate one or more of the surgical end effector components while also employing one or more motors within the tool mounting portion to power one or more other components of the surgical end effector.

In various embodiments, the tool mounting plate **3302** is configured to support a first firing motor **3310** for supplying firing and retraction motions to the transmission arrangement **3305** to drive a knife bar **3335** that is coupled to a cutting instrument **3332** of the type described above. As can be seen in FIG. **75**, the tool mounting plate **3212** has an array of electrical connecting pins **3014** which are configured to interface with the slots **1258** (FIG. **42**) in the adapter **1240'**. Such arrangement permits the controller **1001** of the robotic system **1000** to provide control signals to the electronic control circuits **3320**, **3340** of the surgical tool **3200**. While the interface is described herein with reference to mechanical, electrical, and magnetic coupling elements, it should be understood that a wide variety of telemetry modalities might be used, including infrared, inductive coupling, or the like.

In one form or embodiment, the first control circuit **3320** includes a first power supply in the form of a first battery **3322** that is coupled to a first on-off solenoid powered switch **3324**. The first firing control circuit **3320** further includes a first on/off firing solenoid **3326** that is coupled to a first double pole switch **3328** for controlling the rotational direction of the first firing motor **3310**. Thus, when the robotic controller **1001** supplies an appropriate control signal, the first switch **3324** will permit the first battery **3322** to supply power to the first double pole switch **3328**. The robotic controller **1001** will also supply an appropriate signal to the first double pole switch **3328** to supply power to the first firing motor **3310**. When it is desired to fire the surgical end effector (i.e., drive the cutting instrument **3232** distally through tissue clamped in the surgical end effector **3212**, the first switch **3328** will be positioned in a first position by the robotic controller **1001**. When it is desired to retract the cutting instrument **3232** to the starting position, the robotic controller **1001** will send the appropriate control signal to move the first switch **3328** to the second position.

Various embodiments of the surgical tool **3200** also employ a first gear box **3330** that is sized, in cooperation with a firing drive gear **3332** coupled thereto that operably interfaces with a firing gear train **3333**. In at least one non-limiting embodiment, the firing gear train **333** comprises a firing driven gear **3334** that is in meshing engagement with drive gear **3332**, for generating a desired amount of driving force necessary to drive the cutting instrument **3232** through tissue and to drive and form staples in the various manners described herein. In the embodiment depicted in FIG. **75**, the driven gear **3334** is coupled to a drive shaft **3335** that has a second driven gear **3336** coupled thereto. The second driven gear **3336** is supported in meshing engagement with a third driven gear **3337** that is in meshing engagement with a fourth driven gear **3338**. The fourth driven gear **3338** is in meshing engagement with a threaded proximal portion **3339** of the knife bar **3235** that is constrained to move axially. Thus, by rotating the drive shaft **3335** in a first direction, the cutting instrument **3232** is driven in the distal direction "DD" and rotating the drive shaft **3335** in an opposite second direction, the cutting instrument **3232** may be retracted in the proximal direction "PD".

As indicated above, the opening and closing of the anvil **3224** is controlled by axially moving the elongated channel **3222** relative to the elongated shaft assembly **3208**. The axial movement of the elongated channel **3222** is controlled by a closure control system **3339**. In various embodiments, the closure control system **3339** includes a closure shaft **3340** which has a hollow threaded end portion **3341** that threadably engages a threaded closure rod **3342**. The threaded end portion **3341** is rotatably supported in a spine shaft **3343** that operably interfaces with the tool mounting portion **3300** and extends through a portion of the shaft assembly **3208** as shown. The closure system **3339** further comprises a closure control circuit **3350** that includes a second power supply in the form of a second battery **3352** that is coupled to a second on-off solenoid powered switch **3354**. Closure control circuit **3350** further includes a second on/off firing solenoid **3356** that is coupled to a second double pole switch **3358** for controlling the rotation of a second closure motor **3360**. Thus, when the robotic controller **1001** supplies an appropriate control signal, the second switch **3354** will permit the second battery **3352** to supply power to the second double pole switch **3354**. The robotic controller **1001** will also supply an appropriate signal to the second double pole switch **3358** to supply power to the second motor **3360**. When it is desired to close the anvil **3224**, the second switch **3348** will be in a first position. When it is desired to open the anvil **3224**, the second switch **3348** will be moved to a second position.

Various embodiments of tool mounting portion **3300** also employ a second gear box **3362** that is coupled to a closure drive gear **3364**. The closure drive gear **3364** is in meshing engagement with a closure gear train **3363**. In various non-limiting forms, the closure gear train **3363** includes a closure driven gear **3365** that is attached to a closure drive shaft **3366**. Also attached to the closure drive shaft **3366** is a closure drive gear **3367** that is in meshing engagement with a closure shaft gear **3360** attached to the closure shaft **3340**. FIG. **75** depicts the end effector **3212** in the open position. As indicated above, when the threaded closure rod **3342** is in the position depicted in FIG. **75**, a spring (not shown) biases the anvil **3224** to the open position. When it is desired to close the anvil **3224**, the robotic controller **1001** will activate the second motor **3360** to rotate the closure shaft **3340** to draw the threaded closure rod **3342** and the channel **3222** in the proximal direction 'PD'. As the anvil **3224** contacts the distal end portion **3209** of the shaft **3208**, the anvil **3224** is pivoted to the closed position.

A method of operating the surgical tool **3200** will now be described. Once the tool mounting portion **3302** has be operably coupled to the tool holder **1270** of the robotic system

1000, the robotic system 1000 can orient the end effector 3212 in position adjacent the target tissue to be cut and stapled. If the anvil 3224 is not already in the open position, the robotic controller 1001 may activate the second closure motor 3360 to drive the channel 3222 in the distal direction to the position depicted in FIG. 75. Once the robotic controller 1001 determines that the surgical end effector 3212 is in the open position by sensor(s) in the and effector and/or the tool mounting portion 3300, the robotic controller 1001 may provide the surgeon with a signal to inform the surgeon that the anvil 3224 may then be closed. Once the target tissue is positioned between the open anvil 3224 and the surgical staple cartridge 3234, the surgeon may then commence the closure process by activating the robotic controller 1001 to apply a closure control signal to the second closure motor 3360. The second closure motor 3360 applies a rotary motion to the closure shaft 3340 to draw the channel 3222 in the proximal direction "PD" until the anvil 3224 has been pivoted to the closed position. Once the robotic controller 1001 determines that the anvil 3224 has been moved to the closed position by sensor(s) in the surgical end effector 3212 and/or in the tool mounting portion 3300 that are in communication with the robotic control system, the motor 3360 may be deactivated. Thereafter, the firing process may be commenced either manually by the surgeon activating a trigger, button, etc. on the controller 1001 or the controller 1001 may automatically commence the firing process.

To commence the firing process, the robotic controller 1001 activates the firing motor 3310 to drive the firing bar 3235 and the cutting instrument 3232 in the distal direction "DD". Once robotic controller 1001 has determined that the cutting instrument 3232 has moved to the ending position within the surgical staple cartridge 3234 by means of sensors in the surgical end effector 3212 and/or the motor drive portion 3300, the robotic controller 1001 may provide the surgeon with an indication signal. Thereafter the surgeon may manually activate the first motor 3310 to retract the cutting instrument 3232 to the starting position or the robotic controller 1001 may automatically activate the first motor 3310 to retract the cutting element 3232.

The embodiment depicted in FIG. 75 does not include an articulation joint. FIGS. 64 and 65 illustrate surgical tools 3200' and 3200" that have end effectors 3212', 3212", respectively that may be employed with an elongated shaft embodiment that has an articulation joint of the various types disclosed herein. For example, as can be seen in FIG. 76, a threaded closure shaft 3342 is coupled to the proximal end 3223 of the elongated channel 3222 by a flexible cable or other flexible member 3345. The location of an articulation joint (not shown) within the elongated shaft assembly 3208 will coincide with the flexible member 3345 to enable the flexible member 3345 to accommodate such articulation. In addition, in the above-described embodiment, the flexible member 33345 is rotatably affixed to the proximal end portion 3223 of the elongated channel 3222 to enable the flexible member 3345 to rotate relative thereto to prevent the flexible member 3229 from "winding up" relative to the channel 3222. Although not shown, the cutting element may be driven in one of the above described manners by a knife bar that can also accommodate articulation of the elongated shaft assembly. FIG. 77 depicts a surgical end effector 3212" that is substantially identical to the surgical end effector 3212 described above, except that the threaded closure rod 3342 is attached to a closure nut 3347 that is constrained to only move axially within the elongated shaft assembly 3208. The flexible member 3345 is attached to the closure nut 3347. Such arrangement also prevents the threaded closure rod 3342 from winding-up the flexible member 3345. A flexible knife bar 3235' may be employed to facilitate articulation of the surgical end effector 3212".

The surgical tools 3200, 3200', and 3200" described above may also employ anyone of the cutting instrument embodiments described herein. As described above, the anvil of each of the end effectors of these tools is closed by drawing the elongated channel into contact with the distal end of the elongated shaft assembly. Thus, once the target tissue has been located between the staple cartridge 3234 and the anvil 3224, the robotic controller 1001 can start to draw the channel 3222 inward into the shaft assembly 3208. In various embodiments, however, to prevent the end effector 3212, 3212', 3212" from moving the target tissue with the end effector during this closing process, the controller 1001 may simultaneously move the tool holder and ultimately the tool such to compensate for the movement of the elongated channel 3222 so that, in effect, the target tissue is clamped between the anvil and the elongated channel without being otherwise moved.

FIGS. 78-80 depict another surgical tool embodiment 3201 that is substantially identical to surgical tool 3200" described above, except for the differences discussed below. In this embodiment, the threaded closure rod 3342' has variable pitched grooves. More specifically, as can be seen in FIG. 79, the closure rod 3342' has a distal groove section 3380 and a proximal groove section 3382. The distal and proximal groove sections 3380, 3382 are configured for engagement with a lug 3390 supported within the hollow threaded end portion 3341'. As can be seen in FIG. 79, the distal groove section 3380 has a finer pitch than the groove section 3382. Thus, such variable pitch arrangement permits the elongated channel 3222 to be drawn into the shaft 3208 at a first speed or rate by virtue of the engagement between the lug 3390 and the proximal groove segment 3382. When the lug 3390 engages the distal groove segment, the channel 3222 will be drawn into the shaft 3208 at a second speed or rate. Because the proximal groove segment 3382 is coarser than the distal groove segment 3380, the first speed will be greater than the second speed. Such arrangement serves to speed up the initial closing of the end effector for tissue manipulation and then after the tissue has been properly positioned therein, generate the amount of closure forces to properly clamp the tissue for cutting and sealing. Thus, the anvil 3234 initially closes fast with a lower force and then applies a higher closing force as the anvil closes more slowly.

The surgical end effector opening and closing motions are employed to enable the user to use the end effector to grasp and manipulate tissue prior to fully clamping it in the desired location for cutting and sealing. The user may, for example, open and close the surgical end effector numerous times during this process to orient the end effector in a proper position which enables the tissue to be held in a desired location. Thus, in at least some embodiments, to produce the high loading for firing, the fine thread may require as many as 5-10 full rotations to generate the necessary load. In some cases, for example, this action could take as long as 2-5 seconds. If it also took an equally long time to open and close the end effector each time during the positioning/tissue manipulation process, just positioning the end effector may take an undesirably long time. If that happens, it is possible that a user may abandon such use of the end effector for use of a conventional grasper device. Use of graspers, etc. may undesirably increase the costs associated with completing the surgical procedure.

The above-described embodiments employ a battery or batteries to power the motors used to drive the end effector components. Activation of the motors is controlled by the

robotic system **1000**. In alternative embodiments, the power supply may comprise alternating current "AC" that is supplied to the motors by the robotic system **1000**. That is, the AC power would be supplied from the system powering the robotic system **1000** through the tool holder and adapter. In still other embodiments, a power cord or tether may be attached to the tool mounting portion **3300** to supply the requisite power from a separate source of alternating or direct current.

In use, the controller **1001** may apply an initial rotary motion to the closure shaft **3340** (FIG. **75**) to draw the elongated channel **3222** axially inwardly into the elongated shaft assembly **3208** and move the anvil from a first position to an intermediate position at a first rate that corresponds with the point wherein the distal groove section **3380** transitions to the proximal groove section **3382**. Further application of rotary motion to the closure shaft **3340** will cause the anvil to move from the intermediate position to the closed position relative to the surgical staple cartridge. When in the closed position, the tissue to be cut and stapled is properly clamped between the anvil and the surgical staple cartridge.

FIGS. **81-85** illustrate another surgical tool embodiment **3400** of the present invention. This embodiment includes an elongated shaft assembly **3408** that extends from a tool mounting portion **3500**. The elongated shaft assembly **3408** includes a rotatable proximal closure tube segment **3410** that is rotatably journaled on a proximal spine member **3420** that is rigidly coupled to a tool mounting plate **3502** of the tool mounting portion **3500**. The proximal spine member **3420** has a distal end **3422** that is coupled to an elongated channel portion **3522** of a surgical end effector **3412**. For example, in at least one embodiment, the elongated channel portion **3522** has a distal end portion **3523** that "hookingly engages" the distal end **3422** of the spine member **3420**. The elongated channel **3522** is configured to support a surgical staple cartridge **3534** therein. This embodiment may employ one of the various cutting instrument embodiments disclosed herein to sever tissue that is clamped in the surgical end effector **3412** and fire the staples in the staple cartridge **3534** into the severed tissue.

Surgical end effector **3412** has an anvil **3524** that is pivotally coupled to the elongated channel **3522** by a pair of trunnions **3525** that are received in corresponding openings **3529** in the elongated channel **3522**. The anvil **3524** is moved between the open (FIG. **81**) and closed positions (FIGS. **82-84**) by a distal closure tube segment **3430**. A distal end portion **3432** of the distal closure tube segment **3430** includes an opening **3445** into which a tab **3527** on the anvil **3524** is inserted in order to open and close the anvil **3524** as the distal closure tube segment **3430** moves axially relative thereto. In various embodiments, the opening **3445** is shaped such that as the closure tube segment **3430** is moved in the proximal direction, the closure tube segment **3430** causes the anvil **3524** to pivot to an open position. In addition or in the alternative, a spring (not shown) may be employed to bias the anvil **3524** to the open position.

As can be seen in FIGS. **81-84**, the distal closure tube segment **3430** includes a lug **3442** that extends from its distal end **3440** into threaded engagement with a variable pitch groove/thread **3414** formed in the distal end **3412** of the rotatable proximal closure tube segment **3410**. The variable pitch groove/thread **3414** has a distal section **3416** and a proximal section **3418**. The pitch of the distal groove/thread section **3416** is finer than the pitch of the proximal groove/thread section **3418**. As can also be seen in FIGS. **81-84**, the distal closure tube segment **3430** is constrained for axial movement relative to the spine member **3420** by an axial retainer pin **3450** that is received in an axial slot **3424** in the distal end of the spine member **3420**.

As indicated above, the anvil **2524** is open and closed by rotating the proximal closure tube segment **3410**. The variable pitch thread arrangement permits the distal closure tube segment **3430** to be driven in the distal direction "DD" at a first speed or rate by virtue of the engagement between the lug **3442** and the proximal groove/thread section **3418**. When the lug **3442** engages the distal groove/thread section **3416**, the distal closure tube segment **3430** will be driven in the distal direction at a second speed or rate. Because the proximal groove/thread section **3418** is coarser than the distal groove/thread segment **3416**, the first speed will be greater than the second speed.

In at least one embodiment, the tool mounting portion **3500** is configured to receive a corresponding first rotary motion from the robotic controller **1001** and convert that first rotary motion to a primary rotary motion for rotating the rotatable proximal closure tube segment **3410** about a longitudinal tool axis LT-LT. As can be seen in FIG. **85**, a proximal end **3460** of the proximal closure tube segment **3410** is rotatably supported within a cradle arrangement **3504** attached to a tool mounting plate **3502** of the tool mounting portion **3500**. A rotation gear **3462** is formed on or attached to the proximal end **3460** of the closure tube segment **3410** for meshing engagement with a rotation drive assembly **3470** that is operably supported on the tool mounting plate **3502**. In at least one embodiment, a rotation drive gear **3472** is coupled to a corresponding first one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **3502** when the tool mounting portion **3500** is coupled to the tool holder **1270**. See FIGS. **43** and **85**. The rotation drive assembly **3470** further comprises a rotary driven gear **3474** that is rotatably supported on the tool mounting plate **3502** in meshing engagement with the rotation gear **3462** and the rotation drive gear **3472**. Application of a first rotary control motion from the robotic controller **1001** through the tool holder **1270** and the adapter **1240** to the corresponding driven element **1304** will thereby cause rotation of the rotation drive gear **3472** by virtue of being operably coupled thereto. Rotation of the rotation drive gear **3472** ultimately results in the rotation of the closure tube segment **3410** to open and close the anvil **3524** as described above.

As indicated above, the surgical end effector **3412** employs a cutting instrument of the type and constructions described above. FIG. **85** illustrates one form of knife drive assembly **3480** for axially advancing a knife bar **3492** that is attached to such cutting instrument. One form of the knife drive assembly **3480** comprises a rotary drive gear **3482** that is coupled to a corresponding third one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **3502** when the tool drive portion **3500** is coupled to the tool holder **1270**. See FIGS. **43** and **85**. The knife drive assembly **3480** further comprises a first rotary driven gear assembly **3484** that is rotatably supported on the tool mounting plate **5200**. The first rotary driven gear assembly **3484** is in meshing engagement with a third rotary driven gear assembly **3486** that is rotatably supported on the tool mounting plate **3502** and which is in meshing engagement with a fourth rotary driven gear assembly **3488** that is in meshing engagement with a threaded portion **3494** of drive shaft assembly **3490** that is coupled to the knife bar **3492**. Rotation of the rotary drive gear **3482** in a second rotary direction will result in the axial advancement of the drive shaft assembly **3490** and knife bar **3492** in the distal direction "DD". Conversely, rotation of the rotary drive gear **3482** in a secondary rotary direction (opposite to the second

rotary direction) will cause the drive shaft assembly **3490** and the knife bar **3492** to move in the proximal direction.

FIGS. **86-95** illustrate another surgical tool **3600** embodiment of the present invention that may be employed in connection with a robotic system **1000**. As can be seen in FIG. **86**, the tool **3600** includes an end effector in the form of a disposable loading unit **3612**. Various forms of disposable loading units that may be employed in connection with tool **3600** are disclosed, for example, in U.S. Patent Application Publication No. US 2009/0206131 A1, entitled "End Effector Arrangements for a Surgical Cutting and Stapling Instrument", the disclosure of which is herein incorporated by reference in its entirety.

In at least one form, the disposable loading unit **3612** includes an anvil assembly **3620** that is supported for pivotal travel relative to a carrier **3630** that operably supports a staple cartridge **3640** therein. A mounting assembly **3650** is pivotally coupled to the cartridge carrier **3630** to enable the carrier **3630** to pivot about an articulation axis AA-AA relative to a longitudinal tool axis LT-LT. Referring to FIG. **91**, mounting assembly **3650** includes upper and lower mounting portions **3652** and **3654**. Each mounting portion includes a threaded bore **3656** on each side thereof dimensioned to receive threaded bolts (not shown) for securing the proximal end of carrier **3630** thereto. A pair of centrally located pivot members **3658** extends between upper and lower mounting portions via a pair of coupling members **3660** which engage a distal end of a housing portion **3662**. Coupling members **3660** each include an interlocking proximal portion **3664** configured to be received in grooves **3666** formed in the proximal end of housing portion **3662** to retain mounting assembly **3650** and housing portion **3662** in a longitudinally fixed position in relation thereto.

In various forms, housing portion **3662** of disposable loading unit **3614** includes an upper housing half **3670** and a lower housing half **3672** contained within an outer casing **3674**. The proximal end of housing half **3670** includes engagement nubs **3676** for releasably engaging an elongated shaft **3700** and an insertion tip **3678**. Nubs **3676** form a bayonet-type coupling with the distal end of the elongated shaft **3700** which will be discussed in further detail below. Housing halves **3670**, **3672** define a channel **3674** for slidably receiving axial drive assembly **3680**. A second articulation link **3690** is dimensioned to be slidably positioned within a slot **3679** formed between housing halves **3670**, **3672**. A pair of blow out plates **3691** are positioned adjacent the distal end of housing portion **3662** adjacent the distal end of axial drive assembly **3680** to prevent outward bulging of drive assembly **3680** during articulation of carrier **3630**.

In various embodiments, the second articulation link **3690** includes at least one elongated metallic plate. Preferably, two or more metallic plates are stacked to form link **3690**. The proximal end of articulation link **3690** includes a hook portion **3692** configured to engage first articulation link **3710** extending through the elongated shaft **3700**. The distal end of the second articulation link **3690** includes a loop **3694** dimensioned to engage a projection formed on mounting assembly **3650**. The projection is laterally offset from pivot pin **3658** such that linear movement of second articulation link **3690** causes mounting assembly **3650** to pivot about pivot pins **3658** to articulate the carrier **3630**.

In various forms, axial drive assembly **3680** includes an elongated drive beam **3682** including a distal working head **3684** and a proximal engagement section **3685**. Drive beam **3682** may be constructed from a single sheet of material or, preferably, multiple stacked sheets. Engagement section **3685** includes a pair of engagement fingers which are dimensioned and configured to mountingly engage a pair of corresponding retention slots formed in drive member **3686**. Drive member **3686** includes a proximal porthole **3687** configured to receive the distal end **3722** of control rod **2720** (See FIG. **95**) when the proximal end of disposable loading unit **3614** is engaged with elongated shaft **3700** of surgical tool **3600**.

Referring to FIGS. **86** and **93-95**, to use the surgical tool **3600**, a disposable loading unit **3612** is first secured to the distal end of elongated shaft **3700**. It will be appreciated that the surgical tool **3600** may include an articulating or a non-articulating disposable loading unit. To secure the disposable loading unit **3612** to the elongated shaft **3700**, the distal end **3722** of control rod **3720** is inserted into insertion tip **3678** of disposable loading unit **3612**, and insertion tip **3678** is slid longitudinally into the distal end of the elongated shaft **3700** in the direction indicated by arrow "A" in FIG. **93** such that hook portion **3692** of second articulation link **3690** slides within a channel **3702** in the elongated shaft **3700**. Nubs **3676** will each be aligned in a respective channel (not shown) in elongated shaft **3700**. When hook portion **3692** engages the proximal wall **3704** of channel **3702**, disposable loading unit **3612** is rotated in the direction indicated by arrow "B" in FIGS. **92** and **95** to move hook portion **3692** of second articulation link **3690** into engagement with finger **3712** of first articulation link **3710**. Nubs **3676** also form a "bayonet-type" coupling within annular channel **3703** in the elongated shaft **3700**. During rotation of loading unit **3612**, nubs **3676** engage cam surface **3732** (FIG. **81**) of block plate **3730** to initially move plate **3730** in the direction indicated by arrow "C" in FIG. **93** to lock engagement member **3734** in recess **3721** of control rod **3720** to prevent longitudinal movement of control rod **3720** during attachment of disposable loading unit **3612**. During the final degree of rotation, nubs **3676** disengage from cam surface **3732** to allow blocking plate **3730** to move in the direction indicated by arrow "D" in FIGS. **92** and **95** from behind engagement member **3734** to once again permit longitudinal movement of control rod **3720**. While the above-described attachment method reflects that the disposable loading unit **3612** is manipulated relative to the elongated shaft **3700**, the person of ordinary skill in the art will appreciate that the disposable loading unit **3612** may be supported in a stationary position and the robotic system **1000** may manipulate the elongated shaft portion **3700** relative to the disposable loading unit **3612** to accomplish the above-described coupling procedure.

FIG. **96** illustrates another disposable loading unit **3612'** that is attachable in a bayonet-type arrangement with the elongated shaft **3700'** that is substantially identical to shaft **3700** except for the differences discussed below. As can be seen in FIG. **96**, the elongated shaft **3700'** has slots **3705** that extend for at least a portion thereof and which are configured to receive nubs **3676** therein. In various embodiments, the disposable loading unit **3612'** includes arms **3677** extending therefrom which, prior to the rotation of disposable loading unit **3612'**, can be aligned, or at least substantially aligned, with nubs **3676** extending from housing portion **3662**. In at least one embodiment, arms **3677** and nubs **3676** can be inserted into slots **3705** in elongated shaft **3700'**, for example, when disposable loading unit **3612'** is inserted into elongated shaft **3700'**. When disposable loading unit **3612'** is rotated, arms **3677** can be sufficiently confined within slots **3705** such that slots **3705** can hold them in position, whereas nubs **3676** can be positioned such that they are not confined within slots **3705** and can be rotated relative to arms **3677**. When rotated, the hook portion **3692** of the articulation link **3690** is engaged with the first articulation link **3710** extending through the elongated shaft **3700'**.

Other methods of coupling the disposable loading units to the end of the elongated shaft may be employed. For example, as shown in FIGS. **97** and **98**, disposable loading unit **3612"** can include connector portion **3613** which can be configured to be engaged with connector portion **3740** of the elongated shaft **3700"**. In at least one embodiment, connector portion **3613** can include at least one projection and/or groove which can be mated with at least one projection and/or groove of connector portion **3740**. In at least one such embodiment, the connector portions can include co-operating dovetail portions. In various embodiments, the connector portions can be configured to interlock with one another and prevent, or at least inhibit, distal and/or proximal movement of disposable loading unit **3612"** along axis **3741**. In at least one embodiment, the distal end of the axial drive assembly **3680'** can include aperture **3681** which can be configured to receive projection **3721** extending from control rod **3720'**. In various embodiments, such an arrangement can allow disposable loading unit **3612"** to be assembled to elongated shaft **3700** in a direction which is not collinear with or parallel to axis **3741**. Although not illustrated, axial drive assembly **3680'** and control rod **3720** can include any other suitable arrangement of projections and apertures to operably connect them to each other. Also in this embodiment, the first articulation link **3710** which can be operably engaged with second articulation link **3690**.

As can be seen in FIGS. **86** and **99**, the surgical tool **3600** includes a tool mounting portion **3750**. The tool mounting portion **3750** includes a tool mounting plate **3751** that is configured for attachment to the tool drive assembly **1010**. The tool mounting portion operably supported a transmission arrangement **3752** thereon. In use, it may be desirable to rotate the disposable loading unit **3612** about the longitudinal tool axis defined by the elongated shaft **3700**. In at least one embodiment, the transmission arrangement **3752** includes a rotational transmission assembly **3753** that is configured to receive a corresponding rotary output motion from the tool drive assembly **1010** of the robotic system **1000** and convert that rotary output motion to a rotary control motion for rotating the elongated shaft **3700** (and the disposable loading unit **3612**) about the longitudinal tool axis LT-LT. As can be seen in FIG. **99**, a proximal end **3701** of the elongated shaft **3700** is rotatably supported within a cradle arrangement **3754** that is attached to the tool mounting plate **3751** of the tool mounting portion **3750**. A rotation gear **3755** is formed on or attached to the proximal end **3701** of the elongated shaft **3700** for meshing engagement with a rotation gear assembly **3756** operably supported on the tool mounting plate **3751**. In at least one embodiment, a rotation drive gear **3757** drivingly coupled to a corresponding first one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **3751** when the tool mounting portion **3750** is coupled to the tool drive assembly **1010**. The rotation transmission assembly **3753** further comprises a rotary driven gear **3758** that is rotatably supported on the tool mounting plate **3751** in meshing engagement with the rotation gear **3755** and the rotation drive gear **3757**. Application of a first rotary output motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding driven element **1304** will thereby cause rotation of the rotation drive gear **3757** by virtue of being operably coupled thereto. Rotation of the rotation drive gear **3757** ultimately results in the rotation of the elongated shaft **3700** (and the disposable loading unit **3612**) about the longitudinal tool axis LT-LT (primary rotary motion).

As can be seen in FIG. **99**, a drive shaft assembly **3760** is coupled to a proximal end of the control rod **2720**. In various embodiments, the control rod **2720** is axially advanced in the distal and proximal directions by a knife/closure drive transmission **3762**. One form of the knife/closure drive assembly **3762** comprises a rotary drive gear **3763** that is coupled to a corresponding second one of the driven rotatable body portions, discs or elements **1304** on the adapter side of the tool mounting plate **3751** when the tool mounting portion **3750** is coupled to the tool holder **1270**. The rotary driven gear **3763** is in meshing driving engagement with a gear train, generally depicted as **3764**. In at least one form, the gear train **3764** further comprises a first rotary driven gear assembly **3765** that is rotatably supported on the tool mounting plate **3751**. The first rotary driven gear assembly **3765** is in meshing engagement with a second rotary driven gear assembly **3766** that is rotatably supported on the tool mounting plate **3751** and which is in meshing engagement with a third rotary driven gear assembly **3767** that is in meshing engagement with a threaded portion **3768** of the drive shaft assembly **3760**. Rotation of the rotary drive gear **3763** in a second rotary direction will result in the axial advancement of the drive shaft assembly **3760** and control rod **2720** in the distal direction "DD". Conversely, rotation of the rotary drive gear **3763** in a secondary rotary direction which is opposite to the second rotary direction will cause the drive shaft assembly **3760** and the control rod **2720** to move in the proximal direction. When the control rod **2720** moves in the distal direction, it drives the drive beam **3682** and the working head **3684** thereof distally through the surgical staple cartridge **3640**. As the working head **3684** is driven distally, it operably engages the anvil **3620** to pivot it to a closed position.

The cartridge carrier **3630** may be selectively articulated about articulation axis AA-AA by applying axial articulation control motions to the first and second articulation links **3710** and **3690**. In various embodiments, the transmission arrangement **3752** further includes an articulation drive **3770** that is operably supported on the tool mounting plate **3751**. More specifically and with reference to FIG. **99**, it can be seen that a proximal end portion **3772** of an articulation drive shaft **3771** configured to operably engage with the first articulation link **3710** extends through the rotation gear **3755** and is rotatably coupled to a shifter rack gear **3774** that is slidably affixed to the tool mounting plate **3751** through slots **3775**. The articulation drive **3770** further comprises a shifter drive gear **3776** that is coupled to a corresponding third one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **3751** when the tool mounting portion **3750** is coupled to the tool holder **1270**. The articulation drive assembly **3770** further comprises a shifter driven gear **3778** that is rotatably supported on the tool mounting plate **3751** in meshing engagement with the shifter drive gear **3776** and the shifter rack gear **3774**. Application of a third rotary output motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding driven element **1304** will thereby cause rotation of the shifter drive gear **3776** by virtue of being operably coupled thereto. Rotation of the shifter drive gear **3776** ultimately results in the axial movement of the shifter gear rack **3774** and the articulation drive shaft **3771**. The direction of axial travel of the articulation drive shaft **3771** depends upon the direction in which the shifter drive gear **3776** is rotated by the robotic system **1000**. Thus, rotation of the shifter drive gear **3776** in a first rotary direction will result in the axial movement of the articulation drive shaft **3771** in the proximal direction "PD" and cause the cartridge carrier **3630** to pivot in a first direction about articulation axis AA-AA. Conversely, rotation of the shifter drive gear **3776** in a second rotary direction (opposite to the first rotary direction) will result in the axial movement of the articulation drive

shaft **3771** in the distal direction "DD" to thereby cause the cartridge carrier **3630** to pivot about articulation axis AA-AA in an opposite direction.

FIG. **100** illustrates yet another surgical tool **3800** embodiment of the present invention that may be employed with a robotic system **1000**. As can be seen in FIG. **100**, the surgical tool **3800** includes a surgical end effector **3812** in the form of an endocutter **3814** that employs various cable-driven components. Various forms of cable driven endocutters are disclosed, for example, in U.S. Pat. No. 7,726,537, entitled "Surgical Stapler With Universal Articulation and Tissue Pre-Clamp" and U.S. Patent Application Publication No. US 2008/0308603A1, entitled "Cable Driven Surgical Stapling and Cutting Instrument With Improved Cable Attachment Arrangements", the disclosures of each are herein incorporated by reference in their respective entireties. Such endocutters **3814** may be referred to as a "disposable loading unit" because they are designed to be disposed of after a single use. However, the various unique and novel arrangements of various embodiments of the present invention may also be employed in connection with cable driven end effectors that are reusable.

As can be seen in FIG. **100**, in at least one form, the endocutter **3814** includes an elongated channel **3822** that operably supports a surgical staple cartridge **3834** therein. An anvil **3824** is pivotally supported for movement relative to the surgical staple cartridge **3834**. The anvil **3824** has a cam surface **3825** that is configured for interaction with a pre-clamping collar **3840** that is supported for axial movement relative thereto. The end effector **3814** is coupled to an elongated shaft assembly **3808** that is attached to a tool mounting portion **3900**. In various embodiments, a closure cable **3850** is employed to move pre-clamping collar **3840** distally onto and over cam surface **3825** to close the anvil **3824** relative to the surgical staple cartridge **3834** and compress the tissue therebetween. Preferably, closure cable **3850** attaches to the pre-clamping collar **3840** at or near point **3841** and is fed through a passageway in anvil **3824** (or under a proximal portion of anvil **3824**) and fed proximally through shaft **3808**. Actuation of closure cable **3850** in the proximal direction "PD" forces pre-clamping collar **3840** distally against cam surface **3825** to close anvil **3824** relative to staple cartridge assembly **3834**. A return mechanism, e.g., a spring, cable system or the like, may be employed to return pre-clamping collar **3840** to a pre-clamping orientation which re-opens the anvil **3824**.

The elongated shaft assembly **3808** may be cylindrical in shape and define a channel **3811** which may be dimensioned to receive a tube adapter **3870**. See FIG. **101**. In various embodiments, the tube adapter **3870** may be slidingly received in friction-fit engagement with the internal channel of elongated shaft **3808**. The outer surface of the tube adapter **3870** may further include at least one mechanical interface, e.g., a cutout or notch **3871**, oriented to mate with a corresponding mechanical interface, e.g., a radially inwardly extending protrusion or detent (not shown), disposed on the inner periphery of internal channel **3811** to lock the tube adapter **3870** to the elongated shaft **3808**. In various embodiments, the distal end of tube adapter **3870** may include a pair of opposing flanges **3872***a* and **3872***b* which define a cavity for pivotably receiving a pivot block **3873** therein. Each flange **3872***a* and **3872***b* may include an aperture **3874***a* and **3874***b* that is oriented to receive a pivot pin **3875** that extends through an aperture in pivot block **3873** to allow pivotable movement of pivot block **3873** about an axis that is perpendicular to longitudinal tool axis "LT-LT". The channel **3822** may be formed with two upwardly extending flanges **3823***a*, **3823***b* that have apertures therein, which are dimensioned to receive a pivot pin **3827**. In turn, pivot pin **3875** mounts through apertures in pivot block **3873** to permit rotation of the surgical end effector **3814** about the "Y" axis as needed during a given surgical procedure. Rotation of pivot block **3873** about pin **3875** along "Z" axis rotates the surgical end effector **3814** about the "Z" axis. See FIG. **101**. Other methods of fastening the elongated channel **3822** to the pivot block **3873** may be effectively employed without departing from the spirit and scope of the present invention.

The surgical staple cartridge **3834** can be assembled and mounted within the elongated channel **3822** during the manufacturing or assembly process and sold as part of the surgical end effector **3812**, or the surgical staple cartridge **3834** may be designed for selective mounting within the elongated channel **3822** as needed and sold separately, e.g., as a single use replacement, replaceable or disposable staple cartridge assembly. It is within the scope of this disclosure that the surgical end effector **3812** may be pivotally, operatively, or integrally attached, for example, to distal end **3809** of the elongated shaft assembly **3808** of a disposable surgical stapler. As is known, a used or spent disposable loading unit **3814** can be removed from the elongated shaft assembly **3808** and replaced with an unused disposable unit. The endocutter **3814** may also preferably include an actuator, preferably a dynamic clamping member **3860**, a sled **3862**, as well as staple pushers (not shown) and staples (not shown) once an unspent or unused cartridge **3834** is mounted in the elongated channel **3822**. See FIG. **101**.

In various embodiments, the dynamic clamping member **3860** is associated with, e.g., mounted on and rides on, or with or is connected to or integral with and/or rides behind sled **3862**. It is envisioned that dynamic clamping member **3860** can have cam wedges or cam surfaces attached or integrally formed or be pushed by a leading distal surface thereof. In various embodiments, dynamic clamping member **3860** may include an upper portion **3863** having a transverse aperture **3864** with a pin **3865** mountable or mounted therein, a central support or upward extension **3866** and substantially T-shaped bottom flange **3867** which cooperate to slidingly retain dynamic clamping member **3860** along an ideal cutting path during longitudinal, distal movement of sled **3862**. The leading cutting edge **3868**, here, knife blade **3869**, is dimensioned to ride within slot **3835** of staple cartridge assembly **3834** and separate tissue once stapled. As used herein, the term "knife assembly" may include the aforementioned dynamic clamping member **3860**, knife **3869**, and sled **3862** or other knife/beam/sled drive arrangements and cutting instrument arrangements. In addition, the various embodiments of the present invention may be employed with knife assembly/cutting instrument arrangements that may be entirely supported in the staple cartridge **3834** or partially supported in the staple cartridge **3834** and elongated channel **3822** or entirely supported within the elongated channel **3822**.

In various embodiments, the dynamic clamping member **3860** may be driven in the proximal and distal directions by a cable drive assembly **3870**. In one non-limiting form, the cable drive assembly comprises a pair of advance cables **3880**, **3882** and a firing cable **3884**. FIGS. **102** and **103** illustrate the cables **3880**, **3882**, **3884** in diagrammatic form. As can be seen in those Figures, a first advance cable **3880** is operably supported on a first distal cable transition support **3885** which may comprise, for example, a pulley, rod, capstan, etc. that is attached to the distal end of the elongated channel **3822** and a first proximal cable transition support **3886** which may comprise, for example, a pulley, rod, capstan, etc. that is operably supported by the elongated channel **3822**. A distal end **3881** of the first advance cable **3880** is

affixed to the dynamic clamping assembly **3860**. The second advance cable **3882** is operably supported on a second distal cable transition support **3887** which may, for example, comprise a pulley, rod, capstan etc. that is mounted to the distal end of the elongated channel **3822** and a second proximal cable transition support **3888** which may, for example, comprise a pulley, rod, capstan, etc. mounted to the proximal end of the elongated channel **3822**. The proximal end **3883** of the second advance cable **3882** may be attached to the dynamic clamping assembly **3860**. Also in these embodiments, an endless firing cable **3884** is employed and journaled on a support **3889** that may comprise a pulley, rod, capstan, etc. mounted within the elongated shaft **3808**. In one embodiment, the retract cable **3884** may be formed in a loop and coupled to a connector **3889'** that is fixedly attached to the first and second advance cables **3880**, **3882**.

Various non-limiting embodiments of the present invention include a cable drive transmission **3920** that is operably supported on a tool mounting plate **3902** of the tool mounting portion **3900**. The tool mounting portion **3900** has an array of electrical connecting pins **3904** which are configured to interface with the slots **1258** (FIG. **42**) in the adapter **1240'**. Such arrangement permits the robotic system **1000** to provide control signals to a control circuit **3910** of the tool **3800**. While the interface is described herein with reference to mechanical, electrical, and magnetic coupling elements, it should be understood that a wide variety of telemetry modalities might be used, including infrared, inductive coupling, or the like.

Control circuit **3910** is shown in schematic form in FIG. **100**. In one form or embodiment, the control circuit **3910** includes a power supply in the form of a battery **3912** that is coupled to an on-off solenoid powered switch **3914**. In other embodiments, however, the power supply may comprise a source of alternating current. Control circuit **3910** further includes an on/off solenoid **3916** that is coupled to a double pole switch **3918** for controlling motor rotation direction. Thus, when the robotic system **1000** supplies an appropriate control signal, switch **3914** will permit battery **3912** to supply power to the double pole switch **3918**. The robotic system **1000** will also supply an appropriate signal to the double pole switch **3918** to supply power to a shifter motor **3922**.

Turning to FIGS. **104-109**, at least one embodiment of the cable drive transmission **3920** comprises a drive pulley **3930** that is operably mounted to a drive shaft **3932** that is attached to a driven element **1304** of the type and construction described above that is designed to interface with a corresponding drive element **1250** of the adapter **1240**. See FIGS. **42** and **96**. Thus, when the tool mounting portion **3900** is operably coupled to the tool holder **1270**, the robot system **1000** can apply rotary motion to the drive pulley **3930** in a desired direction. A first drive member or belt **3934** drivingly engages the drive pulley **3930** and a second drive shaft **3936** that is rotatably supported on a shifter yoke **3940**. The shifter yoke **3940** is operably coupled to the shifter motor **3922** such that rotation of the shaft **3923** of the shifter motor **3922** in a first direction will shift the shifter yoke in a first direction "FD" and rotation of the shifter motor shaft **3923** in a second direction will shift the shifter yoke **3940** in a second direction "SD". Other embodiments of the present invention may employ a shifter solenoid arrangement for shifting the shifter yoke in said first and second directions.

As can be seen in FIGS. **104-107**, a closure drive gear **3950** mounted to a second drive shaft **3936** and is configured to selectively mesh with a closure drive assembly, generally designated as **3951**. Likewise a firing drive gear **3960** is also mounted to the second drive shaft **3936** and is configured to selectively mesh with a firing drive assembly generally designated as **3961**. Rotation of the second drive shaft **3936** causes the closure drive gear **3950** and the firing drive gear **3960** to rotate. In one non-limiting embodiment, the closure drive assembly **3951** comprises a closure driven gear **3952** that is coupled to a first closure pulley **3954** that is rotatably supported on a third drive shaft **3956**. The closure cable **3850** is drivingly received on the first closure pulley **3954** such that rotation of the closure driven gear **3952** will drive the closure cable **3850**. Likewise, the firing drive assembly **3961** comprises a firing driven gear **3962** that is coupled to a first firing pulley **3964** that is rotatably supported on the third drive shaft **3956**. The first and second driving pulleys **3954** and **3964** are independently rotatable on the third drive shaft **3956**. The firing cable **3884** is drivingly received on the first firing pulley **3964** such that rotation of the firing driven gear **3962** will drive the firing cable **3884**.

Also in various embodiments, the cable drive transmission **3920** further includes a braking assembly **3970**. In at least one embodiment, for example, the braking assembly **3970** includes a closure brake **3972** that comprises a spring arm **3973** that is attached to a portion of the transmission housing **3971**. The closure brake **3972** has a gear lug **3974** that is sized to engage the teeth of the closure driven gear **3952** as will be discussed in further detail below. The braking assembly **3970** further includes a firing brake **3976** that comprises a spring arm **3977** that is attached to another portion of the transmission housing **3971**. The firing brake **3976** has a gear lug **3978** that is sized to engage the teeth of the firing driven gear **3962**.

At least one embodiment of the surgical tool **3800** may be used as follows. The tool mounting portion **3900** is operably coupled to the interface **1240** of the robotic system **1000**. The controller or control unit of the robotic system is operated to locate the tissue to be cut and stapled between the open anvil **3824** and the staple cartridge **3834**. When in that initial position, the braking assembly **3970** has locked the closure driven gear **3952** and the firing driven gear **3962** such that they cannot rotate. That is, as shown in FIG. **105**, the gear lug **3974** is in locking engagement with the closure driven gear **3952** and the gear lug **3978** is in locking engagement with the firing driven gear **3962**. Once the surgical end effector **3814** has been properly located, the controller **1001** of the robotic system **1000** will provide a control signal to the shifter motor **3922** (or shifter solenoid) to move the shifter yoke **3940** in the first direction. As the shifter yoke **3940** is moved in the first direction, the closure drive gear **3950** moves the gear lug **3974** out of engagement with the closure driven gear **3952** as it moves into meshing engagement with the closure driven gear **3952**. As can be seen in FIG. **104**, when in that position, the gear lug **3978** remains in locking engagement with the firing driven gear **3962** to prevent actuation of the firing system. Thereafter, the robotic controller **1001** provides a first rotary actuation motion to the drive pulley **3930** through the interface between the driven element **1304** and the corresponding components of the tool holder **1240**. As the drive pulley **3930** is rotated in the first direction, the closure cable **3850** is rotated to drive the preclamping collar **3840** into closing engagement with the cam surface **3825** of the anvil **3824** to move it to the closed position thereby clamping the target tissue between the anvil **3824** and the staple cartridge **3834**. See FIG. **100**. Once the anvil **3824** has been moved to the closed position, the robotic controller **1001** stops the application of the first rotary motion to the drive pulley **3930**. Thereafter, the robotic controller **1001** may commence the firing process by sending another control signal to the shifter motor **3922** (or shifter solenoid) to cause the shifter yoke to move in the second direction "SD" as shown in FIG. **106**. As the shifter yoke **3940** is moved in the second direction, the

firing drive gear **3960** moves the gear lug **3978** out of engagement with the firing driven gear **3962** as it moves into meshing engagement with the firing driven gear **3962**. As can be seen in FIG. **94**, when in that position, the gear lug **3974** remains in locking engagement with the closure driven gear **3952** to prevent actuation of the closure system. Thereafter, the robotic controller **1001** is activated to provide the first rotary actuation motion to the drive pulley **3930** through the interface between the driven element **1304** and the corresponding components of the tool holder **1240**. As the drive pulley **3930** is rotated in the first direction, the firing cable **3884** is rotated to drive the dynamic clamping member **3860** in the distal direction "DD" thereby firing the staples and cutting the tissue clamped in the end effector **3814**. Once the robotic system **1000** determines that the dynamic clamping member **3860** has reached its distal most position—either through sensors or through monitoring the amount of rotary input applied to the drive pulley **3930**, the controller **1001** may then apply a second rotary motion to the drive pulley **3930** to rotate the closure cable **3850** in an opposite direction to cause the dynamic clamping member **3860** to be retracted in the proximal direction "PD". Once the dynamic clamping member has been retracted to the starting position, the application of the second rotary motion to the drive pulley **3930** is discontinued. Thereafter, the shifter motor **3922** (or shifter solenoid) is powered to move the shifter yoke **3940** to the closure position (FIG. **104**). Once the closure drive gear **3950** is in meshing engagement with the closure driven gear **3952**, the robotic controller **1001** may once again apply the second rotary motion to the drive pulley **3930**. Rotation of the drive pulley **3930** in the second direction causes the closure cable **3850** to retract the preclamping collar **3840** out of engagement with the cam surface **3825** of the anvil **3824** to permit the anvil **3824** to move to an open position (by a spring or other means) to release the stapled tissue from the surgical end effector **3814**.

FIG. **110** illustrates a surgical tool **4000** that employs a gear driven firing bar **4092** as shown in FIGS. **111-113**. This embodiment includes an elongated shaft assembly **4008** that extends from a tool mounting portion **4100**. The tool mounting portion **4100** includes a tool mounting plate **4102** that operable supports a transmission arrangement **4103** thereon. The elongated shaft assembly **4008** includes a rotatable proximal closure tube **4010** that is rotatably journaled on a proximal spine member **4020** that is rigidly coupled to the tool mounting plate **4102**. The proximal spine member **4020** has a distal end that is coupled to an elongated channel portion **4022** of a surgical end effector **4012**. The surgical effector **4012** may be substantially similar to surgical end effector **3412** described above. In addition, the anvil **4024** of the surgical end effector **4012** may be opened and closed by a distal closure tube **4030** that operably interfaces with the proximal closure tube **4010**. Distal closure tube **4030** is identical to distal closure tube **3430** described above. Similarly, proximal closure tube **4010** is identical to proximal closure tube segment **3410** described above.

Anvil **4024** is opened and closed by rotating the proximal closure tube **4010** in manner described above with respect to distal closure tube **3410**. In at least one embodiment, the transmission arrangement comprises a closure transmission, generally designated as **4011**. As will be further discussed below, the closure transmission **4011** is configured to receive a corresponding first rotary motion from the robotic system **1000** and convert that first rotary motion to a primary rotary motion for rotating the rotatable proximal closure tube **4010** about the longitudinal tool axis LT-LT. As can be seen in FIG. **113**, a proximal end **4060** of the proximal closure tube **4010** is rotatably supported within a cradle arrangement **4104** that is attached to a tool mounting plate **4102** of the tool mounting portion **4100**. A rotation gear **4062** is formed on or attached to the proximal end **4060** of the closure tube segment **4010** for meshing engagement with a rotation drive assembly **4070** that is operably supported on the tool mounting plate **4102**. In at least one embodiment, a rotation drive gear **4072** is coupled to a corresponding first one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **4102** when the tool mounting portion **4100** is coupled to the tool holder **1270**. See FIGS. **43** and **113**. The rotation drive assembly **4070** further comprises a rotary driven gear **4074** that is rotatably supported on the tool mounting plate **4102** in meshing engagement with the rotation gear **4062** and the rotation drive gear **4072**. Application of a first rotary control motion from the robotic system **1000** through the tool holder **1270** and the adapter **1240** to the corresponding driven element **1304** will thereby cause rotation of the rotation drive gear **4072** by virtue of being operably coupled thereto. Rotation of the rotation drive gear **4072** ultimately results in the rotation of the closure tube segment **4010** to open and close the anvil **4024** as described above.

As indicated above, the end effector **4012** employs a cutting element **3860** as shown in FIGS. **111** and **112**. In at least one non-limiting embodiment, the transmission arrangement **4103** further comprises a knife drive transmission that includes a knife drive assembly **4080**. FIG. **113** illustrates one form of knife drive assembly **4080** for axially advancing the knife bar **4092** that is attached to such cutting element using cables as described above with respect to surgical tool **3800**. In particular, the knife bar **4092** replaces the firing cable **3884** employed in an embodiment of surgical tool **3800**. One form of the knife drive assembly **4080** comprises a rotary drive gear **4082** that is coupled to a corresponding second one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **4102** when the tool mounting portion **4100** is coupled to the tool holder **1270**. See FIGS. **43** and **113**. The knife drive assembly **4080** further comprises a first rotary driven gear assembly **4084** that is rotatably supported on the tool mounting plate **4102**. The first rotary driven gear assembly **4084** is in meshing engagement with a third rotary driven gear assembly **4086** that is rotatably supported on the tool mounting plate **4102** and which is in meshing engagement with a fourth rotary driven gear assembly **4088** that is in meshing engagement with a threaded portion **4094** of drive shaft assembly **4090** that is coupled to the knife bar **4092**. Rotation of the rotary drive gear **4082** in a second rotary direction will result in the axial advancement of the drive shaft assembly **4090** and knife bar **4092** in the distal direction "DD". Conversely, rotation of the rotary drive gear **4082** in a secondary rotary direction (opposite to the second rotary direction) will cause the drive shaft assembly **4090** and the knife bar **4092** to move in the proximal direction. Movement of the firing bar **4092** in the proximal direction "PD" will drive the cutting element **3860** in the distal direction "DD". Conversely, movement of the firing bar **4092** in the distal direction "DD" will result in the movement of the cutting element **3860** in the proximal direction "PD".

FIGS. **114-120** illustrate yet another surgical tool **5000** that may be effectively employed in connection with a robotic system **1000**. In various forms, the surgical tool **5000** includes a surgical end effector **5012** in the form of a surgical stapling instrument that includes an elongated channel **5020** and a pivotally translatable clamping member, such as an anvil **5070**, which are maintained at a spacing that assures effective stapling and severing of tissue clamped in the surgical end effector **5012**. As can be seen in FIG. **116**, the elongated

channel **5020** may be substantially U-shaped in cross-section and be fabricated from, for example, titanium, 203 stainless steel, 304 stainless steel, 416 stainless steel, 17-4 stainless steel, 17-7 stainless steel, 6061 or 7075 aluminum, chromium steel, ceramic, etc. A substantially U-shaped metal channel pan **5022** may be supported in the bottom of the elongated channel **5020** as shown.

Various embodiments include an actuation member in the form of a sled assembly **5030** that is operably supported within the surgical end effector **5012** and axially movable therein between a staring position and an ending position in response to control motions applied thereto. In some forms, the metal channel pan **5022** has a centrally-disposed slot **5024** therein to movably accommodate a base portion **5032** of the sled assembly **5030**. The base portion **5032** includes a foot portion **5034** that is sized to be slidably received in a slot **5021** in the elongated channel **5020**. See FIG. **104**. As can be seen in FIGS. **115**, **116**, **119**, and **120**, the base portion **5032** of sled assembly **5030** includes an axially extending threaded bore **5036** that is configured to be threadedly received on a threaded drive shaft **5130** as will be discussed in further detail below. In addition, the sled assembly **5030** includes an upstanding support portion **5038** that supports a tissue cutting blade or tissue cutting instrument **5040**. The upstanding support portion **5038** terminates in a top portion **5042** that has a pair of laterally extending retaining fins **5044** protruding therefrom. As shown in FIG. **116**, the fins **5044** are positioned to be received within corresponding slots **5072** in anvil **5070**. The fins **5044** and the foot **5034** serve to retain the anvil **5070** in a desired spaced closed position as the sled assembly **5030** is driven distally through the tissue clamped within the surgical end effector **5014**. As can also be seen in FIGS. **118** and **120**, the sled assembly **5030** further includes a reciprocatably or sequentially activatable drive assembly **5050** for driving staple pushers toward the closed anvil **5070**.

More specifically and with reference to FIGS. **116** and **117**, the elongated channel **5020** is configured to operably support a surgical staple cartridge **5080** therein. In at least one form, the surgical staple cartridge **5080** comprises a body portion **5082** that may be fabricated from, for example, Vectra, Nylon (6/6 or 6/12) and include a centrally disposed slot **5084** for accommodating the upstanding support portion **5038** of the sled assembly **5030**. See FIG. **116**. These materials could also be filled with glass, carbon, or mineral fill of 10%-40%. The surgical staple cartridge **5080** further includes a plurality of cavities **5086** for movably supporting lines or rows of staple-supporting pushers **5088** therein. The cavities **5086** may be arranged in spaced longitudinally extending lines or rows **5090**, **5092**, **5094**, **5096**. For example, the rows **5090** may be referred to herein as first outboard rows. The rows **5092** may be referred to herein as first inboard rows. The rows **5094** may be referred to as second inboard rows and the rows **5096** may be referred to as second outboard rows. The first inboard row **5090** and the first outboard row **5092** are located on a first lateral side of the longitudinal slot **5084** and the second inboard row **5094** and the second outboard row **5096** are located on a second lateral side of the longitudinal slot **5084**. The first staple pushers **5088** in the first inboard row **5092** are staggered in relationship to the first staple pushers **5088** in the first outboard row **5090**. Similarly, the second staple pushers **5088** in the second outboard row **5096** are staggered in relationship to the second pushers **5088** in the second inboard row **5094**. Each pusher **5088** operably supports a surgical staple **5098** thereon.

In various embodiments, the sequentially-activatable or reciprocatably-activatable drive assembly **5050** includes a pair of outboard drivers **5052** and a pair of inboard drivers **5054** that are each attached to a common shaft **5056** that is rotatably mounted within the base **5032** of the sled assembly **5030**. The outboard drivers **5052** are oriented to sequentially or reciprocatingly engage a corresponding plurality of outboard activation cavities **5026** provided in the channel pan **5022**. Likewise, the inboard drivers **5054** are oriented to sequentially or reciprocatingly engage a corresponding plurality of inboard activation cavities **5028** provided in the channel pan **5022**. The inboard activation cavities **5028** are arranged in a staggered relationship relative to the adjacent outboard activation cavities **5026**. See FIG. **117**. As can also be seen in FIGS. **117** and **119**, in at least one embodiment, the sled assembly **5030** further includes distal wedge segments **5060** and intermediate wedge segments **5062** located on each side of the bore **5036** to engage the pushers **5088** as the sled assembly **5030** is driven distally in the distal direction "DD". As indicated above, the sled assembly **5030** is threadedly received on a threaded portion **5132** of a drive shaft **5130** that is rotatably supported within the end effector **5012**. In various embodiments, for example, the drive shaft **5130** has a distal end **5134** that is supported in a distal bearing **5136** mounted in the surgical end effector **5012**. See FIGS. **104** and **105**.

In various embodiments, the surgical end effector **5012** is coupled to a tool mounting portion **5200** by an elongated shaft assembly **5108**. In at least one embodiment, the tool mounting portion **5200** operably supports a transmission arrangement generally designated as **5204** that is configured to receive rotary output motions from the robotic system. The elongated shaft assembly **5108** includes an outer closure tube **5110** that is rotatable and axially movable on a spine member **5120** that is rigidly coupled to a tool mounting plate **5201** of the tool mounting portion **5200**. The spine member **5120** also has a distal end **5122** that is coupled to the elongated channel portion **5020** of the surgical end effector **5012**.

In use, it may be desirable to rotate the surgical end effector **5012** about a longitudinal tool axis LT-LT defined by the elongated shaft assembly **5008**. In various embodiments, the outer closure tube **5110** has a proximal end **5112** that is rotatably supported on the tool mounting plate **5201** of the tool drive portion **5200** by a forward support cradle **5203**. The proximal end **5112** of the outer closure tube **5110** is configured to operably interface with a rotation transmission portion **5206** of the transmission arrangement **5204**. In various embodiments, the proximal end **5112** of the outer closure tube **5110** is also supported on a closure sled **5140** that is also movably supported on the tool mounting plate **5201**. A closure tube gear segment **5114** is formed on the proximal end **5112** of the outer closure tube **5110** for meshing engagement with a rotation drive assembly **5150** of the rotation transmission **5206**. As can be seen in FIG. **114**, the rotation drive assembly **5150**, in at least one embodiment, comprises a rotation drive gear **5152** that is coupled to a corresponding first one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **5201** when the tool drive portion **5200** is coupled to the tool holder **1270**. The rotation drive assembly **5150** further comprises a rotary driven gear **5154** that is rotatably supported on the tool mounting plate **5201** in meshing engagement with the closure tube gear segment **5114** and the rotation drive gear **5152**. Application of a first rotary control motion from the robotic system **1000** through the tool holder **1270** and the adapter **1240** to the corresponding driven element **1304** will thereby cause rotation of the rotation drive gear **5152**. Rotation of the rotation drive gear **5152** ultimately results in the rotation of the elongated shaft assembly **5108** (and the end effector **5012**) about the longitudinal tool axis LT-LT (represented by arrow "R" in FIG. **114**).

Closure of the anvil **5070** relative to the surgical staple cartridge **5080** is accomplished by axially moving the outer closure tube **5110** in the distal direction "DD". Such axial movement of the outer closure tube **5110** may be accomplished by a closure transmission portion closure transmission portion **5144** of the transmission arrangement **5204**. As indicated above, in various embodiments, the proximal end **5112** of the outer closure tube **5110** is supported by the closure sled **5140** which enables the proximal end **5112** to rotate relative thereto, yet travel axially with the closure sled **5140**. In particular, as can be seen in FIG. **114**, the closure sled **5140** has an upstanding tab **5141** that extends into a radial groove **5115** in the proximal end portion **5112** of the outer closure tube **5110**. In addition, as was described above, the closure sled **5140** is slidably mounted to the tool mounting plate **5201**. In various embodiments, the closure sled **5140** has an upstanding portion **5142** that has a closure rack gear **5143** formed thereon. The closure rack gear **5143** is configured for driving engagement with the closure transmission **5144**.

In various forms, the closure transmission **5144** includes a closure spur gear **5145** that is coupled to a corresponding second one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **5201**. Thus, application of a second rotary control motion from the robotic system **1000** through the tool holder **1270** and the adapter **1240** to the corresponding second driven element **1304** will cause rotation of the closure spur gear **5145** when the interface **1230** is coupled to the tool mounting portion **5200**. The closure transmission **5144** further includes a driven closure gear set **5146** that is supported in meshing engagement with the closure spur gear **5145** and the closure rack gear **5143**. Thus, application of a second rotary control motion from the robotic system **1000** through the tool holder **1270** and the adapter **1240** to the corresponding second driven element **1304** will cause rotation of the closure spur gear **5145** and ultimately drive the closure sled **5140** and the outer closure tube **5110** axially. The axial direction in which the closure tube **5110** moves ultimately depends upon the direction in which the second driven element **1304** is rotated. For example, in response to one rotary closure motion received from the robotic system **1000**, the closure sled **5140** will be driven in the distal direction "DD" and ultimately the outer closure tube **5110** will be driven in the distal direction as well. The outer closure tube **5110** has an opening **5117** in the distal end **5116** that is configured for engagement with a tab **5071** on the anvil **5070** in the manners described above. As the outer closure tube **5110** is driven distally, the proximal end **5116** of the closure tube **5110** will contact the anvil **5070** and pivot it closed. Upon application of an "opening" rotary motion from the robotic system **1000**, the closure sled **5140** and outer closure tube **5110** will be driven in the proximal direction "PD" and pivot the anvil **5070** to the open position in the manners described above.

In at least one embodiment, the drive shaft **5130** has a proximal end **5137** that has a proximal shaft gear **5138** attached thereto. The proximal shaft gear **5138** is supported in meshing engagement with a distal drive gear **5162** attached to a rotary drive bar **5160** that is rotatably supported with spine member **5120**. Rotation of the rotary drive bar **5160** and ultimately rotary drive shaft **5130** is controlled by a rotary knife transmission **5207** which comprises a portion of the transmission arrangement **5204** supported on the tool mounting plate **5210**. In various embodiments, the rotary knife transmission **5207** comprises a rotary knife drive system **5170** that is operably supported on the tool mounting plate **5201**. In various embodiments, the knife drive system **5170** includes a rotary drive gear **5172** that is coupled to a corresponding third one of the driven discs or elements **1304** on the adapter side of the tool mounting plate **5201** when the tool drive portion **5200** is coupled to the tool holder **1270**. The knife drive system **5170** further comprises a first rotary driven gear **5174** that is rotatably supported on the tool mounting plate **5201** in meshing engagement with a second rotary driven gear **5176** and the rotary drive gear **5172**. The second rotary driven gear **5176** is coupled to a proximal end portion **5164** of the rotary drive bar **5160**.

Rotation of the rotary drive gear **5172** in a first rotary direction will result in the rotation of the rotary drive bar **5160** and rotary drive shaft **5130** in a first direction. Conversely, rotation of the rotary drive gear **5172** in a second rotary direction (opposite to the first rotary direction) will cause the rotary drive bar **5160** and rotary drive shaft **5130** to rotate in a second direction. **2400**. Thus, rotation of the drive shaft **2440** results in rotation of the drive sleeve **2400**.

One method of operating the surgical tool **5000** will now be described. The tool drive **5200** is operably coupled to the interface **1240** of the robotic system **1000**. The controller **1001** of the robotic system **1000** is operated to locate the tissue to be cut and stapled between the open anvil **5070** and the surgical staple cartridge **5080**. Once the surgical end effector **5012** has been positioned by the robot system **1000** such that the target tissue is located between the anvil **5070** and the surgical staple cartridge **5080**, the controller **1001** of the robotic system **1000** may be activated to apply the second rotary output motion to the second driven element **1304** coupled to the closure spur gear **5145** to drive the closure sled **5140** and the outer closure tube **5110** axially in the distal direction to pivot the anvil **5070** closed in the manner described above. Once the robotic controller **1001** determines that the anvil **5070** has been closed by, for example, sensors in the surgical end effector **5012** and/or the tool drive portion **5200**, the robotic controller **1001** system may provide the surgeon with an indication that signifies the closure of the anvil. Such indication may be, for example, in the form of a light and/or audible sound, tactile feedback on the control members, etc. Then the surgeon may initiate the firing process. In alternative embodiments, however, the robotic controller **1001** may automatically commence the firing process.

To commence the firing process, the robotic controller applies a third rotary output motion to the third driven disc or element **1304** coupled to the rotary drive gear **5172**. Rotation of the rotary drive gear **5172** results in the rotation of the rotary drive bar **5160** and rotary drive shaft **5130** in the manner described above. Firing and formation of the surgical staples **5098** can be best understood from reference to FIGS. **115**, **117**, and **118**. As the sled assembly **5030** is driven in the distal direction "DD" through the surgical staple cartridge **5080**, the distal wedge segments **5060** first contact the staple pushers **5088** and start to move them toward the closed anvil **5070**. As the sled assembly **5030** continues to move distally, the outboard drivers **5052** will drop into the corresponding activation cavity **5026** in the channel pan **5022**. The opposite end of each outboard driver **5052** will then contact the corresponding outboard pusher **5088** that has moved up the distal and intermediate wedge segments **5060**, **5062**. Further distal movement of the sled assembly **5030** causes the outboard drivers **5052** to rotate and drive the corresponding pushers **5088** toward the anvil **5070** to cause the staples **5098** supported thereon to be formed as they are driven into the anvil **5070**. It will be understood that as the sled assembly **5030** moves distally, the knife blade **5040** cuts through the tissue that is clamped between the anvil and the staple cartridge. Because the inboard drivers **5054** and outboard drivers **5052** are attached to the same shaft **5056** and the inboard drivers

5054 are radially offset from the outboard drivers 5052 on the shaft 5056, as the outboard drivers 5052 are driving their corresponding pushers 5088 toward the anvil 5070, the inboard drivers 5054 drop into their next corresponding activation cavity 5028 to cause them to rotatably or reciprocatingly drive the corresponding inboard pushers 5088 towards the closed anvil 5070 in the same manner. Thus, the laterally corresponding outboard staples 5098 on each side of the centrally disposed slot 5084 are simultaneously formed together and the laterally corresponding inboard staples 5098 on each side of the slot 5084 are simultaneously formed together as the sled assembly 5030 is driven distally. Once the robotic controller 1001 determines that the sled assembly 5030 has reached its distal most position—either through sensors or through monitoring the amount of rotary input applied to the drive shaft 5130 and/or the rotary drive bar 5160, the controller 1001 may then apply a third rotary output motion to the drive shaft 5130 to rotate the drive shaft 5130 in an opposite direction to retract the sled assembly 5030 back to its starting position. Once the sled assembly 5030 has been retracted to the starting position (as signaled by sensors in the end effector 5012 and/or the tool drive portion 5200), the application of the second rotary motion to the drive shaft 5130 is discontinued. Thereafter, the surgeon may manually activate the anvil opening process or it may be automatically commenced by the robotic controller 1001. To open the anvil 5070, the second rotary output motion is applied to the closure spur gear 5145 to drive the closure sled 5140 and the outer closure tube 5110 axially in the proximal direction. As the closure tube 5110 moves proximally, the opening 5117 in the distal end 5116 of the closure tube 5110 contacts the tab 5071 on the anvil 5070 to pivot the anvil 5070 to the open position. A spring may also be employed to bias the anvil 5070 to the open position when the closure tube 5116 has been returned to the starting position. Again, sensors in the surgical end effector 5012 and/or the tool mounting portion 5200 may provide the robotic controller 1001 with a signal indicating that the anvil 5070 is now open. Thereafter, the surgical end effector 5012 may be withdrawn from the surgical site.

FIGS. 121-126 diagrammatically depict the sequential firing of staples in a surgical tool assembly 5000' that is substantially similar to the surgical tool assembly 5000 described above. In this embodiment, the inboard and outboard drivers 5052', 5054' have a cam-like shape with a cam surface 5053 and an actuator protrusion 5055 as shown in FIGS. 121-127. The drivers 5052', 5054' are journaled on the same shaft 5056' that is rotatably supported by the sled assembly 5030'. In this embodiment, the sled assembly 5030' has distal wedge segments 5060' for engaging the pushers 5088. FIG. 121 illustrates an initial position of two inboard or outboard drivers 5052', 5054' as the sled assembly 5030' is driven in the distal direction "DD". As can be seen in that Figure, the pusher 5088*a* has advanced up the wedge segment 5060' and has contacted the driver 5052', 5054'. Further travel of the sled assembly 5030' in the distal direction causes the driver 5052', 5054' to pivot in the "P" direction (FIG. 122) until the actuator portion 5055 contacts the end wall 5029*a* of the activation cavity 5026, 5028 as shown in FIG. 123. Continued advancement of the sled assembly 5030' in the distal direction "DD" causes the driver 5052', 5054' to rotate in the "D" direction as shown in FIG. 124. As the driver 5052', 5054' rotates, the pusher 5088*a* rides up the cam surface 5053 to the final vertical position shown in FIG. 125. When the pusher 5088*a* reaches the final vertical position shown in FIGS. 125 and 126, the staple (not shown) supported thereon has been driven into the staple forming surface of the anvil to form the staple.

FIGS. 128-133 illustrate a surgical end effector 5312 that may be employed for example, in connection with the tool mounting portion 1300 and shaft 2008 described in detail above. In various forms, the surgical end effector 5312 includes an elongated channel 5322 that is constructed as described above for supporting a surgical staple cartridge 5330 therein. The surgical staple cartridge 5330 comprises a body portion 5332 that includes a centrally disposed slot 5334 for accommodating an upstanding support portion 5386 of a sled assembly 5380. See FIGS. 128-130. The surgical staple cartridge body portion 5332 further includes a plurality of cavities 5336 for movably supporting staple-supporting pushers 5350 therein. The cavities 5336 may be arranged in spaced longitudinally extending rows 5340, 5342, 5344, 5346. The rows 5340, 5342 are located on one lateral side of the longitudinal slot 5334 and the rows 5344, 5346 are located on the other side of longitudinal slot 5334. In at least one embodiment, the pushers 5350 are configured to support two surgical staples 5352 thereon. In particular, each pusher 5350 located on one side of the elongated slot 5334 supports one staple 5352 in row 5340 and one staple 5352 in row 5342 in a staggered orientation. Likewise, each pusher 5350 located on the other side of the elongated slot 5334 supports one surgical staple 5352 in row 5344 and another surgical staple 5352 in row 5346 in a staggered orientation. Thus, every pusher 5350 supports two surgical staples 5352.

As can be further seen in FIGS. 128, 129, the surgical staple cartridge 5330 includes a plurality of rotary drivers 5360. More particularly, the rotary drivers 5360 on one side of the elongated slot 5334 are arranged in a single line 5370 and correspond to the pushers 5350 in lines 5340, 5342. In addition, the rotary drivers 5360 on the other side of the elongated slot 5334 are arranged in a single line 5372 and correspond to the pushers 5350 in lines 5344, 5346. As can be seen in FIG. 128, each rotary driver 5360 is rotatably supported within the staple cartridge body 5332. More particularly, each rotary driver 5360 is rotatably received on a corresponding driver shaft 5362. Each driver 5360 has an arcuate ramp portion 5364 formed thereon that is configured to engage an arcuate lower surface 5354 formed on each pusher 5350. See FIG. 133. In addition, each driver 5360 has a lower support portion 5366 extend therefrom to slidably support the pusher 5360 on the channel 5322. Each driver 5360 has a downwardly extending actuation rod 5368 that is configured for engagement with a sled assembly 5380.

As can be seen in FIG. 130, in at least one embodiment, the sled assembly 5380 includes a base portion 5382 that has a foot portion 5384 that is sized to be slidably received in a slot 5333 in the channel 5322. See FIG. 128. The sled assembly 5380 includes an upstanding support portion 5386 that supports a tissue cutting blade or tissue cutting instrument 5388. The upstanding support portion 5386 terminates in a top portion 5390 that has a pair of laterally extending retaining fins 5392 protruding therefrom. The fins 5392 are positioned to be received within corresponding slots (not shown) in the anvil (not shown). As with the above-described embodiments, the fins 5392 and the foot portion 5384 serve to retain the anvil (not shown) in a desired spaced closed position as the sled assembly 5380 is driven distally through the tissue clamped within the surgical end effector 5312. The upstanding support portion 5386 is configured for attachment to a knife bar 2200 (FIG. 49). The sled assembly 5380 further has a horizontally-extending actuator plate 5394 that is shaped for actuating engagement with each of the actuation rods 5368 on the pushers 5360.

Operation of the surgical end effector 5312 will now be explained with reference to FIGS. 128 and 129. As the sled

assembly **5380** is driven in the distal direction "DD" through the staple cartridge **5330**, the actuator plate **5394** sequentially contacts the actuation rods **5368** on the pushers **5360**. As the sled assembly **5380** continues to move distally, the actuator plate **5394** sequentially contacts the actuator rods **5368** of the drivers **5360** on each side of the elongated slot **5334**. Such action causes the drivers **5360** to rotate from a first unactuated position to an actuated portion wherein the pushers **5350** are driven towards the closed anvil. As the pushers **5350** are driven toward the anvil, the surgical staples **5352** thereon are driven into forming contact with the underside of the anvil. Once the robotic system **1000** determines that the sled assembly **5080** has reached its distal most position through sensors or other means, the control system of the robotic system **1000** may then retract the knife bar and sled assembly **5380** back to the starting position. Thereafter, the robotic control system may then activate the procedure for returning the anvil to the open position to release the stapled tissue.

FIGS. **134-138** depict one form of an automated reloading system embodiment of the present invention, generally designated as **5500**. In one form, the automated reloading system **5500** is configured to replace a "spent" surgical end effector component in a manipulatable surgical tool portion of a robotic surgical system with a "new" surgical end effector component. As used herein, the term "surgical end effector component" may comprise, for example, a surgical staple cartridge, a disposable loading unit or other end effector components that, when used, are spent and must be replaced with a new component. Furthermore, the term "spent" means that the end effector component has been activated and is no longer useable for its intended purpose in its present state. For example, in the context of a surgical staple cartridge or disposable loading unit, the term "spent" means that at least some of the unformed staples that were previously supported therein have been "fired" therefrom. As used herein, the term "new" surgical end effector component refers to an end effector component that is in condition for its intended use. In the context of a surgical staple cartridge or disposable loading unit, for example, the term "new" refers to such a component that has unformed staples therein and which is otherwise ready for use.

In various embodiments, the automated reloading system **5500** includes a base portion **5502** that may be strategically located within a work envelope **1109** of a robotic arm cart **1100** (FIG. **35**) of a robotic system **1000**. As used herein, the term "manipulatable surgical tool portion" collectively refers to a surgical tool of the various types disclosed herein and other forms of surgical robotically-actuated tools that are operably attached to, for example, a robotic arm cart **1100** or similar device that is configured to automatically manipulate and actuate the surgical tool. The term "work envelope" as used herein refers to the range of movement of the manipulatable surgical tool portion of the robotic system. FIG. **35***generally* depicts an area that may comprise a work envelope of the robotic arm cart **1100**. Those of ordinary skill in the art will understand that the shape and size of the work envelope depicted therein is merely illustrative. The ultimate size, shape and location of a work envelope will ultimately depend upon the construction, range of travel limitations, and location of the manipulatable surgical tool portion. Thus, the term "work envelope" as used herein is intended to cover a variety of different sizes and shapes of work envelopes and should not be limited to the specific size and shape of the sample work envelope depicted in FIG. **35**.

As can be seen in FIG. **122**, the base portion **5502** includes a new component support section or arrangement **5510** that is configured to operably support at least one new surgical end effector component in a "loading orientation". As used herein, the term "loading orientation" means that the new end effector component is supported in such away so as to permit the corresponding component support portion of the manipulatable surgical tool portion to be brought into loading engagement with (i.e., operably seated or operably attached to) the new end effector component (or the new end effector component to be brought into loading engagement with the corresponding component support portion of the manipulatable surgical tool portion) without human intervention beyond that which may be necessary to actuate the robotic system. As will be further appreciated as the present Detailed Description proceeds, in at least one embodiment, the preparation nurse will load the new component support section before the surgery with the appropriate length and color cartridges (some surgical staple cartridges may support certain sizes of staples the size of which may be indicated by the color of the cartridge body) required for completing the surgical procedure. However, no direct human interaction is necessary during the surgery to reload the robotic endocutter. In one form, the surgical end effector component comprises a staple cartridge **2034** that is configured to be operably seated within a component support portion (elongated channel) of any of the various other end effector arrangements described above. For explanation purposes, new (unused) cartridges will be designated as "**2034***a*" and spent cartridges will be designated as "**2034***b*". The Figures depict cartridges **2034***a*, **2034***b* designed for use with a surgical end effector **2012** that includes a channel **2022** and an anvil **2024**, the construction and operation of which were discussed in detail above. Cartridges **2034***a*, **2034***b* are identical to cartridges **2034** described above. In various embodiments, the cartridges **2034***a*, **2034***b* are configured to be snappingly retained (i.e., loading engagement) within the channel **2022** of a surgical end effector **2012**. As the present Detailed Description proceeds, however, those of ordinary skill in the art will appreciate that the unique and novel features of the automated cartridge reloading system **5500** may be effectively employed in connection with the automated removal and installation of other cartridge arrangements without departing from the spirit and scope of the present invention.

In the depicted embodiment, the term "loading orientation" means that the distal tip portion **2035***a* of the a new surgical staple cartridge **2034***a* is inserted into a corresponding support cavity **5512** in the new cartridge support section **5510** such that the proximal end portion **2037***a* of the new surgical staple cartridge **2034***a* is located in a convenient orientation for enabling the arm cart **1100** to manipulate the surgical end effector **2012** into a position wherein the new cartridge **2034***a* may be automatically loaded into the channel **2022** of the surgical end effector **2012**. In various embodiments, the base **5502** includes at least one sensor **5504** which communicates with the control system **1003** of the robotic controller **1001** to provide the control system **1003** with the location of the base **5502** and/or the reload length and color doe each staged or new cartridge **2034***a*.

As can also be seen in the Figures, the base **5502** further includes a collection receptacle **5520** that is configured to collect spent cartridges **2034***b* that have been removed or disengaged from the surgical end effector **2012** that is operably attached to the robotic system **1000**. In addition, in one form, the automated reloading system **5500** includes an extraction system **5530** for automatically removing the spent end effector component from the corresponding support portion of the end effector or manipulatable surgical tool portion without specific human intervention beyond that which may be necessary to activate the robotic system. In various

embodiments, the extraction system **5530** includes an extraction hook member **5532**. In one form, for example, the extraction hook member **5532** is rigidly supported on the base portion **5502**. In one embodiment, the extraction hook member has at least one hook **5534** formed thereon that is configured to hookingly engage the distal end **2035** of a spent cartridge **2034***b* when it is supported in the elongated channel **2022** of the surgical end effector **2012**. In various forms, the extraction hook member **5532** is conveniently located within a portion of the collection receptacle **5520** such that when the spent end effector component (cartridge **2034***b*) is brought into extractive engagement with the extraction hook member **5532**, the spent end effector component (cartridge **2034***b*) is dislodged from the corresponding component support portion (elongated channel **2022**), and falls into the collection receptacle **5020**. Thus, to use this embodiment, the manipulatable surgical tool portion manipulates the end effector attached thereto to bring the distal end **2035** of the spent cartridge **2034***b* therein into hooking engagement with the hook **5534** and then moves the end effector in such a way to dislodge the spent cartridge **2034***b* from the elongated channel **2022**.

In other arrangements, the extraction hook member **5532** comprises a rotatable wheel configuration that has a pair of diametrically-opposed hooks **5334** protruding therefrom. See FIGS. **134** and **137**. The extraction hook member **5532** is rotatably supported within the collection receptacle **5520** and is coupled to an extraction motor **5540** that is controlled by the controller **1001** of the robotic system. This form of the automated reloading system **5500** may be used as follows. FIG. **136** illustrates the introduction of the surgical end effector **2012** that is operably attached to the manipulatable surgical tool portion **1200**. As can be seen in that Figure, the arm cart **1100** of the robotic system **1000** locates the surgical end effector **2012** in the shown position wherein the hook end **5534** of the extraction member **5532** hookingly engages the distal end **2035** of the spent cartridge **2034***b* in the surgical end effector **2012**. The anvil **2024** of the surgical end effector **2012** is in the open position. After the distal end **2035** of the spent cartridge **2034***b* is engaged with the hook end **5532**, the extraction motor **5540** is actuated to rotate the extraction wheel **5532** to disengage the spent cartridge **2034***b* from the channel **2022**. To assist with the disengagement of the spent cartridge **2034***b* from the channel **2022** (or if the extraction member **5530** is stationary), the robotic system **1000** may move the surgical end effector **2012** in an upward direction (arrow "U" in FIG. **137**). As the spent cartridge **2034***b* is dislodged from the channel **2022**, the spent cartridge **2034***b* falls into the collection receptacle **5520**. Once the spent cartridge **2034***b* has been removed from the surgical end effector **2012**, the robotic system **1000** moves the surgical end effector **2012** to the position shown in FIG. **138**.

In various embodiments, a sensor arrangement **5533** is located adjacent to the extraction member **5532** that is in communication with the controller **1001** of the robotic system **1000**. The sensor arrangement **5533** may comprise a sensor that is configured to sense the presence of the surgical end effector **2012** and, more particularly the tip **2035***b* of the spent surgical staple cartridge **2034***b* thereof as the distal tip portion **2035***b* is brought into engagement with the extraction member **5532**. In some embodiments, the sensor arrangement **5533** may comprise, for example, a light curtain arrangement. However, other forms of proximity sensors may be employed. In such arrangement, when the surgical end effector **2012** with the spent surgical staple cartridge **2034***b* is brought into extractive engagement with the extraction member **5532**, the sensor senses the distal tip **2035***b* of the surgical staple cartridge **2034***b* (e.g., the light curtain is broken). When the extraction member **5532** spins and pops the surgical staple cartridge **2034***b* loose and it falls into the collection receptacle **5520**, the light curtain is again unbroken. Because the surgical end effector **2012** was not moved during this procedure, the robotic controller **1001** is assured that the spent surgical staple cartridge **2034***b* has been removed therefrom. Other sensor arrangements may also be successfully employed to provide the robotic controller **1001** with an indication that the spent surgical staple cartridge **2034***b* has been removed from the surgical end effector **2012**.

As can be seen in FIG. **138**, the surgical end effector **2012** is positioned to grasp a new surgical staple cartridge **2034***a* between the channel **2022** and the anvil **2024**. More specifically, as shown in FIGS. **135** and **138**, each cavity **5512** has a corresponding upstanding pressure pad **5514** associated with it. The surgical end effector **2012** is located such that the pressure pad **5514** is located between the new cartridge **2034***a* and the anvil **2024**. Once in that position, the robotic system **1000** closes the anvil **2024** onto the pressure pad **5514** which serves to push the new cartridge **2034***a* into snapping engagement with the channel **2022** of the surgical end effector **2012**. Once the new cartridge **2034***a* has been snapped into position within the elongated channel **2022**, the robotic system **1000** then withdraws the surgical end effector **2012** from the automated cartridge reloading system **5500** for use in connection with performing another surgical procedure.

FIGS. **139-143** depict another automated reloading system **5600** that may be used to remove a spent disposable loading unit **3612** from a manipulatable surgical tool arrangement **3600** (FIGS. **86-99**) that is operably attached to an arm cart **1100** or other portion of a robotic system **1000** and reload a new disposable loading unit **3612** therein. As can be seen in FIGS. **139** and **140**, one form of the automated reloading system **5600** includes a housing **5610** that has a movable support assembly in the form of a rotary carrousel top plate **5620** supported thereon which cooperates with the housing **5610** to form a hollow enclosed area **5612**. The automated reloading system **5600** is configured to be operably supported within the work envelop of the manipulatable surgical tool portion of a robotic system as was described above. In various embodiments, the rotary carrousel plate **5620** has a plurality of holes **5622** for supporting a plurality of orientation tubes **5660** therein. As can be seen in FIGS. **140** and **141**, the rotary carrousel plate **5620** is affixed to a spindle shaft **5624**. The spindle shaft **5624** is centrally disposed within the enclosed area **5612** and has a spindle gear **5626** attached thereto. The spindle gear **5626** is in meshing engagement with a carrousel drive gear **5628** that is coupled to a carrousel drive motor **5630** that is in operative communication with the robotic controller **1001** of the robotic system **1000**.

Various embodiments of the automated reloading system **5600** may also include a carrousel locking assembly, generally designated as **5640**. In various forms, the carrousel locking assembly **5640** includes a cam disc **5642** that is affixed to the spindle shaft **5624**. The spindle gear **5626** may be attached to the underside of the cam disc **5642** and the cam disc **5642** may be keyed onto the spindle shaft **5624**. In alternative arrangements, the spindle gear **5626** and the cam disc **5642** may be independently non-rotatably affixed to the spindle shaft **5624**. As can be seen in FIGS. **140** and **141**, a plurality of notches **5644** are spaced around the perimeter of the cam disc **5642**. A locking arm **5648** is pivotally mounted within the housing **5610** and is biased into engagement with the perimeter of the cam disc **5642** by a locking spring **5649**. As can be seen in FIG. **139**, the outer perimeter of the cam disc **5642** is rounded to facilitate rotation of the cam disc **5642**

relative to the locking arm **5648**. The edges of each notch **5644** are also rounded such that when the cam disc **5642** is rotated, the locking arm **5648** is cammed out of engagement with the notches **5644** by the perimeter of the cam disc **5642**.

Various forms of the automated reloading system **5600** are configured to support a portable/replaceable tray assembly **5650** that is configured to support a plurality of disposable loading units **3612** in individual orientation tubes **5660**. More specifically and with reference to FIGS. **140** and **141**, the replaceable tray assembly **5650** comprises a tray **5652** that has a centrally-disposed locator spindle **5654** protruding from the underside thereof. The locator spindle **5654** is sized to be received within a hollow end **5625** of spindle shaft **5624**. The tray **5652** has a plurality of holes **5656** therein that are configured to support an orientation tube **5660** therein. Each orientation tube **5660** is oriented within a corresponding hole **5656** in the replaceable tray assembly **5650** in a desired orientation by a locating fin **5666** on the orientation tube **5660** that is designed to be received within a corresponding locating slot **5658** in the tray assembly **5650**. In at least one embodiment, the locating fin **5666** has a substantially V-shaped cross-sectional shape that is sized to fit within a V-shaped locating slot **5658**. Such arrangement serves to orient the orientation tube **5660** in a desired starting position while enabling it to rotate within the hole **5656** when a rotary motion is applied thereto. That is, when a rotary motion is applied to the orientation tube **5660** the V-shaped locating fin **5666** will pop out of its corresponding locating slot enabling the tube **5660** to rotate relative to the tray **5652** as will be discussed in further detail below. As can also be seen in FIGS. **139-141**, the replaceable tray **5652** may be provided with one or more handle portions **5653** to facilitate transport of the tray assembly **5652** when loaded with orientation tubes **5660**.

As can be seen in FIG. **143**, each orientation tube **5660** comprises a body portion **5662** that has a flanged open end **5664**. The body portion **5662** defines a cavity **5668** that is sized to receive a portion of a disposable loading unit **3612** therein. To properly orient the disposable loading unit **3612** within the orientation tube **5660**, the cavity **5668** has a flat locating surface **5670** formed therein. As can be seen in FIG. **143**, the flat locating surface **5670** is configured to facilitate the insertion of the disposable loading unit into the cavity **5668** in a desired or predetermined non-rotatable orientation. In addition, the end **5669** of the cavity **5668** may include a foam or cushion material **5672** that is designed to cushion the distal end of the disposable loading unit **3612** within the cavity **5668**. Also, the length of the locating surface may cooperate with a sliding support member **3689** of the axial drive assembly **3680** of the disposable loading unit **3612** to further locate the disposable loading unit **3612** at a desired position within the orientation tube **5660**.

The orientation tubes **5660** may be fabricated from Nylon, polycarbonate, polyethylene, liquid crystal polymer, 6061 or 7075 aluminum, titanium, 300 or 400 series stainless steel, coated or painted steel, plated steel, etc. and, when loaded in the replaceable tray **5662** and the locator spindle **5654** is inserted into the hollow end **5625** of spindle shaft **5624**, the orientation tubes **5660** extend through corresponding holes **5662** in the carrousel top plate **5620**. Each replaceable tray **5662** is equipped with a location sensor **5663** that communicates with the control system **1003** of the controller **1001** of the robotic system **1000**. The sensor **5663** serves to identify the location of the reload system, and the number, length, color and fired status of each reload housed in the tray. In addition, an optical sensor or sensors **5665** that communicate with the robotic controller **1001** may be employed to sense the type/size/length of disposable loading units that are loaded within the tray **5662**.

Various embodiments of the automated reloading system **5600** further include a drive assembly **5680** for applying a rotary motion to the orientation tube **5660** holding the disposable loading unit **3612** to be attached to the shaft **3700** of the surgical tool **3600** (collectively the "manipulatable surgical tool portion") that is operably coupled to the robotic system. The drive assembly **5680** includes a support yoke **5682** that is attached to the locking arm **5648**. Thus, the support yoke **5682** pivots with the locking arm **5648**. The support yoke **5682** rotatably supports a tube idler wheel **5684** and a tube drive wheel **5686** that is driven by a tube motor **5688** attached thereto. Tube motor **5688** communicates with the control system **1003** and is controlled thereby. The tube idler wheel **5684** and tube drive wheel **5686** are fabricated from, for example, natural rubber, sanoprene, isoplast, etc. such that the outer surfaces thereof create sufficient amount of friction to result in the rotation of an orientation tube **5660** in contact therewith upon activation of the tube motor **5688**. The idler wheel **5684** and tube drive wheel **5686** are oriented relative to each other to create a cradle area **5687** therebetween for receiving an orientation tube **5060** in driving engagement therein.

In use, one or more of the orientation tubes **5660** loaded in the automated reloading system **5600** are left empty, while the other orientation tubes **5660** may operably support a corresponding new disposable loading unit **3612** therein. As will be discussed in further detail below, the empty orientation tubes **5660** are employed to receive a spent disposable loading unit **3612** therein.

The automated reloading system **5600** may be employed as follows after the system **5600** is located within the work envelope of the manipulatable surgical tool portion of a robotic system. If the manipulatable surgical tool portion has a spent disposable loading unit **3612** operably coupled thereto, one of the orientation tubes **5660** that are supported on the replaceable tray **5662** is left empty to receive the spent disposable loading unit **3612** therein. If, however, the manipulatable surgical tool portion does not have a disposable loading unit **3612** operably coupled thereto, each of the orientation tubes **5660** may be provided with a properly oriented new disposable loading unit **3612**.

As described hereinabove, the disposable loading unit **3612** employs a rotary "bayonet-type" coupling arrangement for operably coupling the disposable loading unit **3612** to a corresponding portion of the manipulatable surgical tool portion. That is, to attach a disposable loading unit **3612** to the corresponding portion of the manipulatable surgical tool portion (**3700**—see FIG. **92**, **93**), a rotary installation motion must be applied to the disposable loading unit **3612** and/or the corresponding portion of the manipulatable surgical tool portion when those components have been moved into loading engagement with each other. Such installation motions are collectively referred to herein as "loading motions". Likewise, to decouple a spent disposable loading unit **3612** from the corresponding portion of the manipulatable surgical tool, a rotary decoupling motion must be applied to the spent disposable loading unit **3612** and/or the corresponding portion of the manipulatable surgical tool portion while simultaneously moving the spent disposable loading unit and the corresponding portion of the manipulatable surgical tool away from each other. Such decoupling motions are collectively referred to herein as "extraction motions".

To commence the loading process, the robotic system **1000** is activated to manipulate the manipulatable surgical tool

portion and/or the automated reloading system **5600** to bring the manipulatable surgical tool portion into loading engagement with the new disposable loading unit **3612** that is supported in the orientation tube **5660** that is in driving engagement with the drive assembly **5680**. Once the robotic controller **1001** (FIG. **34**) of the robotic control system **1000** has located the manipulatable surgical tool portion in loading engagement with the new disposable loading unit **3612**, the robotic controller **1001** activates the drive assembly **5680** to apply a rotary loading motion to the orientation tube **5660** in which the new disposable loading unit **3612** is supported and/or applies another rotary loading motion to the corresponding portion of the manipulatable surgical tool portion. Upon application of such rotary loading motions(s), the robotic controller **1001** also causes the corresponding portion of the manipulatable surgical tool portion to be moved towards the new disposable loading unit **3612** into loading engagement therewith. Once the disposable loading unit **3612** is in loading engagement with the corresponding portion of the manipulatable tool portion, the loading motions are discontinued and the manipulatable surgical tool portion may be moved away from the automated reloading system **5600** carrying with it the new disposable loading unit **3612** that has been operably coupled thereto.

To decouple a spent disposable loading unit **3612** from a corresponding manipulatable surgical tool portion, the robotic controller **1001** of the robotic system manipulates the manipulatable surgical tool portion so as to insert the distal end of the spent disposable loading unit **3612** into the empty orientation tube **5660** that remains in driving engagement with the drive assembly **5680**. Thereafter, the robotic controller **1001** activates the drive assembly **5680** to apply a rotary extraction motion to the orientation tube **5660** in which the spent disposable loading unit **3612** is supported and/or applies a rotary extraction motion to the corresponding portion of the manipulatable surgical tool portion. The robotic controller **1001** also causes the manipulatable surgical tool portion to withdraw away from the spent rotary disposable loading unit **3612**. Thereafter the rotary extraction motion(s) are discontinued.

After the spent disposable loading unit **3612** has been removed from the manipulatable surgical tool portion, the robotic controller **1001** may activate the carrousel drive motor **5630** to index the carrousel top plate **5620** to bring another orientation tube **5660** that supports a new disposable loading unit **3612** therein into driving engagement with the drive assembly **5680**. Thereafter, the loading process may be repeated to attach the new disposable loading unit **3612** therein to the portion of the manipulatable surgical tool portion. The robotic controller **1001** may record the number of disposable loading units that have been used from a particular replaceable tray **5652**. Once the controller **1001** determines that all of the new disposable loading units **3612** have been used from that tray, the controller **1001** may provide the surgeon with a signal (visual and/or audible) indicating that the tray **5652** supporting all of the spent disposable loading units **3612** must be replaced with a new tray **5652** containing new disposable loading units **3612**.

FIGS. **144-149** depicts another non-limiting embodiment of a surgical tool **6000** of the present invention that is well-adapted for use with a robotic system **1000** that has a tool drive assembly **1010** (FIG. **39**) that is operatively coupled to a master controller **1001** that is operable by inputs from an operator (i.e., a surgeon). As can be seen in FIG. **144**, the surgical tool **6000** includes a surgical end effector **6012** that comprises an endocutter. In at least one form, the surgical tool **6000** generally includes an elongated shaft assembly **6008** that has a proximal closure tube **6040** and a distal closure tube **6042** that are coupled together by an articulation joint **6100**. The surgical tool **6000** is operably coupled to the manipulator by a tool mounting portion, generally designated as **6200**. The surgical tool **6000** further includes an interface **6030** which may mechanically and electrically couple the tool mounting portion **6200** to the manipulator in the various manners described in detail above.

In at least one embodiment, the surgical tool **6000** includes a surgical end effector **6012** that comprises, among other things, at least one component **6024** that is selectively movable between first and second positions relative to at least one other component **6022** in response to various control motions applied to component **6024** as will be discussed in further detail below to perform a surgical procedure. In various embodiments, component **6022** comprises an elongated channel **6022** configured to operably support a surgical staple cartridge **6034** therein and component **6024** comprises a pivotally translatable clamping member, such as an anvil **6024**. Various embodiments of the surgical end effector **6012** are configured to maintain the anvil **6024** and elongated channel **6022** at a spacing that assures effective stapling and severing of tissue clamped in the surgical end effector **6012**. Unless otherwise stated, the end effector **6012** is similar to the surgical end effector **2012** described above and includes a cutting instrument (not shown) and a sled (not shown). The anvil **6024** may include a tab **6027** at its proximal end that interacts with a component of the mechanical closure system (described further below) to facilitate the opening of the anvil **6024**. The elongated channel **6022** and the anvil **6024** may be made of an electrically conductive material (such as metal) so that they may serve as part of an antenna that communicates with sensor(s) in the end effector, as described above. The surgical staple cartridge **6034** could be made of a nonconductive material (such as plastic) and the sensor may be connected to or disposed in the surgical staple cartridge **6034**, as was also described above.

As can be seen in FIG. **144**, the surgical end effector **6012** is attached to the tool mounting portion **6200** by the elongated shaft assembly **6008** according to various embodiments. As shown in the illustrated embodiment, the elongated shaft assembly **6008** includes an articulation joint generally designated as **6100** that enables the surgical end effector **6012** to be selectively articulated about a first tool articulation axis AA**1**-AA**1** that is substantially transverse to a longitudinal tool axis LT-LT and a second tool articulation axis AA**2**-AA**2** that is substantially transverse to the longitudinal tool axis LT-LT as well as the first articulation axis AA**1**-AA**1**. See FIG. **145**. In various embodiments, the elongated shaft assembly **6008** includes a closure tube assembly **6009** that comprises a proximal closure tube **6040** and a distal closure tube **6042** that are pivotably linked by a pivot links **6044** and **6046**. The closure tube assembly **6009** is movably supported on a spine assembly generally designated as **6102**.

As can be seen in FIG. **146**, the proximal closure tube **6040** is pivotally linked to an intermediate closure tube joint **6043** by an upper pivot link **6044**U and a lower pivot link **6044**L such that the intermediate closure tube joint **6043** is pivotable relative to the proximal closure tube **6040** about a first closure axis CA**1**-CA**1** and a second closure axis CA**2**-CA**2**. In various embodiments, the first closure axis CA**1**-CA**1** is substantially parallel to the second closure axis CA**2**-CA**2** and both closure axes CA**1**-CA**1**, CA**2**-CA**2** are substantially transverse to the longitudinal tool axis LT-LT. As can be further seen in FIG. **146**, the intermediate closure tube joint **6043** is pivotally linked to the distal closure tube **6042** by a left pivot link **6046**L and a right pivot link **6046**R such that the inter-

mediate closure tube joint **6043** is pivotable relative to the distal closure tube **6042** about a third closure axis CA**3**-CA**3** and a fourth closure axis CA**4**-CA**4**. In various embodiments, the third closure axis CA**3**-CA**3** is substantially parallel to the fourth closure axis CA**4**-CA**4** and both closure axes CA**3**-CA**3**, CA**4**-CA**4** are substantially transverse to the first and second closure axes CA**1**-CA**1**, CA**2**-CA**2** as well as to longitudinal tool axis LT-LT.

The closure tube assembly **6009** is configured to axially slide on the spine assembly **6102** in response to actuation motions applied thereto. The distal closure tube **6042** includes an opening **6045** which interfaces with the tab **6027** on the anvil **6024** to facilitate opening of the anvil **6024** as the distal closure tube **6042** is moved axially in the proximal direction "PD". The closure tubes **6040**, **6042** may be made of electrically conductive material (such as metal) so that they may serve as part of the antenna, as described above. Components of the spine assembly **6102** may be made of a non-conductive material (such as plastic).

As indicated above, the surgical tool **6000** includes a tool mounting portion **6200** that is configured for operable attachment to the tool mounting assembly **1010** of the robotic system **1000** in the various manners described in detail above. As can be seen in FIG. **148**, the tool mounting portion **6200** comprises a tool mounting plate **6202** that operably supports a transmission arrangement **6204** thereon. In various embodiments, the transmission arrangement **6204** includes an articulation transmission **6142** that comprises a portion of an articulation system **6140** for articulating the surgical end effector **6012** about a first tool articulation axis TA**1**-TA**1** and a second tool articulation axis TA**2**-TA**2**. The first tool articulation axis TA**1**-TA**1** is substantially transverse to the second tool articulation axis TA**2**-TA**2** and both of the first and second tool articulation axes are substantially transverse to the longitudinal tool axis LT-LT. See FIG. **145**.

To facilitate selective articulation of the surgical end effector **6012** about the first and second tool articulation axes TA**1**-TA**1**, TA**2**-TA**2**, the spine assembly **6102** comprises a proximal spine portion **6110** that is pivotally coupled to a distal spine portion **6120** by pivot pins **6122** for selective pivotal travel about TA**1**-TA**1**. Similarly, the distal spine portion **6120** is pivotally attached to the elongated channel **6022** of the surgical end effector **6012** by pivot pins **6124** to enable the surgical end effector **6012** to selectively pivot about the second tool axis TA**2**-TA**2** relative to the distal spine portion **6120**.

In various embodiments, the articulation system **6140** further includes a plurality of articulation elements that operably interface with the surgical end effector **6012** and an articulation control arrangement **6160** that is operably supported in the tool mounting member **6200** as will described in further detail below. In at least one embodiment, the articulation elements comprise a first pair of first articulation cables **6144** and **6146**. The first articulation cables are located on a first or right side of the longitudinal tool axis. Thus, the first articulation cables are referred to herein as a right upper cable **6144** and a right lower cable **6146**. The right upper cable **6144** and the right lower cable **6146** extend through corresponding passages **6147**, **6148**, respectively along the right side of the proximal spine portion **6110**. See FIG. **149**. The articulation system **6140** further includes a second pair of second articulation cables **6150**, **6152**. The second articulation cables are located on a second or left side of the longitudinal tool axis. Thus, the second articulation cables are referred to herein as a left upper articulation cable **6150** and a left articulation cable **6152**. The left upper articulation cable **6150** and the left lower articulation cable **6152** extend through passages **6153**, **6154**, respectively in the proximal spine portion **6110**.

As can be seen in FIG. **145**, the right upper cable **6144** extends around an upper pivot joint **6123** and is attached to a left upper side of the elongated channel **6022** at a left pivot joint **6125**. The right lower cable **6146** extends around a lower pivot joint **6126** and is attached to a left lower side of the elongated channel **6022** at left pivot joint **6125**. The left upper cable **6150** extends around the upper pivot joint **6123** and is attached to a right upper side of the elongated channel **6022** at a right pivot joint **6127**. The left lower cable **6152** extends around the lower pivot joint **6126** and is attached to a right lower side of the elongated channel **6022** at right pivot joint **6127**. Thus, to pivot the surgical end effector **6012** about the first tool articulation axis TA**1**-TA**1** to the left (arrow "L"), the right upper cable **6144** and the right lower cable **6146** must be pulled in the proximal direction "PD". To articulate the surgical end effector **6012** to the right (arrow "R") about the first tool articulation axis TA**1**-TA**1**, the left upper cable **6150** and the left lower cable **6152** must be pulled in the proximal direction "PD". To articulate the surgical end effector **6012** about the second tool articulation axis TA**2**-TA**2**, in an upward direction (arrow "U"), the right upper cable **6144** and the left upper cable **6150** must be pulled in the proximal direction "PD". To articulate the surgical end effector **6012** in the downward direction (arrow "DW") about the second tool articulation axis TA**2**-TA**2**, the right lower cable **6146** and the left lower cable **6152** must be pulled in the proximal direction "PD".

The proximal ends of the articulation cables **6144**, **6146**, **6150**, **6152** are coupled to the articulation control arrangement **6160** which comprises a ball joint assembly that is a part of the articulation transmission **6142**. More specifically and with reference to FIG. **137**, the ball joint assembly **6160** includes a ball-shaped member **6162** that is formed on a proximal portion of the proximal spine **6110**. Movably supported on the ball-shaped member **6162** is an articulation control ring **6164**. As can be further seen in FIG. **149**, the proximal ends of the articulation cables **6144**, **6146**, **6150**, **6152** are coupled to the articulation control ring **6164** by corresponding ball joint arrangements **6166**. The articulation control ring **6164** is controlled by an articulation drive assembly **6170**. As can be most particularly seen in FIG. **149**, the proximal ends of the first articulation cables **6144**, **6146** are attached to the articulation control ring **6164** at corresponding spaced first points **6149**, **6151** that are located on plane **6159**. Likewise, the proximal ends of the second articulation cables **6150**, **6152** are attached to the articulation control ring **6164** at corresponding spaced second points **6153**, **6155** that are also located along plane **6159**. As the present Detailed Description proceeds, those of ordinary skill in the art will appreciate that such cable attachment configuration on the articulation control ring **6164** facilitates the desired range of articulation motions as the articulation control ring **6164** is manipulated by the articulation drive assembly **6170**.

In various forms, the articulation drive assembly **6170** comprises a horizontal articulation assembly generally designated as **6171**. In at least one form, the horizontal articulation assembly **6171** comprises a horizontal push cable **6172** that is attached to a horizontal gear arrangement **6180**. The articulation drive assembly **6170** further comprises a vertically articulation assembly generally designated as **6173**. In at least one form, the vertical articulation assembly **6173** comprises a vertical push cable **6174** that is attached to a vertical gear arrangement **6190**. As can be seen in FIGS. **148** and **149**, the horizontal push cable **6172** extends through a support plate **6167** that is attached to the proximal spine

portion **6110**. The distal end of the horizontal push cable **6174** is attached to the articulation control ring **6164** by a corresponding ball/pivot joint **6168**. The vertical push cable **6174** extends through the support plate **6167** and the distal end thereof is attached to the articulation control ring **6164** by a corresponding ball/pivot joint **6169**.

The horizontal gear arrangement **6180** includes a horizontal driven gear **6182** that is pivotally mounted on a horizontal shaft **6181** that is attached to a proximal portion of the proximal spine portion **6110**. The proximal end of the horizontal push cable **6172** is pivotally attached to the horizontal driven gear **6182** such that, as the horizontal driven gear **6172** is rotated about horizontal pivot axis HA, the horizontal push cable **6172** applies a first pivot motion to the articulation control ring **6164**. Likewise, the vertical gear arrangement **6190** includes a vertical driven gear **6192** that is pivotally supported on a vertical shaft **6191** attached to the proximal portion of the proximal spine portion **6110** for pivotal travel about a vertical pivot axis VA. The proximal end of the vertical push cable **6174** is pivotally attached to the vertical driven gear **6192** such that as the vertical driven gear **6192** is rotated about vertical pivot axis VA, the vertical push cable **6174** applies a second pivot motion to the articulation control ring **6164**.

The horizontal driven gear **6182** and the vertical driven gear **6192** are driven by an articulation gear train **6300** that operably interfaces with an articulation shifter assembly **6320**. In at least one form, the articulation shifter assembly comprises an articulation drive gear **6322** that is coupled to a corresponding one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **6202**. See FIG. **43**. Thus, application of a rotary input motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding driven element **1304** will cause rotation of the articulation drive gear **6322** when the interface **1230** is coupled to the tool holder **1270**. An articulation driven gear **6324** is attached to a splined shifter shaft **6330** that is rotatably supported on the tool mounting plate **6202**. The articulation driven gear **6324** is in meshing engagement with the articulation drive gear **6322** as shown. Thus, rotation of the articulation drive gear **6322** will result in the rotation of the shaft **6330**. In various forms, a shifter driven gear assembly **6340** is movably supported on the splined portion **6332** of the shifter shaft **6330**.

In various embodiments, the shifter driven gear assembly **6340** includes a driven shifter gear **6342** that is attached to a shifter plate **6344**. The shifter plate **6344** operably interfaces with a shifter solenoid assembly **6350**. The shifter solenoid assembly **6350** is coupled to corresponding pins **6352** by conductors **6352**. See FIG. **136**. Pins **6352** are oriented to electrically communicate with slots **1258** (FIG. **42**) on the tool side **1244** of the adaptor **1240**. Such arrangement serves to electrically couple the shifter solenoid assembly **6350** to the robotic controller **1001**. Thus, activation of the shifter solenoid **6350** will shift the shifter driven gear assembly **6340** on the splined portion **6332** of the shifter shaft **6330** as represented by arrow "S" in FIGS. **148** and **149**. Various embodiments of the articulation gear train **6300** further include a horizontal gear assembly **6360** that includes a first horizontal drive gear **6362** that is mounted on a shaft **6361** that is rotatably attached to the tool mounting plate **6202**. The first horizontal drive gear **6362** is supported in meshing engagement with a second horizontal drive gear **6364**. As can be seen in FIG. **149**, the horizontal driven gear **6182** is in meshing engagement with the distal face portion **6365** of the second horizontal driven gear **6364**.

Various embodiments of the articulation gear train **6300** further include a vertical gear assembly **6370** that includes a first vertical drive gear **6372** that is mounted on a shaft **6371** that is rotatably supported on the tool mounting plate **6202**. The first vertical drive gear **6372** is supported in meshing engagement with a second vertical drive gear **6374** that is concentrically supported with the second horizontal drive gear **6364**. The second vertical drive gear **6374** is rotatably supported on the proximal spine portion **6110** for travel thereabout. The second horizontal drive gear **6364** is rotatably supported on a portion of said second vertical drive gear **6374** for independent rotatable travel thereon. As can be seen in FIG. **149**, the vertical driven gear **6192** is in meshing engagement with the distal face portion **6375** of the second vertical driven gear **6374**.

In various forms, the first horizontal drive gear **6362** has a first diameter and the first vertical drive gear **6372** has a second diameter. As can be seen in FIGS. **148** and **149**, the shaft **6361** is not on a common axis with shaft **6371**. That is, the first horizontal driven gear **6362** and the first vertical driven gear **6372** do not rotate about a common axis. Thus, when the shifter gear **6342** is positioned in a center "locking" position such that the shifter gear **6342** is in meshing engagement with both the first horizontal driven gear **6362** and the first vertical drive gear **6372**, the components of the articulation system **6140** are locked in position. Thus, the shiftable shifter gear **6342** and the arrangement of first horizontal and vertical drive gears **6362**, **6372** as well as the articulation shifter assembly **6320** collectively may be referred to as an articulation locking system, generally designated as **6380**.

In use, the robotic controller **1001** of the robotic system **1000** may control the articulation system **6140** as follows. To articulate the end effector **6012** to the left about the first tool articulation axis TA**1**-TA**1**, the robotic controller **1001** activates the shifter solenoid assembly **6350** to bring the shifter gear **6342** into meshing engagement with the first horizontal drive gear **6362**. Thereafter, the controller **1001** causes a first rotary output motion to be applied to the articulation drive gear **6322** to drive the shifter gear in a first direction to ultimately drive the horizontal driven gear **6182** in another first direction. The horizontal driven gear **6182** is driven to pivot the articulation ring **6164** on the ball-shaped portion **6162** to thereby pull right upper cable **6144** and the right lower cable **6146** in the proximal direction "PD". To articulate the end effector **6012** to the right about the first tool articulation axis TA**1**-TA**1**, the robotic controller **1001** activates the shifter solenoid assembly **6350** to bring the shifter gear **6342** into meshing engagement with the first horizontal drive gear **6362**. Thereafter, the controller **1001** causes the first rotary output motion in an opposite direction to be applied to the articulation drive gear **6322** to drive the shifter gear **6342** in a second direction to ultimately drive the horizontal driven gear **6182** in another second direction. Such actions result in the articulation control ring **6164** moving in such a manner as to pull the left upper cable **6150** and the left lower cable **6152** in the proximal direction "PD". In various embodiments the gear ratios and frictional forces generated between the gears of the vertical gear assembly **6370** serve to prevent rotation of the vertical driven gear **6192** as the horizontal gear assembly **6360** is actuated.

To articulate the end effector **6012** in the upper direction about the second tool articulation axis TA**2**-TA**2**, the robotic controller **1001** activates the shifter solenoid assembly **6350** to bring the shifter gear **6342** into meshing engagement with the first vertical drive gear **6372**. Thereafter, the controller **1001** causes the first rotary output motion to be applied to the articulation drive gear **6322** to drive the shifter gear **6342** in a

first direction to ultimately drive the vertical driven gear **6192** in another first direction. The vertical driven gear **6192** is driven to pivot the articulation ring **6164** on the ball-shaped portion **6162** of the proximal spine portion **6110** to thereby pull right upper cable **6144** and the left upper cable **6150** in the proximal direction "PD". To articulate the end effector **6012** in the downward direction about the second tool articulation axis TA2-TA2, the robotic controller **1001** activates the shifter solenoid assembly **6350** to bring the shifter gear **6342** into meshing engagement with the first vertical drive gear **6372**. Thereafter, the controller **1001** causes the first rotary output motion to be applied in an opposite direction to the articulation drive gear **6322** to drive the shifter gear **6342** in a second direction to ultimately drive the vertical driven gear **6192** in another second direction. Such actions thereby cause the articulation control ring **6164** to pull the right lower cable **6146** and the left lower cable **6152** in the proximal direction "PD". In various embodiments, the gear ratios and frictional forces generated between the gears of the horizontal gear assembly **6360** serve to prevent rotation of the horizontal driven gear **6182** as the vertical gear assembly **6370** is actuated.

In various embodiments, a variety of sensors may communicate with the robotic controller **1001** to determine the articulated position of the end effector **6012**. Such sensors may interface with, for example, the articulation joint **6100** or be located within the tool mounting portion **6200**. For example, sensors may be employed to detect the position of the articulation control ring **6164** on the ball-shaped portion **6162** of the proximal spine portion **6110**. Such feedback from the sensors to the controller **1001** permits the controller **1001** to adjust the amount of rotation and the direction of the rotary output to the articulation drive gear **6322**. Further, as indicated above, when the shifter drive gear **6342** is centrally positioned in meshing engagement with the first horizontal drive gear **6362** and the first vertical drive gear **6372**, the end effector **6012** is locked in the articulated position. Thus, after the desired amount of articulation has been attained, the controller **1001** may activate the shifter solenoid assembly **6350** to bring the shifter gear **6342** into meshing engagement with the first horizontal drive gear **6362** and the first vertical drive gear **6372**. In alternative embodiments, the shifter solenoid assembly **6350** may be spring activated to the central locked position.

In use, it may be desirable to rotate the surgical end effector **6012** about the longitudinal tool axis LT-LT. In at least one embodiment, the transmission arrangement **6204** on the tool mounting portion includes a rotational transmission assembly **6400** that is configured to receive a corresponding rotary output motion from the tool drive assembly **1010** of the robotic system **1000** and convert that rotary output motion to a rotary control motion for rotating the elongated shaft assembly **6008** (and surgical end effector **6012**) about the longitudinal tool axis LT-LT. In various embodiments, for example, a proximal end portion **6041** of the proximal closure tube **6040** is rotatably supported on the tool mounting plate **6202** of the tool mounting portion **6200** by a forward support cradle **6205** and a closure sled **6510** that is also movably supported on the tool mounting plate **6202**. In at least one form, the rotational transmission assembly **6400** includes a tube gear segment **6402** that is formed on (or attached to) the proximal end **6041** of the proximal closure tube **6040** for operable engagement by a rotational gear assembly **6410** that is operably supported on the tool mounting plate **6202**. As can be seen in FIG. **148**, the rotational gear assembly **6410**, in at least one embodiment, comprises a rotation drive gear **6412** that is coupled to a corresponding second one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **6202** when the tool mounting portion **6200** is coupled to the tool drive assembly **1010**. See FIG. **43**. The rotational gear assembly **6410** further comprises a first rotary driven gear **6414** that is rotatably supported on the tool mounting plate **6202** in meshing engagement with the rotation drive gear **6412**. The first rotary driven gear **6414** is attached to a drive shaft **6416** that is rotatably supported on the tool mounting plate **6202**. A second rotary driven gear **6418** is attached to the drive shaft **6416** and is in meshing engagement with tube gear segment **6402** on the proximal closure tube **6040**. Application of a second rotary output motion from the tool drive assembly **1010** of the robotic system **1000** to the corresponding driven element **1304** will thereby cause rotation of the rotation drive gear **6412**. Rotation of the rotation drive gear **6412** ultimately results in the rotation of the elongated shaft assembly **6008** (and the surgical end effector **6012**) about the longitudinal tool axis LT-LT. It will be appreciated that the application of a rotary output motion from the tool drive assembly **1010** in one direction will result in the rotation of the elongated shaft assembly **6008** and surgical end effector **6012** about the longitudinal tool axis LT-LT in a first direction and an application of the rotary output motion in an opposite direction will result in the rotation of the elongated shaft assembly **6008** and surgical end effector **6012** in a second direction that is opposite to the first direction.

In at least one embodiment, the closure of the anvil **2024** relative to the staple cartridge **2034** is accomplished by axially moving a closure portion of the elongated shaft assembly **2008** in the distal direction "DD" on the spine assembly **2049**. As indicated above, in various embodiments, the proximal end portion **6041** of the proximal closure tube **6040** is supported by the closure sled **6510** which comprises a portion of a closure transmission, generally depicted as **6512**. As can be seen in FIG. **148**, the proximal end portion **6041** of the proximal closure tube portion **6040** has a collar **6048** formed thereon. The closure sled **6510** is coupled to the collar **6048** by a yoke **6514** that engages an annular groove **6049** in the collar **6048**. Such arrangement serves to enable the collar **6048** to rotate about the longitudinal tool axis LT-LT while still being coupled to the closure transmission **6512**. In various embodiments, the closure sled **6510** has an upstanding portion **6516** that has a closure rack gear **6518** formed thereon. The closure rack gear **6518** is configured for driving engagement with a closure gear assembly **6520**. See FIG. **148**.

In various forms, the closure gear assembly **6520** includes a closure spur gear **6522** that is coupled to a corresponding second one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **6202**. See FIG. **43**. Thus, application of a third rotary output motion from the tool drive assembly **1010** of the robotic system **1000** to the corresponding second driven element **1304** will cause rotation of the closure spur gear **6522** when the tool mounting portion **6202** is coupled to the tool drive assembly **1010**. The closure gear assembly **6520** further includes a closure reduction gear set **6524** that is supported in meshing engagement with the closure spur gear **6522** and the closure rack gear **2106**. Thus, application of a third rotary output motion from the tool drive assembly **1010** of the robotic system **1000** to the corresponding second driven element **1304** will cause rotation of the closure spur gear **6522** and the closure transmission **6512** and ultimately drive the closure sled **6510** and the proximal closure tube **6040** axially on the proximal spine portion **6110**. The axial direction in which the proximal closure tube **6040** moves ultimately depends upon the direction in which the third driven element **1304** is rotated. For example, in response

to one rotary output motion received from the tool drive assembly **1010** of the robotic system **1000**, the closure sled **6510** will be driven in the distal direction "DD" and ultimately drive the proximal closure tube **6040** in the distal direction "DD". As the proximal closure tube **6040** is driven distally, the distal closure tube **6042** is also driven distally by virtue of it connection with the proximal closure tube **6040**. As the distal closure tube **6042** is driven distally, the end of the closure tube **6042** will engage a portion of the anvil **6024** and cause the anvil **6024** to pivot to a closed position. Upon application of an "opening" out put motion from the tool drive assembly **1010** of the robotic system **1000**, the closure sled **6510** and the proximal closure tube **6040** will be driven in the proximal direction "PD" on the proximal spine portion **6110**. As the proximal closure tube **6040** is driven in the proximal direction "PD", the distal closure tube **6042** will also be driven in the proximal direction "PD". As the distal closure tube **6042** is driven in the proximal direction "PD", the opening **6045** therein interacts with the tab **6027** on the anvil **6024** to facilitate the opening thereof. In various embodiments, a spring (not shown) may be employed to bias the anvil **6024** to the open position when the distal closure tube **6042** has been moved to its starting position. In various embodiments, the various gears of the closure gear assembly **6520** are sized to generate the necessary closure forces needed to satisfactorily close the anvil **6024** onto the tissue to be cut and stapled by the surgical end effector **6012**. For example, the gears of the closure transmission **6520** may be sized to generate approximately 70-120 pounds of closure forces.

In various embodiments, the cutting instrument is driven through the surgical end effector **6012** by a knife bar **6530**. See FIG. **148**. In at least one form, the knife bar **6530** is fabricated with a joint arrangement (not shown) and/or is fabricated from material that can accommodate the articulation of the surgical end effector **6102** about the first and second tool articulation axes while remaining sufficiently rigid so as to push the cutting instrument through tissue clamped in the surgical end effector **6012**. The knife bar **6530** extends through a hollow passage **6532** in the proximal spine portion **6110**.

In various embodiments, a proximal end **6534** of the knife bar **6530** is rotatably affixed to a knife rack gear **6540** such that the knife bar **6530** is free to rotate relative to the knife rack gear **6540**. The distal end of the knife bar **6530** is attached to the cutting instrument in the various manners described above. As can be seen in FIG. **148**, the knife rack gear **6540** is slidably supported within a rack housing **6542** that is attached to the tool mounting plate **6202** such that the knife rack gear **6540** is retained in meshing engagement with a knife drive transmission portion **6550** of the transmission arrangement **6204**. In various embodiments, the knife drive transmission portion **6550** comprises a knife gear assembly **6560**. More specifically and with reference to FIG. **148**, in at least one embodiment, the knife gear assembly **6560** includes a knife spur gear **6562** that is coupled to a corresponding fourth one of the driven discs or elements **1304** on the adapter side **1307** of the tool mounting plate **6202**. See FIG. **43**. Thus, application of another rotary output motion from the robotic system **1000** through the tool drive assembly **1010** to the corresponding fourth driven element **1304** will cause rotation of the knife spur gear **6562**. The knife gear assembly **6560** further includes a knife gear reduction set **6564** that includes a first knife driven gear **6566** and a second knife drive gear **6568**. The knife gear reduction set **6564** is rotatably mounted to the tool mounting plate **6202** such that the firs knife driven gear **6566** is in meshing engagement with the knife spur gear **6562**. Likewise, the second knife drive gear **6568** is in meshing engagement with a third knife drive gear assembly **6570**. As shown in FIG. **148**, the second knife driven gear **6568** is in meshing engagement with a fourth knife driven gear **6572** of the third knife drive gear assembly **6570**. The fourth knife driven gear **6572** is in meshing engagement with a fifth knife driven gear assembly **6574** that is in meshing engagement with the knife rack gear **6540**. In various embodiments, the gears of the knife gear assembly **6560** are sized to generate the forces needed to drive the cutting instrument through the tissue clamped in the surgical end effector **6012** and actuate the staples therein. For example, the gears of the knife gear assembly **6560** may be sized to generate approximately 40 to 100 pounds of driving force. It will be appreciated that the application of a rotary output motion from the tool drive assembly **1010** in one direction will result in the axial movement of the cutting instrument in a distal direction and application of the rotary output motion in an opposite direction will result in the axial travel of the cutting instrument in a proximal direction.

As can be appreciated from the foregoing description, the surgical tool **6000** represents a vast improvement over prior robotic tool arrangements. The unique and novel transmission arrangement employed by the surgical tool **6000** enables the tool to be operably coupled to a tool holder portion **1010** of a robotic system that only has four rotary output bodies, yet obtain the rotary output motions therefrom to: (i) articulate the end effector about two different articulation axes that are substantially transverse to each other as well as the longitudinal tool axis; (ii) rotate the end effector **6012** about the longitudinal tool axis; (iii) close the anvil **6024** relative to the surgical staple cartridge **6034** to varying degrees to enable the end effector **6012** to be used to manipulate tissue and then clamp it into position for cutting and stapling; and (iv) firing the cutting instrument to cut through the tissue clamped within the end effector **6012**. The unique and novel shifter arrangements of various embodiments of the present invention described above enable two different articulation actions to be powered from a single rotatable body portion of the robotic system.

The various embodiments of the present invention have been described above in connection with cutting-type surgical instruments. It should be noted, however, that in other embodiments, the inventive surgical instrument disclosed herein need not be a cutting-type surgical instrument, but rather could be used in any type of surgical instrument including remote sensor transponders. For example, it could be a non-cutting endoscopic instrument, a grasper, a stapler, a clip applier, an access device, a drug/gene therapy delivery device, an energy device using ultrasound, RF, laser, etc. In addition, the present invention may be in laparoscopic instruments, for example. The present invention also has application in conventional endoscopic and open surgical instrumentation as well as robotic-assisted surgery.

FIG. **150** depicts use of various aspects of certain embodiments of the present invention in connection with a surgical tool **7000** that has an ultrasonically powered end effector **7012**. The end effector **7012** is operably attached to a tool mounting portion **7100** by an elongated shaft assembly **7008**. The tool mounting portion **7100** may be substantially similar to the various tool mounting portions described hereinabove. In one embodiment, the end effector **7012** includes an ultrasonically powered jaw portion **7014** that is powered by alternating current or direct current in a known manner. Such ultrasonically-powered devices are disclosed, for example, in U.S. Pat. No. 6,783,524, entitled "Robotic Surgical Tool With Ultrasound Cauterizing and Cutting Instrument", the entire disclosure of which is herein incorporated by reference. In the

illustrated embodiment, a separate power cord **7020** is shown. It will be understood, however, that the power may be supplied thereto from the robotic controller **1001** through the tool mounting portion **7100**. The surgical end effector **7012** further includes a movable jaw **7016** that may be used to clamp tissue onto the ultrasonic jaw portion **7014**. The movable jaw portion **7016** may be selectively actuated by the robotic controller **1001** through the tool mounting portion **7100** in anyone of the various manners herein described.

FIG. **151** illustrates use of various aspects of certain embodiments of the present invention in connection with a surgical tool **8000** that has an end effector **8012** that comprises a linear stapling device. The end effector **8012** is operably attached to a tool mounting portion **8100** by an elongated shaft assembly **3700** of the type and construction describe above. However, the end effector **8012** may be attached to the tool mounting portion **8100** by a variety of other elongated shaft assemblies described herein. In one embodiment, the tool mounting portion **8100** may be substantially similar to tool mounting portion **3750**. However, various other tool mounting portions and their respective transmission arrangements describe in detail herein may also be employed. Such linear stapling head portions are also disclosed, for example, in U.S. Pat. No. 7,673,781, entitled "Surgical Stapling Device With Staple Driver That Supports Multiple Wire Diameter Staples", the entire disclosure of which is herein incorporated by reference.

Various sensor embodiments described in U.S. Patent Publication No. 2011/0062212 A1 to Shelton, IV et al., the disclosure of which is herein incorporated by reference in its entirety, may be employed with many of the surgical tool embodiments disclosed herein. As was indicated above, the master controller **1001** generally includes master controllers (generally represented by **1003**) which are grasped by the surgeon and manipulated in space while the surgeon views the procedure via a stereo display **1002**. See FIG. **34**. The master controllers **1001** are manual input devices which preferably move with multiple degrees of freedom, and which often further have an actuatable handle for actuating the surgical tools. Some of the surgical tool embodiments disclosed herein employ a motor or motors in their tool drive portion to supply various control motions to the tool's end effector. Such embodiments may also obtain additional control motion(s) from the motor arrangement employed in the robotic system components. Other embodiments disclosed herein obtain all of the control motions from motor arrangements within the robotic system.

Such motor powered arrangements may employ various sensor arrangements that are disclosed in the published U.S. patent application cited above to provide the surgeon with a variety of forms of feedback without departing from the spirit and scope of the present invention. For example, those master controller arrangements **1003** that employ a manually actuatable firing trigger can employ run motor sensor(s) to provide the surgeon with feedback relating to the amount of force applied to or being experienced by the cutting member. The run motor sensor(s) may be configured for communication with the firing trigger portion to detect when the firing trigger portion has been actuated to commence the cutting/stapling operation by the end effector. The run motor sensor may be a proportional sensor such as, for example, a rheostat or variable resistor. When the firing trigger is drawn in, the sensor detects the movement, and sends an electrical signal indicative of the voltage (or power) to be supplied to the corresponding motor. When the sensor is a variable resistor or the like, the rotation of the motor may be generally proportional to the amount of movement of the firing trigger. That is, if the operator only draws or closes the firing trigger in a small amount, the rotation of the motor is relatively low. When the firing trigger is fully drawn in (or in the fully closed position), the rotation of the motor is at its maximum. In other words, the harder the surgeon pulls on the firing trigger, the more voltage is applied to the motor causing greater rates of rotation. Other arrangements may provide the surgeon with a feed back meter **1005** that may be viewed through the display **1002** and provide the surgeon with a visual indication of the amount of force being applied to the cutting instrument or dynamic clamping member. Other sensor arrangements may be employed to provide the master controller **1001** with an indication as to whether a staple cartridge has been loaded into the end effector, whether the anvil has been moved to a closed position prior to firing, etc.

In alternative embodiments, a motor-controlled interface may be employed in connection with the controller **1001** that limit the maximum trigger pull based on the amount of loading (e.g., clamping force, cutting force, etc.) experienced by the surgical end effector. For example, the harder it is to drive the cutting instrument through the tissue clamped within the end effector, the harder it would be to pull/actuate the activation trigger. In still other embodiments, the trigger on the controller **1001** is arranged such that the trigger pull location is proportionate to the end effector-location/condition. For example, the trigger is only fully depressed when the end effector is fully fired.

The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, the device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps of disassembly of the device, followed by cleaning or replacement of particular pieces, and subsequent reassembly. In particular, the device can be disassembled, and any number of the particular pieces or parts of the device can be selectively replaced or removed in any combination. Upon cleaning and/or replacement of particular parts, the device can be reassembled for subsequent use either at a reconditioning facility, or by a surgical team immediately prior to a surgical procedure. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

Although the present invention has been described herein in connection with certain disclosed embodiments, many modifications and variations to those embodiments may be implemented. For example, different types of end effectors may be employed. Also, where materials are disclosed for certain components, other materials may be used. The foregoing description and following claims are intended to cover all such modification and variations.

Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated materials does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

What is claimed is:

1. A tool mounting device for coupling a surgical end effector configured to selectively perform at least two actions in response to control motions applied thereto to a tool drive assembly of a robotic system that is operatively coupled to a control unit of the robotic system, said tool mounting device comprising:

a tool mounting portion configured for operable attachment to the tool drive assembly of the robotic system;

an elongated shaft assembly having a proximal end portion operably supported on said tool mounting portion and a distal end portion operably interfacing with said surgical end effector to apply said control motions thereto; and

a transmission arrangement operably supported on said tool mounting portion such that when said tool mounting portion is attached to the tool drive assembly, said transmission arrangement is configured to operably interface with a rotatable driven element of the tool drive assembly to receive a rotary output motion therefrom, said transmission arrangement communicating with the control unit of the robotic system and being responsive to actuation motions therefrom to move between first and second positions such that when said transmission arrangement is in said first position, an application of said rotary output motion thereto by said rotatable driven element of the tool drive assembly causes a first one of said control motions to be applied to a portion of said surgical end effector through said elongated shaft assembly and when said transmission arrangement is in said second position, said application of said rotary output motion thereto by said rotatable driven element of the tool drive assembly causes a second one of said control motions to be applied to another portion of said surgical end effector through said elongated shaft assembly.

2. The tool mounting device of claim 1 wherein the tool drive assembly of the robotic system comprises at least one rotatable drive element operably supported on a tool holder and wherein said tool mounting device further comprises an adapter portion operably attachable to the tool holder and said tool mounting portion for establishing an interface therebetween, said adapter portion operably supporting a rotatable adapter body configured to operably engage a corresponding one of the rotatable drive elements when said adapter portion is coupled to the tool holder and wherein said rotatable driven element is configured to operably engage said rotatable adapter body when said tool mounting portion is coupled to said adapter portion.

3. The tool mounting device of claim 2 wherein the corresponding rotatable drive element has a pair of spaced drive pins that are configured to be received in corresponding first drive holes in said rotatable adapter body when said adapter portion is coupled to the tool holder.

4. The tool mounting device of claim 3 wherein said rotatable driven element has a pair of spaced driven pins protruding therefrom that are configured to be received in corresponding second drive holes in said rotatable adapter body when said tool mounting portion is coupled to said adapter portion.

5. The tool mounting device of claim 4 further comprising a releasable latch arrangement on said adapter portion for releasably coupling said adapter portion to the tool holder.

6. The tool mounting device of claim 1 wherein said transmission arrangement comprises:

a first control assembly operably interfacing with said elongated shaft assembly to apply said first control motion thereto;

a second control assembly operably interfacing with said elongated shaft assembly to apply said second control motion thereto; and

a transmission shifter assembly communicating with the control unit of the robotic system and configured to receive said rotary output motion from said rotatable driven element of the tool drive assembly, said transmission shifter assembly configured to shift between said first and second positions in response to control inputs from the control unit of the robotic system such that when said transmission shifter assembly is in said first position, said rotary output motion is applied to said first control assembly and when said transmission shifter assembly is in said second position, said rotary output motion is applied to said second control assembly.

7. The tool mounting device of claim 6 wherein said transmission shifter assembly comprises:

a shifter drive gear configured to receive said rotary output motion from said rotatable driven element of the tool drive assembly when said tool mounting portion is coupled thereto;

a shifter shaft in meshing engagement with said shifter drive gear; and

a shifter driven gear mounted on said shifter shaft such that rotation of said shifter shaft rotates said shifter driven gear and wherein said shifter driven gear is selectively axially movable on said shifter shaft between said first position wherein said shifter driven gear is in driving engagement with said first control assembly and said second position wherein said shifter driven gear is in driving engagement with said second control assembly in response to said control inputs.

8. The tool mounting device of claim 7 wherein said shifter driven gear is selectively axially movable on said shifter shaft to an intermediate locked position wherein said shifter driven gear is in locking engagement with said first control assembly and said second control assembly to thereby prevent an application of said control motions to said surgical end effector.

9. The tool mounting device of claim 8 wherein said shifter driven gear is axially movable on said shifter shaft by a shifter solenoid communicating with the control unit of the robotic system and receiving said control inputs from the control unit of the robotic system.

10. The tool mounting device of claim 1 wherein said elongated shaft assembly has an articulation joint therein such that upon application of said first control motion to said surgical end effector, said surgical end effector articulates about a first tool articulation axis that is substantially transverse to a longitudinal tool axis defined by said elongated shaft assembly.

11. The tool mounting device of claim 10 wherein said articulation joint is configured to enable said surgical end effector to pivot about a second tool articulation axis upon application of another said control motion to said surgical end effector.

12. The tool mounting device of claim 1 wherein said surgical end effector further comprises a surgical staple cartridge and wherein said portion of said surgical end effector comprises an anvil selectively movable relative to said surgical staple cartridge between an open position and a closed position in response to a closure control motion applied thereto by said transmission arrangement.

13. The tool mounting device of claim 12 wherein said another portion of said surgical end effector comprises a cutting instrument that is axially movable within said surgical

staple cartridge between a starting position and an ending position in response to a firing motion applied thereto by said transmission arrangement.

14. A tool mounting device for coupling a surgical end effector capable of performing at least two actions in response to control motions applied thereto to a rotatable drive element that is operably supported on a tool holder of a robotic system that is operatively coupled to a control unit, said tool mounting device comprising:

a tool mounting portion operably supporting a rotatable driven element thereon, said rotatable driven element having a pair of spaced driven pins protruding therefrom;

an adapter portion operably attachable to the tool holder and said tool mounting portion for establishing an interface therebetween, said adapter portion operably supporting a rotatable adapter body having a first pair of drive holes therein configured to receive corresponding drive pins protruding from the rotatable drive element when said adapter portion is coupled to the tool holder, said rotatable adapter body further having a pair of driven holes therein for receiving said driven pins therein when said adapter portion is coupled to said tool mounting portion;

an elongated shaft assembly having a proximal end portion operably supported on said tool mounting portion and a distal end portion operably interfacing with said surgical end effector to apply said control motions thereto; and

a transmission arrangement operably supported on said tool mounting portion and comprising:

a first control assembly operably interfacing with said elongated shaft assembly to apply a first said control motion thereto;

a second control assembly operably interfacing with said elongated shaft assembly to apply a second said control motion thereto; and

a transmission shifter assembly comprising:

a shifter drive gear operably coupled to said rotatable driven element for receiving a rotary output motion therefrom;

a shifter shaft in meshing engagement with said shifter drive gear;

a shifter driven gear mounted on said shifter shaft such that rotation of said shifter shaft rotates said shifter driven gear and wherein said shifter driven gear is selectively axially movable on said shifter shaft between a first position wherein said shifter driven gear is in driving engagement with said first control assembly and a second position wherein said shifter driven gear is in driving engagement with said second control assembly; and

a shifter solenoid operably interfacing with said shifter driven gear to selectively move said shifter driven gear between said first and second positions in response to corresponding control inputs from the control unit of the robotic system.

15. The tool mounting device of claim **14** wherein said shifter driven gear is selectively axially movable on said shifter shaft to an intermediate locked position wherein said shifter driven gear is in locking engagement with said first control assembly and said second control assembly to thereby prevent an application of said control motions to said surgical end effector.

16. The tool mounting device of claim **14** wherein said elongated shaft assembly has an articulation joint therein such that upon application of said first control motion to said surgical end effector, said surgical end effector articulates about a first tool articulation axis that is substantially transverse to a longitudinal tool axis defined by said elongated shaft assembly.

17. The tool mounting device of claim **16** wherein said articulation joint is configured to enable said surgical end effector to pivot about a second tool articulation axis upon application of another said control motion to said surgical end effector.

18. The tool mounting device of claim **17** wherein said surgical end effector comprises:

a surgical staple cartridge; and

an anvil selectively movable relative to said surgical staple cartridge between an open position and a closed position in response to a closure control motion applied thereto by said transmission arrangement.

19. The tool mounting device of claim **18** wherein said surgical end effector further comprises a cutting instrument that is axially movable within said surgical staple cartridge between a starting position and an ending position in response to a firing motion applied thereto by said transmission arrangement.

20. A tool mounting device for coupling a surgical end effector configured to selectively perform at least two actions in response to control motions applied thereto to a tool drive assembly of a robotic system that is operatively coupled to a control unit of the robotic system, said tool mounting device comprising:

a tool mounting portion configured for operable attachment to the tool drive assembly of the robotic system;

an elongated shaft assembly having a proximal end portion operably supported on said tool mounting portion and a distal end portion operably interfacing with said surgical end effector to apply said control motions thereto; and

a transmission arrangement comprising:

a first control assembly operably interfacing with said elongated shaft assembly to apply a first said control motion thereto;

a second control assembly operably interfacing with said elongated shaft assembly to apply a second said control motion thereto; and

a transmission shifter assembly communicating with the control unit of the robotic system and configured to receive a rotary output motion from the tool drive assembly, said transmission shifter assembly configured to shift between first and second positions in response to control inputs from the control unit of the robotic system such that when said transmission shifter assembly is in said first position, said rotary output motion is applied to said first control assembly and when said transmission shifter assembly is in said second position, said rotary output motion is applied to said second control assembly and wherein said transmission shifter assembly further comprises:

a shifter drive gear configured to receive said rotary output motion from the tool drive assembly when said tool mounting portion is coupled thereto;

a shifter shaft in meshing engagement with said shifter drive gear; and

a shifter driven gear mounted on said shifter shaft such that rotation of said shifter shaft rotates said shifter driven gear and wherein said shifter driven gear is selectively axially movable on said shifter shaft between said first position wherein said shifter driven gear is in driving engagement with said first control assembly and said second position wherein said shifter driven gear is in driving engagement with said

second control assembly in response to said control inputs.

21. The tool mounting device of claim **20** wherein said shifter driven gear is selectively axially movable on said shifter shaft to an intermediate locked position wherein said shifter driven gear is in locking engagement with said first control assembly and said second control assembly to thereby prevent an application of said control motions to said surgical end effector.

22. The tool mounting device of claim **21** wherein said shifter driven gear is axially movable on said shifter shaft by a shifter solenoid communicating with the control unit of the robotic system and receiving said control inputs from the control unit of the robotic system.

23. The tool mounting device of claim **20** wherein said elongated shaft assembly has an articulation joint therein such that upon application of said first control motion to said surgical end effector, said surgical end effector articulates about a first tool articulation axis that is substantially transverse to a longitudinal tool axis defined by said elongated shaft assembly.

24. The tool mounting device of claim **23** wherein said articulation joint is configured to enable said surgical end effector to pivot about a second tool articulation axis upon application of another said control motion to said surgical end effector.

25. The tool mounting device of claim **20** wherein said surgical end effector comprises:

a surgical staple cartridge; and

an anvil selectively movable relative to said surgical staple cartridge between an open position and a closed position in response to a closure control motion applied thereto by said transmission arrangement.

26. The tool mounting device of claim **25** wherein said surgical end effector further comprises a cutting instrument that is axially movable within said surgical staple cartridge between a starting position and an ending position in response to a firing motion applied thereto by said transmission arrangement.

* * * * *