



US009788853B2

(12) **United States Patent**  
**Robinson et al.**

(10) **Patent No.:** **US 9,788,853 B2**  
(45) **Date of Patent:** **Oct. 17, 2017**

(54) **ATHERECTOMY DEVICES AND METHODS**

(71) Applicant: **Cardio Flow Inc.**, Long Lake, MN (US)  
(72) Inventors: **Paul Joseph Robinson**, Mahtomedi, MN (US); **Cassandra Ann Piippo Svendsen**, Blaine, MN (US); **Charles Anthony Plowe**, Blaine, MN (US); **Albert Selden Benjamin**, St. Paul, MN (US)

2017/320716; A61B 2017/320725; A61B 2017/320733; A61B 2017/320741; A61B 2017/320775; A61B 2017/320783; A61B 2017/320791; A61M 2025/1095; A61M 2025/1084; A61M 2025/1086; A61M 25/104; A61M 25/1011; A61M 2025/1013; A61M 2025/1015; A61M 2025/1043; A61M 2025/1045; A61M 2025/1047; A61M 2025/105  
(Continued)

(73) Assignee: **Cardio Flow, Inc.**, St. Paul, MN (US)  
(\*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 378 days.

(56) **References Cited**  
**U.S. PATENT DOCUMENTS**  
1,431,416 A 10/1922 Parsons et al.  
1,916,085 A 6/1933 Summers et al.  
(Continued)

(21) Appl. No.: **14/155,549**  
(22) Filed: **Jan. 15, 2014**

**FOREIGN PATENT DOCUMENTS**

(65) **Prior Publication Data**  
US 2015/0196320 A1 Jul. 16, 2015

EP 0419154 3/1991  
EP 0 820 729 1/1998  
(Continued)

(51) **Int. Cl.**  
**A61B 17/22** (2006.01)  
**A61B 17/3207** (2006.01)  
(Continued)

**OTHER PUBLICATIONS**

Declaration of Aleksey Filippov, Apr. 23, 2007, 1 page.  
(Continued)


(52) **U.S. Cl.**  
CPC ..... **A61B 17/320758** (2013.01); **A61B 2017/22069** (2013.01); **A61B 2017/320004** (2013.01);  
(Continued)

*Primary Examiner* — Jonathan Miles  
*Assistant Examiner* — Kankindi Rwego  
(74) *Attorney, Agent, or Firm* — Fish & Richardson P.C.

(58) **Field of Classification Search**  
CPC ..... A61B 17/320758; A61B 29/02; A61B 2017/22069; A61B 2017/320004; A61B 2017/320766; A61B 17/32; A61B 17/32002; A61B 17/320016; A61B 17/3207; A61B 2017/320008; A61B 2017/320012; A61B 2017/320708; A61B

(57) **ABSTRACT**  
This document describes rotational atherectomy devices and systems for removing or reducing stenotic lesions in blood vessels by rotating an abrasive element within the vessel to partially or completely remove the stenotic lesion material.

**15 Claims, 6 Drawing Sheets**



Page 2 of 18


(56)





**References Cited**


OTHER PUBLICATIONS



European Search Report in Application No. 15737946.2, dated Aug. 1, 2017, 8 pages.



\* cited by examiner















## ATHERECTOMY DEVICES AND METHODS

## TECHNICAL FIELD

This document relates to rotational atherectomy devices and systems for removing or reducing stenotic lesions in blood vessels, for example, by rotating an abrasive element within the vessel to partially or completely remove the stenotic lesion material.

## BACKGROUND

Atherosclerosis, the clogging of arteries with plaque, is often a cause of coronary heart disease or vascular problems in other regions of the body. Plaque is made up of fat, cholesterol, calcium, and other substances found in the blood. Over time, the plaque hardens and narrows the arteries. This limits the flow of oxygen-rich blood to organs and other parts of the body.

Blood flow through the peripheral arteries (e.g., carotid, iliac, femoral, renal etc.), can be similarly affected by the development of atherosclerotic blockages. Peripheral artery disease (PAD) can be serious because without adequate blood flow, the kidneys, legs, arms, and feet may suffer irreversible damage. Left untreated, the tissue can die or harbor infection.

One method of removing or reducing such blockages in blood vessels is known as rotational atherectomy. In some implementations, a drive shaft carrying an abrasive burr or other abrasive surface (e.g., formed from diamond grit or diamond particles) rotates at a high speed within the vessel, and the clinician operator slowly advances the atherectomy device distally so that the abrasive burr scrapes against the occluding lesion and disintegrates it, reducing the occlusion and improving the blood flow through the vessel. Examples of some rotational atherectomy devices are depicted in U.S. Patent Publication Nos. 2009/0018564, 2009/0182359, 2009/0069829, 2009/0312777, 2009/0326568, 2009/0318942, 2010/0010522, 2010/0049226, 2011/0009888, 2012/0109170, and 2012/0035633; British Patent Publication No. GB2454943; and U.S. Pat. Nos. 4,990,134; 5,314,438; 6,132,444 and 6,146,395.

## SUMMARY

Some embodiments of rotational atherectomy devices and systems described herein can remove or reduce stenotic lesions in blood vessels by rotating an abrasive element according to a stable and predictable orbiting profile. In particular embodiments, a rotational atherectomy device comprises an elongate flexible drive shaft with an eccentric abrasive element that is attached to the drive shaft, and two or more weighted stability elements are attached to the drive shaft such that at least one stability element is on each side of the abrasive element. Optionally, the stability elements have a center of mass that is axially aligned with a central longitudinal axis of the drive shaft while the eccentric abrasive element has a center of mass that is axially offset from central longitudinal axis of the drive shaft. A flexible polymer coating may surround at least a portion of the drive shaft, including the stability elements in some embodiments. Also, in some optional embodiments, a distal extension portion of the drive shaft may extend distally beyond the distal-most stability element.

In one aspect, this document provides a rotational atherectomy device for removing stenotic lesion material from a blood vessel of a patient. In some embodiments, the rota-

tional atherectomy device includes an elongate flexible drive shaft comprising a torque-transmitting coil that defines a longitudinal axis, and the drive shaft is configured to rotate about the longitudinal axis. The rotational atherectomy device may also include an abrasive element that is attached to the drive shaft such that a center of mass of the abrasive element is offset from the longitudinal axis of the drive shaft. The rotational atherectomy device may also include a proximal stability element that is fixed to the drive shaft and that has a center of mass aligned with the longitudinal axis of the drive shaft. The proximal stability element can be proximally spaced apart from the abrasive element. The rotational atherectomy device may also include a distal stability element that is fixed to the drive shaft and that has a center of mass aligned with the longitudinal axis of the drive shaft. The distal stability element can be distally spaced apart from the abrasive element. The rotational atherectomy device may also include a flexible polymer coating along the drive shaft, such that the coating surrounds an outer diameter of at least a portion of drive shaft.

In various implementations of the rotational atherectomy device, the proximal and distal stability elements may be equally spaced apart from the abrasive element by a stability spacing distance. The drive shaft may optionally comprise a distal-most extension portion that extends distally of the distal stability element for a distal extension distance. The distal extension distance may be substantially greater than the stability spacing distance. In some embodiments, the drive shaft may have a central lumen extending along the longitudinal axis that is configured to receive a guidewire. The proximal and distal stability elements may comprise hollow cylinders that surround the torque-transmitting coil of the drive shaft. In particular embodiments, the hollow cylinders may have an exterior cylindrical surface that is smoother and different from an abrasive exterior surface of the abrasive element. Optionally, the hollow cylinders may have an axial length that is greater than a maximum exterior diameter of the hollow cylinders. the flexible polymer coating surrounds the torque-transmitting coil of the drive shaft extending between the first and second stability elements, and exteriors of the abrasive element and the proximal and distal stability elements are uncoated and outwardly exposed.

In some embodiments of the rotational atherectomy device, the flexible polymer coating may surround the torque-transmitting coil of the drive shaft extending between the first and second stability elements. In some such embodiments, the exteriors of the abrasive element and the proximal and distal stability elements may be uncoated and outwardly exposed. In particular embodiments, the flexible polymer coating may surround the outer diameter of the drive shaft extending between the first and second stability elements and may surround exterior surfaces of the first and second stability elements. In some such embodiments, an abrasive outer surface of the abrasive element may be uncoated and outwardly exposed. Optionally, the flexible polymer coating may comprise a fluid-impermeable material that provides a fluid-impermeable lumen along the drive shaft. In some embodiments, the flexible polymer coating may have a different durometer at different locations on the drive shaft.

In some implementations, the rotational atherectomy device may further comprise a second proximal stability element and a second distal stability element. Optionally, the second proximal stability element may be located proximally to the abrasive element and the second distal stability element may be located distally to the abrasive element. In some embodiments, the abrasive element may comprise two

3

or more abrasive segments that may be positioned adjacent to one another along the drive shaft. In particular embodiments, the abrasive element may comprise at least three segments, and a middle segment may optionally have a larger outer diameter than a proximal segment and a larger outer diameter than a distal segment.

In another aspect, this document provides a system for performing rotational atherectomy to remove stenotic lesion material from a blood vessel of a patient. In some embodiments, the system includes an elongate flush tube defining a first lumen and a second lumen. The flush tube may include an inflatable balloon member attached to and surrounding an outer diameter of a distal end portion of the flush tube. The balloon member can be in fluid communication with the first lumen. The balloon member can be configured to contact a blood vessel wall when the balloon member is in an inflated configuration. The system also includes a rotational atherectomy device. The rotational atherectomy device can include an elongate flexible drive shaft defining a longitudinal axis. The drive shaft can be configured for rotation about the longitudinal axis and configured to be at least partially disposed within the second lumen when the system is used for performing the rotational atherectomy. The rotational atherectomy device can also include an abrasive element that is fixed to the drive shaft such that a center of mass of the abrasive element is offset from the longitudinal axis. The rotational atherectomy device can also include a stability element that is fixed to the drive shaft and that has a center of mass aligned with the longitudinal axis, the second stability element being distally spaced apart from the abrasive element.

In various implementations of the system for performing rotational atherectomy, the balloon member may optionally define channel spaces that are configured to allow blood flow therethrough when the balloon member is in the inflated configuration within the blood vessel. In some embodiments, the system for performing rotational atherectomy can further comprise a second stability element that may be fixed to the drive shaft and located proximally of the abrasive element. The system may further comprise a guidewire that can be configured to slidably withdrawn into a fluid-impermeable lumen of the drive shaft of rotational atherectomy device. In some embodiments of the system for performing rotational atherectomy, the rotational atherectomy device may further comprise a flexible polymer coating along the drive shaft such that the coating may surround an outer diameter of at least a portion of drive shaft.

In another aspect, this document provides a method for performing rotational atherectomy to remove stenotic lesion material from a blood vessel of a patient. In some embodiments, the method includes delivering a rotational atherectomy device into the blood vessel. In some embodiments, the rotational atherectomy device includes an elongate flexible drive shaft defining a longitudinal axis. The drive shaft can be configured for rotation about the longitudinal axis. The rotational atherectomy device can also include an abrasive element that is fixed to the drive shaft such that a center of mass of the abrasive element is offset from the longitudinal axis. The rotational atherectomy device can also include a first stability element that is fixed to the drive shaft and that has a center of mass aligned with the longitudinal axis. The first stability element can be proximally spaced apart from the abrasive element. The rotational atherectomy device can also include a second stability element that is fixed to the drive shaft and that has a center of mass aligned with the longitudinal axis. The second stability element can be distally spaced apart from the

4

abrasive element. The method for performing rotational atherectomy to remove stenotic lesion material from a blood vessel of a patient can also include rotating the drive shaft about the longitudinal axis such that a portion of the drive shaft extending between the first and second stability elements traces a generally bicone shape.

In various implementations of the method for performing rotational atherectomy to remove stenotic lesion material from a blood vessel of a patient, during the rotation, the abrasive element may have an orbital path about an axis of rotation. The orbital path may have a substantially greater diameter than a travel path of each of the first and second stability elements. In some embodiments, the method for performing rotational atherectomy may further comprise translating the drive shaft distally during the rotating the drive shaft. The rotating the drive shaft may cause the abrasive element to remove the stenotic lesion material from a vessel wall. In some embodiments, the method for performing rotational atherectomy may further comprise delivering an elongate flush tube into the blood vessel. The flush tube may define a first lumen and a second lumen. The flush tube may include a balloon member attached to and surrounding an outer diameter of a distal end portion of the flush tube. The balloon member may be in fluid communication with the first lumen, and at least a portion of the drive shaft may be disposed within the second lumen. Optionally, the method for performing rotational atherectomy may further comprise inflating the balloon member by supplying an inflation fluid through the first lumen. The inflating may cause the balloon member to expand into contact with the blood vessel.

Some of the embodiments described herein may provide one or more of the following advantages. First, some embodiments of the rotational atherectomy devices and systems operate with a stable and predictable rotary motion profile for enhanced atherectomy performance. That is, when the device is being rotated in operation, the eccentric abrasive element follows a predefined, consistent orbital path (offset from an axis of rotation of the device) while the stability elements and other portions of the device remain on or near to the axis of rotation for the drive shaft in a stable manner. This predictable orbital motion profile can be attained by the use of design features including, but not limited to, stability elements that have centers of mass that are coaxial with the longitudinal axis of the drive shaft, a polymeric coating on at least a portion of the drive shaft, a distal-most drive shaft extension portion, and the like. Some embodiments of the rotational atherectomy devices and systems provided herein may include one or more of such design features.

Second, some embodiments of the rotational atherectomy devices and systems provided herein can be used to treat large-diameter vessels (including renal and iliac arteries having an internal diameter that is multiple time greater than the outer diameter of the abrasive element) while requiring only a small introducer sheath size. In other words, in some embodiments the rotating eccentric abrasive element traces an orbital path that is substantially larger than the outer diameter of the rotational atherectomy device in the non-rotating state. This feature improves the ability of the rotational atherectomy devices provided herein to treat very large vessels while still fitting within a small introducer size. In some embodiments, this feature can be at least partially attained when a guidewire that is used to navigate the atherectomy device to the site of the target lesion is withdrawn prior to rotation of the drive shaft, such that the guidewire does not resist the deflection of the drive shaft

5

during rotation. Further, in some embodiments this feature can be at least partially attained by using an eccentric abrasive element that has a high eccentric mass (e.g., the center of mass of the abrasive element is significantly offset from the central longitudinal axis of the drive shaft).

The details of one or more embodiments of the invention are set forth in the accompanying drawings and the description below. Other features, objects, and advantages of the invention will be apparent from the description and drawings, and from the claims.

#### DESCRIPTION OF DRAWINGS

FIG. 1A is a side view of a distal portion of a rotational atherectomy device, in accordance with some embodiments.

FIG. 1B is a longitudinal cross-sectional view of a portion of the rotational atherectomy device of FIG. 1A, including the device's eccentric abrasive element.

FIGS. 1C and 1D are longitudinal cross-sectional views of portions of the rotational atherectomy device of FIG. 1A that include the device's stability elements.

FIG. 2A is a side view of the rotational atherectomy device of FIG. 1A after being deployed within a vessel that is shown in longitudinal cross-section.

FIGS. 2B through 2D illustrate the rotational atherectomy device of FIG. 2A being rotated to provide an atherectomy treatment.

FIG. 3A is a side view of a distal portion of another rotational atherectomy device, in accordance with some embodiments.

FIG. 3B is a longitudinal cross-sectional view of a portion of the rotational atherectomy device of FIG. 3A, including the device's eccentric abrasive element.

FIGS. 3C and 3D are longitudinal cross-sectional views of portions of the rotational atherectomy device of FIG. 3A that include the device's stability elements.

FIG. 4A is a side view of a distal portion of another rotational atherectomy device, in accordance with some embodiments.

FIG. 4B is a longitudinal cross-sectional view of a portion of the rotational atherectomy device of FIG. 4A, including some of the device's stability elements.

FIG. 5A is a side view of a distal portion of another rotational atherectomy device, in accordance with some embodiments.

FIG. 5B is a longitudinal cross-sectional view of a portion of the rotational atherectomy device of FIG. 5A, including some of the device's stability elements.

FIG. 6 is a side view of a distal portion of another rotational atherectomy device, in accordance with some embodiments.

FIG. 7 is a side view of a distal portion of a rotational atherectomy system, including a flush tube with a proximal stabilization balloon, in accordance with some embodiments.

FIG. 8 is a side view of the rotational atherectomy system of FIG. 7 deployed within a vessel that is shown in longitudinal cross-section.

FIG. 9 is a side view of another rotational atherectomy system, in accordance with some embodiments, deployed within a vessel that is shown in longitudinal cross-section.

Like reference symbols in the various drawings indicate like elements.

#### DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

Referring to FIG. 1A, in some embodiments a rotational atherectomy device 100 can include a drive shaft 110, a

6

proximal stability element 120, a distal stability element 130, and an eccentric abrasive element 140. In this embodiment, the stability elements 120 and 130 have a center of mass that is axially aligned with a central longitudinal axis 102 of the drive shaft 110 while the eccentric abrasive element 140 has a center of mass that is axially offset from central longitudinal axis 102 of the drive shaft 110. As will be described further below, the rotational atherectomy device 100 is configured to remove some or all of a stenotic lesion from within a vessel of a patient. As the rotational atherectomy device 100 is rotated about its longitudinal axis 102, centrifugal force will cause the eccentric abrasive element 140 to follow a transverse circular orbit around the longitudinal axis. The orbiting eccentric abrasive element 140 will contact the stenotic lesion to ablate the lesion to a reduced size.

The proximal stability element 120 and the distal stability element 130 are each fixedly attached to the drive shaft 110. The proximal stability element 120 is located proximal to the distal stability element 130. The eccentric abrasive element 140 is located between the proximal stability element 120 and the distal stability element 130. The eccentric abrasive element 140 is also fixedly attached to the drive shaft 110. A distal drive shaft extension portion 112 of the drive shaft 110 extends distally of the distal stability element 130.

Referring now to FIGS. 1A-1D, the elongate drive shaft 110 of rotational atherectomy device 100 is laterally flexible so that the drive shaft 110 can readily conform to the tortuous non-linear vasculature of the patient, and so that a portion of the drive shaft 110 adjacent to the eccentric abrasive element 140 will laterally deflect when acted on by the centrifugal forces resulting from the rotation of the eccentric abrasive element 120. In this embodiment, the drive shaft 110 comprises one or more helically wound wires 114 (or filars 114). In some embodiments, the one or more helically wound wires 114 are made of a metallic material such as, but not limited to, stainless steel (e.g., 316, 316L, or 316LVM), nitinol, titanium, titanium alloys (e.g., titanium beta 3), carbon steel, or another suitable metal or metal alloy. In some alternative embodiments, the filars 114 are or include graphite, Kevlar, or a polymeric material. In some embodiments, the filars 114 can be woven, rather than wound. In some embodiments, individual filars 114 can comprise multiple strands of material that are twisted, woven, or otherwise coupled together to form a filar 114. In some embodiments, the filars 114 have different cross-sectional geometries (size or shape) at different portions along the axial length of the drive shaft 110. In some embodiments, the filars 114 have a cross-sectional geometry other than a circle, e.g., an ovalar, square, triangular, or another suitable shape. The one or more helically wound wires 114 can transmit a torque from a rotary actuator (comprising, for example, a pneumatic motor or an electric motor) located exterior to the patient (not shown in FIG. 1A). The torque from the external actuator is transmitted via the drive shaft 110 to the elements 120, 130, 140, and 112 along the distal portion of the rotational atherectomy device 100.

In this embodiment, the drive shaft 110 has a hollow core. That is, the drive shaft 110 has a longitudinal lumen 115 running therethrough. The lumen 115 can be used to receive a guidewire therein, as will be described further below. In some embodiments, the lumen can be used to aspirate particulate or to convey fluids that are beneficial for the atherectomy procedure.

7

The size of the drive shaft **110** can be scaled commensurately with the size of vessels to be treated and the performance desired. In a first example embodiment, the outer diameter of the drive shaft **110** is about 0.030 inches (0.76 mm) and the inner diameter is about 0.020 inches (0.51 mm). The first example embodiment uses a six (6) filar configuration with each filar having a diameter of about 0.005 inches (0.13 mm). In a second example embodiment, the outer diameter of the drive shaft **110** is about 0.051 inches (1.30 mm) and the inner diameter is about 0.041 inches (1.04 mm). The second example embodiment uses a nine (9) filar configuration with each filar having a diameter of about 0.005 inches (0.13 mm).

From the description provided herein, it should be understood that a range of sizes of drive shafts **110** are contemplated. For example, the outer diameter of the drive shaft **110** may range from about 0.020 inches to about 0.100 inches (0.50 mm to 2.54 mm). The drive shafts **110** can have any number of filars, and the diameter of the filars may range from about 0.002 inches to about 0.020 inches (0.05 mm to 0.51 mm).

In the depicted embodiment, the drive shaft **110** also includes a coating **116** on the outer diameter of the drive shaft **110**. The coating **116** may also be described as a jacket, a sleeve, a covering, a casing, and the like. In some embodiments, the coating **116** adds column strength to the drive shaft **110** to facilitate a greater ability to push the drive shaft **110** through stenotic lesions. In addition, the coating **116** can enhance the stability of the drive shaft **110** during use. In some embodiments, the coating **116** is a flexible polymer coating that surrounds an outer diameter of at least a portion of drive shaft **110** (e.g., the portion of the drive shaft located exterior to the patient and extending fully to at least the proximal stability element **120**). In particular embodiments, the coating **116** is a fluid impermeable material such that the lumen **115** provides a fluid impermeable flow path to the distal portion of the device **100**.

The coating **116** may be made of materials including, but not limited to, PEBEX, PICO FLEX, TECOFLEX, PTFE, ePTFE, FEP, PEEK, silicone, PVC, urethane, polyethylene, polypropylene, and the like, and combinations thereof. In some embodiments, a second coating that is analogous to the coating **116** may also be included on the inner diameter of the drive shaft **110**. Alternatively, the coating on the inner diameter of the drive shaft **110** may be included as an alternative to the coating **116** on the outer diameter of the drive shaft **110**. In the depicted embodiment, the coating **116** covers not only the drive shaft **110**, but also the proximal stability element **120**, the distal stability element **130**, and the distal extension portion **112**, thereby leaving only the abrasive element **140** exposed (non-coated) along the distal portion of the device **100**. In alternative embodiments, the proximal stability element **120** and the distal stability element **130** are not covered with the coating **116**, and thus would be exposed like the abrasive element **140**. In some embodiments, two or more layers of the coating **116** can be included on portions of the drive shaft **110**. Further, in some embodiments different coating materials (e.g., with different durometers and/or stiffnesses) can be used at different locations on the drive shaft **110**. For example, a first portion of the coating **116** extending along the drive shaft that is proximal to the proximal stability element **120** and distal to the distal stability element **130** can have a first durometer that is different from (e.g., substantially higher than) a second durometer of a second portion of the coating **116** extending between the proximal stability element **120** and the distal stability element **130**.

8

Still referring to FIGS. 1A-1D, in this embodiment, the proximal stability element **120** and the distal stability element **130** are each hollow cylindrical members having an inner diameter that surrounds a portion of the outer diameter of the drive shaft **110**. In some embodiments, the proximal stability element **120** and the distal stability element **130** have an axial length that is greater than a maximum exterior diameter of the proximal stability element **120** and the distal stability element **130**. As shown in FIGS. 1C-1D, the proximal stability element **120** and the distal stability element **130** are coaxial with the longitudinal axis **102** of the drive shaft **110**. Therefore, the centers of mass of the proximal stability element **120** and the distal stability element **130** are axially aligned (non-eccentric) with the longitudinal axis **102**. In alternative rotational atherectomy device embodiments, stability elements that have centers of mass that are eccentric in relation to the longitudinal axis **102** may be included in addition to, or as an alternative to, the coaxial proximal and distal stability elements **120** and **130**. For example, in some alternative embodiments, the stability elements can have centers of mass that are eccentric in relation to the longitudinal axis **102** and that are offset 180 degrees in relation to the center of mass of the eccentric abrasive element **140**.

The proximal stability element **120** and the distal stability element **130** may be made of a suitable biocompatible material, such as a higher-density biocompatible material. For example, in some embodiments the proximal stability element **120** and the distal stability element **130** may be made of metallic materials such as stainless steel, tungsten, molybdenum, iridium, cobalt, cadmium, and the like, and alloys thereof. The proximal stability element **120** and the distal stability element **130** may be mounted to the filars **114** using a biocompatible adhesive, by welding, by press fitting, and the like, and by combinations thereof. The coating **116** may also be used to attach or to supplement the attachment of the proximal stability element **120** and the distal stability element **130** to the filars **114** of the drive shaft **110**. Alternatively, the proximal stability element **120** and the distal stability element **130** can be integrally formed as a unitary structure with the filars **114** of the drive shaft **110** (e.g., using filars of a different size or density, using filars that are double-wound to provide multiple filar layers, or the like). The proximal stability element **120** and the distal stability element **130** have an exterior cylindrical surface that is smoother and different from an abrasive exterior surface of the abrasive element **140**.

Still referring to FIGS. 1A-1D, the eccentric abrasive element **140**, which may also be referred to as a burr, can comprise a biocompatible material that is coated with an abrasive media such as diamond grit, diamond particles, silicon carbide, and the like. As shown in FIG. 1B, the center of mass of the eccentric abrasive element **140** is offset from the longitudinal axis **102** of the rotational atherectomy device **100**. The eccentric abrasive element **140** has at least one outwardly exposed surface (the abrasive surface **142**) that is not covered by the coating **116**. Therefore, as the eccentric abrasive element **140** is rotated in an orbital path, at least a portion of the abrasive surface **142** of the eccentric abrasive element **140** can make contact with surrounding stenotic lesion material. As with the stability elements **120** and **130**, the eccentric abrasive element **140** may be mounted to the filars **114** using a biocompatible adhesive, welding, press fitting, and the like. Alternatively, the eccentric abrasive element **140** can be integrally formed as a unitary structure with the filars **114** of the drive shaft **110** (e.g., using filars that are wound in a different pattern to create an axially offset structure, or the like).

9

Referring again to FIG. 1A, in some embodiments, the spacing of the proximal stability element **120** and the distal stability element **130** (relative to the eccentric abrasive element **140**) and the length of the distal extension portion **112** can be selected to advantageously provide a stable and predictable rotary motion profile during high-speed rotation of the device **100**. For example, in this embodiment, the eccentric abrasive element **140** is separated from the proximal stability element **120** by a distance D1. The eccentric abrasive element **140** is separated from the distal stability element **130** by a distance D2. In the depicted embodiment, the distances D1 and D2 are equal. The distal driveshaft extension portion **112** is a portion of the driveshaft **110** that extends distally from the distal stability element **130** by a distance D3. In use, the distal driveshaft extension portion **112** adds to the stability of the rotational atherectomy device **100**, while the eccentric abrasive element **140** is following its orbital path around the longitudinal axis **102**. In the depicted embodiment, the distal driveshaft extension portion **112** is covered with the coating **116**. In this particular embodiment, the distance D3 is significantly greater than the distance D1 or D2.

In embodiments that include the distal driveshaft extension portion **112**, the ratio of the distance D3 to the distance D1 (or D2) can be selected to affect the performance characteristics (e.g., the stability of the rotary motion profile) of the rotational atherectomy device **100**. In some embodiments, the ratio of D3:D1 (or D3:D2) is about 1:1, about 1.5:1, about 2:1, about 2.5:1, about 3:1, or higher than 3:1. It should be understood from the description herein, that in some alternative embodiments, the distances D1 and D2 may be unequal.

Referring now to FIG. 2A, the rotational atherectomy device **100** can be used to treat a vessel **180** having a stenotic lesion **190** along an inner wall **182** of the vessel **180**. The rotational atherectomy device **100** is used to fully or partially remove the stenotic lesion **190**, thereby removing or reducing the blockage within the vessel **180** caused by the stenotic lesion **190**. By performing such a treatment, the blood flow through the vessel **180** may be thereafter increased or otherwise improved. The vessel **180** and lesion **190** are shown in longitudinal cross-sectional views to enable visualization of the rotational atherectomy device **100**.

Briefly, in some implementations the following activities may occur to provide the deployed arrangement shown in FIG. 2A. An introducer sheath (not shown in FIG. 2A) can be percutaneously advanced into the vasculature of the patient and navigated within the patient's vasculature to the targeted vessel **180**. Techniques such as x-ray fluoroscopy or ultrasonic imaging may be used to provide visualization of the introducer sheath and other atherectomy system components during placement. A guidewire (not shown in FIG. 2A) can then be inserted through a lumen of the introducer sheath and advanced to extend beyond the distal tip of the introducer sheath (and, optionally, through the area of the stenotic lesion **190**). Next, the rotational atherectomy device **100** can be inserted over the guidewire (via the lumen **115**) and advanced to the deployed position shown (optionally, the introduced sheath can be withdrawn before the rotational atherectomy device is advanced over the guidewire). In some implementations, a flush tube (e.g., refer to FIGS. 8 and 9) may surround a portion of the drive shaft **110** while the rotational atherectomy device **100** is so inserted over the guidewire.

In the deployed position as shown in the embodiment depicted in FIG. 2A, the eccentric abrasive element **140** is

10

positioned near to the lesion **190** such that the eccentric abrasive element **140** can contact the lesion **190** when the drive shaft **110** is later rotated and advanced to remove the lesion **190**. After the rotational atherectomy device **100** is placed in the deployed position, the guidewire is pulled back from within the lumen **115** of the drive shaft **110**. In some implementations, the guidewire is withdrawn completely out of the lumen **115** of the drive shaft **110**. In other implementations, the guidewire is withdrawn only partially (e.g., to a position that is proximal of the proximal stability element **120** and preferably proximal of the distal tip of the flush tube. That is, in some implementations a portion of the guidewire remains within the lumen of the drive shaft **110** during rotation of the drive shaft **110**, but remains only in the portion that is not subject to the significant orbital path in the area of the abrasive element **140**. After the guidewire is withdraw (fully or partially), the drive shaft **110** is then rotated (via the actuator located at the proximal end outside of the patient's body) at a high degree of rotation (e.g., 20,000-160,000 rpm) such that the eccentric abrasive element **140** revolves in an orbital path about an axis of rotation **103** and thereby contacts and removes portions of the lesion **190**, even those portions of the lesion **190** that are spaced further from the axis of rotation **103** than the maximum diameter of the abrasive element **140**.

Referring now to FIGS. 2B through 2D, the rotational atherectomy device **100** is depicted during the high-speed rotation of the drive shaft **110**. The centrifugal force acting on the eccentrically weighted abrasive element **140** causes the eccentric abrasive element **140** to orbit in an orbital path around the axis of rotation **103**. In some implementations, the orbital path can be somewhat similar to the motion of a "jump rope." As shown in FIGS. 2B-2D, some portions of the drive shaft **110** (e.g., a portion that is proximal of the proximal stability element **120** and another portion that is distal of the distal stability element **130**) can be aligned with the axis of rotation **103**, but the particular portion of the drive shaft **110** adjacent to the abrasive element **140** is not aligned with the axis of rotation **103** (and instead orbits around the axis **103**). In such circumstances, the longitudinal axis **102** of the drive shaft **110** in those particular portions (e.g., the shaft portion that is proximal of the proximal stability element **120** and the other shaft portion that is distal of the distal stability element **130**) may be generally axially aligned with the axis of rotation **103**, as shown in FIGS. 2B-D. It should be understood from the description herein that the term "generally axially aligned" is intended to account for the momentary variances that occur in the drive shaft position due to the high-speed rotation of the drive shaft, but that the longitudinal axis **102'** (FIGS. 2B-2C) at the particular portion of the drive shaft **110** adjacent to the abrasive element **140** is not generally axially aligned with the axis of rotation **103** during the high speed rotation. In some implementations, as the eccentric abrasive element **140** rotates, the clinician operator slowly advances the atherectomy device **100** distally (and, optionally, reciprocates both distally and proximally) in the axial direction so that the abrasive surface of the eccentric abrasive element **140** scrapes against additional portions of the occluding lesion **190** to reduce the size of the occlusion, and to thereby improve the blood flow through the vessel **180**.

During rotation of the atherectomy device **100**, the proximal and distal stability elements **120** and **130**, as well as the distal drive shaft extension portion **112**, can be configured to advantageously achieve improved stability for the drive shaft **110** relative to the axis of rotation **103**. For example, the device **100** can achieve a stable and predictable rotary

11

motion profile in which the shaft portion that is proximal of the proximal stability element **120** and the other shaft portion that is distal of the distal stability element **130** remain generally aligned with the axis of rotation **103**, even though the particular portion of the drive shaft **110** adjacent to the abrasive element **140** is not generally aligned with the axis of rotation **103** (and instead orbits around the axis **103**). In this stability rotary motion profile, the eccentric abrasive element can follow a predictable orbital path (offset from an axis of rotation **103**), yet other portions of the drive shaft **110** (especially the distal extension **112**) can remain in a substantially stable axial alignment that greatly reduces the likelihood of uncontrolled whipping of the distal-most tip of the drive shaft **110** (which might cause unnecessary damage to the vessel wall **182**). For example, such stability can be achieved by selecting some or all of the following design aspects of the rotational atherectomy device **100**: (i) the mass of the proximal and distal stability elements **120** and **130**, (ii) the length of the distal drive shaft extension portion **112** as a ratio to the distance between the proximal and distal stability elements **120** and **130** and the eccentric abrasive element **140**, and (iii) the stiffness of the drive shaft **110** including any coating **116** on the drive shaft **110**. In some embodiments, different coatings **116** (e.g., different materials and/or durometers) are used on different portions of the drive shaft **110** to enhance the in-operation stability of the rotational atherectomy device **100**. In particular embodiments, multiple layers of coatings can be used on different portions of the drive shaft **110** to enhance the in-operation stability of the rotational atherectomy device **100**.

As best seen in FIG. 2D, when rotating, the operative portion of the drive shaft **110** between the proximal and distal support elements **120** and **130** traces a generally bicone shape. By providing this predictable shape during high-speed rotation of the drive shaft **110**, the shaft portion that is proximal of the proximal stability element **120** and the other shaft portion that is distal of the distal stability element **130** can remain both generally aligned with one another and can remain in a generally stable position within the vessel **180** (e.g., centrally aligned with the vessel **180**). Also, when the device **100** provides this stable and predictable rotary motion profile, the orbital path of the abrasive element **140** is substantially greater than any orbital path of the proximal and distal stability elements **120** and **130** (if those elements **120** and **130** have any orbital path at all). As shown in the example in FIG. 2D, the orbital path diameter of the abrasive element **140** is substantially greater than the maximum diameter of the rotational path of each of the proximal and distal stability elements **120** and **130**.

Referring now to FIGS. 3A through 3D, some embodiments of a rotational atherectomy device **300** can include proximal and distal stability elements **320** and **330** that are uncoated in this embodiment. The other aspects (e.g., materials, structure, construction, and alternatives) of the rotational atherectomy device **300** are similar to the rotational atherectomy device **100** described above.

In the depicted embodiment, a coating **316** surrounds at least some sections of filars **314** of drive shaft **310** (e.g., from the stability elements **320** and **330** to an eccentric abrasive element **340**, and on a distal driveshaft extension portion **312**). However, the coating **316** does not surround the outer diameters of the proximal and distal stability elements **320** and **330** in this embodiment. In some embodiments, one stability element **320** or **330** may be coated while the other stability element **320** or **330** remains uncoated.

Referring now to FIGS. 4A and 4B, some embodiments of a rotational atherectomy device **400** can include multiple

12

proximal stability elements **420a-b** and multiple distal stability elements **430a-b**. For example, as shown in FIGS. 4A-4B, the atherectomy device **400** includes two proximal stability elements **420a-b** and two distal stability elements **430a-b**. The other aspects (e.g., materials, structure, construction, and alternatives) of the rotational atherectomy device **400** can be similar to the rotational atherectomy device **100** described above. In some embodiments, the inclusion of such multiple stability elements can enhance the stability and predictability of rotary motion profile of the abrasive element **440** and the drive shaft **410** along the distal portion of the rotational atherectomy device **400**.

In the depicted embodiment, each of the stability elements **420a-b** and **430a-b** has a center of mass that is axially aligned with a longitudinal axis **402** of drive shaft **410**. However, in alternative embodiments the center of mass of one or more of the stability elements **420a-b** and/or **430a-b** may be offset from the longitudinal axis **402**. In the depicted embodiment, a distal drive shaft extension portion **412** extends distally from the distal-most stability element **430b**. However, in alternative embodiments, the distal driveshaft extension portion **412** may be omitted. In the depicted embodiment, the outer diameters of the stability elements **420a-b** and **430a-b** are surrounded by a coating **416**, which can be similar to the coating **116** described in connection with FIGS. 1A-D. However, in alternative embodiments one or more of the stability elements **420a-b** and **430a-b** may be uncoated.

In some embodiments, the stability elements **420a** and **420b** (and the same applies to the stability elements **430a** and **430b**) are spaced closely enough together such that the stability elements **420a** and **420b** perform much like a single stability element to stabilize the drive shaft **410**. In alternative embodiments, the stability elements **420a** and **420b** (and the same applies to the stability elements **430a** and **430b**) are spaced apart from each other enough such that the stability elements **420a** and **420b** perform much like independent stability elements to stabilize the drive shaft **410**.

Referring now to FIGS. 5A and 5B, some embodiments of a rotational atherectomy device **500** can include three proximal stability elements **520a-c** and three distal stability elements **530a-c**. The other aspects (e.g., materials, structure, construction, and alternatives) of the rotational atherectomy device **500** can be similar to the rotational atherectomy device **100** described above. In some embodiments, the inclusion of such multiple stability elements can enhance the stability and predictability of rotary motion profile of the abrasive element **540** and the drive shaft **510** along the distal portion of the rotational atherectomy device **500**.

In the depicted embodiment, each of the stability elements **520a-c** and **530a-c** has a center of mass that is axially aligned with a longitudinal axis **502** of drive shaft **510**. However, in alternative embodiments the center of mass of one or more of the stability elements **520a-b-c** and **530a-b-c** may be offset from the longitudinal axis **502**. In the depicted embodiment, a distal driveshaft extension portion **512** extends distally from the distal-most stability element **530c**. However, in alternative embodiments the distal drive shaft extension portion **512** may be omitted. In the depicted embodiment, the outer diameters of the stability elements **520a-b-c** and **530a-b-c** are uncoated. However, in alternative embodiments the outer diameters of one or more of the stability elements **520a-b-c** and **530a-b-c** may be surrounded by a coating **516**, which can be similar to the coating **116** described in connection with FIGS. 1A-D.

Referring now to FIG. 6, some embodiments of a rotational atherectomy device **600** can include a segmented

13

eccentric abrasive element that includes multiple side-by-side abrasive segments **640a-c**. The other aspects (e.g., materials, structure, construction, and alternatives) of the rotational atherectomy device **600** are similar to the rotational atherectomy device **100** described above. In some embodiments, the inclusion of the segmented abrasive element **640a-c** can enhance the flexibility of the portion of the drive shaft **610** within the segments **640a-c**, thereby providing (in some circumstances) a greater orbital path diameter as compared to other embodiments having a single, elongate abrasive element. The segmentation of the abrasive element **640a-c** can also provide for a wider abrasive element, thereby increasing the treatment efficiency (e.g., reducing the treatment time) of the rotational atherectomy device **600**.

In the depicted embodiment, the segmented eccentric abrasive element **640a-c** includes three segments. In alternative embodiments, two, four, five, or more than five segments can be included. In the depicted embodiment, all three segments **640a-c** have centers of mass that are offset from a longitudinal axis **602** of a drive shaft **610**. In alternative embodiments, one or more of the segments may have a center of mass that is aligned with the longitudinal axis **602** while the other segment(s) is eccentric and thus not aligned with the longitudinal axis **602**. In the depicted embodiment, all three segments **640a-c** are shaped as ellipsoids. In alternative embodiments, one or more of the segments may have a different shape such as, but not limited to, spherical, cylindrical, conical, frusto conical, polyhedral, and the like. In the depicted embodiment, the outer diameters of the two outer abrasive elements **640a** and **640c** are smaller than the central abrasive element **640b**. Together, the segmented eccentric abrasive element **640a-b-c** therefore has a tapered outer profile. In alternative embodiments, all segments may have essentially the same outer diameter, or may define a different outer profile shape.

Referring now to FIG. 7, as previously described herein, some embodiments of a rotational atherectomy system include a rotational atherectomy device **700** and a flush tube **750**. The rotational atherectomy device **700** can be configured as any of the above-described atherectomy devices **100**, **300**, **400**, **500**, and **600**. In use, a portion of a drive shaft **710** of the rotational atherectomy device **700** can be slidably positioned within a lumen of the flush tube **750**. As such, while the drive shaft **710** is rotating at a high speed (e.g., 20,000 to 180,000 rpm), the flush tube **750** can remain stationary relative to the vessel wall. In these circumstances, the flush tube **750** can further enhance to the stability of the portion of the drive shaft **710** that is proximal to the abrasive element (not shown in FIG. 7, refer to FIG. 8) and improve the predictability of the rotary motion profile of the abrasive element. In some embodiments, the flush tube also increases the column strength (and therefore the ability to be pushed) of the drive shaft and flush tube system **710** and **750** during the system's advancement over the guidewire within the vasculature of the patient.

In this embodiment, the flush tube **750** includes a multi-lumen shaft **752** and a stabilization balloon **754**, which can be inflated after deployment into the targeted vessel. The stabilization balloon **754** is attached to a distal end portion of the multi-lumen shaft **752** and is in fluid communication with an inflation lumen of the multi-lumen shaft **752**. The inflation lumen of the multi-lumen shaft **752** can be used to convey an inflation fluid (e.g., saline) to the stabilization balloon **754**. When inflation fluid is supplied to the stabilization balloon **754**, the stabilization balloon **754** can expand to the configuration shown. Conversely, when inflation fluid is not supplied to the stabilization balloon **754**, the stabili-

14

zation balloon **754** contracts to a configuration that is smaller in size than the expanded configuration shown.

In addition to the inflation lumen, the multi-lumen shaft **752** includes a longitudinal drive shaft lumen in which a portion of the drive shaft **710** can be slidably positioned. A physical clearance exists between the outer diameter of the drive shaft **710** and the inner diameter of the drive shaft lumen. The clearance allows the drive shaft **710** to freely rotate while the flush tube **750** is stationary relative to the vessel. In some embodiments, the clearance is in a range of about 0.05 mm to about 0.15 mm, or about 0.13 mm to about 0.23 mm, or about 0.20 mm to about 0.30 mm, or about 0.28 mm to about 0.38 mm, or about 0.35 mm to about 0.46 mm, or more than about 0.46 mm. In addition to allowing the drive shaft **710** to rotate while the flush tube **750** is stationary, the clearance therebetween can be used to convey a flush fluid (e.g., saline). The flush fluid prevents blood from the vessel being treated from backing up into the clearance space. In addition, in some embodiments the flush fluid can provide cooling and lubrication to the surface friction between the drive shaft **710** and the drive shaft lumen of the flush tube **750** as the drive shaft **710** is rotating.

Still referring to FIG. 7, in some embodiments, the stabilization balloon **754** can include one or more ribs **756**. As will be described further below, the ribs **756** facilitate the flow of blood past the stabilization balloon **754** even while the stabilization balloon **754** is in an expanded configuration and in contact with an inner wall of the targeted vessel. This feature for facilitating blood flow is advantageous in that blood flow is not cut off during an atherectomy procedure. While the depicted embodiment of stabilization balloon **754** includes the ribs **756**, in alternative embodiments other types of features for facilitating blood flow through or around a stabilization balloon can be included. For example, in some embodiments features such as, but not limited to, through-holes or lumens, grooves, and the like, can be included to facilitate blood flow through or around a stabilization balloon.

Referring to FIG. 8, the rotational atherectomy device **700** in conjunction with the flush tube **750** can be used to provide an atherectomy treatment to a stenotic lesion **890** within a vessel **880**. The vessel **880** and lesion **890** are shown in longitudinal cross-sectional views to enable visualization of the rotational atherectomy device **700** and the flush tube **750**. In some implementations, the flush tube **750** can further enhance to the stability of the portion of the drive shaft **710** that is proximal to the abrasive element **740** and improve the predictability of the rotary motion profile of the abrasive element **740**.

During rotation of the drive shaft **710** about its axis **702**, the stabilization balloon **756** is in an expanded configuration as shown. As such, the ribs **756** make contact with the inner wall of the vessel **880** to maintain the position of the balloon **756** relative to the vessel **880** while also permitting continued blood flow past the balloon **756**. The drive shaft **710** can then be rotated to cause the eccentric abrasive element **740** to orbit around the axis of rotation **703** of the atherectomy device **700** to ablate the lesion **890**. Similar to previously described embodiments, the device **700** can achieve a stable and predictable rotary motion profile in which the shaft portion that is proximal of the proximal stability element **720** and the other shaft portion that is distal of the distal stability element **730** remain generally aligned with the axis of rotation **703**, even though the particular portion of the drive shaft **710** adjacent to the abrasive element **740** is not generally aligned with the axis of rotation **703** (and instead orbits around the axis **703**). The flush tube **750** remains

15

substantially stationary as the drive shaft **710** is rotated. The contact between the ribs **756** and the inner wall of the vessel **880** help the stabilization balloon **754** to further stabilize the atherectomy device **700** during rotation and to also centrally position the shaft portion that is proximal of the proximal stability element **720** within the targeted vessel **880**. During the atherectomy procedure, on-going blood flow through the vessel **880** is facilitated by the channel spaces defined between the ribs **756** of the stabilization balloon **754**.

Referring to FIG. 9, another embodiment of a rotational atherectomy can include an alternative rotational atherectomy device **900** and the previously described flush tube **750**, which can be used together to provide an atherectomy treatment to a stenotic lesion **990** within a targeted vessel **980**. In this embodiment, the rotational atherectomy device **900** includes a distal stability element **930**, but does not include a corresponding proximal stability element. Rather, the stabilization balloon **754** of the flush tube **750** provides the function of stabilizing the portion of the drive shaft **910** that is proximal of the abrasive element **940** during high-speed rotation of the drive shaft **910**. Thus, the stabilization balloon **754** and the distal stability element can work in tandem to provide a stable and predictable rotary motion profile in which the shaft portion that is proximal of the abrasive element **940** (and immediately adjacent to the balloon **754**) and the other shaft portion that is distal of the distal stability element **930** remain generally aligned with the axis of rotation **903**, even though the particular portion of the drive shaft **910** adjacent to the abrasive element **940** is not generally aligned with the axis of rotation **903** (and instead orbits around the axis **903**).

A number of embodiments of the invention have been described. Nevertheless, it will be understood that various modifications may be made without departing from the spirit and scope of the invention. For example, design features of the embodiments described herein can be combined with other design features of other embodiments described herein. Accordingly, other embodiments are within the scope of the following claims.

What is claimed is:

1. A system for performing rotational atherectomy to remove stenotic lesion material from a blood vessel of a patient, the system comprising:

an elongate flush tube defining a first lumen and a second lumen; and

a rotational atherectomy device comprising:

an elongate flexible drive shaft comprising helically wound metallic filars that form a coil having a constant outer diameter, the drive shaft defining a longitudinal axis, the drive shaft configured for rotation about the longitudinal axis, the drive shaft configured to be at least partially disposed within the second lumen when the system is used for performing the rotational atherectomy;

an array of at least three spherical abrasive elements positioned adjacent to one another along the coil, the spherical abrasive elements being fixed to the drive shaft such that a center of mass of each abrasive element is offset from the longitudinal axis, each abrasive elements being spaced apart from an adjacent abrasive element by an element spacing distance; and

a metallic stability element having a cylindrical shape defining an inner diameter, the metallic stability element being fixed along the inner diameter to the helically wound metallic filars of the drive shaft, the metallic stability element having a center of mass

16

aligned with the longitudinal axis, the stability element being distally spaced apart from a distal-most abrasive element of the spherical abrasive elements by a distal separation distance, the distal separation distance being greater than the element spacing distance;

wherein the drive shaft includes a distal extension portion extending distally beyond a distal end of the metallic stability element; and

wherein the drive shaft, the abrasive elements, and the metallic stability element rotate together about the longitudinal axis.

2. The system of claim 1, further comprising a second stability element fixed to the drive shaft and located proximally of the abrasive elements.

3. The system of claim 1, further comprising a guidewire configured to be slidably disposed within a fluid-impermeable lumen of the drive shaft.

4. The system of claim 1, wherein the abrasive elements comprise five spherical abrasive elements positioned adjacent to one another along the drive shaft.

5. The system of claim 4, wherein the array comprises outer spherical abrasive elements and at least one inner spherical abrasive element, wherein an outer diameter of the outer spherical abrasive element is smaller than an outer diameter of the at least one inner spherical abrasive element.

6. The system of claim 1, wherein the drive shaft has a central lumen extending along the longitudinal axis that is configured to receive a guidewire.

7. The system of claim 1, wherein the drive shaft comprises a torque-transmitting coil and wherein the stability element comprises a hollow metallic cylinder with an inner diameter that is fixed along the inner diameter to an outer diameter of the torque-transmitting coil.

8. The system of claim 7, wherein the hollow metallic cylinder has an axial length that is greater than a maximum exterior diameter of the hollow metallic cylinder.

9. The system of claim 1, wherein each spherical abrasive element of the at least three spherical abrasive elements has an abrasive outer surface, and wherein a middle spherical abrasive element of the at least three spherical abrasive elements has a larger outer diameter than a proximal spherical abrasive element of the at least three spherical abrasive elements and a larger outer diameter than a distal spherical abrasive element of the at least three spherical abrasive elements.

10. The system of claim 1, wherein the metallic stability element comprises a hollow metallic cylinder with an exterior cylindrical surface.

11. The system of claim 1, wherein an outer surface of the balloon member defines channel spaces configured to allow blood flow past the balloon member when the balloon member is in the inflated configuration and in contact with the blood vessel wall.

12. The system of claim 1, wherein the flush tube includes an inflatable balloon member attached to and surrounding an outer diameter of a distal end portion of the flush tube, the balloon member is in fluid communication with the first lumen, and the balloon member is configured to contact a blood vessel wall when the balloon member is in an inflated configuration.

13. The system of claim 1, wherein the device further comprises a flexible polymer coating covering an outer diameter of the metallic stability element and an outer diameter of at least a portion of the drive shaft, and wherein the drive shaft has an outer diameter covered by the flexible polymer coating.

17

14. The system of claim 13, wherein the flexible polymer coating comprises a fluid-impermeable material that provides a fluid-impermeable lumen along the drive shaft.

15. The system of claim 13, wherein the flexible polymer coating has a different durometer at different locations on the drive shaft.

\* \* \* \* \*

18