



US007563267B2

(12) **United States Patent**
Goldfarb et al.

(10) **Patent No.:** **US 7,563,267 B2**
(45) **Date of Patent:** **Jul. 21, 2009**

(54) **FIXATION DEVICE AND METHODS FOR ENGAGING TISSUE**

(75) Inventors: **Eric A. Goldfarb**, San Francisco, CA (US); **Alfred H. Raschdorf, Jr.**, San Francisco, CA (US); **Jaime E. Sarabia**, San Jose, CA (US); **Sylvia Wen Chin Fan**, San Francisco, CA (US); **Kent D. Dell**, Redwood City, CA (US); **Jan Komtebedde**, Los Gatos, CA (US); **Ferolyn T. Powell**, San Francisco, CA (US)

(73) Assignee: **Evalve, Inc.**, Menlo Park, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1074 days.

(21) Appl. No.: **10/441,531**

(22) Filed: **May 19, 2003**

(65) **Prior Publication Data**

US 2004/0049207 A1 Mar. 11, 2004

Related U.S. Application Data

(60) Continuation-in-part of application No. 09/894,463, filed on Jun. 27, 2001, now Pat. No. 6,752,813, which is a continuation-in-part of application No. 09/544,930, filed on Apr. 7, 2000, now Pat. No. 6,629,534, which is a division of application No. 60/128,690, filed on Apr. 9, 1999.

(51) **Int. Cl.**
A61B 17/08 (2006.01)

(52) **U.S. Cl.** **606/151; 606/153**

(58) **Field of Classification Search** **606/139, 606/142, 151-153, 157, 213, 215-221; 227/175.1**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,097,018 A 10/1937 Chamberlain

(Continued)

FOREIGN PATENT DOCUMENTS

DE 3504292 7/1986

(Continued)

OTHER PUBLICATIONS

Bernal et al., "The 'Valve Racket': a new and different concept of atrioventricular valve repair," Eur. J. Cardio-thoracic Surgery 29:1026-29 (2006).

(Continued)

Primary Examiner—(Jackie) Tan-Uyen T. Ho


Assistant Examiner—Gregory A. Anderson

(74) *Attorney, Agent, or Firm*—Townsend and Townsend and Crew LLP; Jonathan Feuchtwang, Esq.

(57) **ABSTRACT**

The invention provides devices, systems and methods for tissue approximation and repair at treatment sites. The devices, systems and methods of the invention will find use in a variety of therapeutic procedures, including endovascular, minimally-invasive, and open surgical procedures, and can be used in various anatomical regions, including the abdomen, thorax, cardiovascular system, heart, intestinal tract, stomach, urinary tract, bladder, lung, and other organs, vessels, and tissues. The invention is particularly useful in those procedures requiring minimally-invasive or endovascular access to remote tissue locations, where the instruments utilized must negotiate long, narrow, and tortuous pathways to the treatment site. In addition, many of the devices and systems of the invention are adapted to be reversible and removable from the patient at any point without interference with or trauma to internal tissues.

33 Claims, 68 Drawing Sheets



Edwards Ex. 1001
IPR Petition - US 7,563,267

US 7,563,267 B2

Page 2

U.S. PATENT DOCUMENTS					
2,108,206	A	2/1938	Meeker	5,571,085	A 11/1996 Accisano, III
3,378,010	A	4/1968	Codling et al.	5,571,137	A 11/1996 Marlow et al.
3,671,979	A	6/1972	Mouloupoulos	5,571,215	A 11/1996 Sterman et al.
3,874,338	A	4/1975	Happel	5,582,611	A 12/1996 Tsuruta et al.
4,056,854	A	11/1977	Boretos et al.	5,609,598	A 3/1997 Laufer et al.
4,064,881	A	12/1977	Meredith	5,618,306	A 4/1997 Roth et al.
4,112,951	A	9/1978	Hulka et al.	5,620,452	A 4/1997 Yoon
4,297,749	A	11/1981	Davis et al.	5,626,588	A 5/1997 Sauer et al.
4,484,579	A	11/1984	Meno et al.	5,634,932	A 6/1997 Schmidt
4,498,476	A	2/1985	Cerwin et al.	5,636,634	A 6/1997 Kordis
4,809,695	A	3/1989	Gwathmey et al.	5,639,277	A 6/1997 Mariant et al.
4,917,089	A	4/1990	Sideris	5,640,955	A 6/1997 Ockuly et al.
4,944,295	A	7/1990	Gwathmey et al.	5,649,937	A 7/1997 Bito et al.
4,994,077	A	2/1991	Dobben	5,669,917	A 9/1997 Sauer et al.
5,015,249	A	5/1991	Nakao et al.	5,690,671	A 11/1997 McGurk et al.
5,042,707	A	8/1991	Taheri	5,695,504	A * 12/1997 Gifford et al. 606/153
5,047,041	A	9/1991	Samuels	5,706,824	A 1/1998 Whittier
5,049,153	A	9/1991	Nakao et al.	5,713,910	A 2/1998 Gordon et al.
5,069,679	A	12/1991	Taheri	5,715,817	A 2/1998 Stevens-Wright et al.
5,108,368	A	4/1992	Hammerslag et al.	5,716,367	A 2/1998 Koike et al.
5,125,758	A	6/1992	DeWan	5,718,725	A 2/1998 Sterman et al.
5,171,252	A	12/1992	Friedland	5,719,725	A 2/1998 Nakao
5,190,554	A	3/1993	Coddington et al.	5,722,421	A 3/1998 Francese et al.
5,195,968	A	3/1993	Lundquist et al.	5,725,556	A 3/1998 Moser et al.
5,209,756	A	5/1993	Seedhom et al.	5,741,280	A 4/1998 Fleenor
5,226,429	A	7/1993	Kuzmak	5,769,812	A 6/1998 Stevens et al.
5,226,911	A	7/1993	Chee et al.	5,769,863	A 6/1998 Garrison
5,234,437	A	8/1993	Sepetka	5,772,578	A 6/1998 Heimberger et al.
5,250,071	A	10/1993	Palermo	5,782,845	A 7/1998 Shewchuk
5,254,130	A	10/1993	Poncet et al.	5,797,927	A 8/1998 Yoon
5,261,916	A	11/1993	Engelson	5,797,960	A 8/1998 Stevens et al.
5,312,415	A	5/1994	Palermo	5,810,847	A 9/1998 Laufer et al.
5,314,424	A	5/1994	Nicholas	5,810,876	A 9/1998 Kelleher
5,318,525	A	6/1994	West et al.	5,814,029	A 9/1998 Hassett et al.
5,325,845	A	7/1994	Adair	5,820,592	A 10/1998 Hammerslag
5,332,402	A	7/1994	Teitelbaum	5,820,631	A 10/1998 Nobles
5,350,397	A	9/1994	Palermo et al.	5,823,956	A 10/1998 Roth et al.
5,359,994	A	11/1994	Krauter	5,824,065	A 10/1998 Gross
5,368,564	A	11/1994	Savage	5,827,237	A 10/1998 Macoviak et al.
5,368,601	A	11/1994	Sauer et al.	5,829,447	A 11/1998 Stevens et al.
5,383,886	A	1/1995	Kensey et al.	5,833,671	A 11/1998 Macoviak et al.
5,403,312	A	4/1995	Yates et al.	5,836,955	A 11/1998 Buelna et al.
5,403,326	A	4/1995	Harrison et al.	5,840,081	A 11/1998 Andersen et al.
5,411,552	A	5/1995	Anderson et al.	5,843,031	A 12/1998 Hermann et al.
5,417,699	A	5/1995	Klein et al.	5,855,271	A 1/1999 Eubanks et al.
5,417,700	A	5/1995	Egan	5,855,614	A 1/1999 Stevens et al.
5,423,857	A *	6/1995	Rosenman et al. 606/219	5,860,990	A 1/1999 Nobles et al.
5,423,858	A	6/1995	Bolanos et al.	5,868,733	A 2/1999 Ockuly et al.
5,423,882	A	6/1995	Jackman et al.	5,879,307	A 3/1999 Chio et al.
5,431,666	A	7/1995	Sauer et al.	5,885,271	A 3/1999 Hamilton et al.
5,437,681	A	8/1995	Meade et al.	5,891,160	A 4/1999 Williamson, IV et al.
5,450,860	A	9/1995	O'Connor	5,916,147	A 6/1999 Boury
5,456,400	A *	10/1995	Shichman et al. 227/176.1	5,928,224	A 7/1999 Laufer
5,456,684	A	10/1995	Schmidt et al.	5,944,733	A 8/1999 Engelson
5,462,527	A	10/1995	Stevens-Wright et al.	5,947,363	A 9/1999 Bolduc et al.
5,472,044	A	12/1995	Hall et al.	5,954,732	A 9/1999 Hart et al.
5,476,470	A	12/1995	Hall et al.	5,980,455	A 11/1999 Daniel et al.
5,478,309	A	12/1995	Sweezer et al.	5,989,284	A 11/1999 Laufer
5,478,353	A	12/1995	Yoon	6,019,722	A 2/2000 Spence et al.
5,487,746	A	1/1996	Yu et al.	6,022,360	A 2/2000 Reimels et al.
5,507,725	A	4/1996	Savage et al.	6,033,378	A 3/2000 Lundquist et al.
5,507,757	A	4/1996	Sauer et al.	6,036,699	A 3/2000 Andreas et al.
5,520,701	A	5/1996	Lerch	6,060,628	A 5/2000 Aoyama et al.
5,522,873	A	6/1996	Jackman et al.	6,060,629	A 5/2000 Pham et al.
5,527,313	A	6/1996	Scott et al.	6,063,106	A 5/2000 Gibson
5,527,322	A	6/1996	Klein et al.	6,066,146	A 5/2000 Carroll et al.
5,536,251	A	7/1996	Evard et al.	6,077,214	A 6/2000 Mortier et al.
5,540,705	A	7/1996	Meade et al.	6,086,600	A 7/2000 Koretenbach
5,542,949	A	8/1996	Yoon	6,099,553	A 8/2000 Hart et al.
5,554,185	A	9/1996	Block et al.	6,117,144	A 9/2000 Nobles et al.
5,562,678	A	10/1996	Meade et al.	6,123,699	A 9/2000 Webster, Jr.
				6,132,447	A 10/2000 Dorsey
				6,136,010	A 10/2000 Modesitt et al.

US 7,563,267 B2

Page 3

6,143,024	A	11/2000	Campbell et al.	2003/0050693	A1	3/2003	Quijano et al.
6,162,233	A	12/2000	Williamson, IV et al.	2003/0069570	A1	4/2003	Witzel et al.
6,165,183	A	12/2000	Kuehn et al.	2003/0069593	A1	4/2003	Tremulis et al.
6,171,320	B1	1/2001	Monassevitch	2003/0069636	A1	4/2003	Solem et al.
6,187,003	B1	2/2001	Buysse et al.	2003/0074012	A1	4/2003	Nguyen et al.
6,190,408	B1	2/2001	Melvin	2003/0078654	A1	4/2003	Taylor et al.
6,203,553	B1	3/2001	Robertson et al.	2003/0083742	A1	5/2003	Spence et al.
6,206,893	B1	3/2001	Klein et al.	2003/0105519	A1	6/2003	Fasol et al.
6,210,432	B1	4/2001	Solem et al.	2003/0120341	A1	6/2003	Shennib et al.
6,245,079	B1	6/2001	Nobles et al.	2003/0130669	A1	7/2003	Damarati
6,267,746	B1	7/2001	Bumbalough	2003/0130730	A1	7/2003	Cohn et al.
6,269,819	B1	8/2001	Oz et al.	2003/0167071	A1	9/2003	Martin et al.
6,299,637	B1	10/2001	Shaolian et al.	2003/0187467	A1	10/2003	Schreck
6,306,133	B1	10/2001	Tu et al.	2003/0195562	A1	10/2003	Collier et al.
6,312,447	B1	11/2001	Grimes	2003/0208231	A1	11/2003	Williamson, IV et al.
6,319,250	B1	11/2001	Falwell et al.	2003/0229395	A1	12/2003	Cox
6,322,559	B1	11/2001	Daulton et al.	2003/0233038	A1	12/2003	Hassett
6,332,893	B1	12/2001	Mortier et al.	2004/0003819	A1	1/2004	St. Goar et al.
6,355,030	B1	3/2002	Aldrich et al.	2004/0019377	A1	1/2004	Taylor et al.
6,402,781	B1	6/2002	Langberg et al.	2004/0019378	A1	1/2004	Hlavka et al.
6,406,420	B1	6/2002	McCarthy et al.	2004/0024414	A1	2/2004	Downing
6,461,366	B1	10/2002	Seguin	2004/0030382	A1	2/2004	St. Goar et al.
6,464,707	B1	10/2002	Bjerkén	2004/0039442	A1	2/2004	St. Goar et al.
6,482,224	B1	11/2002	Michler et al.	2004/0039443	A1	2/2004	Solem et al.
6,533,796	B1	3/2003	Sauer et al.	2004/0044350	A1	3/2004	Martin et al.
6,537,314	B2	3/2003	Langberg et al.	2004/0049207	A1	3/2004	Goldfarb et al.
6,551,331	B2	4/2003	Nobles et al.	2004/0049211	A1	3/2004	Tremulis et al.
6,562,037	B2	5/2003	Paton et al.	2004/0073302	A1	4/2004	Rourke et al.
6,562,052	B2	5/2003	Nobles et al.	2004/0078053	A1	4/2004	Berg et al.
6,575,971	B2	6/2003	Hauck et al.	2004/0087975	A1	5/2004	Lucatero et al.
6,585,761	B2	7/2003	Taheri	2004/0088047	A1	5/2004	Spence et al.
6,619,291	B2	9/2003	Hlavka et al.	2004/0092962	A1	5/2004	Thornton et al.
6,626,899	B2	9/2003	Houser et al.	2004/0097878	A1	5/2004	Svanidze et al.
6,626,930	B1	9/2003	Allen et al.	2004/0106989	A1	6/2004	Wilson et al.
6,629,534	B1	10/2003	St. Goar et al.	2004/0111099	A1	6/2004	Nguyen et al.
6,641,592	B1	11/2003	Sauer et al.	2004/0122448	A1	6/2004	Levine
6,656,221	B2	12/2003	Taylor et al.	2004/0127981	A1	7/2004	Rahdert et al.
6,689,164	B1	2/2004	Seguin	2004/0127982	A1	7/2004	Machold et al.
6,695,866	B1	2/2004	Kuehn et al.	2004/0127983	A1	7/2004	Mortier et al.
6,701,929	B2	3/2004	Hussein	2004/0133063	A1	7/2004	McCarthy et al.
6,702,825	B2	3/2004	Frazier et al.	2004/0133082	A1	7/2004	Pal et al.
6,702,826	B2	3/2004	Liddicoat et al.	2004/0133192	A1	7/2004	Houser et al.
6,709,382	B1	3/2004	Horner	2004/0133220	A1	7/2004	Lashinski et al.
6,709,456	B2	3/2004	Langberg et al.	2004/0133240	A1	7/2004	Adams et al.
6,723,038	B1	4/2004	Schroeder et al.	2004/0133273	A1	7/2004	Cox
6,726,716	B2	4/2004	Marquez	2004/0138744	A1	7/2004	Lashinski et al.
6,740,107	B2	5/2004	Loeb et al.	2004/0138745	A1	7/2004	Macoviak et al.
6,746,471	B2	6/2004	Mortier et al.	2004/0148021	A1	7/2004	Cartledge et al.
6,752,813	B2	6/2004	Goldfarb et al.	2004/0152847	A1	8/2004	Schroeder et al.
6,755,777	B2	6/2004	Schweich et al.	2004/0153144	A1	8/2004	Seguin
6,764,510	B2	7/2004	Vidlund et al.	2004/0158123	A1	8/2004	Jayaraman
6,767,349	B2	7/2004	Ouchi	2004/0162610	A1	8/2004	Liska et al.
6,770,083	B2	8/2004	Seguin	2004/0167539	A1	8/2004	Kuehn et al.
6,797,001	B2	9/2004	Mathis et al.	2004/0193191	A1	9/2004	Starksen et al.
6,797,002	B2	9/2004	Spence et al.	2004/0215339	A1	10/2004	Drasler et al.
6,875,224	B2	4/2005	Grimes	2004/0220593	A1	11/2004	Greenhalgh
6,945,978	B1	9/2005	Hyde	2004/0220657	A1	11/2004	Nieminen et al.
6,949,122	B2	9/2005	Adams et al.	2004/0225300	A1	11/2004	Goldfarb et al.
6,966,914	B2	11/2005	Abe	2004/0236354	A1	11/2004	Seguin
7,011,669	B2	3/2006	Kimblad	2004/0243229	A1	12/2004	Vidlund et al.
7,112,207	B2	9/2006	Allen et al.	2004/0249452	A1	12/2004	Adams et al.
2001/0037084	A1	11/2001	Nardeo	2004/0249453	A1	12/2004	Cartledge et al.
2002/0013571	A1	1/2002	Goldfarb et al.	2005/0004583	A1	1/2005	Oz et al.
2002/0035361	A1	3/2002	Houser et al.	2005/0004668	A1	1/2005	Aklog et al.
2002/0087148	A1	7/2002	Brock et al.	2005/0021056	A1	1/2005	St. Goar et al.
2002/0087169	A1	7/2002	Brock et al.	2005/0021057	A1	1/2005	St. Goar et al.
2002/0107534	A1	8/2002	Schaefer et al.	2005/0033446	A1	2/2005	Deem et al.
2002/0147456	A1	10/2002	Diduch et al.	2005/0038508	A1	2/2005	Gabbay
2002/0158528	A1	10/2002	Hlavka et al.	2005/0049698	A1	3/2005	Bolling et al.
2002/0161378	A1	10/2002	Downing	2005/0055089	A1	3/2005	Macoviak et al.
2002/0169360	A1	11/2002	Taylor et al.	2005/0059351	A1	3/2005	Cauwels et al.
2002/0183766	A1	12/2002	Seguin	2005/0149014	A1	7/2005	Hauck et al.
2002/0183835	A1	12/2002	Taylor et al.	2005/0159810	A1	7/2005	Filsoofi

2005/0197694	A1	9/2005	Pai et al.
2005/0197695	A1	9/2005	Stacchino et al.
2005/0216039	A1	9/2005	Lederman
2005/0228422	A1	10/2005	Machold et al.
2005/0228495	A1	10/2005	Macoviak
2005/0251001	A1	11/2005	Hassett
2005/0267493	A1	12/2005	Schreck et al.
2005/0273160	A1	12/2005	Lashinski et al.
2006/0004247	A1	1/2006	Kute et al.
2006/0020275	A1	1/2006	Goldfarb et al.
2006/0030866	A1	2/2006	Schreck
2006/0030867	A1	2/2006	Zadno
2006/0030885	A1	2/2006	Hyde
2006/0058871	A1	3/2006	Zakay et al.
2006/0064115	A1	3/2006	Allen et al.
2006/0064116	A1	3/2006	Allen et al.
2006/0064118	A1	3/2006	Kimblad
2006/0089671	A1	4/2006	Goldfarb et al.
2006/0195012	A1	8/2006	Mortier et al.
2006/0252984	A1	11/2006	Rahdert et al.

FOREIGN PATENT DOCUMENTS

EP	179562	7/1989
EP	0558031	9/1993
EP	684012	A2 2/1995
EP	0727239	8/1996
GB	1598111	9/1981
GB	2151142	7/1985
JP	11-89937	6/1999
WO	WO 81/00668	3/1981
WO	WO 91/01689	2/1991
WO	WO 91/18881	12/1991
WO	WO 92/12690	8/1992
WO	WO 94/18881	9/1994
WO	WO 94/18893	9/1994
WO	WO 97/39688	10/1997
WO	WO 98/07375	2/1998
WO	WO 98/30153	7/1998
WO	WO 98/35638	8/1998
WO	WO 99/00059	1/1999
WO	WO 99/01377	1/1999
WO	WO 99/07354	2/1999
WO	WO 00/03759	1/2000
WO	WO 00/60995	10/2000
WO	WO 01/26557	4/2001
WO	WO 01/26588	4/2001
WO	WO 01/28432	4/2001
WO	WO 01/54618	8/2001
WO	WO 02/03892	1/2002
WO	WO 03/001893	1/2003
WO	WO 03/020179	3/2003
WO	WO 03/028558	4/2003
WO	WO 03/037171	5/2003
WO	WO 03/047467	6/2003
WO	WO 03/049619	6/2003
WO	WO 03/073910	9/2003
WO	WO 03/073913	9/2003
WO	WO 00/59382	A1 10/2003
WO	WO 03/105667	A3 12/2003
WO	WO 2004/004607	1/2004
WO	WO 2004/012583	2/2004
WO	WO 2004/012789	2/2004
WO	WO 2004/019811	3/2004
WO	WO 2004/082538	A2 3/2004
WO	WO 2004/030570	4/2004
WO	WO 2004/037317	5/2004
WO	WO 2004/045370	6/2004
WO	WO 2004/045378	A2 6/2004
WO	WO 2004/045463	6/2004
WO	WO 2004/047679	6/2004
WO	WO 2004/062725	7/2004
WO	WO 2004/082523	A2 9/2004

WO	WO 2004/093730	11/2004
WO	WO 2004/112585	12/2004
WO	WO 2004/112651	12/2004
WO	WO 2005/002424	1/2005
WO	WO 2005/018507	3/2005
WO	WO 2005/027797	A1 3/2005
WO	WO 2005/032421	A2 4/2005
WO	WO 2005/062931	A2 7/2005
WO	WO 2005/112792	12/2005
WO	WO 2006/105008	10/2006
WO	WO 2006/105009	10/2006
WO	WO 2006/115875	11/2006
WO	WO 2006/115876	11/2006

OTHER PUBLICATIONS

Derwent citing German language patent EP 684012 published Nov. 12, 1995 for: "Thread for constructing surgical seam has flexible section with two ends, with lower fastening part on thread first end having hollow cylinder with continuous hole through which surgical needle threads" 2 pgs.

Derwent citing Japanese language patent JP 11089937 published Jun. 4, 1999 for: "Catheter for mitral regurgitation test—includes jet nozzles provided on rear side of large diametered spindle shaped portion attached to end of narrow diametered tube" 1 pg.

Filsooufi et al., "Restoring Optimal Surface of Coaptation With a Mini Leaflet Prosthesis: A New Surgical Concept for the Correction of Mitral Valve Prolapse," Int'l. Soc. for Minimally Invasive Cardiothoracic Surgery 1(4):186-87 (2006).

Langer et al., "Posterior mitral leaflet extensions: An adjunctive repair option for ischemic mitral regurgitation?," J. Thorac. Cardiovasc. Surg. 131:868-77 (2006).

Abe et al., "De Vega's annuloplasty for acquired tricuspid disease: Early and late results in 110 patients" Ann. Thorac. Surg. (1989) 48:670-676.

Abe et al., "Updated: De Vega's annuloplasty for acquired tricuspid disease: Early and late results in 110 patients" Ann. Thorac. Surg. (1996) 62:1876-1877.

Agricola et al., "Mitral valve reserve in double orifice technique: an exercise echocardiographic study," Journal of Heart Valve Disease, (2002)11(5):637-643.

Alfieri et al., "An effective technique to correct anterior mitral leaflet prolapse," J Card Sug, (1999) 14(6):468-470.

Alfieri et al., "Novel suture device for beating heart mitral leaflet approximation," Annals of Thoracic Surgery, (2002)74:1488-1493.

Alfieri et al., "The double orifice technique in mitral valve repair: a simple solution for complex problems," Journal of Thoracic Cardiovascular Surgery, (2001)122:674-681.

Alfieri et al., "The edge to edge technique," The European Association for Cardio-Thoracic Surgery 14th Annual Meeting, (Oct. 7-11, 2000), Book of Proceedings.

Alfieri, "The edge-to-edge repair of the mitral valve," [Abstract] Annual NewEra Cardiac Care: Innovation & Tecnology, Heart Surgery Forum, (2003) p. 103.

Alvarez et al., "Repairing the degenerative mitral valve: Ten- to fifteen-year follow-up" J. Thorac. Cardiovasc. Surg., (1996) 112:238-247.

Arisi et al., "Mitral valve repair with Alfieri technique in mitral regurgitation of diverse etiology: early echocardiographic results," Circulation Supplement II, (2001) 104(17):3240.

Bach et al., "Early improvement in congestive heart failure after correction of secondary mitral regurgitation in end-stage cardiomyopathy," Am. Heart J., (1995) 129:1165-1170.

Bach et al., "Improvement following correction of secondary mitral regurgitation in end-stage cardiomyopathy with mitral annuloplasty" Am. J. Cardiol., (1996) 78:966-969.

Bailey, "Surgery of the Heart," Chapter 20, (1995) pp. 686-737.

Bhudia, S., "Edge-to-edge mitral repair: a versatile mitral repair technique," The Cleveland clinic Foundation, (date unknown).

Bolling et al., "Surgery for acquired heart disease," (1995) 109:676-683.

- Borghetti et al., "Preliminary observations on haemodynamics during physiological stress conditions following 'double-orifice' mitral valve repair, *European Journal of Cardio-thoracic Surgery*, (Apr. 18, 2001) 20:262-269.
- Castedo, "Edge-to-edge tricuspid repair for redeveloped valve incompetence after DeVega's annuloplasty," *Ann Thora Surg.* (2003) 75:605-6.
- Dec et al., "Idiopathic dilated cardiomyopathy," *N. Engl. J. Med.*, (1994) 331:1564-1575.
- Dottori et al., "Echocardiographic imaging of the Alfieri type mitral valve repair," *Ital Heart J.* (2001) 2(4):319-320.
- Downing et al., "Beating heart mitral valve surgery: Preliminary model and methodology," *Journal of Thoracic and Cardiovascular Surgery*, (2002) 123(6):1141-1146.
- Falk et al., "Computer-enhanced mitral valve surgery: toward a total endoscopic procedure," *Seminars in thoracic and cardiovascular surgery*, (1999) 11(3):224-249.
- Fucci et al., "Improved results with mitral valve repair using new surgical techniques," *Eur J Cardio-thorac Surg.* 1995; 9:621-627.
- Fundaro et al., "Chordal plication and free edge remodeling for mitral anterior leaflet prolapse repair: 8-year follow-up," *Annals of Thoracic Surgery*, (2001) 72:1515-1519.
- Garcia-Rinaldi et al., "Left ventricular volume reduction and reconstruction is ischemic cardiomyopathy," *Journal of Cardiac Surgery*, (1999) 14:199-210.
- Gateliene, "Early and postoperative results of metal and tricuspid valve insufficiency surgical treatment using edge-to-edge central coaptation procedure," (2002) 38 Suppl 2:172-5.
- Gatti et al., "The edge to edge technique as a trick to rescue an imperfect mitral valve repair," *Eur J Cardiothorac Surg.* (2002) 22(5):817-20.
- Gillinov et al., "Is minimally invasive heart valve surgery a paradigm for the future?" *Current Cardiology Reports*, (1999) 1:318-322.
- Gundry, "Facile mitral valve repair utilizing leaflet edge approximation: midterm results of the Alfieri figure of eight repair," Presented at the Meeting of The Western Thoracic Surgical Association, (1999).
- Ikeda et al., "Batista's operation with coronary artery bypass grafting and mitral valve plasty for ischemic dilated cardiomyopathy," *The Japanese Journal of Thoracic and Cardiovascular Surgery*, (2000) 48:746-749.
- Izzat et al., "Early experience with partial left ventriculectomy in the Asia-Pacific Region," *Annals of Thoracic Surgery*, (1999) 67:1703-1707.
- Källner et al., "Transaortic approach for the Alfieri Stitch," *Ann Thorac Surg.* (2001) 71:378-380.
- Kameda et al., "Annuloplasty for severe mitral regurgitation due to dilated cardiomyopathy," *Am. Thorac. Surg.* (1996) 61:1829-1832.
- Kavama et al., "Transaortic repair of mitral regurgitation," Presented at the third annual New Era Cardiac Care conference, San Diego, CA, (Jan. 13-16, 2000) <http://www.hsforum.com/vol3/issue1/2000-2389print.html>.
- Kaza et al., "Ventricular reconstruction results in improved left ventricular function and amelioration of mitral insufficiency," *Annals of Surgery*, (2002) 235(6):828-832.
- Khan et al., "Blade atrial septostomy: Experience with the first 50 procedures" *Cathet. Cardiovasc. Diagn.* (1991) 23:257-262.
- Kherani, The edge-to-edge mitral valve repair: the Columbia Presbyterian experience, Columbia University, (date unknown).
- Konertz et al., "Results after partial left ventriculectomy in a European heart failure population," *Journal of Cardiac Surgery*, (1999) 14(2):129-135.
- Kron et al., "Surgical relocation of the posterior papillary muscle in chronic ischemic mitral regurgitation," *Annals. of Thoracic Surgery*, (2002) 74:600-601.
- Krüger et al., "Edge to edge technique in complex mitral valve repair," *Thorac Cardiovasc Surg.* (2000) Thema: Poster, http://www.thieme.de/thoracic/abstracts/abstracts/p_73.html.
- Lorusso et al., "Double-Orifice technique to repair extensive mitral valve excision following acute endocarditis," *J Card Surg.* (1998) 13:24-26.
- Lorusso et al., "The double-orifice technique for mitral valve construction: predictors of postoperative outcome," *Eur J. Cardiothorac Surg.* (2001) 20(3):583-589.
- Maisano et al., "The double orifice repair for Barlow Disease: a simple solution for a complex repair," *Supplement I Circulation*, (1999) 100(18):1-94.
- Maisano et al., "The double orifice technique as a standardized approach to treat mitral regurgitation due to severe myxomatous disease: surgical technique," *European Journal of Cardiothoracic Surgery*, (2000) 17:201-215.
- Maisano et al., "The hemodynamic effects of double-orifice valve repair for mitral regurgitation: a 3D computational model," *European Journal of Cardio-thoracic Surgery*, (1999) 15:419-425.
- Maisano et al., "Valve repair for traumatic tricuspid regurgitation," *Eur J. Cardio-thorac Surg.* (1996) 10:867-873.
- Maisano et al., "The edge-to-edge technique: A simplified method to correct mitral insufficiency" *Eur. J. Cardiothorac. Surg.* (1998) 13:240-246.
- Mantovani et al., "Edge-to-edge repair of congenital familial tricuspid regurgitation: case report," *J. Heart Valve Dis.*, (2000) 9 (5):641-643.
- McCarthy et al., "Tricuspid valve repair with the Cosgrove-Edwards annuloplasty system" *Am. Thorac. Surg.*, (1997) 64:267-268.
- McCarthy et al., "Partial left ventriculectomy and mitral valve repair for end-stage congestive heart failure," *European Journal of Cardio-thoracic Surgery*, (1998) 13:337-343.
- Moalnie et al., Correction of traumatic tricuspid regurgitation using the double orifice technique, *Annals of Thoracic Surgery*, (2002) 73:963-965.
- Morales et al., "Development of an off bypass mitral valve repair, *The Heart Surgery Forum #1999-4963*," (1999) 2(2):115-120.
- Nakanishi et al., "Early outcome with the Alfieri mitral valve repair," *J Cardiol.* (2001) 37(5):263-266, (Abstract in English; Article in Japanese.).
- Nielsen et al., "The edge-to-edge mitral repair: tension on the approximating suture and leaflet deformation during acute ischemic mitral regurgitation in the ovine heart," *Circulation*, (2001) 104[suppl I]:I-29-I-35.
- Osawa et al., "Partial left ventriculectomy in a 3 year old boy with dilated cardiomyopathy," *Japanese Journal of Throacic and Cardiovascular Surgery*, (2000) 48(9):590-593.
- Park et al., "Clinical use of a blade atrial septostomy" *Circulation* (1978) 58:600-608.
- Pnivera et al., "Mitral Valve Repair: Clinical Outcome and Pathology," *Circulation*, (2002) 106:173.
- Redaelli, et al., A computational study of the hemodynamics after 'edge-to-edge' mitral valve repair, *Journal of Biomechanical Engineering*, (2001) 123:565-570.
- Reul, "Mitral valve reconstruction for mitral insufficiency," *Progress in Cardiovascular Diseases*, (1997) vol. XXXIX, No. 6, pp. 567-599.
- Ricchi et al., "Linear segmental annuloplasty for mitral valve repair" *Ann. Thorac. Surg.*, (1997) 63:1805-1806.
- Tager et al., "Long-term follow-up of Rheumatic patients undergoing left-sided valve replacement with tricuspid annuloplasty—Validity of preoperative echocardiographic criteria in the decision to perform tricuspid annuloplasty" *Am. J. Cardiol.*, (1998) 81:1013-1016.
- Tamura et al., Edge to edge repair for mitral regurgitation in a patient with chronic hemodialysis: report of a case, *Kyobu Geka*, (2001) 54(9):788-790.
- Timek, "Edge-to-edge mitral repair: gradients and three-dimensional annular dynamics in vivo during inotropic stimulation," *European Journal of Cardio-thoracic Surgery*, (2001) 19:431-437.
- Timek, "Edge-to-edge mitral valve repair without annuloplasty ring in acute ischemic mitral regurgitation," [Abstract] *Clinical Science*, Abstracts from Scientific Sessions, (2002) II-461.
- Totaro, "Mitral valve repair for isolated prolapse of the anterior leaflet: an 11-year follow-up," *European Journal of Cardio-thoracic Surgery*, (1999) 15:119-126.
- Uchida et al., "Percutaneous cardiomyotomy and valvotomy with angioscopic guidance," *Am. Heart J.*, (1991) 121:1221-1224.
- Umaña et al., "'Bow-tie' mitral valve repair successfully addresses subvalvular dysfunction in ischemic mitral regurgitation," (1997) *Surgical Forum* pp. 279-280.
- Umaña, "'Bow-Tie' mitral valve repair: an adjuvant technique for ischemic mitral regurgitation," *Ann Thora Surg.* (1998) 66:1640-6.
- Votta et al., "3 D computational analysis of the stress distribution on the leaflets after edge to edge repair of mitral regurgitation," *Journal of Heart Valve Disease*, (2002) 11:810-822.

* cited by examiner




FIG. 1




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D




FIG. 8A




FIG. 8B




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14




FIG. 15




FIG. 16




FIG. 17A




FIG. 17B




FIG. 17C




FIG. 18






FIG. 19






FIG. 22A




FIG. 22B




FIG. 23




FIG. 24A







FIG. 24B






FIG. 27




FIG. 28




FIG. 29








FIG. 30








FIG. 35




FIG. 36




FIG. 37




FIG. 38




FIG. 39




FIG. 40A




FIG. 40B




FIG. 40C




FIG. 40D




FIG. 41




FIG. 42




FIG. 43A




FIG. 43B




FIG. 43C




FIG. 44A




FIG. 44B

FIG. 45





FIG. 46




FIG. 47





FIG. 48






FIG. 50




FIG. 51




FIG. 52




FIG. 52A




FIG. 52B




FIG. 53A




FIG. 53B




FIG. 53C




FIG. 54A




FIG. 54B




FIG. 55




FIG. 56




FIG. 57




FIG. 57A




FIG. 58A




FIG. 58B




FIG. 59




FIG. 59A




FIG. 59B




FIG. 60




FIG. 61A






FIG. 61B






FIG. 62A




FIG. 62B




FIG. 63A




FIG. 63B




FIG. 63C




FIG. 63D




FIG. 64A




FIG. 64B




FIG. 64C




FIG. 64D




FIG. 64E







FIG. 65F

FIG. 65G

FIG. 65H






FIG. 65G




FIG. 65H




FIG. 65I




FIG. 66A




FIG. 66B




FIG. 66C




FIG. 67A




FIG. 67B




FIG. 68




FIG. 69






FIG. 70






FIG. 73A




FIG. 73B










FIG. 73C







FIG. 75







FIG. 76A






FIG. 77






FIG. 78








FIG. 81

1

FIXATION DEVICE AND METHODS FOR ENGAGING TISSUE

CROSS-REFERENCES TO RELATED APPLICATIONS

This application is a continuation-in-part of, and claims the benefit of priority from co-pending U.S. patent application Ser. No. 09/894,463, filed Jun. 27, 2001, which is a continuation-in-part of co-pending U.S. patent application Ser. No. 09/544,930, filed Apr. 7, 2000, which claims the benefit of prior Provisional Application No. 60/128,690, filed on Apr. 9, 1999 under 37 CFR §1.78(a), the full disclosures of which are hereby incorporated herein by reference. This application is related to U.S. patent application Ser. No. 10/441,753, U.S. patent application Ser. No. 10/441,508, and U.S. patent application Ser. No. 10/441,687, all of which are filed on the same day as the instant application, the full disclosures of which are incorporated herein by reference.

STATEMENT AS TO RIGHTS TO INVENTIONS MADE UNDER FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

NOT APPLICABLE

REFERENCE TO A "SEQUENCE LISTING," A TABLE, OR A COMPUTER PROGRAM LISTING APPENDIX SUBMITTED ON A COMPACT DISK

NOT APPLICABLE

BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates generally to medical methods, devices, and systems. In particular, the present invention relates to methods, devices, and systems for the endovascular, percutaneous or minimally invasive surgical treatment of bodily tissues, such as tissue approximation or valve repair. More particularly, the present invention relates to repair of valves of the heart and venous valves.

Surgical repair of bodily tissues often involves tissue approximation and fastening of such tissues in the approximated arrangement. When repairing valves, tissue approximation includes coapting the leaflets of the valves in a therapeutic arrangement which may then be maintained by fastening or fixing the leaflets. Such coaptation can be used to treat regurgitation which most commonly occurs in the mitral valve.

Mitral valve regurgitation is characterized by retrograde flow from the left ventricle of a heart through an incompetent mitral valve into the left atrium. During a normal cycle of heart contraction (systole), the mitral valve acts as a check valve to prevent flow of oxygenated blood back into the left atrium. In this way, the oxygenated blood is pumped into the aorta through the aortic valve. Regurgitation of the valve can significantly decrease the pumping efficiency of the heart, placing the patient at risk of severe, progressive heart failure.

Mitral valve regurgitation can result from a number of different mechanical defects in the mitral valve or the left ventricular wall. The valve leaflets, the valve chordae which connect the leaflets to the papillary muscles, the papillary muscles or the left ventricular wall may be damaged or otherwise dysfunctional. Commonly, the valve annulus may be damaged, dilated, or weakened limiting the ability of the mitral valve to close adequately against the high pressures of the left ventricle.

2

The most common treatments for mitral valve regurgitation rely on valve replacement or repair including leaflet and annulus remodeling, the latter generally referred to as valve annuloplasty. A recent technique for mitral valve repair which relies on suturing adjacent segments of the opposed valve leaflets together is referred to as the "bow-tie" or "edge-to-edge" technique. While all these techniques can be very effective, they usually rely on open heart surgery where the patient's chest is opened, typically via a sternotomy, and the patient placed on cardiopulmonary bypass. The need to both open the chest and place the patient on bypass is traumatic and has associated high mortality and morbidity.

For these reasons, it would be desirable to provide alternative and additional methods, devices, and systems for performing the repair of mitral and other cardiac valves. Such methods, devices, and systems should preferably not require open chest access and be capable of being performed either endovascularly, i.e., using devices which are advanced to the heart from a point in the patient's vasculature remote from the heart or by a minimally invasive approach. Further, such devices and systems should provide features which allow repositioning and optional removal of a fixation device prior to fixation to ensure optimal placement. Still more preferably, the methods, devices, and systems would be useful for repair of tissues in the body other than heart valves. At least some of these objectives will be met by the inventions described hereinbelow.

2. Description of the Background Art

Minimally invasive and percutaneous techniques for coapting and modifying mitral valve leaflets to treat mitral valve regurgitation are described in PCT Publication Nos. WO 98/35638; WO 99/00059; WO 99/01377; and WO 00/03759.

Maisano et al. (1998) *Eur. J. Cardiothorac. Surg.* 13:240-246; Fucci et al. (1995) *Eur. J. Cardiothorac. Surg.* 9:621-627; and Umana et al. (1998) *Ann. Thorac. Surg.* 66:1640-1646, describe open surgical procedures for performing "edge-to-edge" or "bow-tie" mitral valve repair where edges of the opposed valve leaflets are sutured together to lessen regurgitation. Dec and Fuster (1994) *N. Engl. J. Med.* 331:1564-1575 and Alvarez et al. (1996) *J. Thorac. Cardiovasc. Surg.* 112:238-247 are review articles discussing the nature of and treatments for dilated cardiomyopathy.

Mitral valve annuloplasty is described in the following publications. Bach and Bolling (1996) *Am. J. Cardiol.* 78:966-969; Kameda et al. (1996) *Ann. Thorac. Surg.* 61:1829-1832; Bach and Bolling (1995) *Am. Heart J.* 129:1165-1170; and Bolling et al. (1995) 109:676-683. Linear segmental annuloplasty for mitral valve repair is described in Ricchi et al. (1997) *Ann. Thorac. Surg.* 63:1805-1806. Tricuspid valve annuloplasty is described in McCarthy and Cosgrove (1997) *Ann. Thorac. Surg.* 64:267-268; Tager et al. (1998) *Am. J. Cardiol.* 81:1013-1016; and Abe et al. (1989) *Ann. Thorac. Surg.* 48:670-676.

Percutaneous transluminal cardiac repair procedures are described in Park et al. (1978) *Circulation* 58:600-608; Uchida et al. (1991) *Am. Heart J.* 121: 1221-1224; and Ali Khan et al. (1991) *Cathet. Cardiovasc. Diagn.* 23:257-262.

Endovascular cardiac valve replacement is described in U.S. Pat. Nos. 5,840,081; 5,411,552; 5,554,185; 5,332,402; 4,994,077; and 4,056,854. See also U.S. Pat. No. 3,671,979 which describes a catheter for temporary placement of an artificial heart valve.

Other percutaneous and endovascular cardiac repair procedures are described in U.S. Pat. Nos. 4,917,089; 4,484,579; and 3,874,338; and PCT Publication No. WO 91/01689.

3

Thoroscopic and other minimally invasive heart valve repair and replacement procedures are described in U.S. Pat. Nos. 5,855,614; 5,829,447; 5,823,956; 5,797,960; 5,769,812; and 5,718,725.

BRIEF SUMMARY OF THE INVENTION

The invention provides devices, systems and methods for tissue approximation and repair at treatment sites. The devices, systems and methods of the invention will find use in a variety of therapeutic procedures, including endovascular, minimally-invasive, and open surgical procedures, and can be used in various anatomical regions, including the abdomen, thorax, cardiovascular system, heart, intestinal tract, stomach, urinary tract, bladder, lung, and other organs, vessels, and tissues. The invention is particularly useful in those procedures requiring minimally-invasive or endovascular access to remote tissue locations, where the instruments utilized must negotiate long, narrow, and tortuous pathways to the treatment site. In addition, many of the devices and systems of the invention are adapted to be reversible and removable from the patient at any point without interference with or trauma to internal tissues.

In preferred embodiments, the devices, systems and methods of the invention are adapted for fixation of tissue at a treatment site. Exemplary tissue fixation applications include cardiac valve repair, septal defect repair, vascular ligation and clamping, laceration repair and wound closure, but the invention may find use in a wide variety of tissue approximation and repair procedures. In a particularly preferred embodiment, the devices, systems and methods of the invention are adapted for repair of cardiac valves, and particularly the mitral valve, as a therapy for regurgitation. The invention enables two or more valve leaflets to be coapted using an "edge-to-edge" or "bow-tie" technique to reduce regurgitation, yet does not require open surgery through the chest and heart wall as in conventional approaches. Using the devices, systems and methods of the invention, the mitral valve can be accessed from a remote surgical or vascular access point and the two valve leaflets may be coapted using endovascular or minimally invasive approaches. While less preferred, in some circumstances the invention may also find application in open surgical approaches as well. According to the invention, the mitral valve may be approached either from the atrial side (antegrade approach) or the ventricular side (retrograde approach), and either through blood vessels or through the heart wall.

The devices, systems and methods of the invention are centered on variety of devices which may be used individually or in a variety of combinations to form interventional systems. In preferred embodiments, the interventional system includes a multi-catheter guiding system, a delivery catheter and an interventional device. Each of these components will be discussed herein.

In an exemplary embodiment, the invention provides a fixation device having a pair of distal elements (or fixation elements), each distal element having a free end and an engagement surface for engaging the tissue, wherein the distal elements are moveable between a first position for capturing the tissue and a second position for fixing the tissue. Preferably, the engagement surfaces are spaced apart in the first position and are closer together and generally face toward each other in the second position. The fixation device is preferably delivered to a target location in a patient's body by a delivery catheter having an elongated shaft, a proximal end and a distal end, the delivery catheter being configured to be positioned at the target location from a remote access point

4

such as a vascular puncture or cut-down or a surgical penetration. In a preferred embodiment, the target location is a valve in the heart.

The fixation device is preferably delivered with the distal elements in a delivery position configured to minimize the profile of the device. When approaching the mitral valve from the atrial side, some embodiments of the fixation device allow the device to be delivered with the free ends of the distal elements pointing in a generally proximal direction forming an angle of less than about 90°, preferably less than about 20°, relative to the longitudinal axis of the delivery device shaft. In this position the engagement surfaces are facing generally toward each other, being disposed at an angle of less than about 180°, and preferably less than about 40°, relative to each other. For ventricular approaches, in the delivery position the free ends of the distal elements are pointing in a generally distal direction and form an angle of less than about 90°, preferably less than about 20°, relative to the longitudinal axis of the delivery device shaft. In this position, the engagement surfaces are facing generally toward each other, usually being disposed at an angle of less than about 180°, and preferably less than about 90°, relative to each other. Alternatively, in some ventricular approaches, it may be preferred to have the free ends of the fixation elements pointing in a generally proximal direction and the engagement surfaces facing away from each other in the delivery position.

In order to provide for the reversibility and removability of the devices and systems of the invention, the distal elements preferably are movable to an inverted position that minimizes entanglement and interferences with surrounding tissues should the device be desired to be withdrawn. In mitral repair applications, this is particularly important due to the presence of chordae tendoneae, valve leaflets and other tissues with which devices may become entangled. For approaches from the atrial side of the mitral valve, in the inverted position, the free ends will be pointing in a generally distal direction relative to the catheter shaft and the engagement surfaces will be facing generally away from each other, usually being disposed at an angle of more than about 180°, and preferably more than 270°, relative to each other. For ventricular approaches to the valve, in the inverted position the free ends will be pointing in a distal direction relative to the catheter shaft and the engagement surfaces will be facing generally toward each other, usually being disposed at an angle of less than about 180°, and preferably less than 90°, relative to each other.

In the open position the engagement surfaces of the distal elements preferably form an angle of up to 180° relative to each other so as to maximize the area in which to capture the valve leaflets or other target tissue. The distal elements are preferably movable to a closed position in which the engagement surfaces engage each other or form an angle as small as 0° relative to each other. The distal elements are configured to be adjusted to and left permanently in any of various positions between the open and closed positions to allow for fixation of tissues of various thickness, geometry, and spacing.

In a preferred embodiment, the fixation device of the invention will further include at least one proximal element (or gripping element). Each proximal element and distal element will be movable relative to each other and configured to capture tissue between the proximal element and the engagement surface of the distal element. Preferably, the distal elements and proximal elements are independently movable but in some embodiments may be movable with the same mechanism. The proximal element may be preferably biased toward the engagement surface of the fixation element to provide a compressive force against tissue captured therebetween.

5

In another aspect, the invention provides a fixation device for engaging tissue comprising a coupling member configured for coupling a catheter and a pair of distal elements connected to the coupling member, each distal element having an engagement surface for engaging the tissue. The distal elements are moveable between an open position wherein the distal elements extend radially outwardly facing the engagement surfaces toward a first direction, and an inverted position wherein the distal elements have rotated away from the first direction facing the engagement surfaces radially outwardly.

In a further aspect, the distal elements of the invention are adapted to receive a suture passed through the target tissue. For example, implant pledgets may be detachably mounted to the distal elements so as to be positionable against a surface of tissue engaged by the distal elements. A suture may then be passed through the tissue and implant pledget, which are supported by the distal element. The implant pledgets are then detached from the distal elements, which may be withdrawn from the site, and the suture is tensioned and secured to the target tissue. The delivery catheter, in this embodiment, will further include a movable fixation tool or penetration element for penetrating the target tissue and the implant pledget. A suture is coupled to the penetration element and preferably an anchor is attached to the suture. The penetration element is movable relative to the catheter to penetrate the target tissue and the implant pledget, bringing with it the suture and anchor. The anchor is configured to deploy into an expanded configuration so as to securely engage the implant pledget opposite the target tissue, retaining the suture therein. For the mitral valve, an implant pledget and suture may be similarly deployed in both leaflets, and the sutures secured to one another to coapt the leaflets. Thus, in this embodiment, the distal elements are used to deliver implant pledgets and secure them to the target tissue, but are not themselves deployed at the site as in other embodiments. However, following deployment of the implant pledgets and associated sutures, the distal elements must be withdrawn from the body. For this purpose, the distal elements are movable to an inverted position like the embodiments described above to facilitate withdrawing the device without interference or injury to surrounding tissues.

In some applications such as the repair of the mitral valve, the fixation device is adapted to be detached from the delivery catheter and left permanently in the patient. In such applications, it is often desirable to promote tissue growth around the fixation device. For this purpose, some or all of the components of the fixation device are preferably covered with a covering or coating to promote tissue growth. In one embodiment, a biocompatible fabric cover is positioned over the distal elements and/or the proximal elements. The cover may optionally be impregnated or coated with various therapeutic agents, including tissue growth promoters, antibiotics, anti-clotting, blood thinning, and other agents. Alternatively or in addition, some or all of the fixation element and/or covering may be comprised of a bioerodable, biodegradable or bioabsorbable material so that it may degrade or be absorbed by the body after the repaired tissues have grown together.

The distal elements and proximal elements will be configured to provide high retention force so that the fixation device remains securely fastened to the target tissue throughout the cardiac cycle. At the same time, the distal and proximal elements will be configured to minimize trauma to the tissue engaged by them. This allows the fixation device to be removed from the tissue after initial application without creating clinically significant injury to the tissue. In order to enhance retention without creating significant trauma, the proximal elements and/or the distal elements may have fric-

6

tion-enhancing features on their surfaces that engage the target tissue. Such friction-enhancing features may include barbs, bumps, grooves, openings, channels, surface roughening, coverings, and coatings, among others. Optionally, magnets may be present in the proximal and/or distal elements. Preferably the friction-enhancing features and the magnets will be configured to increase the retention force of the distal and proximal elements on the tissue, while not leaving significant injury or scarring if the device is removed.

The distal and proximal elements may further have a shape and flexibility to maximize retention force and minimize trauma to the target tissue. In a preferred embodiment, the engagement surfaces of the distal elements have a concave shape configured to allow the proximal elements, along with the target tissue, to be nested or recessed within the distal elements. This increases the surface area of the tissue engaged by the distal elements and creates a geometry of tissue engagement that has a higher retention force than a planar engagement surface. To minimize trauma, the longitudinal edges as well as the free ends of the distal elements are preferably curved outwardly away from the engagement surface so that these edges present a rounded surface against the target tissue. The distal elements and/or the proximal elements may also be flexible so that they deflect to some degree in response to forces against the tissue engaged thereby, reducing the chances that the tissue will tear or bruise in response to such forces.

The fixation device will include an actuation mechanism for moving the distal elements between the open, closed, and inverted positions. A variety of actuation mechanisms may be used. In an exemplary embodiment, a coupling member connects the fixation device to the delivery catheter, and a stud is slidably coupled to the coupling member. In a "push to close/pull to open" embodiment, the distal elements are pivotably coupled to the stud and the actuation mechanism comprises a pair of link members connected between the distal elements and the coupling member, whereby sliding the stud relative to the coupling member pivots the distal elements inwardly or outwardly into the various positions. Alternatively, in a "push to open/pull to close" embodiment, the distal elements are pivotably coupled to the coupling member and the links connected between the distal elements and the stud.

The fixation device of the invention preferably includes a coupling member that is detachably connectable to the delivery catheter. The coupling member may have various constructions, but in an exemplary embodiment comprises an outer member having an axial channel, the outer member being coupled to one of either the distal elements or the actuation mechanism. An inner member extends slidably through the axial channel and is coupled to the other of either the distal elements or the actuation mechanism. The delivery catheter will be configured to detachably connect to both the inner member and the outer member. In one embodiment, the delivery catheter has a tubular shaft and an actuator rod slidably disposed in the tubular shaft. The junction of the outer member with the tubular shaft comprises a joining line, which may have a variety of shapes including sigmoid curves. The actuator rod extends from the delivery catheter through the axial channel in the outer member to maintain its connection with the tubular shaft. The actuator rod may be connected to the inner member by various connection structures, including threaded connections. By detachment of the actuator rod from the inner member and retraction of the actuator rod back into the tubular shaft, the outer member is released from the tubular shaft to allow deployment of the fixation device.

In a preferred embodiment, the fixation device further includes a locking mechanism that maintains the distal ele-

7

ments in a selected position relative to each other. Because the ideal degree of closure of the fixation device may not be known until it is actually applied to the target tissue, the locking mechanism is configured to retain the distal elements in position regardless of how open or closed they may be. While a variety of locking mechanisms may be used, in an exemplary embodiment the locking mechanism comprises a wedging element that is movable into frictional engagement with a movable component of the fixation device to prevent further movement of the distal elements. In embodiments utilizing the actuation mechanism described above, the component with which the wedging element engages may be the coupling member or the stud slidably coupled thereto. In one embodiment the stud passes through an aperture in the coupling member that has a sloping sidewall, and the wedging element comprises a barbell disposed between the sidewall and the stud.

The fixation device preferably also includes an unlocking mechanism for releasing the locking mechanism, allowing the distal elements and proximal elements to move. In one embodiment, the unlocking mechanism comprises a harness coupled to the wedging element of the locking mechanism to reduce frictional engagement with the movable component of the fixation device. In an exemplary embodiment, the harness is slidably coupled to the coupling member and extends around the wedging element of the locking mechanism, whereby the harness can be retracted relative to the coupling member to disengage the wedging element from the stud.

In a further aspect, the invention provides an interventional system comprising a tubular guide having a proximal end, a distal end and a channel therebetween, the distal end of the tubular guide being deflectable about a first axis; a delivery catheter positionable through the channel, the delivery catheter having a flexible shaft with a proximal end, a distal end, a lumen therebetween, and an actuation element movably disposed in the lumen; and a fixation device having a coupling member releasably coupled to the distal end of the shaft, a first distal element movably coupled to the coupling member, and a first proximal element movable relative to the distal element, the first distal element being releasably coupled to the actuation element and movable therewith, the first distal element and the first proximal element being adapted to engage tissue therebetween.

The delivery device of the invention is adapted to allow the user to deliver the fixation device to the target site from a remote access point, whether through endovascular or surgical approaches, align the device with the target tissue, and to selectively close, open, invert, lock or unlock the distal element. In some embodiments, the delivery device will have a highly flexible, kink resistant, torsionally stiff shaft with minimal elongation and high compressive strength. The delivery device will also have the movable components and associated actuators to move the distal elements between the open, closed, and inverted positions, to move the proximal elements into engagement with the target tissue, to unlock the locking mechanism, and to detach the distal element from the delivery catheter. In a preferred embodiment, the delivery device comprises a delivery catheter having an elongated shaft which has an inner lumen. The distal end of the shaft is configured for detachable connection to the coupling member of the fixation device. An actuator rod is slidably disposed in the inner lumen and is adapted for detachable coupling to the stud or other component of the fixation device that moves the distal elements. A plurality of tubular guides, preferably in the form of metallic or polymeric coils, extend through the inner lumen of the shaft and are typically fixed to the shaft near its proximal and distal ends but are unrestrained therebetween,

8

providing a highly flexible and kink-resistant construction. Lines for actuating the proximal elements and the unlocking mechanism of the fixation device extend through these tubular guides and are detachably coupled to the proximal element and unlocking mechanisms. These and other aspects of delivery catheters suitable for use in the present invention are described in copending application Ser. No. 10/441,687, filed on the same day as the present application, which has been incorporated herein by reference.

The delivery catheter may additionally include a tether that is detachably coupled to a portion of the fixation device for purposes of retrieval of the device following detachment from the delivery catheter. The tether may be a separate flexible filament extending from the delivery catheter to the fixation device, but alternatively may be a line coupled to either the unlocking mechanism or the proximal element and used also for actuating those components. In either case, the tether will be detachable from the fixation device so that it may be detached once the device has been deployed successfully.

The system of the invention may additionally include a guide that facilitates introduction and navigation of the delivery catheter and fixation device to the target location. The guide is preferably tubular with a channel extending between its proximal and distal ends in which the delivery catheter and fixation device may be slidably positioned. The distal end of the guide is steerable, usually being deflectable about at least one axis, and preferably about two axes. The guide will have a size, material, flexibility and other characteristics suitable for the application in which it is being used. For mitral valve repair, the guide is preferably configured to be introduced in a femoral vein and advanced through the inferior vena cava into the heart, across a penetration in the interatrial septum, and into alignment with the mitral valve in the left atrium. Alternatively, the guide may be configured for introduction in a femoral, axillary, or brachiocephalic artery and advancement through the aorta and aortic valve into the ventricle where it is steered into alignment with the mitral valve. In a further alternative, the guide may be configured for introduction through a puncture or incision in the chest wall and through an incision in the wall of the heart to approach the mitral valve.

In an exemplary embodiment, the guide comprises a multi-catheter guiding system which has two components, including an inner tubular member or inner guide catheter and an outer tubular member or outer guide catheter. The inner tubular member has a distal end deflectable about a first axis. The outer tubular member has a distal end deflectable about a second axis. Further, the inner tubular member may be rotatable relative to the outer tubular member about its longitudinal axis. Mobility in additional directions and about additional axes may optionally be provided. Additional aspects of guides usable in the system of the invention are described in copending application Ser. No. 10/441,508, filed on the same day as the present application, which has been incorporated herein by reference.

The invention further provides methods of performing therapeutic interventions at a tissue site. In one embodiment, the method includes the steps of advancing an interventional tool having a proximal end, a distal end and a fixation device near the distal end to a location within a patient's body, wherein the fixation device includes a pair of distal elements each having a free end and an engagement surface; moving the distal elements to an open position wherein the free ends are spaced apart; positioning the distal elements such that the engagement surfaces engage tissue at the tissue site; and detaching the fixation device from the interventional tool. Preferably, the method further includes the step of inverting

the distal elements to an inverted position wherein the free ends point generally in a distal direction. In some embodiments, the engagement surfaces will face generally away from each other in the inverted position, while in other embodiments, the engagement surfaces will face generally toward each other in the inverted position.

In an exemplary embodiment, the tissue site comprises first and second leaflets, and the step of moving the distal elements comprises coapting the leaflets. The leaflets may be part of a variety of tissue structures, but are preferably part of a cardiac valve such as the mitral valve. In antegrade approaches, the step of advancing will usually include inserting the fixation device through a valve annulus, e.g. from an atrium of the heart to a ventricle of the heart. In such approaches, the method may further include a step of withdrawing the fixation device through the valve annulus with the fixation device in the inverted position. Retrograde approaches are also provided, in which the step of advancing will include the step of passing the fixation device through a ventricle of the heart into an atrium of the heart. The step of advancing may further comprise transluminally positioning the fixation device through a blood vessel into the heart, and may include inserting the fixation device through an interatrial septum of the heart. Alternatively, the step of advancing may comprise inserting the device through a surgical penetration in a body wall.

The method may further include moving the distal elements to a closed position after the step of positioning, the free ends of the distal element being closer together in the closed position with the engagement surfaces facing generally toward each other. In addition, the method may include a step of deploying a proximal element on the fixation device toward each engagement surface to as to capture tissue therebetween. Before the step of inverting, the proximal elements are retracted away from the engagement surfaces. The method optionally includes a step of locking the distal elements in a desired position, and may further include a step of unlocking the distal elements so that they are movable again.

In a further aspect, a method according to the invention comprises advancing a catheter having a proximal end, a distal end and a fixation device near the distal end to a location within a body, wherein the fixation device includes a pair of distal elements each having an engagement surface; moving the distal elements to an open position wherein the distal elements extend radially outwardly facing the engagement surfaces toward a direction other than radially outwardly; and moving the distal elements to an inverted position wherein the engagement surfaces face radially outwardly.

In still another aspect, the invention provides a method for fixing tissues together comprising advancing a catheter having a proximal end, a distal end and a fixation device disposed near the distal end to a location near the tissues, wherein the fixation device includes a pair of distal elements each having a removable implant pledget; moving the distal elements so that each implant pledget engages one of the tissues; penetrating each tissue and engaged implant pledget and passing a tie therethrough; fastening the ties to fix the tissues together; and removing the fixation device leaving the implant pledget in place.

In an additional aspect of the invention, kits for performing an intervention at a tissue site in a patient's body include a fixation device and Instructions for Use setting forth the steps of using the fixation device according to the methods of the invention. The fixation device may be as described in any of the various examples set forth herein. The kits may further include a delivery tool or catheter for delivering the fixation

device to the tissue site, as well as a tubular guide through which the delivery tool or catheter may be positioned.

Other aspects of the nature and advantages of the invention are set forth in the detailed description set forth below, taken in conjunction with the drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 illustrates the left ventricle and left atrium of the heart during systole.

FIG. 2A illustrates free edges of leaflets in normal coaptation, and FIG. 2B illustrates the free edges in regurgitative coaptation.

FIGS. 3A-3C illustrate grasping of the leaflets with a fixation device, inversion of the distal elements of the fixation device and removal of the fixation device, respectively.

FIG. 4 illustrates the position of the fixation device in a desired orientation relative to the leaflets.

FIGS. 5A-5B, 6A-6B illustrate exemplary embodiments of coupling mechanisms of the instant application.

FIGS. 7A-7D illustrate an embodiment of a fixation device in various positions.

FIGS. 8A-8B illustrate an embodiment of the fixation device wherein some or all of the components are molded as one part.

FIG. 9 illustrates another embodiment of the fixation device of the present invention.

FIGS. 10A-10B, 11A-11B, 12A-12B, 13A-13B, 14-16 illustrate embodiments of a fixation device in various possible positions during introduction and placement of the device within the body to perform a therapeutic procedure.

FIGS. 17A-17C illustrate a covering on the fixation device wherein the device is in various positions.

FIG. 18 illustrates an embodiment of the fixation device including proximal elements and a locking mechanism.

FIG. 19 provides a cross-sectional view of the locking mechanism of FIG. 18.

FIGS. 20-21 provide a cross-sectional view of the locking mechanism in the unlocked and locked positions respectively.

FIGS. 22A-22B illustrate a variation of the fixation device to facilitate capture of more widely-separated leaflets or other tissue flaps.

FIGS. 23, 24A-24B illustrate another embodiment of a locking mechanism.

FIGS. 25, 26A-26B illustrate yet another embodiment of a locking mechanism.

FIGS. 27-28 illustrate an additional embodiment of the fixation device wherein separation of couplers rotate the distal elements around pins.

FIGS. 29-30 illustrate the fixation device of FIGS. 27-28 with additional features such as barbs and bumpers.

FIG. 31 illustrates an embodiment of the fixation device having engagement surfaces with a serrated edge and wherein the fixation device is mounted for a ventricular approach to a mitral valve.

FIGS. 32-34 illustrate an additional embodiment of the fixation device which allows tissue to be grasped between the distal elements and the proximal elements while in an arrangement wherein the distal elements are parallel to each other.

FIGS. 35-39, 40A-40D, 41-42, 43A-43C illustrate another embodiment of the fixation device wherein the fixation device includes distal elements having implant pledgets.

FIGS. 44A-44B, 45-46 illustrate another embodiment of the fixation device wherein the distal elements are comprised of a semi-rigid material having a folded shape.

11

FIG. 47 is a perspective view of an embodiment of a delivery catheter for a fixation device.

FIG. 48 illustrates an embodiment of a fixation device coupled to the distal end of a delivery catheter.

FIG. 49 illustrates a portion of the shaft of a delivery catheter and a fixation device which is coupleable with the catheter.

FIGS. 50-52 are cross-sectional views of embodiments of the shaft of the delivery catheter.

FIGS. 52A-52B illustrate embodiments of the nose of the shaft of the delivery catheter.

FIG. 53A-53C illustrate various arrangements of lock lines engaging release harnesses of a locking mechanism.

FIGS. 54A-54B illustrate various arrangements of proximal element lines engaging proximal elements of a fixation device.

FIG. 55 illustrates an embodiment of the handle of the delivery catheter.

FIG. 56 is a cross-sectional view of the main body of the handle.

FIG. 57 illustrates an embodiment of a lock line handle.

FIG. 57A illustrates the lock line handle of FIG. 57 positioned within a semi-tube which is disposed within the sealed chamber.

FIGS. 58A-58B illustrate a mechanism for applying tension to lock lines.

FIGS. 59, 59A-59B illustrate features of the actuator rod control and handle.

FIG. 60 is a perspective view of an embodiment of a multi-catheter guiding system of the present invention, and an interventional catheter positioned therethrough.

FIG. 61A illustrates a primary curvature in an outer guide catheter.

FIG. 61B illustrates a secondary curvature in an inner guide catheter.

FIGS. 61C-61D illustrate example movement of an inner guide catheter through angle thetas.

FIG. 62A is a perspective side view of a multi-catheter guiding system having an additional curve in the outer guide catheter.

FIG. 62B illustrates lifting of the outer guide catheter due to the additional curve of FIG. 62A.

FIGS. 63A-63D illustrate a method of using the multi-catheter guiding system for accessing the mitral valve.

FIGS. 64A-64D illustrate curvature of a guide catheter of the present invention by the actuation of one or more pullwires.

FIG. 64E illustrates attachment of a pullwire to a tip ring.

FIGS. 65A-65I illustrate embodiments of the present invention comprising sections constructed with the inclusion of braiding or coil.

FIGS. 66A-66C illustrate a keying feature of the present invention.

FIGS. 67A-67B are perspective views of a guide catheter including a series of articulating members.

FIG. 68 illustrates embodiments of the handles.

FIG. 69 illustrates the handles of FIG. 68 with a portion of the housing removed.

FIG. 70 illustrates steering mechanisms within a handle.

FIG. 71 illustrates attachment of a pullwire to a disk.

FIGS. 72A-72B illustrate a hard stop peg restricting rotation of a disk.

FIGS. 73A-73C illustrates a portion of a hard stop gear assembly.

FIGS. 74A-74F illustrate a ball restricting rotation of a disk.

FIG. 75 illustrates an embodiment of a friction assembly.

12

FIG. 76 illustrates an embodiment of an interventional system of the present invention.

FIG. 76A illustrates an embodiment of a hemostatic valve for use with the present invention.

FIG. 76B illustrates an embodiment of a fixation device introducer.

FIG. 77 illustrates another embodiment of an interventional system of the present invention.

FIGS. 78-80 illustrate an embodiment of a stabilizer base for use with the present invention.

FIG. 81 illustrates a kit constructed in accordance with the principles of the present invention

DETAILED DESCRIPTION OF THE INVENTION

I. Cardiac Physiology

The left ventricle LV of a normal heart H in systole is illustrated in FIG. 1. The left ventricle LV is contracting and blood flows outwardly through the tricuspid (aortic) valve AV in the direction of the arrows. Back flow of blood or "regurgitation" through the mitral valve MV is prevented since the mitral valve is configured as a "check valve" which prevents back flow when pressure in the left ventricle is higher than that in the left atrium LA. The mitral valve MV comprises a pair of leaflets having free edges FE which meet evenly to close, as illustrated in FIG. 1. The opposite ends of the leaflets LF are attached to the surrounding heart structure along an annular region referred to as the annulus AN. The free edges FE of the leaflets LF are secured to the lower portions of the left ventricle LV through chordae tendinae CT (referred to hereinafter as the chordae) which include plurality of branching tendons secured over the lower surfaces of each of the valve leaflets LF. The chordae CT in turn, are attached to the papillary muscles PM which extend upwardly from the lower portions of the left ventricle and intraventricular septum IVS.

A number of structural defects in the heart can cause mitral valve regurgitation. Regurgitation occurs when the valve leaflets do not close properly allowing leakage from the ventricle into the atrium. As shown in FIG. 2A, the free edges of the anterior and posterior leaflets normally meet along a line of coaptation C. An example of a defect causing regurgitation is shown in FIG. 2B. Here an enlargement of the heart causes the mitral annulus to become enlarged, making it impossible for the free edges FE to meet during systole. This results in a gap G which allows blood to leak through the valve during ventricular systole. Ruptured or elongated chordae can also cause a valve leaflet to prolapse since inadequate tension is transmitted to the leaflet via the chordae. While the other leaflet maintains a normal profile, the two valve leaflets do not properly meet and leakage from the left ventricle into the left atrium will occur. Such regurgitation can also occur in patients who have suffered ischemic heart disease where the left ventricle does not contract sufficiently to effect proper closure.

II. General Overview

The present invention provides methods and devices for grasping, approximating and fixating tissues such as valve leaflets to treat cardiac valve regurgitation, particularly mitral valve regurgitation. The present invention also provides features that allow repositioning and removal of the device if so desired, particularly in areas where removal may be hindered by anatomical features such as chordae CT. Such removal would allow the surgeon to reapproach the valve in a new manner if so desired.

Grasping will preferably be atraumatic providing a number of benefits. By atraumatic, it is meant that the devices and

13

methods of the invention may be applied to the valve leaflets and then removed without causing any significant clinical impairment of leaflet structure or function. The leaflets and valve continue to function substantially the same as before the invention was applied. Thus, some minor penetration or denting of the leaflets may occur using the invention while still meeting the definition of "atraumatic". This enables the devices of the invention to be applied to a diseased valve and, if desired, removed or repositioned without having negatively affected valve function. In addition, it will be understood that in some cases it may be necessary or desirable to pierce or otherwise permanently affect the leaflets during either grasping, fixing or both. In some of these cases, grasping and fixation may be accomplished by a single device. Although a number of embodiments are provided to achieve these results, a general overview of the basic features will be presented herein. Such features are not intended to limit the scope of the invention and are presented with the aim of providing a basis for descriptions of individual embodiments presented later in the application.

The devices and methods of the invention rely upon the use of an interventional tool that is positioned near a desired treatment site and used to grasp the target tissue. In endovascular applications, the interventional tool is typically an interventional catheter. In surgical applications, the interventional tool is typically an interventional instrument. In preferred embodiments, fixation of the grasped tissue is accomplished by maintaining grasping with a portion of the interventional tool which is left behind as an implant. While the invention may have a variety of applications for tissue approximation and fixation throughout the body, it is particularly well adapted for the repair of valves, especially cardiac valves such as the mitral valve. Referring to FIG. 3A, an interventional tool 10, having a delivery device, such as a shaft 12, and a fixation device 14, is illustrated having approached the mitral valve MV from the atrial side and grasped the leaflets LF. The mitral valve may be accessed either surgically or by using endovascular techniques, and either by a retrograde approach through the ventricle or by an antegrade approach through the atrium, as described above. For illustration purposes, an antegrade approach is described.

The fixation device 14 is releasably attached to the shaft 12 of the interventional tool 10 at its distal end. When describing the devices of the invention herein, "proximal" shall mean the direction toward the end of the device to be manipulated by the user outside the patient's body, and "distal" shall mean the direction toward the working end of the device that is positioned at the treatment site and away from the user. With respect to the mitral valve, proximal shall refer to the atrial or upstream side of the valve leaflets and distal shall refer to the ventricular or downstream side of the valve leaflets.

The fixation device 14 typically comprises proximal elements 16 (or gripping elements) and distal elements 18 (or fixation elements) which protrude radially outward and are positionable on opposite sides of the leaflets LF as shown so as to capture or retain the leaflets therebetween. The proximal elements 16 are preferably comprised of cobalt chromium, nitinol or stainless steel, and the distal elements 18 are preferably comprised of cobalt chromium or stainless steel, however any suitable materials may be used. The fixation device 14 is coupleable to the shaft 12 by a coupling mechanism 17. The coupling mechanism 17 allows the fixation device 14 to detach and be left behind as an implant to hold the leaflets together in the coapted position.

In some situations, it may be desired to reposition or remove the fixation device 14 after the proximal elements 16, distal elements 18, or both have been deployed to capture the

14

leaflets LF. Such repositioning or removal may be desired for a variety of reasons, such as to reapproach the valve in an attempt to achieve better valve function, more optimal positioning of the device 14 on the leaflets, better purchase on the leaflets, to detangle the device 14 from surrounding tissue such as chordae, to exchange the device 14 with one having a different design, or to abort the fixation procedure, to name a few. To facilitate repositioning or removal of the fixation device 14 the distal elements 18 are releasable and optionally invertible to a configuration suitable for withdrawal of the device 14 from the valve without tangling or interfering with or damaging the chordae, leaflets or other tissue. FIG. 3B illustrates inversion wherein the distal elements 18 are moveable in the direction of arrows 40 to an inverted position. Likewise, the proximal elements 16 may be raised, if desired. In the inverted position, the device 14 may be repositioned to a desired orientation wherein the distal elements may then be reverted to a grasping position against the leaflets as in FIG. 3A. Alternatively, the fixation device 14 may be withdrawn (indicated by arrow 42) from the leaflets as shown in FIG. 3C. Such inversion reduces trauma to the leaflets and minimizes any entanglement of the device with surrounding tissues. Once the device 14 has been withdrawn through the valve leaflets, the proximal and distal elements may be moved to a closed position or configuration suitable for removal from the body or for reinsertion through the mitral valve.

FIG. 4 illustrates the position of the fixation device 14 in a desired orientation in relation to the leaflets LF. This is a short-axis view of the mitral valve MV from the atrial side, therefore, the proximal elements 16 are shown in solid line and the distal elements 18 are shown in dashed line. The proximal and distal elements 16, 18 are positioned to be substantially perpendicular to the line of coaptation C. The device 14 may be moved roughly along the line of coaptation to the location of regurgitation. The leaflets LF are held in place so that during diastole, as shown in FIG. 4, the leaflets LF remain in position between the elements 16, 18 surrounded by openings O which result from the diastolic pressure gradient. Advantageously, leaflets LF are coapted such that their proximal or upstream surfaces are facing each other in a vertical orientation, parallel to the direction of blood flow through mitral valve MV. The upstream surfaces may be brought together so as to be in contact with one another or may be held slightly apart, but will preferably be maintained in the vertical orientation in which the upstream surfaces face each other at the point of coaptation. This simulates the double orifice geometry of a standard surgical bow-tie repair. Color Doppler echo will show if the regurgitation of the valve has been reduced. If the resulting mitral flow pattern is satisfactory, the leaflets may be fixed together in this orientation. If the resulting color Doppler image shows insufficient improvement in mitral regurgitation, the interventional tool 10 may be repositioned. This may be repeated until an optimal result is produced wherein the leaflets LF are held in place.

Once the leaflets are coapted in the desired arrangement, the fixation device 14 is then detached from the shaft 12 and left behind as an implant to hold the leaflets together in the coapted position. As mentioned previously, the fixation device 14 is coupled to the shaft 12 by a coupling mechanism 17. FIGS. 5A-5B, 6A-6B illustrate exemplary embodiments of such coupling mechanisms. FIG. 5A shows an upper shaft 20 and a detachable lower shaft 22 which are interlocked at a joining line or mating surface 24. The mating surface 24 may have any shape or curvature which will allow or facilitate interlocking and later detachment. A snugly fitting outer sheath 26 is positioned over the shafts 20, 22 to cover the mating surface 24 as shown. FIG. 5B illustrates detachment

15

of the lower shaft 22 from the upper shaft 20. This is achieved by retracting the outer sheath 26, so that the mating surface 24 is exposed, which allows the shafts 20, 22 to separate.

Similarly, FIG. 6A illustrates a tubular upper shaft 28 and a detachable tubular lower shaft 30 which are interlocked at a mating surface 32. Again, the mating surface 32 may have any shape or curvature which will allow or facilitate interlocking and later detachment. The tubular upper shaft 28 and tubular lower shaft 30 form an outer member having an axial channel. A snugly fitting rod 34 or inner member is inserted through the tubular shafts 28, 30 to bridge the mating surface 32 as shown. FIG. 6B illustrates detachment of the lower shaft 30 from the upper shaft 28. This is achieved by retracting the rod 34 to a position above the mating surface 32 which in turn allows the shafts 28, 30 to separate. Other examples of coupling mechanisms are described and illustrated in copending U.S. patent application Ser. No. 09/894,493, incorporated herein by reference for all purposes.

In a preferred embodiment, mating surface 24 (or mating surface 32) is a sigmoid curve defining a male element and female element on upper shaft 20 (or upper shaft 28) which interlock respectively with corresponding female and male elements on lower shaft 22 (or lower shaft 30). Typically, the lower shaft is the coupling mechanism 17 of the fixation device 14. Therefore, the shape of the mating surface selected will preferably provide at least some mating surfaces transverse to the axial axis of the a mechanism 19 to facilitate application of compressive and tensile forces through the coupling mechanism 17 to the fixation device 14, yet causing minimal interference when the fixation device 14 is to be released from the upper shaft.

III. Fixation Device

A. Introduction and Placement of Fixation Device

The fixation device 14 is delivered to the valve or the desired tissues with the use of a delivery device. The delivery device may be rigid or flexible depending on the application. For endovascular applications, the delivery device comprises a flexible delivery catheter which will be described in later sections. Typically, however, such a catheter comprises a shaft, having a proximal end and a distal end, and a fixation device releasably attached to its distal end. The shaft is usually elongate and flexible, suitable for intravascular introduction. Alternatively, the delivery device may comprise a shorter and less flexible interventional instrument which may be used for trans-thoracic surgical introduction through the wall of the heart, although some flexibility and a minimal profile will generally be desirable. A fixation device is releasably coupleable with the delivery device as illustrated in FIG. 3A. The fixation device may have a variety of forms, a few embodiments of which will be described herein.

FIGS. 7A-7D illustrate an embodiment of a fixation device 14 in various positions or configurations. FIG. 7A illustrates the fixation device 14 in a closed configuration for delivery through the patient's vasculature and, in this example, through the mitral valve. The fixation device 14 includes a coupling member 19 which allows detachment of the fixation device 14 for implantation. In this example, the coupling member 19 is shown to include the lower shaft 22 and mating surface 24 of FIGS. 5A-5B, and therefore the coupling member 19 would function similarly as described above. The fixation device 14 also includes a pair of opposed distal elements 18, each distal element 18 having an engagement surface 50 facing inwardly toward the opposed distal element 18 in the closed configuration. Distal elements 18 preferably

16

comprise elongate arms 53, each arm having a proximal end 52 rotatably connected to the coupling member 19 and a free end 54. Suitable connections for arms 53 to coupling member 19 include pins, living hinges, or other known rotational connection mechanisms. In the closed configuration of FIG. 7A, free ends 54 point in a first direction such that the arms 53 and engagement surfaces 50 are nearly parallel to each other and to an axis 21, and preferably are angled slightly inwardly toward each other. In a preferred embodiment, when tissue is not present between arms 53, the arms 53 may be closed until free ends 54 either touch each other or engage shaft 12 when fixation device 14 is attached thereto, thereby minimizing the profile of the fixation device 14 for passage through a delivery device.

FIGS. 7B-7C illustrate the fixation device 14 in an open position wherein the engagement surfaces 50 are disposed at a separation angle 56 apart, wherein the separation angle 56 is typically up to approximately 180 degrees, preferably up to 90-180 degrees, and arms 53 are disposed generally symmetrically relative to axis 21. The arms 53 may be moveable to the open position by a variety of actuation mechanisms. For example, a plunger or actuator rod may be advanced through the coupling member 19, as indicated by arrow 62, so as to engage a spring or spring loaded actuation mechanism 58 which is attached to the distal elements 18. By exerting a force against the actuation mechanism 58, the distal elements 18 are rotated relative to coupling member 19. The distal elements 18 may be held in this open position by the actuator rod against the resistance provided by the spring of the actuation mechanism 58 which biases the distal elements 18 toward the closed position of FIG. 7A when the distal elements 18 are less than 180 degrees apart. The spring loading of the actuation mechanism 58 resists outward movement of the actuation mechanism 58 and urges the device 14 towards the closed position.

In this embodiment, proximal elements 16 comprise resilient loop-shaped wire forms biased outwardly and attached to the coupling member 19 so as to be biased to an open position shown in FIG. 7C but moveable rotationally inwardly when arms 53 are closed. The wire forms may be flexible enough to be rigidly attached to coupling member 19 and resiliently deflectable inwardly, or they may be attached by a rotational coupling such as a pin or living hinge. In use, leaflets LF are positioned between the proximal elements 16 and distal elements 18. Once, the leaflets LF are positioned between the proximal and distal elements 16, 18, the distal elements 18 may be closed, compressing the leaflets between engagement surfaces 50 and proximal elements 18. Depending upon the thickness of the leaflets, the arrangements of the leaflets, the position of the fixation device on the leaflets and other factors, the arms 53 may be maintained in the open position of FIG. 7B, moved to the fully closed position of FIG. 7A, or placed in any of various positions in between so as to coapt the leaflets LF and hold them in the desired position with the desired degree of force. In any case, the fixation device 14 will remain in place as an implant following detachment from the delivery catheter.

In some situations, as previously mentioned, it may be desirable to reopen the fixation device 14 following initial placement. To reopen the device 14, the actuator rod may be readvanced or reinserted through the coupling member 19 and readvanced to press against the actuation mechanism 58, as previously indicated by arrow 62 in FIG. 7B. Again, such advancement applies a force against the actuation mechanism 58 in the manner described above thus moving arms 53 outwardly to release force against leaflets and move engagement surfaces 50 away from proximal elements 16. The leaflets are

17

then free to move relative to fixation device **14**. The fixation device **14** may then be repositioned as desired and the actuator rod retracted to reclose the distal elements **18** to coapt the leaflets.

Under some circumstances, it may be further desirable to withdraw the fixation device **14** back through the valve or completely from the patient following initial insertion through the valve. Should this be attempted with the clip in the closed or open positions illustrated in FIGS. 7A-7C, there may be a risk that arms **53** could interfere or become entangled with the chordae, leaflets or other tissues. To avoid this, the fixation element **14** is preferably adapted for inversion of arms **53** so that free ends **54** point in a second direction, opposite to the first direction in which the free ends **54** pointed in the closed position, each arm **53** forming an obtuse angle relative to axis **21** as illustrated in FIG. 7D. The arms **53** may be rotated so that the engagement surfaces **50** are disposed at a separation angle **56** of up to 360 degrees, and preferably at least up to 270 degrees. This may be accomplished by exerting a force against actuation mechanism **58** with a push rod or plunger extending through coupling member **19** as described above. In this embodiment, once the distal elements **18** have rotated beyond 180 degrees apart, the spring loading of the actuation mechanism **58** biases the distal elements **18** toward the inverted position. The spring loading of the actuation mechanism **58** resists outward movement of the actuation mechanism **58** and urges the device **14** towards the inverted position.

With arms **53** in the inverted position, engagement surfaces **50** provide an atraumatic surface deflect tissues as the fixation device is withdrawn. This allows the device to be retracted back through the valve annulus without risk of injury to valvular and other tissues. In some cases, once the fixation device **14** has been pulled back through the valve, it will be desirable to return the device to the closed position for withdrawal of the device from the body (either through the vasculature or through a surgical opening).

The embodiment illustrated in FIGS. 7A-7D is assembled from separate components composed of biocompatible materials. The components may be formed from the same or different materials, including but not limited to stainless steel or other metals, Elgiloy®, nitinol, titanium, tantalum, metal alloys or polymers. Additionally, some or all of these components may be made of bioabsorbable materials that will be absorbed by surrounding tissues or will dissolve into the bloodstream following implantation. It has been found that in mitral valve repair applications the fixation devices of the invention are completely surrounded by tissue within a few months of implantation, after which the devices could dissolve or be absorbed without negative impact to the repair.

In a further embodiment, some or all of the components may be molded as one part, as illustrated in FIGS. 8A-8B. Here, the coupling member **19**, distal elements **18** and actuation mechanism **58** of the fixation device **14** are all molded from a polymer material as one moveable piece. FIG. 8A shows the fixation device **14** in the open position. Advancement of an actuator rod **64** rotates the distal elements **18** relative to the coupling member **19** by a living hinge or by elastic deformation of the plastic at the point of connection between the elements **18** and the coupling member **19**. Typically, this point of connection comprises a thinner segment of polymer to facilitate such bending. Likewise, the actuation mechanism **58** coupled to the distal elements **18** in the same manner. FIG. 8B shows the fixation device **14** in the inverted position.

FIG. 9 illustrates another embodiment of a fixation device **14**. Here, the fixation device **14** is shown coupled to a shaft **12**

18

to form an interventional tool **10**. The fixation device **14** includes a coupling member **19** and a pair of opposed distal elements **18**. The distal elements **18** comprise elongate arms **53**, each arm having a proximal end **52** rotatably connected to the coupling member **19** and a free end **54**. The free ends **54** have a rounded shape to minimize interference with and trauma to surrounding tissue structures. Preferably, each free end **54** defines a curvature about two axes, one being an axis **66** perpendicular to longitudinal axis of arms **53**. Thus, the engagement surfaces **50** have a cupped or concave shape to surface area in contact with tissue and to assist in grasping and holding the valve leaflets. This further allows arms **53** to nest around the shaft **12** in the closed position to minimize the profile of the device. Preferably, arms **53** are at least partially cupped or curved inwardly about their longitudinal axes **66**. Also, preferably, each free end **54** defines a curvature about an axis **67** perpendicular to axis **66** or the longitudinal axis of arms **53**. This curvature is a reverse curvature along the most distal portion of the free end **54**. Likewise, the longitudinal edges of the free ends **54** may flare outwardly. Both the reverse curvature and flaring minimize trauma to the tissue engaged therewith.

In a preferred embodiment suitable for mitral valve repair, the transverse width across engagement surfaces **50** (which determines the width of tissue engaged) is at least about 2 mm, usually 3-10 mm, and preferably about 4-6 mm. In some situations, a wider engagement is desired wherein the engagement surfaces **50** are larger, for example about 2 cm, or multiple fixation devices are used adjacent to each other. Arms **53** and engagement surfaces **50** are configured to engage a length of tissue of about 4-10 mm, and preferably about 6-8 mm along the longitudinal axis of arms **53**. Arms **53** further include a plurality of openings to enhance grip and to promote tissue ingrowth following implantation.

The valve leaflets are grasped between the distal elements **18** and proximal elements **16**. In some embodiments, the proximal elements **16** are flexible, resilient, and cantilevered from coupling member **19**. The proximal elements are preferably resiliently biased toward the distal elements. Each proximal element **16** is shaped and positioned to be at least partially recessed within the concavity of the distal element **18** when no tissue is present. When the fixation device **14** is in the open position, the proximal elements **16** are shaped such that each proximal element **16** is separated from the engagement surface **50** near the proximal end **52** of arm **53** and slopes toward the engagement surface **50** near the free end **54** with the free end of the proximal element contacting engagement surface **50**, as illustrated in FIG. 9. This shape of the proximal elements **16** accommodates valve leaflets or other tissues of varying thicknesses.

Proximal elements **16** include a plurality of openings **63** and scalloped side edges **61** to increase grip on tissue. The proximal elements **16** optionally include frictional accessories, frictional features or grip-enhancing elements to assist in grasping and/or holding the leaflets. In preferred embodiments, the frictional accessories comprise barbs **60** having tapering pointed tips extending toward engagement surfaces **50**. It may be appreciated that any suitable frictional accessories may be used, such as prongs, windings, bands, barbs, grooves, channels, bumps, surface roughening, sintering, high-friction pads, coverings, coatings or a combination of these. Optionally, magnets may be present in the proximal and/or distal elements. It may be appreciated that the mating surfaces will be made from or will include material of opposite magnetic charge to cause attraction by magnetic force. For example, the proximal elements and distal elements may each include magnetic material of opposite charge so that

19

tissue is held under constant compression between the proximal and distal elements to facilitate faster healing and ingrowth of tissue. Also, the magnetic force may be used to draw the proximal elements 16 toward the distal elements 18, in addition to or alternatively to biasing of the proximal elements toward the distal elements. This may assist in deployment of the proximal elements 16. In another example, the distal elements 18 each include magnetic material of opposite charge so that tissue positioned between the distal elements 18 is held therebetween by magnetic force.

The proximal elements 16 may be covered with a fabric or other flexible material as described below to enhance grip and tissue ingrowth following implantation. Preferably, when fabrics or coverings are used in combination with barbs or other frictional features, such features will protrude through such fabric or other covering so as to contact any tissue engaged by proximal elements 16.

In an exemplary embodiment, proximal elements 16 are formed from metallic sheet of a spring-like material using a stamping operation which creates openings 63, scalloped edges 61 and barbs 60. Alternatively, proximal elements 16 could be comprised of a spring-like material or molded from a biocompatible polymer. It should be noted that while some types of frictional accessories that can be used in the present invention may permanently alter or cause some trauma to the tissue engaged thereby, in a preferred embodiment, the frictional accessories will be atraumatic and will not injure or otherwise affect the tissue in a clinically significant way. For example, in the case of barbs 60, it has been demonstrated that following engagement of mitral valve leaflets by fixation device 14, should the device later be removed during the procedure barbs 60 leave no significant permanent scarring or other impairment of the leaflet tissue and are thus considered atraumatic.

The fixation device 14 also includes an actuation mechanism 58. In this embodiment, the actuation mechanism 58 comprises two link members or legs 68, each leg 68 having a first end 70 which is rotatably joined with one of the distal elements 18 at a riveted joint 76 and a second end 72 which is rotatably joined with a stud 74. The legs 68 are preferably comprised of a rigid or semi-rigid metal or polymer such as Elgiloy®, cobalt chromium or stainless steel, however any suitable material may be used. While in the embodiment illustrated both legs 68 are pinned to stud 74 by a single rivet 78, it may be appreciated, however, that each leg 68 may be individually attached to the stud 74 by a separate rivet or pin. The stud 74 is joinable with an actuator rod 64 (not shown) which extends through the shaft 12 and is axially extendable and retractable to move the stud 74 and therefore the legs 68 which rotate the distal elements 18 between closed, open and inverted positions. Likewise, immobilization of the stud 74 holds the legs 68 in place and therefore holds the distal elements 18 in a desired position. The stud 74 may also be locked in place by a locking feature which will be further described in later sections.

In any of the embodiments of fixation device 14 disclosed herein, it may be desirable to provide some mobility or flexibility in distal elements 18 and/or proximal elements 16 in the closed position to enable these elements to move or flex with the opening or closing of the valve leaflets. This provides shock absorption and thereby reduces force on the leaflets and minimizes the possibility for tearing or other trauma to the leaflets. Such mobility or flexibility may be provided by using a flexible, resilient metal or polymer of appropriate thickness to construct the distal elements 18. Also, the locking mechanism of the fixation device (described below) may be constructed of flexible materials to allow some slight movement

20

of the proximal and distal elements even when locked. Further, the distal elements 18 can be connected to the coupling mechanism 19 or to actuation mechanism 58 by a mechanism that biases the distal element into the closed position (inwardly) but permits the arms to open slightly in response to forces exerted by the leaflets. For example, rather than being pinned at a single point, these components may be pinned through a slot that allowed a small amount of translation of the pin in response to forces against the arms. A spring is used to bias the pinned component toward one end of the slot.

FIGS. 10A-10B, 11A-11B, 12A-12B, 13A-13B, and FIGS. 14-16 illustrate embodiments of the fixation device 14 of FIG. 9 in various possible positions during introduction and placement of the device 14 within the body to perform a therapeutic procedure. FIG. 10A illustrates an embodiment of an interventional tool 10 delivered through a catheter 86. It may be appreciated that the interventional tool 10 may take the form of a catheter, and likewise, the catheter 86 may take the form of a guide catheter or sheath. However, in this example the terms interventional tool 10 and catheter 86 will be used. The interventional tool 10 comprises a fixation device 14 coupled to a shaft 12 and the fixation device 14 is shown in the closed position. FIG. 10B illustrates a similar embodiment of the fixation device of FIG. 10A in a larger view. In the closed position, the opposed pair of distal elements 18 are positioned so that the engagement surfaces 50 face each other. Each distal element 18 comprises an elongate arm 53 having a cupped or concave shape so that together the arms 53 surround the shaft 12 and optionally contact each other on opposite sides of the shaft. This provides a low profile for the fixation device 14 which is readily passable through the catheter 86 and through any anatomical structures, such as the mitral valve. In addition, FIG. 10B further includes an actuation mechanism 58. In this embodiment, the actuation mechanism 58 comprises two legs 68 which are each movably coupled to a base 69. The base 69 is joined with an actuator rod 64 which extends through the shaft 12 and is used to manipulate the fixation device 14. In some embodiments, the actuator rod 64 attaches directly to the actuation mechanism 58, particularly the base 69. However, the actuator rod 64 may alternatively attach to a stud 74 which in turn is attached to the base 69. In some embodiments, the stud 74 is threaded so that the actuator rod 64 attaches to the stud 74 by a screw-type action. However, the rod 64 and stud 74 may be joined by any mechanism which is releasable to allow the fixation device 14 to be detached from shaft 12.

FIGS. 11A-11B illustrate the fixation device 14 in the open position. In the open position, the distal elements 18 are rotated so that the engagement surfaces 50 face a first direction. Distal advancement of the stud 74 relative to coupling member 19 by action of the actuator rod 64 applies force to the distal elements 18 which begin to rotate around joints 76 due to freedom of movement in this direction. Such rotation and movement of the distal elements 18 radially outward causes rotation of the legs 68 about joints 80 so that the legs 68 are directly slightly outwards. The stud 74 may be advanced to any desired distance correlating to a desired separation of the distal elements 18. In the open position, engagement surfaces 50 are disposed at an acute angle relative to shaft 12, and are preferably at an angle of between 90 and 180 degrees relative to each other. In one embodiment, in the open position the free ends 54 of arms 53 have a span therebetween of about 10-20 mm, usually about 12-18 mm, and preferably about 14-16 mm.

Proximal elements 16 are typically biased outwardly toward arms 53. The proximal elements 16 may be moved inwardly toward the shaft 12 and held against the shaft 12

21

with the aid of proximal element lines **90** which can be in the form of sutures, wires, nitinol wire, rods, cables, polymeric lines, or other suitable structures. The proximal element lines **90** may be connected with the proximal elements **16** by threading the lines **90** in a variety of ways. When the proximal elements **16** have a loop shape, as shown in FIG. 11A, the line **90** may pass through the loop and double back. When the proximal elements **16** have an elongate solid shape, as shown in FIG. 11B, the line **90** may pass through one or more of the openings **63** in the element **16**. Further, a line loop **48** may be present on a proximal element **16**, also illustrated in FIG. 11B, through which a proximal element line **90** may pass and double back. Such a line loop **48** may be useful to reduce friction on proximal element line **90** or when the proximal elements **16** are solid or devoid of other loops or openings through which the proximal element lines **90** may attach. A proximal element line **90** may attach to the proximal elements **16** by detachable means which would allow a single line **90** to be attached to a proximal element **16** without doubling back and would allow the single line **90** to be detached directly from the proximal element **16** when desired. Examples of such detachable means include hooks, snares, clips or breakable couplings, to name a few. By applying sufficient tension to the proximal element line **90**, the detachable means may be detached from the proximal element **16** such as by breakage of the coupling. Other mechanisms for detachment may also be used. Similarly, a lock line **92** may be attached and detached from a locking mechanism by similar detachable means.

In the open position, the fixation device **14** can engage the tissue which is to be approximated or treated. The embodiment illustrated in FIGS. 9-11 is adapted for repair of the mitral valve using an antegrade approach from the left atrium. The interventional tool **10** is advanced through the mitral valve from the left atrium to the left ventricle. The distal elements **18** are oriented to be perpendicular to the line of coaptation and then positioned so that the engagement surfaces **50** contact the ventricular surface of the valve leaflets, thereby grasping the leaflets. The proximal elements **16** remain on the atrial side of the valve leaflets so that the leaflets lie between the proximal and distal elements. In this embodiment, the proximal elements **16** have frictional accessories, such as barbs **60** which are directed toward the distal elements **18**. However, neither the proximal elements **16** nor the barbs **60** contact the leaflets at this time.

The interventional tool **10** may be repeatedly manipulated to reposition the fixation device **14** so that the leaflets are properly contacted or grasped at a desired location. Repositioning is achieved with the fixation device in the open position. In some instances, regurgitation may also be checked while the device **14** is in the open position. If regurgitation is not satisfactorily reduced, the device may be repositioned and regurgitation checked again until the desired results are achieved.

It may also be desired to invert the fixation device **14** to aid in repositioning or removal of the fixation device **14**. FIGS. 12A-12B illustrate the fixation device **14** in the inverted position. By further advancement of stud **74** relative to coupling member **19**, the distal elements **18** are further rotated so that the engagement surfaces **50** face outwardly and free ends **54** point distally, with each arm **53** forming an obtuse angle relative to shaft **12**. The angle between arms **53** is preferably in the range of about 270 to 360 degrees. Further advancement of the stud **74** further rotates the distal elements **18** around joints **76**. This rotation and movement of the distal elements **18** radially outward causes rotation of the legs **68** about joints **80** so that the legs **68** are returned toward their

22

initial position, generally parallel to each other. The stud **74** may be advanced to any desired distance correlating to a desired inversion of the distal elements **18**. Preferably, in the fully inverted position, the span between free ends **54** is no more than about 20 mm, usually less than about 16 mm, and preferably about 12-14 mm. In this illustration, the proximal elements **16** remain positioned against the shaft **12** by exerting tension on the proximal element lines **90**. Thus, a relatively large space may be created between the elements **16**, **18** for repositioning. In addition, the inverted position allows withdrawal of the fixation device **14** through the valve while minimizing trauma to the leaflets. Engagement surfaces **50** provide an atraumatic surface for deflecting tissue as the fixation device is retracted proximally. It should be further noted that barbs **60** are angled slightly in the distal direction (away from the free ends of the proximal elements **16**), reducing the risk that the barbs will catch on or lacerate tissue as the fixation device is withdrawn.

Once the fixation device **14** has been positioned in a desired location against the valve leaflets, the leaflets may then be captured between the proximal elements **16** and the distal elements **18**. FIGS. 13A-13B illustrate the fixation device **14** in such a position. Here, the proximal elements **16** are lowered toward the engagement surfaces **50** so that the leaflets are held therebetween. In FIG. 13B, the proximal elements **16** are shown to include barbs **60** which may be used to provide atraumatic gripping of the leaflets. Alternatively, larger, more sharply pointed barbs or other penetration structures may be used to pierce the leaflets to more actively assist in holding them in place. This position is similar to the open position of FIGS. 11A-11B, however the proximal elements **16** are now lowered toward arms **53** by releasing tension on proximal element lines **90** to compress the leaflet tissue therebetween. At any time, the proximal elements **16** may be raised and the distal elements **18** adjusted or inverted to reposition the fixation device **14**, if regurgitation is not sufficiently reduced.

After the leaflets have been captured between the proximal and distal elements **16**, **18** in a desired arrangement, the distal elements **18** may be locked to hold the leaflets in this position or the fixation device **14** may be returned to or toward a closed position. Such locking will be described in a later section. FIG. 14 illustrates the fixation device **14** in the closed position wherein the leaflets (not shown) are captured and coapted. This is achieved by retraction of the stud **74** proximally relative to coupling member **19** so that the legs **68** of the actuation mechanism **58** apply an upwards force to the distal elements **18** which in turn rotate the distal elements **18** so that the engagement surfaces **50** again face one another. The released proximal elements **16** which are biased outwardly toward distal elements **18** are concurrently urged inwardly by the distal elements **18**. The fixation device **14** may then be locked to hold the leaflets in this closed position as described below.

As shown in FIG. 15, the fixation device **14** may then be released from the shaft **12**. As mentioned, the fixation device **14** is releasably coupleable to the shaft **12** by coupling member **19**. FIG. 15 illustrates the coupling structure, a portion of the shaft **12** to which the coupling member **19** of the fixation device **14** attaches. As shown, the proximal element lines **90** may remain attached to the proximal elements **16** following detachment from shaft **12** to function as a tether to keep the fixation device **14** connected with the catheter **86**. Optionally, a separate tether coupled between shaft **12** and fixation device **14** may be used expressly for this purpose while the proximal element lines **90** are removed. In any case, the repair of the leaflets or tissue may be observed by non-invasive visualization techniques, such as echocardiography, to ensure the desired outcome. If the repair is not desired, the fixation

23

device **14** may be retrieved with the use of the tether or proximal element lines **90** so as to reconnect coupling member **19** with shaft **12**.

In an exemplary embodiment, proximal element lines **90** are elongated flexible threads, wire, cable, sutures or lines extending through shaft **12**, looped through proximal elements **16**, and extending back through shaft **12** to its proximal end. When detachment is desired, one end of each line may be released at the proximal end of the shaft **12** and the other end pulled to draw the free end of the line distally through shaft **12** and through proximal element **16** thereby releasing the fixation device.

FIG. **16** illustrates a released fixation device **14** in a closed position. As shown, the coupling member **19** remains separated from the shaft **12** of the interventional tool **10** and the proximal elements **16** are deployed so that tissue (not shown) may reside between the proximal elements **16** and distal elements **18**.

While the above described embodiments of the invention utilize a push-to-open, pull-to-close mechanism for opening and closing distal elements **18**, it should be understood that a pull-to-open, push-to-close mechanism is equally possible. For example, distal elements **18** may be coupled at their proximal ends to stud **74** rather than to coupling member **19**, and legs **68** may be coupled at their proximal ends to coupling member **19** rather than to stud **74**. In this example, when stud **74** is pushed distally relative to coupling member **19**, distal elements **18** would close, while pulling on stud **74** proximally toward coupling member **19** would open distal elements **18**.

B. Covering on Fixation Device

The fixation device **14** may optionally include a covering. The covering may assist in grasping the tissue and may later provide a surface for tissue ingrowth. Ingrowth of the surrounding tissues, such as the valve leaflets, provides stability to the device **14** as it is further anchored in place and may cover the device with native tissue thus reducing the possibility of immunologic reactions. The covering may be comprised of any biocompatible material, such as polyethylene terephthalate, polyester, cotton, polyurethane, expanded polytetrafluoroethylene (ePTFE), silicon, or various polymers or fibers and have any suitable form, such as a fabric, mesh, textured weave, felt, looped or porous structure. Generally, the covering has a low profile so as not to interfere with delivery through an introducer sheath or with grasping and coapting of leaflets or tissue.

FIGS. **17A-17C** illustrate a covering **100** on the fixation device **14** wherein the device **14** is in various positions. FIG. **17A** shows the covering **100** encapsulating the distal elements **18** and the actuation mechanism **58** while the device **14** is in the open position. Thus, the engagement surfaces **50** are covered by the covering **100** which helps to minimize trauma on tissues and provides additional friction to assist in grasping and retaining tissues. FIG. **17B** shows the device **14** of FIG. **17A** in the inverted position. The covering **100** is loosely fitted and/or is flexible or elastic such that the device **14** can freely move to various positions and the covering **100** conforms to the contours of the device **14** and remains securely attached in all positions. FIG. **17C** shows the device **14** in the closed position. Thus, when the fixation device **14** is left behind as an implant in the closed position, the exposed surfaces of the device **14** are substantially covered by the covering **100**. It may be appreciated that the covering **100** may cover specific parts of the fixation device **14** while leaving other parts exposed. For example, the covering **100** may comprise sleeves that fit over the distal elements **18** and not

24

the actuation mechanism **58**, caps that fit over the distal ends **54** of the distal elements **18** or pads that cover the engagement surfaces **50**, to name a few. It may be appreciated that, the covering **100** may allow any frictional accessories, such as barbs, to be exposed. Also, the covering **100** may cover the proximal elements **16** and/or any other surfaces of the fixation device **14**. In any case, the covering **100** should be durable to withstand multiple introduction cycles and, when implanted within a heart, a lifetime of cardiac cycles.

The covering **100** may alternatively be comprised of a polymer or other suitable materials dipped, sprayed, coated or otherwise adhered to the surfaces of the fixation device **14**. Optionally, the polymer coating may include pores or contours to assist in grasping the tissue and/or to promote tissue ingrowth.

Any of the coverings **100** may optionally include drugs, antibiotics, anti-thrombosis agents, or anti-platelet agents such as heparin, COUMADIN® (Warfarin Sodium), to name a few. These agents may, for example, be impregnated in or coated on the coverings **100**. These agents may then be delivered to the grasped tissues surrounding tissues and/or bloodstream for therapeutic effects.

C. Fixation Device Locking Mechanisms

As mentioned previously, the fixation device **14** optionally includes a locking mechanism for locking the device **14** in a particular position, such as an open, closed or inverted position or any position therebetween. It may be appreciated that the locking mechanism includes an unlocking mechanism which allows the device to be both locked and unlocked. FIGS. **18-21** illustrate an embodiment of a locking mechanism **106**. Referring to FIG. **18**, in this embodiment, the locking mechanism **106** is disposed between the coupling member **19** and the base **69** of the actuation mechanism **58**. The base **69** is fixedly attached to the stud **74** which extends through the locking mechanism **106**. The stud **74** is releasably attached to the actuator rod **64** which passes through the coupling member **19** and the shaft **12** of the interventional tool **10**. The base **69** is also connected to the legs **68** of the actuation mechanism **58** which are in turn connected to the distal elements **18**.

FIG. **18** also illustrates the proximal elements **16**, which in this embodiment straddle the locking mechanism and join beneath the locking mechanism **106**. The proximal elements **16** are shown supported by proximal element lines **90**. The proximal elements **16** are raised and lowered by manipulation of the proximal element lines **90**. In addition, lock lines **92** are shown connected with a release harness **108** of the locking mechanism **106**. The lock lines **92** are used to lock and unlock the locking mechanism **106** as will be described below. The proximal element lines **90** and lock lines **92** may be comprised of any suitable material, typically wire, nitinol wire, cable, suture or thread, to name a few. In addition, the proximal element lines **90** and/or lock lines **92** may include a coating, such as parylene. Parylene is a vapor deposited pinhole free protective film which is conformal and biocompatible. It is inert and protects against moisture, chemicals, and electrical charge.

FIG. **19** provides a front view of the locking mechanism **106** of FIG. **18**. However, here the proximal elements **16** are supported by a single proximal element line **90** which is through both of the proximal elements **16**. In this arrangement both of the elements are raised and lowered simultaneously by action of a single proximal element line **90**. Whether the proximal elements **16** are manipulated individually by separate proximal element lines **90** or jointly by a single proximal

25

element line 90, the proximal element lines 90 may extend directly through openings in the proximal elements and/or through a layer or portion of a covering 100 on the proximal elements, or through a suture loop above or below a covering 100.

FIGS. 20-21 illustrate the locking mechanism 106 showing the locking mechanism 106 in the unlocked and locked positions respectively. Referring to FIG. 20, the locking mechanism 106 includes one or more wedging elements, such as rolling elements. In this embodiment, the rolling elements comprise a pair of barbells 110 disposed on opposite sides of the stud 74, each barbell having a pair of generally cylindrical caps and a shaft therebetween. The barbells 110 and the stud 74 are preferably comprised of cobalt chromium or stainless steel, however any suitable material may be used. The barbells 110 are manipulated by hooked ends 112 of the release harness 108. When an upwards force is applied to the harness 108 by the lock line 92 (illustrated in FIG. 18), the hooked ends 112 raise the barbells 110 against a spring 114, as shown in FIG. 20. This draws the barbells 110 up along a sidewall or sloping surface 116 which unwedges the barbells 110 from against the stud 74. In this position, the stud 74 is free to move. Thus, when the lock line 92 raises or lifts the harness 108, the locking mechanism 106 is in an unlocked position wherein the stud 74 is free to move the actuation mechanism 58 and therefore the distal elements 18 to any desired position. Release of the harness 108 by the lock line 92 transitions the locking mechanism 106 to a locked position, illustrated in FIG. 21. By releasing the upwards force on the barbells 110 by the hooked ends 112, the spring 114 forces the barbells 110 downwards and wedges the barbells 110 between the sloping surface 116 and the stud 74. This restricts motion of the stud 74, which in turn locks the actuation mechanism 58 and therefore distal elements 18 in place. In addition, the stud 74 may include one or more grooves 82 or indentations which receive the barbells 110. This may provide more rapid and positive locking by causing the barbells 110 to settle in a definite position, increase the stability of the locking feature by further preventing movement of the barbells 110, as well as tangible indication to the user that the barbell has reached a locking position. In addition, the grooves 82 may be used to indicate the relative position of the distal elements 18, particularly the distance between the distal elements 18. For example, each groove 82 may be positioned to correspond with a 0.5 or 1.0 mm decrease in distance between the distal elements 18. As the stud 74 is moved, the barbells 110 will contact the grooves 82; by counting the number of grooves 82 that are felt as the stud 74 is moved, the user can determine the distance between the distal elements 18 and can provide the desired degree of coaptation based upon leaflet thickness, geometry, spacing, blood flow dynamics and other factors. Thus, the grooves 82 may provide tactile feedback to the user.

The locking mechanism 106 allows the fixation device 14 to remain in an unlocked position when attached to the interventional tool 10 during grasping and repositioning and then maintain a locked position when left behind as an implant. It may be appreciated, however, that the locking mechanism 106 may be repeatedly locked and unlocked throughout the placement of the fixation device 14 if desired. Once the final placement is determined, the lock line 92 and proximal element lines 90 are removed and the fixation device is left behind.

FIGS. 23, 24A-24B illustrate another embodiment of a locking mechanism 106. Referring to FIG. 23, in this embodiment, the locking mechanism 106 is again disposed between the coupling member 19 and the base 69 of the actuation mechanism 58. The base 69 is connected to the stud 74 which

26

extends through the locking mechanism 106, and connects to an actuator rod which extends through the coupling member 19 and the shaft 12 of the interventional tool 10. The base 69 is also connected to the legs 68 of the actuation mechanism 58 which are in turn connected to the distal elements 18. FIG. 23 also illustrates the proximal elements 16 which manipulate the locking mechanism 106 in this embodiment. The locking mechanism 106 comprises folded leaf structures 124 having overlapping portions 124a, 124b, each folded structure 124 being attached to a proximal element 16. In FIG. 23 and FIG. 24A, the folded structures 124 are shown without the remainder of the locking mechanism 106 for clarity. Proximal elements 16 are flexible and resilient and are biased outwardly. The folded leaf structures 124 include holes 125 (FIG. 24B) in each overlapping portion 124a, 124b so that the stud 74 passes through the holes 125 of the portions 124a, 124b as shown. The locking mechanism includes slots into which ends 123 of the folded leaf structures 124 are fixed. When the proximal elements 16 are in an undeployed position, as in FIG. 23, the folded leaf structures 124 lie substantially perpendicular to the stud 74 so that the holes 125 in each overlapping portion are vertically aligned. This allows the stud 74 to pass freely through the holes and the locking mechanism 106 is considered to be in an unlocked position.

Deployment of the proximal elements 16, as shown in FIG. 24A, tilts the folded leaf structures 124 so as to be disposed in a non-perpendicular orientation relative to the stud 74 and the holes 125 are no longer vertically aligned with one another. In this arrangement, the stud 74 is not free to move due to friction against the holes of the folded leaf structure 124. FIG. 24B provides a larger perspective view of the folded structures 124 in this position. Thus, the locking mechanism 106 is considered to be in a locked position. This arrangement allows the fixation device 14 to maintain an unlocked position during grasping and repositioning and then maintain a locked position when the proximal elements 16 are deployed and the fixation device 14 is left behind as an implant. It may be appreciated, however, that the locking mechanism 106 may be repeatedly locked and unlocked throughout the placement of the fixation device 14 if desired.

FIGS. 25, 26A-26B illustrate another embodiment of a locking mechanism 106. Referring to FIG. 25, in this embodiment, the locking mechanism 106 is again disposed between the coupling member 19 and the base 69 of the actuation mechanism 58. And, the base 69 is connected to the stud 74 which extends through the locking mechanism 106 and connects to an actuator rod which extends through the coupling member 19 and the shaft of the interventional tool 10. FIG. 25 illustrates the proximal elements 16 which manipulate the locking mechanism 106 in this embodiment. The locking mechanism 106 comprises C-shaped structures 128, each C-shaped structure 128 attached to a proximal element 16. The C-shaped structures 128 hook around the stud 74 so that the stud 74 passes through the "C" of each structure 128 as shown in FIGS. 26A-26B. As shown, the structures 128 cross each other and the "C" of each structure 128 faces each other. A spring 130 biases the C-shaped structures into engagement with one another. When the proximal elements are in an undeployed position, as in FIG. 26A, the C-shaped structures 128 are urged into an orientation more orthogonal to the axial direction defined by stud 74, thus bringing the "C" of each structure 128 into closer axial alignment. This allows the stud 74 to pass freely through the "C" of each structure 128. Deployment of the proximal elements 16 outwardly urges the C-shaped structures into a more angular, non-orthogonal orientation relative to stud 74 causing the sidewalls of the "C" of each structure 128 to engage stud 74 more forcefully. In this

27

arrangement, the stud 74 is not free to move due to friction against the "C" shaped structures 128.

D. Additional Embodiments of Fixation Devices

FIGS. 22A-22B illustrate a variation of the fixation device 14 described above in which the distal and proximal elements 16, 18 on each side of the fixation device are movable laterally toward and away from each other to facilitate capture of more widely-separated leaflets or other tissue flaps. The coupling member 19 is bifurcated into two resilient and flexible branches 19A, 19B which are biased outwardly into the position shown in FIG. 22A, but which are movable to the position shown in FIG. 22B. As an alternative, branches 19A, 19B may be more rigid members connected to coupling member 19 by pins or hinges so as to be pivotable toward and away from each other. Each of proximal elements 16 and distal elements 18 are coupled at their proximal ends to one branch 19A or 19B of the coupling member 19. Legs 68 are coupled at their proximal ends to base 69, and therefore stud 74, and at their distal ends to distal elements 18, as described above. Translation of stud 74 distally or proximally relative to coupling member 19 opens or closes distal elements 18 as in formerly described embodiments. A collar 131 is slidably disposed over coupling member 19 and has an annular groove 133 on its inner wall configured to slide over and frictionally engage detents 135 on branches 19A, 19B. A sheath 137 is positioned coaxially over shaft 12 and is slideable relative thereto to facilitate pushing collar 131 distally over coupling member 19.

In use, the embodiment of FIGS. 22A-22B is introduced with distal and proximal elements 16, 18 in the closed position. Collar 131 is pushed distally against, but not over, detents 135 so that branches 19A, 19B are disposed together and fixation device 14 has a minimal profile. When the user is ready to capture the target tissue (e.g. valve leaflets), sheath 137 is retracted so that collar 131 slides proximally over coupling member 19. This allows branches 19A, 19B to separate into the position of FIG. 22A. Actuator 64 is pushed distally so as to open distal elements 18. Tension is maintained on proximal element lines 90 (not shown in FIGS. 22A-22B) so that proximal elements 16 remain separated from distal elements 18. When tissue is positioned between the proximal and distal elements, tension is released on proximal element lines 90 allowing the tissue to be captured between the proximal and distal elements. Sheath 137 may then be advanced distally so that collar 131 urges branches 19A, 19B back together. Sheath 137 is advanced until groove 133 in collar 131 slides over detents 135 and is frictionally maintained thereon as shown in FIG. 22B. Sheath 137 may then be retracted from collar 131. Distal elements 18 may be closed, opened or inverted by advancing or retracting stud 74 via actuator 64, as in the embodiments described above. It should be understood that the embodiment of FIGS. 22A-22B preferably includes a locking mechanism as described above, which has been omitted from the figures for clarity.

In a further alternative of the embodiment of FIGS. 22A-22B, fixation device 14 may be configured to allow for independent actuation of each of the lateral branches 19A, 19B and/or distal elements 18. In an exemplary embodiment, shaft 12 and coupling member 19 may be longitudinally split into two identical halves such that a first branch 19A may be drawn into collar 131 independently of a second branch 19B. Similarly, actuator shaft 64 may be longitudinally split so that each half can slide independently of the other half, thus allowing one of distal elements 18 to be closed independently of the other distal element 18. This configuration permits the user to

28

capture one of the valve leaflets between one of the distal and proximal elements 16, 18, then draw the corresponding branch 19A into the collar 131. The fixation device 14 may then be repositioned to capture a second of the valve leaflets between the other proximal and distal elements 16, 18, after which the second branch 19B may be drawn into collar 131 to complete the coaptation. Of course, the closure of distal elements 18 may occur either before or after branches 19A, 19B are drawn into collar 131.

FIGS. 27-28 illustrate an additional embodiment of the fixation device 14. As shown in FIG. 27, the fixation device 14 includes a coupling member 19 which couples the device 14 to the shaft 12 of the interventional tool 10. Here, the device 14 also includes a top coupler 150 attached to coupling member 19 and a bottom coupler 152 attached to the stud 74 so that the two couplers are axially moveable relative to one another. The distal elements 18 are rotatably attached to the top coupler 150 by upper pins 156 and rotatably attached to the bottom coupler 152 by lower pins 160. When the bottom coupler 152 is advanced, the pins 156, 160 are drawn apart. The upper pins 156 are disposed within slots 158 as shown. When the bottom coupler 152 is advanced distally relative to top coupler 150, pins 156, 160 are drawn apart. Angling of the slots 158 causes the distal elements 18 to rotate toward the coupling member 19 as the pins 156, 160 are drawn apart. Relative movement of the couplers 150, 152 may be achieved by any suitable mechanism including sliding or threading.

FIG. 28 illustrates the fixation device 14 in the closed position. Here, the device 14 has a low profile (width in the range of approximately 0.140-0.160 inches orthogonal to the axial direction defined by shaft 12/stud 74) so that the device 14 may be easily passed through a catheter and through any tissue structures. To open the device 14 the bottom coupler 152 is then retracted or the couplers 150, 152 brought toward one another to rotate the distal elements 18 outward. The components of the fixation device 14 may be formed from stainless steel or other suitable metal, such as by machining, or formed from a polymer, such as by injection molding. In addition, portions of the fixation device 14, particularly the distal elements 18, may be covered with a covering such as described above, to promote tissue ingrowth, reduce trauma, enhance friction and/or release pharmacological agents. Alternatively, the device 14 may have a smooth surface which prevents cellular adhesion thereby reducing the accumulation of cells having potential to form an emboli.

Optionally, the fixation device 14 may include tissue retention features such as barbs 170 and/or bumpers 172, illustrated in FIGS. 29-30. The barbs 170 may extend from the engagement surfaces 50 of the distal elements 18, as shown, and may be present in any number and any arrangement. Thus, the barbs 170 will engage the leaflets or tissue during grasping to assist in holding the tissue either by frictional engagement, minor surface penetration or by complete piercing of the tissue, depending on the length and shape of the barbs 170 selected. Alternatively or in addition, bumpers 172 may extend from the distal elements 18. As shown in FIG. 29, each bumpers 172 may extend from the proximal end 52 of the distal element 18 and curve toward the free end 54 of the distal element 18. Or, as shown in FIG. 30, each bumper 172 may extend from the free end 54 and curve toward the proximal end 52. Bumpers 172 are preferably constructed of a resilient metal or polymer and may have any of various geometries, including a solid thin sheet or a loop-shaped wire form. The bumpers 172 may help to actively engage and disengage tissue from the barbs 170 during opening and closing of the fixation device 14. Further, to assist in grasping a tissue, the engagement surfaces 50 may have any texture or form to

29

increase friction against the grasped tissue. For example, the surfaces **50** may include serrations, scales, felt, barbs, polymeric frictional elements, knurling or grooves, to name a few.

FIG. **31** illustrates the engagement surface **50** having a serrated edge **174** to improve grip on tissue engaged. FIG. **31** also illustrates an embodiment of the fixation device **14** mounted on an interventional tool **10** or delivery catheter for ventricular approach to the mitral valve. Here the device **14** is mounted on the shaft **12** with the engagement surfaces **50** facing distally relative to shaft **12** (and facing upstream relative to the mitral valve). Thus, when the mitral valve is approached from the ventricular side, the engagement surfaces **50** can be pressed against the downstream surfaces of the valve without passing through the valve. It may be appreciated that any of the embodiments of the fixation device **14** described herein may be mounted on shaft **12** in this orientation for approach to any valve or tissue, including embodiments that include both proximal and distal elements.

It may be appreciated that when the fixation device **14** is mounted on the shaft **12** in orientation illustrated in FIG. **31**, the position of the distal elements and the proximal elements are reversed. In such instances it is useful to keep in mind that the distal elements contact the distal surface or downstream surface of the leaflets and the proximal elements contact the proximal surface or upstream surface of the leaflets. Thus, regardless of the approach to the valve and the relative position of the proximal and distal elements on the fixation device, the proximal and distal elements remain consistent in relation to the valve.

FIGS. **32-34** illustrate an additional embodiment of the fixation device **14**. As shown in FIG. **32**, the fixation device **14** includes a coupling member **19**, proximal elements **16** and distal elements **18** which are each connected to a set of base components **186**. The distal elements **18** are connected to the base components **186** (top base component **186a** and a bottom base component **186b**) by extension arms **188**. In this embodiment, each distal element **18** is connected by two extension arms **188** in a crossed arrangement so that one extension arm **188** connects the distal element **18** to the top base component **186a** and the other extension arm **188'** connects the distal element **18** to the bottom base component **186b**. The top base component **186a** can be separated from the bottom base component **186b** by any suitable method which may be torque driven, spring driven or push/pull. Increasing the separation distance between the base components **186** draws the distal elements **18** inward toward the base components **186**, as shown in FIG. **33**. This allows the tissue to be grasped between the distal elements **18** and proximal elements **16** while in an arrangement wherein the distal elements **18** are parallel to each other. This may prevent inconsistent compression of the tissue and may better accommodate tissues or leaflets of varying thicknesses. As shown in FIG. **34**, the distal elements **18** may be drawn together and the proximal elements **16** may be retracted to form a low profile fixation device **14**.

FIGS. **35-39**, **40A-40D**, **41-42**, **43A-43C** illustrate another embodiment of the fixation device **14**. In this embodiment, the device **14** is deliverable in the inverted position and moveable to the open position for grasping of the tissue. FIG. **35** illustrates the fixation device **14** in the inverted position. The fixation device **14** includes a shaft **198**, proximal elements **16** and distal elements **18**. Each distal element **18** has a proximal end **52** rotatably connected to the shaft **198** and a free end **54**. The fixation device **14** also includes an actuator rod **204**, a base **202** and a pair of deployment arms **200** attached to the base **202** as shown. In the inverted position, the extender **204** is extended and deployment arms **200** are disposed between

30

the actuator rod **204** and the distal elements **18**. As shown in FIG. **36**, the actuator rod **204** may be retracted so that the deployment arms **200** press against the distal elements **18**, rotating the distal elements **18** from the inverted position to the open position. The angle of the distal elements **18** may be adjusted by retracting or extending the actuator rod **204** various distances. As shown in FIG. **37**, further retraction of the actuator rod **204** raises the distal elements **18** further.

In the open position, tissue or leaflets may be grasped between the distal elements **18** and proximal elements **16**. FIG. **38** illustrates the proximal elements **16** in their released position wherein the tissue or leaflet would be present therebetween. Hereinafter, the tissue will be referred to as leaflets. In this embodiment, each distal element **18** includes an implant pledget **210**, typically press-fit or nested within each distal element **18**. The implant pledgets **210** will be attached to the leaflets by ties, such as sutures or wires, and will be used to hold the leaflets in desired coaptation. The implant pledgets **210** will then be separated from the fixation device **14** and will remain as an implant.

To attach the implant pledgets **210** to the leaflets, the leaflets and implant pledgets **210** are punctured by fixation tools **220**, as shown in FIG. **39**. The fixation tools **220** extend from the catheter **86**, pass through the leaflets and puncture the implant pledgets **210**. Thus, the pledgets **210** are comprised of a puncturable material, such as structural mesh. The fixation tools **220** are used to deliver an anchor **222** as illustrated in larger view in FIGS. **40A-40D**. FIG. **40A** shows the fixation tool **220** including a sleeve **224** surrounding the fixation tool **220** and an anchor **222** loaded therebetween. In this embodiment, the anchor includes one or more flaps **228** which are held within the sleeve **224**. It may be appreciated that the anchor **222** may have any suitable form. Additional exemplary embodiments of anchors are provided in commonly assigned U.S. patent application Ser. No. 09/894,463 incorporated herein for all purposes. A suture **226** is attached to the anchor **222** and extends through the sleeve **224** or on the outside of the sleeve **224**, as shown, to the catheter **86**. The fixation tools **220** are advanced so that the anchor **222** passes through the leaflet (not shown) and the pledget **210**, as shown in FIG. **41**.

Referring now to FIG. **40B**, the sleeve **224** is then retracted to expose the flaps **228** which releases the anchor **222** from the confines of the sleeve **224**. The flaps **228** extend radially outwardly, illustrated in FIG. **40C**, by spring loading, shape memory or other self-expanding mechanism. Thus, the flaps **228** are positioned against the distal side of the pledget **210**, the suture **226** passing through the pledget **210** and the leaflet, as shown in FIG. **41**. At this point, the pledgets **210** can be removed from the distal elements **18**. By extending the actuator rod **204** distally, the base **202** draws the deployment arms **200** distally which returns the distal elements **18** to the inverted position, as shown in FIG. **42**. Since the pledgets **210** have been pierced by the fixation tools **220** and the anchors **222** have been deployed, the pledgets **210** and the leaflets disengage from distal elements **18** and remain in position. The proximal elements **16** may also be returned to their initial position as shown, using any of various mechanisms as have been described above in connection with other embodiments. Referring now to FIG. **40D**, the fixation tool **220** is then removed while the anchor **222** remains in place with suture **226** attached.

The implant pledgets **210** are then separated from the fixation device **14** and left behind to maintain coaptation of the leaflets in the desired position. FIGS. **43A-43C** illustrate the implant pledgets **210** from various perspective views. FIG. **43A** provides a perspective top view showing that the

31

pledgets 210 are connected by a link 230 that allows the pledgets 210 to be released from one side of the fixation device 14. In addition, the sutures 226 are fixed together, either by knot tying or placement of a suture fastener 232 as shown. It may be appreciated that the suture fastener 232 may have any suitable form. Additional exemplary embodiments of suture fasteners 232 are provided in commonly-assigned U.S. patent application Ser. No. 10/087,004, filed Mar. 1, 2002, which is incorporated herein by reference for all purposes. FIG. 43B provides a perspective bottom view showing the anchor 222 positioned against the bottom side of the pledget 210. Likewise, FIG. 43C provides a perspective side view also showing the anchor 222 positioned against the bottom side of the pledget 210.

FIGS. 44A-44B, 45-46 illustrate another embodiment of the fixation device 14. As shown in FIG. 44A, the fixation device 14 is mounted on the shaft 12 and is comprised of distal elements 18 and a retention clip 36 comprised of a semi-rigid material having a folded shape. The material may be any suitable material providing rigidity with recoiling properties such as various metals or plastics. The folded shape is such that a fold 252 is directed distally and free ends 254 are directed proximally toward the distal elements 18. Penetration elements 256 are disposed near the free ends 254 and directed toward the shaft 12. In addition, an opening 258 is located near the fold 252, as illustrated in FIG. 44B which provides a perspectives view of the device 14. Referring back to FIG. 44A, the fold 252 is attached to an actuator rod 74 which passes through the shaft 12 and an arrow-shaped structure 260 is disposed on the shaft 12 between the free ends 254, proximal to the opening 258, as shown. In this arrangement, the fixation device 14 is advanced through the valve so that the distal elements 18 are disposed below the leaflets. The device may then be retracted proximally to capture the leaflets within the distal elements 18. As shown in FIG. 45, retraction of the actuator rod 74 draws the retention clip 36 toward the distal elements 18 so that the sloping sides of the arrow-shaped structure 260 force the free ends 254 outward, away from the shaft 12. Further retraction of actuator rod 74 results in the sloping sides of arrow shaped structure 260 falling into the opening 258 in retention clip 36, causing retention clip 36 to recoil back to the closed position as shown in FIG. 46, with the free ends 254 extending through the distal elements 18. This allows the penetration elements 256 to penetrate the leaflets (not shown) to secure engagement therewith. The actuator rod 74 is then detached from the retention clip 36 and shaft 12 is detached from distal elements 18 which are left in place to hold the leaflets in a coapted arrangement.

It may be appreciated that the foregoing embodiment may also include proximal elements 16 configured to be positioned on the upstream side of the valve leaflets to assist in the capture and fixation. Such proximal elements may be mounted to shaft 12 so as to be removed following fixation of the leaflets, or the proximal elements may be connected to distal elements 18 and/or retention clip 36 to be implanted therewith.

In further embodiments, the proximal elements may be manipulated to enhance gripping. For example, the proximal elements may be lowered to grasp leaflets or tissue between the proximal and distal elements, and then the proximal elements may be moved to drag the leaflets or tissue into the fixation device. In another example, the proximal elements may be independently lowered to grasp the leaflets or tissue. This may be useful for sequential grasping. In sequential grasping, one proximal element is lowered to capture a leaflet or tissue portion between the proximal and distal elements. The fixation device is then moved, adjusted or maneuvered to

32

a position for grasping another leaflet or tissue portion between another set of proximal and distal elements. In this position, the second proximal element is then lowered to grasp this other leaflet or tissue portion.

IV. Delivery Device

A. Overview of Delivery Device

FIG. 47 provides a perspective view of an embodiment of a delivery device or delivery catheter 300 which may be used to introduce and position a fixation device as described above. The delivery catheter 300 includes a shaft 302, having a proximal end 322 and a distal end 324, and a handle 304 attached to the proximal end 322. A fixation device (not shown) is removably coupleable to the distal end 324 for delivery to a site within the body, typically for endovascular delivery to the mitral valve. Thus, extending from the distal end 324 is a coupling structure 320 for coupling with a fixation device. Also extending from the distal end 324 is an actuator rod 64. The actuator rod 64 is connectable with the fixation device and acts to manipulate the fixation device, typically opening and closing the distal elements. Such coupling to a fixation device is illustrated in FIG. 48.

FIG. 48 illustrates an embodiment of a fixation device 14 coupled to the distal end 324 of the delivery catheter 300. The shaft 302 is shown having a nose 318 near its distal end 324. In this embodiment, the nose 318 has a flanged shape. Such a flanged shape prevents the nose 318 from being retracted into a guiding catheter or introducer as will be discussed in later sections. However, it may be appreciated that the nose 318 may have any shape including bullet, rounded, blunt or pointed, to name a few. Extending from the nose 318 is a compression coil 326 through which the coupling structure 320 and actuator rod 64 pass. The actuator rod 64 is coupleable, as shown, with the stud 74 of the fixation device 14. Such coupling is illustrated in FIG. 49.

FIG. 49 illustrates a portion of the shaft 302 of the delivery catheter 300 and a fixation device 14 which is coupleable with the catheter 300. Passing through the shaft 302 is the actuator rod 64. In this embodiment, the actuator rod 64 comprises a proximal extremity 303 and a distal extremity 328, the distal extremity 328 of which is surrounded by a coil 330. The proximal extremity 303 is typically comprised of stainless steel, nitinol, or Elgiloy®, to name a few, and may have a diameter in the range of 0.010 in. to 0.040 in., preferably 0.020 in. to 0.030 in., more preferably 0.025 in., and a length in the range of 48 to 72 in. The distal extremity 328 may be tapered, is typically comprised of stainless steel, nitinol, or Elgiloy®, to name a few, and may have a diameter in the range of 0.011 to 0.025 in and a length in the range of 4 to 12 in. Such narrowing increases flexibility of the distal end 324 of the actuator rod 64. The actuator rod 64 further comprises a joiner 332 which is attached to the distal extremity 328. The joiner 332 is removably attachable with stud 74 of the fixation device 14. In this embodiment, the joiner 332 has internal threads which mate with external threads on the stud 74 of the fixation device 14. As described previously, the stud 74 is connected with the distal elements 18 so that advancement and retraction of the stud 74, by means of the actuator rod 64, manipulates the distal elements. Likewise, the coupling member 19 of the fixation device 14 mates with the coupling structure 320 of the catheter 300. Thus, the coupling member 19 and coupling structure 320 function as previously described in relation to FIGS. 6A-6B.

Referring back to FIG. 48, the fixation device 14 may also include a locking mechanism which includes a release har-

33

ness 108, as previously described in relation to FIGS. 18-21. Lock lines 92 are connected with the release harness 108 to lock and unlock the locking mechanism 106 as previously described. The lock lines 92 extend through the shaft 302 of the delivery catheter 300 and may connect with the release harness 108 in various arrangements as will be illustrated in later sections. Similarly, proximal element lines 90 extend through the shaft 302 of the delivery catheter 300 and connect with the proximal elements 16. The proximal elements 16 are raised and lowered by manipulation of the proximal element lines 90 as previously described. The proximal element lines 90 may connect with the proximal elements 16 in various arrangements as will be illustrated in later sections.

Referring back to FIG. 47, the handle 304 attached to the proximal end 322 of the shaft 302 is used to manipulate the coupled fixation device 14 and to optionally decouple the fixation device 14 for permanent implantation. As described, the fixation device 14 is primarily manipulated by the actuator rod 64, proximal element lines 90 and lock lines 92. The actuator rod 64 manipulates the distal elements 18, the proximal element lines 90 manipulate the proximal elements 16 and the lock lines 92 manipulate the locking mechanism. In this embodiment, the actuator rod 64 may be translated (extended or retracted) to manipulate the distal elements 18. This is achieved with the use of the actuator rod control 314 which will be described in later sections. The actuator rod 64 may also be rotated to engage or disengage the threaded joiner with the threaded stud 74. This is achieved with the use of the actuator rod handle 316 which will also be described in later sections. Further, the proximal element lines 90 may be extended, retracted, loaded with various amounts of tension or removed with the use of the proximal element line handle 312. And, the lock lines 92 may be extended, retracted, loaded with various amounts of tension or removed with the use of the lock line handle 310. Both of these handles 310, 312 will be described in more detail in later sections. The actuator rod handle 316, actuator rod control 314, proximal element line handle 312 and lock line handle 310 are all joined with a main body 308 within which the actuator rod 64, proximal element lines 90 and lock lines 92 are guided into the shaft 302. The handle 304 further includes a support base 306 connected with the main body 308. The main body 308 is slideable along the support base 306 to provide translation of the shaft 302. Further, the main body 308 is rotateable around the support base 306 to rotate the shaft.

B. Delivery Catheter Shaft

FIG. 50 illustrates a cross-sectional view of the delivery catheter shaft 302 of FIG. 47. In this embodiment, the shaft 302 has a tubular shape with inner lumen 348 and is comprised of a material which provides hoop strength while maintaining flexibility and kink resistance, such as a braided laminated material. Such material may include stainless steel braided or coiled wire embedded in a polymer such as polyurethane, polyester, Pebax, Grilamid TR55, and AESNO to name a few. To provide further support and hoop strength, a support coil 346 is disposed within the lumen 348 of shaft 302 as illustrated in FIG. 50.

Passing through the support coil 346 are a variety of elongated bodies, including tubular guides and cylindrical rods. For example, one type of tubular guide is a compression coil 326 extending through lumen 348 from the proximal end 322 to the distal end 324 of the shaft 302, and the actuator rod 64 extends through the compression coil 326. Therefore, the compression coil typically has a length in the range of 48 to 60 in. and an inner diameter in the range of 0.020 to 0.035 in. to

34

allow passage of the actuator rod 64 therethrough. The actuator rod 64 is manipulable to rotate and translate within and relative to the compression coil 326. The compression coil 326 allows lateral flexibility of the actuator rod 64 and therefore the shaft 302 while resisting buckling and providing column strength under compression. The compression coil may be comprised of 304V stainless steel to provide these properties.

To provide additional tensile strength for the shaft 302 and to minimize elongation, a tension cable 344 may also pass through the support coil 346. The tension cable 344 extends through lumen 348 from the proximal end 322 to the distal end 324 of the shaft 302. Therefore, the tension cable 344 typically has a diameter in the range of 0.005 in. to 0.010 in. and a length in the range of 48 to 60 in. In preferred embodiments, the tension cable 344 is comprised of 304V stainless steel.

In addition, at least one lock line shaft 341 having a tubular shape may be present having a lock line lumen 340 through which lock lines 92 pass between the lock line handle 310 and the locking mechanism 106. The lock line shaft 341 extends through lumen 348 from the proximal end 322 to the distal end 324 of the shaft 302. Therefore, the lock line shaft 341 typically has a length in the range of 48 to 60 in., an inner diameter in the range of 0.016 to 0.030 in., and an outer diameter in the range of 0.018 to 0.034 in. In preferred embodiments, the lock line shaft 341 is comprised of a 304V stainless steel coil however other structures or materials may be used which provide kink resistance and compression strength.

Similarly, at least one proximal element line shaft 343 having a tubular shape may be present having a proximal element line lumen 342. Proximal element lines 90 pass through this lumen 342 between the proximal element line handle 312 and the proximal elements 16. Thus, the proximal element line shaft 343 extends through lumen 348 from the proximal end 322 to the distal end 324 of the shaft 302. Therefore, the proximal element line shaft 343 typically has a length in the range of 48 to 60 in., an inner diameter in the range of 0.016 to 0.030 in., and an outer diameter in the range of 0.018 to 0.034 in. In preferred embodiments, the proximal element line shaft 343 is comprised of a 304V stainless steel coil however other structures or materials may be used which provide kink resistance and compression strength.

In this embodiment, the elongated bodies (compression coil 326 enclosed actuator rod 64, tension cable 344, lock line shaft 342, proximal element line shaft 343) each "float" freely in inner lumen 348 within the support coil 346 and are fixed only at the proximal end 322 and distal end 324 of shaft 302. The lumen 348 is typically filled and flushed with heparinized saline during use. Alternatively or in addition, the lumen 348 may be filled with one or more fillers, such as flexible rods, beads, extruded sections, gels or other fluids. Preferably the fillers allow for some lateral movement or deflection of the elongated bodies within lumen 348 but in some cases may restrict such movement. Typically, the elongated bodies are fixed at the proximal and distal ends of the shaft and are free to move laterally and rotationally therebetween. Such freedom of movement of the elongated bodies provides the shaft 302 with an increased flexibility as the elongated bodies self-adjust and reposition during bending and/or torquing of the shaft 302. It may be appreciated that the elongated bodies may not be fixed at the proximal and distal ends. The elongated bodies are simply unconstrained relative to the shaft 302 in at least one location so as to be laterally moveable within the lumen 348. Preferably the elongated bodies are unrestrained in at least a distal portion of the catheter, e.g.

35

5-15 cm from the distal end 324, so as to provide maximum flexibility in the distal portion.

It may be appreciated, however, that alternate shaft 302 designs may also be used. For example, referring to FIG. 51, in this embodiment the shaft 302 again has a tubular shape with an inner lumen 348 and a support coil 346 disposed within the lumen 348 of shaft 302. Filling the inner lumen 348 within the support coil 346 is an extrusion 334 having lumens through which pass a variety of elongated bodies, including the compression coil 326 enclosed actuator rod 64, tension cable 344, lock line shafts 342, and proximal element line shafts 343, as shown. The support coil 346 and elongated bodies may have the same geometries and be comprised of the same materials as described above in relation to FIG. 50.

Alternatively, as shown in FIG. 52, the shaft 302 may include an internal partition 350 to create multiple lumens within the shaft 302. For example, the partition 350 may have a central lumen 352 for passage of the actuator rod 64, optionally surrounded by the compression coil 326. In addition, the partition 350 may also create at least one lock line lumen 340 for passage of a lock line 92 and at least one proximal element line lumen 341 for passage of a proximal element line 90. Optionally, each of the lumens defined by partition 350 may be lined with a kink-resistant element, such as a coil as in previous embodiments.

FIGS. 52A-52C illustrate embodiments of the nose 318 of the shaft 302. In FIG. 52A, the nose 318 comprises a tip ring 280 and a lock ring 282. In preferred embodiments, Epoxy and PEBAX are deposited between the tip ring 280 and the lock ring 282 to bond them together. The lock ring 282 has a geometry to mate with the tip ring 280 to maintain relative alignment between the two. FIG. 52B illustrates another embodiment of the nose 318 of the shaft 302. Here, the tip ring 280 is covered by a soft tip 284 to provide a more atraumatic tip and a smoother transition to the shaft.

C. Lock Line Arrangements

As mentioned previously, when lock lines 92 are present, the lines 92 pass through at least one lock line lumen 340 between the lock line handle 310 and the locking mechanism 106. The lock lines 92 engage the release harnesses 108 of the locking mechanism 106 to lock and unlock the locking mechanism 106 as previously described. The lock lines 92 may engage the release harnesses 108 in various arrangements, examples of which are illustrated in FIGS. 53A-53C. In each embodiment, two lock line lumens 340 are present within the shaft 302 of the delivery catheter 300 terminating at the nose 318. The lumens 340 are disposed on alternate sides of the actuator rod 64 so that each lumen 340 is directed toward a release harness 108.

FIG. 53A illustrates an embodiment wherein two lock lines 92, 92' pass through a single lock line lumen 340 and are threaded through a release harness 108 on one side of the actuator rod 64 (the actuator rod 64 is shown without surrounding housing such as coupling structure, for clarity). The lock lines 92, 92' are then separated so that each lock line passes on an opposite side of the actuator rod 64. The lock lines 92, 92' then pass through the release harness 108' on the opposite side of the actuator rod 64 and continue together passing through a another single lock line lumen 340'. This lock line arrangement is the same arrangement illustrated in FIG. 48.

FIG. 53B illustrates an embodiment wherein one lock line 92 passes through a single lock line lumen 340, is threaded through a release harness 108 on one side of the actuator rod 64, and is returned to the lock line lumen 340. Similarly,

36

another lock line 92' passes through another single lock line lumen 340', is threaded through a different release harness 108' located on the opposite side of the actuator rod 64, and is returned to the another single lock line lumen 340'.

FIG. 53C illustrates an embodiment wherein both lock lines 92, 92' pass through a single lock line lumen 340. One lock line 92 is threaded through a release harness 108 on one side of the actuator rod 64 and is then passed through another lock line lumen 340' on the opposite side of the actuator rod 64. The other lock line 92' is threaded through another release harness 108' on the other side of the actuator rod 64' and is then passed through the another lock line lumen 340' with the previous lock line 92.

It may be appreciated that a variety of lock line arrangements may be used and are not limited to the arrangements illustrated and described above. The various arrangements allow the harnesses 108 to be manipulated independently or jointly, allow various amounts of tension to be applied and vary the force required for removal of the lock lines when the fixation device is to be left behind. For example, a single lock line passing through one or two lumens may be connected to both release harnesses for simultaneous application of tension.

D. Proximal Element Line Arrangements

As mentioned previously, when proximal element lines 90 are present, the lines 90 pass through at least one proximal element line lumen 342 between the proximal element line handle 312 and at least one proximal element 16. The proximal element lines 90 engage the proximal elements 16 to raise or lower the element 16 as previously described. The proximal element lines 90 may engage the proximal elements 16 in various arrangements, examples of which are illustrated in FIGS. 54A-54B. In each embodiment, two proximal element line lumens 342 are present within the shaft 302 of the delivery catheter 300 terminating at the nose 318. The lumens 342 are disposed on alternate sides of the actuator rod 64 (the actuator rod 64 is shown without surrounding housing such as coupling structure, for clarity) so that each lumen 342 is directed toward a proximal element 16.

FIG. 54A illustrates an embodiment wherein one proximal element line 90 passes through a single proximal element line lumen 342. The proximal element line 90 is threaded through an eyelet 360 of a proximal element 16 on one side of the actuator rod 64, passes over the actuator rod 64 and is threaded through an eyelet 360' of another proximal element 16' on the other side of the actuator rod 64. The proximal element line 90 then passes through another single proximal element line lumen 342'. This proximal element line arrangement is the same arrangement illustrated in FIG. 48.

FIG. 54B illustrates an embodiment wherein one proximal element line 90 passes through a single proximal element line lumen 342, is threaded through an eyelet 360 of a proximal element 16 on one side of the actuator rod 64, and is returned to the proximal element line lumen 342. Similarly, another proximal element line 90' passes through another single proximal element line lumen 342' on the opposite side of the actuator rod 64, and is returned to the another single proximal element line lumen 342'.

It may be appreciated that a variety of proximal element line arrangements may be used and are not limited to the arrangements illustrated and described above. The various arrangements allow the proximal elements to be manipulated independently or jointly, allow various amounts of tension to be applied and vary the force required for removal of the proximal element lines when the fixation device is to be left

37

behind. For example, a single proximal element line passing through one or two lumens in shaft 302 may be used for simultaneous actuation of both proximal elements.

E. Main Body of Handle

FIG. 55 illustrates an embodiment of the handle 304 of the delivery catheter 300. As mentioned previously, the actuator rod handle 316, actuator rod control 314, proximal element line handle 312 and lock line handle 310 are all joined with the main body 304. The handle 304 further includes a support base 306 connected with the main body 308. The main body 308 is slideable along the support base 306 to provide translation of the shaft 302 and the main body 308 is rotateable around the support base 306 to rotate the shaft.

FIG. 56 provides a partial cross-sectional view of the main body 308 of the handle 304 depicted in FIG. 55. As shown, the main body 308 includes a sealed chamber 370 within which the actuator rod 64, proximal element lines 90 and lock lines 92 are guided into the shaft 302. The sealed chamber 370 is in fluid communication with the inner lumen 348 of shaft 302 and is typically filled with saline and flushed with heparin or heparinized saline. The sealed chamber 370 has a seal 372 along its perimeter to prevent leakage and the introduction of air to the chamber 370. Any air in the chamber 370 may be bled from the chamber 370 by one or more luers 374 which pass through the main body 308 into the chamber 370 as illustrated in FIG. 55. In this embodiment, the handle 304 includes two such luers 374, one on each side of the main body 308 (second luer symmetrically positioned on backside of main body 308 in FIG. 55, hidden from view). Referring now to FIG. 56, the sealed chamber 370 also has various additional seals, such as an actuator rod seal 376 which surrounds the actuator rod 64 where the actuator rod 64 enters the sealed chamber 370, and a shaft seal 378 which surrounds the shaft 302 where the shaft 302 enters the sealed chamber 370.

F. Lock Line Handle and Proximal Element Line Handle

As mentioned previously, the lock lines 92 may be extended, retracted, loaded with various amounts of tension or removed using the lock line handle 310. Likewise, the proximal element lines 90 may be extended, retracted, loaded with various amounts of tension or removed using the proximal element line handle 312. Both of these handles 310, 312 may be similarly designed to manipulate the appropriate lines 90, 92 passing therethrough.

FIG. 57 illustrates an embodiment of a lock line handle 310 having lock lines 92 passing therethrough. The lock line handle 310 has a distal end 384, a proximal end 382 and an elongate shaft 383 therebetween. The distal end 382 is positionable within the sealed chamber 370 so that the proximal end 382 extends out of the chamber 370, beyond the main body 308. The free ends of the lock lines 92 are disposed near the proximal end 382, passing through the wall of the handle 310 near a threaded nub 390. The handle 310 further includes a cap 388 which is positionable on the nub 390. Internal threading with the cap 388 mates with the threading on the threaded nub 390 so that the cap 388 holds the free ends of the lock lines 92 between the cap 388 and the nub 390 and/or other portions of the handle 310 by friction. The lock lines 92 pass through a central lumen (not shown) of the elongate shaft 383, extend through the sealed chamber 370 (as shown in FIG. 56) and extend through the shaft 302 to the locking mechanism 106.

38

Disposed near the distal end 384 of the handle 310 is at least one wing 392. In the embodiment of FIG. 57, two wings 392 are present, each wing 392 disposed on opposite sides of the elongate shaft 383. The wings 392 extend radially outwardly and curve proximally so that a portion is parallel to the elongate shaft 383, as shown. It may be appreciated that the wings 392 may alternatively have the shape of solid or continuous protrusions which extend radially and have a portion which is parallel to the elongate shaft 383. The wings 392 are used to hold the lock line handle 310 in a desired position which in turn holds the lock under a desired load of tension, as will be described further below. The handle 310 also includes a finger grip 386 near the proximal end 382 which extends radially outwardly in alignment with the radial extension of the at least one wing 392. Thus, the user may determine the orientation of the wings 392 within the sealed chamber 370 from the orientation of the finger grip 386 outside of the main body 308. The finger grip 386 may also serve an ergonomic purpose to assist in manipulating the handle 310.

The portion of the wings 392 parallel to the elongate shaft 383 have grooves or serrations 394. The serrations 394 are used to apply tension to the lock lines 92. As shown in FIG. 57A, the lock line handle 310 is positioned within a semi-tube 400 which is disposed within the sealed chamber 370. The semi-tube 400 comprises a top half 402 and a bottom half 404, each half 402, 404 having grooves or serrations 406 which mate with the serrations 394 of the wings 392. Thus, when the wings 392 are rotated to mate the serrations 394, 406, as shown in FIG. 58A, the elongate shaft 383 is held in place. Likewise, the wings 392 may be rotated, as shown in FIG. 58B, so that the wings 392 are disposed between the halves 402, 404 and the serrations 394, 406 are disengaged. In this position, the shaft 383 may be translated to apply or release tension in the lock lines 92. Thus, tension in the lines 92 may be adjusted by rotating the shaft 383 to disengage the serrations 394, 406, translating the shaft 383 and then rotating the shaft 383 back to reengage the serrations 394, 406. Alternatively, the finger grip 386 may be pulled to apply tension to the lock lines 92. Pulling the finger grip 386 translates the lock line handle 310 within the semi-tube 400. Such translation is achievable due to angling of the serrations 394, 406 and flexibility of wings 382. However, the angling of the serrations 394, 406 prevents translation in the opposite direction, i.e. by pushing the finger grip 386. Therefore, to release tension from the lock lines 92, the shaft 383 is rotated to disengage the serrations 394, 406, allowing translation of the shaft 383, and then the shaft 383 is rotated back to reengage the serrations 394, 406.

To remove the lock lines 92, the cap 388 is removed from the threaded nub 390 exposing the free ends of the lock lines 92. If one lock line 92 is present having two free ends, continuous pulling on one of the free ends draws the entire length of lock line 92 out of the catheter 300. If more than one lock line 92 is present, each lock line 92 will have two free ends. Continuous pulling on one of the free ends of each lock line 92 draws the entire length of each lock line 92 out of the catheter 300.

It may be appreciated that the proximal element line handle 312 has corresponding features to the lock line handle 310 and operates in the same manner as illustrated in FIGS. 57A, 58A-58B. It may also be appreciated that other mechanisms

39

maybe used for manipulating the lock lines **92** and proximal element lines **90**, such as including buttons, springs, levers and knobs.

G. Actuator Rod Control and Handle

The actuator rod **64** may be manipulated using the actuator rod control **314** and the actuator rod handle **316**. FIG. **59** provides a cross-sectional view of a portion of the handle **304** which includes the actuator rod control **314** and the actuator rod handle **316**. The actuator rod handle **316** is located at the proximal end of the handle **314**. The actuator rod handle **316** is fixedly attached to the proximal end of the actuator rod **64**. The actuator rod **64** is inserted through a collet **426** which is disposed within a holder **428** as shown. The holder **428** has external threads **434** which mate with internal threads **432** of the actuator rod control **314**. Thus, rotation of the actuator rod control **314** causes the holder **428** to translate along the actuator rod control **314** by action of the threading, as will be described in more detail below. The actuator rod control **314** is rotatably coupled with the main body **308** of the handle **304** and is held in place by a lip **430**.

Referring to FIG. **59A**, the actuator rod control **314** may be manually rotated in a clockwise or counter clockwise direction, as indicated by arrow **436**. Rotation of the actuator rod control **314** translates (extends or retracts) the actuator rod **64** to manipulate the distal elements **18** of the fixation device **14**. Specifically, rotation of the actuator rod control **314** causes the external threads **434** of the adjacent holder **428** to translate along the mated internal threads **432** of the actuator rod control **314**. Rotation of the holder **428** itself is prevented by holding pins **424** which protrude from the holder **428** and nest into grooves **438** in the main body **308** of the handle **304**. As the holder **428** translates, each holding pin **424** translates along its corresponding groove **438**. Since the collet **426** is attached to the holder **428**, the collet **426** translates along with the holder **428**. To simultaneously translate the actuator rod **64**, the actuator rod **64** is removably attached to the collet **426** by a pin **422**. The pin **422** may have any suitable form, including a clip-shape which partially wraps around the collet **426** as illustrated in FIG. **59**. Thus, rotation of the actuator rod control **314** provides fine control of translation of the actuator rod **64** and therefore fine control of positioning the distal elements **18**.

Referring to FIG. **59B**, removal of the pin **422**, as shown, allows disengagement of the actuator rod handle **316** and fixedly attached actuator rod **64** from the collet **426**. Once disengaged, the actuator rod **64** may be rotated, as indicated by arrow **440**, by manually rotating the actuator rod handle **316**. As described previously, rotation of the actuator rod **64** engages or disengages the threaded joiner **332** of the delivery catheter **300** from the threaded stud **74** of the fixation device **14**. This is used to attach or detach the fixation device **14** from the delivery catheter **300**. In addition, when the actuator rod **64** is in the disengaged state, the actuator rod **64** may optionally be retracted and optionally removed from the catheter **300** by pulling the actuator rod handle **316** and withdrawing the actuator rod **64** from the handle **304**.

Depending on the application, the location of the target site, and the approach selected, the devices of the invention may be modified in ways well known to those of skill in the art or used in conjunction with other devices that are known in the art. For example, the delivery catheter may be modified in length, stiffness, shape and steerability for a desired application. Likewise, the orientation of the fixation device relative to the delivery catheter may be reversed or otherwise changed. The actuation mechanisms may be changed to be

40

driven in alternate directions (push to open, pull to close, or pull to open, push to close). Materials and designs may be changed to be, for example, more flexible or more rigid. And the fixation device components may be altered to those of different size or shape. Further, the delivery catheter of the present invention may be used to deliver other types of devices, particularly endovascular and minimally invasive surgical devices used in angioplasty, atherectomy, stent-delivery, embolic filtration and removal, septal defect repair, tissue approximation and repair, vascular clamping and ligation, suturing, aneurysm repair, vascular occlusion, and electrophysiological mapping and ablation, to name a few. Thus, the delivery catheter of the present invention may be used for applications in which a highly flexible, kink-resistant device is desirable with high compressive, tensile and torsional strength.

V. Multi-Catheter Guiding System

A. Overview of Guiding System

Referring to FIG. **60**, an embodiment of a multi-catheter guiding system **1** of the present invention is illustrated. The system **1** comprises an outer guide catheter **1000**, having a proximal end **1014**, a distal end **1016**, and a central lumen **1018** therethrough, and an inner guide catheter **1020**, having a proximal end **1024**, distal end **1026** and central lumen **1028** therethrough, wherein the inner guide catheter **1020** is positioned coaxially within the central lumen **1018** of the outer guide catheter **1000**, as shown. The distal ends **1016**, **1026** of catheters **1000**, **1020**, respectively, are sized to be passable to a body cavity, typically through a body lumen such as a vascular lumen. Thus, the distal end **1016** preferably has an outer diameter in the range of approximately 0.040 in. to 0.500 in., more preferably in the range of 0.130 in. to 0.320 in. The central lumen **1018** is sized for the passage of the inner guide catheter **1020**; the distal end **1026** preferably has an outer diameter in the range of approximately 0.035 in. to 0.280 in., more preferably 0.120 in. to 0.200 in. The central lumen **1028** is sized for the passage of a variety of devices therethrough. Therefore, the central lumen **1028** preferably has an inner diameter in the range of approximately 0.026 in. to 0.450 in., more preferably in the range of 0.100 in. to 0.180 in.

FIG. **60** illustrates an interventional catheter **1030** positioned within the inner guide catheter **1020** which may optionally be included in system **1**, however other interventional devices may be used. The interventional catheter **1030** has a proximal end **1034** and a distal end **1036**, wherein an interventional tool **1040** is positioned at the distal end **1036**. In this embodiment, the interventional tool **1040** comprises a detachable fixation device or clip. Optionally, the interventional catheter **1030** may also include a nosepiece **1042** having a stop **1043**, as shown. The stop **1043** prevents the interventional tool **1040** from entering the central lumen **1028** of the inner guide catheter **1020**. Thus, the interventional catheter **1030** may be advanced and retracted until the stop **1043** contacts the distal end **1026** of the inner guiding catheter **1020** preventing further retraction. This may provide certain advantages during some procedures. It may be appreciated that in embodiments which include such a stop **1043**, the interventional catheter **1030** would be preloaded within the inner guide catheter **1020** for advancement through the outer guiding catheter **1000** or both the interventional catheter **1030** and the inner guiding catheter **1020** would be pre-loaded into the outer guiding catheter **1000** for advancement to the target

41

tissue. This is because the stop **1043** prevents advancement of the interventional catheter **1030** through the inner guiding catheter **1020**.

The outer guide catheter **1000** and/or the inner guide catheter **1020** are precurved and/or have steering mechanisms, embodiments of which will be described later in detail, to position the distal ends **1016**, **1026** in desired directions. Precurvature or steering of the outer guide catheter **1000** directs the distal end **1016** in a first direction to create a primary curve while precurvature and/or steering of the inner guide catheter **1020** directs distal end **1026** in a second direction, differing from the first, to create a secondary curve. Together, the primary and secondary curves form a compound curve. Advancement of the interventional catheter **1030** through the coaxial guide catheters **1000**, **1020** guides the interventional catheter **1030** through the compound curve toward a desired direction, usually in a direction which will allow the interventional catheter **1030** to reach its target.

Steering of the outer guide catheter **1000** and inner guide catheter **1020** may be achieved by actuation of one or more steering mechanisms. Actuation of the steering mechanisms is achieved with the use of actuators which are typically located on handles connected with each of the catheters **1000**, **1020**. As illustrated in FIG. 60, handle **1056** is connected to the proximal end **1014** of the outer guide catheter **1000** and remains outside of the patient's body during use. Handle **1056** includes steering actuator **1050** which may be used to bend, arc or reshape the outer guide catheter **1000**, such as to form a primary curve. Handle **1057** is connected to the proximal end (not shown) of the inner guide catheter **1020** and may optionally join with handle **1056** to form one larger handle, as shown. Handle **1057** includes steering actuator **1052** which may be used to bend, arc or reshape the inner guide catheter **1020**, such as to form a secondary curve and move the distal end **1026** of the inner guide catheter **1020** through an angle theta, as will be described in a later section.

In addition, locking actuators **1058**, **1060** may be used to actuate locking mechanisms to lock the catheters **1000**, **1020** in a particular position. Actuators **1050**, **1052**, **1058**, **1060** are illustrated as buttons, however it may be appreciated that these and any additional actuators located on the handles **1056**, **1057** may have any suitable form including knobs, thumbwheels, levers, switches, toggles, sensors or other devices. Other embodiments of the handles will be described in detail in a later section.

In addition, the handle **1056** may include a numerical or graphical display **1061** of information such as data indicating the position the catheters **1000**, **1020**, or force on actuators. It may also be appreciated that actuators **1050**, **1052**, **1058**, **1060** and any other buttons or screens may be disposed on a single handle which connects with both the catheters **1000**, **1020**.

B. Example Positions

FIGS. 61A-61D illustrate examples of positions that the catheters **1000**, **1020** may hold. Referring to FIG. 61A, the outer guide catheter **1000** may be precurved and/or steered into a position which includes a primary curve **1100**. The primary curve **1100** typically has a radius of curvature **1102** in the range of approximately 0.125 in. to 1.000 in., preferably in the range of approximately 0.250 in. to 0.500 in. or forms a curve in the range of approximately 0° to 120°. As shown, when the position includes only a primary curve **1100**, the distal end **16** lies in a single plane X. An axis x, transversing through the center of the central lumen **18** at the distal end **16**, lies within plane X.

42

Referring to FIG. 61B, the inner guide catheter **1020** extends through the central lumen **1018** of the outer guide catheter **1000**. The inner guide catheter **1020** maybe precurved and/or steered into a position which includes a secondary curve **1104**. The secondary curve **1104** typically has a radius of curvature **10600** in the range of approximately 0.050 in. to 0.750 in., preferably in the range of approximately 0.125 in. to 0.250 in. or forms a curve in the range of approximately 0° to 180°. The secondary curve **1104** can lie in the same plane as the primary curve **1100**, plane X, or it can lie in a different plane, such as plane Z as shown. In this example, plane Z is substantially orthogonal to plane X. Axis z, transversing through the center of the central lumen **1028** of the inner guide catheter **1020** at the distal end **1026**, lies within plane Z. In this example, axis x and axis z are at substantially 90 degree angles to each other; however, it may be appreciated that axis x and axis z may be at any angle in relation to each other. Also, although in this example the primary curve **1100** and the secondary curve **1104** lie in different planes, particularly in substantially orthogonal planes, the curves **1100**, **1104** may alternatively lie in the same plane.

Referring now to FIG. 61C, the inner guide catheter **1020** may be further manipulated to allow the distal end **1026** to move through an angle theta **1070**. The angle theta **1070** is in the range of approximately -180° to +180°, typically in the range of -90° to +90°, possibly in the range of -60° to +60°, -45° to +45°, -30° to +30° or less. As shown, the angle theta **1070** lies within a plane Y. In particular, axis y, which runs through the center of the central lumen **1028** at the distal end **1026**, forms the angle theta **1070** with axis z. In this example, plane Y is orthogonal to both plane X and plane Z. Axes x, y, z all intercept at a point within the central lumen **1028** which also coincides with the intersection of planes X, Y, Z.

Similarly, FIG. 61D illustrates movement of the distal end **1026** through an angle theta **1070** on the opposite side of axis z. Again, the angle theta **1070** is measured from the axis z to the axis y, which runs through the center of the central lumen **1016** at the distal end **1026**. As shown, the angle theta **1070** lies in plane Y. Thus, the primary curve **1100**, secondary curve **1104**, and angle theta **1070** can all lie in different planes, and optionally in orthogonal planes. However, it may be appreciated that the planes within which the primary curve **1100**, secondary curve **1104** and angle theta **1070** lie may be mutually dependent and therefore would allow the possibility that some of these lie within the same plane.

In addition, the outer guide catheter **1000** may be preformed and/or steerable to provide additional curves or shapes. For example, as illustrated in FIG. 62A, an additional curve **1110** may be formed by the outer guide catheter **1000** proximal to the primary curve **1100**. In this example, the curve **1110** provides lift or raises the distal end **1016** of the outer guide catheter **1000**, which in turn raises the distal end **1026** of the inner guide catheter **1020**. Such lifting is illustrated in FIG. 62B. Here, the system **1** is shown prior to lifting in dashed line wherein the axis y' passes through the intersection of axis z and axis x'. After application of curve **1110**, the distal portion of the system **1** is lifted in the direction of axis z so that axis x' is raised to axis x'' and axis y' is raised to axis y''. This raises distal end **1026** to a desired height.

The articulated position of the multi-catheter guiding system **1** illustrated in FIGS. 61A-61D and FIGS. 62A-62B is particularly useful for accessing the mitral valve. FIGS. 63A-63D illustrate a method of using the system **1** for accessing the mitral valve MV. To gain access to the mitral valve, the outer guide catheter **1000** may be tracked over a dilator and guidewire from a puncture in the femoral vein, through the inferior vena cava and into the right atrium. As shown in FIG.

43

63A, the outer guide catheter **1000** may be punctured through a fossa F in the interatrial septum S. The outer guide catheter **1000** is then advanced through the fossa F and curved by the primary curve **1100** so that the distal end **1016** is directed over the mitral valve MV. Again, it may be appreciated that this approach serves merely as an example and other approaches may be used, such as through the jugular vein, femoral artery, port access or direct access, to name a few. Positioning of the distal end **1016** over the mitral valve MV may be accomplished by precurvature of the outer guide catheter **1000**, wherein the catheter **1000** assumes this position when the dilator and guidewire are retracted, and/or by steering of the outer guide catheter **1000** to the desired position. In this example, formation of the primary curve **1100** moves the distal end **1016** within a primary plane, corresponding to previous plane X, substantially parallel to the valve surface. This moves the distal end **1016** laterally along the short axis of the mitral valve MV, and allows the distal end **1016** to be centered over the opening O between the leaflets LF.

Referring to FIG. 63B, the inner guide catheter **1020** is advanced through the central lumen **1018** of the outer guide catheter **1000** and the distal end **1026** is positioned so that the central lumen **1028** is directed toward the target tissue, the mitral valve MV. In particular, the central lumen **1028** is to be directed toward a specific area of the mitral valve MV, such as toward the opening O between the valve leaflets LF, so that a particular interventional procedure may be performed. In FIG. 63B, the inner guide catheter **1020** is shown in a position which includes a secondary curve **1104** in a secondary plane, corresponding to previous plane Z. Formation of the secondary curve **1104** moves the distal end **1026** vertically and angularly between the commissures C, directing the central lumen **1028** toward the mitral valve MV. In this position an interventional device or catheter **1030** which is passed through the central lumen **1028** would be directed toward and/or through the opening O. Although the primary curve **1100** and the secondary curve **1104** may be varied to accommodate different anatomical variations of the valve MV and different surgical procedures, further adjustment may be desired beyond these two curvatures for proper positioning of the system **1**.

Referring to FIG. 63C, the distal end **1026** of the inner guide catheter **1020** may be positioned through an angle theta **1070**. This moves the distal end **1026** vertically and angularly through a theta plane, corresponding to previous plane Y. Movement of the distal end **1026** through the angle theta **1070** in either direction is shown in dashed line in FIG. 63B. Such movement can be achieved by precurvature and/or by steering of the catheter **1020**. Consequently, the central lumen **1028** can be directed toward the mitral valve MV within a plane which differs from the secondary plane. After such movements, the inner guide catheter **1020** will be in a position so that the opening of the central lumen **1028** at the end **1016** faces the desired direction. In this case, the desired direction is toward the center of and orthogonal to the mitral valve.

In some instances, it is desired to raise or lower the distal end **1026** so that it is at a desired height in relation to the mitral valve MV. This may be accomplished by precurvature and/or by steering of the outer guide catheter **1000** to form additional curve **1110**. Generally this is used to lift the distal end **1026** above the mitral MV wherein such lifting was illustrated in FIG. 62B.

When the curvatures in the catheters **1000**, **1020** are formed by steering mechanisms, the steering mechanisms may be locked in place by a locking feature. Locking can provide additional stiffness and stability in the guiding system **1** for the passage of interventional devices or catheters

44

1030 therethrough, as illustrated in FIG. 60. The interventional catheter **1030** can be passed through the central lumen **1028** toward the target tissue, in this case the mitral valve MV. Positioning of the distal end **1026** over the opening O, as described above, allows the catheter **1030** to pass through the opening O between the leaflets LF if desired, as shown in FIG. 63D. At this point, any desired procedure may be applied to the mitral valve for correction of regurgitation or any other disorder.

C. Steering Mechanisms

As described previously, the curvatures may be formed in the catheters **1000**, **1020** by precurving, steering or any suitable means. Precuring involves setting a specific curvature in the catheter prior to usage, such as by heat setting a polymer or by utilizing a shape-memory alloy. Since the catheters are generally flexible, loading of the catheter on a guidewire, dilator obturator or other introductory device straightens the catheter throughout the curved region. Once the catheter is positioned in the anatomy, the introductory device is removed and the catheter is allowed to relax back into the precurved setting.

To provide a higher degree of control and variety of possible curvatures, steering mechanisms may be used to create the curvatures and position the catheters. In some embodiments, the steering mechanisms comprise cables or pullwires within the wall of the catheter. As shown in FIG. 64A, the outer guide catheter **1000** may include a pullwire **1120** slidably disposed in lumens within the wall of the catheter **1000** extending to the distal end **1016**. By applying tension to the pullwire **1120** in the proximal direction, the distal end **1016** curves in the direction of the pullwire **1120** as illustrated by arrow **1122**. Likewise, as shown in FIG. 64A, placement of the pullwire **1120** along the opposite side of the catheter **1000** will allow the distal end **1016** to curve in the opposite direction, as illustrated by arrow **1124**, when tension is applied to the pullwire **1120**. Thus, referring to FIG. 64C, diametrically opposing placement of pullwires **1120** within the walls of the catheter **1000** allows the distal end **1016** to be steered in opposite directions. This provides a means of correcting or adjusting a curvature. For example, if tension is applied to one pullwire to create a curvature, the curvature may be lessened by applying tension to the diametrically opposite pullwire. Referring now to FIG. 64D, an additional set of opposing pullwires **1120'** may extend within the wall of the catheter **1000** as shown. This combination of pullwires **1120**, **1120'** allows curvature of the distal end in at least four directions illustrated by arrows **1122**, **1124**, **1126**, **1128**. In this example, pullwires **1120** create the primary curve **1100** of the outer guide catheter **1000** and the pullwires **1120'** create the lift. It may be appreciated that FIGS. 64A-64D also pertain to the inner guide catheter **1020**. For example, in FIG. 64D, pullwires **1120** may create the secondary curve **1104** of the inner guide catheter **1020** and the pullwires **1120'** create the angle theta **1070**.

Such pullwires **1120** and/or pullwires **1120'** and associated lumens may be placed in any arrangement, singly or in pairs, symmetrically or nonsymmetrically and any number of pullwires may be present. This may allow curvature in any direction and about various axes. The pullwires **1120**, **1120'** may be fixed at any location along the length of the catheter by any suitable method, such as gluing, tying, soldering, or potting, to name a few. When tension is applied to the pullwire, the curvature forms from the point of attachment of the pullwire toward the proximal direction. Therefore, curvatures may be formed throughout the length of the catheter depending upon

the locations of the points of attachment of the pullwires. Typically, however, the pullwires will be attached near the distal end of the catheter, optionally to an embedded tip ring **280**, illustrated in FIG. **64E**. As shown, the pullwire **1120** passes through an orifice **286** in the tip ring **280**, forms a loop shape and then passes back through the orifice **286** and travels back up through the catheter wall (not shown). In addition, the lumens which house the pullwires may be straight, as shown in FIGS. **64A-64D**, or may be curved.

D. Catheter Construction

The outer guide catheter **1000** and inner guide catheter **1020** may have the same or different construction which may include any suitable material or combination of materials to create the above described curvatures. For clarity, the examples provided will be in reference to the outer guide catheter **1000**, however it may be appreciated that such examples may also apply to the inner guide catheter **1020**.

In embodiments in which the catheter is precurved rather than steerable or in addition to being steerable, the catheter **1000** may be comprised of a polymer or copolymer which is able to be set in a desired curvature, such as by heat setting. Likewise, the catheter **1000** may be comprised of a shape-memory alloy.

In embodiments in which the catheter is steerable, the catheter **1000** may be comprised of one or more of a variety of materials, either along the length of the catheter **1000** or in various segments. Example materials include polyurethane, Pebax, nylon, polyester, polyethylene, polyimide, polyethyleneterephthalate (PET), polyetheretherketone (PEEK). In addition, the walls of the catheter **1000** may be reinforced with a variety of structures, such as metal braids or coils. Such reinforcements may be along the length of the catheter **1000** or in various segments.

For example, referring to FIG. **65A**, the catheter **1000** may have a proximal braided segment **1150**, a coiled segment **1152** and distal braided segment **1154**. The proximal braided segment **1150** provides increased column strength and torque transmission. The coiled segment **1152** provides increased steerability. The distal braided segment **1154** provides a blend of steerability and torque/column strength. In another example, referring to FIG. **65B**, the outer guiding catheter **1000** has a proximal double-layer braided segment **1151** and a distal braided segment **1154**. Thus, the proximal double-layer segment **1151** comprises a multi-lumen tube **1160** (having steering lumens **1162** for pullwires, distal ends of the steering lumens **1162** optionally embedded with stainless steel coils for reinforcement, and a central lumen **1163**), an inner braided layer **1164**, and an outer braided layer **1166**, as illustrated in the cross-sectional view of FIG. **65C**. Similarly, FIG. **65D** provides a cross-sectional view of the distal braided segment **1154** comprising the multi-lumen tube **1160** and a single braided layer **1168**. In a further example, referring to FIG. **65E**, the inner guiding catheter **1020** comprises a multi-lumen tube **1160** without reinforcement at its proximal end, a single braided layer middle segment **1170** and a single braided layer distal segment **1171**. Each of the single braided layer segments **1170**, **1171** have a multi-lumen tube **1160** and a single layer of braiding **1168**, as illustrated in cross-sectional view FIG. **65F**. However, the segments **1170**, **1171** are comprised of polymers of differing durometers, typically decreasing toward the distal end.

FIG. **65G** illustrates an other example of a cross-section of a distal section of an outer guiding catheter **1000**. Here, layer **1130** comprises 55D Pebax and has a thickness of approximately 0.0125 in. Layer **1131** comprises a 30 ppi braid and

has a thickness of approximately 0.002 in. by 0.0065 in. Layer **1132** comprises 55D Pebax and has a thickness of approximately 0.006 in. Layer **1133** comprises 30 ppi braid and has a thickness of approximately 0.002 in. by 0.0065 in. And finally, layer **1134** comprises Nylon 11 and includes steering lumens for approximately 0.0105 in. diameter pullwires **1120**. Central lumen **1163** is of sufficient size for passage of devices.

FIGS. **65H-65I** illustrate additional examples of cross-sections of an inner guiding catheter **1020**, FIG. **65I** illustrating a cross-section of a portion of the distal end and FIG. **65I** illustrating a cross-section of a more distal portion of the distal end. Referring to FIG. **65H**, layer **1135** comprises 40D polymer and has a thickness of approximately 0.0125 in. Layer **1136** comprises a 30 ppi braid and has a thickness of approximately 0.002 in. by 0.0065 in. Layer **1137** comprises 40D polymer and has a thickness of approximately 0.006 in. Layer **1138** comprises a 40 D polymer layer and has a thickness of approximately 0.0035 in. And finally, layer **1139** comprises a 55D liner. In addition, coiled steering lumens are included for approximately 0.0105 in. diameter pullwires **1120**. And, central lumen **1163** is of sufficient size for passage of devices. Referring to FIG. **65I**, layer **1140** comprises a 40D polymer, layer **1141** comprises a 35D polymer, layer **1142** comprises a braid and layer **1143** comprises a liner. In addition, coiled steering lumens **1144** are included for pullwires. And, central lumen **1163** is of sufficient size for passage of devices.

FIGS. **66A-66C** illustrate an embodiment of a keying feature which may be incorporated into the catheter shafts. The keying feature is used to maintain relationship between the inner and outer guide catheters to assist in steering capabilities. As shown in FIG. **66A**, the inner guide catheter **1020** includes one or more protrusions **1400** which extend radially outwardly. In this example, four protrusions **1400** are present, equally spaced around the exterior of the catheter **1020**. Likewise, the outer guide catheter **1000** includes corresponding notches **1402** which align with the protrusions **1400**. Thus, in this example, the catheter **1000** includes four notches equally spaced around its central lumen **1018**. Thus, the inner guide catheter **1020** is able to be translated within the outer guide catheter **1000**, however rotation of the inner guide catheter **1020** within the outer guide catheter **1000** is prevented by the keying feature, i.e. the interlocking protrusions **1400** and notches **1402**. Such keying helps maintain a known correlation of position between the inner guide catheter **1020** and outer guide catheter **1000**. Since the inner and outer guide catheters **1020**, **1000** form curvatures in different directions, such keying is beneficial to ensure that the compound curvature formed by the separate curvatures in the inner and outer guide catheters **1020**, **1000** is the compound curvature that is anticipated. Keying may also increase stability wherein the curvatures remain in position reducing the possibility of compensating for each other.

FIG. **66B** illustrates a cross-sectional view of the outer guiding catheter **1000** of FIG. **66A**. Here, the catheter **1000** includes a notched layer **1404** along the inner surface of central lumen **1018**. The notched layer **1404** includes notches **1402** in any size, shape, arrangement and number. Optionally, the notched layer **1404** may include lumens **1406**, typically for passage of pullwires **1120**. However, the lumens **1406** may alternatively or in addition be used for other uses. It may also be appreciated that the notched layer **1404** may be incorporated into the wall of the catheter **1000**, such as by extrusion, or may be a separate layer positioned within the catheter **1000**. Further, it may be appreciated that the notched layer **1404** may extend the entire length of the catheter **1000** or one

or more portions of the length of the catheter **1000**, including simply a small strip at a designated location along the length of the catheter **1000**.

FIG. 66C illustrates a cross-sectional view of the inner guiding catheter **1020** of FIG. 66A. Here, the catheter **1020** includes protrusions **1400** along the outer surface of the catheter **1020**. The protrusions **1400** may be of any size, shape, arrangement and number. It may be appreciated that the protrusions **1400** may be incorporated into the wall of the catheter **1020**, such as by extrusion, may be included in a separate cylindrical layer on the outer surface of the catheter **1020**, or the protrusions **1400** may be individually adhered to the outer surface of the catheter **1020**. Further, it may be appreciated that the protrusions **1400** may extend the entire length of the catheter **1000** or one or more portions of the length of the catheter **1020**, including simply a small strip at a designated location along the length of the catheter **1020**.

Thus, the keying feature may be present along one or more specific portions of the catheters **1000**, **1020** or may extend along the entire length of the catheters **1000**, **1020**. Likewise, the notches **1402** may extend along the entire length of the outer guiding catheter **1020** while the protrusions **1400** extend along discrete portions of the inner guiding catheter **1000** and vice versa. It may further be appreciated that the protrusions **1400** may be present on the inner surface of the outer guiding catheter **1000** while the notches **1402** are present along the outer surface of the inner guiding catheter **1020**.

Alternatively or in addition, one or more steerable portions of the catheter **1000** may comprise a series of articulating members **1180** as illustrated in FIG. 67A. Exemplary embodiments of steerable portions of catheters comprising such articulating members **1180** are described in U.S. patent application Ser. No. 10/441,753 incorporated herein by reference for all purposes. FIG. 67B illustrates the outer guide catheter **1000** having a steerable portion comprising articulating members **1180** at its distal end **1016**.

Briefly, referring to FIG. 67A, each articulating member **1180** may have any shape, particularly a shape which allows intermitting or nesting as shown. In addition, it is desired that each member **1180** have the capability of independently rotating against an adjacent articulating member **1180**. In this embodiment, the articulating members **1180** comprise interfitting domed rings **1184**. The domed rings **1184** each include a base **1188** and a dome **1186**. The base **1188** and dome **1186** have a hollow interior which, when the domed rings **1184** are interfit in a series, forms a central lumen **1190**. In addition, the dome **1186** allows each articulating member **1180** to mate against an inner surface of an adjacent domed ring **1184**.

The interfitting domed rings **1184** are connected by at least one pullwire **1120**. Such pullwires typically extend through the length of the catheter **1000** and at least one of the interfitting domed rings **1184** to a fixation point where the pullwire **1120** is fixedly attached. By applying tension to the pullwire **1120**, the pullwire **1120** arcs the series of interfitting domed rings **1184** proximal to the attachment point to form a curve. Thus, pulling or applying tension on at least one pullwire, steers or deflects the catheter **1000** in the direction of that pullwire **1120**. By positioning various pullwires **1120** throughout the circumference of the domed rings **1184**, the catheter **1000** may be directed in any number of directions.

Also shown in FIG. 67A, each intermitting domed ring **1184** may comprise one or more pullwire lumens **1182** through which the pullwires **1120** are threaded. Alternatively, the pullwires **1120** may be threaded through the central lumen **1190**. In any case, the pullwires are attached to the catheter **1000** at a position where a desired curve is to be formed. The

pullwires **1120** may be fixed in place by any suitable method, such as soldering, gluing, tying, welding or potting, to name a few. Such fixation method is typically dependent upon the materials used. The articulating members **1180** may be comprised of any suitable material including stainless steel, various metals, various polymers or co-polymers. Likewise the pullwires **1120** may be comprised of any suitable material such as fibers, sutures, metal wires, metal braids, or polymer braids.

E. Handles

As mentioned previously, manipulation of the guide catheters **1000**, **1020** is achieved with the use of handles **1056**, **1057** attached to the proximal ends of the catheters **1000**, **1020**. FIG. 68 illustrates a preferred embodiment of handles **1056**, **1057**. As shown, handle **1056** is attached to the proximal end **1014** of outer guide catheter **1000** and handle **1057** is attached to the proximal end **1024** of inner guide catheter **1020**. Inner guide catheter **1020** is inserted through handle **1056** and is positioned coaxially within outer guide catheter **1000**. In this embodiment, the handles **1056**, **1057** are not linked together as shown in the embodiment illustrated in FIG. 60. It may be appreciated that such handles **1056**, **1057** may alternatively be connected by external connecting rods, bars or plates or by an additional external stabilizing base. An embodiment of a stabilizing base will be described in a later section. Referring back to FIG. 68, interventional catheter is inserted through handle **1057** and is positioned coaxially within inner guide catheter **1020** and outer guide catheter **1000**.

Each handle **1056**, **1057** includes two steering knobs **1300a**, **1300b** emerging from a handle housing **1302** for manipulation by a user. Steering knobs **1300a** are disposed on a side of the housing **1302** and steering knobs **1300b** are disposed on a face of the housing **1302**. However, it may be appreciated that such placement may vary based on a variety of factors including type of steering mechanism, size and shape of handle, type and arrangement of parts within handle, and ergonomics to name a few.

FIG. 69 illustrates the handles **1056**, **1057** of FIG. 68 with a portion of the housing **1302** removed to reveal the assemblies of the handles. Each knob **1300a**, **1300b** controls a steering mechanism which is used to form a curvature in the attached catheter. Each steering mechanism includes a hard stop gear assembly **1304** and a friction assembly **1306**. Tension is applied to one or more pullwires by action of the hard stop gear assembly to form a curve in a catheter. Tension is maintained by the friction assembly. When tension is released from the one or more pullwires the catheter returns to a straightened position.

FIG. 70 illustrates steering mechanisms within a handle wherein the housing **1302** is removed for clarity. Here, steering knob **1300a** is attached to a hard stop gear assembly **1304** and a friction assembly (not in view) and steering knob **1300b** is attached to a separate hard stop gear assembly **1304** and friction assembly **1306**. Steering knob **1300a** is attached to a knob post **1318** which passes through a base **1308**, terminating in a knob gear wheel **1310**. The knob gear wheel **1310** actuates the hard stop gear assembly **1304**, thereby applying tension to one or more pullwires **1120**.

The knob gear wheel **1310** is a toothed wheel that engages a disk gear wheel **1312**. Rotation of the steering knob **1300a** rotates the knob post **1318** and knob gear wheel **1310** which in turn rotates the disk gear wheel **1312**. Rotation of the disk gear wheel **1312** applies tension to one or more pullwires extending through the attached catheter, in this example the

outer guiding catheter 1000. As shown, the outer guiding catheter 1000 passes through the base 1308, wherein one or more pullwires 1120 extending through the catheter 1000 are attached to the disk 1314. Such attachment is schematically illustrated in FIG. 71. Catheter 1000 is shown passing through base 1308. A pullwire 1120 passing through a steering lumen 1162 in the catheter 1000 emerges from the wall of the catheter 1000, passes through an aperture 1320 in the disk 1314 and is attached to an anchor peg 1316 on the disk 1314. Rotation of the disk 1314 (indicated by arrow 1328) around disk post 1315 by action of the disk gear wheel 1312, applies tension to the pullwire 1120 by drawing the pullwire 1120 through the aperture 1320 and wrapping the pullwire 1120 around the disk 1314 as it rotates. Additional rotation of the disk 1314 applies increasing tension to the pullwire 1120. To limit the amount of tension applied to the pullwire 1120, to limit curvature of the catheter and/or to avoid possible breakage of the pullwire 1120, the rotation of the disk 1314 may be restricted by hard stop peg 1322 which is attached to the disk 1314 and extends into the base 1308.

FIGS. 72A-72B illustrate how the hard stop peg 1322 is used to restrict rotation of disk 1314. FIGS. 72A-72B provide a top view, wherein the disk 1314 is disposed on the base 1308. The anchor peg 1316 is shown with the pullwire 1120 there attached. A groove 1326 is formed in the base 1308 beneath the disk 1314 and forms an arc shape. The hard stop peg 1322 extends from the disk 1314 into the groove 1326 in the base 1308. Referring now to FIG. 72B, rotation of the disk 1314 around knob post 1318, indicated by arrow 1330, draws the pullwire 1120 through the aperture 1320 as previously described, wrapping the pullwire 1120 around the disk 1314. As the disk 1314 rotates, the hard stop peg 1322 follows along the groove 1326, as shown. The disk 1314 continues rotating until the hard stop peg 1322 reaches a hard stop 1324. The hard stop 1324 is positioned in the groove 1326 and prevents further passage of the hard stop peg 1322. Thus, disk 1314 rotation may be restricted to any degree of rotation less than or equal to 360 degrees by positioning of the hard stop 1324.

In some instances, it is desired to restrict rotation of the disk 1314 to a degree of rotation which is more than 360 degrees. This may be achieved with another embodiment of the hard stop gear assembly 1304. Referring now to FIGS. 73A-73B, a portion of such a hard stop gear assembly 1304 is shown. FIG. 73A illustrates the base 1308 and the disk post 1315 positioned therethrough. Also shown in the base 1308 is an aperture 1334 through which the knob post 1318, knob gear wheel 1310 and friction assembly 1306 pass, and a passageway 1336 through which the catheter 1000 passes. In this embodiment of the hard stop gear assembly 1304, a groove 1326 is also present in an arc shape around the disk post 1315, however a ball 1332 is positioned in the groove 1326 rather than a hard stop peg 1322. Disk 1314 is positioned over the groove 1326 and the ball 1332 as shown in FIG. 73B. The disk 1314, illustrated in FIG. 73C, has a groove 1356 in its surface which is positioned adjacent to the base 1308, the groove 1356 having an arc shape similar to the groove 1326 in the base 1308. The ball 1332 is not fixedly attached to the base 1308 or the disk 1314 and is therefore free to move along the channel formed by the groove 1326 in the base 1308 and the groove in the disk 1314.

FIGS. 74A-74F illustrate how rotation of the disk 1314 may be restricted by the ball 1332 to a degree of rotation which is more than 360 degrees. FIGS. 74A-74F illustrate the groove 1326 in the base 1308 wherein the groove 1326 has an arc shape around disk post 1315. The groove 1326 does not form a complete circle; a first groove end 1350a and a second groove end 1350b form a wall which prevent passage of the

ball 1332. It may be appreciated that the groove ends 1350a, 1350b may be any distance apart, shortening the length of the groove 1326 by any amount, and allowing the ball 1332 movement, and hence catheter deflection, to be adjusted to any desired amount. To begin, referring to FIG. 74A, the ball 1332 is positioned within the groove 1326 near the first groove end 1350a. The disk 1314 has a matching groove 1352 (shape illustrated in dashed line) including a first groove end 1354a and a second groove end 1354b. The disk 1314 is positioned over the ball 1332 so that the ball 1332 is near the second groove end 1354b.

Referring now to FIG. 74B, the disk 1314 may be rotated while the ball 1332 remains in place. Here, the disk 1314 has rotated 90 degrees, as indicated by arrow 36000 and the position of the groove ends 1354a, 1354b. Referring now to FIG. 74C, the disk 1314 may be further rotated while the ball 1332 remains in place. Here, the disk 1314 has rotated 270 degrees, as indicated by arrow 36000 and the position of the groove ends 1354a, 1354b. The disk 1314 may continue rotating to 360 degrees, as shown in FIG. 74D, indicated by arrow 36000. Here, the first groove end 1354a in the disk 1314 has contacted the ball 1332 and pushes the ball 1332 along groove 1326 in the base. Referring now to FIG. 74E, the disk 1314 may be further rotated while the ball 1332 is pushed along the groove 1326 in the base 1308 by the first groove end 1354a in the disk 1314. Here, the disk 1314 is shown to have rotated 540 degrees. Referring to FIG. 74F, the disk 1314 rotates until the ball 1332 reaches the second groove end 1350b of the base 1308, providing a hard stop. In this position, the ball 1332 is held between the first groove end 1354a of the disk 1314 and the second groove end 1350b of the base 1308 and further rotation of the disk 1314 is prevented. Thus, the disk 1314 was rotated approximately 660 degrees in this example. Any maximum degree of rotation may be set by positioning of groove ends 1350a, 1350b and/or groove ends 1354a, 1354b. Additionally, in some embodiments, rotation can be limited by adding more than one ball 1332 to the groove 1326, for example, two, three, four, five, six, seven, eight, nine, ten or more balls may be used to limit travel and hence curvature.

It may be appreciated that one or more pullwires 1120 are attached to the disk 1314 in a manner similar to that illustrated in FIG. 71. Therefore, as the disk 1314 rotates, around disk post 1315 by action of the disk gear wheel 1312, tension is applied to the pullwire 1120 by drawing the pullwire 1120 through the aperture 1320 and wrapping the pullwire 1120 around the disk 1314 as it rotates. Additional rotation of the disk 1314 applies increasing tension to the pullwire 1120. Restriction of rotation as described above limits the amount of tension applied to the pullwire 1120, to limit curvature of the catheter and/or to avoid possible breakage of the pullwire 1120.

As mentioned, each steering mechanism includes at least a hard stop gear assembly 1304 and a friction assembly 1306. As described above, tension is applied to one or more pullwires by action of the hard stop gear assembly to form a curve in a catheter. Tension is maintained by the friction assembly. FIG. 75 illustrates an embodiment of a friction assembly 1306. The friction assembly 1306 essentially holds a steering knob, in this example steering knob 1300b, and the associated knob post 1318 in a rotated position. Here, rotation of the knob 1300b and post 1318 rotates attached knob gear wheel 1310. The knob gear wheel 1310 actuates the hard stop gear assembly 1304, thereby applying tension to one or more pullwires 1120. The knob gear wheel 1310 is a toothed wheel that engages a disk gear wheel 1312. Rotation of the steering knob 1300b rotates the knob post 1318 and knob gear wheel

51

1310 which in turn rotates the disk gear wheel **1312**. Rotation of the disk gear wheel **1312** applies tension to one or more pullwires extending through the attached catheter, in this example the outer guiding catheter **1000**.

The steering knob **1300b** and knob post **1318** are held in a rotated position by friction provided by a frictional pad **1370**. The frictional pad **1370** is positioned between ring **1372** attached to the knob post **1318** and a plate **1374** attached to the base **1308**. The knob post **1318** extends from the knob **1300b** through the ring **1372**, the frictional pad **1370** and then the plate **1374**. The plate **1374** has internal threads which mate with threads on the knob post **1318**. As the knob post **1318** rotates, the threads on the post **1318** advance through the threads on the plate **1374**. This draws the ring **1372** closer to the plate **1374**, compressing the frictional pad **1370** therebetween. Frictional pad **1370** may be comprised of any O-ring or sheet material with desirable frictional and compressibility characteristics, such as silicone rubber, natural rubber or synthetic rubbers, to name a few. In preferred embodiments, an EPDM rubber O-ring is used. Reverse rotation of the knob post **1318** is resisted by friction of the frictional pad **1370** against the ring **1372**. The higher the compression of the frictional pad **1370** the stronger the frictional hold. Therefore, as the steering knob **1300b** is rotated and increasing amounts of tension are applied to the pullwires **1120**, increasing amounts of friction are applied to the ring **1372** to hold the knob **1300b** in place.

Manual reverse rotation of the steering knob **1300b** releases tension on the pullwires **1120** and draws the ring **1372** away from the plate **1374** thereby reducing the frictional load. When tension is released from the pullwires **1120** the catheter **1000** returns toward a straightened position.

It may be appreciated that each handle **1056**, **1057** includes a steering mechanism for each curve to be formed in the attached catheter. Thus, as shown in FIG. 69, handle **1056** includes a steering mechanism to form the primary curve **1100** in outer guiding catheter **1000** and a steering mechanism to form the additional curve **1110**. Likewise, handle **1057** includes a steering mechanism to form the secondary curve **1104** in inner guiding catheter **1020** and a steering mechanism to form the angle theta **1070**.

Some curves, such as the primary curve **1100**, secondary curve **1104** and additional curve **1110** each typically vary in curvature between a straight configuration and a curved configuration in a single direction. Such movement may be achieved with single set of a hard stop gear assembly **1304** and a friction assembly **1306**. However, other curves, such as the angle theta **1070**, may be formed in two directions as shown in FIGS. 61C-61D. Such movement is achieved with two sets of the hard stop gear assembly **1304** and the friction assembly **1306**, each set controlling curvature in a single direction.

FIG. 75 illustrates the presence of an additional set of the friction assembly **1306'**. One or more pullwires **1120'**, such as an opposing set as illustrated in FIG. 64D, extending within the wall of the catheter **1000** are attached to the disk **1314'** in the same manner as pullwires **1120** are attached to disk **1314**. The disks **1314**, **1314'** are arranged so that rotation of steering knob **1300b** in one direction applies tension to the pullwires **1120** via disk **1314** and rotation of steering knob **1300b** in the opposite direction applies tension to the pullwires **1120'** via disk **1314'**. Likewise, the additional friction assembly **1306'** is shown having a ring **1372'** attached to the knob post **1318** and a frictional pad **1370'** disposed between the ring **1372'** and the opposite side of the plate **1374**. Therefore, as rotation of the steering knob **1300b** in the opposite direction applies tension

52

to the pullwires **1120'** via disk **1314'**, the frictional pad **1370'** applies tension to the ring **1372'** holding the knob post **1318'** in place.

It maybe appreciated that various other mechanisms may be used for tensioning and holding pullwires **1120** in place. Example mechanisms that may alternatively be used include clutches, ratchets, levers, knobs, rack and pinions, and deformable handles, to name a few.

F. Interventional System

FIG. 76 illustrates an embodiment of an interventional system **3** of the present invention. An embodiment of the multi-catheter guiding system **1** of the present invention is shown comprising an outer guide catheter **1000**, having a proximal end **1014** and a distal end **1016**, and an inner guide catheter **1020**, having a proximal end **1024** and a distal end **1026**, wherein the inner guide catheter **1020** is positioned coaxially within the outer guide catheter **1000**, as shown. In addition, a hemostatic valve **1090** is disposed within handle **1056** or external to handle **1056** as shown to provide leak-free sealing with or without the inner guide catheter **1020** in place. The valve **1090** also prevents back bleeding and reduces the possibility of air introduction when inserting the inner guide catheter **1020** through the outer guide catheter **1000**. An example of a hemostatic valve **1090** is illustrated in FIG. 76A, however any suitable valve or hemostatic valve may be used to provide similar functions. In FIG. 76A, the valve **1090** has a first end **1091**, a second end **1092** and a lumen **1093** there-through. The inner wall of lumen **1093** is preferably tapered toward end **1091** and may further include a plurality of tapered axial channels configured to receive the protrusions **1400** on the inner guide catheter **1020**. The first end **1091** is attached to the outer guide catheter **1000** and the second end **1092** is free. Referring now back to FIG. 76, the distal ends **1016**, **1026** of catheters **1000**, **1020**, respectively, are sized to be passable to a body cavity, typically through a body lumen such as a vascular lumen.

To assist in inserting the fixation device **14** through a hemostatic valve **1090**, a fixation device introducer may be used. For example, when the fixation device **14** is loaded on a delivery catheter **300** and an inner guide catheter **1020**, insertion of the fixation device **14**, delivery catheter **300** and inner guide catheter **1020** through an outer guide catheter **1000** involves passing the fixation device **14** through a hemostatic valve **1090** on the outer guide catheter **1000**. To reduce any trauma to the fixation device **14** by the hemostatic valve **1090**, a fixation device introducer may be used. An embodiment of a fixation device introducer **1420** is illustrated in FIG. 76B. The introducer **1420** includes a loading body **1422** and an insertion endpiece **1424**. The fixation device **14** is loaded into the loading body **1422** and into the insertion endpiece **1424** to approximately the dashed line **1428**. The insertion endpiece **1424** has a split end creating individual split sections **1430**, in this embodiment, four split sections **1430**. By compressing the split sections **1430**, the endpiece **1424** forms a taper. Such a taper is then inserted through a hemostatic valve **1090**, so that the insertion endpiece **1424** creates a smooth passageway through the valve for the fixation device **14**. Once the insertion endpiece **1424** is inserted through the valve **1090**, the fixation device **14**, and attached delivery catheter **300** and inner guide catheter **1020**, may then be advanced through the fixation device introducer **1420**. The fixation device introducer **1420** also includes a hemostatic valve within the loading body **1422** to prevent any backbleeding or leakage through the introducer **1420**.

53

Manipulation of the guide catheters **1000**, **1020** is achieved with the use of handles **1056**, **1057** attached to the proximal ends of the catheters **1000**, **1020**. As shown, handle **1056** is attached to the proximal end **1014** of outer guide catheter **1000** and handle **1057** is attached to the proximal end **1024** of inner guide catheter **1020**. Inner guide catheter **1020** is inserted through handle **1056** and is positioned coaxially within outer guide catheter **1000**.

An embodiment of the delivery catheter **300** of the present invention is inserted through handle **1057** and is positioned coaxially within inner guide catheter **1020** and outer guide catheter **1000**. Therefore, a hemostatic valve **1090** is disposed within handle **1057** or external to handle **1057** as shown to provide leak-free sealing with or without the delivery catheter **300** in place. The valve **1090** functions as described above. The delivery catheter **300** includes a shaft **302**, having a proximal end **322** and a distal end **324**, and a handle **304** attached to the proximal end **322**. A fixation device **14** is removably coupled to the distal end **324** for delivery to a site within the body.

The outer guide catheter **1000** and/or the inner guide catheter **1020** are precurved and/or have steering mechanisms to position the distal ends **1016**, **1026** in desired directions. Precurvature or steering of the outer guide catheter **1000** directs the distal end **1016** in a first direction to create a primary curve while precurvature and/or steering of the inner guide catheter **1020** directs distal end **1026** in a second direction, differing from the first, to create a secondary curve. Together, the primary and secondary curves form a compound curve. Advancement of the delivery catheter **300** through the coaxial guide catheters **1000**, **1020** guides the delivery catheter **300** through the compound curve toward a desired direction, usually in a direction which will position the fixation device **14** in a desired location within the body.

FIG. 77 illustrates portions of another embodiment of an interventional system **3** of the present invention. Handles **1056**, **1057** of the multi-catheter guiding system **1** of the present invention are shown. Each handle **1056**, **1057** includes a set of steering knobs **1300a**, **1300b**, as shown. Manipulation of the guide catheters **1000**, **1020** is achieved with the use of the steering knobs **1300a**, **1300b** attached to the proximal ends of the catheters **1000**, **1020**. Handle **304** of the delivery catheter **300** is also shown, including the proximal element line handle **312**, the lock line handle **310**, the actuator rod control **314** and the actuator rod handle **316**, among other features. The handle **304** is supported by the support base **306** which is connected to the handle **1057**.

It may be appreciated the above described systems **3** are not intended to limit the scope of the present invention. The systems **3** may include any or all of the components of the described invention. In addition, the multi-catheter guiding system **1** of the present invention may be used to introduce other delivery catheters, interventional catheters or other devices. Likewise, the delivery catheter **300** may be introduced through other introducers or guiding systems. Also, the delivery catheter **300** may be used to deliver other types of devices to a target location within the body, including endoscopic staplers, devices for electrophysiology mapping or ablation, septal defect repair devices, heart valves, annuloplasty rings and others.

In addition, many of the components of the system **3** may include one or more hydrophilic coatings. Hydrophilic coatings become slippery when wet, eliminate the need for separate lubricants. Thus, such coatings may be present on the multi-catheter guiding system, delivery catheter, and fixation device, including the proximal elements and distal elements, to name a few.

54

Further, the system **3** may be supported by an external stabilizer base **1440**, an embodiment of which is illustrated in FIG. 78. Stabilizer base **1440** maintains the relative positions of the outer guide, inner guide and delivery catheter during a procedure. In this embodiment, the base **1440** comprises a platform **1442** having a planar shape for positioning on or against a flat surface, such as a table or benchtop. The base **1440** further includes a pair of handle holders **1444**, **1448**, each attached to the platform **1442** and extending upwardly from the platform **1442**, either angularly or perpendicularly. Handle holder **1444** includes a notch **1446** for holding the outer guiding catheter **1000**, as illustrated in FIG. 79, thereby supporting the handle **1056**. FIG. 79 shows the handle **1056** attached to the outer guiding catheter **1000** positioned so that the proximal end **1014** of the outer guiding catheter **1000** rests in the notch **1446**. Referring back to FIG. 78, handle holder **1448** includes an elongate portion **1452** having a trough **1450** and a hooked end **1454**. As shown in FIG. 80, handle **1057** rests on the elongate portion **1452** and the handle **304** rests on hooked end **1454** so that the inner guiding catheter **1020** extends from the handle **1057** to the handle **1056** and continues on within outer guiding catheter **1000**. The handle **304** is additionally supported by support base **306**, as shown.

It may be appreciated that the stabilizer base **1440** may take a variety of forms and may include differences in structural design to accommodate various types, shapes, arrangements and numbers of handles.

G. Kits

Referring now to FIG. 81, kits **1500** according to the present invention comprise any of the components described in relation to the present invention. The kits **1500** may include any of the components described above, such as the outer guide catheter **1000** including handle **1056**, the inner guide catheter **1020** including handle **1057**, the delivery catheter **300** and the fixation device **14** and instructions for use IFU. Optionally, any of the kits may further include any other system components described above, such as various interventional tools **1040**, or components associated with positioning a device in a body lumen, such as a guidewire **1202**, dilator **1206** or needle **1204**. The instructions for use IFU will set forth any of the methods as described above, and all kit components will usually be packaged together in a pouch **1505** or other conventional medical device packaging. Usually, those kit components which will be used in performing the procedure on the patient will be sterilized and maintained within the kit. Optionally, separate pouches, bags, trays or other packaging may be provided within a larger package, where the smaller packs may be opened separately to separately maintain the components in a sterile fashion.

While the foregoing is a complete description of the preferred embodiments of the invention, various alternatives, substitutions, additions, modifications, and equivalents are possible without departing from the scope of the invention. For example, in many of the above-described embodiments, the invention is described in the context of approaching a valve structure from the upstream side—that is, the atrial side in the case of a mitral valve. It should be understood that any of the foregoing embodiments may be utilized in other approaches as well, including from the ventricular or downstream side of the valve, as well as using surgical approaches through a wall of the heart. Moreover, the invention may be used in the treatment of a variety of other tissue structures besides heart valves, and will find usefulness in a variety of

55

tissue approximation, attachment, closure, clamping and ligation applications, some endovascular, some endoscopic, and some open surgical.

Again, although the foregoing invention has been described in some detail by way of illustration and example, for purposes of clarity of understanding, it will be obvious that various alternatives, modifications and equivalents may be used and the above description should not be taken as limiting in scope of the invention which is defined by the appended claims.

What is claimed is:

1. A fixation device for engaging tissue comprising; a pair of fixation elements each having a first end, a free end opposite the first end, and an engagement surface therebetween for engaging the tissue, the first ends being movably coupled together such that the fixation elements are moveable between a closed position wherein the engagement surfaces face each other to an inverted position wherein the engagement surfaces face away from each other; and an actuation mechanism coupled to the fixation elements adapted to move the fixation elements between the closed position and the inverted position; and a pair of gripping elements, each gripping element moveable with respect to one of the fixation elements and being disposed in opposition to one of the engagement surfaces so as to capture tissue therebetween, wherein each fixation element is at least partially concave and each gripping element is at least partially recessed within the fixation element in the deployed configuration, and wherein the gripping elements are movable from an undeployed configuration in which each gripping element is separated from an opposing engagement surface, to a deployed configuration in which the gripping element is closer to the opposing engagement surface.
2. A fixation device as in claim 1, wherein the fixation elements are further moveable to an open position between the closed position and the inverted position.
3. A fixation device as in claim 2, wherein in the open position the engagement surface of one fixation element forms an angle of about 5° up to an angle less than about 180° with the engagement surface of the other fixation element.
4. A fixation device as in claim 2 wherein in the open position the engagement surface of one fixation element forms an angle of more than about 90° up to an angle less than about 180° with the engagement surface of the other fixation element.
5. A fixation device as in claim 1, wherein the gripping elements have frictional features configured to enhance grip on tissue engaged thereby.
6. A fixation device as in claim 1, wherein the gripping elements are movable independently of the fixation elements.
7. A fixation device as in claim 1, wherein the gripping elements are biased toward the engagement surfaces.
8. A fixation device as in claim 1, wherein the gripping elements are approximately parallel to each other in the undeployed configuration.
9. The fixation device of claim 1, further comprising a coupling member for detachably coupling the fixation device to a delivery device.
10. The fixation device of claim 9, wherein the coupling member comprises an outer member having an axial channel, the outer member being coupled to one of either the fixation elements or the actuation mechanism, and an inner member

56

extending slidably through the axial channel and coupled to the other of either the fixation elements or the actuation mechanism.

11. The fixation device of claim 10, wherein the outer member has a mating surface for engagement with the delivery device, the mating surface having a sigmoid shape.

12. The fixation device of claim 1, further comprising a covering on the fixation elements adapted for promoting tissue growth.

13. The fixation device of claim 1, further comprising a coating on the fixation elements adapted for delivering a therapeutic agent.

14. A fixation device as in claim 1, wherein the fixation elements have longitudinal edges between the first end and the free end, the longitudinal edges being curved about a longitudinal axis away from the engagement surfaces.

15. A fixation device as in claim 1, wherein the free ends of the fixation elements curve away from the engagement surfaces about a transverse axis generally parallel to the engagement surface.

16. A fixation device as in claim 15, wherein the free ends of the fixation elements are curved about a second axis not parallel to the transverse axis.

17. A fixation device as in claim 1, wherein in the closed position the engagement surface of one fixation element forms an angle of less than about 0° up to an angle of about 5° with the engagement surface of the other fixation element.

18. A fixation device for engaging tissue comprising:

a pair of fixation elements each having a first end, a free end opposite the first end, and an engagement surface therebetween for engaging the tissue, the first ends being movably coupled together such that the fixation elements are moveable between a closed position wherein the engagement surfaces face each other to an inverted position wherein the engagement surfaces face away from each other; and

an actuation mechanism coupled to the fixation elements adapted to move the fixation elements between the closed position and the inverted position,

wherein the actuation mechanism comprises a pair of link members coupled to the first and second fixation elements whereby moving the link members moves the first and second fixation elements and the actuation mechanism further comprises a coupling member and a stud slidably coupled to the coupling member, the first ends being coupled led to one of either the coupling member or the stud, and the link members being coupled to the other of either the coupling member or the stud and wherein the link members are connected to one of either the coupling member or the stud by a hinge.

19. A fixation device as in claim 18, wherein the link members are connected to the fixation elements by a hinge.

20. A fixation device as in claim 18, wherein the link members are connected to one of either the coupling member or the stud by a pin.

21. A fixation device as in claim 18, wherein the link members are connected to the fixation elements by a pin.

22. The fixation device of claim 18, further comprising a coupling member for detachably coupling the fixation device to a delivery device.

23. The fixation device as in claim 22, wherein the coupling member comprises an outer member having an axial channel, the outer member being coupled to one of either the fixation elements or the actuation mechanism and an inner member extending slidably through the axial channel and coupled to the other of either the fixation elements or the actuation mechanism.

57

24. A fixation device for engaging tissue comprising:
 a pair of fixation elements each having a first end, a free end
 opposite the first end, and an engagement surface there-
 between for engaging the tissue, the first ends being
 movably coupled together such that the fixation ele- 5
 ments are moveable between a closed position wherein
 the engagement surfaces face each other to an inverted
 position wherein the engagement surfaces face away
 from each other;
 an actuation mechanism coupled to the fixation elements 10
 adapted to move the fixation elements between the
 closed position and the inverted position; and
 a locking mechanism adapted to lock the fixation elements
 in a desired position,
 wherein the actuation mechanism comprises a movable 15
 stud coupled to the fixation elements, the locking
 mechanism being configured to frictionally engage the
 stud to prevent movement thereof.
25. A fixation device as in claim 24, wherein the locking
 mechanism comprises a wedging element for frictionally 20
 engaging the stud.
26. A fixation device as in claim 25, further comprising a
 coupling member having a pair of sidewalls, at least one of the
 sidewalls sloping toward the other sidewall, the stud being
 slideable between the sidewalls, the wedging element being 25
 movably disposed between the stud and at least one sidewall.
27. A fixation device as in claim 26, wherein the wedging
 element comprises a rolling element configured to roll along
 the at least one sidewall in engagement with the stud.
28. The fixation device of claim 27, wherein the rolling 30
 element comprises a barbell having a pair of generally cylin-
 drical caps and a shaft therebetween, the shaft being config-
 ured to engage the stud between the caps.
29. The fixation device of claim 24, further comprising an
 unlocking mechanism adapted to unlock the fixation ele- 35
 ments so as to be movable from the desired position.
30. The fixation device of claim 25, further comprising an
 unlocking mechanism adapted to unlock the fixation ele-
 ments so as to be movable from the desired position, the

58

- unlocking mechanism comprising a harness coupled to the
 wedging element, the harness adapted to move the wedging
 element to reduce frictional engagement of the stud.
31. The fixation device of claim 24, further comprising a
 coupling member for detachably coupling the fixation device
 to a delivery device.
32. The fixation device as in claim 31, wherein the coupling
 member comprises an outer member having an axial channel,
 the outer member being coupled to one of either the fixation
 elements or the actuation mechanism, and an inner member
 extending slidably through the axial channel and coupled to
 the other of either the fixation elements or the actuation
 mechanism.
33. A fixation device for engaging tissue comprising:
 a pair of fixation elements each having a first end, a free end
 opposite the first end, and an engagement surface ther-
 ebetween for engaging the tissue, the first ends being
 movably coupled together such that the fixation ele-
 ments are moveable between a closed position wherein
 the engagement surfaces face each other to an inverted
 position wherein the engagement surfaces face away
 from each other;
 an actuation mechanism coupled to the fixation elements
 adapted to move the fixation elements between the
 closed position and the inverted position; and
 a coupling member for detachably coupling the fixation
 device to a delivery device;
 wherein the coupling member comprises an outer member
 having an axial channel, the outer member being
 coupled to one of either the fixation elements or the
 actuation mechanism, and an inner member extending
 slidably through the axial channel and coupled to the
 other of either the fixation elements or the actuation
 mechanism; and
 wherein outer member has a mating surface for engage-
 ment with the delivery device, the mating surface having
 a sigmoid shape.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 7,563,267 B2
APPLICATION NO. : 10/441531
DATED : July 21, 2009
INVENTOR(S) : Goldfarb et al.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:


On the cover page,

Item [*] Notice: Subject to any disclaimer, the term of this patent is extended or adjusted
under 35 USC 154(b) by 1074 days

Delete the phrase "by 1074 days" and insert -- by 1743 days --

Signed and Sealed this

Twenty-fourth Day of August, 2010

A handwritten signature in black ink that reads "David J. Kappos". The signature is written in a cursive, flowing style.

David J. Kappos
Director of the United States Patent and Trademark Office