



US008882755B2

(12) **United States Patent**
Leung et al.

(10) **Patent No.:** **US 8,882,755 B2**
(45) **Date of Patent:** **Nov. 11, 2014**

(54) **ELECTROSURGICAL DEVICE FOR TREATMENT OF TISSUE**

(56) **References Cited**

(75) Inventors: **Mark Leung**, Toronto (CA); **Krishan Shah**, Mississauga (CA); **Laura Conquergood**, Mississauga (CA); **Subashini Chandran**, Toronto (CA)

U.S. PATENT DOCUMENTS

2,526,662	A	10/1950	Hipps et al.
3,477,423	A	11/1969	Griffith
3,732,858	A	5/1973	Banko
3,774,612	A	11/1973	Marco
4,177,797	A	12/1979	Baylis et al.

(Continued)

(73) Assignee: **Kimberly-Clark Inc.**, Mississauga, Ontario (CA)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 506 days.

EP	0438242	A	7/1991
EP	966920		5/2000

(Continued)

(21) Appl. No.: **11/105,527**

(22) Filed: **Apr. 14, 2005**

(65) **Prior Publication Data**

US 2005/0177211 A1 Aug. 11, 2005

Related U.S. Application Data

(63) Continuation-in-part of application No. 10/087,856, filed on Mar. 5, 2002, now Pat. No. 6,896,675.

(60) Provisional application No. 60/604,348, filed on Aug. 25, 2004.

(51) **Int. Cl.**
A61B 18/12 (2006.01)
A61B 18/14 (2006.01)
A61B 18/00 (2006.01)

(52) **U.S. Cl.**
CPC **A61B 18/148** (2013.01); **A61B 2018/00875** (2013.01); **A61B 2018/00023** (2013.01); **A61B 2018/0044** (2013.01)
USPC **606/31**; 606/20; 606/21; 606/22; 606/23; 606/24; 607/96; 607/101

(58) **Field of Classification Search**
USPC 606/20–31; 607/96, 101
See application file for complete search history.

OTHER PUBLICATIONS

Amoretta et al., "Preliminary Communication on a Decompression Probe (Dekompressor1) in Percutaneous Discectomy. Ten Case Reports", Journal of Clinical Imaging 29 (2005) 98-101.

(Continued)


Primary Examiner — Aaron Roane

(74) *Attorney, Agent, or Firm* — Dority & Manning, P.A.

(57) **ABSTRACT**

A novel medical probe assembly, system, and methods for the use thereof to treat tissue are described. The system optionally comprises an energy source, two probe assemblies, and one or more cooling devices to provide cooling to at least one of the probe assemblies. The probe assemblies may be configured in a bipolar mode, whereby current flows preferentially between the probe assemblies. The probe assemblies and system described herein are particularly useful to deliver radio frequency energy to a patient's body. RF energy delivery may be used for various applications, including the treatment of pain, tumor ablation and cardiac ablation.

22 Claims, 10 Drawing Sheets



Medtronic 1001

(56)

References Cited

U.S. PATENT DOCUMENTS

4,369,788 A	1/1983	Goald	6,053,937 A	4/2000	Edwards et al.
4,411,266 A	10/1983	Cosman	6,063,085 A	5/2000	Tay et al.
4,512,344 A	4/1985	Barber	6,073,051 A	6/2000	Sharkey et al.
4,600,014 A	7/1986	Beraha	6,074,386 A	6/2000	Goble et al.
4,649,919 A	3/1987	Thimsen et al.	6,074,389 A	6/2000	Levine et al.
4,699,154 A	10/1987	Lindgren	6,074,412 A	6/2000	Mikus et al.
4,834,729 A	5/1989	Sjostrom	6,083,237 A	7/2000	Huitema et al.
4,857,046 A	8/1989	Stevens et al.	6,095,149 A	8/2000	Sharkey et al.
4,883,458 A	11/1989	Shiber	6,099,514 A	8/2000	Sharkey et al.
4,907,589 A	3/1990	Cosman	6,109,268 A	8/2000	Thapliyal et al.
4,958,625 A	9/1990	Bates et al.	6,113,595 A	9/2000	Muntermann
4,979,939 A	12/1990	Shiber	6,122,549 A	9/2000	Sharkey et al.
5,002,553 A	3/1991	Shiber	6,123,702 A	9/2000	Swanson et al.
5,027,792 A	7/1991	Meyer	6,126,682 A	10/2000	Sharkey et al.
5,074,841 A	12/1991	Ademovic et al.	6,136,014 A	10/2000	Sirimanne et al.
5,084,052 A	1/1992	Jacobs	6,139,545 A	10/2000	Utley et al.
RE34,056 E	9/1992	Lindgren	6,146,380 A	11/2000	Racz et al.
5,167,658 A	12/1992	Ensslin	6,161,048 A	12/2000	Sluijter et al.
5,183,054 A	2/1993	Burkholder et al.	6,183,468 B1	2/2001	Swanson et al.
5,201,729 A	4/1993	Hertzmann	6,197,021 B1	3/2001	Panescu et al.
5,233,515 A	8/1993	Cosman	6,206,876 B1	3/2001	Levine et al.
5,234,000 A	8/1993	Hakky et al.	6,217,573 B1	4/2001	Webster
5,277,201 A	1/1994	Stern	6,228,080 B1	5/2001	Gines
5,334,193 A	8/1994	Nardella	6,228,081 B1	5/2001	Goble
5,342,357 A	8/1994	Nardella	6,237,569 B1	5/2001	Stelzer et al.
5,383,874 A	1/1995	Jackson et al.	6,238,387 B1	5/2001	Miller, III
5,383,884 A	1/1995	Summers	6,241,725 B1	6/2001	Cosman
5,423,799 A	6/1995	Shiu	6,246,912 B1	6/2001	Sluijter et al.
5,423,807 A *	6/1995	Milder	6,258,086 B1	7/2001	Ashley et al.
5,423,811 A	6/1995	Imran et al.	6,259,952 B1	7/2001	Sluijter et al.
5,433,739 A *	7/1995	Sluijter et al.	6,261,311 B1	7/2001	Sharkey et al.
5,437,662 A	8/1995	Nardella	6,264,650 B1	7/2001	Hovda
5,458,596 A	10/1995	Lax et al.	6,264,651 B1	7/2001	Underwood et al.
5,484,400 A	1/1996	Edwards et al.	6,273,861 B1	8/2001	Bates et al.
5,489,161 A	2/1996	Sugita et al.	6,277,112 B1	8/2001	Underwood et al.
5,520,682 A *	5/1996	Baust et al.	6,283,960 B1	9/2001	Ashley
5,536,267 A	7/1996	Edwards et al.	6,283,961 B1	9/2001	Underwood et al.
5,546,161 A	8/1996	Sakai et al.	6,290,715 B1	9/2001	Sharkey et al.
5,569,242 A	10/1996	Lax et al.	6,293,943 B1	9/2001	Panescu et al.
5,571,147 A	11/1996	Sluijter et al.	6,296,636 B1	10/2001	Cheng et al.
5,574,117 A	11/1996	Yoshida et al.	6,309,387 B1	10/2001	Eggers et al.
5,591,187 A	1/1997	Dekel	6,312,428 B1	11/2001	Eggers et al.
5,599,346 A	2/1997	Edwards et al.	6,325,806 B1	12/2001	Fox
5,603,221 A *	2/1997	Maytal	6,355,031 B1	3/2002	Edwards et al.
5,647,871 A	7/1997	Levine et al.	6,355,032 B1	3/2002	Hovda et al.
5,651,780 A	7/1997	Jackson et al.	6,379,348 B1 *	4/2002	Onik
5,658,278 A	8/1997	Imran et al.	6,391,026 B1	5/2002	Hung et al.
5,688,267 A *	11/1997	Panescu et al.	6,416,508 B1	7/2002	Eggers et al.
5,697,927 A	12/1997	Imran et al.	6,432,103 B1	8/2002	Ellsberry et al.
5,718,701 A *	2/1998	Shai et al.	6,451,015 B1	9/2002	Rittman, III et al.
5,735,847 A	4/1998	Gough et al.	6,461,353 B1	10/2002	Baker, Jr. et al.
5,785,705 A	7/1998	Baker	6,464,695 B2	10/2002	Hovda et al.
5,800,481 A	9/1998	Loos	6,468,270 B1	10/2002	Hovda et al.
5,810,804 A	9/1998	Gough et al.	6,468,274 B1	10/2002	Alleyn et al.
5,873,882 A	2/1999	Straub et al.	6,478,793 B1	11/2002	Cosman et al.
5,876,414 A	3/1999	Straub	6,482,204 B1	11/2002	Lax et al.
5,906,612 A *	5/1999	Chinn	6,491,690 B1	12/2002	Goble et al.
5,913,859 A	6/1999	Shapira	6,494,880 B1	12/2002	Swanson et al.
5,916,163 A	6/1999	Panescu et al.	6,500,172 B1	12/2002	Panescu et al.
5,928,159 A	7/1999	Eggers et al.	6,500,173 B2	12/2002	Underwood et al.
5,957,922 A *	9/1999	Imran	6,506,189 B1	1/2003	Rittman, III et al.
5,957,961 A *	9/1999	Maguire et al.	6,517,568 B1	2/2003	Sharkey et al.
5,968,062 A	10/1999	Thomas et al.	6,530,992 B1	3/2003	Yank et al.
5,971,980 A	10/1999	Sherman	6,533,780 B1	3/2003	Laird et al.
5,980,504 A	11/1999	Sharkey et al.	6,540,741 B1	4/2003	Underwood et al.
5,983,141 A	11/1999	Sluijter et al.	6,544,195 B2	4/2003	Wilson et al.
6,007,570 A	12/1999	Sharkey et al.	6,547,810 B1	4/2003	Sharkey et al.
6,015,407 A	1/2000	Rieb et al.	6,557,559 B1	5/2003	Eggers et al.
6,016,809 A	1/2000	Mulier et al.	6,558,381 B2	5/2003	Ingle et al.
6,024,751 A	2/2000	Lovato et al.	6,575,968 B1	6/2003	Eggers et al.
6,032,673 A	3/2000	Savage et al.	6,575,969 B1	6/2003	Rittman et al.
6,033,399 A	3/2000	Gines	6,584,360 B2	6/2003	Francischelli et al.
6,035,238 A	3/2000	Ingle et al.	6,587,731 B1	7/2003	Ingle et al.
6,051,019 A *	4/2000	Dobak, III	6,602,248 B1 *	8/2003	Sharps et al.
6,053,912 A	4/2000	Panescu et al.	6,604,003 B2	8/2003	Fredricks et al.
			6,613,047 B2	9/2003	Edwards
			6,620,155 B2	9/2003	Underwood et al.
			6,645,203 B2	11/2003	Sharkey et al.
			6,645,464 B1	11/2003	Hainfeld

(56)

References Cited**U.S. PATENT DOCUMENTS**

6,652,513 B2 11/2003 Panescu et al.
 6,673,023 B2 1/2004 Pflueger
 6,673,063 B2 1/2004 Brett
 6,702,810 B2 3/2004 McClurken et al.
 6,706,038 B2 3/2004 Francischelli et al.
 6,712,811 B2 3/2004 Underwood et al.
 6,712,813 B2 3/2004 Ellman et al.
 6,712,816 B2 3/2004 Hung et al.
 6,723,091 B2 4/2004 Goble et al.
 6,726,684 B1 4/2004 Woloszko et al.
 6,726,685 B2 4/2004 To et al.
 6,730,081 B1 5/2004 Desai
 6,733,496 B2 5/2004 Sharkey et al.
 6,736,815 B2 5/2004 Ginn
 6,749,605 B2 6/2004 Ashley et al.
 6,749,617 B1 6/2004 Palasis et al.
 6,767,347 B2 7/2004 Sharkey et al.
 6,772,012 B2 8/2004 Woloszko et al.
 6,783,532 B2 8/2004 Steiner et al.
 6,796,982 B2 9/2004 Carmet et al.
 6,821,276 B2 11/2004 Lambrecht et al.
 6,827,716 B2 12/2004 Ryan et al.
 6,832,996 B2 12/2004 Woloszko et al.
 6,832,997 B2 12/2004 Uchida et al.
 6,837,884 B2 1/2005 Woloszko
 6,837,888 B2 1/2005 Ciarrocca et al.
 6,846,314 B2 1/2005 Shapira
 6,878,155 B2 4/2005 Sharkey et al.
 6,896,675 B2 5/2005 Leung et al.
 6,929,640 B1 8/2005 Underwood et al.
 6,997,941 B2 2/2006 Sharkey et al.
 7,097,641 B1 8/2006 Arless et al.
 7,267,683 B2 9/2007 Sharkey et al.
 7,282,061 B2 10/2007 Sharkey et al.
 7,309,336 B2 12/2007 Ashley et al.
 7,400,930 B2 7/2008 Sharkey et al.
 7,593,778 B2 9/2009 Chandran et al.
 2001/0001314 A1 5/2001 Woloszko et al.
 2001/0025176 A1 9/2001 Ellsberry et al.
 2001/0025177 A1 9/2001 Woloszko et al.
 2001/0032002 A1 10/2001 McClurken et al.
 2002/0019626 A1 2/2002 Sharkey et al.
 2002/0032441 A1 3/2002 Ingle et al.
 2002/0072688 A1 6/2002 Burbank et al.
 2002/0128641 A1 9/2002 Underwood et al.
 2002/0138020 A1 9/2002 Pflueger
 2002/0138091 A1 9/2002 Pflueger
 2002/0188290 A1 12/2002 Sharkey et al.
 2002/0188292 A1 12/2002 Sharkey et al.
 2002/0193790 A1 12/2002 Fleischman et al.
 2003/0158545 A1 8/2003 Hovda et al.
 2004/0002746 A1 1/2004 Ryan et al.

2004/0059254 A1 3/2004 Pflueger
 2004/0064137 A1 4/2004 Pellegrino et al.
 2004/0176759 A1 9/2004 Krishnamurthy et al.
 2004/0193151 A1 9/2004 To et al.
 2004/0215181 A1 10/2004 Christopherson et al.
 2005/0177209 A1 8/2005 Leung et al.
 2005/0209530 A1 9/2005 Pflueger
 2005/0234445 A1 10/2005 Conquergood et al.

FOREIGN PATENT DOCUMENTS

EP 1059067 A1 12/2000
 EP 1402838 A1 3/2004
 IT 1246197 11/1994
 JP 11-504539 A 4/1999
 WO 98/17190 A3 4/1998
 WO 99/47058 A3 9/1999
 WO 01/45579 A1 6/2001
 WO 01/62168 A2 8/2001
 WO WO 01/57655 8/2001
 WO 01/74251 A2 10/2001
 WO 03/073948 A2 9/2003
 WO WO 03/073948 9/2003
 WO 2005/110263 11/2005

OTHER PUBLICATIONS

Case et al., "Changes of Intradisc Pressure Versus Volume Change", J. Clin. Laser Med & Surg., Jun. 1995, vol. 13(3), pp. 143-147.
 Choy et al., "B. Fall of Intradiscal Pressure with Laser Ablation", J. Clin. Laser Med & Surg., vol. 13, No. 3, 1995, pp. 149-151.
 Cripton et al., "A Minimally Disruptive Technique for Measuring Intervertebral Disc Pressure in Vitro: Application to the Cervical Spine", J. Biomech, Apr. 2001, vol. 34 (4), 545-549.
 Freemont, "Nerve Ingrowth into Diseased Intervertebral Disc in Chronic Back Pain", The Lancet, 1997, 350, pp. 178-181.
 Houpt, "Experimental Study of Temperature Distributions and Thermal Transport During Radio Frequency Current Therapy of the Intervertebral Disc", Spine, 1996 21(15), 1808-1813.
 McNally et al., "Development and Validation of a New Transducer for Intradiscal Pressure Measurement", J. Biomed. Eng., Nov. 1992, vol. 14(6) 495-498.
 Panjabi et al., "Intrinsic Disc Pressure as a Measurement of Integrity of the Lumbar Spine", Spine, Aug. 1988, vol. 13(8) 913-977.
 Wilke et al., "New in Vivo Measurements of Pressures in the Intervertebral Disc in Daily Life", Spine, Apr. 1999, vol. 15:24(8), 913-977.
 International Preliminary Report on Patentability with Written Opinion from PCT/CA2005/001297—6 pages.
 Ferrante, Michael F. "Radiofrequency sacroiliac joint denervation for sacroiliac syndrome". Regional Anesthesia and Pain Medicine. 2001, 26(2), 137-142.

* cited by examiner




FIG.1



FIG. 2A



FIG. 2B



FIG. 2C



FIG. 2D



FIG. 2E



FIG. 2F




FIG. 3A




FIG. 3B




FIG.4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7




FIG. 8




FIG. 9A




FIG. 9B




FIG. 10




FIG.11A




FIG.11B




FIG.12A




FIG.12B

1

ELECTROSURGICAL DEVICE FOR TREATMENT OF TISSUE

REFERENCES TO PARENT AND CO-PENDING APPLICATIONS

This application is a continuation-in-part of U.S. application Ser. No. 10/087,856, filed Mar. 5, 2002 now U.S. Pat. No. 6,896,675 and claims the benefit of U.S. provisional application No. 60/604,348, filed Aug. 25, 2004.

TECHNICAL FIELD

The present invention relates to a medical device, system and method for applying energy, particularly radio frequency electrical energy, to a patient's body.

BACKGROUND OF THE ART

The human intervertebral junction is characterized principally by an intervertebral disc interposed between adjacent vertebral surfaces. The size and configuration of discs vary between the six discs of the cervical region, the twelve discs of the thoracic region, six of the lumbar region and one disc between the sacrum and coccyx.

Intervertebral discs are neither homogeneous nor static. Changes to a disc can affect the vertebral column activity significantly. The intervertebral disc is a complex structure where its dynamic properties result from the interaction of a central, gelatinous nucleus pulposus encircled by a tough, fibrous, semielastic annulus fibrosus. Further, thin cartilage endplates and vertebral body ring apophyseal attachments of the annulus fibrosus join the disc to the vertebrae cranial and caudal to the disc. Although the nucleus pulposus is gelatinous and somewhat fluid while the annulus fibrosus comprises circularly arranged fibers, the border between these components is not distinct in a healthy adult disc. Any distinction is less apparent in a damaged disc where tissues are intermingled in a gradual transition layer.

The annulus fibrosus is composed of concentric layers of fibrocartilage, in which collagen fibers are arranged in parallel strands running obliquely between vertebral bodies. The inclination is reversed in alternate layers thereby crossing over each other obliquely. In children and adolescents, the nucleus pulposus is an amorphous colloidal mass of gelatinous material containing glycosaminoglycans, collagen fibrils, mineral salt, water and cellular elements. The nucleus pulposus has an important function in nutrition of the disc and contributes to the mechanical ability of the disc to act as a shock absorber and allow flexibility. The nucleus pulposus is normally under pressure and is contained within an ovoid cavity formed laterally by the annulus fibrosus and bounded by thin plates of hyaline cartilage endplates covering the adjacent vertebrae.

The intervertebral discs form about one-quarter the length of the vertebral column in a healthy adult human. Discs are thickest in the cervical and lumbar regions, where the movements of the vertebral column are greatest. The vertebral column, including the intervertebral discs, undergo various morphological and biochemical changes over time, such as dehydration of the discs and concaving vertebral bodies. As a result, the size and configuration of the disc components vary considerably from person to person.

Lower back injuries and chronic back pain are a major health problem resulting not only in a debilitating condition for the patient, but also in the consumption of a large proportion of funds allocated for health care, social assistance and

2

disability programs. Disc abnormalities and pain may result from trauma, repetitive use in the workplace, metabolic disorders, inherited proclivity or aging. The existence of adjacent nerve structures and innervation of the disc are very important issues in respect to patient treatment for back pain.

Common disorders of the intervertebral disc include localized tears or fissures in the annulus fibrosus; disc herniations with contained or escaped extrusions of the nucleus pulposus; and chronic circumferential bulging of discs. For most patients, however, a well-defined abnormality cannot be found to solely explain the cause of the low back pain, making treatment and pain management very difficult. Since isolating a specific anatomic disorder as the sole cause of pain is rare, most patients are merely treated symptomatically to reduce pain, rather than receiving treatment to eliminate the cause of the condition.

One course of pain may be attributed to the structure of the annulus fibrosus. The annulus fibrosus is thinner nearer to the posterior than to the anterior margin of the disc, and many disc ruptures occur in the posterior region thereby exerting pressure on the adjacent nerve fibers causing pain. The pain experienced by the disc exerting pressure on the adjacent nerves is characterized by referred pain, or pain felt predominantly elsewhere in the body where the affected nerve travels. A common example of this is sciatica where an intervertebral disc exerts pressure on the sciatic nerve.

Another cause of pain resulting from disc pathology is chemically-induced pain. The nucleus pulposus contains chemicals that may induce pain if contact is made with certain nerve structures. If an intervertebral disc is herniated severely enough that a portion of the nucleus pulposus is extruded from the disc, and the portion comes in contact with an adjacent nerve, chemically-induced pain can be felt. This is also a cause of sciatica.

Increasingly, evidence suggests that the source of back pain in many patients is a result of nerves within the degenerated disc itself or nerves that have grown into the disc in concordance with disc injury. For example, as documented by Jonathan C. Hout, B.A., Edison S. Conner, M.D., and Eric W. McFarland in "Experimental Study of Temperature Distributions and Thermal Transport During Radio frequency Current Therapy of the Intervertebral Disc", *Spine*. 1996; 21 (15), 1808-1813, afferent innervation of the outer half of the annulus fibrosus has been established whereas the nucleus pulposus contains no nerves or blood vessels. Pain response has been widely reported in response to specific stimulation of the outer layers of the annulus fibrosus. In another study documented by A. J. Freemont, "Nerve ingrowth into diseased intervertebral disc in chronic back pain", *The Lancet*. 1997; 350, 178-181, nociceptive nerves were found ingrown deeper into the disc, as far as the nucleus pulposus, in association with disc degeneration. The pain experienced from nerves in a damaged intervertebral disc is more localized to the spine. The stimulation can be both mechanical and chemical. Some patients may feel a combination of back pain and referred pain indicating that pain is being transmitted both from nerves in the disc and from impinged nerves adjacent to the disc. It appears that the disc is devoid of temperature-sensing neurological structures, possibly due to the fact that the disc is at core body temperature, and only mechanical and chemical stimulus-sensing nociceptors exist in the disc.

Where patients are diagnosed with clear chronic discogenic pain (i.e. pain originating from a disc), complete surgical removal of the intervertebral disc (called discectomy) and fusion of the adjacent vertebrae is often carried out with success rates over 80% in measurable pain reduction after surgery. Such major surgical procedures are highly invasive,

expensive and involve significant risk. Furthermore motion is impeded once the vertebrae are fused and there may be adverse mechanical effects on the adjacent remaining discs.

To alleviate some of the disadvantages of open-surgery discectomy, percutaneous methods of removing the disc or part of the disc have been practiced. Methods that remove part of the nucleus pulposus are designed to decrease the volume in order to reduce internal disc pressure thus reducing external pressure exerted on adjacent nerves. Examples of such methods that include mechanical means can be found in, for example, U.S. Pat. No. 4,369,788 to Goald that describes the use of a mechanical device for use in microlumbar discectomy, and in U.S. Pat. No. 5,201,729 to Hertzmann et al. that describes a percutaneous method of discectomy using a laser. Other methods of removing the disc or part of the disc include chemically dissolving the nucleus pulposus using the enzyme Chymopapain. U.S. Pat. No. 6,264,650 to Hovda et al. describes a method of vaporizing a portion of the nucleus pulposus using radio frequency electrical current. These prior art methods have shown variable success and there are several advantages of percutaneous procedures over open surgical discectomy and vertebral fusion including less trauma to the patient, preserved spinal movement, less disruptive effect on adjacent discs, less risk of infection and less risk of accidental injury. However, these methods involve removing a portion of the nucleus pulposus, which is essential to the maintenance of the disc. Further, the damaged annulus fibrosus is not treated.

Due to the pain reduction success of surgical discectomy, less drastic means of denervating rather than surgically removing the disc are of significant interest. To denervate is to intervene with the transmission of a sensory signal in a nerve. A denervated disc does not cause discogenic pain and the disc is left intact to preserve its mechanical function. Denervating the disc especially by using percutaneous probes is much less invasive, less costly and less risky. The procedure is also simpler to administer and does not require the fusing of adjacent vertebrae thereby better preserving the patient's freedom of movement.

A minimally invasive technique of delivering high-frequency electrical current has been shown to relieve localized pain in many patients. Generally, the high-frequency current used for such procedures is in the radio frequency (RF) range, i.e. between 100 kHz and 1 GHz and more specifically between 300-600 kHz. The RF electrical current is typically delivered from a generator via connected electrodes that are placed in a patient's body, in a region of tissue that contains a neural structure suspected of transmitting pain signals to the brain. The electrodes generally include an insulated shaft with an exposed conductive tip to deliver the radio frequency electrical current. Tissue resistance to the current causes heating of tissue adjacent resulting in the coagulation of cells (at a temperature of approximately 45° C. for small unmyelinated nerve structures) and the formation of a lesion that effectively denervates the neural structure in question. Denervation refers to a procedure whereby the ability of a neural structure to transmit signals is affected in some way and usually results in the complete inability of a neural structure to transmit signals, thus removing the pain sensations. This procedure may be done in a monopolar mode where a second dispersive electrode with a large surface area is placed on the surface of a patient's body to complete the circuit, or in a bipolar mode where a second radio frequency electrode is placed at the treatment site. In a bipolar procedure, the current is preferentially concentrated between the two electrodes.

In order to extend the size of a lesion, radio frequency treatment may be applied in conjunction with a cooling mechanism, whereby a cooling means is used to reduce the

temperature of the tissue in the vicinity of an energy delivery device, allowing a higher voltage to be applied without causing an unwanted increase in local tissue temperature. The application of a higher voltage allows regions of tissue further away from the energy delivery device to reach a temperature at which a lesion can form, thus increasing the size/volume of the lesion

The treatment of pain using high-frequency electrical current has been applied successfully to various regions of patients' bodies suspected of contributing to chronic pain sensations. For example, with respect to back pain, which affects millions of individuals every year, high-frequency electrical treatment has been applied to several tissues, including intervertebral discs, facet joints, sacroiliac joints as well as the vertebrae themselves (in a process known as intraosseous denervation). In addition to creating lesions in neural structures, application of RF energy has also been used to treat tumors throughout the body.

In an effort to reduce back pain through early intervention techniques, some investigators have focused upon nerves contained within the vertebral bodies which are adjacent to the intervertebral discs. For example, in PCT Patent Publication No. WO 01/0157655, Heggeness discloses ablating nerves contained within the vertebral body (intraosseous nerves) by first boring into the vertebral body with a nerve ablation device, placing the tip of the device in close proximity to the nerve, and then ablating the nerve using the tip. However, previous techniques fail to describe how to effectively carry out nerve ablation when the precise location of the intraosseous nerve is unknown, or when the electrode tip cannot be maneuvered relatively close to the intraosseous nerve.

With respect to the intervertebral disc itself, U.S. Pat. No. 5,433,739 to Sluijter et al. describes a method of relieving back pain through percutaneous insertion of a needle or electrode into the center of the intervertebral disc within the nucleus pulposus under fluoroscopy or other imaging control. The U.S. Pat. No. 5,433,739 describes the heating of the outer layers of the annulus fibrosus to a temperature that is lethal to the nerve structures thereby denervating the disc to relieve discogenic pain. The temperature of the tissue is increased by applying high frequency electric current through the tissue.

It is well known to those skilled in the art that percutaneous access to an intervertebral lumbar disc involves either a posterolateral approach or an anterior approach. The anterior approach is more invasive than the posterolateral approach because of the organs in the abdominal and pelvic cavities. The most common percutaneous approach to the lumbar disc, to those skilled in the art, is to insert a needle or tube posterolateral to the disc, just lateral of the zygapophyseal joint, inferior to the spinal nerve and into the posterolateral region of the annulus fibrosus.

In accordance with U.S. Pat. Nos. 5,980,504; 6,007,570; 6,073,051; 6,095,149; 6,099,514; 6,122,549; 6,126,682; 6,258,086 B1; 6,261,311 B1; 6,283,960 B1; and 6,290,715 B1 ("the Sharkey et al. patents") to Sharkey et al. to permit percutaneous access to the posterior half of the nucleus or to the posterior inner wall of the disc, a flexible heating element may be inserted into the nucleus pulposus through a hollow tube that has been inserted through the annulus fibrosus. The flexible heating element has sufficient rigidity to be advanced longitudinally under force through the nucleus pulposus while having sufficient flexibility to be compliant to the inner wall of the annulus fibrosus. The heating element is guided by sliding contact with the inner wall and ideally should not puncture or damage the annulus fibrosus during positioning. Another embodiment disclosed in U.S. Pat. No. 6,258,086 B1

5

is a flexible probe that contains an activation element on the distal portion that changes the shape of the probe once it is in the nucleus pulposus. According to the Sharkey et al. patents, the flexible heating elements operate to denervate the outer layers of the annulus fibrosus as well as modulate the collagen in the annulus fibrosus by applying heat. Raising the temperature above about 60° C. will break structural bonds of collagen fibers causing them to contract and tighten. This collagen-tightening effect is lost once the temperature of the collagen is raised above about 75° C. where the fibers loosen, resulting in zero net volume change.

There is interest among researchers that the application of high frequency current without a rise in temperature alters nerve function to relieve pain. Use of high frequency current without heating to relieve pain by modifying neural tissue is described in U.S. Pat. Nos. 5,983,141; 6,161,048; 6,246,912; and 6,259,952 ("the Sluijter et al. patents") to Sluijter et al. These patents describe the use of a modified signal wave that includes rest periods to allow heat to dissipate. The modified high frequency signal is applied to the patient using a single active electrode and a ground electrode attached to the skin of the patient. These disclosures (the Sluijter et al. patents) do not discuss using high frequency current to increase collagen production nor do they discuss this application in the intervertebral disc. The disclosures that are specifically designed for treatment of intervertebral discs (the Sharkey et al. patents; U.S. Pat. No. 5,433,739 of Sluijter et al.; and Finch PCT publication number WO 01/45579) do not discuss the application of high frequency current without a rise in temperature to alter nerve function to relieve pain or to cause collagen production to increase. The advantages of non-thermal application of high frequency electrical current to treat intervertebral discs include reduced risk of thermal damage, increased production of collagen to strengthen the annulus fibrosus, and reduced discogenic pain while stimulating the healing processes.

The above referenced publications describe the use of monopolar devices for treatment procedures and are therefore restricted by the limitations of using a monopolar probe. For example, since energy is primarily concentrated around the lone electrode in a monopolar device, precise knowledge of the location of the tissue to be treated is required. In contrast, in a bipolar procedure, the energy is concentrated between two electrodes allowing a tissue to be affected by the treatment procedure provided it is located substantially between the electrodes. The use of two electrodes in a bipolar configuration also allows for the creation of a more uniform lesion than with a single electrode where the energy is concentrated at the surface of the electrode.

Thus, it would be beneficial to have a device and a system that overcomes some or all of the limitations of the prior art.

SUMMARY OF THE INVENTION

There is a continued need for improvement in systems used for RF treatment of bodily tissue. Specifically, it would be beneficial to incorporate cooled probes and temperature and impedance monitoring concepts into an RF treatment system. In addition, the system should be capable of providing newer treatment modalities, such as bipolar RF. Finally, the probes used in the system should be relatively compact while still providing the benefits and advantages mentioned herein. Thus, the present invention attempts to overcome some or all of the deficiencies in the prior art.

In accordance with a first aspect of the present invention, a medical probe assembly for delivering energy to a patient's body is provided. The probe assembly optionally comprises

6

an elongate member having a distal region and a proximal region and defining a lumen therebetween, an energy delivery device, comprising a protrusion, associated with the distal region of the elongate member and a temperature sensor associated with the protrusion of the energy delivery device. The temperature sensor may, for example, be selected from the group consisting of a thermocouple, a thermistor, a thermometer and an optical fluorescent sensor. In addition, if the temperature sensor is a thermocouple, the protrusion may be a component of the thermocouple.

As a feature of this aspect of the present invention, the probe assembly may further comprise a means of delivering a fluid to, and removing a fluid from, at least a portion of the probe assembly. For example, at least two tubular members may be disposed within the lumen for delivering a fluid to and removing a fluid from the energy delivery device. The tubular members may be hypotubes and the fluid delivered to the energy delivery device may serve to reduce the temperature of tissue surrounding the energy delivery device. The tubular members may be located adjacent to each other and they may be coupled to another two flexible tubular members associated with the proximal region of the elongate member.

As additional features of this aspect of the present invention, the probe assembly may further comprise at least one secondary temperature sensor. This temperature sensor may also be selected from the group consisting of a thermocouple, a thermistor, a thermometer and an optical fluorescent sensor and may be located at any location of the probe assembly. For example, the secondary temperature sensor may be located at the distal region of the elongate member, proximal from the temperature sensor associated with the protrusion of the energy delivery device. The secondary temperature sensor may also be located on an optional introducer tube or on a separate elongate member inserted into a patient's body. In addition, the probe assembly may comprise a thermal insulator for thermally insulating at least one of the temperature sensors.

The probe assembly may also comprise at least one marker, for example, a radiopaque marker, a visible marker or a tactile marker. In addition, the probe assembly may comprise an active shape control mechanism for directing at least a portion of the distal region of the elongate member as it is advanced through said patient's body. Furthermore, the probe assembly may comprise a flow impeding structure that may be useful to restrict circulation of a fluid to a specific portion of the probe assembly.

In accordance with a second aspect of the present invention, a system for delivering energy to a patient's body is provided. The system optionally comprises (i) an energy source (ii) at least two probe assemblies, each probe assembly comprising an elongate member having a distal region and a proximal region and defining a lumen therebetween, an energy delivery device associated with said distal region of said elongate member, said energy delivery device comprising a protrusion, and a temperature sensor associated with the protrusion.

As a feature of this aspect of the present invention, the system may further comprise an apparatus coupled to at least two of the probe assemblies, the apparatus being operable to reduce a temperature of the probe assemblies to which it is coupled. Furthermore, the system may comprise a controller operable to control an operation of the apparatus with respect to each of the probe assemblies to which the apparatus is coupled, wherein the operation of the apparatus for one probe to which the apparatus is coupled is independent of the operation of the apparatus for any other probe to which the apparatus is coupled. As an additional feature, the apparatus may

comprise at least one peristaltic pump for delivering a cooling fluid to the probe assemblies to which it's coupled. In addition, each of the probe assemblies to which the apparatus is coupled may further comprise at least two tubular members disposed within the lumen for delivering a fluid to and removing a fluid from the energy delivery device.

In accordance with a third aspect of the present invention, a method of treating tissue of a patient's body is provided. The method optionally comprises the following steps: (i) providing an energy source and first and second probe assemblies, wherein each of the probe assemblies comprises an elongate member having a distal region and a proximal region and defining a lumen therebetween, an energy delivery device associated with the distal region of the elongate member, the energy delivery device comprising a protrusion, and a temperature sensor associated with the protrusion; (ii) inserting the energy delivery devices of the first and second probe assemblies into spaced-apart treatment sites for the tissue; (iii) delivering energy from the energy source to the tissue through said energy delivery devices; and (iv) measuring a temperature using at least one of the temperature sensors. As a feature of this aspect, the method may further comprise a step of controlling the delivery of energy based on the temperature measured by the temperature sensors.

The tissue being treated may, for example, be spinal tissue and may be selected from the group consisting of an intervertebral disc and a vertebra or portions thereof. Furthermore, the energy source may be a radio-frequency generator and the step of delivering energy may comprise delivering electrical current in a radio-frequency range. In addition, the step of inserting the energy delivery devices may further comprise inserting at least one introducer tube into a patient's body, wherein the energy delivery devices may be inserted into the treatment sites through a bore of the at least one introducer tube.

As an additional feature of this aspect of the present invention, the probe assemblies may be internally-cooled. The internally-cooled probe assemblies may each further comprise at least two tubular members disposed within the lumen for delivering a cooling fluid to and removing a cooling fluid from the energy delivery devices.

These features and others will become apparent in the detailed description that follows.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the invention may be readily understood, embodiments of the invention are illustrated by way of examples in the accompanying drawings, in which:

FIG. 1 is an illustration of a portion of a first embodiment of a system of the present invention;

FIGS. 2A to 2F depict side views of alternate embodiments of a distal tip region of a probe assembly;

FIG. 3A is an isometric view of one embodiment of the handle of the probe assembly of the present invention.

FIG. 3B is a longitudinal cross-section of one embodiment of a handle of the probe assembly of the present invention;

FIG. 4 is a perspective cut-away view of one embodiment of a distal tip region of a probe assembly of the present invention;

FIG. 5A is an axial cross-section through the distal tip region of the probe assembly shown in FIG. 4;

FIG. 5B is an axial cross-section through a more proximal portion of the distal tip region of the probe assembly shown in FIG. 4;

FIGS. 6A-6C are sectional views of various embodiments of a liquid-cooled distal tip region of a probe assembly;

FIG. 7 is a sectional view of an embodiment of a liquid-cooled distal tip region comprising an impedance monitoring tip;

FIG. 8 shows two probes placed within an intervertebral disc;

FIGS. 9A and 9B are sectional views of alternate embodiments of a liquid-cooled distal tip region illustrating various embodiments of a temperature sensing element;

FIG. 10 is a lateral view of a portion of a human spine;

FIGS. 11A and 11B show possible placements of two probe assemblies in an intervertebral disc;

FIG. 12A is a graph of temperature in a uniform tissue vs. relative distance using cooled and non-cooled probe assemblies; and

FIG. 12B is a graph of energy in a uniform tissue vs. relative distance using cooled and non-cooled probe assemblies.

DETAILED DESCRIPTION OF THE INVENTION

With specific reference now to the drawings in detail, it is stressed that the particulars shown are by way of example and for purposes of illustrative discussion of some embodiments of the present invention only, and are presented in the cause of providing what is believed to be the most useful and readily understood description of the principles and conceptual aspects of the invention. In this regard, no attempt is made to show structural details of the invention in more detail than is necessary for a fundamental understanding of the invention, the description taken with the drawings making apparent to those skilled in the art how the several forms of the invention may be embodied in practice.

Before explaining at least one embodiment of the invention in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth in the following description or illustrated in the drawings. The invention is capable of other embodiments or of being practiced or carried out in various ways. Also, it is to be understood that the phraseology and terminology employed herein is for the purpose of description and should not be regarded as limiting.

For the purposes of this invention, a lesion refers to any effect achieved through the application of energy to a tissue in a patient's body, and the invention is not intended to be limited in this regard. Furthermore, for the purposes of this description, proximal generally indicates that portion of a device or system next to or nearer to a user (when the device is in use), while the term distal generally indicates a portion further away from the user (when the device is in use).

With reference to FIG. 1, a first embodiment of a system 100 of the present invention is shown. System 100 comprises a generator 102, a cable 104, first and second probe assemblies 106 (only one probe assembly is shown), one or more cooling devices 108, a pump cable 110, one or more proximal cooling supply tubes 112 and one or more proximal cooling return tubes 114. In this embodiment, generator 102 is a radio frequency (RF) generator, but may optionally be any energy source that may deliver other forms of energy, including but not limited to microwave energy, thermal energy, ultrasound and optical energy. Generator 102 may comprise a display means incorporated into said generator. Said display means may be operable to display various aspects of a treatment procedure, including but not limited to any parameters that are relevant to a treatment procedure, such as temperature, impedance, etc. and errors or warnings related to a treatment procedure. If no display means is incorporated into generator 102, generator 102 may comprise a means of transmitting a

signal to an external display. In the first embodiment, generator **102** is operable to communicate with one more devices, for example with one or more of first and second probe assemblies **106** and the one or more cooling devices **108**. Such communication may be unidirectional or bidirectional depending on the devices used and the procedure performed. An example of an RF generator that fulfills the above criteria is the Pain Management Generator (PMG) of Baylis Medical Company Inc. (Montreal, QC, Canada).

As illustrated in FIG. 1, in this first embodiment of a system of the present invention, a distal region **124** of cable **104** comprises a splitter **130** that divides cable **104** into two distal ends **136** as illustrated in FIG. 1 such that two probe assemblies **106** can be connected to cable **104**. A proximal end **128** of cable **104** is connected to generator **102**. This connection can be permanent, whereby, for example, the proximal end **128** of cable **104** is embedded within generator **102**, or temporary, whereby, for example, the proximal end **128** of cable **104** is connected to generator **102** via an electrical connector. The two distal ends **136** of cable **104** terminate in connectors **140** operable to couple to probe assemblies **106** and establish an electrical connection between probe assemblies **106** and generator **102**. In alternate embodiments (not shown), system **100** may comprise a separate cable for each probe assembly **106** being used to couple probe assemblies **106** to generator **102**. Alternatively, splitter **130** may comprise more than two distal ends. Such a connector would be useful in embodiments where it would be desirable to connect more than two devices to generator **102**, for example, if more than two probe assemblies are being used or if separate temperature sensors (i.e. not attached to the probe assemblies) are to be placed in a patient's body.

One or more cooling devices **108** may comprise any means of reducing a temperature of material located at and proximate to one or more of probe assemblies **106**. In the first embodiment, one or more cooling devices **108** comprises two peristaltic pumps operable to circulate a fluid from the one or more cooling devices **108** through one or more proximal cooling supply tubes **112**, probe assemblies **106**, one or more proximal cooling return tubes **114** and back to the one or more cooling devices **108**. The fluid may be water or any other suitable fluid. In alternate embodiments, one or more cooling devices **108** may comprise only one peristaltic pump or one or more electrothermal cooling devices or any other cooling means.

In the first embodiment, system **100** comprises a means of facilitating communication between the one or more cooling devices **108** and generator **102**, and one or more cooling devices **108** is operable to communicate at least uni-directionally and optionally bi-directionally, with generator **102**. In this way, feedback control is established between the one or more cooling devices **108** and the generator **102**. The feedback control of the first embodiment of the present invention involves generator **102**, first and second probe assemblies **106** and the one or more cooling devices **108**, although any feedback between any two devices is within the scope of the present invention. The feedback control may be implemented, for example, in a controller or control module which may be a component of generator **102**. In this embodiment, generator **102** is operable to communicate bi-directionally with first and second probe assemblies **106** as well as with the one or more cooling devices **108**. In the context of this invention, bi-directional communication refers to the capability of a device to both receive a signal from and send a signal to another device.

As an example of feedback control in system **100** of the present invention, generator **102** may receive temperature

measurements from one or both of first and second probe assemblies **106**. Based on the temperature measurements, generator **102** may perform some action, such as modulating the power that is sent to first and/or second probe assemblies **106**. Thus, both probe assemblies **106** may be individually controlled based on their respective temperature measurements. For example, power to each of the probe assemblies could be increased when a temperature measurement is low or decreased when a measurement is high. This variation of power may be different for each probe assembly. In some cases, generator **102** may terminate power to one or more probe assemblies **106**. Thus, generator **102** may receive a signal (e.g. temperature measurement) from one or both of first and second probe assemblies **106**, determine the appropriate action, and send a signal (e.g. decreased or increased power) back to one or both of first and second probe assemblies **106**. Alternatively, generator **102** may send a signal to the one or more cooling devices **108** to either increase or decrease the flow rate or degree of cooling being supplied to one or both of first and second probe assemblies **106**.

Alternatively, if one or more cooling devices **108** comprises one or more peristaltic pumps, the one or more pumps may communicate a fluid flow rate to generator **102** and may receive communications from generator **102** instructing the pumps to modulate this flow rate. In some instances, the one or more peristaltic pumps may respond to generator **102** by changing the flow rate or turning off for a period of time. With cooling devices **108** turned off, any temperature sensing elements associated with probe assemblies **106** would not be affected by the cooling fluid allowing a more precise determination of the surrounding tissue temperature to be made. In addition, when using more than one probe assembly **106**, the average temperature or a maximum temperature in the temperature sensing elements associated with probe assemblies **106** may be used to modulate cooling.

In other embodiments, the one or more cooling devices **108** may reduce the rate of cooling or disengage depending on the distance between the probe assemblies **106**. For example, when the distance is small enough such that a sufficient current density exists in the region to achieve a desired temperature, little or no cooling may be required. In such an embodiment, energy is preferentially concentrated between first and second energy delivery devices **192** through a region of tissue to be treated, thereby creating a strip lesion. A strip lesion is characterized by an oblong volume of heated tissue that is formed when an active electrode is in close proximity to a return electrode of similar dimensions. This occurs because at a given power, the current density is preferentially concentrated between the electrodes and a rise in temperature results from current density.

One or more cooling devices **108** may also communicate with generator **102** in order to alert generator **102** to one or more possible errors and/or anomalies associated with one or more cooling devices **108**. For example, if cooling flow is impeded or if a lid of the one or more cooling devices **108** is opened. Generator **102** may then act on the error signal by at least one of alerting a user, aborting the procedure, and modifying an action.

In still other embodiments, generator **102** may communicate with only one of the one or more cooling devices **108** or communication between devices may be uni-directional. For example, the one or more cooling devices **108** may be operable to receive incoming signals from generator **102** but not to send signals back to generator **102**. In addition to the aforementioned feedback systems, generator **102** may respond to Somatosensory evoked potentials (SSEP)/Electromyogram (EMG) measurements or some other measure of patient

11

response to a treatment procedure. Many variations in feedback control may exist in a system of the present invention, and the invention is not limited in this regard.

As illustrated in FIG. 1, the means of facilitating communication between the one or more cooling devices 108 and generator 102 may take the form of a pump cable 110 electrically connecting generator 102 to the one or more cooling devices 108. In other embodiments, generator 102 and the one or more cooling devices 108 may be connected with an RS-232 cable, a fiber optic cable, a USB cable, a Firewire™ (IEEE 1394) cable or other means of electrical coupling. In yet further embodiments, communication between generator 102 and the one or more cooling devices 108 may be achieved using some other communication protocol including but not limited to infrared, wireless, Bluetooth™ and others and the invention is not limited in this regard.

In the first embodiment of a system of the invention as illustrated in FIG. 1, the one or more proximal cooling supply tubes 112 comprise proximal supply tube connectors 116 at the distal ends of the one or more proximal cooling supply tubes 112. Additionally, the one or more proximal cooling return tubes 114 comprise proximal return tube connectors 118 at the distal ends of the one or more proximal cooling return tubes 114. In the first embodiment, proximal supply tube connectors 116 are female luer-lock type connectors and proximal return tube connectors 118 are male luer-lock type connectors although other connector types are intended to be within the scope of the present invention.

In the first embodiment of a system of the present invention and referring still to FIG. 1, probe assembly 106 comprises a proximal region 160, a handle 180, a hollow elongate shaft 184 and a distal tip region 190 comprising one or more energy delivery devices 192. Proximal region 160 comprises distal cooling supply tube 162, distal supply tube connector 166, distal cooling return tube 164, distal return tube connector 168, probe assembly cable 170 and probe cable connector 172. In this embodiment, distal cooling supply tube 162 and distal cooling return tube 164 are flexible to allow for greater maneuverability of probe assemblies 106, but alternate embodiments with rigid tubes are possible.

In a first embodiment, distal supply tube connector 166 is a male luer-lock type connector and distal return tube connector 168 is a female luer-lock type connector. Thus, proximal supply tube connector 116 is operable to interlock with distal supply tube connector 166 and proximal return tube connector 118 is operable to interlock with distal return tube connector 168. This helps to establish a circuit within which a cooling fluid may flow while maintaining modularity of probe assembly 106. As a further benefit, having different types of connectors on either proximal tube as well as different types of connectors on either distal tube adds a measure of safety by ensuring that the tubes will not be connected incorrectly (i.e. supply to return and vice versa).

In the first embodiment illustrated in FIG. 1, probe cable connector 172 is located at a proximal end of probe assembly cable 170 and is operable to reversibly couple to one of connectors 140, thus establishing an electrical connection between generator 102 and probe assembly 106. Probe assembly cable 170 comprises one or more conductors depending on the specific configuration of probe assembly 106. For example, in this embodiment of system 100 of the present invention, probe assembly cable 170 comprises five conductors allowing probe assembly cable 170 to transmit RF current from generator 102 to the one or more energy delivery devices 192 as well as to connect multiple temperature sensing devices to generator 102 as discussed below.

12

One or more energy delivery devices 192 may comprise any means of delivering energy to a region of tissue adjacent distal tip region 190. For example, the one or more energy delivery devices 192 may comprise an ultrasonic device, an electrode or any other energy delivery means and the invention is not limited in this regard. Similarly, energy delivered via the one or more energy delivery devices 192 may take several forms including but not limited to thermal energy, ultrasonic energy, radio frequency energy, microwave energy or any other form of energy. In a first embodiment, the one or more energy delivery devices 192 comprise an electrode. The active region of the electrode may be 2-20 mm in length and energy delivered by the electrode is electrical energy in the form of current in the RF range. The size of the active region of the electrode in this embodiment is optimized for placement within an intervertebral disc, however, different sizes of active regions, all of which are within the scope of the present invention, may be used depending on the specific procedure being performed. In some embodiments, feedback from generator 102 may automatically adjust the exposed area of energy delivery device 192 in response to a given measurement such as impedance or temperature. This may be accomplished through the use of an adjustable insulation sleeve associated with energy delivery device 192. Adjustment of the insulation sleeve could be accomplished through sliding the sleeve proximally or distally along the energy delivery device. The adjustment may be done manually in other embodiments. Alternatively, additional conductive regions may be provided along distal tip region 190 proximate energy delivery device 192. In such an embodiment, the size or shape of a lesion may be altered by selectively delivering energy through one or more of the additional conductive regions and energy delivery device 192. Furthermore, one or more energy delivery devices 192 may comprise any combination of active electrodes and return electrodes, as is well known in the art.

FIGS. 2A-2F show different shapes which the distal end of energy delivery device 192 can adopt for insertion in the patient's body. FIG. 2A shows a pencil tip. FIG. 2B shows a sharp beveled tip. FIG. 2C shows a blunt end when cutting or piercing is not required. FIGS. 2D and 2E show front and side views of a spatula shaped tip whereas FIG. 2F shows a curved tip with a cutting bevel end. The different shapes can allow for the current to be directed into the disc in a profile corresponding to the shape of the tip, thereby controlling the current density which will in turn control the size and shape of a lesion created in the tissue. These embodiments are intended to be exemplary only and various tip shapes may be used with the invention.

Cooling can be supplied to the one or more energy delivery devices 192 in various ways. The scope of the present invention includes any and all cooling means known in the art that may be used to provide cooling to the one or more energy delivery devices 192 and is not limited in this regard. In a first embodiment as has been described earlier, and with reference now to FIG. 3, distal cooling supply tube 162 and distal cooling return tube 164 are connected to shaft supply tube 302 and shaft return tube 304, respectively, within handle 180, using connecting means 301 and 303. Connecting means 301 and 303 can be any means of connecting two tubes including but not limited to ultraviolet (UV) glue, epoxy or any other adhesive as well as friction or compression fitting. Arrows 312 and 314 indicate the direction of flow of a cooling fluid supplied by the one or more cooling devices 108, in such embodiments that comprise a cooling fluid as part of the cooling means. In this first embodiment, shaft supply tube 302 and shaft return tube 304 are hypotubes made of a conductive material such as stainless steel. The hypotubes extend

13

from handle **180** through a lumen of hollow elongate shaft **184** to distal tip region **190**, as shown in FIG. **4**, wherein arrow **408** indicates the direction of cooling fluid flow within a lumen **450** defined by the one or more energy delivery devices **192**. Thus, using the configuration described in a first embodiment of a system of the invention, a cooling fluid is circulated between the one or more cooling devices **108** and distal tip region **190** of at least one probe assembly **106**. As detailed later in the description, in alternate embodiments one hypotube may be used to supply cooling fluid to the one or more energy delivery devices **192** while two or more hypotubes may be used to return cooling fluid to the one or more cooling devices **108**. The number of hypotubes used for supplying cooling fluid and the number used for returning cooling fluid and the combination thereof may vary and all such combinations are intended to be within the scope of the present invention.

In alternate embodiments of a system of the present invention, not all probe assemblies may be cooled, in which case, the probe assemblies that are not being cooled may not be associated with cooling tubes and the elongate hollow shafts of those probe assemblies may not comprise tubes for supplying cooling to and returning cooling from the distal tip regions of those probe assemblies.

In this first embodiment of a system of the present invention, distal cooling supply tube **162** may be connected to distal cooling return tube **164** in order to keep the tubing used in a system of the invention as organized as possible. This connection may be temporary, such as with a cable tie or other temporary connecting means, or may be more permanent, for example by using some form of adhesive bonding. Whether temporary or more permanent, this connection can be achieved using various means of connecting two or more tubes and the present invention is not limited in this regard. Referring again to FIG. **3**, handle **180** may be at least partially filled with a filling agent **320** in order to lend more strength and stability to handle **180** as well as to hold the various cables, tubes and wires in place. Filling agent **320** may be epoxy or any other suitable material. In addition, handle **180** is operable to easily and securely couple to an optional introducer tube (discussed below) in a first embodiment where an introducer tube would facilitate insertion of the one or more probe assemblies **106** into a patient's body. For example, as shown in FIG. **3**, handle **180** may taper at its distal end in order to accomplish this function, i.e. to enable it to securely couple to an optional introducer tube.

In this first embodiment of a system of the present invention, hollow elongate shaft **184** is manufactured out of polyimide, which provides exceptional electrical insulation while maintaining sufficient flexibility and compactness. In alternate embodiments, hollow elongate shaft **184** may be any other material imparting similar qualities. In still other embodiments, hollow elongate shaft **184** may be manufactured from an electrically conductive material and may be covered by an insulating material so that delivered energy remains concentrated at energy delivery device **192** of distal tip region **190**. In the first embodiment, probe assembly **106** comprises a marker **384** at some point along handle **180** or along the length of elongate hollow shaft **184**. In an embodiment where a probe assembly **106** is inserted into an optional introducer tube, marker **384** may be located on elongate hollow shaft **184** (as shown in FIG. **3**) and may be a visual depth marker that functions to indicate when the distal tip of the probe assembly is located at a distal end of the introducer tube by aligning with a hub of the introducer tube. Marker **384** will thus provide a visual indication as to the location of the distal tip of a probe assembly **106** relative to an optional introducer

14

tube. Alternatively, marker **384** may be a tactile marker and may be used to indicate the orientation of a particular component of probe assembly **106**. For example, as discussed below, probe assembly **106** may comprise a secondary temperature sensor. In such an embodiment, marker **384** may serve to indicate the radial location of the secondary temperature sensor within probe assembly **106**.

Referring in detail to FIG. **4**, a perspective cut-away view of a first embodiment of distal tip region **190** of probe assembly **106** is shown. In this embodiment, distal tip region **190** comprises one or more temperature sensing elements **402** which are operable to measure the temperature at and proximate to the one or more energy delivery devices **192**. The one or more temperature sensing elements **402** may comprise one or more thermocouples, thermometers, thermistors, optical fluorescent sensors or any other means of sensing temperature. In the first embodiment, the one or more temperature sensing elements **402** are connected to generator **102** via probe assembly cable **170** and cable **104** although any means of communication between the one or more temperature sensing elements **402** and generator **102**, including wireless protocols, are included within the scope of the present invention. In the embodiment illustrated by FIG. **4**, one or more temperature sensing elements **402** comprises a thermocouple junction made by joining a stainless steel hypotube **406** to a constantan wire **410**, wherein constantan wire **410** is insulated by wire insulation **412**. In this embodiment, the junction of hypotube **406** and constantan wire **410** is made by laser welding, although any other means of joining two metals may be used. Furthermore, in this embodiment, hypotube **406** and constantan wire **410** extend through a lumen of hollow elongate shaft **184** and connect to probe assembly cable **170** within handle **180**. In the embodiment shown in FIG. **4**, the one or more temperature sensing elements **402** protrudes beyond the one or more energy delivery devices **192**. In this specific embodiment, whereby temperature sensing element **402** comprises a stainless steel hypotube **406**, stainless steel hypotube **406** may be electrically conductive and may be electrically coupled to the one or more energy delivery devices **192**. Thus, in such an embodiment whereby energy may be conducted to the protrusion and delivered from the protrusion to surrounding tissue, the protrusion may be understood to be a component of both temperature sensing element **402** as well as the one or more energy delivery devices **192**. Placing the one or more temperature sensing elements **402** at this location, rather than within lumen **450** defined by the one or more energy delivery devices **192**, is beneficial because it allows the one or more temperature sensing elements **402** to provide a more accurate indication of the temperature of tissue proximate to the one or more energy delivery devices **192**. This is due to the fact that, when extended beyond the one or more energy delivery devices **192**, the one or more temperature sensing elements **402** will not be as affected by the cooling fluid flowing within a lumen **450** as it would be were it located within lumen **450**. Thus, in this embodiment of the present invention, probe assembly **106** comprises a protrusion protruding from the distal region of the probe assembly, whereby the protrusion is a component of temperature sensing element **402**.

In the first embodiment of a probe assembly of the present invention, probe assembly **106** further comprises one or more secondary temperature sensing elements **404** located within hollow elongate shaft **184** at some distance away from one or more energy devices **192**, and positioned adjacent a wall of hollow elongate shaft **184**. For example, if the one or more energy delivery devices **192** comprises an electrode that is 5-7 mm in length, then locating a secondary temperature sensing

15

element **404** approximately 3 mm away from a proximal end of said electrode is optimal for measuring temperature at the periphery of an intervertebral disc as is discussed in more detail below. As mentioned above with respect to the one or more temperature sensing elements **402**, the one or more secondary temperature sensing elements **404** may similarly comprise one or more thermocouples, thermometers, thermistors, optical fluorescent sensors or any other means of sensing temperature. In the first embodiment illustrated by FIG. 4, the secondary temperature sensing element **404** is a thermocouple made by joining copper and constantan thermocouple wires, designated as **420** and **422** respectively. As mentioned earlier with respect to the one or more temperature sensing elements **402**, the copper and constantan wires **420** and **422** may extend through a lumen of hollow elongate shaft **184** and may connect to probe assembly cable **170** within handle **180**.

Probe assembly **106** may further comprise a thermal insulator **430** located proximate to any of the one or more temperature sensing elements **402** or the one or more secondary temperature sensing elements **404**. Thermal insulator **430** may be made from any thermally insulating material, for example silicone, and may be used to insulate any temperature sensing element from other components of probe assembly **106**, so that the temperature sensing element will be able to more accurately measure the temperature of the surrounding tissue. In the first embodiment illustrated by FIG. 4, thermal insulator **430** is used to insulate the one or more secondary temperature sensing elements **404** from cooling fluid passing through shaft supply tube **302** and shaft return tube **304**.

As an additional feature of a first embodiment of a system of the present invention, probe assembly **106** comprises a radiopaque marker **440** incorporated somewhere along hollow elongate shaft **184**. For example, an optimal location for a radiopaque marker may be at or proximate to distal tip region **190**, adjacent the one or more energy delivery devices **192** as shown in FIG. 4. Radiopaque markers are visible on fluoroscopic x-ray images and can be used as visual aids when attempting to place devices accurately within a patient's body. These markers can be made of many different materials, as long as they possess sufficient radiopacity. Suitable materials include, but are not limited to silver, gold, platinum and other high-density metals as well as radiopaque polymeric compounds. Various methods for incorporating radiopaque markers into or onto medical devices may be used, and the present invention is not limited in this regard.

In the first embodiment of a system of the present invention, radiopaque marker **440** may comprise silver solder placed within hollow elongate shaft **184**, proximate to the one or more energy delivery devices **192**. When viewed under x-ray fluoroscopy, the silver solder will appear dark, allowing a user to readily distinguish the location of the solder. If the solder is placed proximate to the one or more energy delivery devices **192**, then the one or more energy delivery devices **192** will be distinguishable relative to other regions of hollow elongate shaft **184**, allowing for accurate positioning of the one or more energy delivery devices **192** at a treatment site within a body of a patient. Radiopaque markers **440** may also be incorporated by other methods, including but not limited to vapor deposition, ion implantation, dip coating, metal plating and electro-plating. Further, there may be more than one radiopaque marker **440** associated with probe assembly **106**.

Cross-sectional views of portions of distal tip region **190**, as indicated in FIG. 4, are shown in FIGS. 5A and 5B. Referring first to FIG. 5A, three hypotubes **302**, **304**, and **406** are positioned within a lumen **450** defined by hollow elongate

16

shaft **184** and the one or more energy delivery devices **192**. Shaft supply tube **302** and shaft return tube **304** carry cooling fluid to and from the distal end of distal tip region **190**, respectively. In this embodiment, hypotube **406** is made of a conductive material such as stainless steel and is operable to transmit energy from probe assembly cable **170** to the one or more energy delivery devices **192**. In addition, hypotube **406** defines a lumen within which a means of connecting the one or more temperature sensing devices **402** to probe assembly cable **170** may be located. For example, if the one or more temperature sensing devices **402** comprises a thermocouple, then a constantan wire **410** may extend from probe assembly cable **170** to the thermocouple junction through hypotube **406** as is shown in FIG. 4. Alternatively, more than one wire may be passed through the lumen of hypotube **406** or the lumen of hypotube **406** may be utilized for another purpose.

In the first embodiment of the present invention, the one or more energy delivery devices **192** is an electrode, as discussed above. FIG. 5A is a cross-section of a portion of distal tip region **190** wherein hollow elongate shaft **184** and electrode **192** overlap in order to secure the electrode in place. In this embodiment, the lumen defined by hollow elongate shaft **184** and electrode **192** at this portion of distal tip region **190**, contains a radiopaque marker **440** comprised of silver solder, as discussed above. The silver solder fills the lumen such that any cooling fluid supplied to probe assembly **106**, that is not located within one of the cooling tubes described earlier, is confined to the distal tip region **190** of probe assembly **106**. Thus, in such an embodiment, the silver solder may be referred to as a flow impeding structure since it functions to restrict the circulation of fluid to a specific portion (in this case, at least a portion of distal region **190**) of probe assembly **106**. In other words, cooling fluid may flow from the one or more cooling devices **108**, through the cooling supply tubes described earlier, to distal tip region **190** of probe assembly **106**. The cooling fluid may then circulate within lumen **450** defined by electrode **192** in order to provide cooling to the electrode. In the context of the present invention, an internally-cooled probe is defined as a probe having such a configuration, whereby a cooling medium does not exit probe assembly **106** from a distal region of probe assembly **106**. The cooling fluid may not circulate further down hollow elongate shaft **184** due to the presence of the silver solder, and flows through the cooling return tubes described earlier back to the one or more cooling devices **108**. In alternate embodiments, other materials may be used instead of silver solder, and the invention is not limited in this regard.

Referring now to FIG. 5B, a cross-section of a portion of distal tip region **190**, proximal from the cross-section of FIG. 5A as illustrated in FIG. 4, is shown. In the embodiment illustrated by FIG. 5B, the one or more secondary temperature sensing elements **404** is located proximate to an inner wall of hollow elongate shaft **184**. This proximity allows the one or more secondary temperature sensing elements **404** to provide a more accurate indication of the temperature of surrounding tissue. In other words, the one or more secondary temperature sensing elements **404** may be operable to measure the temperature of the inner wall of hollow elongate shaft **184** at the location of the one or more secondary temperature sensing elements **404**. This temperature is indicative of the temperature of tissue located proximate to the outer wall of hollow elongate shaft **184**. Thus, it is beneficial to have the one or more secondary temperature sensing elements **404** located proximate to an inner wall of hollow elongate shaft **184**, rather than further away from the inner wall.

As described above, thermal insulator **430** is placed between the one or more secondary temperature sensing ele-

17

ments **404** and shaft supply and return tubes **302** and **304** in the first embodiment of the present invention. This serves to insulate the one or more secondary temperature sensing elements **404** from the cooling effect of the cooling fluid located within shaft supply tube **302** and shaft return tube **304**. Thus, by minimizing the cooling effect, one or more secondary temperature sensing elements **404** is able to provide a more accurate indication as to the surrounding tissue temperature.

FIGS. **5A** and **5B** also illustrate the relative positions of the three hypotubes used in a first embodiment of a system of the present invention. In this embodiment, the three hypotubes are held together in some fashion in order to increase the strength of probe assembly **106**. For example, the three hypotubes may be bound together temporarily or may be more permanently connected using solder, welding or any suitable adhesive means. Various means of binding and connecting hypotubes are well known in the art and the present invention is not intended to be limited in this regard.

As stated earlier, the figures included in this application, which illustrate some embodiments of a system of the present invention, are intended to be exemplary only. For example, with respect to FIG. **5A**, the relative positions of the three hypotubes as shown are not intended to limit the scope of the invention in any way. It will be readily apparent to those skilled in the art that many variations are possible, relating to both the number as well as the position of the hypotubes, all of which are included within the scope of the present invention. In alternate embodiments, the shape of the hypotubes may be optimized so that more efficient use is made of a lumen defined by hollow elongate shaft **184** and the one or more energy delivery devices **192**. In yet further embodiments, distal cooling supply tube **162** may provide cooling to the one or more energy delivery devices **192** without the use of hypotubes, and this invention is intended to include any means of supplying cooling to and returning cooling from distal tip region **190**, as well as any and all means of transmitting energy between probe assembly cable **170** and the one or more energy delivery devices **192**. For example, one or more cooling devices **108** may comprise an electrothermal cooling device, as mentioned above. In such embodiments, the mechanism of supplying cooling to the one or more energy delivery devices **192** may differ significantly from the illustrated embodiment but is nevertheless included within the scope of the present invention.

As described above, providing cooling to probe assemblies **106** allows heat delivered through energy delivery devices **192** to be translated further into the tissue without raising the temperature of the tissue immediately adjacent energy delivery device **192**. FIGS. **6A-6C** illustrate various embodiments for the internal cooling of distal tip region **190** of probe assembly **106**. Arrows **408**, **630**, and **660** indicate the direction of flow of the cooling liquid in FIGS. **6A**, **6B**, and **6C**, respectively. FIG. **6A** shows a longitudinal cross-section of an internal liquid cooled distal tip region **190** of the first embodiment of the present invention, as shown in FIG. **4**. As described previously, the cooling supply mechanism comprises two hypotubes, shaft supply tube **302** and shaft return tube **304**. In FIG. **6B**, the cooling supply mechanism comprises a single hypotube **600** defining a central bore **610** and an outer annular passageway **620**. Cooling liquid passes down the central bore **610**, as indicated by arrow **630**, and passes back through the outer annular passageway **620**.

FIG. **6C** shows a cooling supply mechanism configured similarly to that shown in FIG. **6B**. However, in this embodiment, a single hypotube **640** defines one or more apertures **650** proximate a distal tip region **190**. Apertures **650** direct the flow of cooling liquid outward towards outer annular pas-

18

sageway **620**. In this embodiment, hypotube **640** may be made of a conductive material such as constantan and may be welded to energy delivery device **192** which may be made of a different conductive material such as stainless steel. In this way, a junction between hypotube **640** and energy delivery device **192** acts as a thermocouple useful to measure temperature, in addition to providing channels for the flow of cooling liquid.

FIG. **7** shows a longitudinal cross-section of an embodiment of a distal tip region **190** further comprising an insulated impedance measuring tip **700** adjacent the distal end of energy delivery device **192**. Impedance measuring tip **700** can be used to help determine a position of energy delivery device **192** while the probe assembly **106** is being inserted into a region of tissue. Impedance measuring tip **700** may be operable to send very small pulses of low power, high frequency current through the tissue to a dispersive ground electrode on the surface of the patient's skin (not shown), or may be used in any other way of measuring impedance known in the art. Insulating material **710** isolates impedance measuring tip **700** from energy delivery device **192**. As probe assembly **106** is moved through tissue, the impedance of the tissue can be measured, allowing the location of energy delivery device **192** to be determined. For example, when impedance measuring tip **700** moves from the annulus fibrosis to the nucleus pulposus of an intervertebral disc, the impedance level will drop. This drop in impedance effectively indicates that energy delivery device **192** is located within the annulus fibrosis since energy delivery device **192** is located proximally from impedance measuring tip **700** and is isolated from impedance measuring tip **700** by insulating material **710**. It will be understood to persons skilled in the art that the embodiments of the invention in which distal tip region **190** comprises an impedance measuring tip will also include internal conduits to hold wires that connect the impedance measuring tip to the generator **102**.

In some embodiments (not shown), distal tip region **190** may further be configured to predominantly expose one side of energy delivery device **192**, allowing increased control of the direction of energy delivery (not shown). This could be accomplished by incorporating an electrically insulating material into some regions of the energy delivery device, or through an associated insulation sleeve.

As mentioned above, system **100** of the present invention may further comprise one or more introducer tubes. Generally, introducer tubes may comprise a proximal end, a distal end and a longitudinal bore extending therebetween. As previously stated with respect to a first embodiment of the present invention, introducer tubes (when used) are operable to easily and securely couple with probe assembly **106**. For example, the proximal end of the introducer tubes may be fitted with a connector able to mate reversibly with handle **180** of probe assembly **106**. An introducer tube may be used to gain access to a treatment site within a patient's body and a hollow elongate shaft **184** of a probe assembly **106** may be introduced to said treatment site through the longitudinal bore of said introducer tube. Introducer tubes may further comprise one or more depth markers in order to enable a user to determine the depth of the distal end of the introducer tube within a patient's body. Additionally, introducer tubes may comprise one or more radiopaque markers to ensure the correct placement of the introducers when using fluoroscopic guidance.

In embodiments of the invention that include one or more introducer tubes, the one or more introducer tubes may comprise one or more temperature sensors along their lengths. In such embodiments, the one or more temperature sensors may

be placed proximate to the distal end of the one more introducer tubes so as to enable the one or more temperature sensors to measure the temperature of tissue surrounding the distal end of the one or more introducer tubes. For example, if a system of the present invention, comprising introducer tubes, is used in a treatment procedure of an intervertebral disc, a temperature sensing element located proximate to the distal end of the introducer tube may be capable of monitoring the temperature of the periphery of the intervertebral disc, or of tissue surrounding the disc, when the introducer tube is inserted into the disc. In other embodiments, multiple temperature sensing elements disposed along the introducer may be used to indicate the size of the lesion as it expands. This may be particularly useful in the treatment of tumor tissue, for example.

Introducer tubes may be made of various materials, as is known in the art and, if said material is electrically conductive, the introducer tubes may be electrically insulated along all or part of their length, in order to prevent energy from being conducted to undesirable locations within a patient's body. In some embodiments, hollow elongate shaft **184** may be electrically conductive, and an introducer may function to insulate the shaft leaving the energy delivery device **192** exposed for treatment. Further, the one or more introducer tubes may be operable to connect to a power source and may therefore form part of an electrical current impedance monitor (wherein at least a portion of the introducer tube is not electrically insulated). Different tissues may have different electrical impedance characteristics and it is therefore possible to determine tissue type based on impedance measurements, as has been described. Thus, it would be beneficial to have a means of measuring impedance in order to determine the tissue within which a device is located. In addition, the gauge of the introducer tubes may vary depending on the procedure being performed and/or the tissue being treated. In some embodiments, the introducer tubes should be sufficiently sized in the radial dimension so as to accept at least one probe assembly **106**. In embodiments of a system of the present invention lacking introducer tubes, hollow elongate shaft **184** may be insulated (in embodiments where hollow elongate shaft **184** is made of a conductive material) for the aforementioned reason, i.e. so as not to conduct energy to portions of a patient's body that are not being treated. Introducers may be manufactured from inconel or a similar non-magnetic metal to allow MRI- or CT-assisted placement.

In some embodiments of a system of the present invention comprising one or more introducer tubes, the system may further comprise one or more stylets. A stylet may have a beveled tip to facilitate insertion of the one or more introducer tubes into a patient's body. Various forms of stylets are well known in the art and the present invention is not limited to include only one specific form. Further, as described above with respect to the introducer tubes, the one or more stylets may be operable to connect to a power source and may therefore form part of an electrical current impedance monitor. In other embodiments, one or more probe assemblies **106** may form part of an electrical current impedance monitor, as has been mentioned with respect to FIG. 7. Thus, generator **102** may receive impedance measurements from one or more of one or more stylets, one or more introducer tubes and one or more probe assemblies **106** and may perform an action, such as alerting a user to an incorrect placement of an energy delivery device **192**, based on the impedance measurements.

In a first embodiment of a system of the present invention, first and second probe assemblies **106** are operated in a bipolar mode. In this embodiment, electrical energy is delivered to first and second probe assemblies **106** and this energy is

preferentially concentrated between first and second probe assemblies **106** through a region of tissue to be treated, as is discussed in greater detail below. The region of tissue to be treated is thus heated by the energy concentrated between first and second probe assemblies **106**. In other embodiments, first and second probe assemblies **106** may be operated in a monopolar mode, in which case an additional grounding pad would be required on the surface of a body of a patient, as is known in the art. Any combination of bipolar and monopolar procedures may also be used.

In alternate embodiments, a system of the present invention may comprise more than two probe assemblies. For example, in some embodiments, three probe assemblies may be used and the probe assemblies may be operated in a triphasic mode, whereby the phase of the current being supplied differs for each probe assembly.

As another feature of the present invention, a system may be configured to control one or more of the flow of current between electrically conductive components and the current density around a particular component. For example, a system of the present invention may comprise three electrically conductive components, including two of similar or identical dimensions and a third of a larger dimension, sufficient to act as a dispersive electrode. Each of the electrically conductive components should beneficially be operable to transmit energy between a patient's body and an energy source. Thus, two of the electrically conductive components may be probe assemblies while the third electrically conductive component may function as a grounding pad or dispersive/return electrode. In one embodiment, the dispersive electrode and a first probe assembly are connected to a same electric pole while a second probe assembly is connected to the opposite electric pole. In such a configuration, electrical current may flow between the two probe assemblies or between the second probe assembly and the dispersive electrode. In order to control the current to flow preferentially to either the first probe assembly or the dispersive electrode, a resistance or impedance between one or more of these conductive components (i.e. the first probe assembly and the dispersive electrode) and a current sink (e.g. circuit 'ground') may be varied. In other words, if it would be desirable to have current flow preferentially between the second probe assembly and the dispersive electrode (as in a monopolar configuration), then the resistance or impedance between the first probe assembly and the circuit 'ground' may be increased so that the current will prefer to flow through the dispersive electrode to 'ground' rather than through the first probe assembly (since electrical current preferentially follows a path of least resistance). This may be useful in situations where it would be desirable to increase the current density around the second probe assembly and/or decrease the current density around the first probe assembly. Similarly, if it would be desirable to have current flow preferentially between the second probe assembly and the first probe assembly (as in a bipolar configuration), then the resistance or impedance between the dispersive electrode and 'ground' may be increased so that the current will prefer to flow through the first probe assembly to 'ground' rather than through the dispersive electrode. This would be desirable when a standard bipolar lesion should be formed. Alternatively, it may be desirable to have a certain amount of current flow between the second probe assembly and the first probe assembly with the remainder of current flowing from the second probe assembly to the dispersive electrode (a quasi-bipolar configuration). This may be accomplished by varying the impedance between at least one of the first probe assembly and the dispersive electrode, and 'ground', so that more or less current will flow along a desired path. This would allow

21

a user to achieve a specific, desired current density around a probe assembly. Thus, this feature of the present invention may allow a system to be alternated between monopolar configurations, bipolar configurations or quasi-bipolar configurations during the course of a treatment procedure.

As a further example of this feature of the present invention, four electrically conductive components may be provided. For example, a system may comprise two probe assemblies as well as two dispersive electrodes and each electric pole may be connected to a single probe assembly and a single dispersive electrode. As was mentioned in the previous example, the resistance or impedance between any of the electrically conductive components and a current sink (e.g. circuit 'ground') can be altered in order to control the flow of current between components. This configuration would be useful to selectively control current density around each probe assembly and thus selectively control tissue temperature and electrical field properties.

In yet another example of this feature, three substantially identical electrically conductive components, for example three probe assemblies, may be provided. In such a configuration, first and second probe assemblies may be connected to a single electric pole while a third probe assembly may be connected to the opposite electrical pole. In such an embodiment, the direction of current flow may be changed during the course of the procedure by varying the resistance or impedance between each of the first and second probe assemblies and 'ground'. Thus, current may flow in a bipolar fashion between the third probe assembly and either the first or second probe assemblies, depending on which probe assembly provides a higher resistance or impedance to the current flow. This system may be useful to alter the size or shape of a treatment area or lesion within a bodily tissue. Different energy modes as are known in the art may also be used depending on whether it is desired to cut or coagulate the tissue.

As has been described, a system of the present invention optionally comprises two or more temperature sensing elements, for example, one associated with the one or more energy delivery devices **192** and a second associated with one or more of hollow elongate shaft **184** or an introducer tube. A secondary temperature sensing element may also be located on a separate device inserted into the patient's body. FIG. **8** illustrates an example of the utility of having two spaced-apart temperature sensors. Two probe assemblies **106** are shown placed within introducer tubes **802**, wherein distal tip regions **190** of probe assemblies **106** are located within an intervertebral disc **800**. Each of probe assemblies **106** comprises a hollow elongate shaft **184**, an energy delivery device **192**, a temperature sensing element **402** and a secondary temperature sensing element **404**. Temperature sensing element **402** measures the tissue temperature at or proximate to energy delivery device **192** and, although temperature sensing element **402** is shown to be protruding from the distal tip of energy delivery device **192**, it will be clear to those skilled in the art that it may also be placed at other locations associated with energy delivery device **192** (for example, protruding from one side of energy delivery device **192**). In this embodiment, secondary temperature sensing element **404** is located within hollow elongate shaft **184** or alternatively on the surface of hollow elongate shaft **184**. In either case, secondary temperature sensing element **404** is operable to measure the temperature of tissue at the periphery of the disc as illustrated in FIG. **8**. Thus, in addition to measuring the temperature at or proximate to energy delivery device **192**, the temperature of tissue at the periphery of the disc is measured as well. Measuring peripheral disc temperature may be ben-

22

eficial in order to ensure that tissue at the disc periphery or external to the disc is not being overheated. FIG. **8** is intended to illustrate the utility of having more than one temperature sensor and is intended to be exemplary only. The number and positions of the temperature sensors and the benefits of having more than one temperature sensor are not limited to cooled probes and may differ depending on the application.

FIG. **9A** illustrates an embodiment whereby a temperature sensor **900** is located, via extrusion or another process, in a wall of hollow elongate shaft **184**. By locating a temperature sensor at this position, the temperature of the tissue surrounding the shaft can be measured as is well understood by a person skilled in the art. Alternatively, temperature sensing elements may be located within probe assembly **106** so as to measure the temperature of inflow and outflow of cooling fluid. By measuring the change in temperature of the inflow and outflow cooling fluid, the temperature of the tissue located adjacent energy delivery device **192** can be determined. In further embodiments, temperature sensing elements may be positioned in any other location as needed. For example, in a treatment procedure involving an intervertebral disc, temperature sensors not associated with probe assemblies **106** may be placed external to the disc, in the spinal canal, or in proximity to the spinal nerve.

FIG. **9B** shows a distal tip region **190** of a probe assembly **106** with an extendible remote temperature sensing element **910** which may be deployed from probe assembly **106**. The internal liquid cooling system has been omitted for ease of illustration. Temperature sensing element **910** allows monitoring of the temperature within tissues located remotely from the surface of energy delivery device **192**. Temperature sensing element **910** may be steerable so that its position may be changed during a procedure to obtain temperature measurements from a variety of tissue regions. In such an embodiment, the cooling feedback may be determined by a combination of temperatures within or surrounding the tissue being treated.

Any or all of the above embodiments of probe assembly **106** may comprise an active shape control mechanism to steer distal tip region **190**, for example as it is moved through the tissue. Such active shape control mechanisms include, but are not limited to, cables for a mechanical actuator, hydraulic or piezo-electric devices, and solenoids.

Usage of a first embodiment of a system **100** of the present invention to treat an intervertebral disc may be described generally as follows: With a patient lying on a radiolucent table, fluoroscopic guidance is used to percutaneously insert an introducer with a stylet to access the posterior of an intervertebral disc. In addition to fluoroscopy, other aids, including but not limited to impedance monitoring and tactile feedback, may be used to assist a user to position the introducer or probe assemblies within the patient's body. The use of impedance monitoring has been described earlier, whereby a user may distinguish between tissues by monitoring impedance as a device is inserted into the patient's body. With respect to tactile feedback, different tissues may offer different amounts of physical resistance to an insertional force. This allows a user to distinguish between different tissues by feeling the force required to insert a device through a given tissue. One method of accessing the disc is the extrapedicular approach in which the introducer passes just lateral to the pedicle, but other approaches may be used. A second introducer with stylet is then placed contralateral to the first introducer in the same manner, and the stylets are removed. Probe assemblies **106** are inserted into each of the two introducers placing electrodes **192** in the disc such that the distance between electrodes **192** is 1 mm to 55 mm. Once in place, a stimulating

electrical signal may be emitted from either of electrodes **192** to a dispersive electrode or to the other electrode **192**. This signal may be used to stimulate sensory nerves where replication of symptomatic pain would verify that the disc is pain-causing. A different signal may be used to stimulate motor nerves where a motor reaction indicates unsafe proximity to motor nerves that should not be heated. Probe assemblies **106** are connected to an RF generator **102** as well as to peristaltic pumps **108** to cool distal tip regions **190**. Radio frequency energy is delivered to electrodes **192** and the power is altered according to the temperature measured by temperature sensing element **402** in the tip of electrode **192** such that a desired temperature is reached between the distal tip regions **190** of the two probe assemblies **106**. During the course of the procedure, a treatment protocol such as the cooling supplied to the probe assemblies **106** and/or the power transmitted to the probe assemblies **106** may be adjusted in order to maintain a desirable treatment area shape, size and uniformity. These adjustments may be made on the basis of feedback from various sources, including but not limited to temperature sensors and impedance sensors. In addition, the treatment protocols may be adjusted based on an error signal received by a control module, which control module may be associated with generator **102**. The cooling devices may be independently controlled to alter the rate of cooling to each electrode **192**. Following treatment, energy delivery and cooling are stopped and probe assemblies **106** are removed from introducers. A fluid such as an antibiotic or contrast agent may be injected through the introducers, followed by removal of the introducers. Alternatively, the distal tips of the probe assemblies **106** may be sharp and sufficiently strong to pierce tissue so that introducers may not be required. As mentioned above, positioning probe assemblies **106**, and more specifically energy delivery devices **192**, within the patient's body, may be assisted by various means, including but not limited to fluoroscopic imaging, impedance monitoring and tactile feedback. Additionally, some embodiments of this method aspect may comprise one or more steps of inserting or removing material into a patient's body. For example, as has been described, a fluid may be inserted through an introducer tube during the course of a treatment procedure. Alternatively, a substance may be inserted through probe assembly **106**, in embodiments where probe assembly **106** comprises an aperture in fluid communication with a patient's body. Furthermore, material may be removed from the patient's body during the course of the treatment procedure. Such material may include, for example, damaged tissue, nuclear tissue and bodily fluids. Possible treatment effects include, but are not limited to, coagulation of nerve structures (nociceptors or nerve fibers), ablation of collagen, biochemical alteration, upregulation of heatshock proteins, alteration of enzymes, and alteration of nutrient supply.

A system of the present invention may be used in various medical procedures where usage of an energy delivery device may prove beneficial. Specifically, a system of the present invention is particularly useful for procedures involving treatment of back pain, including but not limited to treatments of tumors, intervertebral discs, facet joint denervation, sacroiliac joint lesioning or intraosseous (within the bone) treatment procedures. Moreover, the system is particularly useful to strengthen the annulus fibrosus, shrink annular fissures and impede them from progressing, cauterize granulation tissue in annular fissures, and denature pain-causing enzymes in nucleus pulposus tissue that has migrated to annular fissures. Additionally, the system may be operated to treat a herniated or internally disrupted disc with a minimally invasive technique that delivers sufficient energy to the annulus fibrosus to

breakdown or cause a change in function of selective nerve structures in the intervertebral disc, modify collagen fibrils with predictable accuracy, treat endplates of a disc, and accurately reduce the volume of intervertebral disc tissue. The system is also useful to coagulate blood vessels and increase the production of heat shock proteins.

As an illustration of the benefits of using a system of the present invention, some of the aforementioned procedures will now be described in more detail. Although some of the figures and the description relate to the percutaneous insertion of the probes into an intervertebral disc it will be understood that the probes can also be used during surgery and can be inserted directly into a disc or other tissue through an open cavity.

Treatment of an intervertebral disc has already been mentioned briefly, but will now be described in more detail. FIG. **10** shows a lateral view of a portion of a human spine with vertebrae **1000** and intervertebral discs **1010** showing the location of the nucleus pulposus **1020** in dashed outline surrounded by overlapping layers of the annulus fibrosus. FIGS. **11A** and **11B** are cross-sections through the intervertebral disc as indicated in FIG. **10**. In the embodiment of the procedure shown in FIG. **11A**, energy delivery devices **192** of two probe assemblies **106** are located partially in the nucleus pulposus and partially in the annulus fibrosis of intervertebral disc **1010** so that at least an equal amount of energy is delivered to the nucleus pulposus as to the annulus fibrosis. An alternate placement of probe assemblies **106** towards the anterior of the intervertebral disc is illustrated in FIG. **11B**. Placement of probe assemblies **106** in this region of the disc could be used for treating anterior fissures or for various other applications in the anterior region of the disc. Alternatively, for some procedures, one probe assembly **106** may be placed in the anterior and one in the posterior of the disc. Other placements are possible for probe assemblies **106** depending on the desired treatment, and the invention is not intended to be limiting in this regard.

Proper positioning of the probe assemblies **106** may be determined using radiopaque markers associated with the introducer, stylet or probe assembly, or any combination thereof. Positioning may be further confirmed by injecting a small amount of radiopaque contrast solution into the disc. The optimal distance between probe assemblies **106** may vary according to disc location, disc size or geometry, hydration, degree of degeneration or other parameters. Motor and/or sensory stimulation may be used before or after the procedure to confirm the location of the probe assemblies and the success of the procedure. Such stimulation may be done in monopolar or bipolar modes, as described in greater detail below.

Using a system of the present invention is beneficial because the use of two probe assemblies **106** in a bipolar configuration allows for the creation of a relatively uniform lesion between the distal tip regions **190** of the two probes. Using liquid-cooled probe assemblies **106** with an appropriate feedback control system as described above also contributes to the uniformity of the treatment. Cooling distal tip regions **190** of probe assemblies **106** helps to prevent excessively high temperatures in these regions which may lead to tissue adhering to probe assemblies **106** as well as an increase in the impedance of tissue surrounding distal tip regions **190** of probe assemblies **106**. Thus, by cooling distal tip regions **190** of probe assemblies **106**, higher power can be delivered to tissue with a minimal risk of tissue charring at or immediately surrounding distal tip regions **190**. Delivering higher power to energy delivery devices **192** allows tissue further away from the energy delivery devices **192** to reach a tem-

perature high enough so as to create a lesion and thus the lesion will not be limited to a region of tissue immediately surrounding energy delivery devices 192 but will rather extend preferentially from an distal tip region 190 of one probe assembly 106 to the other.

This concept is illustrated in FIG. 12A, showing a graph of temperature vs. distance in a tissue with uniform thermal/electrical properties. The distal tip regions 190 of the two probe assemblies 106 are located at positions p1 and p2 on the x-axis and the temperature needed to create a lesion is noted as T_{LES} on the y-axis. In FIGS. 12A and 12B, solid lines 1202 and 1204 represent a cooled probe assembly, while dashed lines 1201 and 1203 represent a non-cooled probe assembly. In order to create a lesion extending from p1 to p2, a large amount of power must be supplied to energy delivery devices 192 so that the energy will be transmitted over a far enough distance away from energy delivery devices 192 to create the lesion. Without the benefits of cooling, the higher the power that is supplied to energy delivery device 192, the higher the temperature around the energy delivery device 192 will be. Curve 1201 shows a temperature profile, as may be typically achieved using non-cooled probes in a uniform tissue. In such a configuration it is difficult to create a lesion extending from p1 to p2 because by supplying a large amount of power to energy delivery device 192, the temperature at the locations p1 and p2 of the distal tip regions reaches very high levels. High temperatures at the distal tip regions may cause nearby tissue to char and possibly adhere to distal tip regions 190. Furthermore, raising the temperature of tissue causes the impedance of the tissue to increase and limits the penetration of current into the tissue, thereby limiting the size of the lesion that can be created. In contrast, cooled probe assemblies may be used to form a desired lesion between p1 and p2 while reducing such temperature effects. Curve 1202 shows a typical temperature profile for a uniform tissue as may be seen when using two cooled probe assemblies. The temperatures at the distal tip regions, p1 and p2, are reduced relative to the surrounding tissue due to the effect of the cooling. This allows for higher power to be transmitted to energy delivery devices 192 without concern for tissue charring. In addition, because the temperature of tissue surrounding energy delivery device 192 is reduced, the impedance of the surrounding tissue will not increase significantly and therefore current supplied by energy delivery device 192 can penetrate more deeply into the tissue. As illustrated in FIG. 12A, a lesion can therefore be created between p1 and p2 using cooled probe assemblies 106 due to the lower local temperatures at p1 and p2. Although FIG. 12A shows the temperature at p1 and p2 to be below the lesioning temperature, the cooling supplied to the cooled probe assemblies may be reduced or eliminated allowing the temperature of tissue around p1 and p2 to increase in order to complete the lesion between p1 and p2.

In certain procedures, treatment with radio frequency energy in the absence of tissue heating may be beneficial. For example, collagen production by chondrocytes has been shown to be increased by treatment with radio frequency energy. Alternatively, some other biochemical or biological effect may be produced. FIG. 12B depicts energy vs. relative distance in a similar graph to FIG. 12A, where curves 1203 and 1204 depict non-cooled and cooled probe assemblies, respectively. As described above, the use of cooled probe assemblies allows the user to deliver more energy to larger tissue areas while minimizing the heating effects on tissue surrounding distal tip regions 190.

A system of the present invention may also be used in intraosseous procedures. Such procedures can treat a tumor in the bone or to denervate a neural structure within the bone. In

an intraosseous procedure, introducer tubes are generally used to gain access to the bone to be treated, for example, a vertebra of a spinal column. In the context of this description, denervation refers to any function that is performed on neural structures so as to intervene with the transmission of a sensory signal (including pain signals) in a nerve associated with said neural structure. As is the case with procedures related to intervertebral discs, two probes may be inserted to spaced-apart sites within a bone and energy may be delivered to energy delivery means located at the distal regions of the probes. One benefit of using two probe assemblies in a bipolar configuration, as in a system of the present invention, is that knowledge of the precise location of the tissue to be treated is not necessary. As has been mentioned, use of bipolar probes allows for a lesion to be created preferentially between the two energy delivery devices. Therefore, so long as the tissue to be treated (e.g. a tumor or a neural structure) is located substantially between the distal regions of the two probes, it will generally be affected by the treatment procedure. Further applications of a device and/or system of the present invention may include, but are not limited to, the treatment of tumors in other parts of the body or for cardiac ablation.

As an additional feature of the method aspect of the present invention, certain embodiments may further comprise a step of performing a function to map the neural pathways in the tissue or to determine the proximity of one of the energy delivery devices 192 to a neural structure and this step may occur one or more times throughout the course of the procedure. This step can involve, in one embodiment, stimulation of the neural tissue at one or more frequencies and subsequent observation to determine the effect of said stimulation. For example, to assess proximity to the target nerve, electrical energy is applied to the energy delivery device using a frequency that excites sensory nerves, typically 30-70 Hz with a current of up to 1 mA. To confirm that the probe is not in proximity to an untargeted nerve, motor nerve stimulation is performed typically at a frequency of 1-5 Hz and a current of 3-5 mA. As is well known in the art, various frequencies and voltages can be used to stimulate both sensory and motor nerves. Observation of said stimulation can take the form of visual, sensory, mechanical, or electrical detection of muscle activity, or the form of sensory or electrical detection of nociceptive or other sensory neural activity (e.g. temperature sensation). The electrical energy ("stimulation energy") applied during this step is beneficially capable of eliciting a response from a neural structure without damaging the neural structure. Using this step, it can be determined whether a target nerve or nerves has a function that would contraindicate its ablation or functional alteration. In one embodiment, the lack of a contraindication would lead to the step of delivering energy, whereas the presence of a contraindication would lead back to the step of inserting one or more probe assemblies, whereby the step of inserting a probe assembly includes modifying the position of a probe assembly within the body. Furthermore, in some embodiments, a method of this aspect of the present invention may comprise a step of stimulating neural tissue after a treatment procedure in order to determine the effectiveness of the treatment procedure. A stimulation step, as has been described, may be performed in a monopolar mode, wherein energy configured to stimulate a nerve is concentrated around a distal tip region of a single probe assembly in order to assess the proximity of neural tissue to that probe assembly. Alternatively, a stimulation procedure may be performed in a bipolar mode, wherein energy configured to stimulate a nerve is preferentially concentrated between the distal tip regions of two probe assemblies, thus allowing a user to detect neural tissue located substantially

27

between the probe assemblies. In general, it may be beneficial to perform a stimulation step employing a similar probe assembly configuration as will be used to deliver energy. Thus, if energy will be delivered using a monopolar configuration, it may be beneficial to perform a stimulation step in a monopolar configuration as well. Similarly, if energy will be delivered using a bipolar configuration, it may be beneficial to perform a stimulation step in a bipolar configuration, as has been described.

As has been mentioned, a system of the present invention may be used to produce a relatively uniform lesion substantially between two probe assemblies **106** when operated in a bipolar mode. Oftentimes, uniform lesions may be contraindicated, such as in a case where a tissue to be treated is located closer to one energy delivery device **192** than to the other. In cases where a uniform lesion may be undesirable, using two or more cooled probe assemblies **106** in combination with a suitable feedback and control system may allow for the creation of lesions of varying size and shape. For example, preset temperature and/or power profiles that the procedure should follow may be programmed into a generator prior to commencement of a treatment procedure. These profiles may define parameters (these parameters would depend on certain tissue parameters, such as heat capacity, etc.) that should be used in order to create a lesion of a specific size and shape. These parameters may include, but are not limited to, maximum allowable temperature, ramp rate (i.e. how quickly the temperature is raised) and the rate of cooling flow, for each individual probe. Based on temperature or impedance measurements performed during the procedure, various parameters, such as power or cooling, may be modulated, in order to comply with the preset profiles, resulting in a lesion with the desired dimensions.

Similarly, it is to be understood that a uniform lesion can be created, using a system of the present invention, using many different pre-set temperature and/or power profiles which allow the thermal dose across the tissue to be as uniform as possible, and that the present invention is not limited in this regard.

It should be noted that the term radiopaque marker as used herein denotes any addition or reduction of material that increases or reduces the radiopacity of the device. Furthermore, the terms probe assembly, introducer, stylet etc. are not intended to be limiting and denote any medical and surgical tools that can be used to perform similar functions to those described. In addition, the invention is not limited to be used in the clinical applications disclosed herein, and other medical and surgical procedures wherein a device of the present invention would be useful are included within the scope of the present invention.

It is appreciated that certain features of the invention, which are, for clarity, described in the context of separate embodiments, may also be provided in combination in a single embodiment. Conversely, various features of the invention, which are, for brevity, described in the context of a single embodiment, may also be provided separately or in any suitable subcombination.

Although the invention has been described in conjunction with specific embodiments thereof, it is evident that many alternatives, modifications and variations will be apparent to those skilled in the art. Accordingly, it is intended to embrace all such alternatives, modifications and variations that fall within the spirit and broad scope of the appended claims.

We claim:

1. A medical probe assembly for delivering energy to a patient's body, the probe assembly comprising:

28

an elongate member having a distal region and a proximal region, said distal region comprising an electrically non-conductive outer circumferential portion;

an electrically conductive energy delivery device extending distally from said electrically non-conductive outer circumferential portion for delivering one of electrical and rf energy to the patient's body, said energy delivery device having a conductive outer circumferential surface and an internal lumen configured for internal longitudinal flow of a cooling fluid to a distal end of said energy delivery device; and

an electrically conductive protrusion extending from said distal end of said energy delivery device and having a diameter that is less than a diameter of said energy delivery device, said electrically conductive protrusion being electrically coupled to said energy delivery device for delivering one of electrical and rf energy to the patient's body and comprising a temperature sensing element, said electrically conductive protrusion protruding distally beyond said lumen such that said cooling fluid does not flow into said electrically conductive protrusion and said temperature sensing element being located within said protrusion such that said cooling fluid does not contact said temperature sensing element, thereby allowing for a more accurate indication of the temperature of tissue proximate to said energy delivery device.

2. The probe assembly of claim 1, further comprising a means of delivering a fluid to, and removing said fluid from, said lumen.

3. The probe assembly of claim 2, wherein the means of delivering and removing fluid comprises at least two tubular members.

4. The probe assembly of claim 3, wherein said at least two tubular members are located adjacent each other.

5. The probe assembly of claim 3, further comprising at least two flexible tubular members associated with said proximal region of said elongate member, wherein said at least two flexible tubular members are coupled to said at least two tubular members.

6. The probe assembly of claim 5, wherein said temperature sensing element is a thermocouple and wherein at least a portion of said protrusion is a component of said thermocouple.

7. The probe assembly of claim 2, further comprising a flow impeding structure for restricting circulation of said fluid to said lumen.

8. The probe assembly of claim 1, wherein said temperature sensing element is selected from the group consisting of a thermocouple, a thermistor, a thermometer and an optical fluorescent sensor.

9. The probe assembly of claim 1, further comprising at least one secondary temperature sensor.

10. The probe assembly of claim 9, further comprising at least one thermal insulator for thermally insulating one or more of said temperature sensing element and said at least one secondary temperature sensor.

11. The probe assembly of claim 10, wherein said thermal insulator insulates said at least one secondary temperature sensor from said cooling fluid.

12. The probe assembly of claim 9, wherein said at least one secondary temperature sensor is located proximate to an inner wall of said elongate member.

13. The probe assembly of claim 1, further comprising at least one radiopaque marker.

14. The probe assembly of claim 1, further comprising at least one visible marker.

29

15. The probe assembly of claim 1, further comprising at least one tactile marker.

16. The probe assembly of claim 1, further comprising an active shape control mechanism for directing at least a portion of said distal region of said elongate member as it is advanced through said patient's body.

17. A system for delivering energy to a patient's body, comprising:

an energy source; and

an elongate member having a distal region with an electrically non-conductive outer circumferential portion and a proximal region, an electrically conductive energy delivery device extending distally from said electrically non-conductive outer circumferential portion for delivering one of electrical and rf energy to the patient's body and having an electrically conductive outer circumferential surface and a longitudinally extending internal lumen for receiving a cooling fluid flow to a distal end of said energy delivery device, and

an electrically conductive protrusion having a diameter less than a diameter of said energy delivery device and extending distally from and being electrically coupled to said energy delivery device for delivering one of electrical and rf energy to the patient's body and comprising a temperature sensing element, said electrically conductive protrusion protruding beyond said lumen such that said cooling fluid does not flow into said electrically conductive protrusion, said temperature sensing element being located within said protrusion such that said cooling fluid does not contact said temperature sensing element.

18. The system of claim 17, further comprising: an apparatus coupled to at least two of the probe assemblies, said apparatus operable to reduce a temperature of the probe assemblies to which it is coupled; and a controller operable to control an operation of said apparatus with respect to each of said probe assemblies to which it is coupled, wherein the operation of said apparatus for one probe to which said apparatus is coupled is independent of the operation of said apparatus for any other probe to which said apparatus is coupled.

19. A method of treating tissue of a patient's body, the method comprising:

providing an energy source and first and second probe assemblies, wherein each of the probe assemblies comprises an elongate member having a distal region with an electrically non-conductive outer circumferential portion and a proximal region, an electrically conductive energy delivery device extending distally from said electrically non-conductive outer circumferential portion for delivering one of electrical and rf energy to the patient's body and having an electrically conductive outer circumferential surface and an internal longitudinally extending lumen for receiving a cooling fluid flow to a distal end of said energy delivery device, and an electrically conductive protrusion having a diameter that is less than a diameter of said energy delivery device extending distally from and being electrically coupled to said energy delivery device for delivering one of electrical and rf energy to the patient's body and comprising a temperature sensing element, said electrically conductive protrusion protruding beyond said lumen such that said cooling fluid does not flow into said electrically conductive protrusion, said temperature sensing element being located within said protrusion such that said cooling fluid does not contact said temperature sensing element;

30

inserting said energy delivery devices of said first and second probe assemblies into spaced-apart treatment sites for said tissue;

delivering energy from said energy source to said tissue through said energy delivery devices; and

measuring a temperature using at least one of the temperature sensing elements.

20. The method of claim 19, further comprising a step of controlling the delivery of energy based on the temperature measured by said at least one temperature sensing element.

21. A medical probe assembly for delivering energy to a patient's body, the probe assembly comprising:

an elongate member having a distal region and a proximal region, said distal region comprising an electrically non-conductive outer circumferential portion;

an electrically conductive energy delivery device extending distally from said electrically non-conductive outer circumferential portion for delivering one of electrical and rf energy to the patient's body, said energy delivery device having an electrically conductive outer circumferential surface and an internal longitudinally extending lumen configured for receipt of an internal cooling fluid along the length of said energy delivery device; and

an electrically conductive protrusion having a diameter less than a diameter of said energy delivery device and extending from a distal end of said energy delivery device and being electrically coupled to said energy delivery device for delivering one of electrical and rf energy to the patient's body and comprising a temperature sensing element, said electrically conductive protrusion protruding beyond said lumen such that said cooling fluid does not flow into said electrically conductive protrusion;

said temperature sensing element protruding beyond said energy delivery device said that it is not affected by the cooling fluid flowing within the lumen.

22. A medical probe assembly for delivering energy to a patient's body, the probe assembly comprising:

an elongate member having a distal region and a proximal region, said distal region comprising an electrically non-conductive outer circumferential portion;

an electrode extending distally from said electrically non-conductive outer circumferential portion for delivering one of electrical and rf energy to the patient's body, said electrode having an electrically conductive outer circumferential surface and a longitudinally extending internal lumen configured for receipt of an internal cooling fluid along the length of said electrode; and

an electrically conductive protrusion having a diameter that is less than a diameter of said energy delivery device extending from a distal end of and being electrically coupled to said electrode for delivering one of electrical and rf energy to the patient's body and comprising a temperature sensing element, said electrically conductive protrusion protruding beyond said lumen such that said cooling fluid does not flow into said electrically conductive protrusion, the protrusion comprising an electrically conductive tube and said temperature sensing element comprising a thermocouple junction formed within the tube by joining an inner surface of the tube to a wire made from a dissimilar metal, whereby said thermocouple junction is positioned within said protrusion and is separated from said cooling fluid.

* * * * *