

US009358155B2

(12) United States Patent

Sorensen et al.

(54) DUAL BLADE OPHTHALMOLOGIC SURGERY DEVICE

- (71) Applicant: Neomedix Corporation, Tustin, CA (US)
- (72) Inventors: John T. Sorensen, Lake Elsinore, CA (US); Michael Mittelstein, Laguna Niguel, CA (US); Soheila Mirhashemi, Laguna Niguel, CA (US)
- (73) Assignee: NeoMedix Corporation, Tustin, CA (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
- (21) Appl. No.: 14/789,632
- (22) Filed: Jul. 1, 2015

(65) **Prior Publication Data**

US 2015/0297400 A1 Oct. 22, 2015

Related U.S. Application Data

(60) Continuation of application No. 14/481,754, filed on Sep. 9, 2014, now Pat. No. 9,107,729, which is a division of application No. 13/159,356, filed on Jun. 13, 2011, now abandoned, which is a division of

(Continued)

(51)	Int. Cl.	
	A61B 17/32	(2006.01)
	A61F 9/007	(2006.01)
		(Continued)

(Continued)

(10) Patent No.: US 9,358,155 B2

(45) **Date of Patent:** Jun. 7, 2016

(56) **References Cited**

U.S. PATENT DOCUMENTS

421,855	Α	*	2/1890	Burk	B26B 3/04
637.463	А	*	11/1899	Router	30/304 B25D 3/00
			04000		30/167
2,130,949	A	*	9/1938	Collens	A47J 17/04 30/113.3

(Continued)

FOREIGN PATENT DOCUMENTS

EP	0073803 A1	3/1983
EP	1455098 AI	9/2004

(Continued)

OTHER PUBLICATIONS

US Patent Office Action dated Sep. 29, 2009 in related U.S. Appl. No. 10/560,267, filed May 11, 2006.

(Continued)

Primary Examiner — Amy R Weisberg (74) Attorney, Agent, or Firm — Robert D. Buyan; Stout, Uxa & Buyan, LLP

(57) **ABSTRACT**

A dual blade device comprising an elongate probe having first and lateral second cutting edges and a blunt protruding distal tip, useable for performing an ab interno procedure to remove a strip of trabecular meshwork tissue from a human eye.

7 Claims, 3 Drawing Sheets



Related U.S. Application Data

application No. 10/560,267, filed as application No. PCT/US2004/018488 on Jun. 10, 2004, now Pat. No. 7,959,641.

- (60) Provisional application No. 60/477,258, filed on Jun. 10, 2003.
- (51) Int. Cl.

A61B 18/14	(2006.01)
A61B 18/00	(2006.01)

(52) U.S. Cl. CPC A61B 2018/00083 (2013.01); A61B 2018/1497 (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,220,169	А	*	11/1940	Murdock A47J 17/02 30/127
2,364,333	A	*	12/1944	Wisher A22C 25/025
3.294.085	А		12/1966	Wallace
3,365,798	Â	*	1/1968	Cunningham A61F 15/02
3,882,872	A	*	5/1975	Douvas A61B 17/32
3,972,117	A	*	8/1976	Fogg B26B 27/00 30/287
4,255,854	A	*	3/1981	Bilbao B26B 27/00 30/114
4,365,957	A	*	12/1982	Das A61C 3/02
4,472,879	A	*	9/1984	Sizemore, Jr B26B 3/03
4 501 274	А		2/1985	Skiaerne
4.689.040	A	*	8/1987	Thompson A61B 17/22004
1,005,010	••		0, 19 0 /	604/22
4,706,669	Α	*	11/1987	Schlegel A61F 9/0133
4 712 546	Δ	*	12/1987	606/107 Noe 461B 17/32
-,, 12,5-10	11		12/1907	433/144
4,753,234	Α	*	6/1988	Martinez A61F 9/00763 30/241
4,759,746	A	*	7/1988	Straus A61F 9/007
4,841,984	A	*	6/1989	Armeniades A61B 3/16
4,900,300	A	*	2/1990	Lee A61B 10/04
4,955,883	A	*	9/1990	604/22 Nevyas A61F 9/00781
4,955,887	A	*	9/1990	Contraction Contra
5,019,035	A	*	5/1991	606/107 Missirlian A61F 9/00763
5,112,299	A	*	5/1992	604/22 Pascaloff A61B 17/32002
5,123,904	Α	*	6/1992	604/22 Shimomura A61B 17/32002
5 200 792			12/1002	604/22
5,209,782	A	*	2/1004	Sugman A61E 0/00763
3,204,472	A		2/1994	604/22
5,431,646	Α		7/1995	Vassiliadis et al.
5,431,671	Α		7/1995	Nallakrishnan
5,458,596	Α		10/1995	Lax et al.
5,529,580	Α	*	6/1996	Kusunoki A61B 17/32002
5,540,706	A	*	7/1996	Aust A61B 17/32002
5,540,708	A	*	7/1996	Lim A61B 17/32002
5.569.283	А		10/1996	Green et al.
5,681,282	Ā		10/1997	Eggers et al.
,,				00

5,733,297	A *	3/1998	Wang A61F 9/00763
5,755,716 5,807,277	A A *	5/1998 9/1998	Garito et al. Swaim A61B 10/025
5,843,106	A *	12/1998	600/567 Heisler B24B 3/40
5,885,279	A *	3/1999	Bretton A61F 9/00736
5,922,003	A *	7/1999	Anctil A61B 17/32002
5,957,881	A *	9/1999	Peters A61B 17/32002
5,957,914	A *	9/1999	Cook A61B 18/26
5,964,777	A *	10/1999	Drucker A61B 17/32002 604/22
6,004,199	A *	12/1999	Habenicht A22C 21/0023 452/166
6,068,629	Α	5/2000	Haissaguerre
6,213,997	B1	4/2001	Hood et al.
6,217,598	B1 *	4/2001	Berman A61B 17/32002 606/167
6,283,961	B1	9/2001	Underwood et al.
6,290,699	B1	9/2001	Hall et al.
6.293.957	B1	9/2001	Peters et al.
6.382.974	B1 *	5/2002	Garfinkel A61C 3/00
-,,			433/141
6 388 043	B1	5/2002	Langer et al
6 4 10 6 84	B1*	7/2002	Heisler A61B 17/32002
0,419,004	ы	772002	A01517/32002
6,428,539	B1 *	8/2002	Baxter A61B 17/320016
6 432 104	B1	8/2002	Durgin et al
6 407 712	DI	12/2002	Exector
DE29.019	DI E	2/2002	A patil at al
KE38,018	E	3/2003	Anctil et al.
6,557,258	BI*	5/2003	Roberts B26B 29/00
			30/1.5
6,720,402	B2	4/2004	Langer et al.
6,759,481	B2	7/2004	Tong
6,979,328	B2	12/2005	Baerveldt et al.
7,131,975	B2 *	11/2006	Adams A61B 17/26
7 244 256	B)*	7/2007	606/101 DeCesare A61B 18/148
7,244,250	D2	5/2000	606/41
7,374,566	BI	5/2008	Schossau
7,604,663	BI	10/2009	Reimink et al.
7,632,303	B1	12/2009	Stalker et al.
7,648,591	B2	1/2010	Furst et al.
7,785,321	B2	8/2010	Baerveldt et al.
7,842,034	B2	11/2010	Mittelstein et al.
7.935.131	B2	5/2011	Anthamatten et al.
7 955 387	B2	6/2011	Richter
7,050,507	D2 D2	6/2011	Soronson et al
8,028,022	D2 D2	10/2011	Derman et al
8,038,923	D2	10/2011	Berger et al.
8,069,546	BI *	12/2011	whittemore B26B 3/04
8,147,424	B2 *	4/2012	29/408 Kassab A61B 17/0057
2001/0034932	A1*	11/2001	600/564 MacDonald B26B 3/04
2001/0053873	41*	12/2001	29/428 Schaaf 461E 9/00781
2001/0033873		1/2001	600/104
2002/0002372	AI	1/2002	Janns et al.
2002/0026205	AI	2/2002	Matsutani et al.
2002/0038129	A1*	3/2002	Peters A61B 17/32002
			606/167
2002/0111608	A1*	8/2002	Baerveldt A61F 9/00781 606/6
2003/0208217	A1	11/2003	Dan
2004/0138685	Δ1*	7/2004	Claque A61B 17/12
2007/0130003	A 1	112004	Chagae A01D 17/12
2004/0152111	A 1 *	8/2004	Hosoada 461D 17/22002
2004/0100111	AI*	0/2004	HUSUADA A01B 1//32002
			606/167
2004/0204732	Al*	10/2004	Muchnik A61F 9/00763
			606/171
2004/0210245	A1*	10/2004	Erickson A61B 17/3401

(56) References Cited

U.S. PATENT DOCUMENTS

2005/0090849	A1*	4/2005	Adams A61B 17/320016
			606/180
2005/0159767	A1*	7/2005	Adams A61B 17/32002
			606/180
2006/0095055	A1*	5/2006	Douglas A61B 17/32
			606/159
2006/0106370	A1	5/2006	Baerveldt et al.
2006/0149194	A1	7/2006	Conston et al.
2006/0149267	A1*	7/2006	Nordt A61B 17/320016
			606/79
2006/0200180	A1*	9/2006	Lee A61B 17/320016
			606/169
2006/0212060	A1*	9/2006	Hacker A61B 17/320016
			606/180
2006/0241580	A1*	10/2006	Mittelstein A61B 18/1482
			606/41
2007/0010812	A1*	1/2007	Mittelstein A61B 18/1482
			606/48
2007/0073275	A1	3/2007	Conston et al.
2007/0149974	A1*	6/2007	Mangione
2001/01/05/11		0/2001	606/79
2007/0276420	A1*	11/2007	Sorensen A61B 18/1482
			606/167
2008/0077146	A1*	3/2008	Pernsteiner A61B 17/3213
		0.2000	606/79
2009/0248141	A1	10/2009	Shandas et al
2009/0287233	A1*	11/2009	Huculak A61F 9/00781
			606/167
2011/0077626	A1	3/2011	Baerveldt et al
2011/0230877	Al	9/2011	Huculak et al.
2012/0083727	Al	4/2012	Barnett
2012/0123533	A1*	5/2012	Shiney
2012/0120000		0/2012	623/5.11
2012/0191120	A1*	7/2012	Linsi A61B 17/3201
2012/01/11/20			606/174
2015/0045820	A1*	2/2015	Kahook A61F 9/00736
2010/00/0020		2,2013	606/170
			000/1/0

FOREIGN PATENT DOCUMENTS

EP	1615604 A1	1/2006
EP	2303203 A1	4/2011
JP	46-25677 Y1	9/1971
KR	1020040058309 A	3/2004
WO	WO 91/17793 A1	11/1991
WO	WO 98/27876 A	7/1998
WO	WO01/78631 A2	10/2001
WO	WO 02/056805 A	7/2002
WO	WO03/045290 A1	6/2003
WO	WO2004/093761 A1	11/2004
WO	WO2004/110501 A2	12/2004
WO	WO2009/140185 A1	11/2009
WO	WO 2011/030081 A1	3/2011

OTHER PUBLICATIONS

US Patent Office Action dated Mar. 12, 2010 in related U.S. Appl. No. 10/560,267, filed May 11, 2006.

Jacobi, Philipp C., et al. "Technique of Goniocurettage: A Potential Treatment for Advanced Chronic Open Angle Glaucoma," British Journal of Ophthalmology, 1997; 81, pp. 302-307.

Soohoo, Jeffrey R., et al. "Ab Interno Trabeculectomy in the Adult Patient," Middle East African Journal of Ophthalmology, vol. 22, No. 1, Jan.-Mar. 2015, pp. 25-29.

Ting, J. L. M. et al., (2012) "Ab interno trabeculectomy: Outcomes in exfoliation versus primary open-angle glaucoma," J Cataract. Refract. Surg. 38(2),315-323.

Francis, B. A. et al., (2006) "Ab interno trabeculectomy: development of a novel device (Trabectome) and surgery for open-angle glaucoma," J Glaucoma 15(1), 68-73.

Minckler, D. S. et al., (2005) "Clinical Results with the Trabectome for Treatment of Open-Angle Glaucoma," Ophthalmology 112(6), 962-967.

Tan, Yar-Li, et al., "Postoperative Complications after Glaucoma Surgery for Primary Angle-Closure Glaucoma vs Primary Open-Angle Glaucoma," Arch Ophthalmol. 2011; 129(8), pp. 987-992.

Quigley, H. A. and Broman, A. T., (2006) "The No. Of people with glaucoma worldwide in 2010 and 2020," Br. J Ophthalmol. 90(3),262-267.

Jacobi, P. C. et al., (1999) "Goniocurettage for removing trabecular meshwork: clinical results of a new surgical technique in advanced chronic open-angle glaucoma," Am. J Ophthalmol. 127(5),505-510. Pantcheva, M. B. and Kahook, M. Y., (2010) "Ab Interno Trabeculectomy," Middle East African Journal of Ophthalmology 17(4), 287-289.

Seibold, L. K. et al., (2013) "Preclinical Investigation of Ab Interno Trabeculectomy Using a Novel Dual-Blade Device," Am. J Ophthalmol. 155(3), 524-529.e522.

Anderson, D.R., (1983) "Trabeculotomy compared to goniotomy for glaucoma in children," Ophthalmology 90 (7),805-806.

Grant, W., (1963) "Experimental aqueous perfusion in enucleated human eyes," Arch.Ophthalmol. 69(6), 783-801.

Grant, W. M., (1951) "Clinical measurements of aqueous outflow," AMA Archives of Ophthalmology 46(2), 113-131.

Herschler, J. and Davis, E. B., (1980) "Modified goniotomy for inflammatory glaucoma. Histologic evidence for the mechanism of pressure reduction," Arch. Ophthalmol. 98(4), 684-687.

Jea, S. Y. et al., (2012) "Ab Interno Trabeculectomy Versus Trabeculectomy for Open Angle Glaucoma," Ophthalmology 119(1), 36-42.

Luntz, M. H. and Livingston, D. G., (1977) "Trabeculotomy ab externo and trabeculectomy in congenital and adult-onset glaucoma," Am. J Ophthalmol. 83(2), 174-179.

* cited by examiner









Fig. 3B













Fig. 5

DUAL BLADE OPHTHALMOLOGIC SURGERY DEVICE

RELATED APPLICATIONS

This application is a continuation of copending U.S. patent application Ser. No. 14/481,754 filed Sep. 9, 2014 and issued as U.S. Pat. No. 9,107,729 on Aug. 18, 2015 which is a division of U.S. patent application Ser. No. 13/159,356 filed Jun. 13, 2011 and currently abandoned, which is a division of U.S. patent application Ser. No. 10/560,267 filed May 11, 2006 and issued as U.S. Pat. No. 7,959,641 on Jun. 14, 2011, which is a 35 U.S.C. §371 national stage of PCT International Patent Application No. PCT/US2004/018488 filed Jun. 10, 2004, which claims priority to U.S. Provisional Patent Application No. 60/477,258 filed on Jun. 10, 2003, the entire disclosure of each such prior patent and application being expressly incorporated herein by reference.

BACKGROUND OF THE INVENTION

There are numerous medical and surgical procedures in which it is desirable to cut and remove a strip of tissue of controlled width from the body of a human or veterinary 25 patient. For example, it may sometimes be desirable to form an incision of a controlled width (e.g., an incision that is wider than an incision made by a typical scalpel or cutting blade) in the skin, mucous membrane, tumor, organ or other tissue or a human or animal. Also, it may sometimes desirable to remove 30 a strip or quantity of tissue from the body of a human or animal for use as a biopsy specimen, for chemical/biological analysis, for retention or archival of DNA identification purposes, etc. Also, some surgical procedures require removal of a strip of tissue of a known width from an anatomical location 35 within the body of a patient.

One surgical procedure wherein a strip of tissue of a known width is removed from an anatomical location within the body of a patient is an ophthalmological procedure used to treat glaucoma. This ophthalmological procedure is some- 40 times referred to as a goniectomy. In a goniectomy procedure, a device that is operative to cut or ablate a strip of tissue of approximately 2-10 mm in length and about 50-200 µm in width is inserted into the anterior chamber of the eye and used to remove a full thickness strip of tissue from the trabecular 45 meshwork. The trabecular meshwork is a loosely organized, porous network of tissue that overlies a collecting canal known as Schlemm's canal. A fluid, known as aqueous humor, is continually produced in the anterior chamber of the eye. In normal individuals, aqueous humor flows through the 50 trabecular meshwork, into Shlemm's Canal and out of the eye through a series of ducts. In patients who suffer from glaucoma, the drainage of aqueous humor from the eye may be impaired by elevated flow resistance through the trabecular meshwork, thereby resulting in an increase in intraocular 55 pressure. The goniectomy procedure can restore normal drainage of aqueous humor from the eye by removing a full thickness segment of the trabecular meshwork, thus allowing the aqueous humor to drain through the open area from which the strip of trabecular meshwork has been removed. The 60 goniectomy procedure and certain prior art instruments useable to perform such procedure are described in U.S. patent application Ser. No. 10/052,473 published as No. 2002/ 011608A1 (Baerveldt), the entirety of which is expressly incorporated herein by reference. 65

At present there remains a need in the art for the development of simple, inexpensive and accurate instruments useable to perform the goniectomy procedure as well as other procedures where it is desired to remove a strip of tissue from a larger mass of tissue.

SUMMARY OF THE INVENTION

The present invention provides a device for cutting a strip of tissue of approximate width W from a mass of tissue. The device generally comprises a) an elongate cutting tube that has a distal end and a lumen that opens through an opening in the distal end and b) first and second cutting edges formed on generally opposite edges of the distal end of the cutting tube and separated by a distance D. The cutting tube is advanceable through tissue such that the first and second cutting edges will cut a strip of tissue having approximate width W, wherein the approximate width W is approximately equal to the distance between the first and second cutting edges. In some embodiments, the strip of tissue may be aspirated or otherwise removed through the lumen of the cutter tube. In some ²⁰ embodiments, the device may include apparatus useable to sever (e.g., transversely cut or transect) the strip of tissue when the strip of tissue has reached a desired length.

Further in accordance with the invention there is provided a method for cutting a strip of tissue of width W from a tissue mass. This method generally comprises the steps of a) providing a device that comprises i) an elongate cutting tube that has a distal end and a lumen that opens through an opening in the distal end and ii) first and second cutting edges formed on generally opposite edges of the distal end of the cutting tube and separated by a distance D that is approximately equal to the width W of the strip of tissue to be cut; and b) advancing the distal end of the cutting tube through the mass of tissue such that the first and second cutting edges cut a strip of tissue of approximate width W. Further aspects and elements of the invention will be understood by those of skill in the art upon reading the detailed description of specific examples set forth herebelow.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a perspective view of a system incorporating a needle cutting device of the present invention.

FIG. **2** is an enlarged perspective view of section **2** of FIG. **1**.

FIGS. **3**A-**3**D show various steps in a method for manufacturing a needle cutter of the present invention.

FIG. **4** is a side view of a distal portion of a needle cutter device of the present invention being used to cut a strip of tissue of approximate width W.

FIG. **5** is a perspective view of the distal portion of a needle cuter device of the present invention incorporating apparatus for severing a strip of tissue cut by the needle cutter device after the strip of tissue has reached a desired length.

FIG. 6 is a side view of the distal portion of another embodiment of a needle cutter device of the present invention having a plurality of curves or bends formed in the cutting tube.

DETAILED DESCRIPTION

The following detailed description, and the drawings to which it refers, are provided for the purpose of describing and illustrating certain preferred embodiments or examples of the invention only, and no attempt has been made to exhaustively describe all possible embodiments or examples of the invention. Thus, the following detailed description and the accompanying drawings shall not be construed to limit, in any way, the scope of the claims recited in this patent application and any patent(s) issuing therefrom.

One example of a needle cutter device 10 of the present invention is shown in FIGS. 1-4. This needle cutter device 10 generally comprises an elongate cutting tube 14 that has a 5 distal end and a lumen 27 that opens through an opening in the distal end. First and second cutting edges 20, 22 are formed on generally opposite edges of the distal end of the cutting tube 14. These first and second cutting edges 20, 22 are separated by a distance D, as shown in the distal end view of FIG. 3B. In 10 the particular example shown in the drawings, the first and second cutting edges 20, 22 are located on opposite lateral sides of the distal end of the cutting tube 14 and a blunt, protruding tip 24 is located on the bottom of the distal end of the cutting tube. Also, a blunt edge 26 is located at the top of 15 the distal end of the cutting tube 14. Thus, only the lateral cutting edges 20, 22 are sharp and intended to cut tissue. The blunt, protruding tip 24 can, in some applications, be configured and used to facilitate insertion of the device 10 to its intended location and/or the blunt protruding tip 24 may be 20 20, 22 may be heated such that they will cauterize as the cut. placed in an anatomical or man made grove or channel (e.g., Schlemm's Canal of the eye) such that it will then advance through the channel or groove and guide the advancement and positioning of the remainder of the device 10.

One or more bends or curves may optionally be formed in 25 the cutting tube 14 to facilitate its use for its intended purpose. For example, in the embodiment of the device 10 shown in FIG. 2, a single bend 17 of approximately 90 degrees is formed near the distal end of the cutting tube 14. In the embodiment of the device 10b shown in FIG. 6, two separate 30 bends of approximately 90 degrees each are formed at spaced apart locations on the cutting tube 14, thereby giving the cutting tube 14 a generally U shaped configuration. It will be appreciated that any number of bends or curves, in any direction and of any severity may be formed in the cutting tube 14 35 to facilitate its use in specific procedures or to enable it to be inserted through tortuous anatomical channels of the body. In most cases, the degree of curvature in embodiments where a single bend or curve is formed will be between approximately 30 and approximately 90 degrees and in embodiments where 40 more than one bend or curve are formed in the cutting tube 14 each such bend or curve will typically be between approximately 15 to approximately 90 degrees.

As shown in FIG. 4, when the cutting tube 14 is advanced through tissue, distal end first, the first and second cutting 45 edges 20, 22 will cut a strip ST of tissue having approximate width W, such approximate width W being approximately equal to the distance D between the first and second cutting edges 20, 22. The severed strip ST of tissue will enter the lumen 27 of the cutting tube 14 as the device advances. 50 Negative pressure may be applied to lumen 27 to aspirate the strip ST of tissue and/or fluid and/or other matter through lumen 27.

The device 10 may optionally include a second lumen. Such second lumen may be used for infusion of fluid through 55 the device 10 or for other purposes. In the embodiment shown in FIGS. 1 and 2, the device 10 comprises an outer tube 16 in addition to the cutting tube 14. The cutting tube 14 is of smaller diameter than the outer tube 16 and the cutting tube 14 may extend through the lumen 19 of the outer tube 16 such 60 that a distal portion of the cutting tube 14 extends out of and beyond the distal end of the outer tube 16, as may be seen in FIG. 2. The distal end of the outer tube 16 is tapered and in close approximation with the outer surface of the cutting tube 14. Fluid may be infused through the lumen 19 of the outer 65 tube 16, through the space between the outer surface of the cutting tube 14 and the inner surface of the outer tube 16.

Fluid that is infused through the lumen 19 of the outer tube 16 may flow out of one or more apertures 11 formed near the distal end of the outer tube.

In some embodiments, the device 10 may be equipped with severing apparatus for severing (e.g., transversely cutting or transecting) the strip ST of tissue to fully excise or detach the strip ST of tissue from the remaining tissue mass and/or from the body of a human or animal subject. Such severing apparatus may comprise any suitable type of tissue cutter such as a blade, scissor, guillotine, electrode(s), laser, energy emitting tissue cutter, mechanical tissue cutter, etc. FIG. 5 shows an example of an embodiment of the device 10a wherein monopolar or bipolar electrode(s) 40 are located on the distal end of the cutting tube 14. When it is desired to sever the strip ST of tissue, the electrode(s) is/are energized with sufficient energy to sever the strip ST, thereby disconnecting the strip ST from the remaining tissue mass and/or the body of the human or animal subject.

In some embodiments of the device 10, the cutting edges As those of skill in the art will appreciate, such heating of the cutting edges 20, 22 may be accomplished by placement of electrode(s) near the cutting edges 20, 22 such that, when the electrode(s) is/are energized, the cutting edges 20, 22 will become heated to a temperature suitable for the desired cauterization function.

The needle cutter device 10 of the present invention may optionally be used as part of a system 12, as shown in FIG. 1. The basic components of the system 12 comprise an aspiration pump module 74 and a source of irrigation fluid 72, mounted on a surgical roller cart 70. Control of the console functions during procedures may be accomplished by an aspiration foot pedal 78 which controls an aspiration pump 74 and variation in the height of the source of infusion fluid 72 to change the gravity fed pressure or flow rate of infusion fluid through the device. A pinch valve, or other means, may also be incorporated in the console to control flow of the irrigation fluid to the needle cutter device 10. In embodiments that include apparatus (e.g., electrode(s)) for heating the cutting edges 20, 22 and/or for severing the strip ST of tissue (FIG. 5), the system 11 may additionally comprise an electrical current source, such as an electrosurgical generator 76 and electrosurgical foot pedal 80 which controls the electrosurgical generator to deliver desired amount(s) of energy to the electrode(s) or other electrical elements (e.g., resistance heater(s), etc.) on the device 10. As an option, all of the basic control functions of system 12 may be integrated into a single foot pedal to facilitate use.

The device 10 may be provided as a pre-sterilized, singleuse disposable probe or tip that is attachable to a standard surgical irrigation/aspiration handpiece such as that commercially available as The Rhein I/A Tip System from Rhein Medical, Inc., Tampa, Fla. After the device 10 has been attached to the handpiece, it may be connected to any or all of the electrosurgical generator module 76, aspiration pump module 74 and the source of irrigation fluid 72, as shown. Thus, the device 10 may be fully equipped for irrigation, aspiration, and electrosurgical capabilities, as described herein.

FIGS. 3A-3D show an example of a method for manufacturing the cutting tube 14 from standard tubing (e.g., stainless steel hypodermic tubing). Initially, the distal end of a tube is cut to form the lateral cutting edges 20, 22, the protruding tip 24 and the blunt top edge 26. Thereafter, if it is desired to have one or more bends or curves in the cutting tube 14, angular cut out(s) 30 may be formed in the tube 14, as shown in FIG. 3C. Thereafter, the tube 14 is bent to bring the edges of each angular cut out **30** into apposition and weld, adhesive or other joining techniques are used to weld or join the apposed edges of the cut outs together, thereby forming the desired bend(s) or curve(s) in the cutting tube **14**. Likewise, if it is desired to have one or more bends or curves in the cutting tube **14**, the 5 tube **14** may be directly bent to form said curves or bends without the use of angular cut outs(s) **30**. It may be appreciated that the use of angular cut-out(s) **30** allow a tube **10** of a given diameter to incorporate a curve or angle in a more compact form than is possible by bending tubing **10** of a given 10 diameter to said curve or angle without kinking or damaging tube **10**.

The device **10** and system **12** are useable to perform a variety of procedures wherein it is desired to form an incision or opening of a desired width or to remove, from a mass of 15 tissue, a strip ST of tissue of a desired width.

One particular procedure that may be performed to treat glaucoma, using the device **10** and system **12** of the present invention, is a goniectomy. As explained herein a goniectomy procedure is an ab interno surgical procedure wherein a sector 20 of the trabecular meshwork is removed from the eye of the patient to facilitate drainage of aqueous humor from the anterior chamber of the eye through Schlemm's Canal and the associated collector channels, thereby relieving elevated intraocular pressure. 25

To perform a goniectomy procedure using the device **10**, first a small incision is made in the cornea at about 3 o'clock in the left eye, or at about 9 o'clock in the right eye. A 1.5 mm slit knife may be used to make this incision.

The device 10 is attached to the source of irrigation fluid 72_{30} (e.g., basic balanced salt solution) such that irrigation fluid will flow through lumen 19 of the outer tube 16 and out of outflow aperture 11. The device 10 is then inserted through the incision and into the anterior chamber of the eye (with irrigation flowing). In some cases, during the insertion of the 35 device 10, the source of irrigation fluid 72 may initially connected to the device such that the irrigation fluid will flow through the lumen 27 of the cutter tube 14. In this manner, irrigation fluid will begin to infuse into the anterior chamber of the eye as soon as the distal end of the cutter tube 14 has 40 entered the anterior chamber, rather than being delayed until the larger outer tube 16 and aperture 11 have been advanced through the incision and into the anterior chamber. By this alternative approach, irrigation fluid may be caused to flow out of the distal end of the cutter tube 14 as the device 10 is 45 being inserted, thereby spreading or opening the incision by hydraulic force while in addition increasing the fluid pressure in the anterior chamber. Such spreading or opening of the incision may facilitate advancement of the larger diameter outer tube 16 through the incision. Pressurizing the fluid in 50 the anterior chamber causes the anterior chamber to deepen and may facilitate maneuvering of device 10 within the anterior chamber. In cases where this alternative approach is used, the source of infusion fluid 72 may be disconnected from lumen 27 of the cutter tube 14 after the device 10 has been 55 inserted into the anterior chamber and, thereafter, the infusion fluid source 72 may be reconnected to lumen 19 of outer tube 16 such that infusion fluid will flow out of aperture 11. Negative pressure (e.g., via aspiration pump module 74) may then be applied to lumen 27 of the cutter tube 14 so as to aspirate 60 fluid and debris through lumen 27 as shown in FIG. 4. The vertical height of the infusion fluid source 72 may be adjusted to provide sufficient gravity feed of infusion fluid to make up for the volume of fluid or matter being aspirated from the anterior chamber through lumen 27, thereby maintaining the 65 desired pressure of fluid within the anterior chamber during the procedure.

A lens device (e.g., Ocular Swan-Jacob Autoclavable Gonioprism, Model OSJAG, Ocular Instruments Inc., Bellevue, Wash.) may be positioned on the anterior aspect of the eye to enable the physician to clearly visualize the angle of the eye where the segment of trabecular meshwork is to be removed. Under direct visualization, the device **10** is advanced until the distal tip of the cutter tube **14** is positioned adjacent to the trabecular meshwork at the location where the strip ST is to be removed. Thereafter, the protruding tip **24** is advanced through the trabecular meshwork and into Schlemm's Canal.

The device 10 is then advanced along Schlemm's Canal, thereby causing the cutting edges 20, 22 to cut a strip of the trabecular meshwork, thereby creating an opening through which aqueous humor may drain from the anterior chamber of the eye.

After a strip of tissue of the desired length (e.g., about 2-10 mm) has been cut by the lateral cutting edges **20**, **22**, any optional tissue severing apparatus (e.g., electrode(s) **40** may be used (if present) to transect or sever the strp ST of tissue thereby disconnecting it from the patient's body and allowing it to be aspirated or drawn into or through lumen **27**.

Thereafter, the aspiration is stopped, the device **10** is removed from the eye, and the infusion is stopped.

Following completion of the surgery, aqueous humor will drain from the anterior chamber through the opening that was created by removal of the strip of tissue from the trabecular meshwork TM.

Although the invention has been described above with respect to certain embodiments and examples, it is to be appreciated that such embodiments and examples are nonlimiting and are not purported to define all embodiments and examples of the invention. Indeed, those of skill in the art will recognize that various modifications may be made to the above-described embodiments and examples without departing from the intended spirit and scope of the invention and it is intended that all such modifications be included within the scope of the following claims.

What is claimed is:

1. A dual blade device useable for performing an ab intern procedure within a human eye to remove a strip of trabecular meshwork tissue, said device comprising:

- a handle configured to be grasped by an operator's hand; an elongate probe comprising a shaft that extends from the handle along a longitudinal axis;
- a blunt protruding tip that extends in a lateral direction from a distal end of the shaft to form a bend or curve of approximately 30 degrees to approximately 90 degrees relative to the adjacent longitudinal axis of the shaft;
- first and second lateral cutting edges formed at stationary side-by-side locations on the shaft, said first and second lateral cutting edges facing in the same lateral direction as the blunt protruding tip and being spaced apart such that an area exists between the first and second lateral cutting edges; and
- a blunt top edge that extends transversely from a top end of the first lateral cutting edge to a top end of the second lateral cutting edge and traverses above the area between the first and second lateral cutting edges;
- the blunt protruding tip having a transverse width, a top surface, a bottom surface and a terminal end, the transverse width being narrowest at the terminal end;
- the blunt protruding tip being below the area between the first and second lateral cutting edges and protruding in the lateral direction beyond the first and second lateral cutting edges such that tissue may pass over the top

5

surface of the blunt protruding tip before coming into contact with the first and second lateral cutting edges;

- a distal portion of the shaft and the blunt protruding tip being sized to pass through an incision formed in the eye by a 1.5 mm slit knife; and
- the blunt protruding tip being further sized to fit within Schlemm's Canal of the human eye and, when so positioned, to be advanceable through Schlemm's Canal with trabecular meshwork tissue passing over its top surface and into contact with the first and second lateral 10 cutting edges.

2. A device according to claim **1** wherein the first and second lateral cutting edges are spaced apart by a distance D and cut a strip of trabecular meshwork tissue having a width W that is substantially equal to distance D.

3. A device according to claim 1 useable for cutting a sector of trabecular meshwork tissue having a length of 2 to 10 millimeters.

4. A device according to claim **1** wherein the bottom surface of the blunt protruding tip extends at an angle of approxi-20 mately 90 degrees relative to the adjacent longitudinal axis of the shaft.

5. A system comprising a device according to claim 1 in combination with a 1.5 mm slit knife for forming said incision in the human eye. 25

6. A device according to claim **1** wherein the device is manually operable to remove a strip of trabecular meshwork tissue.

7. A device according claim 1 wherein the shaft comprises a tube having at least one lumen. 30

* * * * *