



(12) **United States Patent**
Weiman

(10) **Patent No.:** **US 10,925,752 B2**
(45) **Date of Patent:** **Feb. 23, 2021**

(54) **EXPANDABLE FUSION DEVICE AND METHOD OF INSTALLATION THEREOF**

(71) Applicant: **GLOBUS MEDICAL, INC.**, Audubon, PA (US)

(72) Inventor: **Mark Weiman**, Downingtown, PA (US)

(73) Assignee: **Globus Medical, Inc.**, Audubon, PA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 14 days.

(21) Appl. No.: **16/127,395**

(22) Filed: **Sep. 11, 2018**

(65) **Prior Publication Data**

US 2019/0000640 A1 Jan. 3, 2019

Related U.S. Application Data

(60) Continuation of application No. 15/158,829, filed on May 19, 2016, now Pat. No. 10,098,759, which is a (Continued)

(51) **Int. Cl.**

A61F 2/44 (2006.01)
A61F 2/46 (2006.01)
A61F 2/30 (2006.01)

(52) **U.S. Cl.**

CPC **A61F 2/447** (2013.01); **A61F 2/44** (2013.01); **A61F 2/442** (2013.01); **A61F 2/4455** (2013.01); **A61F 2/4611** (2013.01); **A61F 2002/30266** (2013.01); **A61F 2002/30387** (2013.01); **A61F 2002/30405** (2013.01); **A61F 2002/30411** (2013.01); **A61F 2002/30471** (2013.01); **A61F 2002/30482** (2013.01); **A61F 2002/30484** (2013.01); **A61F 2002/30517** (2013.01); **A61F 2002/30522**

(2013.01); **A61F 2002/30523** (2013.01); **A61F 2002/30538** (2013.01); **A61F 2002/30556** (2013.01); **A61F 2002/30558** (2013.01); **A61F 2002/30579** (2013.01); **A61F 2002/30593** (2013.01); **A61F 2002/30601** (2013.01); **A61F 2002/30622** (2013.01); **A61F 2002/30841** (2013.01); **A61F 2002/30843** (2013.01); **A61F 2002/30904** (2013.01);

(Continued)

(58) **Field of Classification Search**

CPC **A61F 2/447**; **A61F 2002/30266**; **A61F 2002/30556**; **A61F 2002/30545**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,349,921 A 9/1982 Kuntz
4,599,086 A 7/1986 Doty
(Continued)

FOREIGN PATENT DOCUMENTS


CA 2088066 A1 1/1992
DE 4012622 C1 7/1991
(Continued)

Primary Examiner — Jan Christopher L Merene

(57) **ABSTRACT**

An expandable fusion device capable of being installed inside an intervertebral disc space to maintain normal disc spacing and restore spinal stability, thereby facilitating an intervertebral fusion. In one embodiment, the fusion device includes a central ramp, a first endplate, and a second endplate, the central ramp capable of being moved in a first direction to move the first and second endplates outwardly and into an expanded configuration. The fusion device is capable of being deployed down an endoscopic tube.

20 Claims, 29 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/109,429, filed on Dec. 17, 2013, now Pat. No. 9,370,434, which is a division of application No. 12/875,818, filed on Sep. 3, 2010, now Pat. No. 8,632,595.

(52) **U.S. Cl.**

CPC *A61F 2220/0016* (2013.01); *A61F 2310/00011* (2013.01); *A61F 2310/00017* (2013.01); *A61F 2310/00023* (2013.01); *A61F 2310/00179* (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

4,863,476 A 9/1989 Shepperd
 4,863,477 A 9/1989 Monson
 5,123,926 A 6/1992 Pisharodi
 5,290,312 A 3/1994 Kojimoto et al.
 5,306,310 A 4/1994 Siebels
 5,375,823 A 12/1994 Navas
 5,390,683 A 2/1995 Pisharodi
 5,522,899 A 6/1996 Michelson
 5,534,030 A 7/1996 Navarro et al.
 5,554,191 A 9/1996 Lahille et al.
 5,571,192 A 11/1996 Schonhoffer
 5,645,596 A 7/1997 Kim
 5,653,763 A 8/1997 Errico et al.
 5,665,122 A 9/1997 Kambin
 5,676,701 A 10/1997 Yuan et al.
 6,039,761 A 3/2000 Li et al.
 6,045,579 A 4/2000 Hochshuler et al.
 6,080,193 A 6/2000 Hochshuler et al.
 6,099,531 A 8/2000 Bonutti
 6,126,689 A 10/2000 Brett
 6,176,882 B1 1/2001 Biedermann et al.
 6,258,125 B1 7/2001 Paul et al.
 6,562,074 B2 5/2003 Gerbec et al.
 6,576,016 B1 6/2003 Hochshuler et al.
 6,554,863 B2 8/2003 Paul et al.
 6,641,614 B1 11/2003 Wagner et al.
 6,648,917 B2 11/2003 Gerbec et al.
 6,666,891 B2 12/2003 Boehm, Jr. et al.
 6,692,495 B1 2/2004 Zacouto
 6,706,070 B1 3/2004 Wagner et al.
 6,752,832 B2 6/2004 Ulrich
 6,830,589 B2 12/2004 Erickson
 6,849,093 B2 2/2005 Michelson
 6,852,129 B2 2/2005 Gerbec et al.
 6,863,673 B2 3/2005 Gerbec et al.
 6,881,228 B2 4/2005 Zdeblick et al.
 7,018,415 B1 3/2006 McKay
 7,070,598 B2 7/2006 Lim et al.
 7,204,853 B2 4/2007 Gordon
 7,217,291 B2 5/2007 Zucherman et al.
 7,282,063 B2 10/2007 Cohen et al.
 7,316,714 B2 1/2008 Gordon
 7,473,276 B2 1/2009 Aebi et al.
 7,547,325 B2 6/2009 Biedermann et al.
 7,621,953 B2 11/2009 Braddock, Jr. et al.
 7,641,693 B2 1/2010 Gutlin et al.
 7,682,396 B2 3/2010 Beaurain et al.
 7,749,270 B2 7/2010 Peterman
 7,753,958 B2 7/2010 Gordon
 7,771,473 B2 8/2010 Thramann
 7,780,732 B2 8/2010 Abernathie
 7,799,081 B2 9/2010 McKinley
 7,815,683 B2 10/2010 Melkent et al.
 7,837,734 B2 11/2010 Zucherman et al.
 7,875,078 B2 1/2011 Wysocki et al.

7,901,409 B2 3/2011 Canaveral et al.
 7,909,869 B2 3/2011 Gordon
 8,123,810 B2 2/2012 Gordon
 8,647,386 B2 2/2014 Gordon
 2002/0045945 A1 4/2002 Liu
 2004/0049271 A1 3/2004 Biedermann
 2004/0054412 A1 3/2004 Gerbec et al.
 2004/0153065 A1 8/2004 Lim
 2005/0021041 A1 1/2005 Michelson
 2005/0021145 A1 1/2005 de Villiers et al.
 2005/0033432 A1 2/2005 Gordon
 2005/0149188 A1 7/2005 Cook
 2005/0171541 A1 8/2005 Boehm
 2005/0251258 A1 11/2005 Jackson
 2005/0273171 A1 12/2005 Gordon
 2005/0273174 A1 12/2005 Gordon
 2005/0278026 A1 12/2005 Gordon
 2005/0283244 A1 12/2005 Gordon
 2005/0283245 A1 12/2005 Gordon
 2006/0004453 A1 1/2006 Bartish, Jr. et al.
 2006/0058878 A1 3/2006 Michelson
 2006/0122701 A1 6/2006 Kister
 2006/0129244 A1 6/2006 Ensign
 2006/0142859 A1 6/2006 Mcluen
 2006/0149385 A1 7/2006 Mckay
 2006/0195192 A1 8/2006 Gordon et al.
 2006/0229729 A1 10/2006 Gordon
 2006/0253201 A1 11/2006 Mcluen
 2007/0043442 A1 2/2007 Abernathie
 2007/0050030 A1 3/2007 Kim
 2007/0050032 A1 3/2007 Gittings et al.
 2007/0055377 A1 3/2007 Hanson et al.
 2007/0191951 A1 8/2007 Branch
 2007/0255415 A1 11/2007 Edie et al.
 2007/0270963 A1 11/2007 Melkent et al.
 2007/0270968 A1 11/2007 Baynham
 2008/0021559 A1 1/2008 Thramann
 2008/0065222 A1 3/2008 Hamada
 2008/0140207 A1 6/2008 Olmos et al.
 2008/0167657 A1 7/2008 Greenhalgh
 2008/0183204 A1 7/2008 Greenhalgh et al.
 2008/0275455 A1 11/2008 Berry et al.
 2008/0281346 A1 11/2008 Greenhalgh et al.
 2008/0288073 A1 11/2008 Renganath et al.
 2008/0300598 A1 12/2008 Barreiro et al.
 2008/0306488 A1 12/2008 Altarac et al.
 2008/0319487 A1 12/2008 Fielding et al.
 2008/0319549 A1 12/2008 Greenhalgh et al.
 2009/0024217 A1 1/2009 Levy et al.
 2009/0125062 A1 5/2009 Amin
 2009/0149956 A1 6/2009 Greenhalgh et al.
 2009/0149959 A1 6/2009 Conner et al.
 2009/0204218 A1 8/2009 Richelsoph
 2009/0222100 A1 9/2009 Cipoletti et al.
 2009/0240334 A1 9/2009 Richelsoph
 2009/0270989 A1 10/2009 Conner et al.
 2009/0281628 A1 11/2009 Oglaza et al.
 2009/0292361 A1 11/2009 Lopez
 2009/0299478 A1 12/2009 Carls et al.
 2009/0312763 A1 12/2009 McCormack
 2010/0049324 A1 2/2010 Valdevit
 2010/0070041 A1 3/2010 Peterman
 2010/0082109 A1 4/2010 Greenhalgh et al.
 2010/0179657 A1 7/2010 Greenhalgh et al.

FOREIGN PATENT DOCUMENTS

DE 4327054 C1 4/1995
 EP 0576379 B1 6/1993
 EP 0610837 B1 7/1994
 SU 1424826 A1 9/1988
 WO 9201428 A1 2/1992
 WO 9525485 A1 9/1995








FIG. 1








FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16








FIG. 17








FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33






FIG. 34






FIG. 37






FIG. 38






FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51




FIG. 52




FIG. 53





FIG. 54






FIG. 56




FIG. 57

1

EXPANDABLE FUSION DEVICE AND METHOD OF INSTALLATION THEREOF

CROSS-REFERENCE TO RELATED APPLICATIONS

This patent application is a continuation of U.S. patent application Ser. No. 15/158,829, filed May 16, 2016, which is a continuation of U.S. patent application Ser. No. 14/109,429, now U.S. Pat. No. 9,370,434, which is a divisional application of U.S. patent application Ser. No. 12/875,818 filed on Sep. 3, 2010, now U.S. Pat. No. 8,632,595, all of which are incorporated by reference herein in their entireties for all purposes.

FIELD OF THE INVENTION

The present invention relates to the apparatus and method for promoting an intervertebral fusion, and more particularly relates to an expandable fusion device capable of being inserted between adjacent vertebrae to facilitate the fusion process.

BACKGROUND OF THE INVENTION

A common procedure for handling pain associated with intervertebral discs that have become degenerated due to various factors such as trauma or aging is the use of intervertebral fusion devices for fusing one or more adjacent vertebral bodies. Generally, to fuse the adjacent vertebral bodies, the intervertebral disc is first partially or fully removed. An intervertebral fusion device is then typically inserted between neighboring vertebrae to maintain normal disc spacing and restore spinal stability, thereby facilitating an intervertebral fusion.

There are a number of known conventional fusion devices and methodologies in the art for accomplishing the intervertebral fusion. These include screw and rod arrangements, solid bone implants, and fusion devices which include a cage or other implant mechanism which, typically, is packed with bone and/or bone growth inducing substances. These devices are implanted between adjacent vertebral bodies in order to fuse the vertebral bodies together, alleviating the associated pain.

However, there are drawbacks associated with the known conventional fusion devices and methodologies. For example, present methods for installing a conventional fusion device often require that the adjacent vertebral bodies be distracted to restore a diseased disc space to its normal or healthy height prior to implantation of the fusion device. In order to maintain this height once the fusion device is inserted, the fusion device is usually dimensioned larger in height than the initial distraction height. This difference in height can make it difficult for a surgeon to install the fusion device in the distracted intervertebral space.

As such, there exists a need for a fusion device capable of being installed inside an intervertebral disc space at a minimum to no distraction height and for a fusion device that can maintain a normal distance between adjacent vertebral bodies when implanted.

SUMMARY OF THE INVENTION

In an exemplary embodiment, the present invention provides an expandable fusion device capable of being installed inside an intervertebral disc space to maintain normal disc spacing and restore spinal stability, thereby facilitating an

2

intervertebral fusion. In one embodiment, the fusion device includes a central ramp, a first endplate, and a second endplate. The central ramp may be capable of moving in a first direction to push the first and second endplates outwardly and into an unexpanded configuration. The expandable fusion device may be capable of being placed into the disc space down an endoscopic tube and then expanded into an expanded configuration.

Further areas of applicability of the present invention will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating the preferred or exemplary embodiments of the invention, are intended for purposes of illustration only and are not intended to limit the scope of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will become more fully understood from the detailed description and the accompanying drawings, wherein:

FIG. 1 is a side view of an embodiment of an expandable fusion device shown between adjacent vertebrae according to the present invention;

FIG. 2 is a front perspective view of the expandable fusion device of FIG. 1 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 3 is a front perspective view of the expandable fusion device of FIG. 1 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 4 is a rear perspective view of the expandable fusion device of FIG. 1 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 5 is a rear perspective view of the expandable fusion device of FIG. 1 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 6 is a side view of the expandable fusion device of FIG. 1 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 7 is a side view of the expandable fusion device of FIG. 1 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 8 is a perspective view of the central ramp of the expandable fusion device of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 9 is a perspective view of the driving ramp of the expandable fusion device of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 10 is a perspective of an endplate of the expandable fusion device of FIG. 1 in accordance with one embodiment of the present invention;

FIG. 11 a perspective view showing placement of the first endplate of an embodiment of an expandable fusion device down an endoscopic tube and into the disc space in accordance with one embodiment of the present invention;

FIG. 12 is a perspective view showing placement of the second endplate of the expandable fusion device down an endoscopic tube and into the disc space in accordance with one embodiment of the present invention;

FIG. 13 is a perspective view showing placement of the central ramp of the expandable fusion device down an endoscopic tube and into the disc space in accordance with one embodiment of the present invention;

FIG. 14 is a perspective view showing expansion of the expandable fusion device in accordance with one embodiment of the present invention;

3

FIG. 15 is a side schematic view of the expandable fusion device of FIG. 1 having different endplates;

FIG. 16 is a partial side schematic view of the expandable fusion device of FIG. 1 showing different modes of endplate expansion;

FIG. 17 is a side schematic view of the expandable fusion device of FIG. 1 with artificial endplates shown between adjacent vertebrae;

FIG. 18 is a front perspective view of an alternative embodiment of an expandable fusion device shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 19 is a front perspective view of the expandable fusion device of FIG. 18 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 20 is a rear perspective view of the expandable fusion device of FIG. 18 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 21 is a rear perspective view of the expandable fusion device of FIG. 18 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 22 is a side view of the expandable fusion device of FIG. 18 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 23 is a side view of the expandable fusion device of FIG. 18 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 24 is a perspective of an endplate of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 25 is a perspective view of the central ramp of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 26 is a side view of the central ramp of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 27 is a top view of the central ramp of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 28 is a perspective view showing placement of the central ramp of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 29 is a perspective view showing placement of the first endplate of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 30 is a perspective view showing placement of the second endplate of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 31 is a perspective view showing placement of the actuation member of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 32 is a perspective view showing expansion of the expandable fusion device of FIG. 18 in accordance with one embodiment of the present invention;

FIG. 33 is a front perspective view of an alternative embodiment of an expandable fusion device shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 34 is a front perspective view of the expandable fusion device of FIG. 33 shown in an expanded position in accordance with one embodiment of the present invention;

4

FIG. 35 is a rear perspective view of the expandable fusion device of FIG. 33 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 36 is a rear perspective view of the expandable fusion device of FIG. 33 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 37 is a side cross-sectional view of the expandable fusion device of FIG. 33 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 38 is a side cross-sectional view of the expandable fusion device of FIG. 33 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 39 is a perspective of an endplate of the expandable fusion device of FIG. 33 in accordance with one embodiment of the present invention;

FIG. 40 is a rear perspective view of an alternative embodiment of an expandable fusion device shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 41 is a rear perspective view of the expandable fusion device of FIG. 40 shown in a partially expanded position in accordance with one embodiment of the present invention;

FIG. 42 is a rear perspective view of the expandable fusion device of FIG. 40 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 43 is a side exploded view of the expandable fusion device of FIG. 40 in accordance with one embodiment of the present invention;

FIG. 44 is a side cross-sectional view of the expandable fusion device of FIG. 40 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 45 is a perspective view of an endplate of the expandable fusion device of FIG. 40 in accordance with one embodiment of the present invention;

FIG. 46 is a perspective view of the central ramp of the expandable fusion device of FIG. 40 in accordance with one embodiment of the present invention;

FIGS. 47-49 are perspective views of the driving ramp of the expandable fusion device of FIG. 40 in accordance with one embodiment of the present invention;

FIG. 50 is a rear perspective view of an alternative embodiment of an expandable fusion device shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 51 is a side cross-sectional view of the expandable fusion device of FIG. 50 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 52 is an exploded view of the expandable fusion device of FIG. 50 in accordance with one embodiment of the present invention;

FIG. 53 is a top view of the expandable fusion device of FIG. 50 shown in an unexpanded position in accordance with one embodiment of the present invention;

FIG. 54 is a read end view of the expandable fusion device of FIG. 50 shown in an expanded position in accordance with one embodiment of the present invention;

FIG. 55 is a perspective view of an endplate of the expandable fusion device of FIG. 50 in accordance with one embodiment of the present invention;

FIG. 56 is a perspective of a central ramp of the expandable fusion device of FIG. 50 in accordance with one embodiment of the present invention; and

5

FIG. 57 is a perspective view of a driving ramp of the expandable fusion device of FIG. 50 in accordance with one embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following description of the preferred embodiment(s) is merely exemplary in nature and is in no way intended to limit the invention, its application, or uses.

A spinal fusion is typically employed to eliminate pain caused by the motion of degenerated disk material. Upon successful fusion, a fusion device becomes permanently fixed within the intervertebral disc space. Looking at FIG. 1, an exemplary embodiment of an expandable fusion device 10 is shown between adjacent vertebral bodies 2 and 3. The fusion device 10 engages the endplates 4 and 5 of the adjacent vertebral bodies 2 and 3 and, in the installed position, maintains normal intervertebral disc spacing and restores spinal stability, thereby facilitating an intervertebral fusion. The expandable fusion device 10 can be manufactured from a number of materials including titanium, stainless steel, titanium alloys, non-titanium metallic alloys, polymeric materials, plastics, plastic composites, PEEK, ceramic, and elastic materials. In an embodiment, the expandable fusion device 10 can be configured to be placed down an endoscopic tube and into the disc space between the adjacent vertebral bodies 2 and 3.

In an exemplary embodiment, bone graft or similar bone growth inducing material can be introduced around and within the fusion device 10 to further promote and facilitate the intervertebral fusion. The fusion device 10, in one embodiment, is preferably packed with bone graft or similar bone growth inducing material to promote the growth of bone through and around the fusion device. Such bone graft may be packed between the endplates of the adjacent vertebral bodies prior to, subsequent to, or during implantation of the fusion device.

With reference to FIGS. 2-7, an embodiment of the fusion device 10 is shown. In an exemplary embodiment, the fusion device 10 includes a first endplate 14, a second endplate 16, a central ramp 18, and a driving ramp 260. In an embodiment, the expandable fusion device 10 can be configured to be placed down an endoscopic tube and into the disc space between the adjacent vertebral bodies 2 and 3. One or more components of the fusion device 10 may contain features, such as through bores, that facilitate placement down an endoscopic tube. In an embodiment, components of the fusion device 10 are placed down the endoscopic tube with assembly of the fusion device 10 in the disc space.

Although the following discussion relates to the second endplate 16, it should be understood that it also equally applies to the first endplate 14 as the second endplate 16 is substantially identical to the first endplate 14 in embodiments of the present invention. Turning now to FIGS. 2-7 and 10, in an exemplary embodiment, the second endplate 16 has a first end 39 and a second end 41. In the illustrated embodiment, the second endplate 16 further comprise an upper surface 40 connecting the first end 39 and the second end 41, and a lower surface 42 connecting the first end 39 and the second end 41. In an embodiment, the second endplate 16 further comprises a through opening 44, as seen on FIG. 11. The through opening 44, in an exemplary embodiment, is sized to receive bone graft or similar bone growth inducing material and further allow the bone graft or similar bone growth inducing material to be packed in the central opening in the central ramp 18.

6

As best seen in FIGS. 7 and 10, the lower surface 42 includes at least one extension 46 extending along at least a portion of the lower surface 42, in an embodiment. In an exemplary embodiment, the extension 46 can extend along a substantial portion of the lower surface 42, including, along the center of the lower surface 42. In the illustrated embodiment, the extension 46 includes a generally concave surface 47. The concave surface 47 can form a through bore with the corresponding concave surface 47 (not illustrated) of the first endplate 14, for example, when the device 10 is in an unexpanded configuration. In another exemplary embodiment, the extension 46 includes at least one ramped surface 48. In another exemplary embodiment, there are two ramped surfaces 48, 50 with the first ramped surface 48 facing the first end 39 and the second ramped surface facing the second end 41. In an embodiment, the first ramped surface 48 can be proximate the first end 39, and the second ramped surface 50 can be proximate the second end 41. It is contemplated that the slope of the ramped surfaces 48, 50 can be equal or can differ from each other. The effect of varying the slopes of the ramped surfaces 48, 50 is discussed below.

In one embodiment, the extension 46 can include features for securing the endplate 16 when the expandable fusion device 10 is in an expanded position. In an embodiment, the extension 46 includes one or more protuberances 49 extending from the lateral sides 51 of the extension. In the illustrated embodiment, there are two protuberances 49 extending from each of the lateral sides 51 with each of the sides 53 having one of the protuberances 49 extending from a lower portion of either end. As will be discussed in more detail below, the protuberances 49 can be figured to engage the central ramp 18 preventing and/or restricting longitudinal movement of the endplate 16 when the device 10 is in an expanded position.

As illustrated in FIGS. 2-5, in one embodiment, the upper surface 40 of the second endplate 16 is flat and generally planar to allow the upper surface 40 of the endplate 16 to engage with the adjacent vertebral body 2. Alternatively, as shown in FIG. 15, the upper surface 40 can be curved convexly or concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral body 2. It is also contemplated that the upper surface 40 can be generally planar but includes a generally straight ramped surface or a curved ramped surface. The ramped surface allows for engagement with the adjacent vertebral body 2 in a lordotic fashion. While not illustrated, in an exemplary embodiment, the upper surface 40 includes texturing to aid in gripping the adjacent vertebral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

Referring now to FIGS. 2-8, in an exemplary embodiment, the central ramp 18 has a first end 20, a second end 22, a first side portion 24 connecting the first end 20 and the second end 22, and a second side portion 26 (best seen on FIG. 5) on the opposing side of the central ramp 12 connecting the first end 20 and the second end 22. The first side portion 24 and the second side portion 26 may be curved, in an exemplary embodiment. The central ramp 18 further includes a lower end 28, which is sized to receive at least a portion of the first endplate 14, and an upper end 30, which is sized to receive at least a portion of the second endplate 16.

The first end 20 of the central ramp 18, in an exemplary embodiment, includes an opening 32. The opening 32 can be configured to receive an endoscopic tube in accordance with

one or more embodiments. The first end **20** of the central ramp **18**, in an exemplary embodiment, includes at least one angled surface **33**, but can include multiple angled surfaces. The angled surface **33** can serve to distract the adjacent vertebral bodies when the fusion device **10** is inserted into an intervertebral space.

The second end **22** of the central ramp **18**, in an exemplary embodiment, includes an opening **36**. The opening **36** extends from the second end **22** of the central ramp **18** into a central guide **37** in the central ramp **18**.

In an embodiment, the central ramp **18** further includes one or more ramped surfaces **33**. As best seen in FIG. **8**, the one or more ramped surfaces **33** positioned between the first side portion **24** and the second side portion **26** and between the central guide **37** and the second end **22**. In an embodiment, the one or more ramped surfaces **33** face the second end **22** of the central ramp **18**. In one embodiment, the central ramp **18** includes two ramped surfaces **33** with one of the ramped surfaces **33** being sloped upwardly and the other of the ramped surfaces **33** being sloped downwardly. The ramped surfaces **33** of the central ramp can be configured and dimensioned to engage the ramped surface **48** in each of the first and second endplates **14**, **16**.

Although the following discussion relates to the second side portion **26** of the central ramp **18**, it should be understood that it also equally applies to the first side portion **24** in embodiments of the present invention. In the illustrated embodiment, the second side portion **26** includes an inner surface **27**. In an embodiment, the second side portion **26** further includes a lower guide **35**, a central guide **37**, and an upper guide **38**. In the illustrated embodiment, the lower guide **35**, central guide **37**, and the upper guide **38** extend out from the inner surface **27** from the second end **22** to the one or more ramped surfaces **31**. In the illustrated embodiment, the second end **22** of the central ramp **18** further includes one or more guides **38**. The guides **38** can serve to guide the translational movement of the first and second endplates **14**, **16** with respect to the central ramp **18**. For example, protuberances **49** on the second endplate **16** may be sized to be received between the central guide **37** and the upper guide **38**. Protuberances **49** of the first endplate **14** may be sized to be received between the central guide **37** and the lower guide **35**. A first slot **29** may be formed proximate the middle of the upper guide **38**. A second slot **31** may be formed between end of the upper guide **38** and the one or more ramped surfaces **33**. The protuberances **49** may be sized to be received within the first slot **29** and/or the second slot **31** when the device **10** is in the expanded position.

Referring now to FIGS. **4-7** and **9**, the driving ramp **260** has a through bore **262**. In an embodiment, the driving ramp **260** is generally wedge-shaped. As illustrated, the driving ramp **260** may comprise a wide end **56**, a narrow end **58**, a first side portion **60** connecting the wide end **56** and the narrow end **58**, and a second side portion **62** connecting the wide end **56** and the narrow end **58**. The driving ramp **260** further may comprise ramped surfaces, including an upper ramped surface **64** and an opposing lower ramped surface **66**. The upper ramped surface **64** and the lower ramped surface **66** may be configured and dimensioned to engage the ramped surface **50** proximate the second end **41** in of the first and the second endplates **14**, **16**. The first and second side portions **60**, **62** may each include grooves **68** that extend, for example, in a direction parallel to the longitudinal axis of the through bore **262**. The grooves **68** may be sized to receive the central guide **37** on the interior surface **27** of each of the side portions **24**, **26** of the central ramp **18**. In this manner, the grooves **68** together with the central

guide **37** can surface to guide the translational movement of the driving ramp **260** in the central ramp **18**.

A method of installing the expandable fusion device **10** of FIG. **1** is now discussed in accordance with one embodiment of the present invention. Prior to insertion of the fusion device **10**, the intervertebral space is prepared. In one method of installation, a discectomy is performed where the intervertebral disc, in its entirety, is removed. Alternatively, only a portion of the intervertebral disc can be removed. The endplates of the adjacent vertebral bodies **2**, **3** are then scraped to create an exposed end surface for facilitating bone growth across the intervertebral space. One or more endoscopic tubes can then be inserted into the disc space. The expandable fusion device **10** can then be introduced into the intervertebral space down an endoscopic tube and seated in an appropriate position in the intervertebral disc space.

After the fusion device **10** has been inserted into the appropriate position in the intervertebral disc space, the fusion device **10** can then be expanded into the expanded position. To expand the fusion device **10**, the driving ramp **260** may be moved in a first direction with respect to the central ramp **18**. Translational movement of the driving ramp **260** through the central ramp **18** may be guided by the central guide **37** on each of the first and second side portions **24**, **26** of the central ramp **18**. As the driving ramp **260** moves, the upper ramped surface **64** pushes against the ramped surface **50** proximate the second end **41** of the second endplate **16**, and the lower ramped surface **66** pushes against the ramped surface **50** proximate the second end **41** of the first endplate **14**. In addition, the ramped surfaces **33** in the central ramp **18** push against the ramped surface **48** proximate the first end **41** of the first and second endplates **14**, **16**. In this manner, the first and second endplates **14**, **16** are pushed outwardly into an expanded configuration. As discussed above, the central ramp **16** includes locking features for securing the endplates **14**, **16**.

It should also be noted that the expansion of the endplates **14**, **16** can be varied based on the differences in the dimensions of the ramped surfaces **48**, **50** and the angled surfaces **62**, **64**. As best seen in FIG. **16**, the endplates **14**, **16** can be expanded in any of the following ways: straight rise expansion, straight rise expansion followed by a toggle into a lordotic expanded configuration, or a phase off straight rise into a lordotic expanded configuration.

Turning back to FIGS. **2-7**, in the event the fusion device **10** needs to be repositioned or revised after being installed and expanded, the fusion device **10** can be contracted back to the unexpanded configuration, repositioned, and expanded again once the desired positioning is achieved. To contract the fusion device **10**, the central ramp **18** is moved with respect to the central ramp **260** away from the central ramp **260**. As the central ramp **18** moves, the ramped surfaces **33** in the central ramp **18** ride along the ramped surfaces **48** of the first and second endplates **14**, **16** with the endplates **14**, **16** moving inwardly into the unexpanded position.

With reference now to FIG. **17**, fusion device **10** is shown with an exemplary embodiment of artificial endplates **100**. Artificial endplates **100** allows the introduction of lordosis even when the endplates **14** and **16** of the fusion device **10** are generally planar. In one embodiment, the artificial endplates **100** have an upper surface **102** and a lower surface **104**. The upper surfaces **102** of the artificial endplates **100** have at least one spike **106** to engage the adjacent vertebral bodies. The lower surfaces **104** have complementary texturing or engagement features on their surfaces to engage with the texturing or engagement features on the upper

endplate 14 and the lower endplate 16 of the fusion device 10. In an exemplary embodiment, the upper surface 102 of the artificial endplates 100 have a generally convex profile and the lower surfaces 104 have a generally parallel profile to achieve lordosis. In another exemplary embodiment, fusion device 10 can be used with only one artificial endplate 100 to introduce lordosis even when the endplates 14 and 16 of the fusion device 10 are generally planar. The artificial endplate 100 can either engage endplate 14 or engage endplate 16 and function in the same manner as described above with respect to two artificial endplates 100.

With reference to FIGS. 11-14, an embodiment for placing an expandable fusion device 10 into an intervertebral disc space is illustrated. The expandable fusion device 10 can be introduced into the intervertebral space down an endoscopic tube utilizing a tool 70 that is attached to endplate 16, with the second endplate 16 being first placed down the tube with tool 70 and into the disc space, as seen in FIG. 11. After insertion of the second endplate 16, the first endplate 14 can be placed down the same endoscopic tube with tool 72 and into the disc space, as shown on FIG. 12. Following the first endplate 14, the central ramp 12 can be placed down the same endoscopic tube and into the disc space guided by tools 70 and 72, as shown on FIGS. 13 and 14.

Referring now to FIGS. 18-23, an alternative embodiment of the expandable fusion device 10 is shown. In an exemplary embodiment, the fusion device 10 includes a first endplate 14, a second endplate 16, a central ramp 18, and an actuator assembly 200. As will be discussed in more detail below, the actuator assembly 200 drives the central ramp 18 which forces apart the first and second endplates 14, 16 to place the expandable fusion device in an expanded position. One or more components of the fusion device 10 may contain features, such as through bores, that facilitate placement down an endoscopic tube. In an embodiment, components of the fusion device 10 are placed down the endoscopic tube with assembly of the fusion device 10 in the disc space.

Although the following discussion relates to the second endplate 16, it should be understood that it also equally applies to the first endplate 14 as the second endplate 16 is substantially identical to the first endplate 14 in embodiments of the present invention. With additional reference to FIG. 24, in an exemplary embodiment, the second endplate 16 has a first end 39 and a second end 41. In the illustrated embodiment, the second endplate 16 further comprise an upper surface 40 connecting the first end 39 and the second end 41, and a lower surface 42 connecting the first end 39 and the second end 41. While not illustrated, in an embodiment, the second endplate 16 further comprises a through opening. The through opening, in an exemplary embodiment, is sized to receive bone graft or similar bone growth inducing material.

In one embodiment, the upper surface 40 of the second endplate 16 is flat and generally planar to allow the upper surface 40 of the endplate 16 to engage with the adjacent vertebral body 2. Alternatively, as shown in FIG. 15, the upper surface 40 can be curved convexly or concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral body 2. It is also contemplated that the upper surface 40 can be generally planar but includes a generally straight ramped surface or a curved ramped surface. The ramped surface allows for engagement with the adjacent vertebral body 2 in a lordotic fashion. While not illustrated, in an exemplary embodiment, the upper surface 40 includes texturing to aid in gripping the adjacent verte-

bral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

In one embodiment, the second endplate 16 further comprises a first side portion 202 connecting the first end 39 and the second end 41, and a second side portion 204 connecting the first end 39 and the second end 41. In the illustrated embodiment, the first and second side portions 202, 204 are extensions from the lower surface 42. In an exemplary embodiment, the first and second side portions 202, 204 each include ramped surfaces 206, 208. In the illustrated embodiment, the ramped surfaces 206, 208 extend from the first end 39 of the second endplate 16 to bottom surfaces 210, 212 of each of the side portions 202, 204. In one embodiment, the ramped surfaces 206, 208 are forward facing in that the ramped surfaces 206, 208 face the first end 39 of the second endplate. As previously discussed, the slope of the ramped surfaces 206, 208 may be varied as desired for a particular application.

In an embodiment, the first and second side portions 202, 204 each comprise at least one protuberance 214. In an exemplary embodiment, the first and second side portions 202, 204 each comprise a first protuberance 214, a second protuberance 216, and a third protuberance 218. In one embodiment, the protuberances 214, 216, 218 extend from the interior surface 220 of the first and second side portions 202, 204. In an exemplary embodiment, the protuberances 214, 216, 218 extend at the lower side of the interior surface 220. As best seen in FIG. 24, the first and the second protuberances 214, 216 form a first slot 222, and the second and third protuberances 216, 218 form a second slot 224.

As best seen in FIG. 24, the lower surface 42 of the second endplate 16, in an embodiment, includes a central extension 224 extending along at least a portion of the lower surface. In the illustrated embodiment, the central extension 224 extends between the first and second side portions 202 and 204. In an exemplary embodiment, the central extension 224 can extend from the second end 41 of the endplate 16 to the central portion of the endplate. In one embodiment, the central extension 224 includes a generally concave surface 226 configured and dimensioned to form a through bore with the corresponding concave surface 226 (not illustrated) of the first endplate 14. The central extension 224 can further include, in an exemplary embodiment, a ramped surface 228. In the illustrated embodiment, the ramped surface 228 faces the first end 39 of the endplate 16. The ramped surface 228 can be at one end of the central extension 224. In an embodiment, the other end of the central extension 224 forms a stop 230. In the illustrated embodiment, the stop 230 is recessed from the second end 41 of the second endplate 16.

Referring to FIGS. 25-27, in an exemplary embodiment, the central ramp 18 includes a body portion 232 having a first end 234 and a second end 236. In an embodiment, the body portion 232 includes at least a first expansion portion 238. In an exemplary embodiment, the body portion 232 includes a first expansion portion 238 and a second expansion portion 240 extending from opposing sides of the body portion with each of the first and second expansion portions 238, 240 having a generally triangular cross-section. In one embodiment, the expansion portions 238, 240 each have angled surfaces 242, 244 configured and dimensioned to engage the ramped surfaces 206, 208 of the first and second endplates 14, 16 and force apart the first and second endplates 14, 16. In an embodiment, the engagement between the angled surfaces 242, 244 of the expansion portions 238,

240 with the ramped surfaces 206, 208 of the first and second endplates 14, 16 may be described as a dovetail connection.

The second end 236 of the central ramp 18, in an exemplary embodiment, includes opposing angled surfaces 246. The angled surfaces 246 can be configured and dimensioned to engage the ramped surface 228 in the central extension 224 in each of the first and second endplates 14, 16. In other words, one of the angled surfaces 246 can be upwardly facing and configured, in one embodiment, to engage the ramped surface 228 in the central extension 224 in the second endplate 16. In an embodiment, the engagement between the angled surfaces 246 of the second end 236 of the central ramp 18 with the ramped surface 228 in the first and second endplates 14, 16 may be described as a dovetail connection.

The second end 236, in an exemplary embodiment, can further include an extension 252. In the illustrated embodiment, the extension 252 is generally cylindrical in shape with a through bore 254 extending longitudinally there-through. In one embodiment, the extension 252 can include a beveled end 256. While not illustrated, at least a portion of the extension 252 can be threaded.

Referring still to FIGS. 25-27, the central ramp 18 can further include features for securing the first and second endplates 14, 16 when the expandable fusion device 10 is in an expanded position. In an embodiment, the body portion 232 of the central ramp 18 includes one or more protuberances 248, 250 extending from opposing sides of the body portion 232. As illustrated, the protuberances 248, 250, in one embodiment, can be spaced along the body portion 232. In an exemplary embodiment, the protuberances 248, 250 can be configured and dimensioned for insertion into the corresponding slots 222, 224 in the first and second endplates 14, 16 when the device 10 is in an expanded position, as best seen in FIGS. 19 and 21. The protuberances 248, 250 can engage the endplates 14, 16 preventing and/or restricting movement of the endplates 14, 16 with respect to the central ramp 18 after expansion of the device 10.

With reference to FIGS. 20-23, in an exemplary embodiment, the actuator assembly 200 has a flanged end 253 configured and dimensioned to engage the stop 232 in the central extension 224 of the first and the second endplates 14, 16. In an embodiment, the actuator assembly 200 further includes an extension 254 that extends from the flanged end 253. In a further embodiment, the actuator assembly 200 includes a threaded hole 256 that extends through the actuator assembly 200. It should be understood that, while the threaded hole 256 in the actuator assembly 200 is referred to as threaded, the threaded hole 256 may only be partially threaded in accordance with one embodiment. In an exemplary embodiment, the threaded hole 256 is configured and dimensioned to threadingly receive the extension 252 of the central ramp 18.

With additional reference to FIGS. 28-32, a method of installing the expandable fusion device 10 of FIGS. 18-27 is now discussed in accordance with one embodiment of the present invention. Prior to insertion of the fusion device, the disc space may be prepared as described above and then one or more endoscopic tubes may be inserted into the disc space. The expandable fusion device 10 can then be inserted into and seated in the appropriate position in the intervertebral disc space, as best seen in FIGS. 28-32. The expandable fusion device 10 can be introduced into the intervertebral space down an endoscopic tube (not illustrated), with the central ramp 18 being first placed down the tube and into the disc space, as seen in FIG. 28. After insertion of the

central ramp, the first endplate 14 can be placed down an endoscopic tube, as shown on FIG. 29, followed by insertion of the second endplate 16, as shown on FIG. 30. After the second endplate 16, the actuator assembly 200 can then be inserted to complete assembly of the device 10, as best seen in FIG. 31.

After the fusion device 10 has been inserted into and assembled in the appropriate position in the intervertebral disc space, the fusion device 10 can then be expanded into the expanded position. To expand the fusion device 10, the actuator assembly 200 can be rotated. As discussed above, the actuator assembly 200 is in threaded engagement with the extension 250 of the central ramp 18. Thus, as the actuator assembly 200 is rotated in a first direction, the central ramp 18 moves toward the flanged end 253 of the actuator assembly 200. In another exemplary embodiment, the actuator assembly 200 can be moved in a linear direction with the ratchet teeth as means for controlling the movement of the central ramp 18. As the central ramp 18 moves, the angled surfaces 242, 244 in the expansion portions 238, 240 of the central ramp 18 push against the ramped surfaces 206, 208 in the first and second side portions 202, 204 of the first and second endplates 14, 16. In addition, the angled surfaces 246 in the second end 236 of the central ramp 18 also push against the ramped surfaces 228 in the central extension 224 of each of the endplates 14, 16. This is best seen in FIGS. 22-23.

Since the expansion of the fusion device 10 is actuated by a rotational input, the expansion of the fusion device 10 is infinite. In other words, the endplates 14, 16 can be expanded to an infinite number of heights dependent on the rotational advancement of the actuator assembly 200. As discussed above, the central ramp 16 includes locking features for securing the endplates 14, 16.

In the event the fusion device 10 needs to be repositioned or revised after being installed and expanded, the fusion device 10 can be contracted back to the unexpanded configuration, repositioned, and expanded again once the desired positioning is achieved. To contract the fusion device 10, the actuator assembly 200 can be rotated in a second direction. As discussed above, actuator assembly 200 is in threaded engagement with the extension 250 of the central ramp 18; thus, as the actuator assembly 200 is rotated in a second direction, opposite the first direction, the central ramp 18 moves with respect to the actuator assembly 200 and the first and second endplates 14, 16 away from the flanged end 253. As the central ramp 18 moves, the first and second endplates are pulled inwardly into the unexpanded position.

Referring now to FIGS. 33-38, an alternative embodiment of the expandable fusion device 10 is shown. In the illustrated embodiment, the fusion device includes a first endplate 14, a second endplate 16, a central ramp 18, and an actuator assembly 200. The fusion device 10 of FIGS. 33-38 and its individual components are similar to the device 10 illustrated on FIGS. 18-23 with several modifications. The modifications to the device 10 will be described in turn below.

Although the following discussion relates to the second endplate 16, it should be understood that it also equally applies to the first endplate 14 as the second endplate 16 is substantially identical to the first endplate 14 in embodiments of the present invention. With additional reference to FIG. 39, in an exemplary embodiment, the lower surface 42 of the second endplate 16 has been modified. In one embodiment, the central extension 224 extending from the lower surface 42 has been modified to include a second ramped

13

surface 258 rather than a stop. In an exemplary embodiment, the second ramped surface 258 faces the second end 41 of the second endplate 16. In contrast, ramped surface 228 on the central extension 228 faces the first end 39 of the second endplate. The concave surface 228 connects the ramped surface 228 and the second ramped surface 258.

With reference to FIGS. 35-38, in an exemplary embodiment, the actuator assembly 200 has been modified to further include a driving ramp 260. In the illustrated embodiment, the driving ramp 260 has a through bore 262 through which the extension 254 extends. In an embodiment, the driving ramp 260 is generally wedge-shaped. As illustrated, the driving ramp 260 may comprise a blunt end 264 in engagement with the flanged end 253. In an exemplary embodiment, the driving ramp 260 further comprises angled surfaces 266 configured and dimensioned to engage the second ramped surface 258 of each of the endplates 14, 16 and force apart the first and second endplates 14, 16.

Referring now to FIGS. 40-44, an alternative embodiment of the expandable fusion device 10 is shown. In the illustrated embodiment, the fusion device 10 includes a first endplate 14, a second endplate 16, a central ramp 18, an actuator assembly 200, and a driving ramp 300. As will be discussed in more detail below, the actuator assembly 200 functions, in an embodiment, to pull the central ramp 18 and the driving ramp 300 together, which forces apart the first and second endplates 14, 16. In an embodiment, the expandable fusion device

Although the following discussion relates to the first endplate 14, it should be understood that it also equally applies to the second endplate 16 as the second endplate 16 is substantially identical to the first endplate 14 in embodiments of the present invention. With reference to FIGS. 40-45, in an exemplary embodiment, the first endplate 14 has a first end 39 and a second end 41. In the illustrated embodiment, the first endplate 14 further comprises an upper surface 40 connecting the first end 39 and the second end 41, and a lower surface 42 connecting the first end 39 and the second end 41. While not illustrated, in an embodiment, the first endplate 14 may comprise further comprises a through opening. The through opening, in an exemplary embodiment, is sized to receive bone graft or similar bone growth inducing material.

In one embodiment, the upper surface 40 of the first endplate 14 is flat and generally planar to allow the upper surface 40 of the endplate 14 to engage with the adjacent vertebral body 2. Alternatively, as shown in FIG. 15, the upper surface 40 can be curved convexly or concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral body 2. It is also contemplated that the upper surface 40 can be generally planar but includes a generally straight ramped surface or a curved ramped surface. The ramped surface allows for engagement with the adjacent vertebral body 2 in a lordotic fashion. While not illustrated, in an exemplary embodiment, the upper surface 40 includes texturing to aid in gripping the adjacent vertebral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

In one embodiment, the first endplate 14 further comprises a first side portion 202 connecting the first end 39 and the second end 41, and a second side portion 204 connecting the first end 39 and the second end 41. In the illustrated embodiment, the first and second side portions 202, 204 are extensions from the lower surface 42. In an embodiment, the first and second side portions each have an interior surface 302 and an exterior surface 304. In an exemplary embodi-

14

ment, the first and second side portions 202, 204 each include one or more ramped portions. In the illustrated embodiment, the first and second side portions 202, 204 include first ramped portions 306, 308 at the first end 39 of the endplate 14 and second ramped portions 310, 312 at the second end 41 of the endplate. The first and second side portions 202, 204 each can include a bridge portion 314 connecting the first ramped portions 306, 308 and the second ramped portions 310, 312. In an embodiment, the first ramped portions 306, 308 abut the exterior surface 304 of the respective side portions 202, 204, and the second ramped portions 310, 312 abut the interior surface 302 of the respective side portions 202, 204. As illustrated, the first ramped portions 306, 308 may include tongue portions 316, 318 with the tongue portions 316, 318 extending in an oblique direction with respect to the upper surface 40 of the endplate 14. As further illustrated, the second ramped portions 310, 312 may include tongue portions 320, 322 that extend in an oblique direction with respect to the upper surface 40 of the endplate 14.

As best seen in FIG. 45, the lower surface 42 of the second endplate 16, in an embodiment, includes a central extension 224 extending along at least a portion of the lower surface. In the illustrated embodiment, the central extension 224 extends between the first and second side portions 202 and 204. In an exemplary embodiment, the central extension 224 can extend generally between the first ramped portions 306, 308 and the second ramped portions 310, 312. In one embodiment, the central extension 224 includes a generally concave surface 226 configured and dimensioned to form a through bore with the corresponding concave surface 226 (not illustrated) of the second endplate 16.

With reference to FIGS. 43 and 44, the actuator assembly 200 includes a head portion 324, a rod receiving extension 326, and a connecting portion 328 that connecting portions that connects the head portion 324 and the rod receiving extension 326. As illustrated, the head portion 324 may include one or more instrument gripping features 330 that can allow it to be turned by a suitable instrument. In addition, the head portion 324 has a larger diameter than the other components of the actuator assembly 200 to provide a contact surface with the driving ramp 300. In the illustrated embodiment, the head portion 324 includes a rim 332 that provides a surface for contacting the driving ramp 300. As can be seen in FIG. 44, in an exemplary embodiment, the rod receiving extension 326 includes an opening sized and dimensioned to receive the extension 336 of the central ramp 18. In an embodiment, the rod receiving extension 326 includes threading for threadingly engaging the extension 336. In another embodiment, the rod receiving extension 326 includes ratchet teeth for engaging the extension 336. In the illustrated embodiment, the head portion 324 and the rod receiving extension 326 are connected by connecting portion 328 which can be generally cylindrical in shape.

With reference to FIGS. 43, 44, and 46, the central ramp 18 includes expansion portion 334 and extension 336. As best seen in FIG. 46, the expansion portion 334 may include an upper portion 338 and side portions 340, 342 that extend down from the upper portion 338. In an embodiment, each of the side portions 340, 342 include dual, overlapping ramped portions. For example, side portions 340, 342 each include a first ramped portion 344 that overlaps a second ramped portion 346. In the illustrated embodiment, the first ramped portion 344 faces the extension 336 while the second ramped portion 344 faces away from the extension 336. In one embodiment, angled grooves 348, 350 are formed in each of the first and second ramped portions 344,

346. In another embodiment, the angled grooves 348, 350 are sized to receive the corresponding tongues 316, 318, 320, 322 in the first and second endplates with angled grooves 348 receiving tongues 320, 322 in the second endplate 16 and angled grooves 350 receiving tongues 316, 318 in the first endplate 14. Although the device 10 is described with tongues 316, 318, 320, 322 on the endplates 14, 16 and angled grooves 348, 350 on the central ramp 18, it should be understood that that device 10 can also be configured with grooves on the endplates 14, 16 and tongues on the central ramp 18, in accordance with one embodiment of the present invention.

In an exemplary embodiment, the extension 336 is sized to be received within the rod receiving extension 326 of the actuator assembly 200. In one embodiment, the extension 336 has threading with the extension 336 being threadingly received within the rod receiving extension 326. In another embodiment, the extension 336 has ratchet teeth with the extension 336 being ratcheted into the rod receiving extension 336. In an embodiment, the extension 336 include nose 352 at the end of the extension 336.

With reference to FIGS. 47-49, in an exemplary embodiment, the driving ramp 300 includes an upper portion 354 having an upper surface 356 and an oblique surface 358. In an embodiment, the driving ramp 300 further includes side portions 360, 362 that extend from the upper portion 354 connecting the upper portion 354 with the lower portion 364 of the driving ramp 300. As best seen in FIGS. 48-49, the driving ramp 300 further includes a bore 366, in an exemplary embodiment, sized to receive the connection portion 328 of the actuator assembly 200. In one embodiment, the driving ramp 300 moves along the connection portion 328 when the actuator assembly 200 is pushing the driving ramp 300. In an exemplary embodiment, the driving ramp 300 further includes contact surface 368 that engages the rim 332 of the head portion 324 of the actuator assembly 200. In the illustrated embodiment, the contact surface 368 has a generally annular shape.

In an exemplary embodiment, the side portions 360, 362 of the driving ramp 300 each include overlapping ramped portions. For example, the side portions 360, 362 each include first ramped portions 370 that overlap second ramped portions 372. In the illustrated embodiment, the first ramped portions 370 face central ramp 18 while the second ramped portions 372 face the opposite direction. In one embodiment, angled grooves 374, 376 are formed in each of the first and second ramped portions 370, 372. FIG. 48 is a perspective view of the driving ramp 300 that shows the top ends of the angled grooves 374 in ramped portions 370. FIG. 49 is a perspective view of the driving ramp 300 that shows the top ends of the angled grooves 376 in ramped portions 372. In an exemplary embodiment, the angled grooves 374, 376 are sized to receive corresponding tongues 316, 318, 320, 322 in the first and second endplates 14, 16 with angled grooves 370 receiving tongues 316, 318 in the second endplate 16 and angled grooves 372 receiving tongues 320, 322 in the first endplate 14. Although the device 10 is described with tongues 316, 318, 320, 322 in the first and second endplates 14, 16 and angled grooves 370, 372, 374, 376 on the driving ramp 300, it should be understood that that device 10 can also be configured with grooves on the second endplate 16 and tongues on the driving ramp 300, in accordance with one embodiment of the present invention.

Turning now to FIGS. 40-42, a method of installing the expandable fusion device 10 of FIGS. 40-49 is now discussed in accordance with one embodiment of the present invention. Prior to insertion of the fusion device, the disc

space may be prepared as described above. The expandable fusion device 10 can then be inserted into and seated in the appropriate position in the intervertebral disc space. The expandable fusion device 10 is then introduced into the intervertebral space, with the end having the expansion portion 334 of the central ramp 18 being inserted. In an exemplary method, the fusion device 10 is in the unexpanded position when introduced into the intervertebral space. In an exemplary method, the intervertebral space may be distracted prior to insertion of the fusion device 10. The distraction provides some benefits by providing greater access to the surgical site making removal of the intervertebral disc easier and making scraping of the endplates of the vertebral bodies 2, 3 easier.

With the fusion device 10 inserted into and seated in the appropriate position in the intervertebral disc space, the fusion device can then be expanded into the expanded position, as best seen in FIG. 42. To expand the fusion device 10, an instrument is engaged with the head portion 324 of the actuator assembly 200. The instrument is used to rotate actuator assembly 200. As discussed above, actuator assembly 200 is threadingly engaged with the extension 336 of the central ramp 18; thus, as the actuator assembly 200 is rotated in a first direction, the central ramp 18 is pulled toward the actuator assembly 200. In an exemplary embodiment, the actuator assembly 200 is moved in a linear direction with the ratchet teeth engaging as means for controlling the movement of the actuator assembly 200 and the central ramp 18. As the central ramp 18 is pulled towards the actuator assembly 200, the first ramped portions 344 of the central ramp 18 push against the second ramped portions 310, 312 of the second endplate 16 and the second ramped portions 346 of the central ramp 18 push against first ramped portions 306, 308 of the first endplate 14. In this manner, the central ramp 18 acts to push the endplates 14, 16 outwardly into the expanded position. This can best be seen in FIGS. 40-42. As the endplates 14, 16 move outwardly the tongues 316, 318, 320, 322 in the endplates 14, 16 ride in the angled grooves 348, 350 with the tongues 320, 322 in the second endplate 16 riding in angled grooves 348 and the tongues 316, 318 in the first endplate 14 riding in angled grooves 350.

As discussed above, the actuator assembly 200 also engages driving ramp 300; thus, as the actuator assembly 200 is rotated in a first direction, the actuator assembly 200 pushes the driving ramp 300 towards the central ramp 18 in a linear direction. As the driving ramp 300 is pushed towards the central ramp 18, the first ramped portions 370 of the driving ramp 300 push against the first ramped portions 306, 308 of the second endplate 16 and the second ramped portions 372 of the driving ramp 300 push against the second ramped portions 310, 312 of the first endplate 14. In this manner, the driving ramp 300 also acts to push the endplates 14, 16 outwardly into the expanded position. This can best be seen in FIGS. 40-42. As the endplates 14, 16 move outwardly the tongues 316, 318, 320, 322 in the endplates 14, 16 ride in the angled grooves 370, 372 with the tongues 316, 318 in the second endplate 16 riding in angled grooves 370 and the tongues 320, 322 in the first endplate 14 riding in angled grooves 372.

Since the expansion of the fusion device 10 is actuated by a rotational input, the expansion of the fusion device 10 is infinite. In other words, the endplates 14, 16 can be expanded to an infinite number of heights dependent on the rotational advancement of the actuator assembly 200.

Referring now to FIGS. 50-54, an alternative embodiment of the expandable fusion device 10 is shown. In the illus-

trated embodiment, the fusion device **10** includes a first endplate **14**, a second endplate **16**, a central ramp **18**, an actuator assembly **200**, and a driving ramp **300**. As will be discussed in more detail below, the actuator assembly **200** functions, in an embodiment, to pull the central ramp **18** and the driving ramp **300** together, which forces apart the first and second endplates **14**, **16**. In an embodiment, the expandable fusion device may contain features, such as a through bore, that facilitate placement down an endoscopic tube. In an embodiment, the assembled fusion device **10** may be placed down the endoscopic tube and then expanded.

Although the following discussion relates to the first endplate **14**, it should be understood that it also equally applies to the second endplate **16** as the second endplate **16** is substantially identical to the first endplate **14** in embodiments of the present invention. It should be understood that, in an embodiment, the first endplate **14** is configured to interlock with the second endplate **16**. With additional reference to FIG. **55**, in an exemplary embodiment, the first endplate **14** has a first end **39** and a second end **41**. As illustrated, the first end **39** may be wider than the second end **41**. In the illustrated embodiment, the first endplate **14** further comprises an upper surface **40** connecting the first end **39** and the second end **41**, and a lower surface **42** connecting the first end **39** and the second end **41**. As best seen in FIG. **54**, the lower surface **42** can be curved concavely such that the first and second endplates **14**, **16** form a through bore when the device **10** is in a closed position. In an embodiment, the first endplate **14** may comprise a through opening **44**. The through opening **44**, in an exemplary embodiment, is sized to receive bone graft or similar bone growth inducing material.

In one embodiment, the upper surface **40** of the first endplate **14** is flat and generally planar to allow the upper surface **40** of the endplate **14** to engage with the adjacent vertebral body **2**. Alternatively, as shown in FIG. **15**, the upper surface **40** can be curved convexly or concavely to allow for a greater or lesser degree of engagement with the adjacent vertebral body **2**. It is also contemplated that the upper surface **40** can be generally planar but includes a generally straight ramped surface or a curved ramped surface. The ramped surface allows for engagement with the adjacent vertebral body **2** in a lordotic fashion. As illustrated, in an exemplary embodiment, the upper surface **40** includes texturing to aid in gripping the adjacent vertebral bodies. For example, the upper surface **40** may further comprise texturing **400** to engage the adjacent vertebral bodies. Although not limited to the following, the texturing can include teeth, ridges, friction increasing elements, keels, or gripping or purchasing projections.

In one embodiment, the first endplate **14** further comprises a first side portion **202** connecting the first end **39** and the second end **41**, and a second side portion **204** connecting the first end **39** and the second end **41**. In the illustrated embodiment, the first and second side portions **202**, **204** are extensions from the lower surface **42**. In an embodiment, the first and second side portions **202**, **204** each include an interior surface **302** and an exterior surface **304**. In an embodiment, the first end **39** of the first endplate **14** is generally designed and configured to fit over the second end **41** of the second endplate **16** when the device **10** is in a closed position. As illustrated, the first and second side portions **202**, **204** each may include first ramped portions **306**, **308**, second ramped portions **310**, **312**, and/or central ramped portion **402**.

In an embodiment, the first ramped portions **306**, **308** are proximate the first end **39** of the endplate **14**. In accordance

with embodiment of the present invention, the first ramped portions **306**, **308** of the first endplate **14** are generally designed and configured to fit over the second ramped portions **310**, **312** of the second endplate **16** when the device **10** is in a closed position. In an exemplary embodiment, the first ramped portions **306**, **308** generally face the first end **39** and can extend in an oblique direction with respect to the upper surface **40**, for example. As illustrated, the first ramped portions **306**, **308** may include tongue portions **316**, **318** extending in an oblique direction with respect to the upper surface **40** of the endplate **14**.

In an embodiment, the second ramped portions **310**, **312** are proximate the second end **41** of the endplate **14**. In an exemplary embodiment, the second ramped portions **310**, **312** can extend in an oblique direction with respect to the upper surface **40** and generally face the second end **41**. The first and second side portions **202**, **204**, in an embodiment, each can include a bridge portion **314** connecting the first ramped portions **306**, **308** and the second ramped portions **310**, **312**. As further illustrated, the second ramped portions **310**, **312** may include tongue portions **320**, **322** that extend in an oblique direction with respect to the upper surface **40** of the endplate **14**.

In an embodiment, the endplate **14** further may include a central ramped portion **402** proximate the bridge portion **314**. In the illustrated embodiment, the endplate **14** includes a central ramped portion **402** proximate the bridge portion **314** of the second side portion **204**. In an exemplary embodiment, the central ramped portion **402** can extend in an oblique direction with respect to the upper surface **40** and face the first end **39** of the endplate **14**. As illustrated, the first ramped portions **306**, **308** may include tongue portions **316**, **318** with the tongue portions **316**, **318** extending in an oblique direction with respect to the upper surface **40** of the endplate **14**.

With reference to FIGS. **50-52** and **54**, in an embodiment, the actuator assembly **200** includes a head portion **324**, an extension **404**, and a through bore **406** that extends longitudinally through the actuator assembly **200**. As illustrated, the head portion **324** may include one or more instrument gripping features **330** that can allow it to be turned by a suitable instrument. In addition, the head portion **324** has a larger diameter than the other components of the actuator assembly **200** to provide a contact surface with the driving ramp **300**. In the illustrated embodiment, the head portion **324** includes a rim **332** that provides a surface for contacting the driving ramp **300**. In an embodiment, the extension **404** is a generally rod-like extension. In another embodiment, the extension **404** includes ratchet teeth for engaging the extension **336**.

With reference to FIGS. **51**, **52**, and **56**, the central ramp **18** has a first end **408** and a second end **410**. In an embodiment, the central ramp **18** includes a first expansion portion **412**, a second expansion portion **414**, a rod-receiving extension **416**, and a through bore **418** that extends longitudinally through the central ramp **18**. In an exemplary embodiment, first expansion portion **412** can be proximate the first end **408** of the central ramp **18**. As best seen in FIG. **56**, the first expansion portion **412** may include side portions **420**, **422**. In an embodiment, each of the side portions **420**, **422** includes dual, overlapping ramped portions that extend in oblique directions with respect to the through bore **418**. For example, side portions **420**, **422** each include a first ramped portion **424** that overlaps a second ramped portion **426**. In the illustrated embodiment, the first ramped portion **424** faces the rod-receiving extension **416** while the second ramped portion **426** faces the opposite direction. In one

19

embodiment, angled grooves **428, 430** are formed in each of the first and second ramped portions **424, 426**. In an exemplary embodiment, the angled grooves **428, 430** are sized to receive the corresponding tongues **316, 318, 320, 322** in the first and second endplates **14, 16** with angled grooves **428** receiving tongues **320, 322** in the second endplate **16** and angled grooves **430** receiving tongues **316, 318** in the first endplate **14**. Although the device **10** is described with tongues **316, 318, 320, 322** on the endplates **14, 16** and angled grooves **428, 430** on the central ramp **18**, it should be understood that that device **10** can also be configured with grooves on the endplates **14, 16** and tongues on the central ramp **18**, in accordance with one embodiment of the present invention.

In an embodiment, the second expansion portion **414** is located on the rod-receiving extension **416** between the first end **408** and the second end **410** of the central ramp **18**. In an exemplary embodiment, the second expansion portion **414** includes central ramped portions **432**. In one embodiment, the second expansion portion **414** includes two central ramped portions **432** on opposite sides of the rod-receiving extension **416**. In an exemplary embodiment, the central ramped portions **424** extend in an oblique direction with respect to the through bore **418** and face the second end **410** of the central ramp **18**.

The rod-receiving extension **416** extends from the first expansion portion **412** and has an opening **434** at the second end of the central ramp **18**. In an embodiment, the rod-receiving extension **416** is sized and configured to receive the extension **404** of the actuator assembly **200**. In an embodiment, the rod-receiving extension **416** has threading with the rod-receiving extension **416** threadingly receiving extension **404** of the actuator assembly **200**. In another embodiment, the rod-receiving extension **416** has ratchet teeth with the extension **404** being ratcheted into the rod-receiving extension **416**.

With reference to FIGS. **50-52** and **57**, in an exemplary embodiment, the driving ramp **300** includes an upper portion **354** having an upper surface **356** and an oblique surface **358**. In an embodiment, the driving ramp **300** further includes a bore **366**, in an exemplary embodiment, sized to receive the extension **404** of the actuator assembly **200**. In the illustrated, embodiment, the upper portion **354** has a hole **436** that extends through the upper surface **356** to the bore **366**. Set screw **438** may be inserted through the hole **436** to secure the driving ramp **300** to the actuator assembly **200**. In one embodiment, the driving ramp **300** further includes contact surface **368** that engages the rim **332** of the head portion **324** of the actuator assembly **200**. In the illustrated embodiment, the contact surface **368** has a generally annular shape.

In an embodiment, the driving ramp **300** further includes side portions **360, 362** that extend from the upper portion **354** connecting the upper portion **354** with the lower portion **364** of the driving ramp **300**. In an exemplary embodiment, the side portions **360, 362** of the driving ramp **300** each include a ramped portion **438**. In the illustrated embodiment, the ramped portion **438** faces central ramp **300**. In an embodiment, the ramped portion **438** is configured and dimensioned to engage the ramped portions **306, 308** at the first end **39** of the second endplate **16**. In one embodiment, angled grooves **440** are formed in the ramped portions **316, 318**. In an exemplary embodiment, the angled grooves **440** are sized to receive the corresponding tongues **316, 318** in the second endplate **16**. Although the device **10** is described with tongues **316, 318** on the second endplate **16** and angled grooves **440** on the driving ramp **300**, it should be under-

20

stood that that device **10** can also be configured with grooves on the second endplate **16** and tongues on the driving ramp **300**, in accordance with one embodiment of the present invention.

A method of installing the expandable fusion device **10** of FIGS. **50-57** is now discussed in accordance with one embodiment of the present invention. Prior to insertion of the fusion device, the disc space may be prepared as described above. The expandable fusion device **10** can then be inserted into and seated in the appropriate position in the intervertebral disc space. In an embodiment, the device **10** is assembled prior to insertion. The expandable fusion device **10** can be introduced into the intervertebral space, with the end having the first end **408** of the central ramp **18** being inserted. In an exemplary method, the fusion device **10** is in the unexpanded position when introduced into the intervertebral space. In an exemplary method, the intervertebral space may be distracted prior to insertion of the fusion device **10**. The distraction provides some benefits by providing greater access to the surgical site making removal of the intervertebral disc easier and making scraping of the endplates of the vertebral bodies **2, 3** easier.

With the fusion device **10** inserted into and seated in the appropriate position in the intervertebral disc space, the fusion device can then expand into the expanded position. To expand the fusion device **10**, an instrument is engaged with the head portion **324** of the actuator assembly **200**. The instrument is used to rotate actuator assembly **200**. As discussed above, actuator assembly **200** is threadingly engaged with the rod receiving extension **416** of the central ramp **18**; thus, as the actuator assembly **200** is rotated in a first direction, the central ramp **18** is pulled toward the actuator assembly **200**. In an exemplary embodiment, the actuator assembly **200** is moved in a linear direction with the ratchet teeth engaging as means for controlling the movement of the actuator assembly **200** and the central ramp **18**.

As the central ramp space **18** is pulled towards the actuator assembly **200**, the central ramp **18** acts to push endplates **14, 16** outwardly into the expanded position. By way of example, the first ramped portions **424**, second ramped portions **426**, and central ramped portions **432** push against the corresponding ramped portions in the first and second endplates **14, 16**. The first ramped portions **424** in the first expansion portion **412** of the central ramp **18** push against the second ramped portions **310, 312** of the second endplate **16** with the corresponding tongues **320, 322** in the second ramped portions **310, 312** of the second endplate **16** riding in angled grooves **428** in the first ramped portions **424** in the first expansion portion **412**. The second ramped portions **426** in the first expansion portion **412** push against the first ramped portions **316, 318** of the first endplate **14** with the corresponding tongues **316, 318** in first ramped portions **316, 318** of the first endplate **14** riding in angled grooves **430** in the second ramped portions **426** in the first expansion portion **412**. The central ramped portions **432** in the second expansion portion **414** push against the central ramped portion **402** in the first and second endplates **14, 16**.

As discussed above, the actuator assembly **200** also engages driving ramp **300**; thus, as the actuator assembly **200** is rotated in a first direction, the actuator assembly **200** pushes the driving ramp **300** towards the central ramp **18** in a linear direction. As the driving ramp **300** is pushed towards the central ramp **18**, the driving ramp **300** also acts to push the endplates **14, 16** outwardly into the expanded position. By way of example, the ramped portions **438** of the driving ramp **300** push against ramped portions **306, 308** at the first end **39** of the second endplate **16**. As the endplates **14, 16**

21

move outwardly, the tongues **316, 318** in the ramped portions **306, 308** of the second endplate **16** ride in the angled grooves **440** in the ramped portions **438** of the driving ramp **300**.

It should also be noted that the expansion of the endplates **14, 16** can be varied based on the differences in the dimensions of the various ramped portions in the central ramp **18**, the driving ramp **300**, and the first and second endplates **14, 16**. As best seen in FIG. **16**, the endplates **14, 16** can be expanded in any of the following ways: straight rise expansion, straight rise expansion followed by a toggle into a lordotic expanded configuration, or a phase off straight rise into a lordotic expanded configuration.

In the event the fusion device **10** needs to be repositioned or revised after being installed and expanded, the fusion device **10** can be contracted back to the unexpanded configuration, repositioned, and expanded again once the desired positioning is achieved. To contract the fusion device **10**, the instrument can be used to rotate the actuator assembly **200** in a second direction that is opposite the first direction. Rotation of the actuator assembly **200** results in movement of the central ramp **18** and the driving ramp **300** away from one another. As the central ramp **18** and the driving ramp **300** move, the endplates **14, 16** move inwardly into the unexpanded position.

Although the preceding discussion only discussed having a single fusion device **10** in the intervertebral space, it is contemplated that more than one fusion device **10** can be inserted in the intervertebral space. It is further contemplated that each fusion device **10** does not have to be finally installed in the fully expanded state. Rather, depending on the location of the fusion device **10** in the intervertebral disc space, the height of the fusion device **10** may vary from unexpanded to fully expanded. It should be noted that, as well as the height being varied from an unexpanded state to an expanded state, the fusion **10** may be positioned permanently anywhere between the expanded state and the unexpanded state.

The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

I claim:

1. An expandable fusion device comprising:

a first endplate and a second endplate,

a central ramp, a driving ramp, and an actuator positioned

between the first and second endplates, the central ramp

non-rotationally coupled to the first and second end-

plates, and including a threaded bore, a first expansion

portion, and a second expansion portion longitudinally

spaced from the first expansion portion, the driving

ramp including a through bore and a third expansion

portion, the actuator including a head portion and a

threaded extension that extends from the head portion,

the extension of the actuator non-threadingly extending

through the through bore of the driving ramp and

threadingly extending into the threaded bore of the

central ramp,

wherein the actuator is rotationally coupled to the driving

ramp and when the actuator is rotated relative to the

central ramp, the central ramp and the driving ramp

move towards one another, thereby causing the first and

second endplates to move apart.

22

2. The device of claim **1**, wherein the first expansion portion is proximate a first end and includes overlapping ramped portions.

3. The device of claim **2**, wherein the second expansion portion is positioned between the first end and a second end and includes central ramped portions.

4. The device of claim **3**, wherein the central ramped portions includes two central ramped portions on opposite side of the central ramp.

5. The device of claim **1**, wherein the driving ramp includes an upper side, a lower side, a first side portion connecting the upper side and the lower side, and a second side portion connecting the upper side and the lower side, and the first and second side portions include the third expansion portion as one or more ramped surfaces.

6. The device of claim **1**, wherein the head portion of the actuator has a larger diameter than the extension.

7. The device of claim **1**, wherein the head portion of the actuator includes a rim configured to contact the driving ramp.

8. The device of claim **1**, wherein the first and second endplates each comprise an opening that extends from an upper surface through a lower surface.

9. The device of claim **1**, wherein a first end of the first endplate is wider than a second end of the first endplate.

10. The device of claim **1**, wherein the first and second endplates comprise texturing for gripping adjacent vertebral bodies.

11. An expandable fusion device comprising:

a first endplate and a second endplate,

a central ramp, a driving ramp, and an actuator positioned

between the first and second endplates, the central ramp

non-rotationally coupled to the first and second end-

plates, and including a threaded bore, a first expansion

portion including at least one ramped surface, and a

second expansion portion including at least one ramped

surface, the second expansion portion being longitudinally

spaced from the first expansion portion, the

driving ramp including an unthreaded through bore and

a third expansion portion including at least one ramped

surface, and a portion of the actuator non-threadingly

extends through the through bore of the driving ramp

and threadingly extends into the threaded bore of the

central ramp,

wherein the actuator is rotationally coupled to the driving

ramp and when the actuator is rotated relative to the

central ramp, the central ramp and the driving ramp

move towards one another, thereby causing the first and

second endplates to move apart.

12. The device of claim **11**, wherein the first expansion portion is proximate a first end and the at least one ramped surface of the first expansion portion includes overlapping ramped portions.

13. The device of claim **12**, wherein the second expansion portion is positioned between the first end and a second end and the at least one ramped surface of the second expansion portion includes central ramped portions.

14. The device of claim **13**, wherein the central ramped portions includes two central ramped portions on opposite side of the central ramp.

15. The device of claim **11**, wherein the driving ramp includes an upper side, a lower side, a first side portion connecting the upper side and the lower side, and a second side portion connecting the upper side and the lower side, and the first and second side portions include the third expansion portion as one or more ramped surfaces.

16. The device of claim 11, wherein the actuator includes a head portion and an extension that extends from the head portion, and the head portion of the actuator has a larger diameter than the extension.

17. The device of claim 16, wherein the head portion of the actuator includes a rim configured to contact the driving ramp. 5

18. The device of claim 11, wherein the first and second endplates each comprise an opening that extends from an upper surface through a lower surface. 10

19. The device of claim 11, wherein a first end of the first endplate is wider than a second end of the first endplate.

20. The device of claim 11, wherein the first and second endplates comprise texturing for gripping adjacent vertebral bodies. 15

* * * * *