



US010376259B2

(12) **United States Patent**
Bonutti et al.

(10) **Patent No.:** **US 10,376,259 B2**

(45) **Date of Patent:** **Aug. 13, 2019**

(54) **DEFORMABLE FASTENER SYSTEM**

(71) Applicant: **P Tech, LLC**, Effingham, IL (US)

(72) Inventors: **Peter M. Bonutti**, Manalapan, FL (US);
Glen A. Phillips, Effingham, IL (US)

(73) Assignee: **P Tech, LLC**, Effingham, IL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/726,503**

(22) Filed: **Oct. 6, 2017**

(65) **Prior Publication Data**

US 2018/0028172 A1 Feb. 1, 2018

Related U.S. Application Data

(63) Continuation of application No. 13/871,892, filed on Apr. 26, 2013, now Pat. No. 9,814,453, which is a (Continued)

(51) **Int. Cl.**
A61B 17/04 (2006.01)
A61B 17/68 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61B 17/0401** (2013.01); **A61B 17/0218** (2013.01); **A61B 17/0469** (2013.01); **A61B 17/0482** (2013.01); **A61B 17/0483** (2013.01); **A61B 17/0487** (2013.01); **A61B 17/1637** (2013.01); **A61B 17/1671** (2013.01); **A61B 17/1675** (2013.01); **A61B 17/17** (2013.01); **A61B 17/683** (2013.01); **A61B 17/7053** (2013.01); **A61B 17/842** (2013.01); **A61B 17/8869** (2013.01); **A61B 17/00491** (2013.01);

A61B 17/0467 (2013.01); **A61B 17/0485** (2013.01); **A61B 17/1615** (2013.01); **A61B 17/1757** (2013.01); **A61B 2017/00004** (2013.01); **A61B 2017/00477** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC **A61B 17/0469**; **A61B 17/0401**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

319,296 A 6/1885 Molesworth
668,878 A 2/1901 Jensen
(Continued)

FOREIGN PATENT DOCUMENTS

CA 2641580 8/2007
CA 2680827 9/2008
(Continued)


Primary Examiner — Christian A Sevilla

(74) *Attorney, Agent, or Firm* — Stinson LLP

(57) **ABSTRACT**

The guidance and positioning device may be a system for creating a passage in tissue, positioning fasteners or other implants, and tensioning an elongated fastening member, like a suture, thread, wire, or pin. In some embodiments, the device may allow for the implantation of multiple sutures and fasteners in tissue. A fastener may be positioned at the distal end of a flexible pushrod. The fastener may be connected with the pushrod or may be loosely fitted with the distal end of the pushrod. A suture may be looped through or connected with the fastener such that one, two, or more sections, legs, strands, or portions of the suture extend from the fastener.

26 Claims, 12 Drawing Sheets



continuation of application No. 11/202,294, filed on
Oct. 5, 2005, now Pat. No. 9,463,012.

(51) **Int. Cl.**

A61B 17/02 (2006.01)

A61F 2/28 (2006.01)

A61F 2/30 (2006.01)

A61F 2/08 (2006.01)

A61B 17/29 (2006.01)

A61B 17/84 (2006.01)

A61B 17/70 (2006.01)

A61B 17/16 (2006.01)

A61F 2/44 (2006.01)

A61B 17/88 (2006.01)

A61B 17/17 (2006.01)

A61B 17/00 (2006.01)

A61B 17/06 (2006.01)

A61B 90/00 (2016.01)

(52) U.S. Cl.

CPC *A61B 2017/00818* (2013.01); *A61B*

2017/00876 (2013.01); A61B 2017/00893

(2013.01); *A61B* 2017/00898 (2013.01); *A61B*

2017/0404 (2013.01); A61B 2017/0409

3.01); *A61B* 2017/0417 (2013.01); *A61B*

2017/0464 (2013.01); A61B 2017/0488

3.01); *A61B* 2017/0496 (2013.01); *A61B*

2017/06176 (2013.01); A61B 2017/2926

13.01); *A61B 2090/064* (2016.02); *A61F*

2/08 (2013.01); A61F 2/28 (2013.01); A61F

2/442 (2013.01); *A61F* 2002/2817 (2013.01);

A61F 2002/30062 (2013.01); *A61F*

2002/30677 (2013.01); A61F 2002/444

(2013.01); *A61F* 2002/4435 (2013.01); *A61F*

2210/0004 (2013.01); A61F 2310/00293

(2013.01); *A61F* 2310/00359 (2013.01)

(56)

References Cited

U.S. PATENT DOCUMENTS

668,879	A	2/1901	Miller
702,789	A	6/1902	Gibson
862,712	A	8/1907	Collins
2,121,193	A	6/1938	Erich
2,178,840	A	11/1939	Libarid
2,187,852	A	1/1940	Friddle
2,199,025	A	4/1940	Conn
2,235,419	A	3/1941	Callahan
2,248,054	A	7/1941	Joseph
2,270,188	A	1/1942	Longfellow
2,518,276	A	8/1950	Brawand
2,557,669	A	6/1951	Lloyd
2,566,499	A	9/1951	Bruno
2,621,653	A	12/1952	Henry
2,725,053	A	11/1955	John
2,830,587	A	4/1958	James
3,204,635	A	9/1965	Voss
3,347,234	A	10/1967	Voss
3,367,809	A	2/1968	Soloff
3,391,690	A	7/1968	Anthony
3,477,429	A	11/1969	Sampson
3,513,848	A	5/1970	Winston
3,518,993	A	7/1970	Blake
3,577,991	A	5/1971	Wilkinson
3,596,292	A	8/1971	Erb
3,608,539	A	9/1971	Miller
3,625,220	A	12/1971	Engelsher
3,648,705	A	3/1972	Lary
3,653,388	A	4/1972	Tenckhoff
3,656,476	A	4/1972	Swinney

3,657,056	A	4/1972	Winston	
3,678,980	A	7/1972	Gutshall	
3,709,218	A	1/1973	Halloran	
3,711,347	A	1/1973	Wagner	
3,760,808	A	9/1973	Bleuer	
3,762,418	A *	10/1973	Wasson	A61B 17/06004 606/226
3,788,318	A	1/1974	Kim	
3,789,852	A	2/1974	Kim	
3,802,438	A	4/1974	Wolvek	
3,807,394	A	4/1974	Attenborough	
3,809,075	A	5/1974	Matles	
3,811,449	A	5/1974	Gravlee	
3,825,010	A	7/1974	McDonald	
3,833,003	A	9/1974	Taricco	
3,835,849	A	9/1974	McGuire	
3,842,824	A	10/1974	Neufeld	
3,857,396	A	12/1974	Hardwick	
3,867,932	A	2/1975	Huene	
3,875,652	A	4/1975	Arnold	
3,898,992	A	8/1975	Balamuth	
3,918,442	A	11/1975	Nikolaev	
3,968,800	A	7/1976	Vilasi	
4,023,559	A	5/1977	Gaskell	
4,064,566	A	12/1977	Fletcher	
4,089,071	A	5/1978	Kalnberz	
4,156,574	A	5/1979	Boden	
4,164,794	A	8/1979	Spector	
4,171,544	A	10/1979	Hench	
4,183,102	A	1/1980	Guiset	
4,199,864	A	4/1980	Ashman	
4,200,939	A	5/1980	Oser	
4,210,148	A	7/1980	Stivala	
4,213,816	A	7/1980	Morris	
4,235,233	A	11/1980	Mouwten	
4,235,238	A	11/1980	Ogiu	
4,257,411	A	3/1981	Cho	
4,265,231	A	5/1981	Scheller	
4,279,249	A	7/1981	Vert	
4,281,649	A	8/1981	Derweduwten	
4,291,698	A	9/1981	Fuchs	
4,309,488	A	1/1982	Heide	
4,320,762	A	3/1982	Bentov	
4,351,069	A	9/1982	Ballintyn	
4,364,381	A	12/1982	Sher	
4,365,356	A	12/1982	Broemer	
4,388,921	A	6/1983	Sutter	
4,395,798	A	8/1983	McVey	
4,409,974	A	10/1983	Freedland	
4,414,166	A	11/1983	Charlson	
4,437,191	A	3/1984	Van Der Zel	
4,437,362	A	3/1984	Hurst	
4,444,180	A	4/1984	Schneider	
4,448,194	A	5/1984	DiGiovanni	
4,456,005	A	6/1984	Lichty	
4,461,281	A	7/1984	Carson	
4,493,317	A	1/1985	Klaue	
4,495,664	A	1/1985	Blanquaert	
4,501,031	A	2/1985	McDaniel	
4,504,268	A	3/1985	Herlitze	
4,506,681	A	3/1985	Mundell	
4,514,125	A	4/1985	Stol	
4,526,173	A	7/1985	Sheehan	
4,532,926	A	8/1985	O'Holla	
4,535,772	A	8/1985	Sheehan	
4,547,327	A	10/1985	Bruins	
4,556,350	A	12/1985	Bernhardt	
4,566,138	A	1/1986	Lewis	
4,589,868	A	5/1986	Dretler	
4,590,928	A	5/1986	Hunt	
4,597,379	A	7/1986	Kihn	
4,599,085	A	7/1986	Riess	
4,601,893	A	7/1986	Cardinal	
4,606,335	A	8/1986	Wedeen	
4,621,640	A	11/1986	Mulhollan	
4,630,609	A	12/1986	Chin	
4,632,100	A	12/1986	Somers	
4,632,101	A	12/1986	Freedland	
4,645,503	A	2/1987	Lin	

(56)

References Cited

U.S. PATENT DOCUMENTS

4,657,460 A	4/1987	Bien	4,997,445 A	3/1991	Hodorek
4,659,268 A	4/1987	Del Mundo	4,998,539 A	3/1991	Delsanti
4,662,063 A	5/1987	Collins	5,002,550 A	3/1991	Li
4,662,068 A	5/1987	Polonsky	5,002,563 A	3/1991	Pyka
4,662,887 A	5/1987	Turner	5,009,652 A	4/1991	Morgan
4,669,473 A	6/1987	Richards	5,009,663 A	4/1991	Broome
4,685,458 A	8/1987	Leckrone	5,009,664 A	4/1991	Sievers
4,691,741 A	9/1987	Affa	5,013,316 A	5/1991	Goble
4,705,040 A	11/1987	Mueller	5,019,090 A	5/1991	Pinchuk
4,706,670 A	11/1987	Andersen	5,021,059 A	6/1991	Kensley
4,708,139 A	11/1987	Dunbar	5,035,713 A	7/1991	Friis
4,713,077 A	12/1987	Small	5,037,404 A	8/1991	Gold
4,716,901 A	1/1988	Jackson	5,037,422 A	8/1991	Hayhurst
4,718,909 A	1/1988	Brown	5,041,093 A	8/1991	Chu
4,722,331 A	2/1988	Fox	5,041,114 A	8/1991	Chapman
4,722,948 A	2/1988	Sanderson	5,041,129 A	8/1991	Hayhurst
4,724,584 A	2/1988	Kasai	5,046,513 A	9/1991	Gattorna
4,738,255 A	4/1988	Goble	5,047,055 A	9/1991	Bao
4,739,751 A	4/1988	Sapega	5,051,049 A	9/1991	Wills
4,741,330 A *	5/1988	Hayhurst	5,053,046 A	10/1991	Janese
	 A61B 17/0401	5,053,047 A	10/1991	Yoon
		606/144	5,059,193 A	10/1991	Kuslich
4,743,257 A	5/1988	Tormala	5,059,206 A	10/1991	Winters
4,749,585 A	6/1988	Greco	5,061,274 A	10/1991	Kensley
4,750,492 A	6/1988	Jacobs	5,061,286 A	10/1991	Lyle
4,759,765 A	7/1988	Van Kampen	5,064,286 A	11/1991	Ai
4,768,507 A	9/1988	Fischell	5,069,674 A	12/1991	Fearnot
4,772,286 A	9/1988	Goble	5,078,731 A	1/1992	Hayhurst
4,776,328 A	10/1988	Frey	5,078,744 A	1/1992	Chvapil
4,776,738 A	10/1988	Winston	5,078,745 A	1/1992	Rhenter
4,776,851 A	10/1988	Bruchman	5,084,050 A	1/1992	Draenert
4,781,182 A	11/1988	Purnell	5,084,051 A	1/1992	Tormala
4,790,303 A	12/1988	Steffee	5,085,660 A	2/1992	Lin
4,792,336 A	12/1988	Hlavacek	5,085,661 A	2/1992	Moss
4,817,591 A	4/1989	Klaue	5,098,433 A	3/1992	Freedland
4,822,224 A	4/1989	Carl	5,098,434 A	3/1992	Serbousek
4,823,794 A	4/1989	Pierce	5,098,436 A	3/1992	Ferrante
4,832,025 A	5/1989	Coates	5,100,405 A	3/1992	McLaren
4,832,026 A	5/1989	Jones	5,100,417 A	3/1992	Cerier
4,834,752 A	5/1989	Van Kampen	5,102,417 A	4/1992	Palmaz
4,841,960 A	6/1989	Garner	5,102,421 A	4/1992	Anspach
4,843,112 A	6/1989	Gerhart	5,108,399 A	4/1992	Eitenmuller
4,846,812 A	7/1989	Walker	5,120,175 A	6/1992	Arbegast
4,862,882 A	9/1989	Venturi	5,123,520 A	6/1992	Schmid
4,869,242 A	9/1989	Galluzzo	5,123,914 A	6/1992	Cope
4,870,957 A	10/1989	Goble	5,123,941 A	6/1992	Lauren
4,883,048 A	11/1989	Purnell	5,133,732 A	7/1992	Wiktor
4,890,612 A	1/1990	Kensley	RE34,021 E	8/1992	Mueller
4,895,148 A	1/1990	Bays	5,141,520 A	8/1992	Goble
4,898,156 A *	2/1990	Gattorna	5,147,362 A	9/1992	Goble
	 A61B 17/0401	5,154,720 A	10/1992	Trott
		411/512	5,156,613 A	10/1992	Sawyer
4,899,729 A	2/1990	Gill	5,156,616 A	10/1992	Meadows
4,899,744 A	2/1990	Fujitsuka	5,158,566 A	10/1992	Pianetti
4,901,721 A	2/1990	Hakki	5,158,934 A	10/1992	Ammann
4,921,479 A	5/1990	Grayzel	5,163,960 A	11/1992	Bonutti
4,922,897 A	5/1990	Sapega	5,171,251 A	12/1992	Bregen
4,924,866 A	5/1990	Yoon	5,176,682 A	1/1993	Chow
4,932,960 A	6/1990	Green	5,179,964 A	1/1993	Cook
4,935,026 A	6/1990	McFadden	5,180,385 A	1/1993	Sontag
4,935,028 A	6/1990	Drews	5,180,388 A	1/1993	DiCarlo
4,945,625 A	8/1990	Winston	5,183,464 A	2/1993	Dubrul
4,946,468 A	8/1990	Li	5,192,287 A	3/1993	Fournier
4,950,285 A *	8/1990	Wilk	5,192,326 A	3/1993	Bao
	 A61B 17/06	5,197,166 A	3/1993	Meier
		24/16 PB	5,197,971 A	3/1993	Bonutti
4,954,126 A	9/1990	Wallsten	5,203,784 A	4/1993	Ross
4,955,910 A	9/1990	Bolesky	5,203,787 A *	4/1993	Noblitt
4,957,498 A	9/1990	Caspari		 A61B 17/0401
4,961,741 A	10/1990	Hayhurst	5,208,950 A	5/1993	Merritt
4,963,151 A	10/1990	Ducheyne	5,209,776 A	5/1993	Bass
4,966,583 A	10/1990	Debbas	5,217,493 A	6/1993	Raad
4,968,315 A	11/1990	Gattorna	5,219,359 A	6/1993	McQuilkin
4,968,317 A	11/1990	Tormala	5,226,899 A	7/1993	Lee
4,969,888 A	11/1990	Scholten	5,234,006 A	8/1993	Eaton
4,969,892 A	11/1990	Burton	5,234,425 A	8/1993	Fogarty
4,990,161 A	2/1991	Kampner	5,234,443 A	8/1993	Phan
4,994,071 A	2/1991	MacGregor	5,236,438 A	8/1993	Wilk
			5,236,445 A	8/1993	Hayhurst

US 10,376,259 B2

Page 4

(56)

References Cited

U.S. PATENT DOCUMENTS

5,242,902	A	9/1993	Murphy	5,464,426	A	11/1995	Bonutti
5,254,113	A	10/1993	Wilk	5,464,427	A	11/1995	Curtis
5,258,007	A	11/1993	Spetzler	5,470,337	A	11/1995	Moss
5,258,015	A	11/1993	Li	5,472,444	A	12/1995	Huebner
5,258,016	A *	11/1993	DiPoto A61B 17/0401	5,474,554	A	12/1995	Ku
			606/104	5,478,351	A	12/1995	Meade
5,261,886	A	11/1993	Chesterfield	5,478,353	A	12/1995	Yoon
5,266,325	A	11/1993	Kuzma	5,480,403	A	1/1996	Lee
5,269,783	A	12/1993	Sander	5,486,197	A	1/1996	Le
5,269,785	A	12/1993	Bonutti	5,487,844	A	1/1996	Fujita
5,269,809	A	12/1993	Hayhurst	5,488,958	A	2/1996	Topel
5,281,235	A	1/1994	Haber	5,496,292	A	3/1996	Burnham
5,282,832	A	2/1994	Toso	5,496,318	A	3/1996	Howland
5,290,281	A	3/1994	Tschakaloff	5,496,335	A	3/1996	Thomason
5,304,119	A	4/1994	Balaban	5,496,348	A	3/1996	Bonutti
5,306,280	A	4/1994	Bregen	5,500,000	A	3/1996	Feagin
5,306,301	A	4/1994	Graf	5,501,700	A	3/1996	Hirata
5,315,741	A	5/1994	Dubberke	5,504,977	A	4/1996	Weppner
5,318,588	A	6/1994	Horzewski	5,505,735	A	4/1996	Li
5,320,611	A	6/1994	Bonutti	5,507,754	A	4/1996	Green
5,324,308	A	6/1994	Pierce	5,522,844	A	6/1996	Johnson
5,328,480	A	7/1994	Melker	5,522,845	A	6/1996	Wenstrom
5,329,846	A	7/1994	Bonutti	5,522,846	A	6/1996	Bonutti
5,329,924	A	7/1994	Bonutti	5,527,341	A	6/1996	Gogolewski
5,330,468	A *	7/1994	Burkhart A61B 17/1796	5,527,342	A	6/1996	Pietrzak
			606/96	5,527,343	A	6/1996	Bonutti
5,330,476	A	7/1994	Hiot	5,529,075	A	6/1996	Clark
5,330,486	A	7/1994	Wilk	5,531,759	A	7/1996	Kensey
5,336,231	A	8/1994	Adair	5,534,012	A	7/1996	Bonutti
5,336,240	A	8/1994	Metzler	5,534,028	A	7/1996	Bao
5,339,799	A	8/1994	Kami	5,540,718	A	7/1996	Bartlett
5,349,956	A	9/1994	Bonutti	5,542,423	A	8/1996	Bonutti
5,352,229	A	10/1994	Goble	5,545,178	A	8/1996	Kensey
5,354,298	A *	10/1994	Lee A61B 17/0401	5,545,180	A	8/1996	Le
			606/139	5,545,206	A	8/1996	Carson
5,354,302	A	10/1994	Ko	5,549,630	A	8/1996	Bonutti
5,366,480	A	11/1994	Corriveau	5,549,631	A	8/1996	Bonutti
5,370,646	A	12/1994	Reese	5,556,402	A	9/1996	Xu
5,370,660	A	12/1994	Weinstein	5,569,252	A	10/1996	Justin
5,372,146	A	12/1994	Branch	5,569,305	A	10/1996	Bonutti
5,374,235	A	12/1994	Ahrens	5,569,306	A	10/1996	Thal
5,376,126	A	12/1994	Lin	5,573,517	A	11/1996	Bonutti
5,382,254	A	1/1995	McGarry	5,573,538	A	11/1996	Laboureau
5,383,883	A	1/1995	Wilk	5,573,542	A	11/1996	Stevens
5,383,905	A	1/1995	Golds	5,575,801	A	11/1996	Habermeyer
5,391,173	A	2/1995	Wilk	5,578,046	A	11/1996	Liu
5,395,308	A	3/1995	Fox	5,580,344	A	12/1996	Hasson
5,397,311	A	3/1995	Walker	5,584,835	A	12/1996	Greenfield
5,400,805	A	3/1995	Warren	5,584,839	A	12/1996	Gieringer
5,403,312	A	4/1995	Yates	5,584,860	A	12/1996	Goble
5,403,348	A *	4/1995	Bonutti A61B 17/0401	5,584,862	A	12/1996	Bonutti
			606/139	5,589,176	A *	12/1996	Seare, Jr. A61L 27/08
5,405,359	A	4/1995	Pierce				424/400
5,411,523	A	5/1995	Goble	5,591,206	A	1/1997	Moufarrege
5,413,585	A	5/1995	Pagedas	5,593,422	A	1/1997	Muijs Van De Moer
5,417,691	A	5/1995	Hayhurst	5,593,425	A	1/1997	Bonutti
5,417,699	A *	5/1995	Klein A61B 17/0057	5,593,625	A	1/1997	Riebel
			112/169	5,601,557	A	2/1997	Hayhurst
5,417,701	A	5/1995	Holmes	5,601,558	A	2/1997	Torrie
5,417,712	A	5/1995	Whittaker	5,601,595	A	2/1997	Smith
5,423,796	A	6/1995	Shikhman	5,607,427	A	3/1997	Tschakaloff
5,431,670	A	7/1995	Holmes	5,609,595	A	3/1997	Pennig
5,439,470	A	8/1995	Li	5,618,314	A	4/1997	Harwin
5,441,538	A	8/1995	Bonutti	5,620,461	A	4/1997	Muijs Van De Moer
5,443,512	A	8/1995	Parr	5,626,612	A	5/1997	Bartlett
5,447,503	A	9/1995	Miller	5,626,614	A	5/1997	Hart
5,449,372	A	9/1995	Schmaltz	5,626,718	A	5/1997	Philippe
5,449,382	A	9/1995	Dayton	5,628,751	A	5/1997	Sander
5,451,235	A	9/1995	Lock	5,630,824	A	5/1997	Hart
5,453,090	A	9/1995	Martinez	5,634,926	A	6/1997	Jobe
5,456,722	A	10/1995	McLeod	5,643,274	A	7/1997	Sander
5,458,653	A	10/1995	Davidson	5,643,293	A	7/1997	Kogasaka
5,462,561	A	10/1995	Voda	5,643,295	A	7/1997	Yoon
5,464,424	A	11/1995	O'Donnell	5,643,321	A	7/1997	McDevitt
				5,645,553	A	7/1997	Kolesa
				5,645,597	A	7/1997	Krapiva
				5,645,599	A	7/1997	Samani
				5,649,955	A	7/1997	Hashimoto
				5,649,963	A	7/1997	McDevitt

(56)

References Cited

U.S. PATENT DOCUMENTS

5,651,377 A	7/1997	O'Donnell	5,891,166 A	4/1999	Schervinsky
5,658,313 A	8/1997	Thal	5,891,168 A	4/1999	Thal
5,660,225 A	8/1997	Saffran	5,893,880 A	4/1999	Egan
5,662,658 A	9/1997	Wenstrom	5,897,574 A	4/1999	Bonutti
5,665,089 A	9/1997	Dall	5,899,911 A	5/1999	Carter
5,665,109 A	9/1997	Yoon	5,899,921 A	5/1999	Caspari
5,667,513 A	9/1997	Torrie	5,906,579 A	5/1999	Vander Salm
5,669,917 A	9/1997	Sauer	5,906,625 A	5/1999	Bito
5,674,240 A	10/1997	Bonutti	5,908,429 A	6/1999	Yoon
5,681,310 A	10/1997	Yuan	5,911,721 A	6/1999	Nicholson
5,681,333 A	10/1997	Burkhart	5,918,604 A	7/1999	Whelan
5,681,351 A	10/1997	Jamiolkowski	5,919,193 A	7/1999	Slavitt
5,681,352 A	10/1997	Clancy	5,919,194 A	7/1999	Anderson
5,685,820 A	11/1997	Riek	5,919,208 A	7/1999	Valenti
5,688,283 A	11/1997	Knapp	5,919,215 A	7/1999	Wiklund
5,690,654 A	11/1997	Ovil	5,921,967 A	7/1999	Sadowski et al.
5,690,655 A	11/1997	Hart	5,921,986 A	7/1999	Bonutti
5,690,676 A	11/1997	DiPoto	5,925,064 A	7/1999	Meyers
5,693,055 A	12/1997	Zahiri	5,928,244 A	7/1999	Tovey
5,697,950 A	12/1997	Fucci	5,928,267 A	7/1999	Bonutti
5,702,397 A	12/1997	Goble	5,931,838 A	8/1999	Vito
5,702,462 A	12/1997	Oberlander	5,931,869 A	8/1999	Boucher
5,707,395 A	1/1998	Li	5,940,942 A	8/1999	Fong
5,713,903 A	2/1998	Sander	5,941,900 A	8/1999	Bonutti
5,713,921 A	2/1998	Bonutti	5,941,901 A	8/1999	Egan
5,718,717 A	2/1998	Bonutti	5,944,750 A	8/1999	Tanner
5,720,747 A	2/1998	Burke	5,945,002 A	8/1999	Leukes
5,720,753 A	2/1998	Sander	5,947,982 A	9/1999	Duran
5,725,541 A	3/1998	Anspach	5,948,000 A	9/1999	Larsen
5,725,556 A	3/1998	Moser	5,948,001 A	9/1999	Larsen
5,725,582 A	3/1998	Bevan	5,948,002 A	9/1999	Bonutti
5,730,747 A	3/1998	Ek	5,951,590 A	9/1999	Goldfarb
5,733,306 A	3/1998	Bonutti	5,954,057 A *	9/1999	Li A61B 17/062 128/898
5,735,875 A	4/1998	Bonutti	5,957,953 A	9/1999	DiPoto
5,735,877 A	4/1998	Pagedas	5,961,499 A	10/1999	Bonutti
5,735,899 A	4/1998	Schwartz	5,961,521 A	10/1999	Roger
5,741,282 A	4/1998	Anspach	5,961,554 A	10/1999	Janson
5,752,952 A	5/1998	Adamson	5,964,765 A	10/1999	Fenton
5,752,974 A	5/1998	Rhee	5,964,769 A	10/1999	Wagner
5,755,809 A	5/1998	Cohen	5,968,046 A	10/1999	Castleman
5,762,458 A	6/1998	Wang	5,968,047 A	10/1999	Reed
5,766,221 A	6/1998	Benderev	5,980,520 A	11/1999	Vancaillie
5,769,894 A	6/1998	Ferragamo	5,980,559 A	11/1999	Bonutti
5,772,672 A	6/1998	Toy	5,984,929 A	11/1999	Bashiri
5,776,151 A	7/1998	Chan	5,989,282 A	11/1999	Bonutti
5,779,706 A	7/1998	Tschakaloff	5,993,458 A	11/1999	Vaitekunas
5,782,862 A	7/1998	Bonutti	5,993,477 A	11/1999	Vaitekunas
5,785,713 A	7/1998	Jobe	6,007,567 A	12/1999	Bonutti
5,792,096 A	8/1998	Rentmeester	6,007,580 A	12/1999	Lehto
5,797,931 A	8/1998	Bito	6,010,525 A	1/2000	Bonutti
5,800,537 A	9/1998	Bell	6,010,526 A	1/2000	Sandstrom
5,807,403 A	9/1998	Beyar	6,017,321 A	1/2000	Boone
5,810,849 A	9/1998	Kontos	6,033,429 A	3/2000	Magovern
5,810,853 A	9/1998	Yoon	6,033,430 A	3/2000	Bonutti
5,810,884 A	9/1998	Kim	6,045,551 A	4/2000	Bonutti
5,814,072 A	9/1998	Bonutti	6,050,998 A	4/2000	Fletcher
5,814,073 A	9/1998	Bonutti	6,056,751 A	5/2000	Fenton
5,817,107 A	10/1998	Schaller	6,056,772 A	5/2000	Bonutti
5,823,994 A	10/1998	Sharkey	6,056,773 A	5/2000	Bonutti
5,824,009 A	10/1998	Fukuda	6,059,797 A	5/2000	Mears
5,830,125 A	11/1998	Scribner	6,059,817 A	5/2000	Bonutti
5,836,897 A	11/1998	Sakurai	6,059,827 A	5/2000	Fenton
5,839,899 A	11/1998	Robinson	6,063,095 A	5/2000	Wang
5,843,084 A	12/1998	Hart	6,066,151 A	5/2000	Miyawaki
5,843,178 A	12/1998	Vanney	6,066,160 A	5/2000	Colvin
5,845,645 A	12/1998	Bonutti	6,066,166 A	5/2000	Bischoff
5,851,185 A	12/1998	Berns	6,068,637 A	5/2000	Popov
5,865,834 A	2/1999	McGuire	6,068,648 A	5/2000	Cole
5,866,634 A	2/1999	Tokushige	6,077,277 A	6/2000	Mollenauer
5,868,749 A	2/1999	Reed	6,077,292 A	6/2000	Bonutti
5,874,235 A	2/1999	Chan	6,080,161 A	6/2000	Eaves
5,879,372 A	3/1999	Bartlett	6,083,522 A	7/2000	Chu
5,891,160 A *	4/1999	Williamson, IV	6,086,593 A	7/2000	Bonutti
		A61B 17/0469	6,086,608 A	7/2000	Ek
		112/169	6,090,072 A	7/2000	Kratoska
			6,099,531 A	8/2000	Bonutti
			6,099,537 A	8/2000	Sugai
			6,099,550 A	8/2000	Yoon

(56)

References Cited

U.S. PATENT DOCUMENTS

6,099,552	A	8/2000	Adams	6,551,343	B1	4/2003	Törmälä et al.
6,102,850	A	8/2000	Wang	6,554,852	B1	4/2003	Oberlander
6,106,545	A	8/2000	Egan	6,557,426	B2	5/2003	Reinemann
6,117,160	A	9/2000	Bonutti	6,558,390	B2	5/2003	Cragg
6,120,511	A	9/2000	Chan	6,568,313	B2	5/2003	Fukui
6,120,536	A	9/2000	Ding	6,569,187	B1	5/2003	Bonutti
6,125,574	A	10/2000	Ganaja	6,572,635	B1	6/2003	Bonutti
6,126,677	A	10/2000	Ganaja	D477,776	S	7/2003	Pontaoe
6,139,320	A	10/2000	Hahn	6,585,750	B2	7/2003	Bonutti
RE36,974	E	11/2000	Bonutti	6,585,764	B2	7/2003	Wright
6,149,669	A	11/2000	Li	6,592,609	B1	7/2003	Bonutti
6,152,949	A	11/2000	Bonutti	6,594,517	B1	7/2003	Nevo
6,155,756	A	12/2000	Mericle	6,602,293	B1	8/2003	Biermann
6,159,224	A	12/2000	Yoon	6,605,090	B1	8/2003	Trieu
6,159,234	A	12/2000	Bonutti	6,610,080	B2	8/2003	Morgan
6,171,299	B1	1/2001	Bonutti	6,618,910	B1	9/2003	Pontaoe
6,171,307	B1	1/2001	Orlich	6,623,486	B1	9/2003	Weaver
6,174,324	B1	1/2001	Egan	6,623,487	B1	9/2003	Goshert
6,179,840	B1	1/2001	Bowman	6,626,944	B1	9/2003	Taylor
6,179,850	B1	1/2001	Goradia	6,632,245	B2	10/2003	Kim
6,187,008	B1	2/2001	Hamman	6,635,073	B2	10/2003	Bonutti
6,190,400	B1	2/2001	Van De Moer	6,638,279	B2	10/2003	Bonutti
6,190,401	B1	2/2001	Green	6,641,592	B1	11/2003	Sauer
6,200,322	B1	3/2001	Branch	6,645,227	B2	11/2003	Fallin
6,217,591	B1	4/2001	Egan	6,666,877	B2	12/2003	Morgan
6,224,593	B1	5/2001	Ryan	6,669,705	B2	12/2003	Westhaver
6,224,630	B1	5/2001	Bao	6,679,888	B2	1/2004	Green
6,228,086	B1	5/2001	Wahl	6,685,750	B1	2/2004	Plos
6,231,592	B1	5/2001	Bonutti	6,699,240	B2	3/2004	Francischelli
6,238,395	B1	5/2001	Bonutti	6,702,821	B2	3/2004	Bonutti
6,238,396	B1	5/2001	Lombardo	6,705,179	B1	3/2004	Mohtasham
6,245,107	B1 *	6/2001	Ferree	6,709,457	B1	3/2004	Otte
			A61B 17/025	6,719,765	B2	4/2004	Bonutti
			606/279	6,719,795	B1	4/2004	Cornwall
6,258,091	B1	7/2001	Sevrain	6,719,797	B1	4/2004	Ferree
6,264,675	B1	7/2001	Brotz	6,722,552	B2	4/2004	Fenton
6,267,761	B1	7/2001	Ryan	6,733,531	B1	5/2004	Trieu
6,273,717	B1	8/2001	Hahn	6,764,514	B1	7/2004	Li
6,280,474	B1	8/2001	Cassidy	6,770,078	B2	8/2004	Bonutti
6,286,746	B1	9/2001	Egan	6,780,198	B1	8/2004	Gregoire
6,287,325	B1	9/2001	Bonutti	6,786,989	B2	9/2004	Torriani
6,293,961	B2	9/2001	Schwartz	6,796,003	B1	9/2004	Marvel
6,306,159	B1	10/2001	Schwartz	6,818,010	B2	11/2004	Eichhorn
6,309,405	B1	10/2001	Bonutti	6,823,871	B2	11/2004	Schmieding
6,312,448	B1	11/2001	Bonutti	6,830,589	B2	12/2004	Erickson
6,338,730	B1	1/2002	Bonutti	6,860,885	B2	3/2005	Bonutti
6,340,365	B2	1/2002	Dittrich	6,878,167	B2	4/2005	Ferree
6,348,056	B1	2/2002	Bates	6,890,334	B2	5/2005	Brace
6,358,271	B1	3/2002	Egan	6,893,434	B2	5/2005	Fenton
6,364,897	B1	4/2002	Bonutti	6,899,722	B2	5/2005	Bonutti
6,368,325	B1	4/2002	McKinley	6,913,666	B1	7/2005	Aeschlimann
6,368,343	B1	4/2002	Bonutti	6,916,321	B2	7/2005	TenHuisen
6,371,957	B1	4/2002	Amrein	6,921,264	B2	7/2005	Mayer
6,409,742	B1	6/2002	Fulton	6,923,824	B2	8/2005	Morgan
6,409,743	B1	6/2002	Fenton	6,932,835	B2	8/2005	Bonutti
6,419,704	B1	7/2002	Ferree	6,942,684	B2	9/2005	Bonutti
6,423,088	B1	7/2002	Fenton	6,944,111	B2	9/2005	Nakamura
6,425,919	B1	7/2002	Lam Brecht	6,955,540	B2	10/2005	Mayer
6,428,562	B2	8/2002	Bonutti	6,955,683	B2	10/2005	Bonutti
6,432,115	B1	8/2002	Mollenauer	6,958,077	B2	10/2005	Suddaby
6,447,516	B1	9/2002	Bonutti	6,981,983	B1	1/2006	Rosenblatt
6,450,985	B1	9/2002	Schoelling	6,997,940	B2	2/2006	Bonutti
6,461,360	B1	10/2002	Adam	7,001,411	B1	2/2006	Dean
6,468,293	B2	10/2002	Bonutti	7,004,959	B2	2/2006	Bonutti
6,475,230	B1	11/2002	Bonutti	7,008,226	B2	3/2006	Mayer
6,488,196	B1	12/2002	Fenton	7,018,380	B2	3/2006	Cole
6,500,195	B2	12/2002	Bonutti	7,033,379	B2	4/2006	Peterson
6,503,259	B2	1/2003	Huxel	7,048,755	B2	5/2006	Bonutti
6,511,498	B1	1/2003	Furnex	7,052,516	B2 *	5/2006	Cauthen, III
6,527,774	B2	3/2003	Lieberman				A61F 2/441
6,530,933	B1	3/2003	Yeung	7,066,960	B1	6/2006	Dickman
6,535,764	B2	3/2003	Imran	7,087,073	B2	8/2006	Bonutti
6,544,267	B1	4/2003	Cole	7,090,111	B2	8/2006	Egan
6,545,390	B1	4/2003	Hahn	7,094,251	B2	8/2006	Bonutti
6,547,792	B1	4/2003	Tsuji	7,104,996	B2	9/2006	Bonutti
6,551,304	B1	4/2003	Whalen	7,128,763	B1	10/2006	Blatt
				7,147,652	B2	12/2006	Bonutti
				7,160,405	B2	1/2007	Aeschlimann
				7,179,259	B1	2/2007	Gibbs

US 10,376,259 B2

Page 7

(56)

References Cited

U.S. PATENT DOCUMENTS

7,192,448	B2	3/2007	Ferree		2003/0195514	A1	10/2003	Trieu
7,217,279	B2	5/2007	Reese		2003/0195530	A1	10/2003	Thill
7,217,290	B2	5/2007	Bonutti		2003/0195565	A1	10/2003	Bonutti
7,229,453	B2 *	6/2007	Anderson A61B 17/0401	2003/0204204	A1	10/2003	Bonutti
				606/151	2003/0208203	A1	11/2003	Urn
7,241,297	B2	7/2007	Shaolian		2003/0216742	A1	11/2003	Wetzler
7,250,051	B2	7/2007	Francischelli		2003/0225438	A1	12/2003	Bonutti
7,252,685	B2	8/2007	Bindseil		2003/0229361	A1	12/2003	Jackson
7,273,497	B2	9/2007	Ferree		2004/0010287	A1	1/2004	Bonutti
7,285,086	B2 *	10/2007	Smith A61B 17/06066	2004/0024459	A1	2/2004	Ferree
				600/30	2004/0030341	A1	2/2004	Aeschlimann
7,326,200	B2	2/2008	Trieu		2004/0034357	A1	2/2004	Beane
7,329,263	B2	2/2008	Bonutti		2004/0039392	A1	2/2004	Trieu
7,335,205	B2	2/2008	Aeschlimann		2004/0049207	A1	3/2004	Goldfarb
7,429,266	B2	9/2008	Bonutti		2004/0097939	A1	5/2004	Bonutti
7,445,634	B2	11/2008	Trieu		2004/0098050	A1	5/2004	Foerster
7,481,825	B2	1/2009	Bonutti		2004/0102788	A1	5/2004	Huebner
7,481,831	B2	1/2009	Bonutti		2004/0116963	A1	6/2004	Lattouf
7,510,895	B2	3/2009	Rateman		2004/0138703	A1	7/2004	Alleyne
7,597,705	B2	10/2009	Forsberg		2004/0138705	A1	7/2004	Heino
7,854,750	B2	12/2010	Bonutti		2004/0143334	A1	7/2004	Ferree
7,879,072	B2	2/2011	Bonutti		2004/0167548	A1	8/2004	Bonutti
7,891,691	B2	2/2011	Bearey		2004/0172063	A1	9/2004	Li
7,918,879	B2 *	4/2011	Yeung A61B 17/0401	2004/0186471	A1	9/2004	Trieu
				606/139	2004/0220616	A1	11/2004	Bonutti
7,967,820	B2	6/2011	Bonutti		2004/0225325	A1	11/2004	Bonutti
8,128,669	B2	3/2012	Bonutti		2004/0230223	A1	11/2004	Bonutti
8,140,982	B2	3/2012	Hamilton		2004/0236374	A1	11/2004	Bonutti
8,147,514	B2	4/2012	Bonutti		2005/0033362	A1	2/2005	Grafton
8,162,977	B2	4/2012	Bonutti		2005/0033366	A1	2/2005	Cole
8,487,844	B2	7/2013	Koyama		2005/0038514	A1	2/2005	Helm
8,771,314	B2	7/2014	Crombie		2005/0043733	A1	2/2005	Eisermann
8,845,699	B2	9/2014	Bonutti		2005/0043796	A1	2/2005	Grant
9,579,129	B2	2/2017	Bonutti		2005/0070765	A1	3/2005	Abdelgany
9,814,453	B2	11/2017	Bonutti		2005/0071012	A1	3/2005	Serhan
9,867,706	B2	1/2018	Bonutti		2005/0075644	A1	4/2005	DiPoto
9,999,499	B2	6/2018	Aguilera et al.		2005/0090827	A1	4/2005	Gedebou
2001/0002439	A1	5/2001	Bonutti		2005/0096699	A1	5/2005	Wixey
2001/0002440	A1	5/2001	Bonutti		2005/0113928	A1	5/2005	Cragg
2001/0008971	A1	7/2001	Schwartz		2005/0125072	A1	6/2005	Kolb
2001/0009250	A1	7/2001	Herman		2005/0126680	A1	6/2005	Aeschlimann
2001/0041916	A1	11/2001	Bonutti		2005/0143826	A1	6/2005	Zucherman
2001/0056287	A1	12/2001	Bonutti		2005/0149024	A1	7/2005	Ferrante
2002/0016593	A1	2/2002	Hearn		2005/0149029	A1	7/2005	Bonutti
2002/0016633	A1	2/2002	Lin		2005/0203521	A1	9/2005	Bonutti
2002/0019649	A1	2/2002	Sikora		2005/0216059	A1	9/2005	Bonutti
2002/0026244	A1	2/2002	Trieu		2005/0216087	A1	9/2005	Zucherman
2002/0029067	A1	3/2002	Bonutti		2005/0222620	A1	10/2005	Bonutti
2002/0029083	A1	3/2002	Zucherman		2005/0234460	A1	10/2005	Miller
2002/0029084	A1	3/2002	Paul		2005/0240190	A1	10/2005	Gall
2002/0045902	A1	4/2002	Bonutti		2005/0240227	A1	10/2005	Bonutti
2002/0058966	A1	5/2002	Tormala		2005/0246021	A1	11/2005	Ringeisen
2002/0062153	A1	5/2002	Paul		2005/0256582	A1	11/2005	Ferree
2002/0087189	A1	7/2002	Bonutti		2005/0261684	A1	11/2005	Shaolian
2002/0103495	A1	8/2002	Cole		2005/0267481	A1	12/2005	Carl
2002/0120269	A1	8/2002	Lange		2005/0267534	A1	12/2005	Bonutti
2002/0123750	A1	9/2002	Eisermann		2005/0283246	A1	12/2005	Cauthen
2002/0160175	A1	10/2002	Pirhonen		2006/0009846	A1	1/2006	Trieu
2002/0161439	A1	10/2002	Strobel		2006/0009855	A1	1/2006	Goble
2002/0183762	A1	12/2002	Anderson		2006/0015101	A1	1/2006	Warburton
2002/0188301	A1	12/2002	Dallara		2006/0015108	A1	1/2006	Bonutti
2003/0039196	A1	2/2003	Nakamura		2006/0024357	A1	2/2006	Carpenter
2003/0040758	A1	2/2003	Wang		2006/0026244	A1	2/2006	Watson
2003/0065361	A1	4/2003	Dreyfuss		2006/0064095	A1	3/2006	Senn
2003/0083667	A1	5/2003	Ralph		2006/0089646	A1	4/2006	Bonutti
2003/0097148	A1	5/2003	Valimaa		2006/0122600	A1	6/2006	Cole
2003/0105474	A1	6/2003	Bonutti		2006/0122704	A1	6/2006	Vresilovic
2003/0118518	A1	6/2003	Hahn		2006/0142799	A1	6/2006	Bonutti
2003/0125749	A1	7/2003	Yuan		2006/0167495	A1	7/2006	Bonutti
2003/0158555	A1	8/2003	Sanders		2006/0189982	A1	8/2006	Lange
2003/0158582	A1	8/2003	Bonutti		2006/0200199	A1	9/2006	Bonutti
2003/0167071	A1 *	9/2003	Martin A61B 17/0469	2006/0212073	A1	9/2006	Bonutti
				606/232	2006/0217765	A1	9/2006	Bonutti
2003/0167072	A1	9/2003	Oberlander		2006/0229623	A1	10/2006	Bonutti
2003/0181800	A1	9/2003	Bonutti		2006/0235413	A1	10/2006	Denham
					2006/0235470	A1	10/2006	Bonutti
					2006/0241695	A1	10/2006	Bonutti
					2006/0264953	A1	11/2006	Falahee
					2006/0265009	A1	11/2006	Bonutti

US 10,376,259 B2

Page 8

(56)

References Cited

U.S. PATENT DOCUMENTS

2006/0265011	A1	11/2006	Bonutti
2007/0032825	A1	2/2007	Bonutti
2007/0088362	A1	4/2007	Bonutti
2007/0118129	A1	5/2007	Fraser
2007/0198555	A1	8/2007	Friedman
2007/0233092	A1	10/2007	Falahee
2007/0265561	A1	11/2007	Yeung
2007/0270833	A1	11/2007	Bonutti
2008/0021474	A1	1/2008	Bonutti
2008/0039845	A1	2/2008	Bonutti
2008/0039873	A1	2/2008	Bonutti
2008/0046090	A1	2/2008	Paul
2008/0097448	A1	4/2008	Binder
2008/0108897	A1	5/2008	Bonutti
2008/0108916	A1	5/2008	Bonutti
2008/0114399	A1	5/2008	Bonutti
2008/0132950	A1	6/2008	Lange
2008/0140116	A1	6/2008	Bonutti
2008/0140117	A1	6/2008	Bonutti
2008/0195145	A1	8/2008	Bonutti
2008/0269753	A1	10/2008	Cannestra
2008/0269808	A1	10/2008	Gall
2009/0024161	A1	1/2009	Bonutti
2009/0093684	A1	4/2009	Schorer
2009/0138014	A1	5/2009	Bonutti
2009/0194969	A1	8/2009	Bearey
2010/0211120	A1	8/2010	Bonutti
2011/0060375	A1	3/2011	Bonutti
2011/0295253	A1	12/2011	Bonutti
2012/0165841	A1	6/2012	Bonutti
2012/0191140	A1	7/2012	Bonutti
2012/0215233	A1	8/2012	Bonutti

FOREIGN PATENT DOCUMENTS

CA	2698057	3/2009
DE	1903316	7/1970

DE	1903016	8/1970
DE	3517204	11/1986
DE	3722538	1/1989
DE	199002844	1/1991
EP	773004	5/1997
EP	784454	7/1997
EP	1614525	1/2006
EP	1988837	11/2008
EP	2134294	12/2009
FR	2696338	4/1994
FR	2717368	9/1995
FR	2728779	7/1996
FR	2736257	1/1997
FR	2750031	12/1997
FR	2771621	6/1999
FR	2785171	5/2000
GB	2093701	9/1982
GB	8140982	6/1996
GB	2306110	4/1997
WO	WO1991012779	9/1991
WO	WO1993023094	11/1993
WO	WO1994008642	4/1994
WO	WO1995016398	6/1995
WO	WO1995031941	11/1995
WO	WO1996014802	5/1996
WO	WO1997012779	4/1997
WO	WO1997049347	12/1997
WO	WO1998011838	3/1998
WO	WO1998026720	6/1998
WO	WO2002053011	7/2002
WO	WO2007092869	8/2007
WO	WO2008116203	9/2008
WO	WO2009029908	3/2009
WO	WO2009124215	10/2009
WO	WO2010099222	9/2010

* cited by examiner




FIG. 1








FIG. 2








FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 12




FIG. 11




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24







FIG. 25






FIG. 29

DEFORMABLE FASTENER SYSTEM**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. application Ser. No. 13/871,892 filed Apr. 26, 2013, entitled "DEFORMABLE FASTENER SYSTEM", which is a continuation of U.S. application Ser. No. 11/202,294 filed Oct. 5, 2005, entitled "APPARATUS AND METHODS FOR SURGERY", which is incorporated herein by reference in its entirety

FIELD

The invention relates to apparatus and methods for surgery. More specifically, the invention relates to the guidance and positioning of tissue, an implant, or other surgical devices within the body.

BACKGROUND

In the medical arts, physicians use various methods and devices to attach soft tissue to other soft tissue, soft tissue to hard tissue, and hard tissue to other hard tissue. These same or similar techniques and devices are also used to position or fix an implant within the body. Such implants may include bone plates, fasteners, stents, filters, drug eluting implants, tissue alignment members, organ transplants, tissue scaffolding, tissue grafts, intervertebral disc replacement components, nucleus pulposus replacement component, and other joint replacements components, prostheses, robotic components, nanotechnology devices, sensors, emitters, radiofrequency emitting diodes, computer chips, RFID (radiofrequency identification) tags, adhesives, and sealants.

Applying pressure or compression to tissue and/or an implant helps during the healing process. Incised or torn soft tissue, for example, may be approximated with bandages, sutures, or staples. Proper and more rapid healing of broken or fractured bones likewise may be facilitated by applying constant pressure to the bone. For instance, physicians may insert pins, screws, or bolts in the area of the fracture in order to apply compression and stabilization to the fracture.

However, inserting screws through or around fractures can be complex and time-consuming. For example, the process of inserting a screw typically involves multiple steps conducted from multiple incisions or openings that provide access to the treated bone or tissue, including the steps of drilling holes, measuring the relevant distances to determine the appropriate screw selection, tapping the hole to establish threads, and screwing the screw into the hole.

In addition to the length and complexity of the process, bone screws also may lose their grip and strip out of the bone. Also, currently available lag screws typically provide only one side of cortex fixation and are generally not suited for percutaneous surgery. Moreover, when placing the screws in the bone, the physician may not accurately set the screw into the distal hole or may miss the distal hole completely, thereby resulting in the screw stripping the threads or breaking the bone.

Many devices and instruments have been disclosed to fasten soft and hard tissue for enhanced healing or tissue reconstruction. Examples of such devices include bone plates, bone wraps, external bone supports, and the like.

For example, U.S. Pat. No. 4,257,411 to Cho discloses a surgical drill guide tool adapted to be temporarily mounted about a distal portion of the femur for drilling a bony tunnel

through a portion of the femur. The surgical tool allows for very precise location of the drill exit within the intercondylar notch, which is often critical in proper reconstruction of the anterior cruciate ligament of the knee. The surgical tool drill guide is characterized by having a first and second upright, with first and second drill sheaths located at their respective distal ends wherein transverse mounting means are provided to allow the surgeon to position the first and second drill sheaths tightly against opposite surfaces of the femur to provide a continuing and exact alignment for the drilling of the bony tunnel. The drill sheath at the distal end of the second upright is configured to fit inside the intercondylar notch, and allow exact placement of the exit of a bony tunnel which is drilled extra-articularly through the skin, and through the lateral femoral condyle.

U.S. Pat. No. 4,922,897 to Sapega et al. discloses a method and apparatus for the permanent surgical reconstruction of the anterior cruciate ligament in the human knee, which will stabilize the tibia and femur relative to each other and restore a full range of motion to the knee, by precisely locating the ends and angular relationship of a replacement ligament within the knee joint, at bone attachment sites such that the degree of shortening and lengthening experienced by the replacement ligament over the range of joint motion is either as close to zero (isometric) as possible, or closely matches that of the natural uninjured ligament (physometric), whichever the surgeon feels is most desirable.

U.S. Pat. No. 5,573,538 to Laboureaux discloses ancillary instruments for the reconstruction of a posterior cruciate knee ligament by drilling one or two tibial canals using a surgical operation performed from the front. The instrument set includes a system for protecting the posterior surface of the upper tibia end and an aiming device for guiding at least one drill. The protection system includes at least one bent tube removably coupled by an extension portion to a locking handle for securing the tube through the intercondylar fossa of the femur on the posterior surface of the upper end of the tibia, so that the distal end of the bent tube serves as the stop to the drill guided by the aiming device and emerging from the tibial bone canal, and the bent tube can form, together with a rectilinear wire feed-through tube disposed in the place of the drill, a continuous canal for guiding a metallic loop used to draw the prosthetic posterior cruciate knee ligament from the anterior surface of the tibia to the femur insertion point.

U.S. Patent Publication No. 2003/0216742 to Wetzler et al. discloses a surgical drill guide generally including a handle connected to an arm with an end that contacts bone. The handle has a plurality of non-parallel channels therein for receiving a sleeve at different angles. Once properly positioned, the sleeve can be used to guide a K-wire into the bone, which can then be used as a guide for drilling a tunnel. The various angles allow the surgeon to achieve a range of tunnel lengths. In some embodiments, the guide has a locking mechanism for locking the sleeve in the channels.

Accordingly, a need exists for a method and device which can provide guided positioning and flexible or rigid fixation of tissue and/or an implant within the body while accessing the procedure site from a small skin portal.

SUMMARY

The present invention provides an instrument and method for guiding and positioning various implants within the body. The instrument may provide for the placement of a biocompatible implant within tissue and/or may provide for dynamic and rigid fixation of tissue. An implant guidance

3

and positioning device includes a body member connected with a hook. The hook may have a lumen extending there-through. The device also includes a guide channel disposed in the body member. The longitudinal axis of the guide channel may be generally aligned with or slightly offset from a distal end of the hook. The device may further include a pushrod for positioning a fastener and suture in the lumen of the hook. Furthermore, the device may include an elongated claw dimensioned for insertion through the guide channel. The claw may include means for grabbing the suture.

In another embodiment, the positioning device includes a body member, an elongated member connected with the body member, a socket member connected to the distal end of the elongated member, and a guide slot disposed in the body member. The longitudinal axis of the guide slot is generally aligned with or slightly offset with the socket member. The socket member may be dimensioned and configured for holding a fastener. The device may also include a fastening member dimensioned for insertion in the guide slot. The fastening member may include means for attaching the fastening member to the fastener, such as threads, ribs, magnets, adhesives, or expandable material.

In a related aspect of the present invention, the distal portion of the hook or elongated member is curved to be positionable at least partially on the distal or backside of the bone or tissue, while the proximal portion of the hook or elongated member may be generally parallel with the guide channel or slot. The hook or elongated member may be removably connected with the body member with means for holding and releasing the hook or elongated member.

The positioning device may further include a drill system having a drill bit dimensioned for insertion through the guide channel or slot. The drill system may create a linear or non-linear passage in tissue. The drill system may be a cannulated drill system. The positioning device may also include means for clamping the device to tissue. Such means may include a threaded tube adjustably attached to the body member, a tube and a finger grip attached to the body member, or one or more pins placed between the positioning device and tissue. Furthermore, the device may include a tensioning mechanism for tensioning the suture or fastening member.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present invention, and the attendant advantages and features thereof, will be more readily understood by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 shows an exemplary embodiment of the guidance and positioning device of the present invention;

FIG. 2 illustrates a cannulated drill system inserted in the device;

FIG. 3 shows a pushrod configured for inserting a fastener and suture into a hook of the positioning device;

FIG. 4 illustrates a fastener and suture positioned in the hook;

FIG. 5 shows a suture claw positioned in the guide channel of the device;

FIG. 6 illustrates the suture claw withdrawn from the guide channel with the suture disposed in the guide channel;

FIG. 7 shows the suture connected with the fastener on the distal side of the bone and the suture extending from the drill system;

FIG. 8 illustrates a fractured bone with the suture extending therethrough;

4

FIG. 9 shows a fastener positioned on the proximal side of the bone and secured to the suture;

FIG. 10 illustrates another embodiment of the implant guidance and positioning device;

FIG. 11 shows a cannulated drill system disposed in a guide slot of the device;

FIG. 12 illustrates a fastener disposed in a socket on the distal end of a hookshaped member of the device;

FIG. 13 shows a fastening member positioned in the guide slot of the device;

FIG. 14 illustrates a threaded distal portion of the fastening member disposed in a threaded hole of the fastener;

FIG. 15 shows a fractured bone with the fastening member extending therethrough;

FIG. 16 illustrates a fastener positioned on the proximal side of the bone and secured to the fastening member;

FIG. 17 shows one embodiment of a clamping mechanism of the device;

FIG. 18 illustrates another embodiment of the clamping mechanism of the device;

FIG. 19 shows an embodiment of a tensioning mechanism of the device;

FIG. 20 illustrates a drill/sleeve combination in accordance with the present invention;

FIG. 21 is a cross sectional view of FIG. 20;

FIG. 22 shows the drill/sleeve combination in use to repair a fractured bone;

FIG. 23 illustrates the sleeve positioned across the fracture of the bone;

FIG. 24 shows another exemplary embodiment of the drill/sleeve combination;

FIG. 25 is a cross sectional view of FIG. 24;

FIG. 26 illustrates the drill/sleeve combination functioning as a fastener;

FIG. 27 shows an exemplary distal portion of the fastener;

FIG. 28 illustrates another exemplary distal portion of the fastener; and

FIG. 29 shows another embodiment of the guidance and positioning device having multiple hooks and guide channels.

DETAILED DESCRIPTION

The present invention provides an instrument and method for guiding and positioning tissue and/or an implant within the body. The instrument may provide for the placement of a biocompatible implant within tissue or may provide for dynamic and rigid fixation of tissue. The device can access and treat a fractured, incised or torn tissue, or the like, from one access area (i.e., from only one opening to the tissue to be fastened) instead of requiring two or more openings. That is, the device is a linear system that can be used with a single, small incision or portal in the skin or other soft tissue to gain access to the tissue, for example a fractured bone.

The guidance and positioning device may be an all-in-one system for creating a passage in tissue, positioning fasteners or other implants, and tensioning an elongated fastening member, like a suture, thread, wire, or pin. In some embodiments, the device may allow for the implantation of multiple sutures and fasteners in tissue with little or no repositioning of the device. For example, the device may have two or more of the elements described below connected to a single grip or handle. Likewise, the incision or opening providing access to the treated bone or tissue may extend at least partially in a direction along the length of the treated area so

5

that the processes described below may be repeatedly performed on other, nearby portions of the bone or tissue in a similar manner.

Tissue Repair

Referring now to the drawing figures in which like reference designators refer to like elements, there is shown in FIG. 1 an exemplary embodiment of the guidance and positioning device 20. The device includes a generally cylindrical handle 22 and a hook 24 with a proximal end connected to the handle 22. In one embodiment, the hook has a tubular construction. An interior passageway may extend from the proximal end to the distal end. The hook 24 may be curved as illustrated in the Figures, may be angular (e.g., may have an open-sided geometric shape), or may have any other desired shape so that its distal end is disposed approximately around the bone or tissue to be treated or fastened.

The proximal portion of the hook 24 may be positioned generally parallel with the longitudinal axis of the handle 22. A plurality of interchangeable hooks 24 may be releasably and interchangeably connected to the handle. In this manner, hooks of different sizes, shapes, or other features may be selected and used as desired by a physician. Thus, the device 20 may have a lever, clip, set-screw, button, spring, match, or latch 26 that allows selective securing and releasing of hooks 24 to or from the handle 22. The lever 26 allows different sized hooks 24 to be placed in the handle 22. For example, the hook may include different sized lumens extending therethrough, may be different lengths, and/or may have different radii of curvature. The curved or angled portion 28 of the hook 24 may be configured for positioning around a fractured bone 30 (as seen in FIG. 1), multiple pieces of similar tissue, multiple pieces of different tissue, or a single tissue element. Examples of such tissue includes, not is not limited to, bone, muscle, cartilage, ligament, tendon, skin, etc. Also, the tissue may be stomach tissue, and the positioning device may be used during bariatric surgery, like gastric stapling. It is further contemplated that measurements such as the depth, angle, length, and/or compression of the hook be determined. The handle may include guides or indicia for measuring and displaying these measurements. Alternatively, the positioning device may include sensors for taking these measurements. For example, the handle of the device may include sensors and/or radiofrequency transmitters for determining and sending measurements to a computer and/or display.

A guide channel 32 extends through the handle 22. Preferably, the guide channel 32 extends generally parallel with the longitudinal axis of the handle 22. The longitudinal axis of the guide channel 32 is generally aligned with or is slightly offset from the distal end 34 of the hook 24. For instance, the shortest distance between the longitudinal axis of the guide channel and the distal end of the hook may be about 2 cm or less. In other embodiments, the shortest distance may be about 1 cm or less, or even about 0.25 cm or less.

Preferably, the guide channel 32 and hook 24 are configured so that the device can be used with a single, small incision in the skin or other soft tissue to gain access to the fractured bone or other tissue requiring fixation. For example, the portions of the guide channel 32 and hook 34 that are near the opening or incision may be spaced apart from each other by about 5 cm or less, and preferably are spaced about 2 cm or less from each other near the incision or opening. In one embodiment, the guide channel and hook

6

are generally parallel and relatively close to each other for a substantial portion of the distance between the handle and the incision or opening.

In use, the device 20 is positioned with the curved portion 28 of the hook 24 placed next to and around the tissue to be fastened. The hook may be positioned subcutaneously, percutaneously, and/or minimally invasively. The tissue may be a fractured bone, a tissue fragment having tendon and bone or ligament and bone, or a tissue with avulsion type fragments. In FIG. 2, a curved portion 28 of the hook 24 is placed around a fractured bone 30 (fracture not shown) or tissue. A drill system 36 is positioned in the guide channel 32. The drill system 36 includes a headpiece 38 configured for attachment to a drill 40. A drill bit 42 is positioned at the distal end of the drill system 36. A drill stop 44 is located distal from the headpiece 38 and prevents the drill bit 42 from penetrating too far beyond the tissue to be drilled. The drill system 36 may be a cannulated drill system. A cannula or sleeve 46 may encircle the drill bit 42 or at least the shaft portion of the drill bit 42. As the drill bit 42 creates a passage 48 through the bone 30, the sleeve 46 is positioned in the passage 48 to link the bone passage 48 and the guide channel 32. The drill system 36 is used to create a passage 48 in the bone 30 from the proximal side of the bone 30 to the distal side of the bone 30, then the drill 40 and drill bit 42 are removed from the sleeve 46 and guide channel 32. The distal opening of the bone passage 48 is generally near the distal aperture 50 of the hook 24.

It is contemplated that the drill system may be used to create a non-linear passage in tissue. The non-linear passage may be formed to go around implants such as an intramedullary rod or prosthesis. The non-linear passage may also allow a physician to avoid critical body parts or tissues such as vessels or organs. Alternatively, no drill system may be employed to create a passage in the tissue. Rather, as described in more detail below, the guide channel may be used to guide and position a self-introducing elongate member like a guide wire, k-wire, claw, grabber, etc. The self-introducing member may be forced through the soft or hard tissue instead of pre-drilling a passage.

Next, as seen in FIG. 3, a fastener 52 is positioned at the distal end of a flexible pushrod 54. The fastener 52 may be connected with the pushrod 54 or may be loosely fitted with the distal end of the pushrod 54. A suture 56 is looped through or connected with the fastener 52 such that one, two, or more sections, legs, strands, or portions of the suture 56 extend from the fastener 52. Examples of fasteners may be found in U.S. Pat. Nos. 5,163,960 and 5,593,425 entitled "Surgical Devices Assembled Using Heat Bondable Materials" which disclose fasteners assembled from a plurality of discrete components, one of which includes a heat bondable material for bonding the components together. The heat bondable material is preferably a polymeric or composite material suitable for surgical applications and implantation in the human body. The heat bondable material may be a biodegradable material. A laser, hot air gun, welding gun, soldering gun, or Bovie tip may be used as a heat source for bonding the fastener. U.S. Pat. No. 6,368,343 entitled "Method of Using Ultrasonic Vibration to Secure Body Tissue" further discloses using ultrasonic vibration energy to bond the heat bondable material of the components of the fastener.

U.S. Pat. No. 5,403,348 entitled "Suture Anchor" discloses an anchor for securing a suture in the body. The anchor includes a tubular wall having a central axis. The tubular wall has a proximal end and a distal end each free of axially inwardly extending slots. The tubular wall also has

an inner surface extending for the entire length of the tube and defining in the anchor a central opening extending between the proximal end and the distal end. The anchor has a width less than its length. A suture may extend through the anchor within the central opening. First and second end portions of the suture extend out of opposite ends of the anchor and are sufficiently long to project out of the body when the suture is secured in the body by the anchor. The anchor has an anchoring orientation in the body achieved by manipulation of the distal end of the anchor by pulling on the second end portion of the suture. Furthermore, the anchor has a removal orientation in the body achieved by manipulation of the proximal end of the anchor by pulling on the first end portion of the suture.

U.S. Pat. No. 5,464,426 entitled "Method of Closing Discontinuity in Tissue" discloses a suture anchor having a generally cylindrical configuration with a lumen extending therethrough. In use, a suture is inserted through openings in a plurality of anchors. Pulling on the suture presses the anchors against the body tissue and presses the body tissue together. The anchors may be pushed through the body tissue with a pusher member or by pushing the anchors against each other.

U.S. Pat. No. 5,549,630 entitled "Method and Apparatus for Anchoring a Suture" discloses a tubular anchor having a polygonal cross-sectional configuration with flat outer side surfaces areas connected by a plurality of outer corner portions. A passage through the anchor may be formed by flat inner side surfaces interconnected by inner corner portions. A suture is inserted through the passage. A concentrated force may be applied against a limited area on a trailing end of the anchor to rotate the anchor to move an outer corner portion of the anchor into engagement with body tissue. The suture may engage an inner corner portion of the anchor. The suture may be inserted through a plurality of anchors and the anchors moved through a tubular member into the body tissue under the influence of force transmitted from a trailing anchor to a leading anchor. When the leading anchor is moved into the body tissue, it is rotated under the influence of force applied against a trailing end of the leading anchor. If desired, two anchors may be interconnected. A groove may advantageously be provided along the leading end and side of an anchor to receive the suture.

U.S. Pat. No. 5,713,921 entitled "Suture Anchor" discloses a suture anchor formed from body tissue. The body tissue is shaped to a desired configuration for the anchor and defines a passage through the anchor. A suture is inserted into the passage in the body tissue of the anchor. The anchor is then positioned in a patient's body with a suture extending into the passage in the anchor. The anchor may be formed of osseous body tissue, hard compact bone, dense connective body tissue, or other body tissue. The body tissue may be dried so that it absorbs fluid and expands upon being inserted into a patient's body.

U.S. Pat. No. 5,718,717 also entitled "Suture Anchor" discloses an anchor formed of a material which absorbs body liquid when exposed to body liquid. The anchor may be at least partially formed of a material having a strong affinity for body liquids. This enables the anchor to absorb body liquid and expand upon being inserted into a patient's body. At least one embodiment of the suture anchor has portions formed of a relatively hard material which does not absorb body liquids and is pressed against body tissue by the material which absorbs body liquid to mechanically interlock the suture anchor and the body tissue. The anchor may be at least partially formed of a cellular material. The cells expand to absorb body liquid. At least one embodiment of

the anchor has a pointed leading end portion to form an opening in an imperforate surface on body tissue. The configuration of the anchor may be changed by tensioning the suture while the anchor is disposed in body tissue.

U.S. Pat. No. 5,782,862 entitled "Suture Anchor Inserter Assembly and Method" discloses a suture anchor inserter assembly including a manually engageable handle and a shaft which extends axially outward from the handle. The shaft includes an inner member which is fixedly connected with the handle and an outer member which is retractable into the handle. An anchor is received in a chamber formed at the outer end of the shaft.

U.S. Pat. No. 5,814,072 entitled "Method and Apparatus for Use in Anchoring a Suture" discloses a suture anchor inserter including a manually engageable handle and a shaft which extends from the handle through a passage in the anchor. During insertion of the anchor into body tissue, an end portion of the shaft pierces the body tissue in advance of the anchor. At the same time, a pusher surface on the shaft applies force against a trailing end portion of the anchor to push the anchor into the body tissue. When the orientation of the anchor is to be changed, rotational force is applied to the anchor by tensioning the suture and pressing the end portion of the shaft against an inner surface of the passage in the anchor.

U.S. Pat. No. 5,814,073 entitled "Method and Apparatus for Positioning a Suture Anchor" discloses an inserter assembly operable between a closed condition blocking movement of a suture anchor through the inserter assembly and an open condition in which the inserter assembly is ineffective to block movement of the anchor.

U.S. Pat. No. 5,845,645 entitled "Method of Anchoring a Suture" discloses a process of fastening a suture to an anchor. The suture is inserted through passages which are spaced apart along and extend transversely to a longitudinal central axis of an anchor. When the anchor is moved into body tissue, a first portion of the suture extends from the first passage in the anchor through an opening in the body tissue to a location disposed to one side of the body tissue. A second portion of the suture extends from the second passage in the anchor through the opening in the body tissue. The suture is tensioned to apply force to the anchor. The force applied to the anchor by the suture initiates tipping of the anchor and movement of an end surface on the anchor across a leading end surface on an inserter member.

U.S. Pat. No. 5,921,986 entitled "Bone Suture" discloses an anchor connected with a suture moved through a passage between opposite sides of a bone. The anchor is then pivoted to change its orientation. A second anchor is connected with the suture. While tension is maintained in the suture, the suture is secured against movement relative to the anchors. This may be done by tying the suture or by using a suture retainer to hold the suture. A suture retainer may be used in place of the second anchor.

U.S. Pat. No. 5,948,002 entitled "Apparatus and Method for Use in Positioning a Suture Anchor" discloses an apparatus which includes a tubular outer member and an inner or pusher member. During assembly of the apparatus, a suture is positioned in a slot in the outer member. During use of the apparatus, the slot facilitates visualization of the position of the suture anchor relative to body tissue. In addition, the slot facilitates separation of the apparatus from the suture after the suture anchor has been positioned in the body tissue. A suture anchor retainer may be provided at one end of the tubular outer member to grip the suture anchor and hold the suture anchor in place during assembly. The tubular outer member may be utilized to guide a drill during formation of

an opening in body tissue and may be subsequently utilized to guide movement of a suture anchor into the opening in the body tissue.

U.S. Pat. Nos. 6,010,525; 6,159,234; and 6,475,230 entitled "Method and Apparatus for Securing a Suture" disclose improved method to secure a suture relative to body tissue. A suture retainer is moved along first and second sections of a suture toward the body tissue. When a predetermined minimum force is being transmitted between the suture retainer and the body tissue, the first and second sections of the suture are gripped with the suture retainer by plastically deforming material of the suture retainer. The material of the suture retainer cold flows under the influence of force applied against the surface areas on the suture retainer. One or more bends are formed in each of the sections of the suture to increase the holding action between the suture retainer and the sections of the suture. The bends may be formed by wrapping a turn of the suture around a portion of the suture retainer. During movement of the suture retainer toward the body tissue, the bends are moved along the first and second sections of the suture.

U.S. Pat. No. 6,045,551 entitled "Bone Suture" discloses an anchor connected with a suture moved through a passage between opposite sides of a bone. The anchor is then pivoted to change its orientation. A second anchor is connected with the suture. While tension is maintained in the suture, the suture is secured against movement relative to the anchors. This may be done by tying the suture or by using a suture retainer to hold the suture. A suture retainer may be used in place of the second anchor. The passage may extend across a fracture in the bone. The passage may have either a nonlinear or linear configuration. A tubular member may be positioned in the passage with the tubular member extending into portions of the passage on opposite sides of the fracture. Opposite end portions of the tubular member may be disposed in a compact outer layer of the bone. If desired, a member other than a suture may be used as a force transmitting member between the two anchors. The tubular member may be formed of bone.

U.S. Pat. No. 6,447,516 entitled "Method of Securing Tissue" discloses a retainer member formed of bone which secures tissue against movement relative to a portion of a bone in a patient's body. The retainer member is utilized to form an opening in a compact outer layer of a portion of the bone in the patient's body. The retainer member formed of bone is advantageously enclosed in a tubular member or sleeve to prevent breaking of the retainer member during the forming of the opening in the bone. The extent of movement of the retainer member into the bone in the patient's body is determined as the retainer member is moved into the bone. A suture may be connected with the retainer member and used to connect tissue with the bone.

U.S. Pat. No. 6,592,609 entitled "Method and Apparatus for Securing Tissue" discloses an anchor having a pointed end portion may be utilized to form an opening in a bone in a patient's body. The anchor is moved into the opening formed in the bone in the patient's body with a suture connected to the anchor. The suture may then be utilized to retain body tissue in a desired position relative to the bone. The body tissue may be either hard or soft body tissue. If desired the anchor may be utilized in conjunction with layers of soft body tissue. When a suture is used it may be secured by connecting a retainer with the suture. Alternatively, sections of the suture may be interconnected. It is believed that it may be preferred to secure the suture in place after at least a predetermined tension has been established in the suture and/or a predetermined force has been transmitted to

the body tissue. The suture may be secured in place by exposing a retainer to ultrasonic vibratory energy or by applying the ultrasonic vibratory energy directly to sections of the suture.

U.S. Pat. No. 6,635,073 entitled "Method of Securing Body Tissue" discloses a process to secure a first body tissue with a second body tissue. A first anchor is moved along a first path through the first body tissue into the second body tissue. A second anchor is moved along a second path through the first body tissue into the second body tissue. A suture extending between the anchors may be tightened by moving the second anchor along a path which extends transverse to the path of the first anchor. The suture which extends between the anchors may have free ends which are connected with a suture retainer. The free ends of the suture may be interconnected either before or after the anchors are moved along the first and second paths. Alternatively, the suture may be a continuous loop which extends between the two anchors. A guide assembly may be provided to guide movement of the anchors along the two paths. The paths along which the anchors move may intersect so that the anchors may be interconnected at the intersection between the two paths.

U.S. Pat. No. 6,719,765 entitled "Magnetic Suturing System and Method" discloses an instrument and method for passing a medical implement through tissue with magnetic forces. The implement can be an implant, either permanent or temporary, and is provided with a magnetic component. A magnetic field is established and the magnetic component and/or magnetic field is manipulated to drive the implant through tissue. Alternatively, the instrument itself is the implement and includes at least one magnetic element so that a magnetic field established by an external magnetic generator drives the instrument through tissue. In another embodiment, the instrument includes two magnetic elements that are moveable with respect to one another and interaction between the magnetic elements drives the instrument through the tissue. Examples of applications of the present invention include a suture passer and a tissue anchor.

Other fastener types and fastening methods are disclosed in U.S. patent application Ser. No. 10/102,413 entitled "Methods of Securing Body Tissue" which discloses an improved method of securing body tissue performed with a robotic mechanism. The robotic mechanism may be utilized to tension a suture with a predetermined force and urge a suture retainer toward body tissue with a predetermined force. Ultrasonic vibratory energy may be transmitted to the suture retainer to effect a gripping of the suture by the suture retainer. The body tissue may be secured with a staple. Legs of the staple may be bonded together to secure the staple. The legs of the staple may be bonded together by transmitting ultrasonic vibratory energy to the legs of the staple. A tissue positioning assembly may be used to hold the body tissue in a desired position. Images of the body tissue being secured may be obtained using various known devices including one or more endoscopes, a fluoroscope, a magnetic resonance imaging device, and/or other known imaging devices.

U.S. patent application Ser. No. 10/228,855 entitled "Apparatus and Method for Securing a Suture" discloses a suture retainer having an upper or cover section and a lower or base section which cooperate to define passages through which portions of a suture extend. Projections on the cover section of the retainer extend into recesses on the base section of the retainer. A center projection on the base section extends between the two projections on the cover section. The projections cooperate with surfaces on body

sections of the cover and base section of the retainer to position and grip portions of the suture. The retainer may be moved along the portions of the suture while the retainer is gripped by an applicator assembly. The applicator assembly is operable to apply energy to the retainer to bond end portions of the projections on the cover section to bottoms of recesses in the base section of the retainer.

U.S. patent application Ser. Nos. 10/779,978; 10/780,444; and 10/797,685 entitled "Method and Device for Securing Body Tissue" disclose sutures and suture retainers positioned relative to body tissue. Energy, such as ultrasonic vibratory energy, is utilized to heat the suture retainer and effect a bonding of portions of the suture retainer to each other and/or to the suture. Portions of the body tissue may be pressed into linear apposition with each other and held in place by cooperation between the suture and the suture retainer. The suture retainer may include one or more portions between which the suture extends. The suture retainer may include sections which have surface areas which are bonded together. If desired, the suture may be wrapped around one of the sections of the suture retainer. The suture retainer may be formed with a recess in which the suture is received. If desired, the suture retainer may be omitted and the sections of the suture bonded to each other.

The characteristics and features of the fasteners and fastening methods just described may be combined and integrated with the devices and methods of the present invention. The above cited patents and patent applications are incorporated herein by reference.

Furthermore, the fasteners may be, but are not limited to, degradable, biodegradable, bioerodible, bioabsorbable, mechanically expandable, hydrophilic, bendable, deformable, malleable, riveting, threaded, toggling, barbed, bubbled, laminated, coated, blocking, pneumatic, one-piece, Morse taper single piece, multi-component, solid, hollow, polygon-shaped, pointed, locking and unlocking, self-introducing, knotless, and combinations thereof. Also, the fasteners may include metallic material, polymeric material, ceramic material, composite material, body tissue, synthetic tissue, hydrophilic material, expandable material, compressible material, heat bondable material, biocompatible adhesive, and combinations thereof. Examples of body tissue include bone, collagen, cartilage, ligaments, or tissue graft material like xenograft, allograft, autograft, and synthetic graft material. The fasteners may also be made from a porous matrix or mesh of biocompatible and bioresorbable fibers acting as a scaffold to regenerate tissue.

The fasteners may also be made of or have a coating made of an expandable material. The material could be compressed then allowed to expand. Alternatively, the material could be hydrophilic and expand when it comes in contact with liquid. Examples of such expandable materials are PEEK, ePTFE, and desiccated body tissue. It is contemplated that the fasteners and implants of the present invention may include any combination of materials and agents disclosed herein. For example, a fastener may include combinations of hydrophilic material, synthetic body tissue, collagen, synthetic collagen, heat bonded material, biocompatible adhesive, and cells, such as stem cells.

Moreover, the fasteners described herein and incorporated by reference may include therapeutic substances to promote healing. These substances could include antibiotics, hydroxyapatite, anti-inflammatory agents, steroids, antibiotics, analgesic agents, chemotherapeutic agents, bone morphogenetic protein (BMP), tissue inductive factors, demineralized bone matrix, collagen, growth factors, autogenetic bone marrow, progenitor cells, calcium sulfate, immo sup-

pressants, fibrin, osteoinductive materials, apatite compositions, germicides, fetal cells, stem cells, enzymes, proteins, hormones, cell therapy substances, gene therapy substances, and combinations thereof. These therapeutic substances may be combined with the materials used to make the fasteners to produce a composite fastener or implant. Alternatively, the therapeutic substances may be impregnated or coated on the fastener. Time-released therapeutic substances and drugs may also be incorporated into or coated on the surface of the fastener. The therapeutic substances may also be placed in a bioabsorbable, degradable, or biodegradable polymer layer or layers.

In addition to including the materials and agents previously described, a fastener may take the configuration of an integrated fastener and arm member. The flexible arm may be incorporated into the fastener and extend therefrom. The arm may be connected with an end portion of the fastener or with any portion between the end portions, like the midpoint. The fastener and flexible arm may include the same or different materials and/or therapeutic agents. In use with the positioning device of the present invention, the fastener may be positioned at the distal end of the hook with the flexible arm extending from the fastener either within the lumen of the hook or exterior to the hook. Once the fastener is properly placed within the body, the flexible arm may be positioned through or around tissue and/or an implant and tensioned to compress and stabilize the tissue and/or implant. Another fastener may be connected with the flexible arm to maintain tension and position of the arm.

The sutures of the present invention may be made of metallic material, non-metallic material, composite material, ceramic material, polymeric material, copolymeric material, or combinations thereof. The sutures may be degradable, biodegradable, bioabsorbable, or nonbiodegradable. Examples of suture materials are polyethylene, polyester, cat gut, silk, nylon, polypropylene, linen, cotton, PLA, PGA, caprolactam, and copolymers of glycolic and lactic acid. Preferably, the sutures are flexible or bendable. They may be threadlike, monofilament, multifilament, braided, or interlaced. The sutures may have a coating of therapeutic substances or drugs. For example, the sutures may include antibiotics, hydroxyapatite, anti-inflammatory agents, steroids, antibiotics, analgesic agents, chemotherapeutic agents, bone morphogenetic protein, demineralized bone matrix, collagen, growth factors, autogenetic bone marrow, progenitor cells, calcium sulfate, immo suppressants, fibrin, osteoinductive materials, apatite compositions, fetal cells, stem cells, enzymes, proteins, hormones, and germicides.

With the fastener **52** and suture **56** on the distal end of the flexible pushrod **54**, the pushrod **54** is moved distally through the lumen of the hook **24** until the fastener **52** is positioned generally next to the distal opening of the bone passage **48**, as seen in FIG. **4**. The pushrod **54** may be advanced to push the fastener **52** beyond the distal aperture **50** of the hook **24** or may be advanced to position the fastener **52** partially in and partially out of the hook **24**. In the latter configuration, the fastener **52** may be easily withdrawn, if necessary, from the hook **24** by moving the pushrod **54** proximally.

Alternatively, the fastener **52** and suture assembly may be assembled in the lumen prior to inserting the device in a patient. For example, a suture may be threaded into the lumen from the distal end of the hook **24**, or may be inserted through the proximal end as described above before inserting the hook into the patient's body. This allows visual confirmation of that the fastener is in a desired position before introducing it into the patient's body. The hollow

13

interior of the hook 24 may be sized to allow sutures to be placed therethrough, but sufficiently small to preclude the fastener 52 from entering it. The distal end may have a bracket or assembly that holds the fastener 52 in a desired position. The bracket or assembly may grip the fastener in place, such as by an interference fit or with friction. In one embodiment, application of tensioning forces to the suture helps hold the fastener 52 in a desired position relative to the distal end of the hook 24.

As illustrated in FIG. 5, a suture claw or grabber 58 is positioned in the guide channel 32 and through the bone passage 48. A hook, claw, or clip 60 is attached to the distal end of the suture claw 58. When the suture claw 58 is inserted distally into the guide channel 32, the hook or clip 60 exits or at least partially exits the distal opening of the bone passage 48. Since the fastener 52 is positioned near the distal opening of the bone passage 48, the hook or clip 60 of the suture claw 58 can grab or capture the suture 56 extending from the fastener 52. The suture 56 may be grabbed by rotating the suture claw 58 and allowing the suture 56 to wrap around the hook 60 at the distal end of the suture claw 58. Alternatively, the suture 56 may be grabbed with a clip 60, like an alligator clip, which may be activated from the proximal end of the suture claw 58. In another embodiment, a spiral member, like a corkscrew, may be disposed on the distal end of the suture claw. The suture claw may be twisted to thereby allow the spiral member to grab the suture. It should be understood that the suture claw should grab all the suture legs or portions attached to the fastener. For example, in FIG. 5, there are two suture legs extending from the fastener. Both legs should be captured by the suture claw either simultaneously or sequentially.

It is also contemplated that the fastener or suture may be pulled or placed in position using magnetic or electromagnetic force. For example, once a passage is drill through tissue or an implant, a magnetic may be used to pull a suture through the passage. Alternatively, when using a fastener with a flexible arm, the arm may be pulled through the passage. In these embodiments, the suture or flexible arm may include a material which is attracted to a magnet.

As previously described, a passage may not need to be pre-drilled into the tissue or bone. In this instance, the suture claw may include a distal tip configured for penetrating into and through the tissue. Using a self-introducing suture claw eliminates the need to bore a passage through the tissue before pulling the suture through the tissue.

In FIG. 6, the suture claw 58 is shown retracted from the guide channel 32. As the suture claw 58 is retracted, it pulls the suture and/or suture portions 56 from the lumen of the hook 24 and into the guide channel 32. As seen in FIG. 7, the proximal ends of the suture portions 56 may extend beyond the proximal end of the guide channel 32 when the suture claw is fully retracted.

As illustrated in FIG. 8, the hook, handle, and drill sleeve of the drill system are removed from the bone 30. The fastener 52 (not shown) is located on the distal side of the bone 30. The suture 56 extends from the fastener 52 through the bone passage and out the proximal opening of the bone or tissue passage. In FIG. 9, another fastener 62 is placed around or otherwise connected with the suture and/or suture portions 56. The suture 56 is tensioned, and the fastener 62 is secured to the suture 56 to thereby approximate the fracture and stabilize the bone 30. The tension of the suture pulls on the fasteners 52 and 62 generally towards each other, thereby applying pressure to the fractured bone or tissue.

14

Another exemplary embodiment of the guidance and positioning device 70 is illustrated in FIG. 10. The device 70 is shown positioned around a fractured bone 30. It should be understood that the device may be used to fasten any tissue type or combination of tissues as previously described. The device 70 includes a generally cylindrical handle 22 and a hookshaped elongated member 72 attached to the handle 22. In this embodiment, the hook-shaped elongated member 72 does not necessarily include a lumen extending there-through. The proximal portion of the hook-shaped member 72 may be positioned generally parallel with the longitudinal axis of the handle 22. The device 70 may include a lever, clip, set-screw, button, spring, or latch 26 for securing and releasing the hook-shaped elongated member 72. The lever 26 allows different sized hooks to be placed in the handle 22. For example, the hooks may be of different lengths, have different radii of curvature, or have different types or sizes of bone engagement portions 28.

A guide slot 74 extends through the handle 22 generally parallel with the longitudinal axis of the handle 22. The longitudinal axis of the guide slot 74 is generally aligned with the distal end of the hook-shaped member 72. The guide slot 74 and hook-shaped member 72 are generally parallel and relatively close to each other at and just distal to the handle 22. In this configuration, a single, small, percutaneous incision may be made in skin or other soft tissue to gain access to the fractured bone or other tissue requiring fixation.

In use, the device 70 is positioned with the hook-shaped portion 76 of the hook-shaped elongated member 72 placed next to and around the tissue to be fastened. In FIG. 11, the hook-shape portion 76 is placed around a fractured bone 30 (fracture not shown). A drill system 36 is positioned in the guide slot. The drill system 36 includes a headpiece 38 configured for attachment to a drill 40. A drill bit 42 is positioned at the distal end of the drill system 36. A drill stop 44 is located distal from the headpiece 38 and prevents the drill bit 42 from penetrating too far beyond the tissue to be drilled. The drill system 36 may be a cannulated drill system. The drill system 36 is used to create a passage 48 in the bone 30 from the proximal side of the bone 30 to the distal side of the bone 30. The distal opening of the bone passage 48 is generally near a socket 78 at the distal end of the hook-shaped portion 76 of the elongated member 72.

As previously noted, a drill system may not be needed to form a passage in the tissue. An elongated member with a distal tip configured for penetrating through tissue may be placed in the guide slot and used for passage through tissue. The elongate member may be a guide wire, k-wire, needle, or like device.

FIG. 12 illustrates the socket 78 at the distal end of the hook-shaped portion 76 of the elongated member. The socket 78 is dimensioned and configured for holding and/or carrying a fastener 52. The socket 78 may be a hollow cylinder or any other configuration capable of accepting a fastener 52. As seen in FIG. 11, the socket 78 is positioned at the distal end of the hook-shaped member 72 such that the fastener 52 is generally aligned with the distal opening of bone passage 48. The fastener may include characteristics, materials, therapeutic substances, coatings, or any other features as previously described herein. It is contemplated that the socket may hold the fastener magnetically, frictionally, with an interlocking mechanism such as a snap, with adhesive, etc.

Next, as shown in FIG. 13, the drill system is removed from the guide slot 74. A fastening member 80 is placed in the guide slot 74 and through the passage in the bone 30. The

15

fastening member **80** is moved distally through the passage and inserted into the fastener disposed in the socket at the distal end of the hook-shaped member **72**. The fastening member may be made of metal, polymer, ceramic, composite, body tissue, or combinations thereof. The fastening member may also include features, therapeutic agents, and coatings similar to the fastener and suture previously described. FIG. **14** illustrates one exemplary embodiment of the connection between the fastening member **80** and the fastener **52**. The distal end of the fastening member includes a threaded portion **82**, and the fastener **52** includes a threaded hole. The fastening member **80** is screwed into the fastener **52**. Other examples of connecting the fastening member and fastener include ball and socket, hook and loop, mechanical expansion, material expansion, dovetail, orientation change, heat bondable material, biocompatible adhesive, and other similar connection means.

In the embodiment wherein a drill system is not used to create a passage in the tissue, the fastening member **80** may include a sharp or pointed distal tip to allow the member to be moved through the tissue, free of a passage. Using a self-introducing fastening member may eliminate the need to pre-drill the passage in the tissue.

As illustrated in FIG. **15**, the guidance and positioning device is removed from the bone **30**. The fastener **52** (not shown) is located on the distal side of the bone **30**. The fastening member **80** extends through the bone passage and out the proximal opening of the bone passage. In FIG. **16**, another fastener **62** is placed around the fastening member **80**. The fastening member **80** is tensioned, and the fastener **62** is secured to the fastener member **80** to thereby approximate the fracture and stabilize the bone **30**. Once again, the tension of the fastening member pulls the fasteners toward each other, which in turn causes pressure to be applied to the treated bone or tissue.

It is further contemplated that the guidance and positioning device **20**, **70** may be used without a distal fastener. In this embodiment, the device **20**, **70** is used to position a suture on the backside or distal portion of the tissue. The suture claw, grabber, or elongate member may be placed in the guide channel or guide slot and moved distally toward the suture located at the distal end of the hook. Using the suture claw, one or two sections of the suture may be pulled through the tissue to the proximal side of the tissue. The suture or sutures may be pulled through a pre-drilled passage created by a drill system or may be pulled through a passage created by a self-introducing suture claw. Once a portion of the suture is positioned on the proximal side of the tissue, it may be tensioned and secured with a fastener. Alternatively, the proximally extending suture section may be fastened with another section of the suture extending from the distal end of the hook and around the tissue. In this embodiment a suture loop is formed with tissue caught or positioned in the middle of the loop. The two sections of the suture may be secured with a knot or a fastener.

FIGS. **17** and **18** illustrate exemplary embodiments of clamping mechanisms for the guidance and positioning device. FIG. **17** shows a tubular clamp member **84** connected with the handle **22** of the device **20**, **70**. The clamp member **84** includes a lumen extending therethrough for allowing passage of the drill system, suture claw, and suture as previously described. The proximal portion of the clamp member **84** includes threads **86**, a ratchet, or the like for advancing the clamp member **84** into and out of the handle **22**. The distal end of the clamp member **84** may include a tissue pad **88** for contacting tissue.

16

The tissue pad **88** may be integrally formed on the distal end of the clamp member. For example, during fabrication of the clamp member, its cross-section may initially be relatively the same size along its length, including at the distal end. Subsequently, the distal end may be deformed or flattened to have a larger cross section.

Alternatively, the tissue pad **88** also may be connected to the clamp member in a manner that allows it to rotate and/or swivel. As the clamp member **84** is moved toward the bone or tissue, some areas of the tissue pad **88** may begin to make contact even though the clamp member **84** may require additional rotation or advancement in order to obtain a desired amount of contact. If the tissue pad **88** is able to rotate or swivel, it can adjust to the contours of the bone or tissue while also reducing potential abrasion.

The contact surface of the tissue pad **88** may be substantially flat, as shown in FIG. **17**, but it also may be curved or have a different shape that may correspond generally to the curvature or shape of the bone or tissue that it may contact. The contact surface also may be deformable so that it can more easily conform to an uneven surface of bone or tissue. The deformable surface of the tissue pad may be formed from a layer of elastomeric material (e.g., rubber or urethane), foam material, or any other elastomeric material suitable for use in a surgical procedure.

In use, the device **20** is positioned about a bone, or other tissue. The clamp member **84** is moved or rotated distally so that the tissue pad **88** contacts the proximal side of the bone. Further advancement of the clamp member **84** causes the tissue pad **88** to apply pressure on the bone or tissue.

Teeth or other friction means **90** may be disposed on the distal portion of the hook **24** to make contact with the distal side of the bone so that when the clamp member **84** extended, the device **20** is clamped or held in position relative to the bone. The contacting surface of the hook also may be modified or configured in the manner described above for the tissue pad.

FIG. **18** shows another embodiment of a clamping mechanism. The tubular clamp member **84** is slideably disposed or connected with the handle **22** of the device **20**, **70**. The clamp member **84** may also include a lumen extending therethrough. A squeeze/finger grip **92** is connected with the handle **22** for advancing and retracting the clamp member **84** relative to the handle **22**. When the squeeze grip **92** is moved toward the handle **22**, the clamp member **84** may be moved or ratcheted distally thereby pressing the tissue pad **88** against the bone or other tissue. In this configuration, the clamp member functions like a come-along with detents and/or teeth. The squeeze grip **92** may be moved away from the handle **22** to move the clamp member **84** proximally, or a release button or spring or clip may be activated to permit the clamp member **84** to move proximally. Teeth or other friction means **90** may be disposed on the proximal side of the socket **78**. With the clamp member **84** extended, the device **70** is held to the bone or other tissue between the tissue pad **88** and teeth **90** or socket **78**.

Other embodiments of the clamping mechanism are further contemplated. For example, the guidance and positioning device **20**, **70** may include one or more inflatable members, such as balloons. An inflatable balloon may be positioned along the hook at a location where the hook passes near the proximal surface of the tissue. That is, the balloon may be located at the proximal end of the curved portion of the hook. In a deflated configuration, the device may be properly positioned by the physician. The balloon may then be inflated to press against the proximal side of the tissue causing the distal end of the hook to press against the

17

distal side of the tissue and thereby hold or lock the device in place. The balloon may be inflated with air, gas, or liquid. Inflation may be made manually with a hand pump, electrically with an electric pump or battery-operated pump, or pneumatically with a pressure cartridge. The balloon may also help guide the distal end of the hook into the proper position. Multiple balloons may be inflated and/or deflated together or separately to guide the hook. Also, the balloon(s) may be used to create space in tissue.

In another example, the device 20, 70 may include a balloon at the distal end of the hook. Operation of the balloon may be similar to as previously described; however, in the current embodiment, the balloon may inflate to press against the distal side of the tissue causing the proximal portion of the hook (which may include a tissue pad or gripping teeth) to press against the proximal side of the tissue to thereby hold the device in position. Furthermore, two or more balloons may be used to position and hold the device relative to the tissue. The plurality of balloons may be located along the hook or guide channel and inflated together or individually to properly align and hold the device in place. In addition to holding the device relative to the tissue, the balloon or balloons may compress the tissue, tissue elements, and/or implant. With the tissue and/or implant compressed, a fastener or other implant may be positioned within the body.

As illustrated in FIG. 19, the device 20, 70 may include a tensioning mechanism 94 to tension the suture 56 or fastening member 80. The tensioning mechanism 94 may be attached to the handle 22, tubular member 24, elongated member 72, or other component of the device 20, 70. After the suture 56 or fastening member 80 is inserted through the passage in tissue, like a fractured bone 30, the tensioning mechanism 94 may pull and tension the suture 56 or fastening member 80 while a proximal fastener 62 is positioned to maintain the tension in the suture 56 or fastening member 80. The tensioning mechanism 94 may be, but is not limited to, two elements which pinch the suture 56 or fastening member 80 to pull it proximally or a spool which rotates to pull the suture 56 or fastening member 80. A tension gauge, strain gauge, read-out display, tension limiter, and/or an audio or visual tension indicator may be used to apply the proper tension to the suture or fastening member. Also, measurement of the tension may be accomplished with a spring, a radiofrequency emitting device, and/or a sensor such as an electrical sensor, flexible sensor, compressive sensor, piezoelectric sensor. Other examples of tension applicators are disclosed in U.S. Pat. No. 6,010,525 entitled "Method and Apparatus for Securing a Suture"; U.S. Pat. No. 6,447,516 entitled "Method of Securing Tissue"; and U.S. Pat. No. 6,635,073 entitled "Method of Securing Body Tissue." The above mentioned patents are hereby incorporated by reference.

As further shown in FIG. 19, the distal portion 96 of the tubular clamp member 84 may be offset or curved thereby exposing the suture 56 or fastening member 80 between the fractured bone 30 and clamp member 84. The tubular clamp member 84 may include a lumen extending therethrough with the lumen having an aperture at or near the proximal end of the offset portion 96 or the distal end of the straight section of the clamp member 84. The offset distal portion 96 allows a fastener 62 to be placed around the suture 56 or fastening member 80 adjacent to the proximal side of the bone 30. When the suture 56 or fastening member 80 is tensioned with the tensioning mechanism 94, the fastener 62 may be applied to maintain the tension in the suture 56 or fastening member 80.

18

It is contemplated that the guidance and positioning device of the present invention may include more than one hook or elongated member for positioning multiple fasteners at the distal side of tissue. For example, as illustrated in FIG. 29, the device 150 may include two hooks or elongated members 152 and 154 attached to the handle 156 and positioned generally parallel to each other. The handle 156 may then include two guide channels, slots, or pins 158 and 160, each being aligned with one of the distal ends of the hook shaped tubular or elongated members. In this configuration, two passages 162 and 164 may be drilled in tissue, like a fractured bone 166, and two sutures or fastening members may be positioned through the passages, tensioned, and secured. One passage 162 may be non-linear while the other passage 164 may be linear. Having multiple hooks and guide channels or slots allows a physician to implant multiple fasteners thereby producing compression on the implant or tissue, enhancing the healing environment, and allowing for tissue ingrowth. The device with multiple hooks or pins may also be used to position other implants disclosed herein, such as adhesives, tissue scaffolds, medicaments, etc.

It is also contemplated that the device of the present invention may be disposable or may be sterilized after use and reused. The device may be partly disposable and partly reusable. For example, the handle may be reusable and the hook and/or guide channel may be disposable. Alternatively, the handle may be disposable. The device, its components, fasteners, drill bits, sutures, and other apparatus disclosed herein may be package in a kit. The kit may be set-up of a specific procedure, such as repair of a fractured bone, securing of an implant, approximating body tissue, etc.

Positioning Implants

The present invention not only provides an instrument and method for dynamic and rigid fastening of tissue, but it also provides for the guidance and positioning of an implant within the body. For example, the present invention may be utilized with tissue scaffolds as described in U.S. patent application Ser. No. 10/457,100 entitled "Scaffold and Method for Implanting Cells" by Peter M. Bonutti. Viable cells may be positioned on a support structure then implanted within a body. One or more blood vessels may be connected with the support structure to provide a flow of blood through the support structure. The devices and methods of the present invention may be used to guide and position the support structure within the body and fasten the scaffold to tissue or another implant by way of a sling support and/or strut. The above mentioned application is hereby incorporated by reference.

Furthermore, the present invention may be used in combination with a medical system for the administration of a pharmaceutical agent in vivo to a patient. The medical system may include an implant positionable in a body of a patient. A pharmaceutical agent may be disposed on the medical implant and at least partially coated with a reactive coating. The reactive coating acts to control the release of the pharmaceutical agent. An energy unit may be provided for transmitting an energy signal to the reactive coating, wherein the reactive coating reacts to the energy signal to control the release rate of the pharmaceutical agent. Additionally, the energy unit may also heat up the treatment site, locally increasing vascularity at the treatment site and allowing thermal necrosis of tissue. The localized increasing in temperature increases the permeability of the local tissue, allowing for an increased and more efficient adsorption of the pharmaceutical agent into the treatment site. Additionally, in response to localized increase in temperature, which

can be perceived as physical damage or an infection to the local area, the local cells may release beneficial proteins, enzymes, hormones, etc.

In another embodiment, a pharmaceutical agent, drug, or medicament may be delivered within the body using the positioning device described herein. The hook and/or guide channel of the positioning device may conduct the passage of a medicament to a specific location within the body. The drug may be transported through the lumen of the hook or guide channel or, alternatively, may be placed on the exterior of the hook or guide channel. When the positioning device has been properly aligned, the medicament may be released in a constant stream or in a pulsatile manner. Examples of medicaments that may be used with the present invention include those disclosed throughout this application and, additionally, but not limited to, an anti-inflammatory agent, non-proliferative agent, anti-coagulant, anti-platelet agent, Tyrosine Kinase inhibitor, anti-infective agent, anti-tumor agent, anti-leukemic agent, and combinations thereof. One or more medicaments may be placed in one or more reservoirs which are in fluid communication with the positioning device. The reservoir may be physically separate from the device with tubing interconnecting the device and reservoir. Alternatively, the reservoir may be integrated into or attached to the positioning device. Release of the medicament may be achieved through manual operation such as with a plunger, air pressure, or valve or through electrical operation such as with a pump or valve. The medicament may be released from the positioning device or remotely away from the device as with a radiofrequency or signal emitting device.

It is contemplated that an adhesive may be delivered within the body in the way a medicament is delivered as described above. The adhesive could be a polysaccharide based adhesive, fibrin adhesive, mollusk based adhesive, cyanoacrylate based adhesive, polymeric based adhesive, or other biocompatible adhesive. The adhesive could be thermally activated or pH activated. The adhesive could be a single part adhesive or a two part adhesive requiring both parts to activate the adhesive. The adhesive may also be hydrophilic or include hydrophilic material. The hydrophilic adhesive/material may expand upon imbibing liquid, such as body fluid. In use, the adhesive may be delivered within the body to bond tissue together such as soft tissue to soft tissue, soft tissue to hard tissue, or hard tissue to hard tissue. For example, portions of a fractured bone may be adhered, a muscle may be bonded to other muscle or to a tendon, and a ligament may be adhered to another ligament, to muscle, and/or to bone. The adhesive may also be used to bond an implant with body tissue or to another implant. For example, a bone or joint replacement component may be adhered to another replacement component or to other bone, tissue scaffolding with cells may be bonded to other tissue or other scaffolding, and fasteners may be adhered to tissue or sutures.

In another embodiment, an energy sink, such as a pH sink, may be incorporated into a medical implant or be positioned separate from the medical implant. The pH sink is configured to absorb energy from the energy unit, releasing a chemical to either increase or decreasing the local pH. The change in local pH can either increase or decrease the degradation rate of a degradable polymer coating, which in turn can control the release rate of a pharmaceutical agent. The pH sink can be formed from calcium carbonate. Additionally, the localized change in pH created by the pH sink has beneficial effects, which include (but are not limited to): aiding in the alleviation of localized pain, fighting of local

infections, and increasing vascular flow and permeability of vessels at the treatment site to control delivery of pharmaceutical agent.

For example, a localized increasing in pH increases the permeability of the local tissue, allowing for an increased and more efficient adsorption of the pharmaceutical agent into the treatment site. The energy sink may also be used to induce the release of beneficial enzymes, proteins, hormones, etc. from the cells in the treatment site. A localized increase in acidity and/or temperature can be perceived as a physical damage or an infection to the local area. In response, to the local cells may release beneficial proteins, enzymes, hormones, etc. The positioning device and method of the present invention may be used to guide and position a drug-eluting implant, a heat sink, or pH sink within the body.

The present invention may also be used with the disclosure of U.S. Provisional Patent Application No. 60/622,095 entitled "Devices and Methods for Stabilizing Tissue and Implants" by Peter M. Bonutti. The provisional application discloses various procedures for repairing, reconstructing, and stabilizing tissue and implants within the body. Examples of such tissue include bone, muscle, ligament, tendon, skin, organ, cartilage, and blood vessels. Examples of implants include an organ, partial organ grafts, tissue graft material (autogenic, allogenic, xenogenic, or synthetic), a malleable implant like a sponge, mesh, bag/sac/pouch, collagen, or gelatin, or a rigid implant made of metal, polymer, composite, or ceramic. Other implants include breast implants, biodegradable plates, metallic fasteners, rods, plates, screws, screw strips, spacers, cages, compliant bearing implants for one or more compartments of the knee, nucleus pulposus implant, stents, meniscal implants, tissue grafts, tissue scaffolds, biodegradable collagen scaffolds, polymeric or other biocompatible scaffolds, abdominal hernia meshes, cochlear implants, tracheal implants, small intestine submucosal grafts, TISSUEMEND scaffolds, prostheses, nanotechnology devices, sensors, emitters, radiofrequency emitting diodes, computer chips, RFID (radiofrequency identification) tags, adhesives, and sealants.

The guidance and positioning device of the present invention may be used to stabilize or fasten these implants and tissues. For example, the spine may be repaired or stabilized with fasteners, sutures, and cables to provide flexible or rigid reinforcement of the joints of the spine. Also, the nucleus pulposus of an intervertebral disc may be repaired or replaced using the guidance and positioning device of the present invention. For example, a prosthetic disc nucleus is positioned between two vertebral bodies and may be secured to surrounding tissue with fasteners and sutures. Additionally, the annulus may be repaired following a nucleus pulposus repair or replacement. The positioning device of the present invention may be used to position a fastener and suture on the internal side of the annulus. The suture may be pulled proximally through the annulus, tensioned, and secured with another fastener. Finally, the tissue alignment sleeves disclosed in the provisional application may be guided and positioned with the instrument and methods of the present invention. The above mentioned provisional application is incorporated herein by reference.

It is contemplated that the present invention may be utilized with the tracheal tube positioning apparatus of U.S. patent application Ser. No. 09/728,553 entitled "Tracheal Intubation" by Peter M. Bonutti. That application discloses positioning apparatus located relative to a patient's trachea by engaging the patient's trachea. Indicia on relatively movable sections of the positioning apparatus provide an

21

indication of the distance between the patient's mouth and the patient's larynx. A flexible guide rod is moved through a distance corresponding to the distance between the patient's mouth and larynx, as determined by the positioning apparatus. A magnet is utilized to attract a leading end portion of the guide rod. A plurality of emitters may be disposed in an array around the patient's trachea. Outputs from the emitters are detected by a detector connected with the tracheal tube. The above mention patent application is hereby incorporated by reference.

Drill/Sleeve Combination

In another embodiment of the present invention, a drill bit and sleeve combination **100** is provided. In the following description, the drill bit and sleeve combination or system **100** is explained with reference to the fixation of two bones, like two portions of a fractured bone. It should be understood that the present embodiment may be utilized for fastening or securing tissue to tissue, an implant to tissue, or an implant to an implant.

In FIG. **20** the system **100** includes a tubular member or sleeve **102** for aligning two portions of bone located on opposite sides of a fracture. A drill bit **104** extends through the longitudinal lumen of the sleeve **102**. The distal portion **106** of the drill bit **104** has one or more pivoting blades **108**. The system **100** may also include a pusher means **110** for inserting the sleeve **102** into the bone passage created by the drill bit **104**. The pusher means **110** may be connected to the sleeve, bit, or the drill. Preferably, a portion of the pusher means **110** does not rotate with the bit or drill so that the sleeve **102** is not rotated as the pusher means **110** contacts the sleeve **102** during the drilling operation. Examples of the pusher means **110** include a washer-shaped member or donut-shaped member positioned over the bit or a U-shaped fork positionable around the shaft of the bit. The lower side of the pusher means **110** may be configured for contact with the proximal end of the sleeve, while the upper side of the pusher means **110** may be configured of applying a distal force with a hand, hammer, or press.

As seen in FIG. **21**, the blades **108**, when extended from the bit **104**, increase the drilling diameter of the bit **104**. The bone passage created by the drill bit **104** and the extended blades **108** has a diameter generally equal to the outside diameter of the sleeve **102**. The blades **108**, when retracted, pivot into or against the distal portion **106** of the bit **104**. The diameter of the drill bit **104** with the blades **108** retracted is slightly less than the inside diameter of the sleeve **102**.

The pivoting blades **108** of the system **100** may be connected with the distal portion **106** of the bit **104** in a variety of ways, but preferably, the blades **108** are pivotally attached to the bit **104**. In one exemplary embodiment as seen in FIGS. **20** and **21**, the blades **108** extend and retract along radial axes of the bit **104**. The blades **108** may pivot downwardly or distally into an extended configuration and may pivot upwardly or proximally into a retracted configuration. In the retracted state, the blades **108** may be positioned within a groove or notch within the distal portion **106** of the bit **104**. Furthermore, the blades **108** may be spring loaded to normally reside in the retracted configuration. When the drill bit **104** is rotated with a drill, the centrifugal force generated by the drill may cause the blades **108** to pivot into the extended configuration. Once in the extended position, the blades **108** may be locked into position to allow drilling or cutting of the bone.

In another exemplary embodiment, the blades **108** may be manually pivoted distally and proximally. A pin or shaft may extend along the center of the drill bit **104** with the distal end of the pin in contact with the blades **108**. As the pin moved

22

longitudinally, the blades **108** may extend and retract. The proximal portion of the pin may include a lever or other means for moving or advancing the pin along the center axis of the bit **104**.

It is further contemplated that the blades **108** may be extended and retracted radially in and out of the distal portion of the bit **104** along a linear path instead of being pivoted as previously described. In this embodiment, the blades **108** may extend with centrifugal force and retract with a spring-like mechanism or may be manually extended and retracted with a pin or shaft along the central axis of the bit **104**. Furthermore, other embodiments of the blades are contemplated. For example, the blades may be generally arch-shaped to conform to the outside circumference of the bit. The distal ends of the blades may be pivotally attached to the bit allowing the blades to extend radially outward for maximum cutting diameter or retract against the outer surface of the bit to minimize the bit diameter.

FIGS. **22** and **23** illustrate the drill bit and sleeve system **100** in use to repair a fractured bone **112**. The drill bit **104** is inserted into the lumen of the sleeve **102**. The distal portion **106** of the bit **104** and the pivoting blades **108** extend beyond the distal end of the sleeve **102**. Preferably, the amount of bit **104** extending from distal end of the sleeve **102** is minimized to prevent damage to soft tissue of the distal side of the bone **112**. The proximal portion of the bit or shank **114** extends from the proximal end of the sleeve **102** and is connected to a drill **116**. The pivoting blades **108**, located beyond the distal end of the sleeve **102**, are in the extended configuration. The bit **104** is rotated and advanced distally through the fractured bone **112**. As the bit **104** advances and creates a passage in the bone **112**, the sleeve **102** is moved distally into the passage with the pusher means **110**. The sleeve **102** is tight or snug within the passage since the diameter of the passage is generally equal to the outside diameter of the sleeve **102**. When the sleeve **102** is in its proper position securing the bone portions **118** and **120** of the fractured bone **112**, and the drill bit **104** may be removed from the lumen of the sleeve **102**. The bit **104** may be pulled from the lumen of the sleeve **102** because the blades **108** may be positioned in the retracted configuration giving the drill bit **104** a diameter generally smaller than the diameter of the lumen of the sleeve **102**. With the sleeve **102** in place, the bone is compressed, and the fracture is stabilized.

In another embodiment of the present invention, the drill bit and sleeve combination or system **100** is dimensioned and configured for transformation into a fastener. As shown in FIGS. **24** and **25**, the system **100** includes the tubular member or sleeve **102**, the pusher means **110**, and a drill bit **104** with an expanding distal portion **122**. The drill bit **104** extends through the lumen of the sleeve **102** with the distal portion **122** of the bit **104** extending beyond the distal end of the sleeve **102**. The cutting diameter of the distal portion **122** of the bit **104** is generally equal to the outside diameter of the sleeve **102**. In this embodiment, the distal portion **122** of the bit **104** does not include pivoting cutting blades. However, the distal portion **122** does include means for expansion to a diameter greater than the cutting diameter.

Some examples of expansion means are shown in FIGS. **26-28**. In FIG. **26** the expansion means includes one or more mechanically extending barbs **126** from the distal portion **122** of the bit **104**. When extended or expanded, the barbs **126** increase the overall diameter of the drill bit **104**. The barbs **126** may extend to the outside diameter of the sleeve **102**, but preferably the barbs **126** extend beyond the outside edge of the sleeve **102**. Most preferably, the barbs **126** extend over or into the distal side of the fractured bone **112**.

23

In the expanded configuration, the drill bit **104** is prevented from being pulled proximally out of the sleeve **102**.

In FIG. 27, the expansion means includes a distal portion **128** of the drill bit **104** which pivots. In a first orientation during a drilling procedure, the distal portion **128** of the bit **104** is generally in-line with rest of the drill bit **104**. After drilling, the distal portion **128** of the bit **104** is rotated about a pivot point into a second orientation. In the second orientation, the distal portion **128** is generally perpendicular to the rest of the drill bit **104**. As a result, the end sections **132** and **134** of the pivoted distal portion **128** of the bit **104** extend beyond the outer diameter of the sleeve **102**. Preferably, the end sections **132** and **134** extend over or into the distal side of the fractured bone **112** to prevent the bit **104** from being pulled from the sleeve **102**.

In FIG. 28, the expansion means includes a distal portion **136** of the bit **104** which has two or more longitudinal sections **138** and **140** that are biased radially outward. The longitudinal sections **138** and **140** may be normally biased outward but held together by the lumen of the sleeve **102** when drilling through the bone **112**. Alternatively, the longitudinal sections **138** and **140** may be normally in a non-biased configuration. After the passage is drilled in the bone **112**, a plunger **142** within the drill bit **104** may be moved distally biasing the longitudinal sections **138** and **140** radially outward. With the longitudinal sections **138** and **140** biased, the distal portion **136** of the bit **104** may extend over or into the distal side of the fractured bone **112** to secure the bit **104** within the sleeve **102** and bone passage.

The drill bit and sleeve system **100** which transforms into a fastener may be utilized to secure various tissue and implants. Generally, in use, the drill bit **104** is inserted into the lumen of the sleeve **102** with the distal portion of the bit **104** extending beyond the distal end of the sleeve **102**. The proximal portion of the bit or shank **114** extends from the proximal end of the sleeve **102** and connects to a drill. The bit **104** is rotated and advanced distally through the fractured bone **112**. As the bit **104** advances and creates a passage in the bone **112**, the sleeve **102** is moved distally into the passage with the pusher means **110**. When the sleeve **102** is in its proper position connecting the two portions **118** and **120** of a fractured bone **112**, the shank **114** of the drill bit **104** is removed from the drill. The distal portion of the bit **104**, which extends just beyond the distal surface of the bone **112**, is expanded with the expansion means.

Once expanded, the drill bit **104** is prevented from being pulled out of the bone passage. A retainer **144** may then be placed around the shank **114** of the bit **104** and moved distally to engage the proximal side of the bone **112**. The retainer **144** is secured to the shank **114**. With the distal portion of the bit expanded and the retainer connected to the shank, the drill bit (and the sleeve) is transformed into a fastener which holds the fractured bone in compression. It is also contemplated that the drill bit may be used without the sleeve so that the drill bit alone becomes a fastener.

The tubular member or sleeve of the present invention is generally tubular shaped having a wall with an inner surface and an outer surface. The inner surface defines a lumen which is dimensioned and configured for receiving a drill bit, suture, cable, K-wire, or similar device. The sleeve may include a slit through the tubular wall. The slit allows the sleeve to be decreased in diameter for implantation and increased in diameter after implantation for proper alignment of the implantation site. In a further embodiment, the sleeve may include two slits in the tubular wall thereby forming two semi-tubular members. The semi-tubular members may be placed separately at the implantation site then

24

aligned to form a complete tubular member. In another embodiment, the tubular member is a solid member.

The tubular member or sleeve may be flexible to enable the tubular member to be inserted into a linear or nonlinear passage through the bone. The tubular member may be formed of metallic material, composite material, ceramic material, polymeric material, or combinations thereof. The sleeve may be made from a degradable, biodegradable, bioerodible, or bioabsorbable material, such as a polymer, composite, or ceramic. The tubular member may also include a therapeutic substance to form a composite tubular member, or the therapeutic substance may be coated onto the tubular member. Furthermore, therapeutic substances or graft material (autogenic, allogenic, xenogenic, or synthetic) may be packed into the sleeve.

Additionally, the outer surface of the tubular member may include a friction or gripping means. A portion of the outer surface of the tubular member may include threads, raised pebbles, bumps, raised ridges, or hills. In addition to a friction means on the outer surface of the tubular member, the wall of the sleeve may include openings for tissue ingrowth. The tubular member of the present invention is further described in U.S. Provisional Patent No. 60/622,095 entitled "Devices and Methods for Stabilizing Tissue and Implants," which is hereby incorporated by reference.

Guidance and Navigation

The guidance and positioning device of the present invention may be placed within the body of a patient with precise navigation. For example, one or more guide wires or k-wires may be utilized—one to hold the device in position and a second wire to drill or pass through tissue toward the distal end of the hook of the device. One of the guide wires or an additional wire can be used to pull a suture or fastener through the tissue. Alternatively, the positioning device may be positioned through an expanding retractor with percutaneous guidance.

Other navigation techniques for precise placement of the positioning device of the present invention include endoscopic guidance, magnetic resonance imaging, CT scan, ultrasound, fluoroscopy, X-ray, computer assisted navigation, magnetic guidance, electromagnetic guidance, radiofrequency guidance, optical guidance, and laser guidance. For example, the hook and/or guide channel of the positioning device may include a magnet, a radiofrequency emitter, or a thermal emitter/sensor. U.S. patent application Ser. No. 10/191,751 entitled "Method of Performing Surgery" discloses computer assisted navigation. In using computer assisted navigation with the present invention, emitters, receivers, and/or reflectors may be attached to the positioning device and/or tissue. The computer navigation system may utilize multiple separate registers which have optical feedback to a central unit. The computer navigation system may utilize electromagnetic or photo-optical feedback. U.S. Pat. No. 5,329,924 entitled "Sequential Imaging Apparatus"; U.S. Pat. No. 5,349,956 entitled "Apparatus and Method for Use in Medical Imaging"; and U.S. Pat. No. 5,542,423 entitled "Indexing Assembly for Joint Imaging" disclose further devices and methods for use in medical imaging. Also, the present invention may be performed using robotics, such as haptic arms or similar apparatus. The above mentioned patents and applications are hereby incorporated by reference.

It is contemplated that the device and method of the present invention be applied using minimally invasive incisions and techniques to preserve muscles, tendons, ligaments, bones, nerves, and blood vessels. A small incision(s) may be made adjacent the target area to be repaired, and a

25

tube, delivery catheter, sheath, cannula, or expandable cannula may be used to perform the methods of the present invention. U.S. Pat. No. 5,320,611 entitled "Expandable Cannula Having Longitudinal Wire and Method of Use" discloses cannulas for surgical and medical use expandable along their entire lengths. The cannulas are inserted through tissue when in an unexpanded condition and with a small diameter. The cannulas are then expanded radially outwardly to give a full-size instrument passage. Expansion of the cannulas occurs against the viscoelastic resistance of the surrounding tissue. The expandable cannulas do not require a full depth incision, or at most require only a needle-size entrance opening. The above mentioned patent is hereby incorporated by reference.

Also, U.S. Pat. Nos. 5,674,240; 5,961,499; and 6,338,730 disclose cannulas for surgical and medical use expandable along their entire lengths. The cannula has a pointed end portion and includes wires having cores which are enclosed by jackets. The jackets are integrally formed as one piece with a sheath of the cannula. The cannula may be expanded by inserting members or by fluid pressure. The cannula is advantageously utilized to expand a vessel, such as a blood vessel. An expandable chamber may be provided at the distal end of the cannula. The above mentioned patents are hereby incorporated by reference.

The present invention may also be utilized with minimally invasive surgery techniques disclosed in U.S. patent application Ser. No. 10/191,751 and U.S. Pat. Nos. 6,702,821 and 6,770,078. These patent documents disclose, inter alia, apparatus and methods for minimally invasive joint replacement. The femoral, tibial, and/or patellar components of a knee replacement may be fastened or locked to each other and to adjacent tissue using fasteners disclosed herein and incorporated by reference. Furthermore, the methods and devices of the present invention may be utilized for repairing, reconstructing, augmenting, and securing tissue or implants during and "on the way out" of a knee replacement procedure. For example, the anterior cruciate ligament and other ligaments may be repaired or reconstructed; quadriceps mechanisms and other muscles may be repaired. The patent documents mentioned above are hereby incorporated by reference.

Furthermore, it is contemplated that the present invention may be used with bariatric surgery, gastric stapling, colorectal surgery, plastic surgery, gastroesophageal reflux disease (GERD) surgery, ligament reconstruction surgery (such as the anterior cruciate ligament, ACL), or for repairing hernias. A band, mesh, or cage of synthetic material or body tissue may be placed around an intestine or other tubular body member. The band may seal the intestine. This method may be performed over a balloon or bladder so that anastomosis is maintained. The inner diameter of the tubular body part is maintained by the balloon. The outer diameter of the body part is then closed or wrapped with a band, mesh, or patch. The inner diameter of the tubular body member may be narrowed or restricted by the band. The band may be secured to the tubular body part or surrounding tissue with the device and method of the present invention.

It is further contemplated that the present invention may be used in conjunction with the devices and methods disclosed in U.S. Pat. No. 5,329,846 entitled "Tissue Press and System" and U.S. Pat. No. 5,269,785 entitled "Apparatus and Method for Tissue Removal." For example, an implant secured within the body using the present invention may include tissue harvested, configured, and implanted as described in the patents. The above mentioned patents are hereby incorporated by reference.

26

Additionally, it is contemplated that the device and method of the present invention may be used with heat bondable materials as disclosed in U.S. Pat. No. 5,593,425 entitled "Surgical Devices Assembled Using Heat Bondable Materials." For example, fasteners may include heat bondable material. The material may be deformed to secure tissue or hold a suture or cable. The fasteners made of heat bondable material may be mechanically crimped, plastically crimped, or may be welded to a suture or cable with RF (Bovie devices), laser, ultrasound, electromagnet, ultraviolet, infrared, electro-shockwave, or other known energy. The welding may be performed in an aqueous, dry, or moist environment. The welding device may be disposable, sterilizable, single-use, and/or battery-operated. The above mentioned patent is hereby incorporated by reference.

Moreover, the device and method of the present invention may be used for the repair and reconstruction of a tubular pathway like a blood vessel, intestine, urinary tract, esophagus, or similar tubular body parts. For example, a blood vessel may be intentionally severed during a surgical operation, or the blood vessel may be damaged or torn as a result of an injury. Flexible fixation of the vessel would permit the vessel to function properly and also compress and stabilize the vessel for enhanced healing. To facilitate the repair or reconstruction of a body lumen, a balloon may be inserted into the lumen and expanded so the damaged, severed, or torn portion of the vessel is positioned against the outer surface of the inflated balloon. In this configuration, the positioning device of the present invention may be used then to approximate the damaged portion of the vessel.

Radiofrequency Identification

The devices, fasteners, and other apparatus disclosed herein may include RFID (radiofrequency identification) tags. Moreover, any surgical device, described herein or not, such as surgical instruments, implants, trays, sponges, screws, bolts, plates, knives, scalpels, etc. may include RFID emitting chips. RFID provides for inventory control before, during, and after surgery. Objects with RFID chips/tags which are located under sterile drapes or within sterile containers may be easily located without having to break the sterile environment. Also, surgical devices and instruments stored in cabinets or placed in an operating room may be scanned with an RFID receiver to help technicians and nurses quickly identify location, type, and quantity. RFID chips/tags placed on surgical objects may save significant time and money during surgery and inventory. Furthermore, matching RFID chips/tags may be placed on an instrument/device and on the tray which holds the device. Using the RF scanner/transmitter, the correct placement of the device can be determined. It is further contemplated that the kits previously described may include RFID chips/tags placed on the container and the components therein.

Surgical Tools

In another exemplary embodiment, the guidance and positioning device of the present invention may be used with pneumatic operated surgical instruments. For example, a gas-powered drill may be couple with the channel guide and/or handle of the positioning device. A surgeon may operate the drill by activating a switch to start the fluid of gas which rotates an air motor thereby rotating a drill bit. The drill may be connected to a compressed gas source with tubing. However, preferably, the drill includes a connecting port for attaching a gas cartridge or canister. Such a drill would be free from electrical and battery power and free from encumbering wires and hoses. The gas cartridge may be sized to fit within the drill body or attached externally on the drill body. The cartridge may be refillable or disposable.

In addition to the drill being gas-powered, the clamping mechanism of the positioning device may be gas-powered. By activating the flow of gas, the clamp may be moved to engage and compress tissue and/or an implant, holding the tissue and/or implant in place until fasteners may be inserted. It is further contemplated that other surgical tools, such as saws, shavers, reamers, grinders, etc., may include gas cartridges as previously described. These gas-powered tools may also include a microprocessor for control and feedback.

All references cited herein are expressly incorporated by reference in their entirety.

It will be appreciated by persons skilled in the art that the present invention is not limited to what has been particularly shown and described herein above. In addition, unless mention was made above to the contrary, it should be noted that all of the accompanying drawings are not to scale. A variety of modifications and variations are possible in light of the above teachings without departing from the scope and spirit of the invention.

What is claimed is:

1. A fastener system comprising:
 - a flexible hollow fastener comprised of fibers of a bio-compatible polymeric material;
 - a flexible elongated fastening member extending through the flexible hollow fastener such that two legs of the flexible elongated fastening member extend from the flexible hollow fastener to enable a user to tension the flexible elongated fastening member, wherein at least a portion of the flexible elongated fastening member is fabricated in part with polyethylene; and
 - an introducer comprised of a pushrod, the pushrod having a distal portion configured to engage the flexible hollow fastener and position the flexible hollow fastener relative to a body tissue, wherein the flexible hollow fastener and flexible elongated fastening member are positioned on the distal end of the pushrod, wherein the flexible hollow fastener is configured to deform from a first configuration to a second configuration to secure the flexible hollow fastener and the flexible elongated fastening member when at least one of the two legs of the flexible elongated fastening member are tensioned relative to the body tissue, and wherein the flexible elongated fastening member is configured to slide through the flexible hollow fastener under tension when the flexible hollow fastener is in the first configuration and the second configuration.
2. The system of claim 1, further comprising at least one additional leg of a flexible elongated fastening member configured to extend from the flexible hollow fastener.
3. The system of claim 1, wherein the flexible hollow fastener is a suture anchor.
4. The system of claim 1, wherein the flexible elongated fastening member includes a suture.
5. The system of claim 2, wherein the at least one additional leg of flexible elongated fastening member is fixed to the flexible hollow fastener.
6. The system of claim 1, wherein the flexible hollow fastener and flexible elongated fastening member include a similar polymer material.
7. The system of claim 1, wherein the flexible hollow fastener is knotless.
8. The system of claim 1, wherein the flexible hollow fastener is a suture-like structure.
9. The system of claim 5, further comprising connecting a second fastener to at least one leg of the flexible elongated

fastening member to secure at least one of the tension in the flexible elongated fastening member and a position of the flexible elongated fastening member.

10. The system of claim 1, wherein the flexible hollow fastener and flexible elongated fastening member include a dissimilar polymer material.

11. A deformable fastener system comprising:

a flexible hollow fastener comprised of polymeric bio-compatible fibers; and

a flexible elongated fastening member extending through the flexible hollow fastener such that two legs of the flexible elongated fastening member extend from the flexible hollow fastener,

wherein the flexible hollow fastener is configured to deform from a first configuration to a second configuration to secure the flexible elongated fastening member in body tissue as at least one of the two legs of the flexible elongated fastening member portion is tensioned relative to the body tissue, and

wherein the flexible elongated fastening member is configured to slide through the flexible hollow fastener under tension when the flexible hollow fastener is in the first configuration and the second configuration.

12. The system of claim 11, further comprising at least one additional leg of a flexible elongated fastening member configured to extend from the flexible hollow fastener.

13. The system of claim 11, wherein the flexible hollow fastener and flexible elongated fastening member include a dissimilar polymer material.

14. The system of claim 11, wherein the flexible elongated fastening member includes a suture.

15. The system of claim 11, wherein the flexible elongated fastening member includes at least in part one of polyester and polyethylene.

16. The system of claim 11, wherein the flexible hollow fastener and flexible and elongated fastening member include a similar polymer material.

17. The system of claim 12, wherein the at least one additional leg of the flexible elongated fastening member is fixed to the flexible hollow fastener.

18. The system of claim 11, wherein the flexible hollow fastener is knotless.

19. The system of claim 11, wherein the flexible hollow fastener is a suture anchor.

20. The system of claim 11, wherein the flexible hollow fastener is a suture-like structure.

21. The system of claim 17, further comprising connecting a second fastener to the flexible elongated fastening member.

22. The system of claim 11, further comprising an introducer with a pushrod configured to engage the flexible hollow fastener, wherein flexible hollow fastener and flexible elongated fastening member are positioned on the distal end of the pushrod.

23. The system of claim 1, wherein the pushrod is flexible.

24. The system of claim 1, wherein the introducer has at least one of a linear configuration and a curved configuration.

25. The system of claim 22, wherein the pushrod is flexible.

26. The system of claim 22, wherein the introducer has at least one of a linear configuration and a curved configuration.

* * * * *