



US009839569B2

(12) **United States Patent**
Behnke et al.

(10) **Patent No.:** **US 9,839,569 B2**
(45) **Date of Patent:** **Dec. 12, 2017**

(54) **METHODS AND APPARATUS FOR BODY WEIGHT SUPPORT SYSTEM**

(71) Applicant: **Bioness Inc.**, Valencia, CA (US)

(72) Inventors: **Joel Behnke**, Valencia, CA (US); **Todd Cushman**, Coto de Caza, CA (US); **Erol Erturk**, Cardiff, CA (US); **Arkady Glukhovsky**, Valencia, CA (US); **Kelvin J. Hasseler**, Murrieta, CA (US); **Keith McBride**, Ventura, CA (US); **Moshe Olim**, San Diego, CA (US); **Perry Payne**, Saugus, CA (US); **Kenneth A. Regas**, Poway, CA (US); **William H. Schwiebert**, Escondido, CA (US); **Daniel Scott Weinstein**, San Diego, CA (US)

(73) Assignee: **MannGroup,LLC**, Sylmar, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **15/471,585**

(22) Filed: **Mar. 28, 2017**

(65) **Prior Publication Data**

US 2017/0196752 A1 Jul. 13, 2017

Related U.S. Application Data

(63) Continuation of application No. 13/745,830, filed on Jan. 20, 2013, now Pat. No. 9,682,000.

(51) **Int. Cl.**
A61G 7/10 (2006.01)
A63B 69/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **A61H 3/008** (2013.01); **A61G 7/1042** (2013.01); **A61G 7/1049** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC A61G 7/1017; A61G 7/1015; A61G 47/1011;
A61G 7/1042; A61G 7/1001; A61G
7/1049; A61H 3/008

(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,536,766 A 5/1925 Cammann
1,971,294 A 8/1934 Bunker

(Continued)

FOREIGN PATENT DOCUMENTS

CH 669780 A5 4/1989
EP 008061 A2 9/1983
JP 2000-237250 9/2000

OTHER PUBLICATIONS

Enclosed Conductor Sysetm KBH Catalogue, Vahle, 2014, 28 pages.

(Continued)


Primary Examiner — Eric J Kurilla

(74) *Attorney, Agent, or Firm* — Cooley LLP

(57) **ABSTRACT**

A body weight support system includes a trolley, a powered conductor operatively coupled to a power supply, and a patient attachment mechanism. The trolley can include a drive system, a control system, and a patient support system. The drive system is movably coupled to a support rail. At least a portion of the control system is physically and electrically coupled to the powered conductor. The patient support mechanism is at least temporarily coupled to the patient attachment mechanism. The control system can control at least a portion of the patient support mechanism based at least in part on a force applied to the patient attachment mechanism.

18 Claims, 34 Drawing Sheets



- (51) **Int. Cl.**
A63B 21/06 (2006.01)
A61H 3/00 (2006.01)
A63B 21/005 (2006.01)
A63B 21/00 (2006.01)
A63B 24/00 (2006.01)
- (52) **U.S. Cl.**
 CPC *A63B 21/0058* (2013.01); *A63B 21/4001*
 (2015.10); *A63B 24/0087* (2013.01); *A61H*
2201/50 (2013.01); *A61H 2201/501* (2013.01);
A61H 2201/5061 (2013.01); *A61H 2201/5064*
 (2013.01); *A61H 2201/5084* (2013.01); *A61H*
2201/5097 (2013.01); *A63B 2220/30*
 (2013.01); *A63B 2220/40* (2013.01); *A63B*
2220/51 (2013.01); *A63B 2220/802* (2013.01);
A63B 2220/806 (2013.01); *A63B 2225/20*
 (2013.01); *A63B 2225/50* (2013.01)
- (58) **Field of Classification Search**
 USPC 212/71; 414/921, 560
 See application file for complete search history.
- (56) **References Cited**
 U.S. PATENT DOCUMENTS
- | | | | |
|--------------|-----|---------|------------------------------------|
| 2,211,220 | A | 8/1940 | Verplanck |
| 2,819,755 | A | 1/1958 | Berger et al. |
| 3,720,172 | A | 3/1973 | Dehne |
| 3,780,663 | A | 12/1973 | Pettit |
| 3,985,082 | A | 10/1976 | Barac |
| 4,243,147 | A | 1/1981 | Twitchell et al. |
| 4,360,307 | A | 11/1982 | Larsson |
| 4,372,452 | A | 2/1983 | McCord |
| 4,606,082 | A | 8/1986 | Kuhlman |
| 4,627,119 | A | 12/1986 | Hachey et al. |
| 4,639,955 | A | 2/1987 | Carminati et al. |
| 4,944,056 | A | 7/1990 | Schroeder et al. |
| 5,138,953 | A | 8/1992 | Horchner et al. |
| 5,337,908 | A | 8/1994 | Beck, Jr. |
| 5,511,486 | A | 4/1996 | Pollard et al. |
| 5,632,206 | A | 5/1997 | Summa et al. |
| 5,809,591 | A | 9/1998 | Capaldi et al. |
| 5,850,928 | A | 12/1998 | Kahlman et al. |
| 6,080,087 | A | 6/2000 | Bingham |
| 6,192,803 | B1 | 2/2001 | Nishino |
| 6,315,138 | B1 | 11/2001 | Dyson |
| 6,464,208 | B1 | 10/2002 | Smith |
| 6,520,484 | B1 | 2/2003 | Shimizu et al. |
| 6,679,185 | B2 | 1/2004 | Sullivan et al. |
| 6,890,288 | B2 | 5/2005 | Bingham |
| 7,137,771 | B2 | 11/2006 | Maurer et al. |
| 7,240,621 | B2 | 7/2007 | Chepurny et al. |
| 7,462,138 | B2 | 12/2008 | Shetty et al. |
| 7,618,223 | B1 | 11/2009 | Begley |
| 7,883,450 | B2 | 2/2011 | Hidler |
| 7,993,248 | B1 | 8/2011 | Rasmussen |
| 8,397,320 | B2 | 3/2013 | Capaldi |
| 8,584,274 | B2 | 11/2013 | Hushek |
| 8,789,682 | B2 | 7/2014 | Fisher |
| 8,978,905 | B2 | 3/2015 | Bergenstrale et al. |
| 2001/0027149 | A1 | 10/2001 | Bingham |
| 2003/0084508 | A1 | 5/2003 | Faucher et al. |
| 2003/0153438 | A1 | 8/2003 | Gordon et al. |
| 2003/0200607 | A1 | 10/2003 | Faucher et al. |
| 2003/0201374 | A1 | 10/2003 | Faucher et al. |
| 2005/0115914 | A1 | 6/2005 | Chepurny et al. |
| 2006/0240952 | A1 | 10/2006 | Schlosser |
| 2007/0004567 | A1 | 1/2007 | Shetty et al. |
| 2008/0287268 | A1 | 11/2008 | Hidler |
| 2009/0308828 | A1 | 12/2009 | Hansen |
| 2010/0000546 | A1 | 1/2010 | Park |
| 2010/0312152 | A1 | 12/2010 | Sarkodie-Gyan et al. |
| 2011/0000015 | A1 | 1/2011 | Faucher et al. |
| 2011/0265260 | A1* | 11/2011 | Darrow A61G 7/1015
5/85.1 |
| 2012/0000876 | A1 | 1/2012 | Bergenstrale et al. |
| 2012/0198612 | A1 | 8/2012 | Tindall |
| 2014/0201905 | A1 | 7/2014 | Glukhovskiy |
| 2014/0206503 | A1 | 7/2014 | Stockmaster et al. |
| 2015/0283921 | A1 | 10/2015 | Zimmerman et al. |
- OTHER PUBLICATIONS
- Extended European Search Report for European Application No. 14740676.3, dated Aug. 18, 2016, 6 pages.
 Notice of Reasons for Rejection for Japanese Application No. 2015-553851, dated Jul. 4, 2016, 5 pages.
 Office Action for U.S. Appl. No. 13/745,830, dated Jun. 15, 2015, 9 pages.
 Office Action for U.S. Appl. No. 13/745,830, dated Dec. 17, 2015, 9 pages.
 Office Action for U.S. Appl. No. 13/745,830, dated Jun. 2, 2016, 10 pages.
 Office Action for U.S. Appl. No. 14/226,021, dated Feb. 22, 2017, 11 pages.
 International Search Report and Written Opinion for International Application No. PCT/US2014/012064, dated May 9, 2014.
 International Search Report and Written Opinion for International Application No. PCT/US2016/016131, dated Apr. 21, 2016, 10 pages.
 International Search Report and Written Opinion for International Application No. PCT/US2016/061552, dated Jan. 31, 2017, 10 pages.
- * cited by examiner




FIG. 1






FIG. 2









FIG. 5



GO
G
L





FIG. 7



85




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14





FIG. 15



১৬




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




Fig. 23




FIG. 24




FIG. 25




FIG. 26





FIG. 27






FIG. 29





FIG. 30



366




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37

1

METHODS AND APPARATUS FOR BODY WEIGHT SUPPORT SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/745,830 entitled, "Methods and Apparatus for Body Weight Support System," filed Jan. 20, 2017, the disclosure of which is incorporated herein by reference in its entirety.

BACKGROUND

The embodiments described herein relate to apparatus and methods for supporting the body weight of a patient. More particularly, the embodiments described herein relate to apparatus and methods for supporting the body weight of a patient during gait therapy.

Successfully delivering intensive yet safe gait therapy to individuals with significant walking deficits can present challenges to skilled therapists. In the acute stages of many neurological injuries such as stroke, spinal cord injury, traumatic brain injury, or the like individuals often exhibit highly unstable walking patterns and poor endurance, making it difficult to safely practice gait for both the patient and therapist. Because of this, rehabilitation centers often move over-ground gait training to a treadmill where body-weight support systems can help minimize falls while raising the intensity of the training.

Numerous studies have investigated the effectiveness of body-weight supported treadmill training and have found that this mode of gait training promotes gains in walking ability similar to or greater than conventional gait training. Unfortunately, there are few systems for transitioning patients from training on a treadmill to safe, weight-supported over-ground gait training. Furthermore, since a primary goal of most individuals with walking impairments is to walk in their homes and in their communities rather than on a treadmill, it is often desirable that therapeutic interventions targeting gait involve over-ground gait training (e.g., not on a treadmill).

Some known support systems involve training individuals with gait impairments over smooth, flat surfaces. In some systems, however, therapists may be significantly obstructed from interacting with the patient, particularly the lower legs of the patient. For patients that require partial assistance to stabilize their knees and/or hips or that need help to propel their legs, the systems present significant barriers between the patient and the therapist.

Some known gait support systems are configured to provide static unloading to a patient supported by the system. That is, under static unloading, the length of shoulder straps that support the patient are set to a fixed length such that the patient either bears substantially all of their weight when the straps are slack or substantially no weight when the straps are taught. Static unloading systems have been shown to result in abnormal ground reaction forces and altered muscle activation patterns in the lower extremities. In addition, static unloading systems may limit the vertical excursions of a patient that prevent certain forms of balance and postural therapy where a large range of motion is necessary. For example, in some known support systems, the extent of the vertical travel of the system is limited. As a result, some known systems may not be able to raise a patient from a wheelchair to a standing position, thereby

2

restricting the use of the system to individuals who are not relegated to a wheelchair (e.g., those patients with minor to moderate gait impairments).

In some known static support systems, there may be a limitation on the amount of body-weight support. In such a system, the body-weight support cannot be modulated continuously, but rather is adjusted before the training session begins and remains substantially fixed at that level during training. Furthermore, the amount of unloading cannot be adjusted continuously since it requires the operator to manually adjust the system.

In other known systems, a patient may be supported by a passive trolley and rail system configured to support the patient while the patient physically drags the trolley along the overhead rail during gait therapy. While the trolley may have a relatively small mass, the patient may feel the presence of the mass. Accordingly, rather than being able to focus on balance, posture, and walking ability, the patient may have to compensate for the dynamics of the trolley. For example, on a smooth flat surface, if the subject stops abruptly, the trolley may continue to move forward and potentially destabilize the subject, thereby resulting in an abnormal compensatory gait strategy that could persist when the subject is removed from the device.

Some known over-ground gait support systems include a motorized trolley and rail system. In such known systems, the motorized trolley can be relatively bulky, thereby placing height restrictions on system. For example, in some known systems, there may be a maximum suitable height for effective support of a patient. In some known systems, a minimum ceiling height may be needed for the system to provide support for patients of varying height.

While the trolley is motorized and programmed to follow the subject's movement, the mechanics and overall system dynamics can result in significant delays in the response of the system such that the patient has the feeling that they are pulling a heavy, bulky trolley in order to move. Such system behavior may destabilize impaired patients during walking. Moreover, some known motorized systems include a large bundle of power cables and/or control cables to power and control the trolley. Such cable bundles present significant challenges in routing and management as well as reducing the travel of the trolley. For example, in some known systems, the cable bundle is arranged in a bellows configuration such that the cable bundle collapses as the trolley moves towards the power supply and expands as the trolley moves away from the power supply. In this manner, the travel of the trolley is limited by the space occupied by the collapsed cable bundle. In some instances, the bundle of cables can constitute a varying inertia which presents significant challenges in the performance of control systems and thus, reduces the efficacy of the overall motorized support system.

Thus, a need exists for improved apparatus and methods for supporting the body-weight of a patient during gait therapy.

SUMMARY

Apparatus and methods for supporting the body weight of a patient during gait therapy are described herein. In some embodiments, a body weight support system includes a trolley, a powered conductor operatively coupled to a power supply, and a patient attachment mechanism. The trolley can include a drive system, a control system, and a patient support system. The drive system is movably coupled to a support rail. At least a portion of the control system is

physically and electrically coupled to the power rail. The patient support mechanism is at least temporarily coupled to the patient attachment mechanism. The control system can control at least a portion of the patient support mechanism based at least in part on a force applied to the patient attachment mechanism.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic illustration of a body weight support system according to an embodiment.

FIGS. 2 and 3 are perspective views of a body weight support system according to an embodiment.

FIGS. 4-7 are various perspective views of a trolley included in the body weight support system of FIG. 2.

FIG. 8 is a top perspective view of a housing included in the trolley of FIG. 4.

FIG. 9 is an exploded view of the housing of FIG. 8.

FIG. 10 is an enlarged view of a portion of the trolley of FIG. 4 identified as region Z.

FIG. 11 is a bottom perspective view of an electronic system included in the trolley of FIG. 4.

FIG. 12 is a perspective view of a drive mechanism included in the trolley of FIG. 4.

FIGS. 13 and 14 are perspective views of a first drive assembly included in the drive mechanism of FIG. 12.

FIGS. 15 and 16 are exploded views of the first drive assembly of FIG. 13.

FIGS. 17-19 are perspective views of a first support member, a second support member, and a third support member, respectively, included in the first drive assembly of FIG. 13.

FIG. 20 is an exploded view of a drive wheel subassembly included in the first drive assembly of FIG. 13.

FIG. 21 is a perspective view of a secondary wheel subassembly included in the first drive assembly of FIG. 13.

FIG. 22 is a perspective view of a portion of the first drive assembly of FIG. 13, illustrating the secondary wheel subassembly of FIG. 21 coupled to the second support member of FIG. 18.

FIG. 23 is a perspective view of the first drive assembly of FIG. 13 in contact with a support track.

FIG. 24 is a perspective view of a second drive assembly included in the drive mechanism of FIG. 12.

FIG. 25 is an exploded view of the second drive assembly of FIG. 24.

FIG. 26 is a perspective view of the second drive assembly of FIG. 24 in contact with the support track of FIG. 20.

FIG. 27 is a perspective view of a support mechanism and a base included in the housing of FIG. 8 both of which are included in the trolley of FIG. 4.

FIG. 28 is a perspective view of the support mechanism of FIG. 27.

FIG. 29 is a perspective view of a winch assembly included in the support mechanism of FIG. 27.

FIG. 30 is an exploded view of the winch assembly of FIG. 29.

FIG. 31 is an exploded view of a guide assembly included in the support mechanism of FIG. 27.

FIG. 32 is a perspective view the support mechanism of FIG. 27 shown without the winch assembly of FIG. 28.

FIG. 33 is an exploded view of a cam assembly included in the support mechanism of FIG. 27.

FIG. 34 is a perspective view of a patient attachment mechanism according to an embodiment.

FIG. 35 is a perspective view of a body weight support system according to an embodiment.

FIG. 36 is a cross sectional view of the body weight support system of FIG. 35 taken along the line X-X.

FIG. 37 is a schematic illustration of a support system according to an embodiment.

DETAILED DESCRIPTION

In some embodiments, a body weight support system includes a trolley, a power rail operative coupled to a power supply, and a patient attachment mechanism. The trolley can include a drive system, a control system, and a patient support system. The drive system is movably coupled to a support rail. At least a portion of the control system is physically and electrically coupled to the power rail. The patient support mechanism is at least temporarily coupled to the patient attachment mechanism. The control system can control at least a portion of the patient support mechanism based at least in part on a force applied to the patient attachment mechanism.

In some embodiments, a body weight support system includes a closed loop track, a powered conductor coupled to the closed loop track, an actively controlled trolley, and a patient support assembly. The actively controlled trolley is movably suspended from the closed loop track and is electrically coupled to the powered conductor. The patient support assembly is coupled to the trolley and is configured to dynamically support a body weight of a patient.

In some embodiments, a body weight support device includes a housing, a drive element, a wheel assembly, and a patient support assembly. At least a portion of the drive element and at least portion of the wheel assembly is disposed within the housing. The patient support assembly is coupled to the drive element and is configured to dynamically support a body weight of a patient.

As used in this specification, the singular forms “a,” “an” and “the” include plural referents unless the context clearly dictates otherwise. Thus, for example, the term “a member” is intended to mean a single member or a combination of members, “a material” is intended to mean one or more materials, or a combination thereof.

As used herein, the terms “about” and “approximately” generally mean plus or minus 10% of the value stated. For example, about 0.5 would include 0.45 and 0.55, about 10 would include 9 to 11, about 10000 would include 900 to 11000.

As used herein, the term “set” can refer to multiple features or a singular feature with multiple parts. For example, when referring to set of walls, the set of walls can be considered as one wall with multiple portions, or the set of walls can be considered as multiple, distinct walls. Thus, a monolithically constructed item can include a set of walls. Such a set of walls may include multiple portions that are either continuous or discontinuous from each other. For example, a monolithically constructed wall can include a set of detents can be said to form a set of walls. A set of walls can also be fabricated from multiple items that are produced separately and are later joined together (e.g., via a weld, an adhesive, or any suitable method).

As used herein, the term “parallel” generally describes a relationship between two geometric constructions (e.g., two lines, two planes, a line and a plane or the like) in which the two geometric constructions are substantially non-intersecting as they extend substantially to infinity. For example, as used herein, a line is said to be parallel to another line when the lines do not intersect as they extend to infinity. Similarly, when a planar surface (i.e., a two-dimensional surface) is said to be parallel to a line, every point along the line is

spaced apart from the nearest portion of the surface by a substantially equal distance. Two geometric constructions are described herein as being “parallel” or “substantially parallel” to each other when they are nominally parallel to each other, such as for example, when they are parallel to each other within a tolerance. Such tolerances can include, for example, manufacturing tolerances, measurement tolerances or the like.

As used herein, the term “tension” is related to the internal forces (i.e., stress) within an object in response to an external force pulling the object in an axial direction. For example, an object with a mass being hung from a rope at one end and fixedly attached to a support at the other end exerts a force to place the rope in tension. The stress within an object in tension can be characterized in terms of the cross-sectional area of the object. For example, less stress is applied to an object having a cross-sectional area greater than another object having a smaller cross-sectional strength. The maximum stress exerted on an object in tension prior to plastic deformation (e.g., necking or the like) is characterized by the object’s tensile strength. The tensile strength is an intensive property of (i.e., is intrinsic to) the constituent material. Thus, the maximum amount of stress of an object in tension can be increased or decreased by forming the object from a material with a greater tensile strength or lesser tensile strength, respectively.

As used herein, the term “kinematics” describes the motion of a point, object, or system of objects without considering a cause of the motion. For example, the kinematics of an object can describe a translational motion, a rotational motion, or a combination of both translational motion and rotational motion. When considering the kinematics of a system of objects, known mathematical equations can be used to describe to the motion of an object relative to a plane or set of planes and/or relative to one or more other objects included in the system of objects.

As used herein, the terms “feedback”, “feedback system”, and/or “feedback loop” relate to a system wherein past or present characteristics influence current or future actions. For example, a thermostat is said to be a feedback system wherein the state of the thermostat (e.g., in an “on” configuration or an “off” configuration) is dependent on a temperature being fed back to the thermostat. Feedback systems include a control scheme such as, for example, a proportional-integral-derivative (PID) controller. Expanding further, an output of some feedback systems can be described mathematically by the sum of a proportional term, an integral term, and a derivative term. PID controllers are often implemented in one or more electronic devices. In such controllers, the proportional term, the integral term, and/or the derivative term can be actively “tuned” to alter characteristics of the feedback system.

Electronic devices often implement feedback systems to actively control the kinematics of mechanical systems in order to achieve and/or maintain a desired system state. For example, a feedback system can be implemented to control a force within a system (e.g., a mass-spring system or the like) by changing the kinematics and/or the position of one or more components relative to any other components included in the system. Expanding further, the feedback system can determine current and/or past states (e.g., position, velocity, acceleration, force, torque, tension, electrical power, etc.) of one or more components included in the mechanical system and return the past and/or current state values to, for example, a PID control scheme. In some instances, an electronic device can implement any suitable numerical method or any combination thereof (e.g., New-

ton’s method, Gaussian elimination, Euler’s method, LU decomposition, etc.). Thus, based on the past and/or current state of the one or more components, the mechanical system can be actively changed to achieve a desired system state.

FIG. 1 is a schematic illustration of a body weight support system 1000 according to an embodiment. The body weight support system 1000 (also referred to herein as “support system”) includes at least a trolley 1100, a patient attachment mechanism 1800 (also referred to herein as “attachment mechanism”), a power supply 1610, a powered conductor or rail 1620, and a control 1900. The support system 1000 can be used, for example, in intensive gait therapy to support patients with walking deficiencies brought on by neurological injuries such as stroke, spinal cord injury, traumatic brain injury, or the like. In such instances, the support system 1000 can be used to support at least a portion of the patient’s body weight to facilitate the gait therapy. In other instances, the support system 1000 can be used to simulate, for example, low gravity scenarios for the training of astronauts or the like. In some embodiments, the support system 1000 can be used to support a patient over a treadmill or stairs instead of or in addition to supporting a patient over and across level ground.

The trolley 1100 included in the support system 1000 can be any suitable shape, size, or configuration and can include one or more systems, mechanisms, assemblies, or subassemblies (not shown in FIG. 1) that can perform any suitable function associated with, for example, supporting at least a portion of the body weight of a patient. The trolley 1100 can include at least a drive system 1300, a patient support mechanism 1500, and an electronic system 1700. In some embodiments, the drive system 1300 can be movably coupled to a support track (not shown in FIG. 1) and configured to move (e.g., slide, roll, or otherwise advance) along a length of the support track. The support track can be any suitable shape, size, or configuration. For example, in some embodiments, the support track can be substantially linear or curvilinear. In other embodiments, the support track can be a closed loop such as, for example, circular, oval, oblong, rectangular (e.g., with or without rounded corners), or any other suitable shape. In some embodiments, the support track can be a beam (e.g., an I-beam or the like) included in a roof or ceiling structure from which at least a portion of the trolley 1100 can “hang” (e.g., at least a portion of the trolley 1100 can extend away from the beam). In other embodiments, at least one end portion of the support track can be coupled to a vertical wall or the like. In still other embodiments, the support track can be included in a free-standing structure such as, for example, a gantry or an A-frame.

The drive system 1300 of the trolley 1100 can include one or more wheels configured to roll along a surface of the support track such that the weight of the trolley 1100 and a portion of the weight of a patient utilizing the support system 1000 (e.g., the patient is temporarily coupled to the trolley 1100 via the patient attachment mechanism 1800, as described in further detail herein) are supported by the support track. Similarly stated, one or more wheels of the drive system 1300 can be disposed adjacent to and on top of a horizontal surface of the support track; thus, the trolley 1100 can be “hung” from or suspended from the support track. In other embodiments, the surface from which the trolley 1100 is hung need not be horizontal. For example, at least a portion of the support track can define a decline (and/or an incline) wherein a first end portion of the support track is disposed at a first height and a second end portion of the support track is disposed at a second height, different

from the first height. In such embodiments, the trolley **1100** can be hung from a surface of the support track that is parallel to a longitudinal centerline (not shown) of the trolley **1100**. In such embodiments, the trolley can be used to support a patient moving across an inclined/declined surface, up or down stairs, etc.

In some embodiments, the trolley **1100** can have or define a relatively small profile (e.g., height) such that the space between a surface of the trolley **1100** and a portion of the patient can be sufficiently large to allow the patient to move between a seated position to a standing position such as, for example, when a patient rises out of a wheelchair. Furthermore, with the trolley **1100** being hung from the support track, the weight of the trolley **1100** and the weight of the patient utilizing the support system can increase the friction (e.g., traction) between the one or more wheels of the drive system and the surface of the support track from which the trolley **1100** is hung. Thus, the one or more wheels of the drive system **1300** can roll along the surface of the support track without substantially slipping.

In some embodiments, the trolley **1100** can be motorized. For example, in some embodiments, the trolley **1100** can include one or more motors configured to power (e.g., drive, rotate, spin, engage, activate, etc.) the drive system **1300**. In some embodiments, the motor(s) can be configured to rotate the wheels of the drive system **1300** at any suitable rate and/or any suitable direction (e.g., forward or reverse) such that the trolley **1100** can pace a patient utilizing the support system **1000**, as described in further detail herein. In some embodiments, the electronic system **1700** and/or the control **1900** can be operatively coupled (e.g., electrically connected) to the one or more motors such that the electronic system **1700** and/or the control **1900** can send an electronic signal associated with operating the motor(s). In some embodiments, the motor(s) can include a clutch, a brake, or the like configured to substantially lock the motor(s) in response to a power failure or the like. Similarly stated, the motor(s) can be placed in a locked configuration to limit movement of the trolley **1100** (e.g., limit movement of the drive system **1300** and/or the patient support mechanism **1500**) in response to a power failure (e.g., a partial power failure and/or a total power failure).

The patient support mechanism **1500** (also referred to herein as "support mechanism") can be any suitable configuration and can be at least temporarily coupled to the attachment mechanism **1800**. For example, in some embodiments, the support mechanism **1500** can include a tether that can be temporarily coupled to a coupling portion of the attachment mechanism **1800**. Moreover, the attachment mechanism **1800** can further include a patient coupling portion (not shown in FIG. 1) configured to receive a portion of a harness or the like worn by or coupled to the patient. Thus, the attachment mechanism **1800** and the support mechanism **1500** can support a portion of the body weight of a patient and temporarily couple the patient to the trolley **1100**.

In some embodiments, an end portion of the tether can be coupled to, for example, a winch. In such embodiments, the winch can include a motor that can rotate a drum to coil or uncoil the tether. Similarly stated, the tether can be wrapped around the drum and the motor can rotate the drum in a first direction to wrap more of the tether around the drum and can rotate the drum in a second direction, opposite the first direction, to unwrap more of the tether from around the drum. In some embodiments, the support mechanism **1500** can include one or more pulleys that can engage the tether such that the support mechanism **1500** gains a mechanical

advantage. Similarly stated, the pulleys can be arranged such that the force exerted by the winch to coil or uncoil the tether around the drum while a patient is coupled to the attachment mechanism **1800** is reduced.

The horizontal drive system/motor that is configured to allow for movement of the trolley along the track, and the vertical drive system configured to move to control the tether can be simultaneously controlled and operated or not. For example, when a patient is walking over a treadmill, there is little or no horizontal movement, but the vertical (weight bearing) drive system is operational to compensate for the changes during the gait, falls, etc.

In some embodiments, the pulley system can include at least one pulley that is configured to move (e.g., pivot, translate, swing, or the like). For example, the pulley can be included in or coupled to a cam mechanism (not shown) that is configured to define a range of motion of the pulley. In such embodiments, the movement of the at least one pulley can coincide and/or be caused by a force exerted on the attachment mechanism **1800**. For example, in some instances, the patient can move relative to the trolley **1100** such that the force exerted on the tether by the weight of the patient is changed (e.g., increased or decreased). In such instances, the pulley can be moved according to the change in the force such that the tension within the tether is substantially unchanged. Moreover, with the pulley included in or coupled to the cam mechanism, the movement of the pulley can move the cam through a predetermined range of motion. In some embodiments, the electronic system **1700** can include a sensor or encoder operatively coupled to the pulley and/or the cam that is configured to determine the amount of movement of the pulley and/or the cam. In this manner, the electronic system **1700** can send a signal to the motor included in the winch associated with coiling or uncoiling the tether around the drum in accordance with the movement of the pulley. For example, the pulley can be moved in a first direction in response to an increase in force exerted on the tether and the electronic system **1700** can send a signal to the motor of the winch associated with rotating the drum to uncoil a portion of the tether from the drum. Conversely, the pulley can be moved in a second direction, opposite the first direction, in response to a decrease in force exerted on the tether and the electronic system **1700** can send a signal to the motor of the winch associated with rotating the drum to coil a portion of the tether about the drum. Thus, the support mechanism **1500** can be configured to exert a reaction force in response to the force exerted by the patient such that the portion of the body weight supported by the support system **1000** remains substantially unchanged. Moreover, by actively supporting the portion of the body weight of the patient, the support system **1000** can limit the likelihood and/or the magnitude of a fall of the patient supported by the support system **1000**. Similarly stated, the support mechanism **1500** and the electronic system **1700** can respond to a change in force exerted on the tether in a relatively short amount of time (e.g., much less than a second) to actively limit the magnitude of the fall of the patient.

As described above, the electronic system **1700** included in the trolley **1100** can be configured to control at least a portion of the trolley **1100**. The electronic system **1700** includes with at least a processor, a memory. The memory can be, for example, a random access memory (RAM), a memory buffer, a hard drive, a read-only memory (ROM), an erasable programmable read-only memory (EPROM), and/or the like. In some embodiments, the memory stores instructions to cause the processor to execute modules,

processes, and/or functions associated with controlling one or more mechanical and/or electrical systems included in the patient support system, as described above. In some embodiments, control signals are delivered through the powered rail using, for example, a broadband over power-line (BOP) configuration.

The processor of the electronic device can be any suitable processing device configured to run or execute a set of instructions or code. For example, the processor can be a general purpose processor (GPU), a central processing unit (CPU), an accelerated processing unit (APU), and/or the like. The processor can be configured to run or execute a set of instructions or code stored in the memory associated with controlling one or more mechanical and/or electrical systems included in a patient support system. For example, the processor can run or execute a set of instructions or code associated with controlling one or more motors, sensors, communication devices, encoders, or the like, as described above. More specifically, the processor can execute a set of instructions in response to receiving a signal from one or more sensors and/or encoders associated with a portion of the drive system **1300** and/or the support mechanism **1500**. Similarly stated, the processor can be configured to execute a set of instructions associated with a feedback loop (e.g., based on a proportional-integral-derivative (PID) control method) wherein the electronic system **1700** can control the subsequent action of the drive system **1300** and/or the support system **1500** based at least in part on current and/or previous data (e.g., position, velocity, force, acceleration, angle of the tether, or the like) received from the drive system **1300** and/or the support system **1500**, as described in further detail herein.

In some embodiments, the electronic system **1700** can include a communication device (not shown in FIG. 1) that can be in communication with the control **1900**. For example, in some embodiments, the communication device can include one or more network interface devices (e.g., a network interface card). The communication device can be configured to transmit data over a wired and/or wireless network (not shown in FIG. 1) associated with sending data to and/or receiving data from the control **1900**. The control **1900** can be any suitable device or module (e.g., hardware module or software module stored in the memory and executed in the process). For example, in some embodiments, the control **1900** can be an electronic device that includes at least a processor and a memory (not shown in FIG. 1) and is configured to run, for example, a personal computer application, a mobile application, a web page, and/or the like. In this manner, a user can engage the control **1900** to establish a set of system parameters associated with the support system **1000**, as described in further detail herein. In some embodiments the control **1900** can be implemented as a handheld controller.

In some embodiments, control of the trolley **1100** can be accomplished using one or more controllers. In embodiments in which multiple controllers are utilized (e.g., a personal computer control and a handheld control), only one controller can be used at a time. In other embodiments, one of the controllers (e.g., the handheld controller) can override the personal computer controller. In other embodiments, a user can designate which controller is utilized by actuating the relevant controller. In other words, the user can either take control using a controller or can pass control to the other controller by actuating the controller.

In some embodiments, the patient support system **1000** is configured to improve gait and stability rehabilitation training by adding visual and audio feedback to a gait and

stability assistance device. The trolley **1100** coordinates the feedback with heuristic patient data from past training sessions, and stores the data for each therapy/training.

As shown in FIG. 1, the trolley **1100** is operatively coupled to the power rail **1620**. The power rail **1620** is further coupled to the power source **1610** that is configured to provide a flow of electrical current (e.g., electrical power) to the power rail **1620**. More specifically, the power rail **1620** can include any suitable transformer, converter, conditioner, capacitor, resistor, insulator, and/or the like (not shown in FIG. 1) such that the power rail **1620** can receive the flow of electrical current from the power source **1610** and transfer at least a portion of the flow of electrical current to the trolley **1100**. The power rail **1620** can include one or more electrical conductors to deliver, for example, single or multiphase electrical power to one or more trolleys **1100**. For example, in some embodiments, the power rail **1620** is a substantially tubular rail configured to receive a conductive portion of the electronic system **1700** of the trolley **1100**. More specifically, the power rail **1620** can include one or more conductive surfaces disposed within an inner portion of the tubular rail along which a conductive member of the electronic system **1700** can move (e.g., slide, roll, or otherwise advance). In this manner, the power rail **1620** can transmit a flow of electrical current from the power source **1610** to the electronic system **1700** of the trolley **1100**, as described in further detail herein. The power rail **1620** can be any suitable shape, size, or configuration. For example, the power rail **1620** can extend in a similar shape as the support track (not shown in FIG. 1) and can be arranged such that the power rail **1620** is substantially parallel to the support track. In this manner, the trolley **1100** can advance along a length of the support track while remaining in electrical contact with the power rail **1620**. Furthermore, the arrangement of the power rail **1620** and the trolley **1100** is such that movement of the trolley **1100** along the length of the support track is not hindered or limited by a bundle of cables, as described above with reference to known support systems.

Moreover, the control **1900** can also be operatively coupled to the power supply **1610** and can be configured to control the amount of power delivered to the power rail **1620**. For example, the control **1900** can be configured to begin a flow of electrical current from the power supply **1610** to the power rail **1620** to turn on or power up the support system **1000**. Conversely, the control **1900** can be configured to stop a flow of electrical current from the power supply **1610** to the power rail **1620** to turn off or power down the support system **1000**.

While the control **1900** is shown in FIG. 1 as being independent from and operatively coupled to the trolley **1100**, in some embodiments, the control **1900** can be included in the electronic system **1700** of the trolley **1100**. For example, in some embodiments, the control **1900** can be a hardware module and/or a software module that can be executed by the processor of the electronic system **1700**. In such embodiments, the electronic system **1700** can include a user interface (e.g., a touch screen and/or one or more dials, buttons, switches, toggles, or the like). Thus, a user (e.g., a physical therapist, a doctor, a nurse, a technician, etc.) can engage the user interface associated with the control **1900** to establish a set of system parameters for the support system **1000**.

Although not shown in FIG. 1, in some embodiments, more than one trolley **1100** can be coupled to the same support track. In such embodiments, the trolleys **1100** hung from the support track can include, for example, sensors

11

(e.g., ultrasonic proximity sensors and/or the like) that can send a signal to the electronic system **1700** associated with the proximity of one or more trolleys **1100** relative to a specific trolley **1100**. In this manner, the electronic system **1700** of the trolleys **1100** can control, for example, a motor included in the drive system **1300** to prevent collision of the trolleys **1100**. Thus, the support system **1000** can be used to support more than one patient (e.g., a number of patients corresponding to a number of trolleys **1100** disposed about the support track) while keeping the patients at a desired distance from one another.

In some embodiments, the support system is configured to provide feedback to a patient during use. In some embodiments, a laser or culminated light source is coupled to the trolley **1100** to create a light path for a patient to follow during a session. The light path allows the patient to look ahead or look at their feet while attempting to train their brain to properly control the leg/foot/hip motion. In some embodiments, a second light source is configured to illuminate a “target” location at which the patient can aim to plant their foot in a proper location. In some embodiments, the size of the target can be varied depending upon the dexterity of the user. In other words, for a user with greater muscle control, the target can be smaller. The light path and target location can be modified using a user interface as described in greater detail herein.

In some embodiments, audible feedback is provided to the patient when the patient’s gate is incorrect. In some embodiments, audible feedback can be provided when the patient begins to fall. Different audible tones can be provided for different issues/purposes.

In some embodiments, a CCD camera interface is configured for video monitoring for future analysis and can be correlated to sensed rope position, speed, tension, etc. In some embodiments, monitors can be coupled to a patient’s body to monitor muscle usage (e.g., leg muscles, torso muscles, etc.). Such information can be wirelessly transmitted to the electronic system **1700** and coordinated in the feedback provided to the patient during and after a therapy/rehabilitation session. Said another way, all of the data collected by the various sensors, cameras, etc. can be coordinated to provide dynamic, real-time feedback and/or post-session feedback.

Although described above as being coupled to a power rail **1620**, in some embodiments, a trolley can be battery powered. In such embodiments, the trolley can include a battery system that is suitable for providing the trolley with a flow of electrical current. The battery system included in such embodiments can be rechargeable. For example, in some embodiments, the trolley and more specifically the battery system can be temporarily coupled to the power source **1610** to charge the battery system. In other embodiments, the battery system can be at least temporarily coupled to the power rail **1620** to recharge the battery system. In some embodiments the charging station(s) can be located in certain location(s) on the track. The trolley(s) can automatically dock to the charging stations according to a certain algorithm. For example, the trolley may travel to and dock to the charging station when the battery level is below certain level or during the break periods (for example when the system is not in use for certain time, at night, or at pre-determined times).

FIGS. 2-33 illustrate a body weight support system **2000** according to an embodiment. The body weight support system **2000** (also referred to herein as “support system”) can be used to support a portion of a patient’s body weight, for example, during gait therapy or the like. FIGS. 2 and 3

12

are perspective views of the support system **2000**. The support system **2000** includes a trolley **2100**, a power system **2600**, and a patient attachment mechanism **2800** (see e.g., FIG. 34). As shown in FIGS. 2 and 3, the trolley **2100** is movably coupled to a support track **2050** that is configured to support the weight of the trolley **2100** and the weight of the patient utilizing the support system **2000**. Although the support track **2050** is shown as having an I-shape, the support track **2050** can be any suitable shape. Furthermore, while the support track **2050** is shown as being substantially linear, the support track **2050** can extend in a curvilinear direction. In other embodiments, the support track **2050** can be arranged in a closed loop such as, for example, circular, oval, oblong, square, or the like. As described in further detail herein, the power system **2600** can include a power rail **2620** that extends substantially parallel to the support track **2050** and is at least electrically coupled to the trolley **2100** to transfer a flow of electrical current from a power source (not shown in FIGS. 2-32) to the trolley **2100**.

FIGS. 4-7 are perspective views of the trolley **2100**. The trolley **2100** can be any suitable shape, size, or configuration. For example, the trolley **2100** can be suspended from the support track **2050** (as described in further detail herein) and can have or define a relatively small profile (e.g., height) such that the space between the trolley **2100** and a patient can be maximized. In this manner, the support system **2000** can be used to support patients of varying heights as well as supporting a patient rising from a sitting position to a standing position as is common in assisting patient at least partially relegated to a wheelchair. The trolley **2100** includes a housing **2200** (see e.g., FIGS. 8 and 9), an electronic system **2700** (see e.g., FIGS. 10 and 11), a drive system **2300** (see e.g., FIGS. 12-26), and a patient support mechanism **2500** (see e.g., FIGS. 27-33).

As shown in FIGS. 8 and 9 the housing **2200** includes a base **2210**, a first side member **2230**, a second side member **2240**, a third side member **2250**, and a cover **2260**. The housing **2200** is configured to enclose and/or cover at least a portion of the electronic system **2700**, as described in further detail herein. As shown in FIG. 9, the base **2210** has a first side **2211** and a second side **2212**. The base **2210** defines a set of drive mechanism openings **2213**, a fan opening **2214**, a guide mechanism opening **2215**, a bias mechanism opening **2217**, a guide member opening **2218**, and a cam pulley opening **2219**, a cam pivot opening **2220**. As described in further detail herein, the drive mechanism openings **2213** receive at least a portion of a first drive assembly **2310** included in the drive mechanism **2300** such that a set of wheels included therein can rotate without contacting the base **2210**. The fan opening **2214** receives a portion of a fan **2740** included in the electronic system **2700**. More specifically, a portion of the fan **2740** can extend through the opening such that the fan can remove heat from within the housing **2200** produced by the electronic system **2700**. The guide mechanism opening **2215** receives a portion of a guide mechanism **2540** included in the patient support mechanism **2500** (also referred to herein as “support mechanism”). More specifically, the base **2210** includes a set of mounting tabs **2216** configured to extend from a surface of the base **2210** that defines the guide mechanism opening **2215**. In this manner, the guide mechanism **2540** can be coupled to the mounting tabs **2216**. The bias mechanism opening **2217**, the guide member opening **2218**, the cam pulley opening **2219**, and the cam pivot opening **2220** can each movably receive a portion of a cam mechanism **2570** included in the support mechanism **2500**, as described in further detail herein.

13

The first side member **2230** has a first side **2231** and a second side **2232**. The second side **2232** defines a slot **2233** that receives a portion of the base **2210** to couple the base **2210** thereto. The first side member **2230** also includes a mounting portion **2235** that is coupled to a portion of a collector **2770** included in the electronic system **2700**, as described in further detail herein. The second side member **2240** has a first side **2241** and a second side **2242**. The second side **2242** defines a slot **2243** that receives a portion of the base **2210** to couple the base **2210** thereto. The second side **2242** also includes a recessed portion **2244** that is coupled to a portion of a winch assembly **2510** included in the support mechanism **2500**. The third side member **2250** is coupled to the first side member **2230**, the second side member **2240**, and the base **2210** and defines a light opening **2251** that receives an indicator light and a power outlet opening that receives a power outlet module.

The cover **2260** is disposed adjacent to the second side **2212** of the base **2210**. More specifically, the cover **2260** can be removably coupled to the second side **2212** of the base **2210** such that the portion of the electronic system **2700** enclosed therein can be accessed. The cover **2260** has a first end portion **2261** and a second end portion **2262**. The first end portion **2261** is open-ended and defines a notch **2265** configured to receive a portion of the collector **2770**, as described in further detail herein. The second end portion **2262** of the cover **2260** is substantially enclosed and is configured to include a recessed region **2264**. In this manner, a portion of the support mechanism **2500** can extend into and/or through the recessed region **2264** to couple to the patient attachment mechanism **2800**, as described in further detail herein. The cover **2260** also defines a set of vents **2263** that can be arranged to provide a flow of air into the area enclosed by the cover **2260** such that at least a portion of the electronic system **2700** disposed therein can be cooled.

FIGS. **10** and **11** illustrate the electronic system **2700** of the trolley **2100**. The electronic system **2700** includes a set of electronic devices that are collectively operated to control at least a portion of the trolley **2100**. As described above, the electronic system **2700** includes the collector **2770** that is coupled to a portion of the housing **2200** and that is placed in physical and/or electrical contact with the power rail **2620**. The collector **2770** can be any suitable shape, size, or configuration and can be formed from any suitable conductive material, such as, for example, iron, steel, or the like. In this manner, the collector **2770** can receive a flow of electrical current from the power rail **2620**. For example, as shown in FIG. **10**, the power rail **2620** is a substantially hollow tube that houses or substantially encloses one or more conductive portions **2621** (e.g., individual conductors or surfaces) that are electrically coupled to a power source (not shown). In this manner, the collector **2770** can be disposed within the hollow tube of the power rail **2620** such that a conductive portion **2771** (e.g., individual conductors, a conductive surface, or the like) of the collector **2770** is placed in electrical communication with the one or more conductive portions **2621** of the power rail **2620**. Thus, the collector **2770** receives a flow of current from the power source and transferred by the power rail **2620**. Moreover, the collector **2770** can be disposed within the power rail **2620** such that a coupling portion **2772** of the collector **2770** extends through a slot **2622** defined by the power rail **2620** to be coupled to the mounting portion **2235** of the housing **2200**. The coupling portion **2772** can further be coupled to a power module (not shown) of the trolley **2100**. Thus, the trolley **2100** receives power from the power source via the power rail **2620**.

14

While not shown in FIGS. **10** and **11**, the electronic system **2700** includes at least a processor, a memory, and a communication device. The memory can be, for example, a random access memory (RAM), a memory buffer, a hard drive, a read-only memory (ROM), an erasable programmable read-only memory (EPROM), and/or the like. In some embodiments, the memory stores instructions to cause the processor to execute modules, processes, and/or functions associated with controlling one or more mechanical and/or electrical systems included in the patient support system **2000**. For example, the memory can store instructions, information, and/or data associated with a proportion-integral-derivative (PID) control system. In some embodiments, the PID control system can be included in, for example, a software package. In some embodiments, the PID control can be a set of user controlled instructions executed by the processor that allow the user to “tune” the PID control, as described in further detail herein.

The processor of the electronic device can be any suitable processing device configured to run or execute a set of instructions or code. For example, the processor can be a general purpose processor (GPU), a central processing unit (CPU), an accelerated processing unit (APU), and/or the like. The processor can be configured to run or execute a set of instructions or code stored in the memory associated with controlling one or more mechanical and/or electrical systems included in a patient support system. For example, the processor can run or execute a set of instructions or code associated with the PID control stored in the memory and further associated with controlling with a portion of the drive system **2300** and/or the patient support mechanism **2500**. More specifically, the processor can execute a set of instructions in response to receiving a signal from one or more sensors and/or encoders (shown and described below) that can control one or more subsequent actions of the drive system **2300** and/or the support mechanism **2500**. Similarly stated, the processor can execute a set of instructions associated with a feedback loop that includes one or more sensors or encoders that send a signal that is at least partially associated with current and/or previous data (e.g., position, velocity, force, acceleration, or the like) received from the drive system **2300** and/or the support mechanism **2500**, as described in further detail herein.

The communication device can be, for example, one or more network interface devices (e.g., network cards) configured to communicate with an electronic device over a wired or wireless network. For example, in some embodiments, a user can manipulate a remote control device that sends one or more signals to and/or receives one or more signals from the electronic system **2700** associated with the operation of the trolley **2100**. The remote control can be any suitable device or module (e.g., hardware module or software module stored in the memory and executed in the process). For example, in some embodiments, the remote control can be an electronic device that includes at least a processor and a memory and that runs, for example, a personal computer application, a mobile application, a web page, and/or the like. In this manner, a user can engage the remote control to establish a set of system parameters associated with the support system **2000** such as, for example, the desired amount of body weight supported by the support system **2000**.

As shown in FIG. **12**, the drive system **2300** includes a first drive assembly **2310** and a second drive assembly **2400**. The drive system **2300** is coupled to the first side **2211** of the base **2210** (see e.g., FIGS. **2** and **3**) and arranged such that the first drive assembly **2310** and the second drive assembly

15

2400 are aligned (e.g., coaxial). In this manner, the first drive assembly 2310 and the second drive assembly 2400 can receive a portion of the support track 2050, as described in further detail herein.

FIGS. 13-23 illustrate the first drive assembly 2310. The first drive assembly 2310 includes a motor 2311, a support structure 2315, a set of guide wheel assemblies 2360, a set of drive wheel assemblies 2370, and a set of secondary wheel assemblies 2390. The motor 2311 is coupled to a side member 2320 of the support structure 2315 and is in electrical communication with a portion of the electronic system 2700. The motor 2311 includes an output shaft 2312 (see e.g., FIGS. 15 and 16) that engages a portion of one of the drive wheel assemblies 2370 to rotate a drive wheel 2385 included therein. More specifically, the motor 2311 receives an activation signal (e.g., a flow of electrical current) from the electronic system 2700 to cause the motor 2311 to rotate the output shaft 2312 which, in turn, rotates the drive wheel 2385. As shown in FIGS. 13 and 14, at least a portion of the first drive assembly 2310 is substantially symmetrical about a longitudinal plane (not shown) defined by the first drive assembly 2310. In this manner, each side of the first drive assembly 2310 includes similar components, thereby increasing versatility and decreasing manufacturing costs. For example, while the first drive assembly 2310 is shown including two side members 2320 with the motor 2311 being coupled to a particular side member 2320, in other embodiments, the motor 2311 can be coupled to the other side member 2320.

The support structure 2315 includes two side members 2320, a base 2340, two leading support members 2350, two trailing support members 2354, and two transverse support members 2358. As shown in FIGS. 13-16, the side members 2320 are the same (e.g., due to the symmetry of the first drive assembly 2310). The side members 2320 each define a bearing opening 2321, a notch 2322, and a set of slots 2325. The bearing opening 2321 of each side member 2320 receives a drive bearing 2376 (FIG. 20) included in the drive wheel assembly 2370. More specifically, the drive bearing 2376 can be disposed within the bearing opening 2321 such that an outer surface of the drive bearing 2376 forms a friction fit with a surface of the side member 2320 that defines the bearing opening 2321. Similarly stated, the drive bearing 2376 and the surface of the side 2320 defining the bearing opening 2321 form a press fit to retain the drive bearing 2376 within the bearing opening 2321.

The notch 2322 defined by each of the side members 2320 receives a spring rod 2323 and a spring 2324. The spring 2324 is disposed about the spring rod 2323 such that the spring rod 2323 substantially limits the motion of the spring 2324. More specifically, the spring rod 2323 is configured to allow the spring 2324 to move in an axial direction (e.g., compress and/or expand) while substantially limiting movement of the spring 2324 in a transverse direction. As described in further detail herein, the spring rod 2323 and the spring 2324 extend from a surface of the notch 2322 to engage a spring protrusion 2344 of the base 2340. The set of slots 2325 is configured such that each slot 2325 receives mounting hardware (e.g., a mechanical fastener, a pin, a dowel, etc.) configured to movably couple the side members 2320 to the base 2340, as described in further detail herein.

As described above, the base 2340 is movably coupled to the side members 2320. The base 2340 includes a set of side walls 2342, and an axle portion 2346. The axle portion 2346 of the base 2340 defines an opening 2347 that receives a transfer axle 2388 included in the drive wheel assembly 2370. More specifically, the transfer axle 2388 can rotate

16

within the opening 2347 of the axle portion 2346 such that a rotational motion can be transferred from one of the drive assemblies 2370 to the other drive assembly 2370, as described in further detail herein.

The side walls 2342 each define a notch 2343 and include the spring protrusion 2344. More specifically, the spring protrusions 2344 each extend in a substantially perpendicular direction from the side walls 2342. As shown in FIGS. 13 and 14, when the side members 2320 are coupled to the base 2340, the notches 2322 of the side members 2320 each receive one of the spring protrusions 2344 of the base 2340. Similarly, when the side members 2320 are coupled to the base 2340, the notches 2343 defined by the base 2340 each receive a portion of one of the springs 2324. In this manner, the spring rod 2323 and the spring 2324 of each side member 2320 are aligned with the spring protrusion 2344 extending from the side walls 2342 of the base 2340 such that the spring 2324 is placed in contact with a surface of the corresponding spring protrusion 2344. With the side members 2320 movably coupled to the base 2340 (e.g., by disposing the mounting hardware in the slots 2325), the spring 2324 of each side member 2320 can dampen a movement of the side member 2320 relative to the base 2340. Similarly stated, the spring 2324 of each side member 2320 can engage the surface of the corresponding spring protrusion 2344 to exert a reaction force (e.g., brought on by a compression of the spring) in response to an external force (e.g., operational vibration, torque exerted by the motor, or the like) applied to one or both of the side members 2320.

FIGS. 17-19 illustrate one of each of the leading support members 2350, the trailing support members 2354, and the transverse support members 2358, respectively. As described above, the symmetry of the first drive assembly 2310 is such that the two leading support member 2350 are the same, the two trailing support members 2354 are the same, and the two transverse support members 2358 are the same. The leading support members 2350 are each fixedly coupled to one of the side members 2320. As shown in FIG. 17, the leading support members 2350 each define a lever arm notch 2355 that receives a lever arm 2391 of the secondary wheel assembly 2390, a spring recess 2352 that receives a spring 2394 of the secondary wheel assembly 2390, and a support track notch 2353 that receives, for example, a horizontal portion 2051 of the support track 2050 (see e.g., FIG. 23).

The trailing support members 2354 are each fixedly coupled to one of the side members 2320 and are disposed in a rearward position relative to the leading support members 2354. Expanding further, the trailing support members 2354 are spaced apart from the leading support members 2354 at a distance sufficiently large to allow a portion of the drive wheel assemblies 2370 to be disposed therebetween. As shown in FIG. 18, the trailing support members 2354 each define a belt notch 2355 configured to receive a drive belt 2389 of the drive wheel assembly 2370 and a support track notch 2353 configured to receive the horizontal portion 2051 of the support track 2050 (e.g., as described with reference to the leading support member 2350).

The transverse support members 2358 are each fixedly coupled to one of the leading support members 2350 and one of the trailing support members 2354. Therefore, with the leading support members 2350 and the trailing support members 2354 each coupled to the corresponding side member 2320, the transverse support member 2358 substantially encloses a space configured to house or receive a portion of the drive wheel assemblies 2370. Furthermore, the arrangement of the support structure 2315 is such that a

space defined between adjacent surfaces of the transverse support member **2358** is sufficiently large to receive, for example, a vertical portion **2052** of the support track **2050**.

As shown in FIG. **19**, the transverse support member **2358** defines a bearing opening **2359** that receives a support bearing **2377** of the drive wheel assemblies **2370**. More specifically, the support bearing **2377** is disposed within the bearing opening **2359** such that an outer surface of the support bearing **2377** forms a friction fit with a surface of the transverse support member **2358** that defines the bearing opening **2359**. Similarly stated, the outer surface of the support bearing **2377** and the surface of the transverse support member **2358** form a press fit to retain the support bearing **2377** within the bearing opening **2359**.

Referring back to FIGS. **13-15**, the first drive assembly **2310** includes four guide wheel assemblies **2360**. The guide wheel assemblies **2360** each include a mounting bracket **2361** and a guide wheel **2363**. More specifically, each of the guide wheels **2363** are rotatably coupled to one of the mounting brackets **2361** such that the guide wheels **2363** can rotate relative to the mounting brackets **2361**.

The guide wheel assemblies **2360** are each configured to be coupled to a portion of the support structure **2315**. Expanding further, as shown in FIGS. **13-16**, the mounting bracket **2361** of each guide wheel assembly **2360** is coupled to one of the leading support members **2350** or one of the trailing support members **2354**. Similarly stated, both of the leading support members **2350** are coupled to the mounting bracket **2361** included in one of the guide wheel assemblies **2360** and both of the trailing support members **2354** are coupled to the mounting bracket **2361** included in one of the guide wheel assemblies **2360**. The guide wheel assemblies **2360** are coupled to the support structure **2315** such that a portion of the guide wheel **2363** extends into the space defined between the transverse members **2358**. In this manner, the guide wheels **2363** can roll along a surface of the vertical portion **2052** of the support track **2050** when the first drive assembly **2310** is coupled thereto (see e.g., FIG. **23**).

As shown in FIGS. **13-15**, the guide wheel assemblies **2360** can be arranged relative to the support structure **2315** such that the guide wheels **2363** included in the guide wheel assemblies **2360** that are coupled to the leading support member **2350** are disposed substantially below the mounting bracket **2361**. Conversely, the guide wheels **2363** included in the guide wheel assemblies **2360** that are coupled to the trailing support member **2350** are disposed substantially above the mounting bracket **2361**. This arrangement can increase the surface area of the vertical portion **2051** of the support track **2050** that is in contact with at least one guide wheel **2360**. In this manner, a rotational motion about a longitudinal centerline (not shown) of the support track **2050** can be minimized or eliminated. While shown in as being in a particular arrangement, in other embodiments, the guide wheels **2363** can be arranged in any suitable manner. For example, in some embodiments, all the guide wheels **2363** can be mounted below the mounting brackets **2361**. In other embodiments, all the guide wheels **2363** can be mounted above the mounting brackets **2361**. In still other embodiments, the guide wheels **2363** can be mounted to the mounting brackets **2361** in any combination of configurations (e.g., mounted above or below the mounting brackets **2361** in any suitable arrangement).

FIG. **20** is an exploded view of the drive wheel assembly **2370**. As described above, the symmetry of the first drive assembly **2310** is such that the drive wheel assemblies are the same. Thus, a discussion of the drive wheel assembly **2370** shown in FIG. **20** applies to both drive wheel assem-

blies **2370**. The drive wheel assembly **2370** includes a drive shaft **2371**, the drive bearing **2376**, the support bearing **2377**, a drive sprocket **2379**, a transfer sprocket **2381**, a drive wheel **2385**, the transfer axle **2388** (not shown in FIG. **20**), and a drive belt **2389**. The drive shaft **2371** has a first portion **2372**, a second portion **2373**, and a third portion **2374** and defines an opening **2375**. The first portion **2372** has a first diameter that is at least partially associated with the drive sprocket **2378**. Expanding further, the drive sprocket **2378** defines an opening **2380** that has a diameter that is associated with the diameter of the first portion **2372** of the drive shaft **2371**. In this manner, the drive sprocket **2378** is disposed about the first portion **2372** of the drive shaft **2371** such that a surface of the drive sprocket **2378** defining the opening **2380** forms a friction fit with an outer surface of the first portion **2372** of the drive shaft **2371**. Similarly, the drive bearing **2376** is disposed about the first portion **2372** such that an inner surface of the bearing forms a friction fit with the outer surface of the second portion **2372** of the drive shaft **2371**. Thus, a rotation of the drive shaft **2371** within the drive bearing **2376** rotates the drive sprocket **2378**. Moreover, with the drive bearing **2376** being retained with the bearing opening **2321** of one of the side member **2370**, the drive shaft **2371** can be rotated relative to the corresponding side member **2370**, as described in further detail herein.

The second portion **2373** of the drive shaft **2371** has a second diameter that is smaller than the diameter of the first portion **2372** and that is at least partially associated with the drive wheel **2385**. Expanding further, the drive wheel **2385** includes a hub **2386** that defines an opening **2387** with a diameter that is associated with the diameter of the second portion **2373** of the drive shaft **2371**. As shown in FIG. **20**, the opening **2387** of the drive wheel **2385** includes a keyway configured to receive a key that extends from an outer surface of the second portion **2373** of the drive shaft **2371**. In this manner, the drive wheel **2385** is fixedly disposed about the second portion **2373** of the drive shaft **2371**.

The third portion **2374** of the drive shaft **2371** has a third diameter that is smaller than the diameter of the second portion **2372** and that is at least partially associated with the support bearing **2377**. Expanding further, the support bearing **2377** is disposed about the third portion **2374** of the drive shaft **2371** such that an outer surface of the third portion **2374** forms a friction fit with an inner surface of the support bearing **2377**. Moreover, with the support bearing **2377** being disposed within the bearing opening **2359** of the transverse support member **2358**, the third portion **2374** of the drive shaft **2371** can be at least partially supported.

The opening **2375** defined by the drive shaft **2371** receives the output shaft **2312** of the motor **2311**. More specifically, the drive shaft **2371** can be fixedly coupled, at least temporarily, to the output shaft **2312** of the motor **2311**; thus, when the output shaft **2312** is rotated (e.g., in response to an activation signal from the electronic system **2700**), the drive shaft **2371** is concurrently rotated. With the drive bearing **2376** and the support bearing **2377** being disposed within the bearing opening **2321** of the side member **2320** and the bearing opening **2359** of the transverse support member **2358**, respectively, the drive shaft **2371** can rotate relative to the support structure **2315**. Moreover, the rotation of the drive shaft **2371** rotates both the drive sprocket **2378** and the drive wheel **2385**.

The drive sprocket **2378** is configured to engage the belt **2389**. More specifically, the drive sprocket **2389** includes a set of teeth **2379** that engage a set of teeth (not shown) that extend from an inner surface of the belt **2389**. The belt **2389**

19

is further coupled the transfer sprocket **2381**. The transfer sprocket **2381** includes a set of teeth **2382** that engage the teeth of the belt **2389**. In this manner, the rotation of the drive sprocket **2378** (described above) rotates the belt **2389**, which, in turn, rotates the transfer sprocket **2381**. The transfer sprocket **2381** defines an opening **2383** configured to receive the transfer axle **2388** (see e.g., FIG. 16). More specifically, the transfer axle **2388** can be fixedly coupled to the transfer sprockets **2381** of each drive wheel assembly **2370** such that a rotation of the transfer sprocket **2381** of the first drive wheel assembly **2370** (e.g., the drive wheel assembly **2370** coupled to the output shaft **2312** of the motor **2311**) rotates the transfer sprocket **2381** of the second drive wheel assembly **2370**. Thus, when the motor **2311** is activated to rotate the output shaft **2312**, both the drive wheels **2385** of both the drive wheel assemblies **2370** are urged to rotate.

In some embodiments, the side members **2320** and the base **2340** of the support structure **2315** can be arranged such that the spring **2324** of the side members **2320** is in a preloaded configuration (e.g., partially compressed without an additional external force being applied to one or both of the side members **2320**). More specifically, each spring **2324** can exert a force (e.g., due to the preload) on the surface of the corresponding spring protrusion **2344** of the base **2340** to place the corresponding side member **2320** in a desired position relative to the base **2340**. Moreover, with the drive bearings **2376** fixedly disposed within the bearing opening **2321** of the corresponding side members **2320** and with the transfer axle **2388** being disposed within the opening **2347** defined by the axle portion **2346** of the base **2340**, the belt **2379** disposed about the drive sprocket **2378** and the transfer sprocket **2381** can be placed in tension. Thus, the arrangement of the side members **2320** being movably coupled to the base **2340** can retain the belt **2379** in a suitable amount tension such that the belt **2379** does not substantially slip along the teeth **2379** of the drive sprocket **2378** and/or along the teeth **2382** of the transfer sprocket **2381**.

As shown in FIG. 21, the first drive assembly **2310** includes the secondary wheel assembly **2390**. The secondary wheel assembly **2390** includes a lever arm **2391**, a secondary wheel **2393**, and a spring **2394**. The lever arm **2391** is a substantially angled member that includes an axle portion **2392**, a pivot portion **2395**, and an engagement portion **2396**. The axle portion **2392** is disposed at a first end of the lever arm **2391** and is movably coupled to the secondary wheel **2393** such that the secondary wheel **2393** rotates about the axle portion **2392**. The pivot portion **2395** is movably coupled to a portion of the leading support member **2350** that defines the lever arm notch **2351**. For example, in some embodiments, the pivot portion **2395** of the lever arm **2391** can include an opening configured to receive, for example, a pivot pin (not shown) included in the leading support member **2350**. In this manner, the pivot pin can define an axis about which the pivot portion **2395** can pivot or rotate.

The engagement portion **2396** is configured to engage a portion of the spring **2394**. More specifically, as shown in FIG. 22, a first end portion of the spring **2394** is in contact with the spring recess **2352** defined by the leading support member **2350** and a second end portion of the spring **2394** is in contact with the engagement portion **2396**. In this manner, the spring **2394** can exert a force on the engagement portion **2396** to pivot the lever arm **2391** about the pivot portion **2395**. Expanding further, as shown in FIG. 22, the force exerted by the spring **2394** can pivot the lever arm **2391** such that the secondary wheel **2393** is pivoted towards

20

the drive wheel **2385**. Therefore, when the first drive assembly **2310** is disposed about the support track **2050**, the secondary wheel **2393** can be placed in contact with a bottom surface of the horizontal portion **2051** of the support track **2050**. Moreover, the force exerted by the spring **2394** can be such that the drive wheel **2385** and the secondary wheel **2393** exert a compressive force on a top surface and the bottom surface, respectively, of the horizontal portion **2051** of the support track **2051**. This arrangement can, for example, increase the friction between the drive wheel **2385** and the horizontal portion **2051** of the support track **2050**.

FIGS. 24-26 illustrate the second drive assembly **2400**. The second drive assembly **2400** can function similarly to the first drive assembly **2310**, thus, some portions of the second drive assembly **2400** are not described in further detail herein. The second drive assembly **2400** includes a support structure **2405**, a set of guide wheel assemblies **2430**, a set of primary wheel assemblies **2440**, a coupler **2460**, and an encoder **2470**. As shown, at least a portion of the second drive assembly **2400** is substantially symmetrical about a longitudinal plane (not shown) defined by the second drive assembly **2400**. In this manner, each side of the second drive assembly **2400** includes similar components, thereby increasing versatility and decreasing manufacturing costs. For example, while the second drive assembly **2400** is shown including two side members **2420** with the coupler **2460** and encoder **2470** being coupled to a particular side member **2420**, in other embodiments, the coupler **2460** and encoder **2470** can be coupled to the other side member **2420**.

The support structure **2405** includes two side members **2410**, a base **2420**, a set of leading support members **2431**, a set of trailing support members **2432**, and a set of transverse support members **2433**. As shown in FIGS. 24-26, the side members **2410** are the same (e.g., due to the symmetry of the first drive assembly **2400**). The side members **2410** each define a bearing opening **2411** that receives a bearing **2454** (FIG. 25) included in the drive wheel assembly **2470**. More specifically, the bearing **2454** can be disposed within the bearing opening **2411** such that an outer surface of the drive bearing **2454** forms a friction fit with a surface of the side member **2410** that defines the bearing opening **2411**. Similarly stated, the drive bearing **2454** and the surface of the side **2410** defining the bearing opening **2411** form a press fit to retain the drive bearing **2454** within the bearing opening **2411**.

The base **2420** is configured to be fixedly coupled to the side members **2410**. The base **2420** includes a mounting plate **2421** configured to extend from a top surface and from a bottom surface of the base **2420** to couple the second drive assembly **2400** to the base **2210** of the housing **2200** (e.g., via any suitable mounting hardware such as, for example, mechanical fasteners or the like). The arrangement of the mounting plate **2421** can be such that when the second drive assembly **2400** is disposed about the support track **2050**, the mounting plate **2421** can substantially limit a movement of the second drive mechanism **2400** in transverse direction relative to the longitudinal centerline (not shown) of the support track **2050**. In some embodiments, the mounting plate **2421** can include any suitable surface finish that can be sufficiently smooth to slide along a bottom surface of the horizontal portion **2051** of the support track **2050**. In other embodiments, the mounting plate **2421** can be formed from a material such as, for example, nylon or the like that facilitates the sliding of the mounting plate **2421** along the bottom surface of the support track **2050**.

The leading support members **2431**, the trailing support members **2432**, and the transverse support members **2433**

21

can be arranged similar to the leading support members 2350, the trailing support members 2354, and the transverse support members 2358 described above with reference to FIGS. 17-19. In this manner, the side members 2410 and the support members 2431, 2432, and 2433 can define a space configured to substantially enclose at least a portion of the primary wheel assemblies 2440. Moreover, the transverse support members 2433 can define an opening configured to receive a bearing 2454 of the primary wheel assembly 2350 in a similar manner as the transverse member 2333 described above. As shown in FIGS. 24-26, the leading support members 2431, the trailing support members 2432, and the transverse support members 2433 can differ, however, in that the leading support members 2431, the trailing support members 2432, and the transverse support members 2433 need not include one or more notches and/or recesses to accommodate any portion of the second drive assembly 2400.

The first drive assembly 2400 includes four guide wheel assemblies 2440. The guide wheel assemblies 2440 each include a mounting bracket 2441 and a guide wheel 2443. More specifically, each of the guide wheels 2443 are rotatably coupled to one of the mounting brackets 2441 such that the guide wheels 2443 can rotate relative to the mounting brackets 2441. The guide wheel assemblies 2440 are each configured to be coupled to a portion of the support structure 2405. Expanding further, as shown in FIGS. 24-26, the mounting bracket 2441 of each guide wheel assembly 2440 is coupled to one of the leading support members 2431 or one of the trailing support members 2432. Similarly stated, both of the leading support members 2431 are coupled to the mounting bracket 2441 included in one of the guide wheel assemblies 2440 and both of the trailing support members 2432 are coupled to the mounting bracket 2441 included in one of the guide wheel assemblies 2440. The guide wheel assemblies 2440 are coupled to the support structure 2405 such that a portion of the guide wheel 2443 extends into the space defined between the transverse members 2433. In this manner, the guide wheels 2443 can roll along a surface of the vertical portion 2052 of the support track 2050 when the second drive assembly 2400 is coupled thereto (see e.g., FIG. 26). As described above with reference to the first drive assembly 2310, the guide wheel assemblies 2440 can be arranged in any suitable configuration to limit a rotational movement of the second drive assembly 2400 about the longitudinal centerline of the support track 2050.

The primary wheel assemblies 2450 each include a primary wheel 2451 having a hub 2452 and an axle 2453, and the bearings 2454. As described above, the axle 2453 can be disposed within the bearings 2354 while the bearings 2354 are coupled to the side members 2410 and the transverse members 2433. In this manner, each primary wheel 2451 can rotate about the corresponding axle 2453 relative to the support structure 2405. As shown in FIG. 26, the second drive assembly 2400 is disposed about the support track 2050 such that the primary wheels 2451 roll along the top surface of the horizontal portion 2051. Similarly, the guide wheels 2443 roll along a surface of the vertical portion 2052 of the support track 2050.

As shown in FIGS. 24 and 26, the axle 2453 is configured to extend through the bearing 2454 disposed within the opening 2411 of the side members 2410. In this manner, the coupler 2460 can couple to the axle 2453 to couple the axle 2453 to the encoder 2470. Thus, the encoder 2470 can receive and/or determine information associated with the rotation of the primary wheel 2451. For example, the encoder 2470 can determine position, rotational velocity,

22

rotational acceleration, or the like. Furthermore, the encoder 2470 can be in electrical communication (e.g., via a wired communication or a wireless communication) with a portion of the electronic system 2700 and can send information associated with the second drive assembly 2400 to the portion of the electronic system 2700. Upon receiving the information from the encoder 2470, a portion of the electronic system 2700 can send a signal to any other suitable system associated with performing an action (e.g., increasing or decreasing the power of one or more motors or the like), as described in further detail herein. In some instances, the electronic system 2700 can determine the position of the trolley 2100 relative to the support track 2050 based at least in part on the information sent from the encoder 2470 associated with the second drive assembly 2400. In such instances, a user (e.g., doctor, physician, nurse, technician, or the like) can input a set of parameters associated with a portion of the support track 2050 along which the trolley 2100 moves. In this manner, the user can define a desired path along the support track 2050 for a therapy session.

FIGS. 27-33 illustrate the support mechanism 2500 included in the trolley 2100. As shown in FIG. 27, the support mechanism 2500 includes a tether 2505, a winch assembly 2510, a guide mechanism 2540, a first pulley 2563, a second pulley 2565, and a cam mechanism 2570. The tether 2505 can be, for example, a rope or other long flexible member that can be formed from any suitable material such as nylon or other suitable polymer. The tether 2505 includes a first end portion 2506 that is coupled to a portion of the winch assembly 2510 and a second end portion 2507 that can be coupled to any suitable patient attachment mechanism such as, for example, the patient attachment mechanism 2800 shown in FIG. 34. The tether 2505 is configured to engage a portion of the winch assembly 2510, the guide mechanism 2540, the cam mechanism 2570, the first pulley 2563, and the second pulley 2565 such that the support mechanism 2500 actively supports at least a portion of the body weight of a patient, as described in further detail herein.

As shown in FIGS. 29 and 30, the winch assembly 2510 includes a motor 2511, a mounting flange 2515, a coupler 2520, a drum 2525, and encoder assembly 5230. The motor 2511 is coupled to the coupler 2520 and is in electrical communication with a portion of the electronic system 2700. The motor 2511 includes an output shaft 2512 that engages an input portion (not shown) of the coupler 2520 such that rotation of the output shaft 2512 of the motor 2511 rotates an output member 2521 of the coupler 2520. More specifically, the motor 2511 receives an activation signal (e.g., a flow of electrical current) from the electronic system 2700 to cause the motor 2511 to rotate the output shaft 2512 in a first rotational direction or in a second rotational direction, opposite the first rotational direction. The output shaft 2512, in turn, rotates the output member 2521 of the coupler 2520 in the first rotational direction or the second rotational direction, respectively.

The mounting flange 2515 is disposed about a portion of the coupler 2520 and includes a portion that can be coupled to the third side member 2250 of the housing 2200. In this manner, the motor 2511 is supported by the mounting flange 2515 and the housing 2200. The output member 2521 of the coupler 2520 is coupled to a mounting plate 2522 of the drum 2525 such that when the output shaft 2512 of the motor 2511 is rotated in the first direction or the second direction, the drum 2525 is rotated in first direction or the second direction, respectively. While not shown, in some embodiments, the coupler 2520 can include one or more gears that

23

can be arranged in any suitable manner to define a desirable gear ratio. In this manner, the rotation of the output shaft **2512** can be in the first direction or the second direction with a first rotational velocity and the rotation of the drum **2525** can be in the first direction or the second direction, respectively, with a second rotational velocity that is different from the first rotational velocity of the output shaft **2525** (e.g., a greater or lesser rotational velocity). In some embodiments, the coupler **2520** can include one or more clutches that can be configured to reduce and/or dampen an impulse (i.e., a force) that can result from the electronic system **2700** sending a signal to the motor **2511** that is associated with changing the rotational direction of the output shaft **2512**.

The drum **2525** is disposed between the mounting plate **2522** and an end plate **2529**. As described in further detail herein, an encoder drum **2531** of the encoder assembly **2530** is coupled to the end flange **2529** such that a least a portion of the encoder assembly **2530** is disposed within an inner volume **2528** defined by the drum **2525**. The drum **2525** has an outer surface **2526** that defines a set of helical grooves **2527**. The helical grooves **2527** receive a portion of the tether **2505** and define a path along which the tether **2505** can wrap to coil and/or uncoil around the drum **2525**. For example, the motor **2511** can receive a signal from the electronic system **2700** to rotate the output shaft **2512** in the first direction. In this manner, the drum **2525** is rotated in the first direction and the tether **2505** can be, for example, coiled around the drum **2525**. Conversely, the motor **2511** can receive a signal from the electronic system **2700** to rotate the output shaft **2512** in the second direction, thus, the drum is rotated in the second direction and the tether **2505** can be, for example, uncoiled from the drum **2525**.

The encoder assembly **2530** includes the encoder drum **2531**, a mounting flange **2532**, a bearing bracket **2533**, a bearing **2535**, a coupler **2536**, an encoder **2537**, and an encoder housing **2538**. As described above, a first end portion of the encoder drum **2531** is coupled to the end flange **2529** of the drum **2525** such that a portion of the encoder assembly **2530** is disposed within the inner volume **2528** of the drum **2525**. The mounting flange **2532** is coupled to a second end portion of the encoder drum **2531** and is further coupled to the bearing bracket **2533**. The bearing bracket **2533** includes an axle **2534** about which the bearing **2535** is disposed. The coupler **2536** is coupled to the axle **2534** of the bearing bracket **2533** and is configured to couple the encoder **2537** to the bearing bracket **2533**. As shown in FIG. 28, the coupler **2536** and the encoder **2537** are disposed within the encoder housing **2538**. More specifically, the coupler **2536** is movably disposed within the encoder housing **2538** and the encoder **2537** is fixedly coupled to the encoder housing **2538**. Moreover, a first end portion of the encoder housing **2538** is disposed about the bearing **2535** and a second end portion of the encoder housing **2538** is in contact with and fixedly coupled to the recessed portion **2244** of the second side member **2240** of the housing **2240**. In this manner, the encoder drum **2531**, the mounting flange **2532**, the bearing bracket **2533**, and the coupler **2536** are configured to rotate concurrently with the drum **2525**, relative to the encoder **2537** and the encoder housing **2538**. Thus, the encoder **2537** can receive and/or determine information associated with the rotation of the drum **2525**. For example, the encoder **2537** can determine position, rotational velocity, rotational acceleration, feed rate of the tether **2505**, or the like. Furthermore, the encoder **2537** can be in electrical communication (e.g., via a wired communication or a wireless communication) with a portion of the electronic system **2700** and can send information

24

associated with the winch assembly **2510** to the portion of the electronic system **2700**. Upon receiving the information from the encoder **2537**, a portion of the electronic system **2700** can send a signal to any other suitable system associated with performing an action (e.g., increasing or decreasing the power of one or more motors or the like), as described in further detail herein.

Referring back to FIG. 27, the guide mechanism **2540** of the support mechanism **2500** is at least partially disposed within the guide mechanism opening **2215** of the base **2210** included in the housing **2200**. More specifically, the guide mechanism **2540** includes a set of mounting brackets **2541** that are coupled to the mounting tabs **2216** of the base **2210**. In this manner, at least a portion of the guide mechanism **2540** is suspended within the guide mechanism opening **2215**. As shown in FIG. 31, the guide mechanism **2540** includes the mounting brackets **2541**, a guide drum assembly **2545**, a stopper bracket **2550**, a stopper **2551**, a roller assembly **2554**, a coupler **2559**, a support bracket **2560**, and an encoder **2561**. As described above, the mounting brackets **2541** are coupled to the mounting tabs **2216** of the base **2210**. The mounting brackets **2541** each include a first mounting portion **2542** that is movably coupled to a portion of the guide drum assembly **2545**, a second mounting portion **2543** that is fixedly coupled to the stopper bracket **2550**, and a pivot portion **2544** that is movably coupled to a portion of the roller assembly **2554**. The stopper bracket **2550** is further coupled to the stopper **2551** and is configured to limit a movement of the guide drum assembly **2545** relative to the mounting brackets **2541**.

The guide drum assembly **2545** includes a guide drum **2546**, a set of pivot plates **2547**, and a stopper plate **2549**. The guide drum **2546** is movably coupled to the pivot plates **2547**. For example, while not shown in FIG. 31, the pivot plates **2547** can each include an opening configured to receive an axle about which the guide drum **2546** can rotate. The pivot plates **2547** each include a pivot axle **2548** that can be disposed within an opening (not shown) defined by the first mounting portion **2542** of the mounting brackets **2541**. In this manner, the guide drum assembly **2545** can pivot about the pivot axles **2548** relative to the mounting brackets **2541**. The stopper plate **2549** is coupled to the pivot plates **2547** and is configured to engage a portion of the stopper **2551** to limit the pivoting motion of the guide drum assembly **2545** relative to the mounting brackets **2541**. More specifically, with the stopper bracket **2550** fixedly coupled to the mounting brackets **2541** and to the stopper **2551**, the guide drum assembly **2545** can pivot toward the stopper bracket **2550** (e.g., in response to a force exerted on tether **2505**, as described in further detail herein) such that the stopper plate **2549** is placed in contact with the stopper **2551**. The stopper **2551** can be any suitable shape, size, or configuration. For example, in some embodiments, the stopper **2551** can be an elastomeric member configured to absorb a portion of a force exerted by the guide drum assembly **2545** when the stopper plate **2549** is placed in contact with the stopper **2551**.

The roller assembly **2554** includes a set of swing arms **2555** and a set of rollers **2558**. The swing arms **2555** include a first end portion **2556** and a second end portion **2557**. The first end portion **2556** of the swing arms **2555** are movably coupled to the rollers **2558**. More specifically, the rollers **2558** can be arranged such that a spaced defined between the rollers **2558** can receive a portion of the tether **2505**. Thus, when the tether **2505** is moved relative to the rollers **2558**, the rollers **2558** can rotate relative to the swing arms **2555**.

25

The second end portion **2557** of the swing arms **2555** are coupled to the pivot portion **2543** of the mounting brackets **2541**. For example, as shown in FIG. **31**, the pivot portion **2543** can include a set of axles disposed within a bearing. In this manner, the second end portion **2557** of the swing arms **2555** can couple to the axles such that the roller assembly **2554** and the axles can pivot relative to the mounting brackets **2541** (e.g., in response to a force exerted on tether **2505**, as described in further detail herein).

The coupler **2559** included in the guide mechanism **2540** is coupled to the axle of the pivot portion **2543** of one of the mounting brackets **2541**. The coupler **2559** is further coupled to an input shaft of the encoder **2561**. More specifically, the support bracket **2560** is coupled to the base **2210** of the housing **2200** and is also coupled to a portion of the encoder **2561** to limit the movement of a portion of the encoder **2561** relative to the base **2210**. Thus, the encoder **2561** can receive and/or determine information associated with the pivoting motion of the roller assembly **2554** relative to the mounting brackets **2541**. For example, the encoder **2561** can determine position, rotational velocity, rotational acceleration, feed rate of the tether **2505**, or the like. Furthermore, the encoder **2561** can be in electrical communication (e.g., via a wired communication or a wireless communication) with a portion of the electronic system **2700** and can send information associated with the guide mechanism **2540** to the portion of the electronic system **2700**. Upon receiving the information from the encoder **2561**, a portion of the electronic system **2700** can send a signal to any other suitable system associated with performing an action (e.g., increasing or decreasing the power of one or more motors **2311** and **2511**, changing the direction of one or more of the motors **2311** and **2511**, or the like).

As shown in FIG. **32**, the first pulley **2563** and the second pulley **2565** are rotatably coupled to a first pulley bracket **2564** and a second pulley bracket **2565**, respectively. The first pulley bracket **2564** and the second pulley bracket **2565** are further coupled to the base **2210** of the housing **2200**. In this manner, the first pulley **2563**, the second pulley **2565**, and at least a portion of the cam mechanism **2570** can be engaged the tether **2505** to provide a mechanical advantage to the winch assembly **2510**, as described in further detail herein.

As shown in FIGS. **32** and **33**, the cam mechanism **2570** includes a cam pulley assembly **2571**, a cam **2580**, a coupler **2585**, a coupler housing **2586**, an encoder **2587**, and a bias mechanism **2588**. The cam pulley assembly **2571** includes a cam pulley **2572**, a cam arm **2574**, a cam axle **2575**, and a spacer **2576**. The cam arm **2574** includes a first end portion that is rotatably coupled to the cam pulley **2572** and a second end portion that is rotatably coupled to the cam axle **2575**. The cam axle **2575** extends through the cam pivot opening **2220** (defined by the base **2210**), the spacer **2576**, and the cam **2580** to be coupled to the coupler **2585**. The spacer **2576** is coupled to the base **2210** and is disposed between the second side **2212** of the base **2210** and a surface of the cam **2580**. The spacer **2576** can be formed from a material having a relatively low friction coefficient such as, for example, polyethylene, nylon, or the like to allow the cam **2580** to move relatively easily along a surface of the spacer **2576**. In this manner, the cam **2580** is spaced a sufficient distance from the second side **2212** of the base **2210** to allow a portion of the bias mechanism **2588** to be disposed therebetween, as described in further detail herein.

The cam **2580** of the cam assembly **2570** defines an opening **2581**, and includes a mounting portion **2582** and an engagement surface **2583**. The engagement surface **2583** of

26

the cam **2580** is in contact with a portion of the bias mechanism **2588**, as described in further detail herein. The opening **2581** defined by the cam **2580** receives a bearing **2584**. When disposed within the opening **2581**, the bearing **2584** allows the cam **2580** to rotate about the cam axle **2575**. The mounting portion **2582** of the cam **2580** is at least partially disposed within the cam pulley opening **2219** and is coupled to the cam pulley **2572**. For example, as shown in FIG. **33**, the mounting portion **2582** is a threaded rod extending from a surface of the cam **2580** that can be received by a threaded opening (not shown) defined by the cam pulley **2572**. In this manner, movement of the cam pulley assembly **2571**, in response to a change in force exerted on the tether **2505** (e.g., an increase or a decrease of force), rotates the cam **2580** about the cam axle **2575** (as described above).

The coupler housing **2586** is coupled to a surface of the cam **2580** that is opposite the side adjacent to the spacer **2576**. In other words, the coupler housing **2586** extends away from the base **2210** when coupled to the cam **2580**. The coupler housing **2586** is further coupled to the encoder **2587**. Thus, when the cam **2580** is rotated about the cam axle **2575**, the coupler housing **2586** and the encoder **2587** are also rotated about the cam axle **2575**. The coupler **2585** is disposed within the coupler housing **2586** and is coupled to both the cam axle **2575** and an input portion (not shown) of the encoder **2587**. Therefore, with the coupler **2585** coupled to the cam axle **2575** and the input portion of the encoder **2587**, the rotation of the cam **2580** and the coupler housing **2586** rotates the encoder **2587** about its input portion. In this manner, the encoder **2587** can receive and/or determine information associated with the pivoting motion of the cam **2580** and/or the cam pulley assembly **2571** relative to the cam axle **2575**. For example, the encoder **2587** can determine position, rotational velocity, rotational acceleration, feed rate of the tether **2505**, or the like. Furthermore, the encoder **2587** can be in electrical communication (e.g., via a wired communication or a wireless communication) with a portion of the electronic system **2700** and can send information associated with the cam mechanism **2570** to the portion of the electronic system **2700**. Upon receiving the information from the encoder **2587**, a portion of the electronic system **2700** can send a signal to any other suitable system associated with performing an action (e.g., increasing or decreasing the power of one or more motors **2311** and **2511**, changing the direction of one or more of the motors **2311** and **2511**, or the like).

The bias mechanism **2588** includes an axle **2589**, a mounting flange **2590**, a first pivot arm **2591**, a second pivot arm **2595**, a guide member **2596**, a bias member **2597**, and a mounting post **2598**. The axle **2589** is movably disposed within the mounting flange **2588** and is configured to extend through the bias mechanism opening **2217** defined by the base **2210** to be fixedly disposed within an axle opening **2592** defined by the second pivot arm **2591**. Expanding further, a portion of the mounting flange **2589** extends through the bias mechanism opening **2217** and beyond the second side **2212** of the base **2210** to be in contact with a surface of the second pivot arm **2591**. In this manner, the surface of the second pivot arm **2591** is offset from the second side **2212** of the base **2210**. Moreover, the arrangement of the spacer **2576** (described above) is such that when the axle **2589** is disposed within the axle opening **2592**, a second surface of the first pivot arm **2591** is offset from a surface of the cam **2580**. Thus, the first pivot arm **2591** can pivot relative to the base **2210** with a relatively low amount of friction. In some embodiments, at least the portion of the

mounting flange **2590** that extends through the bias mechanism opening **2217** can be made from a material having a relatively low coefficient of friction such as, for example, polyethylene, nylon, or the like.

The first pivot arm **2591** defines the axle opening **2592** and a guide member opening **2593**, and includes an engagement member **2594**. The guide member opening **2593** is configured to receive a portion of the guide member **2596** to couple the guide member **2596** to the first pivot arm **2591**. The guide member **2596** extends from a surface of the first pivot arm **2591** toward the base **2210** such that a portion of the guide member **2596** extends through the guide member opening **2218** defined by the base **2210**. In some embodiments, the guide member **2596** can include a sleeve or the like configured to engage the base **2210**. In such embodiments, the sleeve can be formed from a material having a relatively low friction coefficient such as, for example, polyethylene, nylon, or the like. Thus, the guide member **2596** can move within the guide member track **2218** when the first pivot arm **2591** is moved relative to the base **2210**.

The engagement member **2594** of the first pivot arm **2591** extends from a surface of the first pivot arm **2591** toward the cam **2580**. In this manner, the engagement member **2594** can be moved along the engagement surface **2583** of the cam **2580** when the cam **2580** is moved relative to the base **2210**, as described in further detail herein. In some embodiments, the engagement member **2594** can be rotatably coupled to the first pivot arm **2591** and can be configured to roll along the engagement surface **2583**. In other embodiments, the engagement member **2594** and/or the engagement surface **2583** can be formed from a material having a relatively low friction coefficient. In such embodiments, the engagement member **2594** can be slid along the engagement surface **2583**.

The second pivot arm **2595** of the bias mechanism **2588** has a first end portion that is fixedly coupled to the axle **2589** and a second end portion that is coupled to a first end portion of the bias member **2597**. The mounting post **2598** is fixedly coupled to the base **2210** and is further coupled to a second end portion of the bias member **2597**. Therefore, the second pivot arm **2595** can pivot relative to the mounting flange **2590** between a first position, where the bias member **2597** is in a first configuration (undeformed configuration), and a second position, where the bias member **2597** is in a second configuration (deformed configuration). For example, in some embodiments, the bias member **2597** can be a spring that can be moved between an uncompressed configuration (e.g., the first configuration) and a compressed configuration (e.g., the second configuration). In other embodiments, the bias member **2597** can be a spring that can be moved between an unexpanded and an expanded configuration. In other words, the bias member **2597** can be either a compression spring or an expansion spring, respectively. In still other embodiments, the bias member **2597** can be any other suitable biasing mechanism and/or energy storage device such as, for example, a gas strut or the like.

When the cam **2580** is rotated from a first position to a second position in response to a force exerted on the tether **2505** (as described above), the bias member **2597** can exert a reaction force that resists the rotation of the cam **2580**. More specifically, with the engagement member **2594** in contact with the engagement surface **2583** of the cam **2580**, the bias member **2587** exerts the reaction force that resists the movement of the engagement member **2594** along the engagement surface **2583**. Therefore, in some instances, relatively small changes in the force exerted on the tether **2505** may not be sufficiently large to rotate the cam **2580** and

the cam pulley assembly **2571**. This arrangement can reduce undesirable changes in the amount of body weight supported by the support system **2000** in response to minor fluctuations of force exerted on the tether **2505**.

FIG. **34** illustrates the patient attachment mechanism **2800**. The patient attachment mechanism **2800** can be mated with the second end portion **2507** of the tether **2505** to couple the patient attachment mechanism **2800** to the trolley **2100**. Moreover, the patient attachment mechanism **2800** can be coupled to a harness or the like, worn by the patient, to couple the patient to the support system **2000**, as described below.

The patient attachment mechanism **2800** has a first coupling portion **2810** and a second coupling portion **2812**. The first coupling portion **2810** includes a coupling mechanism **2811** configured to couple to the second end portion **2507** of the tether, as described above. For example, the coupling mechanism **2811** can be a loop or hook configured to couple to an attachment device of the tether **2505** (not shown in FIGS. **2-34**). The second coupling portion **2821** is movably coupled to a first arm **2820** and a second arm **2840**. As described in further detail herein, the first **2820** and the second arm **2840** can pivot relative to each other to absorb at least a portion of a force exerted by the weight of a patient coupled to the patient attachment mechanism **2800**.

The first arm **2820** of the patient attachment mechanism **2800** includes a pivot portion **2821** and a mount portion **2822**. The pivot portion **2821** is movably coupled to the second coupling portion **2812**. The mount portion **2822** receives a guide rod **2830**, as described in further detail herein. The first arm **2820** defines a slot **2824** that receives a portion of the second arm **2840** and an opening **2826** that receives a portion of a harness worn by the patient.

The second arm **2840** has a pivot portion **2841** and a coupling portion **2842**. The pivot portion **2841** is movably coupled to the second coupling portion **2812**. In this manner, both the first arm **2820** and the second arm **2840** can pivot relative to the coupling portion **2812** and relative to each other, as described in further detail herein. The coupling portion **2842** defines an opening **2843** that receives a portion of the harness worn by the patient. The coupling portion **2842** is also movably coupled to a first end portion of a first energy storage member **2844** and a first end portion of a second energy storage member **2851** (collectively referred to as energy storage member **2850**). The energy storage members **2850** can be, for example, gas struts or the like.

As shown in FIG. **34**, the energy storage members **2850** are configured to extend towards the first arm **2820**. More specifically, the second energy storage member **2851** includes a coupling portion **2852** that is movably coupled to the guide rod **2830** of the first arm **2820**. The first energy storage member **2844** also includes a coupling portion (not shown in FIG. **34**) that is movably coupled to an engagement member **2845** and further coupled to the coupling portion **2852** of the second energy storage member **2851**. Similarly stated, the coupling portion of the first energy storage member **2844** extends in a substantially perpendicular direction relative to a longitudinal centerline (not shown) of the first energy storage member **2844**.

The engagement member **2845** is movably coupled to the coupling portion of the first energy storage member **2844** and the coupling portion **2852** of the second coupling portion **2851**. The engagement member **2845** is configured to be placed in contact with an engagement surface **2825** of the first arm **2820** that at least partially defines the slot **2825**. Similarly stated, the engagement member **2845** is disposed within the slot **2824** defined by the first arm **2820** and in

contact **2825** with the engagement surface **2825**. Moreover, the arrangement of the engagement member **2845** and the energy storage members **2850** allows the engagement member **2845** to roll along the engagement surface **2825**.

When a force is exerted on the first arm **2820** the second arm **2840** by the patient, the first arm **2820** and the second arm **2840** pivot about the second coupling portion **2812** towards one another. The pivoting of the first arm **2820** and the second arm **2840** moves the engagement member **2845** along the engagement surface **2825** and further moves the energy storage members **2850** for a configuration of lower potential energy to a configuration of higher potential energy (e.g., compresses a gas strut). Thus, the energy storage members **2850** can absorb at least a portion of a force exerted of the patient attachment mechanism **2800**. Moreover, when the force exerted on the patient attachment mechanism **2800** is less than the potential energy of the energy storage members **2850** in the second configuration, the energy storage members **2850** can move towards their first position to pivot the first arm **2820** and the second arm **2840** away from one another.

In use, the patient support system **2000** can be used to actively support at least a portion of the body weight of a patient that is coupled thereto. For example, in some instances, a patient is coupled to the patient attachment mechanism **2800** which, in turn, is coupled to the second end portion **2507** of the tether **2505**, as described above. In this manner, the support system **2000** (e.g., the tether **2505**, the trolley **2100**, and the support rail **2050**) can support at least a portion of the body weight of the patient.

In some instances, a user (e.g., a technician, a therapist, a doctor, a physician, or the like) can input a set of system parameters associated with the patient and the support system **2000**. For example, in some embodiments, the user can input a set of system parameters via a remote control device such as, for example, a personal computer, a mobile device, a smart phone, or the like. In other embodiments, the user can input system parameters on, for example, a control panel included in or on the trolley **2100**. The system parameters can include, for example, the body weight of the patient, the height of the patient, a desired amount of body weight to be supported by the support system **2000**, a desired speed of the patient walking during gait therapy, a desired path or distance along the length of the support track **2050**, or the like.

With the system parameters entered the patient can begin, for example, a gait therapy session. In some instances, the trolley **2100** can move along the support structure **2050** (as described above with reference to FIGS. 23 and 26) in response to the movement of the patient. Similarly stated, the trolley **2100** can move along the support structure **2050** as the patient walks. In some instances, the trolley **2100** can be configured to remain substantially over-head of the patient. In such instances, the electronic system **2700** can execute a set of instructions associated with controlling the motor **2311** of the drive system **2300** based on information received from, for example, the encoder **2470** of the drive system **2300**, the encoder **2561** of the guide mechanism **2540**, and/or the encoder **2587** of the cam assembly **2570**. For example, the electronic system **2700** can send a signal to the motor **2311** of the drive system **2300** operative in changing the rotational velocity of the drive wheels **2385** based at least in part on information associated with the encoder **2561** of the guide mechanism **2540**. Expanding further, in some instances, the patient may walk faster than the trolley **2100**, thereby changing the angle of the tether **2505** and the guide mechanism **2540** relative to the base

2210. Thus, the encoder **2561** of the guide mechanism **2540** can send a signal associated with the angle of the guide mechanism **2540** relative to the base **2210** and upon receiving the signal, the electronic system **2700** can send a signal to the motor **2311** of the drive system **2300** to increase the rotational velocity of the drive wheels **2385**. In this manner, the position of the trolley **2100** relative to the patient can be actively controlled based at least in part on a user defined parameter and further based at least in part on information received from the encoder **2470** of the drive system **2300**, the encoder **2561** of the guide mechanism **2540**, and/or the encoder **2587** of the cam assembly **2570**. Although described as being actively controlled to be over-head of the patient, in other instances, the user can define a parameter associated with the trolley **2100** trailing the patient by a desired distance or leading the patient by a desired distance.

In some instances, the amount of force exerted on the tether **2505** by the patient may increase or decrease. By way of example, a patient may stumble, thereby increasing the amount of force exerted on the tether **2505**. In such instances, the increase of force exerted on the tether **2505** can pivot the guide mechanism **2540** and can move the cam pivot arm **2571** in response to the increase in force. The movement of the cam pivot arm **2571** moves the cam assembly **2570** (as described above with reference to FIG. 33). In this manner, the encoder **2561** of the guide mechanism **2540** and the encoder **2587** of the cam assembly **2570** can send a signal to the electronic system **2700** associated with the changes in the state of the guide mechanism **2540** and the cam assembly **2570**, respectively.

Upon receiving the signals from the encoders **2561** and **2587**, the processor can execute a set of instructions included in the memory associated with the cam assembly **2570**. For example, the processor can determine the position of the cam **2580** or the guide mechanism **2540**, the velocity and the acceleration of the cam **2580** or the guide mechanism **2540**, or the like. Based on the determining of the changes in the guide mechanism **2540** and the cam assembly **2570** configurations, the processor can send a signal to the motor **2311** of the first drive assembly **2310** and/or the motor **2511** of the winch assembly **2510** to change the current state of the drive system **2300** and/or the patient support mechanism **2500**. In some instances, the magnitude of change in the state of the drive system and/or the patient support mechanism **2500** is based at least in part on a proportional-integral-derivative (PID) control. In such instances, the electronic system **2700** (e.g., the processor or any other electronic device in communication with the processor) can determine the changes of the patient support mechanism **2500** and model the changes based on the PID control. Based on the result of the modeling the processor can determine the suitable magnitude of change in the drive system **2300** and/or the patient support mechanism **2500**.

After a relatively short time period (e.g., much less than a second, for example, after one or a few clock cycles of the processor) the processor can receive a signal from the encoder **2470** of the drive system **2300**, the encoder **2537** of the winch assembly **2510**, the encoder **2561** of the guide mechanism **2540**, and/or the encoder **2587** of the cam assembly **2570** associated with a change in configuration of the drive system **2300**, the winch assembly **2510**, the guide mechanism **2540**, and/or the cam assembly **2570**, respectively. In this manner, one or more of the electronic devices included in the electronic system **2700**, including but not limited to the processor, execute a set of instructions stored in the memory associated with the feedback associated with the encoders **2470**, **2537**, **2561**, and **2587**. Thus, the drive

31

system **2300** and the patient support mechanism **2500** of the trolley **2100** can be actively controlled in response to a change in force exerted on the tether **2505** and based at least in part on the current and/or previous states of the drive system **2300** and the patient support system **2500**. Similarly stated, the support system **2000** can actively reduce the amount a patient falls after stumbling or falling for other reasons.

While the patient support system **2000** is described above with reference to FIGS. 2-34 as actively supporting a portion of the body weight of the patient, in some embodiments, a patient support system can passively (i.e., not actively) support a portion of the body weight of a patient. For example, FIGS. 35 and 36 illustrate a body weight support system **3900** according to an embodiment. The body weight support system **3900** (also referred to herein as “support system”) can be used to support a portion of a patient’s body weight, for example, during gait therapy, gait training, or the like. The support system **3900** can be movably coupled to a support track (not shown) that is configured to support the weight of the support system **3900** and the weight of the patient utilizing the support system **3900**. The support track can be, for example, similar to or the same as the support track **2050** described above.

The support system **3900** includes a first coupling portion **3910** and a second coupling portion **3940**. The first coupling portion **3910** is configured to movably couple to the support track, as described above. The first coupling portion **3910** includes a first side assembly **3911**, a second side assembly **3921**, and a base **3930**. The first side assembly **3911** includes a set of drive wheels **3912**, a set of guide wheels **3913**, an outer wall **3914**, an inner wall **3915**, and a set of couplers **3916**. The couplers **3916** are configured to extend between the outer wall **3914** and the inner wall **3915** to couple the outer wall **3914** and the inner wall **3915** together. The outer wall **3914** is further coupled to the base **3930**. The drive wheels **3912** are arranged into an upper set of drive wheels **3912** configured to be disposed on a top surface of the support track, and a lower set of drive wheels **3912** configured to be disposed on a bottom surface of the support track. In this manner, the drive wheels **3912** roll along a horizontal portion of the support track (not shown in FIGS. 35 and 36). The guide wheels **3913** are arranged in a perpendicular orientation relative to the drive wheels **3912** and are configured to roll along a vertical portion of the support track (e.g., as similarly described above with reference to FIG. 23).

The second side assembly **3921** includes a set of drive wheels **3922**, a set of guide wheels **3923**, an outer wall **3924**, an inner wall **3925**, and a set of couplers **3916**. The first side assembly **3911** and the second side assembly **3921** are substantially the same and arranged in a mirrored configuration. Therefore, the second side assembly **3921** is not described in further detail herein and should be considered the same as the first side assembly **3921** unless explicitly described.

As shown in FIG. 36, the second coupling portion **3940** includes a cylinder **3941**, an attachment member **3945**, a piston **3950**, and an energy storage member **3960**. The cylinder **3941** is coupled to the base **3930** and is configured to house the spring **3960** and at least a portion of the piston **3950**. More specifically, the cylinder **3941** defines an opening **3942** at an end portion, opposite the base **3930**, through which at least a first end portion **3951** of the piston **3950** can move. The piston **3950** further has a second end portion **3952** that is in contact with a portion of the energy storage member **3960**. The energy storage member **3960** can be any suitable device configured to move between a first configuration

32

having lower potential energy and a second configuration having a higher potential energy. For example, as shown in FIG. 36, the energy storage member **3960** can be a spring that is compressed when moved to its second configuration.

The attachment mechanism **3945** includes a first coupling portion **3946** that is coupled to the first end portion **3951** of the piston **3950**, and a second coupling portion **3947** that can be coupled to, for example, a harness worn by a patient. As shown in FIGS. 35 and 36, the second end portion **3952** can be an annular protrusion. In this manner, a portion of the harness such as a hook or the like can be at least partially disposed within the opening defined by the second coupling portion **3947** to couple the patient to the support system **3900**.

In use, the patient can be coupled to the support system **3900** (as described above) such that the support system **3900** supports at least a portion of the body weight of the patient. In this manner, the patient can walk along a path associated with the support track (not shown). With the support system **3900** coupled to the patient, the movement of the patient moves the support system **3900** along the support track. Similarly stated, the patient pulls the support system **3900** along the support track. In some instances, a patient may stumble while walking, thereby increasing the amount of force exerted on the support system **3900**. In such instances, the increase in force exerted on the support system **3900** can be sufficient to cause the energy storage member **3960** to move from its first configuration towards its second configuration (e.g., compress). In this manner, the piston **3950** can move relative to the cylinder **3941** and the energy storage member **3960** can absorb at least a portion of the increase in the force exerted on the support structure **3900**. Thus, if the patient stumbles the support system **3900** can dampen the impulse experienced by the patient that would otherwise result in known passive support systems **3900**.

Although the support system **3900** is described as including an energy storage member, in other embodiments, the support system **3900** need not include the energy storage member. For example, in some embodiments, the support system **3900** can be coupled to, for example, the attachment mechanism **2800** described above with reference to FIG. 34. In this manner, the attachment mechanism **2800** can be used to dampen at least a portion of a change in force exerted on the support system **3900**. For example, in some instances a patient coupled to the support system **3900** may stumble, thereby increasing the force exerted on the support system **3900**. In such instances, the increase in force can move the first arm **2820** towards the second arm **2840** (see e.g., FIG. 34), thereby moving the energy storage member **2850** towards their second configuration. Thus, at least a portion of the increase in force can be absorbed by the attachment mechanism **2800**.

Although not shown in FIG. 2-36, one or more active support system (e.g., support system **2000**) and/or one or more passive support system (e.g., **3900**) can be disposed about a similar support track and can be utilized at the same time. For example, FIG. 37 is a schematic illustration of a support system **4000** according to an embodiment. The support system **4000** includes a support track **4050**, a first support member **4100**, and a second support member **4900**. The support system **4000** can be used to support at least a portion of the body weight of one or more patients during, for example, gait therapy (e.g., after injury), gait training (e.g., low gravity simulation), or the like. The support track **4050** is configured to support the weight of the first support member **4100** and the second support member **4900** and the

33

weight of the patient utilizing the first support member **4100** and/or the second support member **4900**.

As shown in FIG. 37, the support track **4050** can form a closed loop track. The support track **4050** can be similar to or the same as the support track **2050**, described above with reference to FIGS. 2 and 3; the first support member **4100** can be similar to or the same as the trolley **2100**, described above with reference to FIGS. 2-33; and the second support member **4900** can be similar to or the same as the support system **3900**, described above with reference to FIGS. 35 and 36. In this manner, the first support member **4100** and the second support member **4900** can be hung from the support track **4050**, as described in detail above.

In some embodiments, a first patient (not shown in FIG. 37) can be coupled to the first support member **4100** and a second patient (not shown in FIG. 37) can be coupled to the second support member **4900** with both being suspended from the support track **4050**. As shown in FIG. 37, the first support member **4100** can move in the direction of the arrow A in response to a movement of the first patient coupled thereto. Similarly, the second support member **4900** can be moved in the direction of the arrow B in response to a movement of the second patient coupled thereto. Expanding further, the first support member **4100** can be an active support member and can be configured to move in accordance with the movement of the first patient, as described in detail above. Conversely, the second support member **4900** can be a passive support member and can be moved by the second patient coupled thereto, as described in detail above.

Although not shown in FIG. 37 the first support member **4100** and/or the second support member **4900** can include a collision avoidance system that is configured to prevent a collision of the first support member **4100** and the second support member **4900**. For example, in some embodiments, the first support member **4100** can include a sensor (e.g., an ultrasonic proximity sensor or the like) configured to sense the relative position of the first support member **4100** relative to the second support member **4900**. Thus, when the distance between the first support member **4100** and the second support member **4900** approaches a predetermined threshold (e.g., a minimum distance), an electronic system (e.g., similar to or the same as the electronic system **2700** described above) included in the first support member **4100** can send a signal to a drive system (not shown) to increase or decrease a rotational velocity of one or more drive wheels. Thus, a collision of the first support member **4100** and the second support member **4900** can be avoided.

Although the support system **4000** is shown and described as including the first support member **4100** and the second support member **4900**, in other embodiments, the support system **4000** can include any suitable number of support members movably coupled to the support track **4050**. Moreover, any combination of active support members and passive support members can be included in the support system **4000**. For example, while shown as including an active support member (e.g., the first support member **4100**) and a passive support member (e.g., the second support member **4900**), in other embodiments, the support system **4000** can include two active support members, two passive support members, two active support members and two passive support members, or any other suitable combination thereof.

Some embodiments described herein relate to a computer storage product with a non-transitory computer-readable medium (also can be referred to as a non-transitory processor-readable medium) having instructions or computer code thereon for performing various computer-implemented operations. The computer-readable medium (or processor-

34

readable medium) is non-transitory in the sense that it does not include transitory propagating signals (e.g., propagating electromagnetic wave carrying information on a transmission medium such as space or a cable). The media and computer code (also referred to herein as code) may be those designed and constructed for the specific purpose or purposes. Examples of non-transitory computer-readable media include, but are not limited to: magnetic storage media such as hard disks, optical storage media such as Compact Disc/Digital Video Discs (CD/DVDs), Compact Disc-Read Only Memories (CD-ROMs), magneto-optical storage media such as optical disks, carrier wave signal processing modules, and hardware devices that are specially configured to store and execute program code, such as Application-Specific Integrated Circuits (ASICs), Programmable Logic Devices (PLDs), Read-Only Memory (ROM) and Random-Access Memory (RAM) devices. Other embodiments described herein relate to a computer program product, which can include, for example, the instructions and/or computer code discussed herein.

Examples of computer code include, but are not limited to, micro-code or micro-instructions, machine instructions, such as produced by a compiler, code used to produce a web service, and files containing higher-level instructions that are executed by a computer using an interpreter. For example, embodiments may be implemented using imperative programming languages (e.g., C, FORTRAN, etc.), functional programming languages (Haskell, Erlang, etc.), logical programming languages (e.g., Prolog), object-oriented programming languages (e.g., Java, C++, etc.), or other programming languages and/or other development tools. Additional examples of computer code include, but are not limited to, control signals, encrypted code, and compressed code.

While various embodiments have been described above, it should be understood that they have been presented by way of example only, and not limitation, and as such, various changes in form and/or detail may be made. For example, while the attachment mechanism **2800** is described above with reference to FIG. 34 as including energy storage members **2850**, in other embodiments, an attachment mechanism need not include an energy storage member. In such embodiments, the attachment mechanism can be coupled to, for example, the trolley **2100** and the further coupled to a harness or the like worn by a patient. In such embodiments, the trolley **2100** can function in a substantially similar manner as described above.

Although the trolley **2100** is described above with reference to FIGS. 2-33 as including a motorized drive system **2300** and an active support mechanism **2500**, in other embodiments, a trolley can include either a motorized drive system or an active support mechanism. Similarly stated, the drive system **2300** and the support mechanism **2500** can be mutually exclusive and can independently function in a similar manner to those described above.

Any portion of the apparatus and/or methods described herein may be combined in any suitable combination, unless explicitly expressed otherwise. For example, in some embodiments, the patient support mechanism **2500** of the trolley **2100** included in the support system **2000** can be replaced with a system similar to the support system **3900**. In such embodiments, a cylinder, a piston, and an energy storage member can extend, for example, from the base **2210** of the housing **2200** of the trolley **2100**. Expanding further, the kinetic and potential energy of the energy storage member (e.g., storage member **3960**) could be actively controlled via a feedback system similar to the system

35

described above with reference to the trolley **2100**. For example, the energy storage member **3960** could be compressed air, the pressure of which could be controlled in response to a force exerted on the piston.

Where methods and/or schematics described above indicate certain events and/or flow patterns occurring in certain order, the ordering of certain events and/or flow patterns may be modified. Additionally certain events may be performed concurrently in parallel processes when possible, as well as performed sequentially.

What is claimed is:

1. A trolley configured to support an amount of a user's weight, the trolley comprising:

a drive assembly including a plurality of wheels and a first motor, the first motor configured to move the plurality of wheels along a track to move the trolley relative to the track;

a patient support mechanism including an adjustable tether and a second motor, the adjustable tether having a first end portion coupled to a drum of the patient support mechanism and a second end portion coupled to a harness worn by the user, the adjustable tether configured to support an amount of weight of the user, the second motor coupled to the drum and operable to adjust the amount of weight supported by the adjustable tether; and

an electronic system electrically coupled to the first motor and the second motor, a portion of the electronic system in contact with at least one conductive surface of a powered conductor coupled adjacent to the track, the electronic system configured to supply the first motor and the second motor with electric power received from the powered conductor, the first motor configured to move at least a portion of the wheels along the track in response to movement of the patient supported by the adjustable tether.

2. The trolley of claim 1, further comprising:

a battery electrically coupled to the electronic system, the battery configured to supply electric power to the electronic system.

3. The trolley of claim 2, wherein the battery is configured to receive electric power from the powered conductor, the electric power operable to electrically charge the battery.

4. The trolley of claim 1, wherein at least a portion of the track is disposed between at least one wheel from the plurality of wheels and the powered conductor such that the at least one wheel is isolated from the powered conductor.

5. The trolley of claim 1, wherein the second motor is configured to adjust an amount of weight supported by the adjustable tether in response to movement of the patient coupled to the adjustable tether.

6. The trolley of claim 1, wherein the second motor is configured to rotate the drum to adjust an amount of weight supported by the adjustable tether.

7. The trolley of claim 1, wherein a first wheel from the plurality of wheels is disposed above a portion of the track and a second wheel from the plurality of wheels is disposed below the portion of the track.

8. A system for supporting the weight of a person, comprising:

a track;

a trolley movably suspended from the track, the trolley being movable along a path defined by the track in a first direction and in a second direction generally opposite to the first direction;

a drive assembly coupled to the trolley, the drive assembly configured to move the trolley along the path defined by the track;

36

a patient support mechanism coupled to the trolley, the patient support mechanism including a drum and an adjustable tether, a first end portion of the adjustable tether coupled to the drum, a second end portion of the adjustable tether configured to couple to a support harness attached to the person; and

a control system in electrical communication with at least a portion of the drive assembly and at least a portion of the patient support mechanism, the control system configured to change an operating condition of at least one of the drive assembly or the patient support mechanism to dynamically adjust an amount of support provided to the person in response to a change in a force applied on the adjustable tether by the person coupled to the adjustable tether.

9. The system of claim 8, wherein the drive assembly includes a sensor configured to send to the control system a signal associated with an operating condition of the drive assembly.

10. The system of claim 8, wherein the patient support mechanism includes a sensor configured to send to the control system a signal associated with an operating condition of the patient support mechanism.

11. The system of claim 8, further comprising:

a powered conductor coupled adjacent to the track, the powered conductor including at least one conductive surface in contact with a portion of the trolley, the powered conductor configured to supply electric power to at least a portion of the drive assembly, at least a portion of the patient support mechanism, and at least a portion of the control system.

12. The system of claim 8, wherein the drive assembly includes a plurality of wheels, a first portion of the plurality of wheels configured to roll along a horizontal surface of the track, a second portion of the plurality of wheels configured to roll along a vertical surface of the track.

13. A system, comprising:

a track;

a first trolley having a drive assembly configured to movably suspend the first trolley from the track, the first trolley including an adjustable tether configured to support a first patient;

a second trolley having a drive assembly configured to movably suspend the second trolley from the track, the second trolley including an adjustable tether configured to support a second patient, at least one of the first trolley or the second trolley including a collision avoidance system configured to limit a collision between the first trolley and the second trolley; and

a powered conductor coupled adjacent to the track, the powered conductor including at least one conductive surface, a portion of the first trolley being in contact with the at least one conductive surface to electrically couple the first trolley to the powered conductor, and a portion of the second trolley being in contact with the at least one conductive surface to electrically couple the second trolley to the powered conductor, the powered conductor configured to provide a flow of electric power to the first trolley and a flow of electric power to the second trolley concurrently;

the track, the drive assembly of the first trolley, and the drive assembly of the second trolley each disposed outside of the powered conductor.

14. The system of claim 13, wherein the drive assembly of the first trolley is configured to move the first trolley along the track in response to movement of the first patient.

15. The system of claim 14, wherein the drive assembly of the second trolley is configured to move the second trolley along the track in response to movement of the second patient.

16. The system of claim 13, wherein the collision avoidance system includes a sensor included in the first trolley and configured to detect a proximity of the second trolley relative to the first trolley. 5

17. The system of claim 16, wherein the first trolley includes an electronic system configured to control an operating condition of the drive assembly of the first trolley based at least in part on a signal received from the sensor. 10

18. The system of claim 13, wherein the collision avoidance system includes a first sensor and a second sensor, the first sensor is included in the first trolley and is configured to detect a proximity of the second trolley relative to the first trolley, the second sensor is included in the second trolley and is configured to detect a proximity of the first trolley relative to the second trolley. 15

* * * * *