



(12) **United States Patent**
Yee et al.

(10) **Patent No.:** **US 11,202,591 B2**
(45) **Date of Patent:** ***Dec. 21, 2021**

(54) **ANALYTE SENSOR AND APPARATUS FOR
INSERTION OF THE SENSOR**

(71) Applicant: **ABBOTT DIABETES CARE INC.,**
Alameda, CA (US)

(72) Inventors: **Phillip Yee**, San Francisco, CA (US);
Christopher A. Thomas, San Leandro, CA (US); **Udo Hoss**, Castro Valley, CA (US); **Lei He**, Moraga, CA (US);
Michael R. Love, Pleasanton, CA (US)

(73) Assignee: **ABBOTT DIABETES CARE INC.,**
Alameda, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

(21) Appl. No.: **17/221,154**

(22) Filed: **Apr. 2, 2021**

(65) **Prior Publication Data**
US 2021/0219886 A1 Jul. 22, 2021

Related U.S. Application Data

(63) Continuation of application No. 17/009,647, filed on Sep. 1, 2020, now Pat. No. 11,006,870, which is a (Continued)

(51) **Int. Cl.**
A61B 5/00 (2006.01)
A61B 5/1486 (2006.01)
(Continued)

(52) **U.S. Cl.**

CPC **A61B 5/14865** (2013.01); **A61B 5/002** (2013.01); **A61B 5/0004** (2013.01); **A61B 5/0022** (2013.01); **A61B 5/0024** (2013.01); **A61B 5/02055** (2013.01); **A61B 5/14503** (2013.01); **A61B 5/14532** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC ... **A61B 5/14865**; **A61B 5/0004**; **A61B 5/002**; **A61B 5/0022**; **A61B 5/14503**; **A61B 5/14532**; **A61B 5/6849**; **A61B 5/6898**; **A61B 5/7425**; **A61B 2560/0412**;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,123,790 A 3/1964 Tyler
3,260,656 A 7/1966 Ross, Jr.
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2003259741 2/2004
CA 2291105 12/1998
(Continued)

OTHER PUBLICATIONS

Armour, J. C., et al., "Application of Chronic Intravascular Blood Glucose Sensor in Dogs", *Diabetes*, vol. 39, 1990, pp. 1519-1526.
(Continued)


Primary Examiner — Christian Jang

(74) *Attorney, Agent, or Firm* — One LLP

(57) **ABSTRACT**

An apparatus for insertion of a medical device in the skin of a subject is provided.

30 Claims, 29 Drawing Sheets



Related U.S. Application Data

continuation of application No. 16/736,728, filed on Jan. 7, 2020, now Pat. No. 10,786,190, which is a continuation of application No. 15/994,129, filed on May 31, 2018, now abandoned, which is a continuation of application No. 15/475,647, filed on Mar. 31, 2017, now Pat. No. 9,993,188, which is a continuation of application No. 15/192,531, filed on Jun. 24, 2016, now Pat. No. 9,636,068, which is a continuation of application No. 12/698,129, filed on Feb. 1, 2010, now Pat. No. 9,402,544.

- (60) Provisional application No. 61/149,639, filed on Feb. 3, 2009.

(51) **Int. Cl.**

A61B 5/0205 (2006.01)
G06K 7/10 (2006.01)
A61B 5/145 (2006.01)
A61M 5/158 (2006.01)
C12Q 1/00 (2006.01)
H04L 29/08 (2006.01)
A61M 5/172 (2006.01)
A61M 5/32 (2006.01)

(52) **U.S. Cl.**

CPC *A61B 5/6849* (2013.01); *A61B 5/6898* (2013.01); *A61B 5/72* (2013.01); *A61B 5/742* (2013.01); *A61B 5/7405* (2013.01); *A61B 5/7425* (2013.01); *A61B 5/7455* (2013.01); *A61M 5/158* (2013.01); *A61M 5/1723* (2013.01); *C12Q 1/001* (2013.01); *C12Q 1/006* (2013.01); *G06K 7/10366* (2013.01); *H04L 67/12* (2013.01); *A61B 2560/0214* (2013.01); *A61B 2560/0412* (2013.01); *A61B 2560/0475* (2013.01); *A61B 2560/0487* (2013.01); *A61B 2562/0295* (2013.01); *A61M 5/3286* (2013.01); *A61M 2005/1726* (2013.01); *A61M 2205/33* (2013.01); *A61M 2205/3584* (2013.01); *A61M 2205/502* (2013.01); *A61M 2230/201* (2013.01)

(58) **Field of Classification Search**

CPC *A61B 2560/0487*; *C12Q 1/006*; *G06K 7/10366*; *H04L 67/12*
 See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,522,807 A 8/1970 Millenbach
 3,581,062 A 5/1971 Aston
 3,653,841 A 4/1972 Klein
 3,670,727 A 6/1972 Reiterman
 3,719,564 A 3/1973 Lilly, Jr. et al.
 3,776,832 A 12/1973 Oswin et al.
 3,837,339 A 9/1974 Aisenberg et al.
 3,926,760 A 12/1975 Allen
 3,949,388 A 4/1976 Fuller
 3,972,320 A 8/1976 Kalman
 3,979,274 A 9/1976 Newman
 4,008,717 A 2/1977 Kowarski
 4,016,866 A 4/1977 Lawton
 4,036,749 A 7/1977 Anderson
 4,055,175 A 10/1977 Clemens et al.
 4,059,406 A 11/1977 Fleet
 4,076,596 A 2/1978 Connery et al.
 4,098,574 A 7/1978 Dappen
 4,100,048 A 7/1978 Pompei et al.
 4,120,292 A 10/1978 LeBlanc, Jr. et al.

4,129,128 A 12/1978 McFarlane
 4,151,845 A 5/1979 Clemens
 4,168,205 A 9/1979 Danninger et al.
 4,172,770 A 10/1979 Semersky et al.
 4,178,916 A 12/1979 McNamara
 4,206,755 A 6/1980 Klein
 4,224,125 A 9/1980 Nakamura et al.
 4,240,438 A 12/1980 Updike et al.
 4,245,634 A 1/1981 Albisser et al.
 4,247,297 A 1/1981 Berti et al.
 4,294,258 A 10/1981 Bernard
 4,327,725 A 5/1982 Cortese et al.
 4,340,458 A 7/1982 Lerner et al.
 4,344,438 A 8/1982 Schultz
 4,349,728 A 9/1982 Phillips et al.
 4,352,960 A 10/1982 Dormer et al.
 4,356,074 A 10/1982 Johnson
 4,365,637 A 12/1982 Johnson
 4,366,033 A 12/1982 Richter et al.
 4,373,527 A 2/1983 Fischell
 4,375,399 A 3/1983 Havas et al.
 4,384,586 A 5/1983 Christiansen
 4,390,621 A 6/1983 Bauer
 4,392,849 A 7/1983 Petre et al.
 4,401,122 A 8/1983 Clark, Jr.
 4,404,066 A 9/1983 Johnson
 4,418,148 A 11/1983 Oberhardt
 4,425,920 A 1/1984 Bourland et al.
 4,427,770 A 1/1984 Chen et al.
 4,431,004 A 2/1984 Bessman et al.
 4,436,094 A 3/1984 Cerami
 4,440,175 A 4/1984 Wilkins
 4,450,842 A 5/1984 Zick et al.
 4,458,686 A 7/1984 Clark, Jr.
 4,461,691 A 7/1984 Frank
 4,469,110 A 9/1984 Slama
 4,477,314 A 10/1984 Richter et al.
 4,478,976 A 10/1984 Goertz et al.
 4,484,987 A 11/1984 Gough
 4,494,950 A 1/1985 Fischell
 4,509,531 A 4/1985 Ward
 4,522,690 A 6/1985 Venkatesetty
 4,524,114 A 6/1985 Samuels et al.
 4,526,661 A 7/1985 Steckhan et al.
 4,527,240 A 7/1985 Kvitash
 4,534,356 A 8/1985 Papadakis
 4,538,616 A 9/1985 Rogoff
 4,543,955 A 10/1985 Schroepel
 4,545,382 A 10/1985 Higgins et al.
 4,552,840 A 11/1985 Riffer
 4,560,534 A 12/1985 Kung et al.
 4,571,292 A 2/1986 Liu et al.
 4,573,994 A 3/1986 Fischell et al.
 4,581,336 A 4/1986 Malloy et al.
 4,595,011 A 6/1986 Phillips
 4,619,754 A 10/1986 Niki et al.
 4,619,793 A 10/1986 Lee
 4,627,445 A 12/1986 Garcia et al.
 4,627,842 A 12/1986 Katz
 4,627,908 A 12/1986 Miller
 4,633,878 A 1/1987 Bombardieri
 4,637,403 A 1/1987 Garcia et al.
 4,639,062 A 1/1987 Taniguchi et al.
 4,650,547 A 3/1987 Gough
 4,654,197 A 3/1987 Lilja et al.
 4,655,880 A 4/1987 Liu
 4,655,885 A 4/1987 Hill et al.
 4,671,288 A 6/1987 Gough
 4,675,346 A 6/1987 Lin et al.
 4,679,562 A 7/1987 Luksha
 4,680,268 A 7/1987 Clark, Jr.
 4,682,602 A 7/1987 Prohaska
 4,684,245 A 8/1987 Goldring
 4,684,537 A 8/1987 Graetzel et al.
 4,685,463 A 8/1987 Williams
 4,685,466 A 8/1987 Rau
 4,698,057 A 10/1987 Joishy
 4,703,324 A 10/1987 White
 4,703,756 A 11/1987 Gough et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

4,711,245 A	12/1987	Higgins et al.	5,036,860 A	8/1991	Leigh et al.
4,711,247 A	12/1987	Fishman	5,047,044 A	9/1991	Smith et al.
4,717,673 A	1/1988	Wrighton et al.	5,050,612 A	9/1991	Matsumura
4,721,601 A	1/1988	Wrighton et al.	5,051,688 A	9/1991	Murase et al.
4,721,677 A	1/1988	Clark, Jr.	5,055,171 A	10/1991	Peck
4,726,378 A	2/1988	Kaplan	5,058,592 A	10/1991	Whisler
4,726,716 A	2/1988	McGuire	5,068,536 A	11/1991	Rosenthal
4,729,672 A	3/1988	Takagi	5,070,535 A	12/1991	Hochmair et al.
4,731,726 A	3/1988	Allen, III	5,082,550 A	1/1992	Rishpon et al.
4,749,985 A	6/1988	Corsberg	5,082,786 A	1/1992	Nakamoto
4,755,173 A	7/1988	Konopka	5,089,112 A	2/1992	Skotheim et al.
4,757,022 A	7/1988	Shults et al.	5,095,904 A	3/1992	Seligman et al.
4,758,323 A	7/1988	Davis et al.	5,101,814 A	4/1992	Palti
4,759,371 A	7/1988	Franetzki	5,106,365 A	4/1992	Hernandez
4,759,828 A	7/1988	Young et al.	5,108,564 A	4/1992	Szuminsky et al.
4,764,416 A	8/1988	Ueyama et al.	5,108,889 A	4/1992	Smith et al.
4,776,944 A	10/1988	Janata et al.	5,109,850 A	5/1992	Blanco et al.
4,777,953 A	10/1988	Ash et al.	5,120,420 A	6/1992	Nankai et al.
4,779,618 A	10/1988	Mund et al.	5,122,925 A	6/1992	Inpyn
4,781,798 A	11/1988	Gough	5,124,661 A	6/1992	Zellin et al.
4,784,736 A	11/1988	Lonsdale et al.	5,126,034 A	6/1992	Carter et al.
4,795,707 A	1/1989	Niiyama et al.	5,133,856 A	7/1992	Yamaguchi et al.
4,796,634 A	1/1989	Huntsman et al.	5,135,003 A	8/1992	Souma
4,805,624 A	2/1989	Yao et al.	5,135,004 A	8/1992	Adams et al.
4,813,424 A	3/1989	Wilkins	5,140,985 A	8/1992	Schroeder et al.
4,815,469 A	3/1989	Cohen et al.	5,141,868 A	8/1992	Shanks et al.
4,818,994 A	4/1989	Orth et al.	5,161,532 A	11/1992	Joseph
4,820,399 A	4/1989	Senda et al.	5,162,407 A	11/1992	Turner
4,822,337 A	4/1989	Newhouse et al.	5,165,407 A	11/1992	Wilson et al.
4,830,959 A	5/1989	McNeil et al.	5,174,291 A	12/1992	Schoonen et al.
4,832,797 A	5/1989	Vadgama et al.	5,190,041 A	3/1993	Palti
RE32,947 E	6/1989	Dormer et al.	5,192,416 A	3/1993	Wang et al.
4,840,893 A	6/1989	Hill et al.	5,198,367 A	3/1993	Aizawa et al.
4,848,351 A	7/1989	Finch	5,202,261 A	4/1993	Musho et al.
4,852,025 A	7/1989	Herpichböhmer	5,205,920 A	4/1993	Oyama et al.
4,854,322 A	8/1989	Ash et al.	5,208,154 A	5/1993	Weaver et al.
4,871,351 A	10/1989	Feingold	5,209,229 A	5/1993	Gilli
4,871,440 A	10/1989	Nagata et al.	5,217,595 A	6/1993	Smith et al.
4,874,500 A	10/1989	Madou et al.	5,228,449 A	7/1993	Christ et al.
4,890,620 A	1/1990	Gough	5,229,282 A	7/1993	Yoshioka et al.
4,894,137 A	1/1990	Takizawa et al.	5,234,835 A	8/1993	Nestor et al.
4,895,147 A	1/1990	Bodicky et al.	5,238,729 A	8/1993	Debe
4,897,162 A	1/1990	Lewandowski et al.	5,245,314 A	9/1993	Kah et al.
4,897,173 A	1/1990	Nankai et al.	5,246,867 A	9/1993	Lakowicz et al.
4,909,908 A	3/1990	Ross et al.	5,250,439 A	10/1993	Musho et al.
4,911,794 A	3/1990	Parce et al.	5,262,035 A	11/1993	Gregg et al.
4,917,800 A	4/1990	Lonsdale et al.	5,262,305 A	11/1993	Heller et al.
4,919,141 A	4/1990	Zier et al.	5,264,103 A	11/1993	Yoshioka et al.
4,919,767 A	4/1990	Vadgama et al.	5,264,104 A	11/1993	Gregg et al.
4,921,199 A	5/1990	Villaveces	5,264,105 A	11/1993	Gregg et al.
4,923,586 A	5/1990	Katayama et al.	5,264,106 A	11/1993	McAleer et al.
4,925,268 A	5/1990	Iyer et al.	5,271,815 A	12/1993	Wong
4,927,516 A	5/1990	Yamaguchi et al.	5,279,294 A	1/1994	Anderson
4,934,369 A	6/1990	Maxwell	5,284,156 A	2/1994	Schramm et al.
4,935,105 A	6/1990	Churchouse	5,285,792 A	2/1994	Sjoquist et al.
4,935,345 A	6/1990	Guibeau et al.	5,286,362 A	2/1994	Hoenes et al.
4,938,860 A	7/1990	Wogoman	5,286,364 A	2/1994	Yacynych et al.
4,944,299 A	7/1990	Silvian	5,288,636 A	2/1994	Pollmann et al.
4,950,378 A	8/1990	Nagara	5,289,497 A	2/1994	Jackobson et al.
4,953,552 A	9/1990	DeMarzo	5,293,546 A	3/1994	Tadros et al.
4,954,129 A	9/1990	Giuliani et al.	5,293,877 A	3/1994	O'Hara et al.
4,969,468 A	11/1990	Byers et al.	5,299,571 A	4/1994	Mastrototaro
4,970,145 A	11/1990	Bennetto et al.	5,305,008 A	4/1994	Turner et al.
4,974,929 A	12/1990	Curry	5,320,098 A	6/1994	Davidson
4,986,271 A	1/1991	Wilkins	5,320,715 A	6/1994	Berg
4,988,341 A	1/1991	Columbus et al.	5,320,725 A	6/1994	Gregg et al.
4,994,167 A	2/1991	Shults et al.	5,322,063 A	6/1994	Allen et al.
4,995,402 A	2/1991	Smith et al.	5,333,615 A	8/1994	Craeli et al.
5,000,180 A	3/1991	Kuypers et al.	5,337,747 A	8/1994	Neftel
5,001,054 A	3/1991	Wagner	5,340,722 A	8/1994	Wolfbeis et al.
5,002,054 A	3/1991	Ash et al.	5,342,789 A	8/1994	Chick et al.
5,006,110 A	4/1991	Garrison et al.	5,352,348 A	10/1994	Young et al.
5,013,161 A	5/1991	Zaragoza et al.	5,356,786 A	10/1994	Heller et al.
5,019,974 A	5/1991	Beckers	5,360,404 A	11/1994	Novacek et al.
5,035,860 A	7/1991	Kleingeld et al.	5,368,028 A	11/1994	Palti
			5,372,133 A	12/1994	Hogen Esch
			5,372,427 A	12/1994	Padovani et al.
			5,376,251 A	12/1994	Kaneko et al.
			5,378,628 A	1/1995	Gratzel et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,379,238	A	1/1995	Stark	5,711,001	A	1/1998	Bussan et al.
5,387,327	A	2/1995	Khan	5,711,297	A	1/1998	Iliff et al.
5,390,671	A	2/1995	Lord et al.	5,711,861	A	1/1998	Ward et al.
5,391,250	A	2/1995	Cheney, II et al.	5,711,862	A	1/1998	Sakoda et al.
5,395,504	A	3/1995	Saurer et al.	5,724,030	A	3/1998	Urbas et al.
5,400,782	A	3/1995	Beaubiah	5,733,044	A	3/1998	Rose et al.
5,400,794	A	3/1995	Gorman	5,733,259	A	3/1998	Valcke et al.
5,408,999	A	4/1995	Singh et al.	5,733,313	A	3/1998	Barreras, Sr. et al.
5,410,326	A	4/1995	Goldstein	5,749,656	A	3/1998	Boehm et al.
5,411,647	A	5/1995	Johnson et al.	5,735,285	A	4/1998	Albert et al.
5,425,361	A	6/1995	Fenzlein et al.	5,741,211	A	4/1998	Renirie et al.
5,425,868	A	6/1995	Pedersen	5,748,103	A	5/1998	Flach et al.
5,431,160	A	7/1995	Wilkins	5,749,907	A	5/1998	Mann
5,431,921	A	7/1995	Thombre	5,758,290	A	5/1998	Nealon et al.
5,437,999	A	8/1995	Diebold et al.	5,766,131	A	6/1998	Kondo et al.
5,462,051	A	10/1995	Oka et al.	5,771,001	A	6/1998	Cobb
5,462,645	A	10/1995	Albery et al.	5,772,586	A	6/1998	Heinonen et al.
5,469,846	A	11/1995	Khan	5,778,879	A	7/1998	Ota et al.
5,472,317	A	12/1995	Field et al.	5,779,665	A	7/1998	Mastrototaro et al.
5,482,473	A	1/1996	Lord et al.	5,791,344	A	8/1998	Schulman et al.
5,489,414	A	2/1996	Schreiber et al.	5,798,961	A	8/1998	Heyden et al.
5,491,474	A	2/1996	Suni et al.	5,800,420	A	9/1998	Gross et al.
5,494,562	A	2/1996	Maley et al.	5,804,047	A	9/1998	Kambe et al.
5,496,453	A	3/1996	Uenoyama et al.	5,807,375	A	9/1998	Gross et al.
5,497,772	A	3/1996	Schulman et al.	5,814,020	A	9/1998	Gross
5,499,243	A	3/1996	Hall	5,820,551	A	10/1998	Hill et al.
5,507,288	A	4/1996	Bocker et al.	5,820,622	A	10/1998	Gross et al.
5,509,410	A	4/1996	Hill et al.	5,822,715	A	10/1998	Worthington et al.
5,514,718	A	5/1996	Lewis et al.	5,823,802	A	10/1998	Bartley
5,516,832	A	5/1996	Kennan et al.	5,827,184	A	10/1998	Netherly et al.
5,527,288	A	6/1996	Gross et al.	5,830,064	A	11/1998	Bradish et al.
5,531,878	A	7/1996	Vadgama et al.	5,833,603	A	11/1998	Kovacs et al.
5,532,686	A	7/1996	Urbas et al.	5,840,020	A	11/1998	Heinonen et al.
5,543,326	A	8/1996	Heller et al.	5,842,983	A	12/1998	Abel et al.
5,544,196	A	8/1996	Tiedmann, Jr. et al.	5,851,197	A	12/1998	Marano et al.
5,545,191	A	8/1996	Mann et al.	5,856,758	A	1/1999	Joffe et al.
5,549,568	A	8/1996	Sheilds	5,858,001	A	1/1999	Tsais et al.
5,551,427	A	9/1996	Altman	5,865,804	A	2/1999	Bachynsky
5,558,638	A	9/1996	Evers et al.	5,885,211	A	3/1999	Eppstein et al.
5,560,357	A	10/1996	Faupei et al.	5,891,049	A	4/1999	Cyrus et al.
5,562,713	A	10/1996	Silvian	5,899,855	A	5/1999	Brown
5,565,085	A	10/1996	Ikeda et al.	5,918,603	A	7/1999	Brown
5,567,302	A	10/1996	Song et al.	5,924,979	A	7/1999	Sedlow et al.
5,568,806	A	10/1996	Cheney, II et al.	5,925,021	A	7/1999	Castellano et al.
5,569,186	A	10/1996	Lord et al.	5,931,814	A	8/1999	Gross et al.
5,575,563	A	11/1996	Chiu et al.	5,935,224	A	8/1999	Svancarek et al.
5,581,206	A	12/1996	Chevallier et al.	5,942,979	A	8/1999	Luppino
5,582,184	A	12/1996	Erickson et al.	5,948,006	A	9/1999	Mann
5,582,697	A	12/1996	Ikeda et al.	5,951,485	A	9/1999	Cyrus et al.
5,582,698	A	12/1996	Flaherty et al.	5,951,521	A	9/1999	Mastrototaro et al.
5,584,813	A	12/1996	Livingston et al.	5,954,643	A	9/1999	Van Antwerp
5,586,553	A	12/1996	Halli et al.	5,954,685	A	9/1999	Tierny
5,589,326	A	12/1996	Deng et al.	5,957,854	A	9/1999	Besson et al.
5,593,852	A	1/1997	Heller et al.	5,961,451	A	10/1999	Reber et al.
5,596,150	A	1/1997	Arndt et al.	5,964,993	A	10/1999	Blubaugh, Jr. et al.
5,600,301	A	2/1997	Robinson, III	5,965,380	A	10/1999	Heller et al.
5,601,435	A	2/1997	Quy	5,971,922	A	10/1999	Arita et al.
5,609,575	A	3/1997	Larson et al.	5,972,199	A	10/1999	Heller et al.
5,617,851	A	4/1997	Lipkovker	5,987,353	A	11/1999	Khatchatrian et al.
5,623,933	A	4/1997	Amano et al.	5,993,411	A	11/1999	Choi
5,628,310	A	5/1997	Rao et al.	5,995,860	A	11/1999	Sun et al.
5,628,890	A	5/1997	Carter et al.	5,997,501	A	12/1999	Gross et al.
5,632,557	A	5/1997	Simons	6,001,067	A	12/1999	Shults et al.
5,634,468	A	6/1997	Platt et al.	6,004,278	A	12/1999	Botich et al.
5,651,869	A	7/1997	Yoshioka et al.	6,022,368	A	2/2000	Gavrinsky et al.
5,653,239	A	8/1997	Pompei et al.	6,024,699	A	2/2000	Surwit et al.
5,659,454	A	8/1997	Vermesse	6,026,321	A	2/2000	Miyata et al.
5,660,163	A	8/1997	Schulman et al.	6,027,459	A	2/2000	Shain et al.
5,665,222	A	9/1997	Heller et al.	6,028,413	A	2/2000	Brockmann
5,670,031	A	9/1997	Hintsche et al.	6,049,727	A	4/2000	Crothall
5,680,858	A	10/1997	Hansen et al.	6,052,565	A	4/2000	Ishikura et al.
5,682,233	A	10/1997	Brinda	6,056,718	A	5/2000	Funderburk et al.
5,695,623	A	12/1997	Michel et al.	6,068,399	A	5/2000	Tseng
5,707,502	A	1/1998	McCaffrey et al.	6,071,391	A	6/2000	Gotoh et al.
5,708,247	A	1/1998	McAleer et al.	6,083,710	A	7/2000	Heller et al.
				6,085,342	A	7/2000	Marholev et al.
				6,088,608	A	7/2000	Schulman et al.
				6,091,975	A	7/2000	Daddona et al.
				6,091,976	A	7/2000	Pfeiffer et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,091,987 A	7/2000	Thompson	6,461,496 B1	10/2002	Feldman et al.
6,093,172 A	7/2000	Funderburk et al.	6,478,736 B1	11/2002	Mault
6,096,364 A	8/2000	Bok et al.	6,482,176 B1	11/2002	Wich
6,097,480 A	8/2000	Kaplan	6,484,045 B1	11/2002	Holker et al.
6,102,896 A	8/2000	Roser	6,484,046 B1	11/2002	Say et al.
6,103,033 A	8/2000	Say et al.	6,493,069 B1	12/2002	Nagashimada et al.
6,117,290 A	9/2000	Say et al.	6,494,830 B1	12/2002	Wessel
6,119,028 A	9/2000	Schulman et al.	6,496,729 B2	12/2002	Thompson
6,120,676 A	9/2000	Heller et al.	6,497,655 B1	12/2002	Linberg et al.
6,121,009 A	9/2000	Heller et al.	6,503,381 B1	1/2003	Gotoh et al.
6,121,611 A	9/2000	Lindsay et al.	6,510,344 B1	1/2003	Halpern
6,122,351 A	9/2000	Schlueter, Jr. et al.	6,514,460 B1	2/2003	Fendrock
6,130,623 A	10/2000	MacLellan et al.	6,514,689 B2	2/2003	Han et al.
6,134,461 A	10/2000	Say et al.	6,514,718 B2	2/2003	Heller et al.
6,143,164 A	11/2000	Heller et al.	6,520,326 B2	2/2003	McIvor et al.
6,144,837 A	11/2000	Quy	6,522,927 B1	2/2003	Bishay et al.
6,144,871 A	11/2000	Saito et al.	6,540,891 B1	4/2003	Stewart et al.
6,159,147 A	12/2000	Lichter et al.	6,544,212 B2	4/2003	Galley et al.
6,161,095 A	12/2000	Brown	6,546,268 B1	4/2003	Ishikawa et al.
6,162,611 A	12/2000	Heller et al.	6,549,796 B2	4/2003	Sohrab
6,175,752 B1	1/2001	Say et al.	6,551,494 B1	4/2003	Heller et al.
6,186,982 B1	2/2001	Gross et al.	6,554,798 B1	4/2003	Lam et al.
6,192,891 B1	2/2001	Gravel et al.	6,558,320 B1	5/2003	Causey, III et al.
6,198,946 B1	3/2001	Shin et al.	6,558,321 B1	5/2003	Burd et al.
6,200,265 B1	3/2001	Walsh et al.	6,558,351 B1	5/2003	Steil et al.
6,203,495 B1	3/2001	Bardy et al.	6,560,471 B1	5/2003	Heller et al.
6,212,416 B1	4/2001	Ward et al.	6,561,975 B1	5/2003	Pool et al.
6,219,574 B1	4/2001	Cormier et al.	6,561,978 B1	5/2003	Conn et al.
6,233,471 B1	5/2001	Berner et al.	6,562,001 B2	5/2003	Lebel et al.
6,248,067 B1	6/2001	Causey, III et al.	6,564,105 B2	5/2003	Starkweather et al.
6,254,536 B1	7/2001	DeVito	6,565,509 B1	5/2003	Say et al.
6,254,586 B1	7/2001	Mann et al.	6,571,128 B2	5/2003	Lebel et al.
6,270,455 B1	8/2001	Brown	6,572,566 B2	6/2003	Effenhauser
6,275,717 B1	8/2001	Gross et al.	6,574,510 B2	6/2003	Von Arx et al.
6,283,761 B1	9/2001	Joao	6,576,101 B1	6/2003	Heller et al.
6,283,982 B1	9/2001	Levaughn et al.	6,577,899 B2	6/2003	Lebel et al.
6,284,478 B1	9/2001	Heller et al.	6,579,231 B1	6/2003	Phipps
6,291,200 B1	9/2001	LeJeune et al.	6,579,690 B1	6/2003	Bonnecaze et al.
6,293,925 B1	9/2001	Safabash et al.	6,585,644 B2	7/2003	Lebel et al.
6,294,997 B1	9/2001	Paratore et al.	6,589,229 B1	7/2003	Connelly et al.
6,295,506 B1	9/2001	Heinonen et al.	6,591,125 B1	7/2003	Buse et al.
6,298,255 B1	10/2001	Cordero et al.	6,592,745 B1	7/2003	Feldman et al.
6,299,347 B1	10/2001	Pompei	6,595,919 B2	7/2003	Berner et al.
6,299,757 B1	10/2001	Feldman et al.	6,600,997 B2	7/2003	Deweese et al.
6,304,766 B1	10/2001	Colvin, Jr.	6,603,995 B1	8/2003	Carter
6,306,104 B1	10/2001	Cunningham et al.	6,604,050 B2	8/2003	Trippel et al.
6,309,884 B1	10/2001	Cooper et al.	6,605,200 B1	8/2003	Mao et al.
6,314,317 B1	11/2001	Willis	6,605,201 B1	8/2003	Mao et al.
6,329,161 B1	12/2001	Heller et al.	6,607,509 B2	8/2003	Bobroff et al.
6,331,244 B1	12/2001	Lewis et al.	6,608,562 B1	8/2003	Kimura et al.
6,336,269 B1	1/2002	Eldridge et al.	6,610,012 B2	8/2003	Mault
6,338,790 B1	1/2002	Feldman et al.	6,611,206 B2	8/2003	Eshelman et al.
6,348,640 B1	2/2002	Navot et al.	6,616,819 B1	9/2003	Liamos et al.
6,359,444 B1	3/2002	Grimes	6,618,934 B1	9/2003	Feldman et al.
6,360,888 B1	3/2002	McIvor et al.	6,627,154 B1	9/2003	Goodman et al.
6,366,794 B1	4/2002	Moussy et al.	6,633,772 B2	10/2003	Ford et al.
6,368,141 B1	4/2002	Van Antwerp et al.	6,635,014 B2	10/2003	Starkweather et al.
6,368,274 B1	4/2002	Van Antwerp et al.	6,635,167 B1	10/2003	Batman et al.
6,377,828 B1	4/2002	Chaiken et al.	6,641,533 B2	11/2003	Causey, III et al.
6,377,894 B1	4/2002	Deweese et al.	6,645,359 B1	11/2003	Bhullar et al.
6,379,301 B1	4/2002	Worthington et al.	6,648,821 B2	11/2003	Lebel et al.
6,387,048 B1	5/2002	Schulman et al.	6,650,471 B2	11/2003	Doi
6,400,974 B1	6/2002	Lesho	6,654,625 B1	11/2003	Say et al.
6,405,066 B1	6/2002	Essenpreis et al.	6,656,114 B1	12/2003	Poulson et al.
6,409,740 B1	6/2002	Kuhr et al.	6,658,396 B1	12/2003	Tang et al.
6,413,393 B1	7/2002	Van Antwerp et al.	6,659,948 B2	12/2003	Lebel et al.
6,416,471 B1	7/2002	Kumar et al.	6,662,439 B1	12/2003	Bhullar
6,418,332 B1	7/2002	Mastrototaro et al.	6,668,196 B1	12/2003	Villegas et al.
6,418,346 B1	7/2002	Nelson et al.	6,676,290 B1	1/2004	Lu
6,424,847 B1	7/2002	Mastrototaro et al.	6,676,816 B2	1/2004	Mao et al.
6,427,088 B1	7/2002	Bowman, IV et al.	6,687,546 B2	2/2004	Lebel et al.
6,437,679 B1	8/2002	Roques	6,689,056 B1	2/2004	Kilcoyne et al.
6,440,068 B1	8/2002	Brown et al.	6,694,191 B2	2/2004	Starkweather et al.
6,442,413 B1	8/2002	Silver	6,695,860 B1	2/2004	Ward et al.
6,445,374 B2	9/2002	Albert et al.	6,698,269 B2	3/2004	Baber et al.
			6,699,188 B2	3/2004	Wessel
			6,702,857 B2	3/2004	Brauker et al.
			6,706,159 B2	3/2004	Moerman et al.
			6,730,072 B2	5/2004	Shawgo et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

6,730,200 B1	5/2004	Stewart et al.	7,058,453 B2	6/2006	Nelson et al.
6,731,976 B2	5/2004	Penn et al.	7,060,031 B2	6/2006	Webb et al.
6,733,446 B2	5/2004	Lebel et al.	7,073,246 B2	7/2006	Bhullar et al.
6,735,183 B2	5/2004	O'Toole et al.	7,074,307 B2	7/2006	Simpson et al.
6,735,479 B2	5/2004	Fabian et al.	7,081,195 B2	7/2006	Simpson et al.
6,736,957 B1	5/2004	Forrow et al.	7,082,334 B2	7/2006	Boute et al.
6,740,075 B2	5/2004	Lebel et al.	7,097,637 B2	8/2006	Triplett et al.
6,741,877 B1	5/2004	Shults et al.	7,098,803 B2	8/2006	Mann et al.
6,746,582 B2	6/2004	Heller et al.	7,108,778 B2	9/2006	Simpson et al.
6,748,445 B1	6/2004	Darcey et al.	7,110,803 B2	9/2006	Shults et al.
6,749,740 B2	6/2004	Liamos et al.	7,113,821 B1	9/2006	Sun et al.
6,758,810 B2	7/2004	Lebel et al.	7,118,667 B2	10/2006	Lee
6,764,581 B1	7/2004	Forrow et al.	7,124,027 B1	10/2006	Ernst et al.
6,767,440 B1	7/2004	Bhullar et al.	7,125,382 B2	10/2006	Zhou et al.
6,770,030 B1	8/2004	Schaupp et al.	7,134,999 B2	11/2006	Brauker et al.
6,773,671 B1	8/2004	Lewis et al.	7,136,689 B2	11/2006	Shults et al.
6,781,522 B2	8/2004	Sleva et al.	7,154,398 B2	12/2006	Chen et al.
6,790,178 B1	9/2004	Mault et al.	7,155,290 B2	12/2006	Von Arx et al.
6,804,558 B2	10/2004	Haller et al.	7,167,818 B2	1/2007	Brown
6,804,561 B2	10/2004	Stover	7,171,274 B2	1/2007	Starkweather et al.
6,809,653 B1	10/2004	Mann et al.	7,190,988 B2	3/2007	Say et al.
6,810,290 B2	10/2004	Lebel et al.	7,192,450 B2	3/2007	Brauker et al.
6,811,533 B2	11/2004	Lebel et al.	7,198,606 B2	4/2007	Boecker et al.
6,811,534 B2	11/2004	Bowman, IV et al.	7,203,549 B2	4/2007	Schommer et al.
6,813,519 B2	11/2004	Lebel et al.	7,207,974 B2	4/2007	Safabash et al.
6,830,551 B1	12/2004	Uchigaki et al.	7,220,387 B2	5/2007	Flaherty et al.
6,837,858 B2	1/2005	Cunningham et al.	7,225,535 B2	6/2007	Feldman et al.
6,837,988 B2	1/2005	Leong et al.	7,226,442 B2	6/2007	Sheppard et al.
6,849,052 B2	2/2005	Uchigaki et al.	7,226,978 B2	6/2007	Tapsak et al.
6,850,790 B2	2/2005	Berner et al.	7,228,162 B2	6/2007	Ward et al.
6,854,882 B2	2/2005	Chen	7,228,182 B2	6/2007	Healy et al.
6,862,465 B2	3/2005	Shults et al.	7,237,712 B2	7/2007	DeRocco et al.
6,873,268 B2	3/2005	Lebel et al.	7,267,665 B2	9/2007	Steil et al.
6,878,112 B2	4/2005	Linberg et al.	7,276,029 B2	10/2007	Goode, Jr. et al.
6,881,551 B2	4/2005	Heller et al.	7,276,146 B2	10/2007	Wilsey
6,892,085 B2	5/2005	McIvor et al.	7,276,147 B2	10/2007	Wilsey
6,893,545 B2	5/2005	Gotoh et al.	7,278,983 B2	10/2007	Ireland et al.
6,895,263 B2	5/2005	Shin et al.	7,286,894 B1	10/2007	Grant et al.
6,895,265 B2	5/2005	Silver	7,287,318 B2	10/2007	Bhullar et al.
6,923,764 B2	8/2005	Aceti et al.	7,291,497 B2	11/2007	Holmes et al.
6,931,327 B2	8/2005	Goode, Jr. et al.	7,295,867 B2	11/2007	Berner et al.
6,932,894 B2	8/2005	Mao et al.	7,297,151 B2	11/2007	Boecker et al.
6,936,006 B2	8/2005	Sabra	7,299,082 B2	11/2007	Feldman et al.
6,937,222 B2	8/2005	Numao	7,310,544 B2	12/2007	Brister et al.
6,940,403 B2	9/2005	Kail, IV	7,318,816 B2	1/2008	Bobroff et al.
6,941,163 B2	9/2005	Ford et al.	7,324,012 B2	1/2008	Mann et al.
6,942,518 B2	9/2005	Liamos et al.	7,324,850 B2	1/2008	Persen et al.
6,950,708 B2	9/2005	Bowman IV et al.	7,329,239 B2	2/2008	Safabash et al.
6,958,705 B2	10/2005	Lebel et al.	7,335,294 B2	2/2008	Heller et al.
6,959,211 B2	10/2005	Rule et al.	7,340,309 B2	3/2008	Miazga et al.
6,968,294 B2	11/2005	Gutta et al.	7,347,819 B2	3/2008	Lebel et al.
6,971,274 B2	12/2005	Olin	7,354,420 B2	4/2008	Steil et al.
6,971,999 B2	12/2005	Py et al.	7,364,592 B2	4/2008	Carr-Brendel et al.
6,973,706 B2	12/2005	Say et al.	7,366,556 B2	4/2008	Brister et al.
6,974,437 B2	12/2005	Lebel et al.	7,379,765 B2	5/2008	Petisce et al.
6,983,867 B1	1/2006	Fugere	7,381,184 B2	6/2008	Funderburk et al.
6,990,366 B2	1/2006	Say et al.	7,384,397 B2	6/2008	Zhang et al.
6,997,907 B2	2/2006	Safabash et al.	7,386,937 B2	6/2008	Bhullar et al.
6,998,247 B2	2/2006	Monfre et al.	7,387,010 B2	6/2008	Sunshine et al.
7,003,336 B2	2/2006	Holker et al.	7,399,277 B2	7/2008	Saidara et al.
7,003,340 B2	2/2006	Say et al.	7,401,111 B1	7/2008	Batman et al.
7,003,341 B2	2/2006	Say et al.	7,402,153 B2	7/2008	Steil et al.
7,009,511 B2	3/2006	Mazar et al.	7,404,796 B2	7/2008	Ginsberg
7,020,508 B2	3/2006	Stivoric et al.	7,407,493 B2	8/2008	Cane
7,022,072 B2	4/2006	Fox et al.	7,408,132 B2	8/2008	Wambsganss et al.
7,024,236 B2	4/2006	Ford et al.	7,416,541 B2	8/2008	Yuzhakov et al.
7,024,245 B2	4/2006	Lebel et al.	7,419,573 B2	9/2008	Gundel
7,025,743 B2	4/2006	Mann et al.	7,424,318 B2	9/2008	Brister et al.
7,027,931 B1	4/2006	Jones et al.	7,455,663 B2	11/2008	Bikovsky
7,029,444 B2	4/2006	Shin et al.	7,460,898 B2	12/2008	Brister et al.
7,041,068 B2	5/2006	Freeman et al.	7,467,003 B2	12/2008	Brister et al.
7,041,468 B2	5/2006	Drucker et al.	7,471,972 B2	12/2008	Rhodes et al.
7,043,305 B2	5/2006	KenKnight et al.	7,492,254 B2	2/2009	Bandy et al.
7,052,483 B2	5/2006	Wojcik	7,494,465 B2	2/2009	Brister et al.
7,056,302 B2	6/2006	Douglas	7,497,827 B2	3/2009	Brister et al.
			7,519,408 B2	4/2009	Rasdal et al.
			7,547,281 B2	6/2009	Hayes et al.
			7,565,197 B2	7/2009	Haubrich et al.
			7,568,619 B2	8/2009	Todd et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,569,030 B2	8/2009	Lebel et al.	8,098,201 B2	1/2012	Choi et al.
7,574,266 B2	8/2009	Dudding et al.	8,098,208 B2	1/2012	Ficker et al.
7,583,990 B2	9/2009	Goode, Jr. et al.	8,102,021 B2	1/2012	Degani
7,591,801 B2	9/2009	Brauker et al.	8,102,154 B2	1/2012	Bishop et al.
7,599,726 B2	10/2009	Goode, Jr. et al.	8,102,263 B2	1/2012	Yeo et al.
7,602,310 B2	10/2009	Mann et al.	8,102,789 B2	1/2012	Rosar et al.
7,604,178 B2	10/2009	Stewart	8,103,241 B2	1/2012	Young et al.
7,604,592 B2	10/2009	Freeman et al.	8,103,325 B2	1/2012	Swedlow et al.
7,613,491 B2	11/2009	Boock et al.	8,111,042 B2	2/2012	Bennett
7,615,007 B2	11/2009	Shults et al.	8,115,488 B2	2/2012	McDowell
7,618,369 B2	11/2009	Hayter et al.	8,116,681 B2	2/2012	Baarman
7,632,228 B2	12/2009	Brauker et al.	8,116,683 B2	2/2012	Baarman
7,637,868 B2	12/2009	Saint et al.	8,117,481 B2	2/2012	Anselmi et al.
7,640,048 B2	12/2009	Dobbles et al.	8,120,493 B2	2/2012	Burr
7,643,798 B2	1/2010	Ljung	8,124,452 B2	2/2012	Sheats
7,651,596 B2	1/2010	Petisce et al.	8,130,093 B2	3/2012	Mazar et al.
7,653,425 B2	1/2010	Hayter et al.	8,131,351 B2	3/2012	Kalgren et al.
7,654,956 B2	2/2010	Brister et al.	8,131,365 B2	3/2012	Zhang et al.
7,657,297 B2	2/2010	Simpson et al.	8,131,565 B2	3/2012	Dicks et al.
7,659,823 B1	2/2010	Killian et al.	8,132,037 B2	3/2012	Fehr et al.
7,666,149 B2	2/2010	Simons et al.	8,135,352 B2	3/2012	Langsweirdt et al.
7,668,596 B2	2/2010	Von Arx et al.	8,136,735 B2	3/2012	Arai et al.
7,697,967 B2	4/2010	Stafford	8,138,925 B2	3/2012	Downie et al.
7,699,807 B2	4/2010	Faust et al.	8,140,160 B2	3/2012	Pless et al.
7,701,052 B2	4/2010	Borland et al.	8,140,168 B2	3/2012	Olson et al.
7,711,402 B2	5/2010	Shults et al.	8,140,299 B2	3/2012	Siess
7,713,574 B2	5/2010	Brister et al.	8,150,321 B2	4/2012	Winter et al.
7,715,893 B2	5/2010	Kamath et al.	8,150,516 B2	4/2012	Levine et al.
7,727,147 B1	6/2010	Osorio et al.	8,172,805 B2	5/2012	Mogensen et al.
7,731,657 B2	6/2010	Stafford	8,179,266 B2	5/2012	Hermle
7,736,344 B2	6/2010	Moberg et al.	8,262,618 B2	9/2012	Scheurer
7,741,734 B2	6/2010	Joannopoulos et al.	8,409,145 B2	4/2013	Raymond et al.
7,763,042 B2	7/2010	Iio et al.	8,538,512 B1	9/2013	Bibian et al.
7,768,387 B2	8/2010	Fennell et al.	8,617,069 B2	12/2013	Bernstein et al.
7,771,352 B2	8/2010	Shults et al.	8,808,515 B2	8/2014	Feldman et al.
7,774,145 B2	8/2010	Brauker et al.	8,870,822 B2	10/2014	Thalmann et al.
7,778,680 B2	8/2010	Goode, Jr. et al.	8,880,138 B2	11/2014	Cho
7,779,332 B2	8/2010	Karr et al.	9,259,175 B2	2/2016	Stafford
7,782,192 B2	8/2010	Jeckelmann et al.	9,295,786 B2	3/2016	Gottlieb et al.
7,783,333 B2	8/2010	Brister et al.	2001/0016682 A1	8/2001	Berner et al.
7,791,467 B2	9/2010	Mazar et al.	2001/0037060 A1	11/2001	Thompson et al.
7,792,562 B2	9/2010	Shults et al.	2001/0037366 A1	11/2001	Webb et al.
7,813,809 B2	10/2010	Strother et al.	2001/0047127 A1	11/2001	New et al.
7,822,454 B1	10/2010	Alden et al.	2001/0056262 A1	12/2001	Cabiri et al.
7,826,981 B2	11/2010	Goode, Jr. et al.	2002/0010390 A1	1/2002	Guice et al.
7,831,310 B2	11/2010	Lebel et al.	2002/0013522 A1	1/2002	Lav et al.
7,833,151 B2	11/2010	Khait et al.	2002/0013538 A1	1/2002	Teller
7,850,652 B2	12/2010	Liniger et al.	2002/0019022 A1	2/2002	Dunn et al.
7,860,574 B2	12/2010	Von Arx et al.	2002/0019584 A1	2/2002	Schulze et al.
7,866,026 B1	1/2011	Wang et al.	2002/0019606 A1	2/2002	Lebel et al.
7,882,611 B2	2/2011	Shah et al.	2002/0022855 A1	2/2002	Bobroff et al.
7,889,069 B2	2/2011	Fifolt et al.	2002/0023852 A1	2/2002	Mclvor et al.
7,896,844 B2	3/2011	Thalmann et al.	2002/0039026 A1	4/2002	Stroth et al.
7,899,511 B2	3/2011	Shults et al.	2002/0042090 A1	4/2002	Heller et al.
7,905,833 B2	3/2011	Brister et al.	2002/0045808 A1	4/2002	Ford et al.
7,912,655 B2	3/2011	Power et al.	2002/0049482 A1	4/2002	Fabian et al.
7,912,674 B2	3/2011	Killoren Clark et al.	2002/0050250 A1	5/2002	Peterson et al.
7,914,450 B2	3/2011	Goode, Jr. et al.	2002/0055711 A1	5/2002	Lavi et al.
7,916,013 B2	3/2011	Stevenson	2002/0065454 A1	5/2002	Lebel et al.
7,955,258 B2	6/2011	Goscha et al.	2002/0072784 A1	6/2002	Sheppard et al.
7,955,297 B2	6/2011	Radmer et al.	2002/0074162 A1	6/2002	Su et al.
7,970,448 B2	6/2011	Shults et al.	2002/0082487 A1	6/2002	Kollias et al.
7,974,672 B2	7/2011	Shults et al.	2002/0084196 A1	7/2002	Liamos et al.
7,976,467 B2	7/2011	Young et al.	2002/0091796 A1	7/2002	Higginson et al.
7,978,063 B2	7/2011	Baldus et al.	2002/0093969 A1	7/2002	Lin et al.
7,985,203 B2	7/2011	Haueter et al.	2002/0103499 A1	8/2002	Perez et al.
7,999,674 B2	8/2011	Kamen	2002/0106709 A1	8/2002	Potts et al.
8,000,918 B2	8/2011	Ffield et al.	2002/0118528 A1	8/2002	Su et al.
8,072,310 B1	12/2011	Everhart	2002/0119711 A1	8/2002	VanAntwerp et al.
8,090,445 B2	1/2012	Ginggen	2002/0128594 A1	9/2002	Das et al.
8,093,991 B2	1/2012	Stevenson et al.	2002/0130042 A1	9/2002	Moerman et al.
8,094,009 B2	1/2012	Allen et al.	2002/0151770 A1	10/2002	Noll et al.
8,098,159 B2	1/2012	Batra et al.	2002/0154050 A1	10/2002	Krupp et al.
8,098,160 B2	1/2012	Howarth et al.	2002/0161288 A1	10/2002	Shin et al.
8,098,161 B2	1/2012	Lavedas	2002/0164836 A1	11/2002	Ho
			2002/0165462 A1	11/2002	Westbrook et al.
			2002/0169369 A1	11/2002	Ward et al.
			2002/0169635 A1	11/2002	Shillingburg
			2002/0183604 A1	12/2002	Gowda et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2002/0185128 A1	12/2002	Theobald	2004/0122353 A1	6/2004	Shahmirian et al.
2002/0185130 A1	12/2002	Wright et al.	2004/0122489 A1	6/2004	Mazar et al.
2002/0197522 A1	12/2002	Lawrence et al.	2004/0116866 A1	7/2004	Gorman et al.
2002/0198444 A1	12/2002	Ughigaki et al.	2004/0133164 A1	7/2004	Funderburk et al.
2003/0004403 A1	1/2003	Drinan et al.	2004/0135684 A1	7/2004	Steinthal et al.
2003/0020477 A1	1/2003	Goldstein	2004/0138544 A1	7/2004	Ward et al.
2003/0023317 A1	1/2003	Brauker et al.	2004/0138588 A1	7/2004	Saikley et al.
2003/0023461 A1	1/2003	Quintanilla et al.	2004/0138688 A1	7/2004	Giraud
2003/0032867 A1	2/2003	Crothall et al.	2004/0146909 A1	7/2004	Duong et al.
2003/0032874 A1	2/2003	Rhodes et al.	2004/0147996 A1	7/2004	Miazga et al.
2003/0042137 A1	3/2003	Mao et al.	2004/0152622 A1	8/2004	Keith et al.
2003/0060692 A1	3/2003	Ruchti et al.	2004/0158207 A1	8/2004	Hunn et al.
2003/0060753 A1	3/2003	Starkweather et al.	2004/0167801 A1	8/2004	Say et al.
2003/0065308 A1	4/2003	Lebel et al.	2004/0171910 A1	9/2004	Moore-Steele
2003/0069510 A1	4/2003	Semler	2004/0171921 A1	9/2004	Say et al.
2003/0076792 A1	4/2003	Theimer	2004/0176672 A1	9/2004	Silver et al.
2003/0077642 A1	4/2003	Fritsch et al.	2004/0186362 A1	9/2004	Brauker et al.
2003/0078481 A1	4/2003	McIvor et al.	2004/0186365 A1	9/2004	Jin et al.
2003/0078560 A1	4/2003	Miller et al.	2004/0193020 A1	9/2004	Chiba et al.
2003/0088166 A1	5/2003	Say et al.	2004/0193025 A1	9/2004	Steil et al.
2003/0097092 A1	5/2003	Flaherty	2004/0193090 A1	9/2004	Lebel et al.
2003/0100040 A1	5/2003	Bonnecaze et al.	2004/0197846 A1	10/2004	Hockersmith et al.
2003/0100821 A1	5/2003	Heller et al.	2004/0199056 A1	10/2004	Husemann et al.
2003/0109775 A1	6/2003	O'Neil et al.	2004/0199059 A1	10/2004	Brauker et al.
2003/0114897 A1	6/2003	Von Arx et al.	2004/0204687 A1	10/2004	Mogensen et al.
2003/0114898 A1	6/2003	Von Arx et al.	2004/0204744 A1	10/2004	Penner et al.
2003/0119457 A1	6/2003	Standke	2004/0204868 A1	10/2004	Maynard et al.
2003/0125612 A1	7/2003	Fox et al.	2004/0206625 A1	10/2004	Bhullar et al.
2003/0130616 A1	7/2003	Steil et al.	2004/0206916 A1	10/2004	Colvin, Jr. et al.
2003/0134347 A1	7/2003	Heller et al.	2004/0221057 A1	11/2004	Darcey et al.
2003/0135333 A1	7/2003	Aceti et al.	2004/0223876 A1	11/2004	Kirollos et al.
2003/0144579 A1	7/2003	Buss	2004/0223985 A1	11/2004	Dunfield et al.
2003/0144581 A1	7/2003	Conn et al.	2004/0225199 A1	11/2004	Evanyk et al.
2003/0144608 A1	7/2003	Kojima et al.	2004/0225338 A1	11/2004	Lebel et al.
2003/0153900 A1	8/2003	Aceti et al.	2004/0236200 A1	11/2004	Say et al.
2003/0155656 A1	8/2003	Chiu et al.	2004/0236251 A1	11/2004	Roe et al.
2003/0168338 A1	9/2003	Gao et al.	2004/0240426 A1	12/2004	Wu et al.
2003/0176933 A1	9/2003	Lebel et al.	2004/0249999 A1	12/2004	Connolly et al.
2003/0187338 A1	10/2003	Say et al.	2004/0254433 A1	12/2004	Bandis et al.
2003/0188427 A1	10/2003	Say et al.	2004/0254434 A1	12/2004	Goodnow et al.
2003/0199790 A1	10/2003	Boecker et al.	2004/0258564 A1	12/2004	Charlton
2003/0199910 A1	10/2003	Boecker et al.	2004/0267300 A1	12/2004	Mace
2003/0204290 A1	10/2003	Sadler et al.	2005/0001024 A1	1/2005	Kusaka et al.
2003/0208113 A1	11/2003	Mault et al.	2005/0003470 A1	1/2005	Nelson et al.
2003/0208114 A1	11/2003	Ackerman	2005/0004439 A1	1/2005	Shin et al.
2003/0212317 A1	11/2003	Kovatchev et al.	2005/0004494 A1	1/2005	Perez et al.
2003/0212379 A1	11/2003	Bylund et al.	2005/0010269 A1	1/2005	Lebel et al.
2003/0212579 A1	11/2003	Brown et al.	2005/0017864 A1	1/2005	Tsoukalis
2003/0216621 A1	11/2003	Alpert et al.	2005/0027177 A1	2/2005	Shin et al.
2003/0216630 A1	11/2003	Jersey-Willuhn et al.	2005/0027180 A1	2/2005	Goode, Jr. et al.
2003/0217966 A1	11/2003	Tapsak et al.	2005/0027181 A1	2/2005	Goode, Jr. et al.
2003/0225361 A1	12/2003	Sabra	2005/0027463 A1	2/2005	Goode, Jr. et al.
2004/0002682 A1	1/2004	Kovelman et al.	2005/0031689 A1	2/2005	Shults et al.
2004/0010207 A1	1/2004	Flaherty et al.	2005/0038332 A1	2/2005	Saidara et al.
2004/0011671 A1	1/2004	Shults et al.	2005/0043598 A1	2/2005	Goode, Jr. et al.
2004/0017300 A1	1/2004	Kotzin et al.	2005/0070819 A1	3/2005	Poux et al.
2004/0030226 A1	2/2004	Quy	2005/0085872 A1	4/2005	Yanagihara et al.
2004/0030531 A1	2/2004	Miller et al.	2005/0090607 A1	4/2005	Tapsak et al.
2004/0030581 A1	2/2004	Levin et al.	2005/0090850 A1	4/2005	Thoes et al.
2004/0039255 A1	2/2004	Simonsen et al.	2005/0096511 A1	5/2005	Fox et al.
2004/0039298 A1	2/2004	Abreu	2005/0096512 A1	5/2005	Fox et al.
2004/0040840 A1	3/2004	Mao et al.	2005/0103624 A1	5/2005	Bhullar et al.
2004/0045879 A1	3/2004	Shults et al.	2005/0104457 A1	5/2005	Jordan et al.
2004/0054263 A1	3/2004	Moerman et al.	2005/0106713 A1	5/2005	Phan et al.
2004/0060818 A1	4/2004	Feldman et al.	2005/0112169 A1	5/2005	Brauker et al.
2004/0061232 A1	4/2004	Shah et al.	2005/0112544 A1	5/2005	Xu et al.
2004/0063435 A1	4/2004	Sakamoto et al.	2005/0113653 A1	5/2005	Fox et al.
2004/0064068 A1	4/2004	DeNuzzio et al.	2005/0113886 A1	5/2005	Fischell et al.
2004/0064133 A1	4/2004	Miller et al.	2005/0114068 A1	5/2005	Chey et al.
2004/0096959 A1	5/2004	Steine et al.	2005/0116683 A1	6/2005	Cheng et al.
2004/0100376 A1	5/2004	Lye et al.	2005/0121322 A1	6/2005	Say et al.
2004/0105411 A1	6/2004	Boatwright et al.	2005/0131346 A1	6/2005	Douglas
2004/0106858 A1	6/2004	Say et al.	2005/0137488 A1	6/2005	Henry et al.
2004/0106859 A1	6/2004	Say et al.	2005/0137530 A1	6/2005	Campbell et al.
2004/0116847 A1	6/2004	Wall	2005/0143635 A1	6/2005	Kamath et al.
			2005/0151976 A1	7/2005	Toma
			2005/0154410 A1	7/2005	Conway et al.
			2005/0165404 A1	7/2005	Miller
			2005/0171442 A1	8/2005	Shirasaki et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0173245	A1	8/2005	Feldman et al.	2006/0036145	A1	4/2006	Chambers et al.
2005/0176136	A1	8/2005	Burd et al.	2006/0081469	A1	4/2006	Lee
2005/0177398	A1	8/2005	Watanabe et al.	2006/0091006	A1	5/2006	Wang et al.
2005/0181010	A1	8/2005	Hunter et al.	2006/0129173	A1	6/2006	Wilkinson
2005/0182306	A1	8/2005	Sloan	2006/0129733	A1	6/2006	Solbelman
2005/0182358	A1	8/2005	Veit et al.	2006/0142651	A1	6/2006	Brister et al.
2005/0187720	A1	8/2005	Goode, Jr. et al.	2006/0154642	A1	7/2006	Scannell
2005/0192494	A1	9/2005	Ginsberg	2006/0155180	A1	7/2006	Brister et al.
2005/0192557	A1	9/2005	Brauker et al.	2006/0155210	A1	7/2006	Beckman et al.
2005/0195930	A1	9/2005	Spital et al.	2006/0155317	A1	7/2006	List
2005/0197554	A1	9/2005	Polcha	2006/0161664	A1	7/2006	Mastrototaro et al.
2005/0199494	A1	9/2005	Say et al.	2006/0166629	A1	7/2006	Reggiardo
2005/0203360	A1	9/2005	Brauker et al.	2006/0173260	A1	8/2006	Gaoni et al.
2005/0204134	A1	9/2005	Von Arx et al.	2006/0173406	A1	8/2006	Hayes et al.
2005/0215871	A1	9/2005	Feldman et al.	2006/0173444	A1	8/2006	Choy et al.
2005/0221504	A1	10/2005	Petrano et al.	2006/0183984	A1	8/2006	Dobbles et al.
2005/0222518	A1	10/2005	Dib	2006/0183985	A1	8/2006	Brister et al.
2005/0222599	A1	10/2005	Czemecki et al.	2006/0189863	A1	8/2006	Peyser et al.
2005/0236277	A9	10/2005	Imran et al.	2006/0189939	A1	8/2006	Gonnelli et al.
2005/0236361	A1	10/2005	Ufer et al.	2006/0193375	A1	8/2006	Lee et al.
2005/0239154	A1	10/2005	Feldman et al.	2006/0195029	A1	8/2006	Shults et al.
2005/0239156	A1	10/2005	Drucker et al.	2006/0200970	A1	9/2006	Brister et al.
2005/0241957	A1	11/2005	Mao et al.	2006/0200981	A1	9/2006	Bhullar et al.
2005/0245795	A1	11/2005	Goode, Jr. et al.	2006/0200982	A1	9/2006	Bhullar et al.
2005/0245799	A1	11/2005	Brauker et al.	2006/0202805	A1	9/2006	Schulman et al.
2005/0245839	A1	11/2005	Stivoric et al.	2006/0202859	A1	9/2006	Mastrototaro et al.
2005/0245844	A1	11/2005	Mace et al.	2006/0220839	A1	10/2006	Fifolt et al.
2005/0245904	A1	11/2005	Estes et al.	2006/0222566	A1	10/2006	Brauker et al.
2005/0247319	A1	11/2005	Berger	2006/0224109	A1	10/2006	Steil et al.
2005/0251033	A1	11/2005	Scarantino et al.	2006/0224141	A1	10/2006	Rush et al.
2005/0261563	A1	11/2005	Zhou et al.	2006/0224171	A1	10/2006	Sakata et al.
2005/0267325	A1	12/2005	Bouchier et al.	2006/0226985	A1	10/2006	Goodnow et al.
2005/0277164	A1	12/2005	Drucker et al.	2006/0229512	A1	10/2006	Petisce et al.
2005/0283114	A1	12/2005	Bresina et al.	2006/0233839	A1	10/2006	Jacquet
2005/0283208	A1	12/2005	Von Arx et al.	2006/0247508	A1	11/2006	Fennell
2005/0283209	A1	12/2005	Katoozi et al.	2006/0247710	A1	11/2006	Goetz et al.
2005/0284758	A1	12/2005	Funke et al.	2006/0248398	A1	11/2006	Neel et al.
2005/0287620	A1	12/2005	Heller et al.	2006/0253085	A1	11/2006	Geismar et al.
2006/0001538	A1	1/2006	Kraft et al.	2006/0253086	A1	11/2006	Moberg et al.
2006/0001551	A1	1/2006	Kraft et al.	2006/0258929	A1	11/2006	Goode, Jr. et al.
2006/0004270	A1	1/2006	Bedard et al.	2006/0264785	A1	11/2006	Dring et al.
2006/0004272	A1	1/2006	Shah et al.	2006/0264888	A1	11/2006	Moberg et al.
2006/0004303	A1	1/2006	Weidenhaupt et al.	2006/0270922	A1	11/2006	Brauker et al.
2006/0009727	A1	1/2006	O'Mahony et al.	2006/0272652	A1	12/2006	Stocker et al.
2006/0010098	A1	1/2006	Goodnow et al.	2006/0276714	A1	12/2006	Holt et al.
2006/0012464	A1	1/2006	Nitzan et al.	2006/0276724	A1	12/2006	Freeman et al.
2006/0015020	A1	1/2006	Neale et al.	2006/0276771	A1	12/2006	Galley et al.
2006/0015024	A1	1/2006	Brister et al.	2006/0287591	A1	12/2006	Ocvirk et al.
2006/0016700	A1*	1/2006	Brister A61B 5/6848 205/777.5	2006/0287691	A1	12/2006	Drew
2006/0019327	A1	1/2006	Brister et al.	2006/0290496	A1	12/2006	Peeters et al.
2006/0020186	A1	1/2006	Brister et al.	2006/0293607	A1	12/2006	Alt et al.
2006/0020187	A1	1/2006	Brister et al.	2007/0016381	A1	1/2007	Kamath et al.
2006/0020188	A1	1/2006	Kamath et al.	2007/0017983	A1	1/2007	Frank et al.
2006/0020189	A1	1/2006	Brister et al.	2007/0027381	A1	2/2007	Stafford
2006/0020190	A1	1/2006	Kamath et al.	2007/0027507	A1	2/2007	Burdett et al.
2006/0020191	A1	1/2006	Brister et al.	2007/0030154	A1	2/2007	Aiki et al.
2006/0020192	A1	1/2006	Brister et al.	2007/0032706	A1	2/2007	Kamath et al.
2006/0020300	A1	1/2006	Nghiem et al.	2007/0033074	A1	2/2007	Nitzan et al.
2006/0025662	A1	2/2006	Buse et al.	2007/0038044	A1	2/2007	Dobbies et al.
2006/0025663	A1	2/2006	Talbot et al.	2007/0055799	A1	3/2007	Koehler et al.
2006/0029177	A1	2/2006	Cranford, Jr. et al.	2007/0056858	A1	3/2007	Chen et al.
2006/0031094	A1	2/2006	Cohen et al.	2007/0059196	A1	3/2007	Brister et al.
2006/0036139	A1	2/2006	Brister et al.	2007/0060814	A1	3/2007	Stafford
2006/0036140	A1	2/2006	Brister et al.	2007/0066873	A1	3/2007	Kamath et al.
2006/0036141	A1	2/2006	Kamath et al.	2007/0068807	A1	3/2007	Feldman et al.
2006/0036142	A1	2/2006	Brister et al.	2007/0071681	A1	3/2007	Gadkar et al.
2006/0036143	A1	2/2006	Brister et al.	2007/0073129	A1	3/2007	Shah et al.
2006/0036144	A1	2/2006	Brister et al.	2007/0078320	A1	4/2007	Stafford
2006/0040793	A1	2/2006	Martens et al.	2007/0078321	A1	4/2007	Mazza et al.
2006/0042080	A1	3/2006	Say et al.	2007/0078322	A1	4/2007	Stafford
2006/0047220	A1	3/2006	Sakata et al.	2007/0078323	A1	4/2007	Reggiardo et al.
2006/0049359	A1	3/2006	Busta et al.	2007/0090511	A1	4/2007	Borland et al.
2006/0058588	A1	3/2006	Zdeblick	2007/0095661	A1	5/2007	Wang et al.
2006/0064035	A1	3/2006	Wang et al.	2007/0100218	A1	5/2007	Sweitzer et al.
				2007/0100222	A1	5/2007	Mastrototaro et al.
				2007/0106133	A1	5/2007	Satchwell et al.
				2007/0106135	A1	5/2007	Sloan et al.
				2007/0108048	A1	5/2007	Wang et al.
				2007/0110124	A1	5/2007	Zaragoza et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2007/0111196 A1	5/2007	Alarcon et al.	2008/0081977 A1	4/2008	Hayter et al.
2007/0123819 A1	5/2007	Memoe et al.	2008/0083617 A1	4/2008	Simpson et al.
2007/0124002 A1	5/2007	Estes et al.	2008/0086042 A1	4/2008	Brister et al.
2007/0129621 A1	6/2007	Kellogg et al.	2008/0086044 A1	4/2008	Brister et al.
2007/0149875 A1	6/2007	Ouyang et al.	2008/0086273 A1	4/2008	Shults et al.
2007/0156033 A1	7/2007	Causey, III et al.	2008/0092638 A1	4/2008	Brenneman et al.
2007/0156094 A1	7/2007	Safabash et al.	2008/0092911 A1	4/2008	Schulman et al.
2007/0163880 A1	7/2007	Woo et al.	2008/0097246 A1	4/2008	Stafford
2007/0168224 A1	7/2007	Letzt et al.	2008/0097289 A1	4/2008	Steil et al.
2007/0173706 A1	7/2007	Neinast et al.	2008/0097908 A1	4/2008	Dicks et al.
2007/0173741 A1	7/2007	Deshmukh et al.	2008/0011971 A1	5/2008	Reggiardo et al.
2007/0173761 A1	7/2007	Kanderian et al.	2008/0102441 A1	5/2008	Chen et al.
2007/0179349 A1	8/2007	Hoyme et al.	2008/0108942 A1	5/2008	Brister et al.
2007/0179352 A1	8/2007	Randlov et al.	2008/0112848 A1	5/2008	Huffstodt et al.
2007/0191701 A1	8/2007	Feldman et al.	2008/0114280 A1	5/2008	Stafford
2007/0197889 A1	8/2007	Brister et al.	2008/0119705 A1	5/2008	Patel et al.
2007/0199818 A1	8/2007	Petyt et al.	2008/0119707 A1	5/2008	Stafford
2007/0203407 A1	8/2007	Hoss et al.	2008/0133702 A1	6/2008	Sharma et al.
2007/0203966 A1	8/2007	Brauker et al.	2008/0139910 A1	6/2008	Mastrototaro et al.
2007/0208246 A1	9/2007	Brauker et al.	2008/0148873 A1	6/2008	Wang
2007/0213611 A1	9/2007	Simpson et al.	2008/0154205 A1	6/2008	Wojcik
2007/0219496 A1	9/2007	Kamen et al.	2008/0154513 A1	6/2008	Kovatchev et al.
2007/0222609 A1	9/2007	Duron et al.	2008/0161666 A1	7/2008	Feldman et al.
2007/0227911 A1	10/2007	Wang et al.	2008/0167543 A1	7/2008	Say et al.
2007/0232880 A1	10/2007	Siddiqui et al.	2008/0167572 A1	7/2008	Stivoric et al.
2007/0233013 A1	10/2007	Schoenberg et al.	2008/0167578 A1	7/2008	Bryer et al.
2007/0235331 A1	10/2007	Simpson et al.	2008/0172205 A1	7/2008	Breton et al.
2007/0244368 A1	10/2007	Bayloff et al.	2008/0179187 A1	7/2008	Ouyang
2007/0244383 A1	10/2007	Talbot et al.	2008/0182537 A1	7/2008	Manku et al.
2007/0244398 A1	10/2007	Lo et al.	2008/0183060 A1	7/2008	Steil et al.
2007/0249922 A1	10/2007	Peyser et al.	2008/0183061 A1	7/2008	Goode, Jr. et al.
2007/0253021 A1	11/2007	Mehta et al.	2008/0183399 A1	7/2008	Goode, Jr. et al.
2007/0255116 A1	11/2007	Mehta et al.	2008/0188731 A1	8/2008	Brister et al.
2007/0255125 A1	11/2007	Moberg et al.	2008/0188796 A1	8/2008	Steil et al.
2007/0255302 A1	11/2007	Koepfel et al.	2008/0189051 A1	8/2008	Goode, Jr. et al.
2007/0255348 A1	11/2007	Holtzclaw	2008/0194926 A1	8/2008	Goh et al.
2007/0255531 A1	11/2007	Drew	2008/0194934 A1	8/2008	Ray et al.
2007/0258395 A1	11/2007	Jollota et al.	2008/0194935 A1	8/2008	Brister et al.
2007/0270672 A1	11/2007	Hayter	2008/0194936 A1	8/2008	Goode, Jr. et al.
2007/0282299 A1	12/2007	Hellwig	2008/0194937 A1	8/2008	Goode, Jr. et al.
2007/0285238 A1	12/2007	Batra	2008/0194938 A1	8/2008	Brister et al.
2008/0004512 A1	1/2008	Funderbunk et al.	2008/0195049 A1	8/2008	Thalmann et al.
2008/0004573 A1	1/2008	Kaufmann et al.	2008/0195232 A1	8/2008	Carr-Brendel et al.
2008/0009304 A1	1/2008	Fry	2008/0195967 A1	8/2008	Goode, Jr. et al.
2008/0009692 A1	1/2008	Stafford	2008/0197024 A1	8/2008	Simpson et al.
2008/0009805 A1	1/2008	Ethelfeld	2008/0200788 A1	8/2008	Brister et al.
2008/0017522 A1	1/2008	Heller et al.	2008/0200789 A1	8/2008	Brister et al.
2008/0018433 A1	1/2008	Pitt-Pladdy	2008/0200791 A1	8/2008	Simpson et al.
2008/0021666 A1	1/2008	Goode, Jr. et al.	2008/0200897 A1	8/2008	Hoss et al.
2008/0027474 A1	1/2008	Curry et al.	2008/0208025 A1	8/2008	Shults et al.
2008/0029391 A1	2/2008	Mao et al.	2008/0208113 A1	8/2008	Damiano et al.
2008/0030369 A1	2/2008	Mann et al.	2008/0214915 A1	9/2008	Brister et al.
2008/0031941 A1	2/2008	Pettersson	2008/0214918 A1	9/2008	Brister et al.
2008/0033254 A1	2/2008	Kamath et al.	2008/0228051 A1	9/2008	Shults et al.
2008/0033268 A1	2/2008	Stafford	2008/0228054 A1	9/2008	Shults et al.
2008/0033273 A1	2/2008	Zhou et al.	2008/0234561 A1	9/2008	Roesicke et al.
2008/0033318 A1	2/2008	Mace et al.	2008/0234992 A1	9/2008	Ray et al.
2008/0039702 A1	2/2008	Hayter et al.	2008/0235469 A1	9/2008	Drew
2008/0045824 A1	2/2008	Tapsak et al.	2008/0242961 A1	10/2008	Brister et al.
2008/0055070 A1	3/2008	Bange et al.	2008/0242962 A1	10/2008	Roesicke et al.
2008/0058625 A1	3/2008	McGarraugh et al.	2008/0252459 A1	10/2008	Butler et al.
2008/0059227 A1	3/2008	Clapp	2008/0255434 A1	10/2008	Hayter et al.
2008/0060955 A1	3/2008	Goodnow	2008/0255437 A1	10/2008	Hayter
2008/0062055 A1	3/2008	Cunningham et al.	2008/0255438 A1	10/2008	Saidara et al.
2008/0064937 A1	3/2008	McGarraugh et al.	2008/0255808 A1	10/2008	Hayter
2008/0064941 A1	3/2008	Funderbunk et al.	2008/0256048 A1	10/2008	Hayter
2008/0064943 A1	3/2008	Talbot et al.	2008/0262469 A1	10/2008	Brister et al.
2008/0065646 A1	3/2008	Zhang et al.	2008/0267823 A1	10/2008	Wang et al.
2008/0066305 A1	3/2008	Wang et al.	2008/0269673 A1	10/2008	Butoi et al.
2008/0067627 A1	3/2008	Boeck et al.	2008/0275313 A1	11/2008	Brister et al.
2008/0071156 A1	3/2008	Brister et al.	2008/0275327 A1	11/2008	Faarbaek et al.
2008/0071157 A1	3/2008	McGarraugh et al.	2008/0278333 A1	11/2008	Fennell et al.
2008/0071158 A1	3/2008	McGarraugh et al.	2008/0283396 A1	11/2008	Wang et al.
2008/0071328 A1	3/2008	Haubrich et al.	2008/0287755 A1	11/2008	Sass et al.
2008/0071580 A1	3/2008	Marcus	2008/0287761 A1	11/2008	Hayter
			2008/0287762 A1	11/2008	Hayter
			2008/0287763 A1	11/2008	Hayter
			2008/0287764 A1	11/2008	Rasdal et al.
			2008/0287765 A1	11/2008	Rasdal et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0287766	A1	11/2008	Rasdal et al.	2009/0124979	A1	5/2009	Raymond et al.
2008/0288180	A1	11/2008	Hayter	2009/0131768	A1	5/2009	Simpson et al.
2008/0288204	A1	11/2008	Hayter et al.	2009/0131769	A1	5/2009	Leach et al.
2008/0294024	A1	11/2008	Cosentino et al.	2009/0131776	A1	5/2009	Simpson et al.
2008/0294096	A1	11/2008	Uber et al.	2009/0131777	A1	5/2009	Simpson et al.
2008/0296155	A1	12/2008	Shults et al.	2009/0131860	A1	5/2009	Nielsen
2008/0300476	A1	12/2008	Stafford	2009/0137886	A1	5/2009	Shariati et al.
2008/0306368	A1	12/2008	Goode, Jr. et al.	2009/0137887	A1	5/2009	Shariati et al.
2008/0306434	A1	12/2008	Dobbles et al.	2009/0143659	A1	6/2009	Li et al.
2008/0306435	A1	12/2008	Kamath et al.	2009/0143660	A1	6/2009	Brister et al.
2008/0306444	A1	12/2008	Brister et al.	2009/0149728	A1	6/2009	Van Antwerp et al.
2008/0312518	A1	12/2008	Jina et al.	2009/0150186	A1	6/2009	Cohen et al.
2008/0312841	A1	12/2008	Hayter	2009/0150454	A1	6/2009	Gejdos et al.
2008/0312842	A1	12/2008	Hayter	2009/0156919	A1	6/2009	Brister et al.
2008/0312844	A1	12/2008	Hayter et al.	2009/0156924	A1	6/2009	Shariati et al.
2008/0312845	A1	12/2008	Hayter et al.	2009/0163790	A1	6/2009	Brister et al.
2008/0319295	A1	12/2008	Bernstein et al.	2009/0163791	A1	6/2009	Brister et al.
2008/0319296	A1	12/2008	Bernstein et al.	2009/0164190	A1	6/2009	Hayter
2008/0319414	A1	12/2008	Yodfat et al.	2009/0164239	A1	6/2009	Hayter et al.
2009/0005659	A1	1/2009	Kollias et al.	2009/0164251	A1	6/2009	Hayter
2009/0005665	A1	1/2009	Hayter et al.	2009/0171182	A1	7/2009	Stafford
2009/0005666	A1	1/2009	Shin et al.	2009/0178459	A1	7/2009	Li et al.
2009/0006034	A1	1/2009	Hayter et al.	2009/0182217	A1	7/2009	Li et al.
2009/0006133	A1	1/2009	Weinert et al.	2009/0189738	A1	7/2009	Hermle
2009/0012377	A1	1/2009	Jennewine et al.	2009/0192366	A1	7/2009	Mensinger et al.
2009/0012379	A1	1/2009	Goode, Jr. et al.	2009/0192380	A1	7/2009	Shariah et al.
2009/0018424	A1	1/2009	Kamath et al.	2009/0192722	A1	7/2009	Shariah et al.
2009/0018425	A1	1/2009	Ouyang et al.	2009/0192724	A1	7/2009	Brauker et al.
2009/0020502	A1	1/2009	Bhullar et al.	2009/0192745	A1	7/2009	Kamath et al.
2009/0030294	A1	1/2009	Petisce et al.	2009/0192751	A1	7/2009	Kamath et al.
2009/0033482	A1	2/2009	Hayter et al.	2009/0198118	A1	8/2009	Hayter et al.
2009/0036747	A1	2/2009	Hayter et al.	2009/0198215	A1	8/2009	Chong et al.
2009/0036758	A1	2/2009	Brauker et al.	2009/0203981	A1	8/2009	Brauker et al.
2009/0036760	A1	2/2009	Hayter	2009/0204340	A1	8/2009	Feldman et al.
2009/0036763	A1	2/2009	Brauker et al.	2009/0204341	A1	8/2009	Brauker et al.
2009/0036915	A1	2/2009	Karbowniczek et al.	2009/0210249	A1	8/2009	Rasch-Menges et al.
2009/0043181	A1	2/2009	Brauker et al.	2009/0212766	A1	8/2009	Olson et al.
2009/0043182	A1	2/2009	Brauker et al.	2009/0216100	A1	8/2009	Ebner et al.
2009/0043525	A1	2/2009	Brauker et al.	2009/0216103	A1	8/2009	Brister et al.
2009/0043541	A1	2/2009	Brauker et al.	2009/0234200	A1	9/2009	Husheer
2009/0043542	A1	2/2009	Brauker et al.	2009/0240120	A1	9/2009	Mensinger et al.
2009/0045055	A1	2/2009	Rhodes et al.	2009/0240128	A1	9/2009	Mensinger et al.
2009/0048503	A1	2/2009	Dalal et al.	2009/0240193	A1	9/2009	Mensinger et al.
2009/0054737	A1	2/2009	Magar et al.	2009/0242399	A1	10/2009	Kamath et al.
2009/0054748	A1	2/2009	Feldman et al.	2009/0242425	A1	10/2009	Kamath et al.
2009/0054866	A1	2/2009	Teisen-Simony et al.	2009/0247855	A1	10/2009	Boock et al.
2009/0055149	A1	2/2009	Hayter et al.	2009/0247856	A1	10/2009	Boock et al.
2009/0058635	A1	3/2009	LaLonde et al.	2009/0247931	A1	10/2009	Damgaard-Sorensen
2009/0062633	A1	3/2009	Brauker et al.	2009/0253973	A1	10/2009	Bashan et al.
2009/0062635	A1	3/2009	Brauker et al.	2009/0259118	A1	10/2009	Feldman et al.
2009/0062767	A1	3/2009	VanAntwerp et al.	2009/0267765	A1	10/2009	Greene et al.
2009/0063187	A1	3/2009	Johnson et al.	2009/0270765	A1	10/2009	Ghesquire et al.
2009/0063402	A1	3/2009	Hayter	2009/0287073	A1	11/2009	Boock et al.
2009/0069658	A1	3/2009	Say et al.	2009/0287074	A1	11/2009	Shults et al.
2009/0069750	A1	3/2009	Schraga	2009/0289796	A1	11/2009	Blumberg
2009/0076356	A1	3/2009	Simpson et al.	2009/0292184	A1	11/2009	Funderburk et al.
2009/0076359	A1	3/2009	Peyser	2009/0292185	A1	11/2009	Funderburk et al.
2009/0076360	A1	3/2009	Brister et al.	2009/0294277	A1	12/2009	Thomas et al.
2009/0076361	A1	3/2009	Kamath et al.	2009/0298182	A1	12/2009	Schulat et al.
2009/0082693	A1	3/2009	Stafford	2009/0299152	A1	12/2009	Taub et al.
2009/0085768	A1	4/2009	Patel et al.	2009/0299155	A1	12/2009	Yang et al.
2009/0085873	A1	4/2009	Betts et al.	2009/0299156	A1	12/2009	Simpson et al.
2009/0088614	A1	4/2009	Taub	2009/0299162	A1	12/2009	Brauker et al.
2009/0088787	A1	4/2009	Koike et al.	2009/0299167	A1	12/2009	Seymour
2009/0099436	A1	4/2009	Brister et al.	2009/0299276	A1	12/2009	Brauker et al.
2009/0102678	A1	4/2009	Mazza et al.	2010/0004597	A1	1/2010	Gryn et al.
2009/0105554	A1	4/2009	Stahmann et al.	2010/0010324	A1	1/2010	Brauker et al.
2009/0105560	A1	4/2009	Solomon	2010/0010329	A1	1/2010	Taub et al.
2009/0105569	A1	4/2009	Stafford	2010/0010331	A1	1/2010	Brauker et al.
2009/0105636	A1	4/2009	Hayter et al.	2010/0010332	A1	1/2010	Brauker et al.
2009/0112478	A1	4/2009	Mueller, Jr. et al.	2010/0016687	A1	1/2010	Brauker et al.
2009/0124877	A1	5/2009	Shariati et al.	2010/0016698	A1	1/2010	Rasdal et al.
2009/0124878	A1	5/2009	Goode et al.	2010/0022855	A1	1/2010	Brauker et al.
2009/0124879	A1	5/2009	Brister et al.	2010/0025238	A1	2/2010	Gottlieb et al.
2009/0124964	A1	5/2009	Leach et al.	2010/0030038	A1	2/2010	Brauker et al.
				2010/0030053	A1	2/2010	Goode, Jr. et al.
				2010/0030484	A1	2/2010	Brauker et al.
				2010/0030485	A1	2/2010	Brauker et al.
				2010/0036215	A1	2/2010	Goode, Jr. et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0036216	A1	2/2010	Goode, Jr. et al.	2010/0228497	A1	9/2010	Kamath et al.
2010/0036222	A1	2/2010	Goode, Jr. et al.	2010/0230285	A1	9/2010	Hoss et al.
2010/0036223	A1	2/2010	Goode, Jr. et al.	2010/0235439	A1	9/2010	Goodnow et al.
2010/0036225	A1	2/2010	Goode, Jr. et al.	2010/0240975	A1	9/2010	Goode, Jr. et al.
2010/0041971	A1	2/2010	Goode, Jr. et al.	2010/0240976	A1	9/2010	Goode, Jr. et al.
2010/0045465	A1	2/2010	Brauker et al.	2010/0259543	A1	10/2010	Tarassenko et al.
2010/0049014	A1	2/2010	Funderburk et al.	2010/0261987	A1	10/2010	Kamath et al.
2010/0049024	A1	2/2010	Saint et al.	2010/0262201	A1	10/2010	He et al.
2010/0057040	A1	3/2010	Hayter	2010/0267161	A1	10/2010	Wu et al.
2010/0057041	A1	3/2010	Hayter	2010/0274107	A1	10/2010	Boock et al.
2010/0057042	A1	3/2010	Hayter	2010/0280341	A1	11/2010	Boock et al.
2010/0057044	A1	3/2010	Hayter	2010/0286496	A1	11/2010	Simpson et al.
2010/0057057	A1	3/2010	Hayter et al.	2010/0298684	A1	11/2010	Leach et al.
2010/0063373	A1	3/2010	Kamath et al.	2010/0312176	A1	12/2010	Lauer et al.
2010/0069728	A1	3/2010	Funderburk et al.	2010/0313105	A1	12/2010	Nekoomaram et al.
2010/0076283	A1	3/2010	Simpson et al.	2010/0317952	A1	12/2010	Budiman et al.
2010/0081905	A1	4/2010	Bommakanti et al.	2010/0324392	A1	12/2010	Yee et al.
2010/0081906	A1	4/2010	Hayter et al.	2010/0324403	A1	12/2010	Brister et al.
2010/0081908	A1	4/2010	Dobbles et al.	2010/0325868	A1	12/2010	Wang et al.
2010/0081910	A1	4/2010	Brister et al.	2010/0326842	A1	12/2010	Mazza et al.
2010/0087724	A1	4/2010	Brauker et al.	2010/0331642	A1	12/2010	Bruce et al.
2010/0096259	A1	4/2010	Zhang et al.	2010/0331644	A1	12/2010	Neale et al.
2010/0099970	A1	4/2010	Shults et al.	2010/0331648	A1	12/2010	Kamath et al.
2010/0099971	A1	4/2010	Shults et al.	2010/0331651	A1	12/2010	Groll
2010/0100113	A1	4/2010	Iio et al.	2010/0331653	A1	12/2010	Stafford
2010/0113897	A1	5/2010	Brenneman et al.	2010/0331656	A1	12/2010	Mensing et al.
2010/0119693	A1	5/2010	Tapsak et al.	2010/0331657	A1	12/2010	Mensing et al.
2010/0119881	A1	5/2010	Patel et al.	2011/0004085	A1	1/2011	Mensing et al.
2010/0121169	A1	5/2010	Petisce et al.	2011/0004276	A1	1/2011	Blair et al.
2010/0152548	A1	6/2010	Koski	2011/0009727	A1	1/2011	Mensing et al.
2010/0152554	A1	6/2010	Steine et al.	2011/0015509	A1	1/2011	Peyser
2010/0160757	A1	6/2010	Weinert et al.	2011/0021889	A1	1/2011	Hoss et al.
2010/0160759	A1	6/2010	Celentano et al.	2011/0022411	A1	1/2011	Hjelm et al.
2010/0168538	A1	7/2010	Keenan et al.	2011/0024043	A1	2/2011	Boock et al.
2010/0168660	A1	7/2010	Galley et al.	2011/0024307	A1	2/2011	Simpson et al.
2010/0174157	A1	7/2010	Brister et al.	2011/0027127	A1	2/2011	Simpson et al.
2010/0174158	A1	7/2010	Kamath et al.	2011/0027453	A1	2/2011	Boock et al.
2010/0174163	A1	7/2010	Brister et al.	2011/0027458	A1	2/2011	Boock et al.
2010/0174164	A1	7/2010	Brister et al.	2011/0028815	A1	2/2011	Simpson et al.
2010/0174165	A1	7/2010	Brister et al.	2011/0028816	A1	2/2011	Simpson et al.
2010/0174166	A1	7/2010	Brister et al.	2011/0040256	A1	2/2011	Bobroff et al.
2010/0174167	A1	7/2010	Kamath et al.	2011/0040263	A1	2/2011	Hordum et al.
2010/0174168	A1	7/2010	Goode et al.	2011/0046467	A1	2/2011	Simpson et al.
2010/0179401	A1	7/2010	Rasdal et al.	2011/0054275	A1	3/2011	Stafford
2010/0179402	A1	7/2010	Goode, Jr. et al.	2011/0060196	A1	3/2011	Stafford
2010/0179404	A1	7/2010	Kamath et al.	2011/0073475	A1	3/2011	Kastanos et al.
2010/0179408	A1	7/2010	Kamath et al.	2011/0077469	A1	3/2011	Blocker et al.
2010/0179409	A1	7/2010	Kamath et al.	2011/0077490	A1	3/2011	Simpson et al.
2010/0185065	A1	7/2010	Goode, Jr. et al.	2011/0082484	A1	4/2011	Saravia et al.
2010/0185069	A1	7/2010	Brister et al.	2011/0097090	A1	4/2011	Cao
2010/0185070	A1	7/2010	Brister et al.	2011/0106126	A1	5/2011	Love et al.
2010/0185071	A1	7/2010	Simpson et al.	2011/0118579	A1	5/2011	Goode et al.
2010/0185072	A1	7/2010	Goode, Jr. et al.	2011/0118580	A1	5/2011	Goode et al.
2010/0185075	A1	7/2010	Brister et al.	2011/0123971	A1	5/2011	Berkowitz et al.
2010/0190435	A1	7/2010	Cook et al.	2011/0124992	A1	5/2011	Brauker et al.
2010/0191082	A1	7/2010	Brister et al.	2011/0124997	A1	5/2011	Goode et al.
2010/0191087	A1	7/2010	Talbot et al.	2011/0125040	A1	5/2011	Crawford et al.
2010/0198033	A1	8/2010	Krulevitch et al.	2011/0125410	A1	5/2011	Goode et al.
2010/0198034	A1	8/2010	Thomas et al.	2011/0130970	A1	6/2011	Goode et al.
2010/0198035	A1	8/2010	Kamath et al.	2011/0130971	A1	6/2011	Goode et al.
2010/0198036	A1	8/2010	Kamath et al.	2011/0130998	A1	6/2011	Goode et al.
2010/0198142	A1	8/2010	Sloan et al.	2011/0137257	A1	6/2011	Gym et al.
2010/0204557	A1	8/2010	Kiaie et al.	2011/0137571	A1	6/2011	Power et al.
2010/0204653	A1	8/2010	Gryn et al.	2011/0144465	A1	6/2011	Shults et al.
2010/0212583	A1	8/2010	Brister et al.	2011/0148905	A1	6/2011	Simmons et al.
2010/0213057	A1	8/2010	Feldman et al.	2011/0152637	A1	6/2011	Kateraas et al.
2010/0213080	A1	8/2010	Celentano et al.	2011/0178378	A1	7/2011	Brister et al.
2010/0214104	A1	8/2010	Goode, Jr. et al.	2011/0178461	A1	7/2011	Chong et al.
2010/0217105	A1	8/2010	Yodfat et al.	2011/0184258	A1	7/2011	Stafford
2010/0217557	A1	8/2010	Kamath et al.	2011/0184482	A1	7/2011	Eberman et al.
2010/0223013	A1	9/2010	Kamath et al.	2011/0184752	A1	7/2011	Ray et al.
2010/0223022	A1	9/2010	Kamath et al.	2011/0190603	A1	8/2011	Stafford
2010/0223023	A1	9/2010	Kamath et al.	2011/0190614	A1	8/2011	Brister et al.
2010/0228109	A1	9/2010	Kamath et al.	2011/0191044	A1	8/2011	Stafford
2010/0228111	A1	9/2010	Friman et al.	2011/0193704	A1	8/2011	Harper et al.
				2011/0201910	A1	8/2011	Rasdal et al.
				2011/0201911	A1	8/2011	Johnson et al.
				2011/0208027	A1	8/2011	Wagner et al.
				2011/0213225	A1	9/2011	Bernstein et al.

(56)	References Cited			EP	1704893	9/2006
	U.S. PATENT DOCUMENTS			EP	0987982	1/2007
				EP	1956371	8/2008
				EP	2031534	3/2009
				EP	2060284	5/2009
2011/0218414	A1	9/2011	Kamath et al.	EP	1897487	11/2009
2011/0230741	A1	9/2011	Liang et al.	EP	1897492	11/2009
2011/0231107	A1	9/2011	Brauker et al.	EP	2113864	11/2009
2011/0231140	A1	9/2011	Goode, Jr. et al.	EP	1897488	12/2009
2011/0231141	A1	9/2011	Goode, Jr. et al.	EP	1681992	4/2010
2011/0231142	A1	9/2011	Goode, Jr. et al.	EP	2201969	6/2010
2011/0253533	A1	10/2011	Shults et al.	EP	1448489	8/2010
2011/0257495	A1	10/2011	Hoss et al.	EP	1971396	8/2010
2011/0257895	A1	10/2011	Brauker et al.	EP	1725163	12/2010
2011/0263958	A1	10/2011	Brauker et al.	EP	2260757	12/2010
2011/0263959	A1	10/2011	Young et al.	EP	1413245	6/2011
2011/0264378	A1	10/2011	Breton et al.	EP	2327362	6/2011
2011/0270062	A1	11/2011	Goode, Jr. et al.	EP	2327984	6/2011
2011/0270158	A1	11/2011	Brauker et al.	EP	2335587	6/2011
2011/0275919	A1	11/2011	Petisce et al.	EP	2153382	2/2012
2011/0287528	A1	11/2011	Fern et al.	EP	2284773	2/2012
2011/0288574	A1	11/2011	Curry et al.	GB	2 067 764 B	1/1984
2011/0290645	A1	12/2011	Brister et al.	GB	2409951	7/2005
2011/0313543	A1	12/2011	Brauker et al.	JP	03-500940	2/1991
2011/0319729	A1	12/2011	Donnay et al.	JP	07-182462	7/1995
2011/0319733	A1	12/2011	Stafford	JP	07-311196	11/1995
2011/0319738	A1	12/2011	Woodruff et al.	JP	10-305016	11/1998
2011/0319739	A1	12/2011	Kamath et al.	JP	11-506629	6/1999
2011/0320130	A1	12/2011	Valdes et al.	JP	11-225359	8/1999
2012/0010642	A1	1/2012	Lee et al.	JP	2003-144417	5/2003
2012/0035445	A1	2/2012	Boock et al.	JP	2004-214014 A	7/2004
2012/0040101	A1	2/2012	Tapsak et al.	JP	2004-520103	7/2004
2012/0046534	A1	2/2012	Simpson et al.	JP	2004-520898	7/2004
2012/0078071	A1	3/2012	Bohm et al.	JP	2006-021031	1/2006
2012/0108934	A1	5/2012	Valdes et al.	JP	2006-280464	10/2006
2012/0108983	A1	5/2012	Banet et al.	JP	2007-152037	6/2007
2012/0143135	A1	6/2012	Cole et al.	WO	WO-1991/015993	10/1991
2013/0111248	A1	5/2013	Ghesquiere et al.	WO	WO-1992/013271	8/1992
2013/0150691	A1	6/2013	Pace et al.	WO	WO-1994/020602	9/1994
2015/0326072	A1	11/2015	Petras et al.	WO	WO-95/28878	2/1995
				WO	WO-1996/039977	5/1996
				WO	WO-1996/025089	8/1996
				WO	WO-96/35370	11/1996
CA	2468577	6/2003		WO	WO-97/33513	9/1997
CA	2495648	2/2004		WO	WO-98/04902	2/1998
CA	2143172	7/2005		WO	WO-1998/035053	8/1998
CA	2498682	9/2005		WO	WO-1998/056293	12/1998
CA	2555749	9/2005		WO	WO-99/27849	6/1999
CA	2632709	6/2007		WO	WO-99/28736	6/1999
CA	2396613	3/2008		WO	WO-1999/033504	7/1999
CA	2678336	5/2008		WO	WO-1999/056613	11/1999
CA	2615575	6/2008		WO	WO-2000/049940	8/2000
CA	2626349	9/2008		WO	WO-00-60350	10/2000
CA	2701374	4/2009		WO	WO-2000/059370	10/2000
CA	2413148	8/2010		WO	WO-00/74753	12/2000
CA	2728831	7/2011		WO	WO-2000/078992	12/2000
CA	2617965	10/2011		WO	WO-2001/052935	7/2001
CN	101163440	4/2008		WO	WO 01/58348 A2	8/2001
CN	101268932	9/2008		WO	WO-2001/054753	8/2001
CN	101296650	10/2008		WO	WO 02/15778 A1	2/2002
DE	4401400	7/1995		WO	WO-2002/016905	2/2002
EP	0098592	1/1984		WO	WO-2002/050534	6/2002
EP	0127958	12/1984		WO	WO-2002/058537	8/2002
EP	0320109	6/1989		WO	WO 03/026728 A2	4/2003
EP	0353328	2/1990		WO	WO-2003/028784	4/2003
EP	0390390	10/1990		WO	WO 03/056319 A2	7/2003
EP	0396788	11/1990		WO	WO-03/057027	7/2003
EP	0286118	1/1995		WO	WO-2003/076893	9/2003
EP	0680727	11/1995		WO	WO-03/085372	10/2003
EP	0724859	8/1996		WO	WO-2003/082091	10/2003
EP	0805574	11/1997		WO	WO-2004/015539	2/2004
EP	0973289	1/2000		WO	WO-2004/028337	4/2004
EP	0678308	5/2000		WO	WO-2004/047445	6/2004
EP	1048264	11/2000		WO	WO 2004/049237 A2	6/2004
EP	1177802	2/2002		WO	WO-2004/060436	7/2004
EP	1292218	3/2003		WO	WO-2004/061420	7/2004
EP	1077634	7/2003		WO	WO-2004/090503	10/2004
EP	1568309	8/2005		WO	WO-2004/098405	11/2004
EP	1666091	6/2006		WO	WO 2004/098683 A1	11/2004
EP	1703697	9/2006				

(56) **References Cited**

FOREIGN PATENT DOCUMENTS

WO	WO-2004/098684	11/2004
WO	WO-2004/112602	12/2004
WO	WO 2005/018450 A2	3/2005
WO	WO-2005/041766	5/2005
WO	WO-2005/045744	5/2005
WO	WO 2005/046780 A1	5/2005
WO	WO-2005/051170	6/2005
WO	WO-2005/057175	6/2005
WO	WO-2005/065538	7/2005
WO	WO-2005/084534	9/2005
WO	WO-2005/089103	9/2005
WO	WO 2005/123186 A1	12/2005
WO	WO-2006/017358	2/2006
WO	WO-2006/020212	2/2006
WO	WO-2006/024671	3/2006
WO	WO-2006/026741	3/2006
WO	WO-2006/032653	3/2006
WO	WO 2006/040083 A1	4/2006
WO	WO-2006/042811	4/2006
WO	WO-2006/064397	6/2006
WO	WO-2006/072035	7/2006
WO	WO-2006/079114	7/2006
WO	WO 2006/086423 A2	8/2006
WO	WO 2006/094513 A2	9/2006
WO	WO-2006/108809	10/2006
WO	WO 2006/114297 A1	11/2006
WO	WO-2006/118947	11/2006
WO	WO 2006/121921 A2	11/2006
WO	WO-2006/124099	11/2006
WO	WO-2007/007459	1/2007
WO	WO-2007/016399	2/2007
WO	WO-2007/019289	2/2007
WO	WO-2007/027788	3/2007
WO	WO-2007/041069	4/2007
WO	WO-2007/041070	4/2007
WO	WO-2007/041248	4/2007
WO	WO-2007/056638	5/2007
WO	WO-2007/065285	6/2007
WO	WO-2007/089738	8/2007
WO	WO-2007/092618	8/2007
WO	WO 2007/097754 A1	8/2007
WO	WO-2007/101223	9/2007
WO	WO-2007/120363	10/2007
WO	WO-2007/126444	11/2007
WO	WO-2007/053832	12/2007
WO	WO-2007/143225	12/2007
WO	WO-2007/149319	12/2007
WO	WO-2007/1140783	12/2007
WO	WO-2008/001366	1/2008
WO	WO 2008/014792 A1	2/2008
WO	WO-2008/021913	2/2008
WO	WO-2008/042760	4/2008
WO	WO-2008/048452	4/2008
WO	WO-2008/052374	5/2008
WO	WO-2008/062099	5/2008
WO	WO 2008/065646	6/2008
WO	WO-2008/086541	7/2008
WO	WO 2008/115409 A1	9/2008
WO	WO-2008/128210	10/2008
WO	WO 2008/129532 A2	10/2008
WO	WO-2008/130896	10/2008
WO	WO-2008/130897	10/2008
WO	WO-2008/130898	10/2008
WO	WO 2008/133702	11/2008
WO	WO 2008/138006 A2	11/2008
WO	WO-2008/143943	11/2008
WO	WO-2008/144445	11/2008
WO	WO-2008/153693	12/2008
WO	WO 2008/155377	12/2008
WO	WO 2008/157821 A1	12/2008
WO	WO-2009/018058	2/2009
WO	WO-2009/035773	3/2009
WO	WO-2009/062675	5/2009
WO	WO-2009/086216	7/2009
WO	WO-2009/096992	8/2009

WO	WO-2009/097594	8/2009
WO	WO-2010/062898	6/2010
WO	WO-2010/077329	7/2010
WO	WO 2010/112521	10/2010
WO	WO-2011/000528	1/2011
WO	WO-2011/002815	1/2011
WO	WO-2011/022418	2/2011
WO	WO-2011/104616	9/2011
WO	WO-2005/121785	12/2015

OTHER PUBLICATIONS

- Blank, T. B., et al., "Clinical Results From a Non-Invasive Blood Glucose Monitor", Optical Diagnostics and Sensing of Biological Fluids and Glucose and Cholesterol Monitoring II, Proceedings of SPIE, vol. 4624, 2002, pp. 1-10.
- Brooks, S. L., et al., "Development of an On-Line Glucose Sensor for Fermentation Monitoring", Biosensors, vol. 3, 1987/88, pp. 45-56.
- Diem, P., et al., "Clinical Performance of a Continuous Viscometric Affinity Sensor for Glucose", Diabetes Technology & Therapeutics, vol. 6, 2004, pp. 790-799.
- El-Khatib, F. H., et al., "Adaptive Closed-Loop Control Provides Blood-Glucose Regulation Using Subcutaneous Insulin and Glucagon Infusion in Diabetic Swine", Journal of Diabetes Science and Technology, vol. 1, No. 2, 2007, pp. 181-192.
- Garg, S., et al., "Improvement in Glycemic Excursions with a Transcutaneous, Real-Time Continuous Glucose Sensor", Diabetes Care, vol. 29, No. 1, 2006, pp. 44-50.
- Kaplan, S. M., "Wiley Electrical and Electronics Engineering Dictionary", IEEE Press, 2004, pp. 141, 142, 548, 549.
- Kondepati, V., et al., "Recent Progress in Analytical Instrumentation for Glycemic Control in Diabetic and Critically Ill Patients", Analytical Bioanalytical Chemistry, vol. 388, 2007, pp. 545-563.
- Lo, B., et al., "Key Technical Challenges and Current Implementations of Body Sensor Networks", Body Sensor Networks, 2005, pp. 1-5.
- Lodwig, V., et al., "Continuous Glucose Monitoring with Glucose Sensors: Calibration and Assessment Criteria", Diabetes Technology & Therapeutics, vol. 5, No. 4, 2003, pp. 573-587.
- Lortz, J., et al., "What is Bluetooth? We Explain The Newest Short-Range Connectivity Technology", Smart Computing Learning Series, Wireless Computing, vol. 8, Issue 5, 2002, pp. 72-74.
- Malin, S. F., et al., "Noninvasive Prediction of Glucose by Near-Infrared Diffuse Reflectance Spectroscopy", Clinical Chemistry, vol. 45, No. 9, 1999, pp. 1651-1658.
- McGarraugh, G., et al., "Glucose Measurements Using Blood Extracted from the Forearm and the Finger", TheraSense, Inc., 2001, 16 Pages.
- McGarraugh, G., et al., "Physiological Influences on Off-Finger Glucose Testing", Diabetes Technology & Therapeutics, vol. 3, No. 3, 2001, pp. 367-376.
- McKean, B. D., et al., "A Telemetry-Instrumentation System for Chronically Implanted Glucose and Oxygen Sensors", IEEE Transactions on Biomedical Engineering, vol. 35, No. 7, 1988, pp. 526-532.
- Rodriguez, N., et al., "Flexible Communication and Control Protocol for Injectable Neuromuscular Interfaces", IEEE Transactions on Biomedical Circuits and Systems, IEEE, vol. 1, No. 1, 2007, pp. 19-27.
- Roe, J. N., et al., "Bloodless Glucose Measurements", Critical Review in Therapeutic Drug Carrier Systems, vol. 15, Issue 3, 1998, pp. 199-241.
- Salditt, P., "Trends in Medical Device Design and Manufacturing", SMTA News and Journal of Surface Mount Technology, vol. 17, 2004, pp. 19-24.
- Sternberg, R., et al., "Study and Development of Multilayer Needle-Type Enzyme-Based Glucose Microsensors", Biosensors, vol. 4, 1988, pp. 27-40.
- Tung, S., "Layers of Security for Active RFID Tags", RFID Handbook: Applications, Technology, Security, and Privacy, Edited by Ehson, et al., Chapter 33, 2008, pp. 1-28.

(56)

References Cited**OTHER PUBLICATIONS**

- Australian Patent Application No. 2008265541, Examiner's Report dated Nov. 29, 2013.
- Australian Patent Application No. 2008265541, Examiner's Report dated Oct. 15, 2012.
- Australian Patent Application No. 2016201703, Examiner's Report dated Mar. 22, 2017.
- Australian Patent Application No. 2017254903, Examiner's Report dated Dec. 11, 2018.
- Australian Patent Application No. 2018200899, Examiner's Report dated Dec. 6, 2018.
- Canadian Patent Application No. 2,765,712, Examiner's Report dated Apr. 10, 2017.
- Canadian Patent Application No. 2,765,712, Examiner's Report dated Mar. 27, 2018.
- Chinese Patent Application No. 201080006480.2, Original Language & English Translation of Office Action dated Dec. 11, 2013.
- Chinese Patent Application No. 201080006480.2, Original Language & English Translation of Office Action dated May 6, 2013.
- Chinese Patent Application No. 201080027344.1, Original Language & English Translation of Office Action dated Feb. 6, 2015.
- Chinese Patent Application No. 201080027344.1, Original Language & English Translation of Office Action dated Jun. 5, 2014.
- Chinese Patent Application No. 20160144860.1, Original Language & English Translation of Office Action dated Mar. 23, 2018.
- Chinese Patent Application No. 20160144860.1, Original Language & English Translation of Office Action dated Dec. 10, 2018.
- Chinese Patent Application No. 20160144860.1, Original Language & English Translation of Office Action dated May 23, 2019.
- European Patent Application No. 13000105.0, Examination Report dated Oct. 18, 2016.
- European Patent Application No. 13000105.0, Minutes of the Oral Proceedings mailed Oct. 18, 2016.
- European Patent Application No. 10739031.2, Extended European Search Report dated May 7, 2013.
- European Patent Application No. 10739031.2, Examination Report dated Oct. 28, 2016.
- European Patent Application No. 10739031.2, Opposition filed Dec. 20, 2018.
- European Patent Application No. 10812438.9, Extended European Search Report dated Dec. 10, 2013.
- European Patent Application No. 13000105.0, Opposition filed Jan. 4, 2019.
- European Patent Application No. 15184320.8, Examination Report dated Apr. 18, 2017.
- European Patent Application No. 17201183.5, Examination Report dated May 17, 2019.
- European Patent Application No. 18192278.2, Extended European Search Report dated Mar. 13, 2019.
- European Patent Application No. 18208224.8, Extended European Search Report dated Oct. 11, 2019.
- Japanese Patent Application No. 2012-526736, Original Language & English Translation of Office Action dated Apr. 15, 2014.
- Japanese Patent Application No. 2012-526736, Original Language & English Translation of Office Action dated Dec. 16, 2014.
- Japanese Patent Application No. 2015-159805, Original Language & English Translation of Office Action dated Aug. 9, 2016.
- PCT Application No. PCT/US2010/002401, International Preliminary Report on Patentability and Written Opinion of the International Searching Authority dated Mar. 15, 2012.
- PCT Application No. PCT/US2010/002401, International Search Report and Written Opinion of the International Searching Authority dated Nov. 12, 2010.
- PCT Application No. PCT/US2010/022928, International Preliminary Report on Patentability and Written Opinion of the International Searching Authority dated Aug. 18, 2011.
- PCT Application No. PCT/US2010/022928, International Search Report and Written Opinion of the International Searching Authority dated Mar. 21, 2010.
- U.S. Appl. No. 12/698,124, Office Action dated Aug. 12, 2012.
- U.S. Appl. No. 12/698,124, Office Action dated Dec. 4, 2013.
- U.S. Appl. No. 12/698,124, Office Action dated Jun. 6, 2013.
- U.S. Appl. No. 12/698,124, Office Action dated Mar. 20, 2015.
- U.S. Appl. No. 12/698,124, Office Action dated Nov. 21, 2012.
- U.S. Appl. No. 12/807,278, Advisory Action dated Jul. 28, 2014.
- U.S. Appl. No. 12/807,278, Advisory Action dated Jun. 13, 2013.
- U.S. Appl. No. 12/807,278, Advisory Action dated Oct. 8, 2014.
- U.S. Appl. No. 12/807,278, Office Action dated Aug. 21, 2012.
- U.S. Appl. No. 12/807,278, Office Action dated Feb. 1, 2013.
- U.S. Appl. No. 12/807,278, Office Action dated Mar. 29, 2013.
- U.S. Appl. No. 12/807,278, Office Action dated Mar. 5, 2015.
- U.S. Appl. No. 12/807,278, Office Action dated Jul. 5, 2016.
- U.S. Appl. No. 12/807,278, Office Action dated Apr. 3, 2017.
- U.S. Appl. No. 12/807,278, Office Action dated Feb. 1, 2018.
- U.S. Appl. No. 12/807,278, Notice of Allowance dated Jul. 5, 2018.
- U.S. Appl. No. 14/094,719, Office Action dated Dec. 26, 2018.
- U.S. Appl. No. 14/094,719, Office Action dated Jul. 10, 2019.
- U.S. Appl. No. 14/741,459, Office Action dated Jun. 5, 2017.
- U.S. Appl. No. 14/741,459, Office Action dated Dec. 14, 2017.
- U.S. Appl. No. 14/741,459, Advisory Action dated Apr. 13, 2018.
- U.S. Appl. No. 14/741,459, Office Action dated Aug. 2, 2019.
- U.S. Appl. No. 14/741,459, Office Action dated Sep. 18, 2020.
- U.S. Appl. No. 14/841,122, Office Action dated Aug. 25, 2016.
- U.S. Appl. No. 14/841,122, Office Action dated Mar. 7, 2017.
- U.S. Appl. No. 14/841,122, Office Action dated Feb. 8, 2018.
- U.S. Appl. No. 14/841,122, Office Action dated Jan. 7, 2020.
- U.S. Appl. No. 14/841,122, Office Action dated May 1, 2019.
- U.S. Appl. No. 14/841,224, Office Action dated Nov. 3, 2016.
- U.S. Appl. No. 14/841,224, Office Action dated Jan. 17, 2017.
- U.S. Appl. No. 14/841,224, Advisory Action dated Jun. 2, 2017.
- U.S. Appl. No. 14/841,224, Office Action dated Jul. 31, 2017.
- U.S. Appl. No. 14/841,224, Office Action dated Feb. 8, 2018.
- U.S. Appl. No. 14/841,224, Office Action dated Apr. 17, 2018.
- U.S. Appl. No. 14/841,224, Office Action dated Sep. 26, 2018.
- U.S. Appl. No. 14/841,224, Advisory Action dated Jan. 28, 2019.
- U.S. Appl. No. 14/841,224, Office Action dated Feb. 19, 2019.
- U.S. Appl. No. 14/841,224, Notice of Allowance dated Jul. 25, 2019.
- U.S. Appl. No. 14/841,429, Office Action dated Oct. 27, 2016.
- U.S. Appl. No. 14/841,429, Office Action dated Feb. 8, 2017.
- U.S. Appl. No. 14/841,429, Office Action dated Feb. 8, 2018.
- U.S. Appl. No. 14/841,429, Advisory Action dated May 2, 2018.
- U.S. Appl. No. 14/841,429, Office Action dated Sep. 21, 2018.
- U.S. Appl. No. 14/841,429, Office Action dated Jun. 12, 2019.
- U.S. Appl. No. 15/985,615, Office Action dated Jul. 27, 2018.
- U.S. Appl. No. 15/985,615, Office Action dated Mar. 7, 2019.
- Ambade, V. N., et al., "Methods for Estimation of Blood Glucose: A Comparative Evaluation", Medical Journal Armed Forces India, 1998, vol. 54, No. 2, pp. 131-133.
- ASTM International, Designation D2240-05, 2010, pp. 1-13.
- Biosensors: Fundamentals and Applications, Turner et al., Eds., 1987, pp. 1-786.
- Bluetooth Core Specification 4.0, Jun. 30, 2010, Master Table of Contents & Compliance Requirements, pp. 1-89.
- Clarke, W., et al., "Statistical Tools to Analyze Continuous Glucose Monitor Data", Diabetes Technology & Therapeutics, 2009, vol. 11, Suppl. 1, pp. S-45-S-54.
- In Vivo Glucose Sensing, Cunningham et al., Eds., 2010, Chemical Analysis, vol. 174, pp. 1-466.
- Decuir, J., "Bluetooth 4.0: Low Energy", IEEE SCV Consultants' Network of Silicon Valley, 2012, pp. 1-68.
- Dementyev, A., et al., "Power Consumption Analysis of Bluetooth Low Energy, ZigBee and ANT Sensor Nodes in a Cyclic Sleep Scenario", IEEE International Wireless Symposium (IWS), 2013, Beijing, China, pp. 1-4.
- DexCom™ STS™ Continuous Glucose Monitoring System User's Guide, 2006, pp. 1-57.
- Dexcom STS®-7 Continuous Glucose Monitoring System User's Guide, 2007, pp. 1-74.
- ECMA International Standard ECMA-340, Near Field Communication Interface and Protocol (NFCIP-1), 2nd Edition, 2004, pp. 1-65.

(56)

References Cited

OTHER PUBLICATIONS

- Facchinetti, A., et al., "A New Index to Optimally Design and Compare Continuous Glucose Monitoring Glucose Prediction Algorithms", *Diabetes Technology & Therapeutics*, 2011, vol. 13, No. 2, pp. 111-119.
- Fujipoly Silver ZEBRA® Connector Data Sheet FSDS 01-34, Version 5, 2006, pp. 1-7.
- Gilligan, B. J., et al., "Evaluation of a Subcutaneous Glucose Sensor out to 3 Months in a Dog Model", *Diabetes Care*, 1994, vol. 17, No. 8, pp. 882-887.
- Guerra, S., et al., "A Dynamic Risk Measure from Continuous Glucose Monitoring Data", *Diabetes Technology & Therapeutics*, 2011, vol. 13, No. 8, pp. 843-852.
- Heise, T., et al., "Hypoglycemia Warning Signal and Glucose Sensors: Requirements and Concepts", *Diabetes Technology & Therapeutics*, 2003, vol. 5, No. 4, pp. 563-571.
- Heller, A., "Implanted Electrochemical Glucose Sensors for the Management of Diabetes", *Annu. Rev. Biomed. Eng.*, 1999, vol. 1, pp. 153-175.
- "In Vitro Diagnostic Products for Human Use", Federal Register, 1974, vol. 39, No. 126, pp. 24136-24147.
- Klonoff, D. C., "A Review of Continuous Glucose Monitoring Technology", *Diabetes Technology & Therapeutics*, 2005, vol. 7, No. 5, pp. 770-775.
- León, L. P., et al., "Continuous-Flow Analysis for Glucose in Serum, with Use of Hexokinase and Glucose-6-Phosphate Dehydrogenase Co-Immobilized in Tubular Form", *Clinical Chemistry*, 1980, vol. 26, No. 1, pp. 123-129.
- Morak, J., et al., "Design and Evaluation of a Telemonitoring Concept Based on NFC-Enabled Mobile Phones and Sensor Devices", *IEEE Transactions on Information Technology in Biomedicine*, 2012, vol. 16, No. 1, pp. 17-23.
- Movassaghi, S., et al., "Wireless Technologies for Body Area Networks: Characteristics and Challenges", 2012 International Symposium on Communications and Information Technologies (ISCIT), 2012, Gold Coast, QLD, Australia, pp. 42-47.
- Passey, R. B., et al., "Evaluation and Comparison of 10 Glucose Methods and the Reference Method Recommendation in the Proposed Product Class Standard (1974)", *Clinical Chemistry*, 1977, vol. 23, No. 1, pp. 131-139.
- Sandham, W., et al., "Blood Glucose Prediction for Diabetes Therapy Using a Recurrent Artificial Neural Network", 9th European Signal Processing Conference, 1998, Rhodes, Greece, pp. 1-4.
- Sparacino, G., et al., "Glucose Concentration Can Be Predicted Ahead in Time from Continuous Glucose Monitoring Sensor Time-Series", *IEEE Transactions on Biomedical Engineering*, 2007, vol. 54, No. 5, pp. 931-937.
- Townsend, K., et al., "Getting Started with Bluetooth Low Energy—Chapter 1", 2014, pp. 1-26.
- U.S. Appl. No. 60/587,787, filed Jul. 13, 2004, pp. 1-69.
- U.S. Appl. No. 60/606,334, filed Aug. 31, 2004, pp. 1-38.
- Wang, X.H., et al., "Bluetooth: Opening a blue sky for healthcare", *Mobile Information Systems*, 2006, vol. 2, pp. 151-167.
- Z-Carbon Connector, retrieved from http://www.zaxisconnector.com/SS_zc.shtml, 2004, 2 pages.
- Z-Silver Connector, retrieved from http://www.zaxisconnector.com/SS_zs.shtml, 2004, 2 pages.
- Alcock & Turner, "Continuous analyte monitoring to aid clinical practice," *IEEE Engineering in Medicine & BioloXY Magazine*, 13:319-25 (1994).
- Armour et al., "Application of Chronic Intravascular Blood Glucose Sensor in Dogs," *Diabetes*, vol. 39, pp. 1519-1526, Dec. 1990.
- Bindra, D.S. et al., "Design and in Vitro Studies of a Needle-Type Glucose Sensor for Subcutaneous Monitoring," *Anal. Chem.*, 63(17):1692-1696 (Sep. 1, 1991).
- Bobbioni-Harsch, E. et al., "Lifespan of subcutaneous glucose sensors and their performances during dynamic glycaemia changes in rats," *J. Biomed. Eng.* 15:457-463 (1993).
- Cass, A.E.G. et al., "Ferrocene-Mediated Enzyme Electrode for Amperometric Determination of Glucose," *Anal. Chem.*, 56(4):667-671 (Apr. 1984).
- Gregg, B. A. et al., "Cross-Linked Redox Gels Containing Glucose Oxidase for Amperometric Biosensor Applications," *Analytical Chemistry*, 62(3):258-263 (Feb. 1, 1990).
- Harrison, D.J. et al., "Characterization of Perfluorosulfonic Acid Polymer Coated Enzyme Electrodes and a Miniaturized Integrated Potentiostat for Glucose Analysis in Whole Blood," *Anal. Chem.*, 60(19):2002-2007 (Oct. 1, 1988).
- Heller, A., "Electrical Connection of Enzyme Redox Centers to Electrodes," *J. Phys. Chem.*, 96(9):3579-3587 (1992).
- Heller, A., "Electrical Wiring of Redox Enzymes," *Acc. Chem. Res.*, 23(5):129-134 (1990).
- International Search Report and Written Opinion from PCT/US2010/022860 dated Mar. 23, 2010.
- International Search Report and Written Opinion from PCT/US2010/047381 dated Oct. 15, 2010.
- International Search Report and Written Opinion from PCT/US2010/050772 dated Dec. 3, 2010.
- International Search Report and Written Opinion from PCT/US2010/050888 dated Nov. 29, 2010.
- International Search Report and Written Opinion from PCT/US2010/051861 dated Nov. 30, 2010.
- Johnson, K., et al., "In vivo evaluation of an electroenzymatic glucose sensor implanted in subcutaneous tissue," *Biosensors and Bioelectronics*, 1992, vol. 7, pp. 709-714.
- Maidan, R. et al., "Elimination of Electrooxidizable Interferant-Produced Currents in Amperometric Biosensors," *Analytical Chemistry*, 64(23):2889-2896 (Dec. 1, 1992).
- Mastrototaro, J.J., et al., "An Electroenzymatic Glucose Sensor Fabricated on a Flexible Substrate," *Sensors and Biosensors B Chemical*, B5: 139-144 (1991).
- McKean, B., et al., "A Telemetry-Instrumentation System for Chronically Implanted Glucose and Oxygen Sensors," *IEEE Transactions on Biomedical Engineering*, vol. 35, No. 7, (Jul. 1988), pp. 526-532.
- Moatti-Sirat, D., et al., "Towards continuous glucose monitoring: in vivo evaluation of a miniaturized glucose sensor implanted for several days in rat subcutaneous tissue," *Diabetologia*, 35(3) (1 page—Abstract only) (Mar. 1992).
- Ohara, T. J., et al., "Glucose Electrodes Based on Cross-Linked [Os(bpy)₂Cl]^{+/2+} Complexed Poly(1-vinylimidazole) Films," *Analytical Chemistry*, 65(23):3512-3516 (Dec. 1, 1993).
- Opinion of the Court, Supreme Court of the United States, No. 04-1350, *KSR International co., Petitioner v. Teleflex Inc. et al.*, Apr. 30, 2007.
- Pickup, J. C., et al., "In vivo molecular sensing in diabetes mellitus: an implantable glucose sensor with direct electron transfer," *Diabetologia*, 32(3):213-217 (1989).
- Pishko, M. V., et al., "Amperometric Glucose Microelectrodes Prepared Through Immobilization of Glucose Oxidase in Redox Hydrogels," *Anal. Chem.*, 63(20):2268-2272 (Oct. 15, 1991).
- Poitout, V., et al., "In vitro and in vivo evaluation in dogs of a miniaturized glucose sensor," *ASAIO Transactions*, 37(3) (1 page—Abstract only) (Jul.-Sep. 1991).
- Reach, G., et al., "Can Continuous Glucose Monitoring Be Used for the Treatment of Diabetes?," *Analytical Chemistry*, 64(6):381-386 (Mar. 15, 1992).
- Rebrin, K., et al., "Automated Feedback Control of Subcutaneous Glucose Concentration in Diabetic Dogs," *Diabetologia*, 32(8):573-576 (Aug. 1989).
- Sakakida, M., et al., "Ferrocene-mediate needle-type glucose sensor covered with newly designed biocompatible membrane," *Sensors and Actuators B*, 13-14:319-322 (1993).
- Sakakida, M., et al., "Development of ferrocene-mediated needle-type glucose sensor as a measure of true subcutaneous tissue glucose concentrations," *Artif Organs Today*, 1992, vol. 2, No. 2, pp. 145-458.
- Shichiri, M., et al., "Glycaemic Control in Pancreatized Dogs with a Wearable Artificial Endocrine Pancreas," *Diabetologia*, 24(3):179-184 (Mar. 1983).

(56)

References Cited**OTHER PUBLICATIONS**

- Shichiri, M., et al., "Telemetry Glucose Monitoring Device with Needle-type Glucose Sensor: A Useful Tool for Blood Glucose Monitoring in Diabetic Individuals," *Diabetes Care*, vol. 9, No. 3 (May-Jun. 1986), pp. 298-301.
- Shichiri, M., et al., "In vivo characteristics of needle-type glucose sensor—Measurement of subcutaneous glucose concentrations in human volunteers," *Horm Metab Res Suppl.* 1988, vol. 20, pp. 17-20.
- Shichiri, M., et al., "Wearable artificial endocrine pancreas with needle-type glucose sensor," *The Lancet*, 1982, vol. 2, No. 8308, pp. 1129-1131.
- Shults, M., "A Telemetry-Instrumentation System for Monitoring Multiple Subcutaneously Implanted Glucose Sensors," *IEEE Transactions on Biomedical Engineering*, vol. 41, No. 10 (Oct. 1994), pp. 937-942.
- Sternberg, R., et al., "Study and Development of Multilayer Needle-type Enzyme-based Glucose Microsensors," *Biosensors*, 4:27-40 (1988).
- Turner, A.P.F., et al., "Diabetes Mellitus: Biosensors for Research and Management", *Biosensors*, 1:85-115 (1985).
- Updike, S. et al., "Principles of Long-term Fully Implanted Sensors with Emphasis on Radiotelemetric Monitoring of Blood Glucose from Inside a Subcutaneous Foreign Body Capsule (FBC)" in "Biosensors in the Body: Continuous in vivo Monitoring" (John Wiley & Sons, Ltd., 1997) Chapter 4, pp. 117-137.
- Updike, S. J., et al., "A Subcutaneous Glucose Sensor With Improved Longevity, Dynamic Range, and Stability of Calibration", *Diabetes Care*, 2000, vol. 23, pp. 208-214.
- Velho, G. et al., "Strategies for calibrating a subcutaneous glucose sensor," *Biomed. Biochim. Acta*, 48 (11112):957-964 (1989).
- Wilson, G. S. et al., "Progress toward the Development of an Implantable Sensor for Glucose," *Clinical Chemistry*, 38(9):1613-1617 (1992).
- Ye, L. et al., "High Current Density "Wired" Quinoprotein Glucose Dehydrogenase Electrode," *Anal. Chem.*, 65(3):238-241 (Feb. 1, 1993).
- Australian Examination Report from 2011269796 dated Apr. 3, 2014.
- Netherlands Search Report from 2009963 dated Aug. 12, 2013.
- European Extended Search Report from 11760268.0 dated Apr. 14, 2014.
- International Search Report and Written Opinion from PCT/US2012/068839 dated Feb. 22, 2013.
- International Search Report and Written Opinion from PCT/US2016/032485 dated Sep. 12, 2016.
- European Search Report from 19151577.4 dated Aug. 16, 2019.
- Aussedat, B., et al., "A User-Friendly Method for Calibrating a Subcutaneous Glucose Sensor-Based Hypoglycemic Alarm", *Biosensors & Bioelectronics*, vol. 12, No. 11, 1997, pp. 1061-1071.
- Bennion, N., et al., "Alternate Site Glucose Testing: A Crossover Design", *Diabetes Technology & Therapeutics*, vol. 4, No. 1, 2002, pp. 25-33.
- Claremont, D. J., et al., "Biosensors for Continuous In Vivo Glucose Monitoring", *Proceedings of the Annual International Conference of the IEEE Engineering in Medicine and Biology Society*, vol. 10, 1988.
- Clark Jr., L. C., et al., "Electrode Systems for Continuous Monitoring in Cardiovascular Surgery", *Annals New York Academy of Sciences*, 1962, pp. 29-45.
- Clark Jr., L. C., et al., "Long-term Stability of Electroenzymatic Glucose Sensors Implanted in Mice", *American Society of Artificial Internal Organs Transactions*, vol. XXXIV, 1988, pp. 259-265.
- Csoregi, E., et al., "Design and Optimization of a Selective Subcutaneously Implantable Glucose Electrode Based on 'Wired' Glucose Oxidase", *Analytical Chemistry*, vol. 67, No. 7, 1995, pp. 1240-1244.
- Csoregi, E., et al., "Design, Characterization, and One-Point in Vivo Calibration of a Subcutaneously Implanted Glucose Electrode", *Analytical Chemistry*, vol. 66 No. 19, 1994, pp. 3131-3138.
- Feldman, B., et al., "A Continuous Glucose Sensor Based on Wired Enzyme™ Technology—Results from a 3-Day Trial in Patients with Type 1 Diabetes", *Diabetes Technology & Therapeutics*, vol. 5, No. 5, 2003, pp. 769-779.
- Feldman, B., et al., "Correlation of Glucose Concentrations in Interstitial Fluid and Venous Blood During Periods of Rapid Glucose Change", *Abbott Diabetes Care, Inc. Freestyle Navigator Continuous Glucose Monitor Pamphlet*, 2004.
- Isermann, R., "Supervision, Fault-Detection and Fault-Diagnosis Methods—An Introduction", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 639-652.
- Gunasingham, et al., "Electrochemically Modulated Optrode for Glucose", *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 353-359.
- Ikeda, T., et al., "Artificial Pancreas—Investigation of the Stability of Glucose Sensors Using a Telemetry System" (English language translation of abstract), *Jpn. J. Artif. Organs*, vol. 19, No. 2, 1990, 889-892.
- Isermann, R., et al., "Trends in the Application of Model-Based Fault Detection and Diagnosis of Technical Processes", *Control Engineering Practice*, vol. 5, No. 5, 1997, pp. 709-719.
- Johnson, P. C., "Peripheral Circulation", *John Wiley & Sons*, 1978, pp. 198.
- Jungheim, K., et al., "How Rapid Does Glucose Concentration Change in Daily Life of Patients with Type 1 Diabetes?", 2002, pp. 250.
- Jungheim, K., et al., "Risky Delay of Hypoglycemia Detection by Glucose Monitoring at the Arm", *Diabetes Care*, vol. 24, No. 7, 2001, pp. 1303-1304.
- Koudelka, M., et al., "In-Vivo Behaviour of Hypodermically Implanted Microfabricated Glucose Sensors", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 31-36.
- Lager, W., et al., "Implantable Electrocatalytic Glucose Sensor", *Hormone Metabolic Research*, vol. 26, 1994, pp. 526-530.
- Minimed Technologies, "Tape Tips and Other Infusion Site Information", 1995.
- Moatti-Sirat, D., et al., "Evaluating In Vitro and In Vivo the Interference of Ascorbate and Acetaminophen on Glucose Detection by a Needle-Type Glucose Sensor", *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 345-352.
- Moatti-Sirat, D., et al., "Reduction of Acetaminophen Interference in Glucose Sensors by a Composite Nafion Membrane: Demonstration in Rats and Man", *Diabetologia*, vol. 37, 1994, pp. 610-616.
- Olivier, C. N., et al., "In Vivo Measurement of Carbon Dioxide Tension with a Miniature Electrodes", *Pflugers Archiv: European Journal of Physiology*, vol. 373, 1978, pp. 269-272.
- Pickup, J., "Developing Glucose Sensors for In Vivo Use", *Tibtech*, vol. 11, 1993, pp. 285-291.
- Pickup, J., et al., "Implantable Glucose Sensors: Choosing the Appropriate Sensing Strategy", *Biosensors*, vol. 3, 1987/88, pp. 335-346.
- Pickup, J., et al., "Potentially-Implantable, Amperometric Glucose Sensors with Mediated Electron Transfer: Improving the Operating Stability", *Biosensors*, vol. 4, 1989, pp. 109-119.
- Poitout, V., et al., "A Glucose Monitoring System for On Line Estimation in Man of Blood Glucose Concentration Using a Miniaturized Glucose Sensor Implanted in the Subcutaneous Tissue and a Wearable Control Unit", *Diabetologia*, vol. 36, 1993, pp. 658-663.
- Poitout, V., et al., "Calibration in Dogs of a Subcutaneous Miniaturized Glucose Sensor Using a Glucose Meter for Blood Glucose Determination", *Biosensors & Bioelectronics*, vol. 7, 1992, pp. 587-592.
- Quinn, C. P., et al., "Kinetics of Glucose Delivery to Subcutaneous Tissue in Rats Measured with 0.3-mm Amperometric Microsensors", *The American Physiological Society*, 1995, E155-E161.
- Salehi, C., et al., "A Telemetry-Instrumentation System for Long-Term Implantable Glucose and Oxygen Sensors", *Analytical Letters*, vol. 29, No. 13, 1996, pp. 2289-2308.
- Scheller, F., et al., "Enzyme Electrodes and Their Application", *Philosophical Transactions of The Royal Society of London B*, vol. 316, 1987, pp. 85-94.
- Schmidt, F. J., et al., "Calibration of a Wearable Glucose Sensor", *The International Journal of Artificial Organs*, vol. 15, No. 1, 1992, pp. 55-61.

(56)

References Cited**OTHER PUBLICATIONS**

- Schmidtke, D. W., et al., "Measurement and Modeling of the Transient Difference Between Blood and Subcutaneous Glucose Concentrations in the Rat After Injection of Insulin", *Proceedings of the National Academy of Sciences*, vol. 95, 1998, pp. 294-299.
- Shaw, G. W., et al., "In Vitro Testing of a Simply Constructed, Highly Stable Glucose Sensor Suitable for Implantation in Diabetic Patients", *Biosensors & Bioelectronics*, vol. 6, 1991, pp. 401-406.
- Shichiri, M., et al., "Membrane Design for Extending the Long-Life of an Implantable Glucose Sensor", *Diabetes Nutrition and Metabolism*, vol. 2, 1989, pp. 309-313.
- Shichiri, M., et al., "Needle-type Glucose Sensor for Wearable Artificial Endocrine Pancreas", *Implantable Sensors for Closed-Loop Prosthetic Systems*, Chapter 15, 1985, pp. 197-210.
- Thompson, M., et al., "In Vivo Probes: Problems and Perspectives", *Clinical Biochemistry*, vol. 19, 1986, pp. 255-261.
- Velho, G., et al., "In Vitro and In Vivo Stability of Electrode Potentials in Needle-Type Glucose Sensors", *Diabetes*, vol. 38, No. 2, 1989, pp. 164-171.
- Von Woedtke, T., et al., "In Situ Calibration of Implanted Electrochemical Glucose Sensors", *Biomedica Biochimica Acta*, vol. 48, 1989, pp. 943-952.
- Chinese Patent Application No. CN 2010800064817, Original Language and English Translation of Office Action dated Dec. 2, 2014.
- European Patent Application No. 10739015.5, Extended European Search Report dated May 10, 2013.
- Ahson, S., et al., "RFID Handbook: Applications, Technology, Security, and Privacy", 2008, Chapter 4, Far-Field Tag Antenna Design Methodology, and Chapter 13, RFID Tags for Metallic Object Identification, pp. 71 and 253-254.
- Application Note AN048, Antenna Part No. FR05-S1-N-0-102, Company Reach Xtend™, Bluetooth®, 802.11b/g WLAN Chip Antenna, 2008, pp. 1-13.
- Application Note AVR2023—AT86RF231 PCB reference design for antenna diversity, Atmel Corporation, 2008, pp. 1-15.
- Application Note nRF9E5 RF and antenna layout, Nordic Semiconductor, 2006, pp. 1-13.
- Benkič, K., et al., "Using RSSI value for distance estimation in Wireless sensor networks based on ZigBee", 15th International Conference on Systems, Signals and Image Processing, Bratislava, Slovakia, 2008, pp. 1-4.
- "Bluetooth Antenna Design", National Semiconductor Application Note, 2005, pp. 1-16.
- Callaway, Jr., E. H., "Wireless Sensor Networks: Architectures and Protocols", 2004, Chapter 8, Antennas and the Definition of RF Performance, pp. 201-202.
- Frenzel, L. E., "Printed-Circuit-Board Antennas, retrieved from <https://www.electronicdesign.com/technologies/boards/article/21751417/printedcircuitboard-antennasprint/3266>", *Electronic Design*, 2005, pp. 1-4.
- Gonzalez, O. L., et al., "Low-Cost Wireless Sensors—Designer Reference Manual", Freescale Semiconductor, 2007, pp. 1-146.
- Güler, N. F., et al., "Theory and Applications of Biotelemetry", *Journal of Medical Systems*, 2002, vol. 26, No. 2, pp. 159-178.
- Heftman, G., "Chip Antenna Reduces Cell-Phone Dimensions", *Microwaves & RF*, 1999, p. 182.
- Huang, Y., et al., "Antennas from Theory to Practice", 2008, Chapter 8, Antenna Diversity, pp. 322-325.
- James, Jr., et al., "Handbook of Microstrip Antennas", 1969, pp. 1038-1047.
- Loy, M., et al., "ISM—Band and Short Range Device Antennas", Texas Instruments Application Report, 2005, pp. 1-38.
- Microchip Technology Inc., MRF24J40MA Data Sheet, 2008, pp. 1-30.
- Moore, B., "The Potential Use of Radio Frequency Identification Devices for Active Monitoring of Blood Glucose Levels", *Journal of Diabetes Science and Technology*, 2009, vol. 3, No. 1, pp. 180-183.
- "Murata Puts Antenna on a Chip", *Passives*, 1999, vol. 44, 1 page.
- Schoepke, E., "Chip Antenna Layout Considerations for 802.11 Applications", Johanson Technology, 2006, retrieved from <https://www.johansontechnology.com/chip-antenna-layout-considerations-for-802-11-applications>, pp. 1-7.
- Sharawi, M. S., "Use of low-cost patch antennas in modern wireless technology", *IEEE Potentials*, 2006, pp. 35-38 and 47.
- Waterhouse, R., "Printed Antennas for Wireless Communications," 2007, pp. 116-129 and 284-289.
- Wong, KL, "Planar Antennas for Wireless Communications," 2003, Chapter 1, Introduction and Overview, pp. 4-17, 38-45, and 218-221.
- EP, 10739015.5 Extended Search Report, dated May 10, 2013.
- EP, 19151577.4 Extended Search Report, dated Aug. 16, 2019.
- EP, 17201183.5 Extended Search Report, dated May 7, 2018.
- EP, 20177703.4 Extended Search Report, dated Sep. 25, 2020.
- EP, 20177712.5 Extended Search Report, dated Sep. 30, 2020.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3






FIG. 4








FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 12




FIG. 11




FIG. 13




FIG. 16




FIG. 15




FIG. 14




FIG. 17




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG.23




FIG.24




FIG. 26




FIG. 25




FIG. 27




FIG.28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34A




FIG. 35A




FIG. 34B




FIG. 35B




FIG. 36A




FIG. 36B




FIG. 37




FIG. 38






FIG. 39






FIG. 42




FIG. 43

1

ANALYTE SENSOR AND APPARATUS FOR INSERTION OF THE SENSOR

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 17/009,647, filed Sep. 1, 2020, which is a continuation of U.S. patent application Ser. No. 16/736,728, filed Jan. 7, 2020, now U.S. Pat. No. 10,786,190, which is a continuation of U.S. patent application Ser. No. 15/994,129, filed May 31, 2018, now abandoned, which is a continuation of U.S. patent application Ser. No. 15/475,647, filed Mar. 31, 2017, now U.S. Pat. No. 9,993,188, which is a continuation of U.S. patent application Ser. No. 15/192,531, filed Jun. 24, 2016, now U.S. Pat. No. 9,636,068, which is a continuation of U.S. patent application Ser. No. 12/698,129, filed Feb. 1, 2010, now U.S. Pat. No. 9,402,544, which claims priority to U.S. Provisional Application No. 61/149,639, filed Feb. 3, 2009, all of which are incorporated herein by reference in their entireties for all purposes. This application is further related to U.S. patent application Ser. No. 12/698,124, filed Feb. 1, 2010, the disclosure of which is incorporated by reference in its entirety herein for all purposes.

FIELD OF THE INVENTION

The present invention relates generally to an inserter device, for example, to insert an analyte sensor and/or an infusion set in an animal such as a human.

BACKGROUND OF THE INVENTION

Diabetes Mellitus is an incurable chronic disease in which the body does not produce or properly utilize insulin. Insulin is a hormone produced by the pancreas that regulates blood sugar (glucose). In particular, when blood sugar levels rise, e.g., after a meal, insulin lowers the blood sugar levels by facilitating blood glucose to move from the blood into the body cells. Thus, when the pancreas does not produce sufficient insulin (a condition known as Type 1 Diabetes) or does not properly utilize insulin (a condition known as Type II Diabetes), the blood glucose remains in the blood resulting in hyperglycemia or abnormally high blood sugar levels.

The vast and uncontrolled fluctuations in blood glucose levels in people suffering from diabetes cause long-term, serious complications. Some of these complications include blindness, kidney failure, and nerve damage. Additionally, it is known that diabetes is a factor in accelerating cardiovascular diseases such as atherosclerosis (hardening of the arteries), leading to stroke, coronary heart disease, and other diseases. Accordingly, one important and universal strategy in managing diabetes is to control blood glucose levels.

One way to manage blood glucose levels is testing and monitoring blood glucose levels by using conventional in vitro techniques, such as drawing blood samples, applying the blood to a test strip, and determining the blood glucose level using colorimetric, electrochemical, or photometric test meters. Another more recent technique for monitoring blood glucose levels is by using an in vivo glucose monitoring system, that continuously or automatically tests glucose, such as for example, the FreeStyle Navigator® Continuous Glucose Monitoring System, manufactured by Abbott Diabetes Care Inc. Unlike conventional blood glucose meters, continuous analyte monitoring systems employ an insertable or implantable sensor, which detects and

2

monitors blood glucose levels. Prior to each use of a new sensor, the user self-implants at least a portion of the sensor under his skin. Typically, an inserter assembly is employed to insert the sensor in the body of the user. In this manner, an introducer sharp, while engaged to the sensor, pierces an opening into the skin of the user, releases the sensor and is removed from the body of the user. Accordingly, there exists a need for an easy-to-use, simple, insertion assembly which is reliable, minimizes pain, and is easy to use.

SUMMARY

Sensor assemblies that include a medical device, such as an analyte sensor (e.g., a glucose sensor) and/or an infusion device, and a device to position at least a portion of the medical device beneath a skin surface of a user are provided, as well as methods of positioning at least a portion of a medical device such as an analyte sensor (e.g., a glucose sensor) and/or an infusion device beneath a skin surface of a user, and methods of analyte testing.

Sensor assembly embodiments include a mount adapted to adhere to a skin of a subject; an analyte sensor coupled to the mount, and an insertion sharp having a longitudinal body including a longitudinal opening to receive at least a portion of the sensor body.

In certain embodiments, the sensor includes a body having a proximal section and a distal section, and the distal section may be longitudinally (or otherwise) aligned with the proximal section. Some sensor embodiments may include an intermediate section. An intermediate section, if present, may be laterally displaced from at least the distal member (or distal section), and a gap may be defined between the laterally displaced intermediate section and a portion of the distal section. In some embodiments, the sensor is integrated with the mount to define an on-body device such as a single unit on-body device. A second gap may be defined in the sensor between the proximal section and the laterally displaced intermediate section. The proximal section of the sensor may have a substantially curved profile.

In some embodiments, the distal section of the sensor body is received in the longitudinally defined opening of the insertion sharp. A gap may be defined between the distal section and the laterally displaced intermediate section, which allows the distal section, in some embodiments a substantial portion—including the entirety of the distal section, to be received in the longitudinal opening of the insertion needle. The intermediate section and the proximal section may be proximate the distal section received in the insertion needle.

In some embodiments, the proximal section of the sensor body is in communication with conductive material disposed on the mount. The conductive material disposed on the mount may define a printed circuit board. The proximal section of the sensor may be disposed in a horizontal plane, and the distal section of the sensor body may be disposed in a vertical plane. In some embodiments, the sensor is a transcutaneous sensor. In some embodiments, the sensor is configured for implantation in a soft tissue of a user. In some embodiments, the sensor is a glucose sensor.

Embodiments include sensor assemblies which include a sensor comprising a portion for operative contact with a fluid of the subject; a mount defining a distal surface adapted for attachment to the skin of a subject and housing a circuit coupled to sensor for performing a function with the sensor; and a switch at least partially disposed in the mount comprising a member having a first position which protrudes

from the distal surface of the mount and a second position which is recessed in the mount, the member configured to activate the circuit when in the second position.

In some embodiments, the member is biased in the first position. The member may comprise an elongated member disposed in an opening in the mount. In some embodiments, the member is moved from the first position to the second position when the mount contacts the skin of the subject. In some embodiments, an adhesive layer is disposed on the skin of the subject, and wherein the member is moved from the first position to the second position when the mount contacts the adhesive layer.

In some embodiments, the switch activates the circuit upon the member reaching the second position. In some embodiments, the switch activates the circuit as long as the member is maintained in the second position. In some embodiments, the sensor is a glucose sensor.

In some embodiments, the circuit applies a potential to the sensor. In some embodiments, the circuit applies a current to the sensor.

In some embodiments, a monitor unit is provided to receive information from the sensor/on-body unit. For example, the system is configured for communication (wired or wirelessly) between the on-body unit and a monitor unit, e.g., using radio frequency communication or other protocol. The communication between the two units may be active or passive. In certain embodiments, the on-body unit circuit includes communication components for wired or wireless transmission of signal relating to analyte level monitored by the sensor to the monitor unit. In certain embodiments, RFID components may be included in the on-body unit and monitor unit to enable RFID communication, in which the on-body unit provides data communication to the monitor unit in response to one or more commands or data communication received from the monitor unit. In some embodiments, the transmitter transmits a signal to the receiver automatically, e.g., continuously or in certain embodiments only periodically, such as according to a predetermined schedule. In some embodiments, in addition to or instead of automatic data communication, the on-body unit may transmit signal to the receiver only in response to a request for the data, e.g., received from the monitor unit or otherwise initiated by the user (e.g., activation of a switch on the receiver or on-body unit to initiate data transfer). In some embodiments, a memory is provided, and the circuit stores a signal relating an analyte level provided by the sensor to the memory. In some embodiments, the sensor is a glucose sensor.

Embodiments include apparatuses for inserting medical devices through the skin of a subject. An insertion apparatus may include a sheath defining a distal surface for placement on the skin of the subject; a handle movable between a proximal position and distal position relative to the sheath; a device support for supporting the medical device and defining an aperture therethrough; a sharp support for supporting a sharp extending through said aperture and coupled to the handle; and driver for biasing the handle and the sharp support towards the proximal position.

In some embodiments, the driver comprises a compression member such as a compression spring. In some embodiments, the handle is at least partially disposed within the sheath. In some embodiments, the handle is at least partially disposed surrounding the sheath. In some embodiments, a bellows portion is provided which is disposed between the handle and the sheath.

In some embodiments, the sharp support is permanently fixed to the handle. In some embodiments, the device support is permanently affixed to the handle.

In some embodiments, a stop portion for retaining the device support in the distal position is included. In some embodiments, the device support is coupled to the sharp support until the device support reaches a distal position.

In some embodiments, the device support is uncoupled from the sharp support when the device support reaches the distal position. In some embodiments, a retention member is provided to couple the sharp support to the sheath when the sharp support is disposed in the proximal position.

In some embodiments, the medical device is an analyte sensor. In some embodiments, the medical device is a glucose sensor. In some embodiments, the medical device is an infusion set.

In certain embodiments, apparatuses for inserting a medical device through the skin of a subject, are provided which include a sheath defining a distal surface for placement on the skin of the subject; a handle movable between a proximal position and distal position; a device support for supporting the medical device and defining an aperture therethrough, the device support coupled to the handle; a sharp support for supporting a sharp extending through said aperture and coupled to the device support; and driver for biasing the sharp support towards the proximal position.

In some embodiments, the driver comprises a compression spring. In some embodiments, the handle is at least partially disposed surrounding the sheath.

In some embodiments, a stop portion for retaining the device support in the distal position is included. In some embodiments, the device support is coupled to the sharp support until the device support reaches a distal position. In some embodiments, the device support is uncoupled from the sharp support when the device support reaches the distal position.

Embodiments of analyte sensors are provided which include a body having a proximal section and a distal section. The distal section may be longitudinally aligned with the proximal section. An intermediate section may be included between the proximal and distal sections, and in some embodiments the intermediate section is laterally displaced from at least the distal member. A gap may be defined between the laterally displaced intermediate section and a portion of the distal section.

In some embodiments, the intermediate section is laterally displaced from at least a portion of the proximal section of the sensor body. A second gap may be defined between the laterally displaced intermediate section and the proximal section of the sensor body. The intermediate section may have a distal end and a proximal end, and further the proximal section may be coupled to the proximal section and the distal section may be coupled to the distal section of the sensor body. In some embodiments, the intermediate section is a longitudinal member. The proximal end may be proximate to the gap defined between the distal member and the intermediate member.

In some embodiments, the proximal end is received within a needle seat to create an anchor region to allow the sensor body to slide into an opening defined in the insertion sharp but prevent the sensor body from inadvertently slipping out of the insertion needle. In some embodiments, a width of the distal section of the sensor body is sized to fit within the opening of the insertion sharp having a diameter less than about 22 to about 24 gauge.

In some embodiments, the intermediate member includes a plane-altering portion. The plane-altering portion allows

the proximal section of the sensor body to be in a plane different than the distal section of the sensor body. In some embodiments, the proximal section and the distal section are in planes substantially perpendicular to each other, e.g., the area may define an angle of about 120° to about 60°, e.g., about 90 degrees.

In some embodiments, the proximal section has a curved portion.

In some embodiments, the sensor body includes conductive material disposed in or on a surface thereto to define one or more electrodes. The sensor body may include conductive material defining traces disposed in or on a surface of the sensor body. The traces are in communication with the one or more electrodes. The traces may be disposed in or on at least surface of the proximal section of the sensor body. The one or more electrodes may be disposed on the distal section of the sensor body. At least one of the traces or electrodes may include a metal or carbon material such as gold, platinum, titanium, carbon. At least one of the traces or electrodes may be formed by ablation of material. The ablation may include laser ablation.

In some embodiments, the sensor comprises a sensing layer. The sensing layer may comprise an enzyme. The sensing layer may comprise an electron transfer agent. The electron transfer agent may be a redox mediator. In some embodiments, the electron transfer agent includes osmium transition metal complexes and one or more ligands. The electron transfer agent may be configured to transfer electrons directly between the analyte and the working electrode. The electron transfer agent may be configured to transfer electrons indirectly between the analyte and the working electrode.

In some embodiments, the sensing layer comprises a redox polymer. The redox polymer may include osmium. The sensing layer may include a catalyst. The catalyst may include an enzyme. The catalyst may act as an electron transfer agent. In some embodiments, the enzyme includes glucose oxidase. In some embodiments, the enzyme includes glucose dehydrogenase.

In some embodiments, the sensing layer is configured such that the reaction of glucose in the presence of an enzyme forms hydrogen peroxide, and glucose level may be correlated to the level of hydrogen peroxide. In some embodiments, the sensor is a subcutaneous sensor.

These and other features, objects and advantages of the disclosed subject matter will become apparent to those persons skilled in the art upon reading the detailed description as more fully described below.

BRIEF DESCRIPTION OF THE DRAWINGS

A detailed description of various aspects, features, and embodiments of the subject matter described herein is provided with reference to the accompanying drawings, which are briefly described below. The drawings are illustrative and are not necessarily drawn to scale, with some components and features being exaggerated for clarity. The drawings illustrate various aspects and features of the present subject matter and may illustrate one or more embodiment(s) or example(s) of the present subject matter in whole or in part.

FIG. 1 is a schematic view of the system in accordance with one embodiment of the disclosed subject matter;

FIG. 2 is a view, in partial cross section, of an electrochemical sensor in accordance with one embodiment of the disclosed subject matter;

FIG. 3 is a view of an electrochemical sensor in accordance with another embodiment of the disclosed subject matter;

FIG. 4 is a view of the electrochemical sensor of FIG. 3 in a folded configuration in accordance with the disclosed subject matter;

FIG. 5 is a view of an electrochemical sensor in accordance with a further embodiment of the disclosed subject matter;

FIG. 6 is a view of the electrochemical sensor of FIG. 5 in a folded configuration in accordance with the disclosed subject matter;

FIG. 7 is a perspective view of an on-body unit in accordance with one embodiment of the disclosed subject matter;

FIG. 8 is a perspective view in partial cross-section of an on-body unit of FIG. 7 in accordance with the disclosed subject matter;

FIG. 9 is a schematic view of the system in accordance with one embodiment of the disclosed subject matter;

FIG. 10 is a sectional, perspective view of another embodiment of an inserter in accordance with the disclosed subject matter;

FIGS. 11-12 are perspective views of components of the inserter of FIG. 10 in accordance with the disclosed subject matter;

FIG. 13 is a sectional view of a component of the inserter of FIG. 10 in accordance with the disclosed subject matter;

FIGS. 14-15 are perspective views of components of the inserter of FIG. 10 in accordance with the disclosed subject matter;

FIG. 16 is a sectional view of the component of FIG. 14 in accordance with the disclosed subject matter;

FIGS. 17-18 are schematic views of a needle hub in accordance with one embodiment of the disclosed subject matter;

FIG. 19 is a distal end view of a sharp in accordance with one embodiment of the disclosed subject matter;

FIG. 20 is a side view of a sharp in accordance with one embodiment of the disclosed subject matter;

FIG. 21 is a side view of a sharp in accordance with one embodiment of the disclosed subject matter;

FIG. 22 is a perspective view with parts of an inserter in accordance with one embodiment of the disclosed subject matter;

FIG. 23 is a perspective view with parts separated of an inserter in accordance with one embodiment of the disclosed subject matter;

FIG. 24 is an enlarged sectional view with parts separated of an inserter in accordance with one embodiment of the disclosed subject matter;

FIGS. 25-27 are perspective views of components of the inserter of FIG. 10 in accordance with the disclosed subject matter;

FIGS. 28-31 are sectional views of the inserter of FIG. 10 in accordance with the disclosed subject matter;

FIGS. 32-33 illustrate a power supply switch mechanism including conductive plug of the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the disclosed subject matter;

FIGS. 34A-36B illustrate a power supply switch mechanism including conductive pads on the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the disclosed subject matter;

FIG. 37 illustrates a power supply switch mechanism including an internal switch with a push rod activation of the

on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the disclosed subject matter;

FIG. 38 illustrates power supply switch mechanism including introducer retraction trigger activation of the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the disclosed subject matter;

FIG. 39 illustrates a power supply switch mechanism with a contact switch of the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the disclosed subject matter;

FIGS. 40-41 illustrate a power supply switch mechanism with a battery contact locking mechanism of the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the disclosed subject matter;

FIGS. 42-43 illustrate a power supply switch mechanism with a bi-modal dome switch of the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the disclosed subject matter.

DETAILED DESCRIPTION OF THE EMBODIMENTS

A detailed description of the disclosure is provided herein. It should be understood, in connection with the following description, that the subject matter is not limited to particular embodiments described, as the particular embodiments of the subject matter may of course vary. It is also to be understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the disclosed subject matter will be limited only by the appended claims.

Where a range of values is provided, it is understood that each intervening value between the upper and lower limit of that range and any other stated or intervening value in that stated range, is encompassed within the disclosed subject matter. Every range stated is also intended to specifically disclose each and every "subrange" of the stated range. That is, each and every range smaller than the outside range specified by the outside upper and outside lower limits given for a range, whose upper and lower limits are within the range from said outside lower limit to said outside upper limit (unless the context clearly dictates otherwise), is also to be understood as encompassed within the disclosed subject matter, subject to any specifically excluded range or limit within the stated range. Where a range is stated by specifying one or both of an upper and lower limit, ranges excluding either or both of those stated limits, or including one or both of them, are also encompassed within the disclosed subject matter, regardless of whether or not words such as "from", "to", "through", or "including" are or are not used in describing the range.

Unless defined otherwise, all technical and scientific terms used herein have the same meaning as commonly understood by one of ordinary skill in the art to which this disclosed subject matter belongs. Although any methods and materials similar or equivalent to those described herein can also be used in the practice or testing of the present disclosed subject matter, this disclosure may specifically mention certain exemplary methods and materials.

All publications mentioned in this disclosure are, unless otherwise specified, incorporated herein by reference for all purposes, including without limitation to disclose and describe the methods and/or materials in connection with which the publications are cited.

The publications discussed herein are provided solely for their disclosure prior to the filing date of the present application. Nothing herein is to be construed as an admission that the present disclosed subject matter is not entitled to antedate such publication by virtue of prior invention. Further, the dates of publication provided may be different from the actual publication dates, which may need to be independently confirmed.

As used herein and in the appended claims, the singular forms "a", "an", and "the" include plural referents unless the context clearly dictates otherwise.

Nothing contained in the Abstract or the Summary should be understood as limiting the scope of the disclosure. The Abstract and the Summary are provided for bibliographic and convenience purposes and due to their formats and purposes should not be considered comprehensive.

As will be apparent to those of skill in the art upon reading this disclosure, each of the individual embodiments described and illustrated herein has discrete components and features which may be readily separated from or combined with the features of any of the other several embodiments without departing from the scope or spirit of the present disclosed subject matter. Any recited method can be carried out in the order of events recited, or in any other order which is logically possible. Reference to a singular item, includes the possibility that there are plural of the same item present. When two or more items (for example, elements or processes) are referenced by an alternative "or", this indicates that either could be present separately or any combination of them could be present together except where the presence of one necessarily excludes the other or others.

System Overview

Certain classes of analyte monitors are provided in small, lightweight, battery-powered and electronically-controlled systems. Such a system may be configured to detect signals indicative of in vivo analyte levels using an electrochemical sensor, and collect such signals, with or without processing the signal. In some embodiments, the portion of the system that performs this initial processing may be configured to provide the raw or initially processed data to another unit for further collection and/or processing. Such provision of data may be effected, for example, via a wired connection, such as an electrical, or via a wireless connection, such as an IR or RF connection.

Certain analyte monitoring systems for in vivo measurement employ a sensor that measures analyte levels in interstitial fluids under the surface of the subject's skin. These may be inserted partially through the skin ("transcutaneous") or entirely under the skin ("subcutaneous"). A sensor in such a system may operate as an electrochemical cell. Such a sensor may use any of a variety of electrode configurations, such as a three-electrode configuration (e.g., with "working", "reference" and "counter" electrodes), driven by a controlled potential (potentiostat) analog circuit, a two-electrode system configuration (e.g., with only working and counter electrodes), which may be self-biasing and/or self-powered, and/or other configurations. In some embodiments, the sensor may be positioned within a blood vessel.

In certain systems, the analyte sensor is in communication with a sensor control unit. As used in this disclosure, an on-body unit sometimes refers to such a combination of an analyte sensor with such a sensor control unit.

Certain embodiments are modular. The on-body unit may be separately provided as a physically distinct assembly, and configured to provide the analyte levels detected by the sensor over a communication link to a monitor unit, referred

to in this disclosure as a “receiver unit” or “receiver device”, or in some contexts, depending on the usage, as a “display unit,” “handheld unit,” or “meter”. The monitor unit, in some embodiments, may include, e.g., a mobile telephone device, a personal digital assistant, other consumer electronic device such as MP3 device, camera, radio, etc., or other communication-enabled data processing device.

The monitor unit may perform data processing and/or analysis, etc. on the received analyte data to generate information pertaining to the monitored analyte levels. The monitor unit may incorporate a display screen, which can be used, for example, to display measured analyte levels, and/or audio component such as a speaker to audibly provide information to a user, and/or a vibration device to provide tactile feedback to a user. It is also useful for a user of an analyte monitor to be able to see trend indications (including the magnitude and direction of any ongoing trend), and such data may be displayed as well, either numerically, or by a visual indicator, such as an arrow that may vary in visual attributes, such as size, shape, color, animation, or direction. The receiver device may further incorporate an in vitro analyte test strip port and related electronics in order to be able to make discrete (e.g., blood glucose) measurements.

The modularity of these systems may vary. In some embodiments the sensor is attachable and detachable from the sensor control unit (and the on-body unit may be reusable), while in other embodiments, the sensor and sensor control unit may be provided as an integrated, un-detachable package, which may be disposable after use.

FIG. 1 shows one embodiment of an analyte measurement system 10. In such a system, a data processing unit or sensor control unit 12 may interact with an analyte sensor 14 to obtain signals representative of analyte levels. Sensor control unit 12 may further include communications circuit with associated electronics (not shown). In some embodiments, the sensor control unit 12 and sensor are constructed to be maintained “on the body” of the subject for a period of time that may include hours, days, weeks, or a month or more. Accordingly, the sensor control unit 12 and sensor 14 may be referred to collectively herein as an on-body unit 16. A receiver unit or monitor unit 18 may also be provided. In the embodiment shown, sensor control unit 12 and monitor unit 18 communicate via connection 20 (in this embodiment, a wireless RF connection). Communication may occur, e.g., via RF communication, infrared communication, Bluetooth® communication, Zigbee® communication, 802.1x communication, or WiFi communication, etc. In some embodiments, the communication may include an RF frequency of 433 MHz, 13.56 MHz, or the like. In some embodiments, a secondary monitor unit 22 may be provided. A data processing terminal 24 is useful for providing further processing or review of analyte data.

In certain embodiments, system 10 may be a continuous analyte monitor (e.g., a continuous glucose monitoring system or CGM), and accordingly operate in a mode in which the communications via connection 20 has sufficient range to support a flow of data from on-body unit 16 to monitor unit 18. In some embodiments, the data flow in a CGM system is automatically provided by the on-body unit 16 to the monitor unit 18. For example, no user intervention may be required for the on-body unit 16 to send the data to the monitor unit 18. In some embodiments, the on-body unit 16 provides the signal relating to analyte level to the receiving unit 18 on a periodic basis. For example, the signal may be provided, e.g., automatically sent, on a fixed schedule, e.g., once every 250 ms, once a second, once a minute,

etc. In some embodiments, the signal is provided to the monitor unit 18 upon the occurrence of an event, e.g., a hyperglycemic event or a hypoglycemic event, etc. In some embodiments, data processing unit 12 may further include local memory in which it may record, “logged data” or buffered data collected over a period of time and provide the some or all of the accumulated data to monitor unit 18 from time-to-time. Or, a separate data logging unit may be provided to acquire periodically transmitted data from a transmitter device. Data transmission in a CGM system may be one-way communication, e.g., the on-body unit 16 provides data to the monitor unit 18 without receiving signals from the monitor unit 18. In some embodiments, two-way communication is provided between the on-body unit 16 and the monitor unit 18.

In some embodiments, a signal is provided to the monitor unit 18 “on demand.” According to such embodiments, the monitor unit 18 requests a signal from the on-body unit 16, or the on-body unit 16 may be activated to send signal upon activation to do so. Accordingly, one or both of the on-body unit 16 and monitor unit 18 may include a switch activatable by a user or activated upon some other action or event, the activation of which causes analyte-related signal to be transferred from the on-body unit 16 to the monitor unit 18. For example, the monitor unit 18 is placed in close proximity with a transmitter device and initiates a data transfer, either over a wired connection, or wirelessly by various means, including, for example various RF-carried encodings and protocols and IR links.

In some embodiments, the signal relating to analyte level is instantaneously generated by the analyte sensor 14 upon receipt of the request, and transmitted to the monitor unit 18 as requested, and/or the signal relating to analyte level is periodically obtained, e.g., once every 250 ms, once a second, once a minute, etc. Upon receipt of the “on demand” request at the on-body unit 16, an analyte signal is provided to the monitor unit. In some cases, the signal provided to the monitor unit 18 is or at least includes the most recent analyte signal(s).

In further embodiments, additional data is provided to the monitor unit 18 “on demand.” For example, analyte trend data may be provided. Such trend data may include two or more analyte data points to indicate that analyte levels are rising, falling, or stable. Analyte trend data may include data from longer periods of time, such as, e.g., several minutes, several hours, several days, or several weeks.

Further details regarding on demand systems are disclosed in U.S. Pat. No. 7,620,438, U.S. Patent Publication Nos. 2009/0054749 A1, published Feb. 26, 2009; 2007/0149873 A1, published Jun. 28, 2007, now U.S. Pat. No. 9,014,773; 2008/0064937 A1, published Mar. 13, 2008; 2008/0071157 A1, published Mar. 20, 2008; 2008/0071158 A1, published Mar. 20, 2008; 2009/0281406 A1, published Nov. 12, 2009; 2008/0058625 A1, published Mar. 6, 2008, now U.S. Pat. No. 7,920,907; 2009/0294277 A1, published Dec. 3, 2009; 2008/0319295 A1, published Dec. 25, 2008, now U.S. Pat. No. 8,597,188; 2008/0319296 A1, published Dec. 25, 2008, now U.S. Pat. No. 8,617,069; 2009/0257911 A1, published Oct. 15, 2009, now U.S. Pat. No. 8,252,229; 2008/0179187 A1, published Jul. 31, 2008, now U.S. Pat. No. 8,808,515; 2007/0149875 A1, published Jun. 28, 2007, now U.S. Pat. No. 8,515,518; 2009/0018425 A1, published Jan. 15, 2009, now U.S. Pat. No. 8,160,670; and U.S. patent application Ser. No. 12/625,524, filed Nov. 24, 2009, now U.S. Pat. No. 8,390,455; Ser. No. 12/625,525, filed Nov. 24, 2009, now U.S. Pat. No. 8,358,210; Ser. No. 12/625,528, filed Nov. 24, 2009, now U.S. Pat. No. 8,115,635; Ser. No.

11

12/628,201, filed Nov. 30, 2009, now U.S. Patent Publication No. 2010/0076280; Ser. No. 12/628,177, filed Nov. 30, 2009, now U.S. Patent Publication No. 2010/0076289; Ser. No. 12/628,198, filed Nov. 30, 2009, now U.S. Patent Publication No. 2010/0076291; Ser. No. 12/628,203, filed Nov. 30, 2009, now U.S. Patent Publication No. 2010/0076292; Ser. No. 12/628,210, filed Nov. 30, 2009, now U.S. Patent Publication No. 2010/0076293; Ser. No. 12/393,921, filed Feb. 26, 2009, now U.S. Patent Publication No. 2010/0213057; 61/149,639, filed Feb. 3, 2009; Ser. No. 12/495,709, filed Jun. 30, 2009, now U.S. Patent Publication No. 2010/0326842; 61/155,889, filed Feb. 26, 2009; 61/155,891, filed Feb. 26, 2009; 61/155,893, filed Feb. 26, 2009; 61/165,499, filed Mar. 31, 2009; 61/227,967, filed Jul. 23, 2009; 61/163,006, filed Mar. 23, 2009; Ser. No. 12/495,730, filed Jun. 30, 2009, now U.S. Patent Publication No. 2010/0331643; Ser. No. 12/495,712, filed Jun. 30, 2009, now U.S. Pat. No. 8,437,827; 61/238,461, filed Aug. 31, 2009; 61/256,925, filed Oct. 30, 2009; 61/238,494, filed Aug. 31, 2009; 61/238,159, filed Aug. 29, 2009; 61/238,483, filed Aug. 31, 2009; 61/238,581, filed Aug. 31, 2009; 61/247,508, filed Sep. 30, 2009; 61/247,516, filed Sep. 30, 2009; 61/247,514, filed Sep. 30, 2009; 61/247,519, filed Sep. 30, 2009; 61/249,535, filed Oct. 7, 2009; Ser. No. 12/544,061, filed Aug. 19, 2009, now U.S. Patent Publication No. 2011/0046466; Ser. No. 12/625,185, filed Nov. 24, 2009, now U.S. Pat. No. 8,354,013; Ser. No. 12/625,208, filed Nov. 24, 2009, now U.S. Pat. No. 9,042,954; Ser. No. 12/624,767, filed Nov. 24, 2009, now U.S. Patent Publication No. 2011/0124993; Ser. No. 12/242,780, filed Sep. 30, 2008, now U.S. Pat. No. 8,983,568; Ser. No. 12/183,602, filed Jul. 31, 2008, now U.S. Patent Publication No. 2010/0030052; Ser. No. 12/211,014, filed Sep. 15, 2008, now U.S. Pat. No. 8,636,884; and Ser. No. 12/114,359, filed May 2, 2008, now U.S. Pat. No. 8,080,385, each of which is incorporated by reference in its entirety herein.

The Sensor

The analyte sensor **14** of the analyte measurement system **10** may be used to monitor levels of a wide variety of analytes. Analytes that may be monitored include, for example, acetyl choline, amylase, bilirubin, cholesterol, chorionic gonadotropin, creatine kinase (e.g., CK-MB), creatine, DNA, fructosamine, glucose, glutamine, growth hormones, hormones, ketones, lactate, peroxide, prostate-specific antigen, prothrombin, RNA, thyroid stimulating hormone, and troponin. The concentration of drugs, such as, for example, antibiotics (e.g., gentamicin, vancomycin, and the like), digitoxin, digoxin, drugs of abuse, theophylline, and warfarin, may also be monitored. One or more analyte may be monitored by a given sensor.

In one embodiment of the present disclosure, sensor **14** is physically positioned in or on the body of a user whose analyte level is being monitored. Sensor **14** may be configured to continuously sample the analyte level of the user and convert the sampled analyte level, e.g., glucose concentration into a corresponding data signal, e.g., a current or voltage, for input into sensor control unit electronics. Alternatively, sensor **14** may be configured to sample analyte levels on demand. The sensor control unit electronics may amplify, filter, or otherwise process the signal provided by the sensor.

The sensor may take on a number of forms. For example, the sensor may include a flexible or rigid substrate. In some embodiments, the sensor may be a wire. In some embodiments, the sensor may include two or three or more electrodes.

12

An embodiment of the sensor **14** is illustrated in FIG. **2**. In some embodiments, sensor **14** includes a substrate which is a dielectric, e.g., a polymer or plastic material, such as polyester or polyamide. In this embodiment, the sensor is constructed so that a portion is positionable beneath skin and a portion is above skin. Accordingly, sensor **14** includes an insertion portion **30** and a contact portion **32**. The contact portion **32** typically includes several conductive contacts **36**, **38**, and **40** (herein shown as 3 contacts) for connection to other electronics, e.g., at the data processing unit **12**. The contacts provided in this embodiment are for a working electrode **36**, a reference electrode **38**, and a counter electrode **40**. In some embodiments, two or more working electrodes are provided. The operative portions of these electrodes, that is, working electrode, reference electrode, and counter electrode (not individually shown), are provided at the distal end of insertion portion **30**. The contact and operative portions of the electrodes are connected by circuit traces **42**, **44**, and **46** running on the surface of substrate. In some embodiments, the traces are provided in channels, or may be embedded within the substrate, or may traverse different sides of the substrate. The conductive contacts, conductive traces, and electrodes are fabricated from a conductive material, such as platinum, palladium, gold, or conductive carbon. Further details of sensors are described, e.g., in U.S. Pat. Nos. 6,175,572; 6,103,033, which are incorporated by reference herein.

Sensor **14** may include a proximal retention portion **48**. In some embodiments, the insertion portion **30** and the proximal retention portion **48** are substantially longitudinally aligned. The insertion portion **30** and the proximal retention portion **48** are sized and configured to be positioned with a sharp for installation into the skin of a subject, as described herein. In use, the sensor **14** may be configured to bend (e.g., along the line B) and therefore be positioned in two substantially perpendicular, intersecting planes.

As illustrated in FIG. **3**, sensor **14'** is substantially identical to sensor **14**, with many of the differences illustrated in FIG. **3** and noted herein. Sensor **14'** further includes additional features useful for connecting to, e.g., mounting to or in or on, a housing associated with the sensor control unit **12**. For example, sensor **14'** includes a laterally displaced portion (or sensor tab) **50'** and a longitudinal displaced portion **52'** which provide a path for electrical connections, e.g., the conductive traces. Sensor **14'** is further provided with a notch **54'** between the proximal retention portion **48'** and the longitudinal displaced portion **52'**. Such configuration permits the sensor **14'** to bend (e.g., along the line are indicated by line B) and therefore be positioned in two substantially perpendicular, intersecting planes, as illustrated in FIG. **4**. As will be described below, the sensor tab **50'** can be encased in a portion of the body of the data processing unit **12** to aid in securing and positioning the sensor **14'**. Proximal retention portion **48'** maintains its longitudinal alignment with insertion portion **30'** for positioning within an insertion sharp.

FIG. **5** illustrates a further embodiment of a sensor **14''** in accordance with the disclosure. Sensor **14''** is substantially identical to sensor **14** and **14'**, with certain exemplary differences illustrated in FIG. **5** and noted herein. For example, sensor **14''** includes a contact portion **32''** which defines a fan-like configuration having a curved edge. Sensor **14''** defines a sensor flag indentation **56''** which also serves to assist in retaining the sensor **14''** in vertical direction, as will be described below, and provides a discrete location for mating with a feature of the data processing unit **12**, e.g., the bottom surface of a printed circuit board. Sensor

13

14" is likewise capable of bending along axis B, as illustrated in FIG. 6. In any of the embodiments of the sensor described herein, the distance between insertion portion 30 to retention portion 48 may be, e.g., about 5 mm, or about 10 mm, or about 15 mm, or about 20 mm.

In general, sensors in accordance with the present disclosure operate electrochemically, through an arrangement of electrodes having chemical sensing layers applied thereto, by generating an electrical current proportional to the volume of a redox reaction of the analyte (and indicative of analyte concentration), catalyzed by an analyte-specific oxidizing enzyme. Embodiments exist in which the number of electrodes provided to bring about and detect the level of these reactions is two, three or a greater number.

A portion of sensor 14 (which collectively refers to sensors 14' and 14" herein) may be situated above the surface of the skin, with a distal portion 30 penetrating through the skin and into the subcutaneous space in contact with the user's biofluid, such as interstitial fluid. The disposition of the sensor in the illustrated embodiment is referred to as "transcutaneous". In general, the term "transcutaneous" as used herein refers to a sensor that is only partially inserted under one or more layers of the skin of the user, whereas the term "subcutaneous" refers to a sensor that is completely inserted under one or more layers of the skin of the user. It is understood that many features described herein would be applicable to both transcutaneous and subcutaneous sensors. Further details regarding the electrochemistry of sensor 14 is provided in U.S. Pat. Nos. 5,264,104; 5,356,786; 5,262,035, 5,320,725, 6,990,366, each of which is incorporated herein by reference.

In some embodiments, the sensor is implantable into a subject's body for a period of time (e.g., three to seven days, or in some embodiments, longer periods of up to several weeks) to contact and monitor an analyte present in a biological fluid. In this regard, the sensor can be disposed in a subject at a variety of sites (e.g., abdomen, upper arm, thigh, etc.), including intramuscularly, transcutaneously, intravascularly, or in a body cavity. In one embodiment, the sensor can be a transcutaneous glucose sensor. Alternatively, the sensor can be a subcutaneous glucose sensor.

In some embodiments, sensor 14 is employed by insertion and/or implantation into a user's body for some usage period. In such embodiments, substrate may be formed from a relatively flexible material to improve comfort for the user and reduce damage to the surrounding tissue of the insertion site, e.g., by reducing relative movement of the sensor with respect to the surrounding tissue.

While the embodiments illustrated in FIGS. 2-6 have three electrodes, other embodiments can include a fewer or greater number of electrodes. For example, a two electrode sensor can be utilized. The sensor may be externally-powered and allow a current to pass proportional to the amount of analyte present. Alternatively, the sensor itself may act as a current source in some embodiments. In some two-electrode embodiments, the sensor may be self-biasing and there may be no need for a reference electrode. An exemplary self-powered, two-electrode sensor is described in U.S. patent application Ser. No. 12/393,921, filed Feb. 26, 2009, and entitled "Self-Powered Analyte Sensor," which is hereby incorporated by reference in its entirety herein for all purposes. The level of current provided by a self-powered sensor may be low, for example, on the order of nanoamperes.

On-Body Unit

An exemplary configuration for sensor 14 (and sensors 14' and 14") and sensor control unit 12 (e.g., collectively

14

on-body unit 16) is illustrated in FIGS. 7-8. Data processing unit 12, may be provided with a substantially circular configuration having a reduced height (i.e., "Z"-dimension) to provide a low-profile when sitting on the skin of the subject. In some embodiments, the height is about 3 mm to about 25 mm, e.g., may be about 4 mm, about 5 mm, about 10 mm, or about 15 mm. In certain embodiments, the unit 12 may have a variable height. Data processing unit 12, including its associated electronics 80, are housed in a sensor housing 122. For example, electronics may include, e.g., an analog interface for connecting to the sensor 14, a processor, and a power supply. A serial communication section may be provided. A temperature sensor, such as a thermistor, which detects skin and/or ambient temperature may be included to provide compensation to the analyte signal. A RF communication circuit is provided to communicate with the monitor unit 18. A data storage unit may be provided to store analyte data points over a short term, e.g., several hours or minutes, or over a long term, e.g., several days or weeks. Additional optional electronics include a serial communication section, a leakage detection circuit, or user input, e.g., a switch to activate/deactivate some or all of the device. Many of the components may be combined together and/or their function provided by common components. Furthermore, certain components may be eliminated entirely. For example, a power supply may be omitted if power is provided by inductive coupling.

In some embodiments, sensor 14 is disposed within the data transmitting unit 12, e.g., in a bent configuration, as illustrated in certain embodiments herein, e.g., in FIGS. 4 and 6. The contact portion 32 of sensor 14 may be oriented in a substantially horizontal configuration, and secured to a printed circuit board of the transmitter unit 12. The insertion portion 30 of the sensor 14 extends in a substantially downwardly vertical orientation for placement in the skin of the subject. It is understood that sensor 14 may be disposed in other configurations, e.g., in an entirely substantially vertical configuration, etc. As a further example, the insertion portion 30 may be disposed at an oblique angle, e.g., between about 0° and about 90° with respect to the skin surface.

As illustrated in FIG. 9, the on-body unit 16 communicates with the monitor unit 18. Such communication may be one-way communication, e.g., from the on-body unit 16 to the monitor unit 18. In some embodiments, the communication may be two-way, e.g., both from the on-body unit 16 to the receiving unit 18 and from the receiving unit 18 to the on-body unit 16. In such cases, the receiving unit 18 may also be referred to herein as a display unit, transceiver or handheld unit. Communication between the on-body unit 16 and monitor unit 18 may occur via RF communication, inductive coupling, direct wired connection, etc.

Insertion Assembly

An insertion assembly is provided, which is used to install a medical device to the subject. In some embodiments, the insertion assembly includes an inserter and the medical device itself. The inserter can be configured to insert various medical devices to the subject, such as for example, an analyte sensor, an infusion set, a cannula, or a lancet. In some embodiments, the inserter can be configured to install a combination of such devices, e.g., a combined sensor/infusion set, etc. In certain embodiments, a given inserter can be configured to install a first device and a second device at different times. For example, an inserter may be modifiable to be used with more than one medical device, include more than one type of medical device, e.g., by attaching an adapter and/or removing detaching a portion of an inserter.

15

The inserter can install the medical device transcutaneously in, under, or through the skin of the subject; or subcutaneously; or placed on the surface of the skin. The medical device can include features or structures, e.g., barbs, tabs, adhesive, etc., to maintain the device in position with respect to the skin after insertion.

In other embodiments, the insertion assembly includes an inserter, a medical device, such as an analyte sensor, and a mount for supporting the medical device at least partially in or on the skin of the subject. The mount may be inserted simultaneously with the medical device by the inserter. In other embodiments, the mount is installed after or before installation of the medical device. In such case the mount may be applied by the inserter or separately. The mount may include features or structures to maintain the sensor in position with respect to the skin after insertion.

In further embodiments, the insertion assembly includes an inserter, an analyte sensor, a mount, and a power supply. The mount and power supply may be inserted simultaneously with the analyte sensor by the inserter. In other embodiments, the mount and battery are installed after or before installation of the analyte sensor. In such case the mount and/or power supply may be applied by the inserter or separately.

In still further embodiments, the insertion assembly includes an inserter, a medical device such as an analyte sensor, a mount, and electronics. The mount and electronics may be inserted simultaneously with the analyte sensor by the inserter. In other embodiments, the mount and electronics are installed after or before installation of the analyte sensor. For example, the mount and the analyte sensor may be installed by the inserter, and the electronics may be subsequently installed. In other embodiments, the mount is installed, followed by insertion of the analyte sensor by the inserter, and further followed by installation of the electronics. In other embodiments, the mount and electronics are installed first, and the analyte sensor is subsequently installed.

In some embodiments, the electronics provide a voltage or current to the analyte sensor. In some embodiments, the electronics processes signals provided by the analyte sensor. In further embodiments, the electronics may include communication functionality for providing a signal relating to the signal provided by the analyte sensor to a further component, such as, e.g., a monitor unit, a handheld unit, a meter, a display unit, a computer, or other component. In some embodiments, communications circuitry, such as RFID antenna or communications circuitry is provided.

The inserter can include a plurality of different components. For example, the inserter may include one or more components for advancing a sharp towards the skin of the subject. The sensor and associated electronics and/or mounting structure may be supported by a support structure, such as a carriage. An actuator may be provided for advancing the sharp and/or the analyte sensor/support structure. In some embodiments, the actuator is coupled to the sharp and/or support structure, such that manual force and speed applied by the user to the actuator is transferred to the sharp and/or support structure.

The inserter can also include one or more components for retracting the sharp, while allowing the analyte sensor and optional mount and/or electronics to remain to the subject. The components for retracting the sharp can include a retractor. It is understood that the retractor and the actuator may be the same structure or include some common components. In some embodiments, the retractor is directly or indirectly coupled to the sharp such that the manual force

16

applied by the user is transferred from the retractor to the sharp to retract the sharp from the skin. In other embodiments, a drive assembly may be provided to retract the sharp. For example, the drive assembly may include a spring, motor, hydraulic piston, etc., to retract the sharp away from the skin of the subject. The drive assembly may also include a linear drive component.

In some embodiments, the retractor withdraws the sharp upon actuation by the user. In such cases, the user actuates the retractor when it is desired to withdraw the sharp. For example, the retractor may include a release switch. Upon activation of the release switch, the drive assembly, e.g., the spring or other driver, retracts the sharp from the skin. In other embodiments, the retractor and the actuator comprise common components. After activating the actuator to advance the sharp and the analyte sensor, the user releases the actuator, which allows the drive assembly to withdraw the sharp from the skin.

In some embodiments, the retractor withdraws the sharp without further user interaction after actuation of insertion. For example, the inserter may include features or components which automatically retract the sharp upon advancement of the sharp and support structure by a predetermined amount. Inserter devices, in which no further action by the user is required to initiate withdrawal of the sharp after insertion, are referred to herein as having "automatic" withdrawal of the sharp.

Inserter Devices

An inserter **100** in accordance with an exemplary embodiment is illustrated in FIG. **10**. Inserter **100** includes a handle **102** and a removable distal cap **104**. The cap **104** may maintain a sterile, contaminant-free environment for the medical device and sharp housed therein. As illustrated in FIGS. **10-16**, distal cap **104** is secured to handle **102**, e.g., by use of one or more mating members, e.g., threads **110** and **111**, or hooks, tape, and the like. Inserter **100** includes a base **142** which defines a distal, substantially planar surface **112** for placement on the skin **S** of a subject, and in other embodiments may be a curved or inclined surface, e.g., a concave or convex surface. Inserter **100** may be utilized to advance a medical device into the skin of the subject, e.g., an analyte sensor, and infusion set, etc. In some embodiments, handle **102** is advanced relative to base **142** in order to advance the medical device into the skin of the patient, as will be described in greater detail herein.

The components of inserter **100** are illustrated in FIGS. **11-27**. As illustrated in FIG. **11**, handle **102** includes a contact surface **114** for contact by a user to insert and install the sensor housing **122** and sensor **14**. Threads **110** are provided on handle **102** for attachment to cap **104** via threads **111** (as illustrated in FIGS. **12-13**). Cap **104** can include an upwardly extending boss **125** to assist positioning of the sharp **124**. The distal portion of cap **104** includes a recess **115** for retaining a desiccant **190** therein. In some embodiments, a silica gel or molecular sieves may be used. Such material can be in either in granular form (pellets) or pressed into tablets. In some embodiments, silica gel tablets are used.

Cap **104** is provided with one or more apertures **117**, which allows for passage of air to the desiccant **190** to remove moisture from the interior of the inserter **100**. Cap **104** includes an annular ridge **113** which engages the distal edge portion **116** of handle **102**. In some embodiments, annular ridge **113** prevents distal movement of handle **102** (as well as sharp **124**) when cap **104** is attached to handle **102**.

17

Base **142**, as illustrated in FIGS. **10** and **14**, includes a distal sheath portion **192**, which shields sharp **124** prior to deployment and a distal rim **112** having a substantially planar surface configuration to rest on the subject's skin. Base **142** also includes side walls **191**, which along with inner rail **128** defines a recess for retraction spring **146**. Base **142** provides a spring floor **148**, as illustrated in FIG. **29**.

Support member or shuttle **134**, as illustrated in FIGS. **15-16**, supports needle hub **136**, from which sharp **124** extends longitudinally within the inserter **100**. In some embodiments, the sharp is supported at an oblique angle, e.g., between about 0° and about 90° with respect to the skin surface. Needle hub **136** can be secured to shuttle **134** via an interlocking O-ring configuration, adhesive, or other techniques known in the art. In some embodiments, sharp **124** is a solid needle. In some embodiments, sharp **124** is provided with a substantially cylindrical configuration defining an interior bore, e.g., a rigid cannula or a hypodermic-style needle.

Needle hub **136** is further illustrated in FIGS. **17-18**. Needle hub **136** supports sharp **124**, having a sharpened distal portion **160**. In some embodiments, as discussed herein, a longitudinal wall opening or gap **162** is provided in at least a portion of the wall of the sharp **124**. The length **N** of the gap **162** is selected to be commensurate with the length of the insertion portion **30** through to the proximal retention portion **48** of the sensor, or about 5 mm, or about 10 mm, or about 15 mm, or about 20 mm. The length **L** of the sharp **124** may be about 5 mm, or about 10 mm, or about 20 mm, about 30 mm, or about 50 mm, and is selected based upon the desired depth of the insertion portion **30** of the sensor **14**.

The distal portion **160** of sharp **124** is illustrated in greater detail in FIGS. **19-21**. As illustrated in FIG. **19**, sharp **124** has a substantially "C"- or "U"-shaped profile in this embodiment, but may have other configurations, e.g., substantially "V"-shaped. A longitudinal gap **162** is provided in the wall of the sharp **124**. FIG. **20** illustrates distal portion **160** is provided with an angled tip. In some embodiments, the angled tip may be provided with a first angled tip portion **164** and a second steep-angled tip portion **166**. The exemplary configuration, which includes multiple edges and faces, provides a sharp point to reduce penetration force, trauma, and bleeding for the subject. The distal section of the sensor body has a width sized to fit within the notch **162** of the insertion sharp **124** having a diameter less than about 22 to about 24 gauge, in certain embodiments the sharp is 25 gauge. In some embodiments, sharp **124** is a fabricated from a sheet of metal, and folded into a substantially "V" or "U" or "C" configuration in cross-section. In some embodiments, a laser is used to form the wall opening or gap **162**.

FIGS. **22-23** illustrate the position of sensor housing **122** with respect to the needle hub **136** and sharp **124**. As illustrated in FIG. **22**, the sharp **124** extends through an aperture **168** in the sensor housing **122**. The distal portion of sensor **14** is positioned with the sharp **124**. As further illustrated in FIG. **23**, electronics **80** (e.g., a printed circuit board containing ASIC electronics) and sensor hub **123** are positioned within sensor housing **122**. A power supply **82**, such as a battery, e.g., a single use disposable battery, or rechargeable battery, is provided. In some embodiments, the active operational life of the battery may exceed the active operational life of the sensor **14**.

FIG. **24** illustrates in cross-section the orientation of the sensor housing **122** with respect to the sharp **124** of inserter **100**. As discussed herein, sensor **14** is disposed in a substantially bent configuration, such that a portion of the

18

sensor, e.g., the insertion portion **30** and the proximal retention portion **48** are substantially vertical (e.g., substantially aligned with the longitudinal axis of the inserter **100** and substantially perpendicular to the skin surface) and the contact portion **32** (shown in profile) is oriented in a substantially horizontal configuration, and in electrical contact with the data processing unit electronics, such as circuit **80**. The sensor tab **50** can be encased in the plastic of the sensor housing **122** (e.g., "overmolded") and secured in place. The notch **56** provides further stability to the sensor **14**, e.g., by allowing the sensor tab **50** to be encased by the material of the sensor housing **122**, and further provides a means for vertically orienting the sensor **14** during mounting, e.g., by allowing vertical positioning of the notch **56** with respect to a vertical landmark of the housing **122**.

The sensor **14**, mounted with the sensor housing **122**, is disposed within the concave recess in the carriage **130**. In the initial configuration of the inserter **100** (see, e.g., FIGS. **10** and **28-29**) the sharp **124** extends through a longitudinal aperture **168** formed in a carriage **130**. In some embodiments, the aperture **168** is appropriately sized, such that neither the sharp **124** nor needle hub **136** is in contact with the carriage **130**. Accordingly, the needle hub **136** (and sharp **124**) on the one hand, and the carriage **130** and the sensor housing **122**, on the other hand, move simultaneously but independently from one another. In other embodiments, a friction fit may be provided between the aperture and the sharp.

The insertion portion **30** and proximal retention portion **48** of the sensor **14** are disposed within a longitudinal bore **162** within the sharp **124**. (See, e.g., FIG. **19**) The proximal retention portion **48** is disposed within the longitudinal bore of the sharp and provides additional stability to the mounting of the sensor **14** within the sharp **124**. The longitudinal wall gap or opening **162** of sharp **124** is aligned with the sensor **14**, such that the tab **50** and the contact portion **32** extend laterally outward from the sharp **124**.

With continued reference to FIGS. **15** and **16**, shuttle **134** includes wings **182** and resilient distally-extending fingers **184**. Inner rail **128** is illustrated in FIG. **25**. As illustrated in FIG. **26**, shuttle **134** is sized and configured for slidable movement within inner rail **128**. Wings **182** of shuttle **134** are configured for slidable movement within axial notches **188** of inner rail **128**. When fingers **184** of shuttle **134** are disposed in their normally biased outward position, fingers **184** engage the lower surface **194** of inner rail **128**. In the configuration illustrated in FIG. **26**, shuttle **134** is locked with respect to inner rail **128**. As will be discussed herein, fingers **184** may be biased radially inward to allow upward movement of shuttle **134** relative to inner rail **128**.

As illustrated in FIG. **10**, inner rail includes an upper surface **186** for engagement with handle **102**. In some embodiments, surface **186** is adhered or otherwise fixed to handle **102**.

The relationship of inner rail **128**, shuttle **134** and base **142** is illustrated in FIG. **27**. In an initial configuration, inner rail **128** and shuttle **134** are in a locked relationship by engagement of wings **182** and fingers **184**. Inner rail **128** and shuttle **134** are axially movable within base **142**. Spring **146**, which is secured between spring floor **148** of base **142** and wings **182** of shuttle **134** biases the inner rail **128** and shuttle **134** in a proximal (upward) direction.

Inserter **100** is illustrated in section in FIGS. **28-29** prior to use in a sensor pre-deployment position. Cap **104** is attached to the distal portion of inserter **100**, via inter-engagement of threads **110** and **111**.

19

As illustrated in FIG. 28, the inserter 100 includes an initial configuration in which the handle 102 is disposed in a proximal position with respect to the base 142. In such configuration, the sharp 124 is disposed in a configuration spaced apart from an aperture of the adhesive layer 118.

As illustrated in FIG. 30, inner rail 128 includes a carriage 130. In a sensor insertion position, the handle 102 is depressed downward (arrow D) against the bias of spring 146, the inner rail 128 moves downwardly with the carriage 130 and the sensor housing 122. Shuttle 134 supports needle hub 136, from which sharp 124 extends longitudinally within the inserter 100. Initially shuttle 134 is coupled to inner rail 128 via inter-engagement of fingers 184 of shuttle 134 with distal surface 194 of inner rail 128, and both shuttle 134 and inner rail 128 move distally together as a unit.

As the sharp 124 is urged distally (FIG. 30), it carries the sensor insertion portion 30 of sensor 14 into the subcutaneous portion of the subject's skin S and into contact with the interstitial fluid. As carriage 130 reaches a distal position, the distal surface of the sensor housing 122 engages the upper surface of adhesive pad 118, thereby becoming adhered to the skin surface S of the subject.

Flanges 170 on base 142 engage fingers 184 of shuttle 134. Fingers 184 are pivoted or bend inwards by contact with flanges 170 (as indicated by arrows F).

As illustrated in FIG. 31, such pivoting of fingers 184 causes fingers 184 to become disengaged from distal edge 194 of inner rail 128. Shuttle 134 is thereby disengaged from inner rail 128. Disengagement of the shuttle 134 from the inner rail 128 permits the spring 146 to expand, thereby advancing the shuttle 134 to a proximal position, and withdrawing the sharp 124 from the sensor 14 and the skin S of the subject, while leaving the sensor 14 in the skin. Once the sharp has been withdrawn from the subject, it is no longer accessible from the distal portion of the inserter 100, which prevents accidental needle sticks. When the carriage 130 reaches the distal position in which flanges 170 engage fingers 184 of needle shuttle 134, needle shuttle 134 withdraws needle 124 automatically without further input from the user.

Prior to activation of the integrated sensor 14 and sensor electronics assembly 16 for use, there may be a period of time from the manufacturing that the assembly 16 may be in a "sleep" or "idle" mode. With a power supply such as a battery integrated within the assembly, for reasons including cost optimization and prolonging shelf life, embodiments of the present disclosure include systems that are activated merely by positioning the sensor 14 and electronics unit 16 on a skin surface as described above, i.e., no additional action may be required of the user other than applying a force to housing 122. As such, insertion of the sensor 14 and/or mounting of the housing 122 causes activation of the electronics 80. In certain embodiments, activation switch configurations are included which may be configured to be triggered, for example, by the insertion device activation, thereby turning on the integrated sensor and sensor electronics assembly into an active mode.

As illustrated in FIG. 29, inserter 100 is also provided with a plunger switch 185, which provides automatic activation of the electronics 80 of the data processing unit 12. In some embodiments, the plunger switch 185 is a longitudinally slidable member disposed on the distal surface of the sensor housing 122. When the sensor housing is advanced proximally, it engages the adhesive pad 118, or alternatively the skin surface of the subject. Upon such engagement, the plunger switch 185 is moved axially (proximally) with respect to the housing 122. The plunger switch in the

20

proximal position is shown in FIG. 30, for example. Such axial movement is used to activate the sensor electronics 80. In some embodiments, the plunger switch is spring biased. Accordingly, as long as the sensor housing is maintained in a fixed relationship with the adhesive pad 118 against the bias, electronic activation is maintained. If the sensor housing is removed from the adhesive or the skin, the plunger switch moves with the bias, and the electronics are deactivated. In other embodiments, the plunger switch provides a one-time activation of the electronics. In such cases, once the electronics are activated, the sensor housing is not required to remain in contact with the adhesive or the skin in order to maintain activation.

As illustrated in FIGS. 32-33, embodiments of a power supply switch mechanism include conductive plugs of the on-body integrated sensor and sensor electronics assembly 16 in accordance with the present disclosure. FIGS. 32-33 illustrate enlarged sectional views of sensor housing 122. As shown, the sensor electronics assembly circuit board 710 may be provided with a physical gap 750 that breaks the electrical circuit between the power supply (e.g., battery) and the other circuitry of the sensor electronics assembly.

In one embodiment, when the predetermined force is applied on the insertion device 100 as discussed above, a conductive portion 720 provided within the housing 122 of the sensor electronics may be moved in a direction as shown by arrow 730 such that electrical contact is established in the physical gap 750 on the circuit board, by for example, the conductive portion 720 coming into physical contact with the conductive portions 760 of the circuit board 710. In this manner, in one embodiment, the electrical path from the power supply and the remaining circuitry on the circuit board of the sensor electronics is completed, thereby powering the sensor electronics.

By way of another example, referring to FIG. 33, the conductive portions 760 of the circuit board are provided on the board itself, and the conductive plug 740, for example, when pushed into the cavity 750, establishes electrical contact between the conductive portions 760 of the circuit board.

In one embodiment, as discussed above, the actuation of the insertion device 100 to position the sensor and sensor electronics assembly triggers the switch mechanism shown in FIGS. 32-33 by also moving the conductive portion 720 or the conductive plug 740 in the direction complementary to the direction of the introducer movement, and thereby switching on the sensor electronics. Within the scope of the present disclosure, the activation of the sensor electronics by moving the conductive portion 720 or the conductive plug may include a separate procedure, where after positioning the sensor and the sensor electronics assembly on the skin surface, a predetermined force is applied on the housing of the integrated sensor 14 and sensor electronics assembly such that the desired movement of the conductive portion 720 or the conductive plug 740 may be achieved.

FIGS. 34A-36B illustrate another configuration of the power supply switch mechanism including conductive pads of the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the present disclosure. Referring to FIG. 34A, an exposed conductive ring 771 may be provided and configured to contact the surface of the circuit board in the sensor housing 122 (shown in cross section in FIG. 34B) such that, the insertion device activation positions the conductive ring 771 on the surface of the circuit board so as to complete the electrical contact of the sensor housing 122 (by for example, manual force

21

applied on the insertion device placing the conductive ring in contact with the circuit board of the sensor electronics).

Referring to FIGS. 35A-B, in another aspect, electrical contact pads 772, 773 may be provided to the circuit board in the sensor housing 122 (shown in cross section in FIG. 35B, such that the mating of the contact pads with the conductive ring 771 switches on the sensor electronics device to provide power to the device from its power source. FIGS. 36A-B show yet another configuration of the switch activation mechanism in accordance with the present disclosure, where a portion of the conductive ring 774 is selectively positioned and provided to establish electrical contact in the sensor housing 122 (shown in cross section in FIG. 36B).

As discussed, each of the activation configurations described above includes a break in the circuitry from the power source such that the power supply is not drained when the device is not in use, and upon activation, the break in the electrical contact is completed, thereby powering the device and activating it for operation.

FIG. 37 illustrates a power supply switch mechanism including an internal switch with a push rod activation of the on-body integrated sensor and sensor housing 122 in accordance with embodiments of the present disclosure. As shown, in one embodiment, push rod 810 may be provided and positioned in the sensor electronics such that when a force is applied in the direction as shown by arrow 830, the push rod 810 is displaced in the same direction and completes the electrical contact between the two contacts 820, 821. In one aspect, the push rod 810 may be provided within a seal 840 such as an O-ring or similar components.

FIG. 38 illustrates power supply switch mechanism including introducer retraction trigger activation of the on-body integrated sensor and sensor housing 122 in accordance with embodiments of the present disclosure. As shown, a nonconducting needle or device 910 is provided to physically separate two electrical contacts 920, 921. Each of the electrical contacts 920, 921 is biased or spring loaded to be urged towards each other, physically separated by the nonconducting needle 910. Accordingly, when the nonconducting needle 910 is retracted or pulled away from the sensor electronics assembly in the direction as shown by arrow 930, the electrical contacts 920, 921 are configured to contact each other, thereby completing the break in the circuit and establishing electrical connection to activate the sensor electronics assembly. In one aspect, the nonconducting device or needle 910 may include, for example, but not limited to, glass, plastic or any other material suitable to separate two electrical contacts and provide insulation therebetween.

FIG. 39 illustrates power supply switch mechanism with a contact switch of the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the present disclosure. As shown, in a further aspect, there is provided an electronic switch 1001 (that is configured to draw an insubstantial amount of power from the sensor electronics power supply), and when triggered, completes the break between the contacts 1010, 1011 by physically contacting the two contacts 1010, 1011 with the activation component 1002 that completes the circuit in the sensor electronics from its power supply such as battery to activate the device for operation.

FIGS. 40-41 illustrate a power supply switch mechanism with a battery contact locking mechanism of the on-body integrated sensor and sensor electronics assembly 122 in accordance with the present disclosure. Referring to FIGS. 40-41, in still another aspect, the battery contact of the

22

sensor electronics may be provided with a barbed tab 1110. In post manufacturing shelf mode when the device is non-operational, the tab 1110 is positioned within the sensor electronics housing in the position as shown in FIG. 40 so that it is not in contact with the conductive contact 1120 of the sensor electronics circuit board. When in use as shown in FIG. 41, the tab 1110 may be biased such that it physically contacts the conductive contact 1120 on the circuit board, thereby closing the circuit to/from the battery/power source and thus activating or switching on the sensor electronics. As shown in the Figures, the tab 1110 may be configured that upon biasing to establish contact with the conductive contact 1120, it locks or latches with the conductive contact 1120 and the circuit board so as to maintain the electrical connection.

FIGS. 42-43 illustrate power supply switch mechanism with a bi-modal dome switch of the on-body integrated sensor and sensor electronics assembly in accordance with embodiments of the present disclosure. Yet in another embodiment, a bi-modal dome shaped switch 1210 is provided on the circuit board of the sensor electronics assembly such that, when pressed down (as shown in FIG. 42), the dome shaped layer 1210 (which may include, for example, a thin sheet metal dome) may be configured to retain the concave shape as shown in FIG. 43 and effectively closing the circuit on the circuit board at the contact point 1220. In one aspect, the dome shaped layer 1210 may be configured to shunt to short two or more electrical contacts at the contact point 1220 of the circuit board. Alternatively, the dome shaped layer 1210 may be connected to the circuit board such that one end of the dome shaped layer 1210 is in contact with one of the two or more open electrical contacts, and the depression of the dome shaped layer 1210 closes the circuit on the circuit board by physically contacting the other one or more of the open electrical contacts.

In the manner described above, in accordance with various embodiments of the present disclosure, sensor electronics activation switch configurations are provided that may be triggered or activated automatically or semi-automatically in response to the activation of the insertion device described above, or alternatively, may be separately activated by the user by, for example, depressing upon a portion of the housing or switch provided on the housing of the sensor electronics. Accordingly, power consumption may be optimized for the sensor electronics assembly while improving post manufacturing shelf life of the device prior to use or activation.

It is understood that the subject matter described herein is not limited to particular embodiments described, as such may, of course, vary. It is also understood that the terminology used herein is for the purpose of describing particular embodiments only, and is not intended to be limiting, since the scope of the present subject matter is limited only by the appended claims.

Additional detailed description of embodiments of the disclosed subject matter are provided in but not limited to: U.S. Pat. Nos. 7,299,082; 7,167,818; 7,041,468; 6,942,518; 6,893,545; 6,881,551; 6,773,671; 6,764,581; 6,749,740; 6,746,582; 6,736,957; 6,730,200; 6,676,816; 6,618,934; 6,616,819; 6,600,997; 6,592,745; 6,591,125; 6,560,471; 6,540,891; 6,514,718; 6,514,460; 6,503,381; 6,461,496; 6,377,894; 6,338,790; 6,299,757; 6,299,757; 6,284,478; 6,270,455; 6,175,752; 6,161,095; 6,144,837; 6,143,164; 6,121,009; 6,120,676; 6,071,391; 5,918,603; 5,899,855; 5,822,715; 5,820,551; 5,628,890; 5,601,435; 5,593,852; 5,509,410; 5,320,715; 5,264,014; 5,262,305; 5,262,035; 4,711,245; 4,545,382; U.S. Patent Publication No. 2004/

23

0186365, published Sep. 23, 2004, now U.S. Pat. No. 7,811,231; U.S. Patent Application No. 61/238,646, filed Aug. 31, 2009, the disclosures of each of which is incorporated herein by reference.

What is claimed is:

1. An insertion assembly, comprising:

(a) an on-body unit, comprising:

a housing comprising a top surface and a bottom surface, wherein the top surface comprises an opening of the top surface, wherein the bottom surface comprises an opening of the bottom surface, and wherein a longitudinal axis extends through the opening of the top surface and the opening of the bottom surface;

a glucose sensor; and

sensor electronics disposed within the housing and coupled with the glucose sensor; and

(b) an inserter, comprising:

a proximal end, a distal end, and an interior; and

a sharp,

wherein the on-body unit and the sharp are entirely disposed in the interior of the inserter,

wherein at least a portion of the glucose sensor is disposed in the sharp,

wherein the sharp extends through the opening of the top surface and the opening of the bottom surface along the longitudinal axis when the on-body unit is in a first position,

wherein the inserter is configured to advance the on-body unit and the sharp in a linear direction from the first position to a second position such that the sharp pierces skin of a user and the housing of the on-body unit is secured to the skin of the user in the second position,

wherein the distal end of the inserter is configured to be positioned on the skin of the user before advancement of the on-body unit and the sharp, wherein the inserter is further configured to automatically retract the sharp from within the user and entirely into the interior of the inserter and leave a part of the glucose sensor in the skin of the user, and

wherein the distal end of the inserter is further configured to be removed from the skin of the user after automatic retraction of the sharp from within the user.

2. The insertion assembly of claim 1, further comprising an adhesive portion configured to secure the housing to the skin of the user, wherein the adhesive portion is further configured to extend outwardly beyond the bottom surface of the housing along the skin in all directions when the housing is secured to the skin of the user.

3. The insertion assembly of claim 2, wherein a distance between the housing when the on-body unit is in the first position and the housing when the on-body unit is in the second position is greater than a maximum height of the housing.

4. The insertion assembly of claim 3, wherein the sensor electronics comprise a processor, a power source, an analog interface, a data storage unit, and wireless communication circuitry configured to communicate data indicative of a glucose level.

5. The insertion assembly of claim 3, wherein the sharp is configured to pierce the skin of the user at an angle substantially perpendicular to the skin of the user.

6. The insertion assembly of claim 3, wherein the on-body unit further comprises a side wall of the housing, wherein

24

the side wall is located between the top surface and the bottom surface, wherein the side wall comprises a first portion and a second portion, and wherein the second portion of the side wall defines a non-orthogonal angle relative to both the first portion of the side wall and the top surface of the housing.

7. The insertion assembly of claim 3, wherein the sensor electronics are in a sleep mode or an idle mode when the on-body unit is in the first position.

8. The insertion assembly of claim 3, wherein the sensor electronics are configured to be activated when the on-body unit is at or near the second position.

9. The insertion assembly of claim 3, wherein the sensor electronics further comprise an opening of the sensor electronics along the longitudinal axis, and wherein the sharp extends through the opening of the sensor electronics when the on-body unit is in the first position.

10. The insertion assembly of claim 3, wherein the inserter further comprises an inserter base, and wherein the proximal end of the inserter is configured to move in a downward direction toward the skin of the user relative to the inserter base in response to an application of force on the proximal end of the inserter.

11. The insertion assembly of claim 10, wherein the inserter is configured to advance the on-body unit and the sharp from the first position to the second position after the application of force on the proximal end of the inserter.

12. The insertion assembly of claim 3, further comprising a cap removably attached to a distal portion of the inserter by a plurality of threads, and wherein the cap comprises an interior space comprising a sterile environment.

13. The insertion assembly of claim 12, wherein the cap further comprises a plurality of vertically extending grooves spaced apart around an outer perimeter surface of the cap.

14. The insertion assembly of claim 3, wherein a height profile of the housing is less than or equal to approximately 10 millimeters.

15. The insertion assembly of claim 3, further comprising a sensor hub,

wherein the glucose sensor comprises a distal sensor portion and a proximal sensor portion,

wherein the distal sensor portion is configured to sense a glucose level of the user,

wherein the proximal sensor portion is engaged with the sensor hub, and

wherein the distal sensor portion is substantially orthogonal to the proximal sensor portion.

16. The insertion assembly of claim 3, wherein the distal end of the inserter defines a plane, and wherein the bottom surface of the housing is parallel to the plane when the on-body unit is in the first position.

17. The insertion assembly of claim 3, wherein the on-body unit is configured to be disposed after a single use.

18. The insertion assembly of claim 2, wherein the opening of the top surface is a first opening of the top surface, wherein the top surface further comprises a second opening of the top surface, wherein the first opening of the top surface has a first maximum width, and wherein the second opening of the top surface has a second maximum width less than the first maximum width.

19. An insertion assembly, comprising:

(a) an on-body unit, comprising:

a housing comprising a top surface and a bottom surface, wherein the top surface comprises an opening of the top surface, wherein the bottom surface comprises an opening of the bottom surface, and

25

wherein a longitudinal axis extends through the opening of the top surface and the opening of the bottom surface;

a glucose sensor; and

sensor electronics disposed within the housing and coupled with the glucose sensor, wherein the sensor electronics comprise a processor, a power source, an analog interface, a data storage unit, and wireless communication circuitry configured to communicate data indicative of a glucose level; and

(b) an inserter, comprising:

a proximal end, a distal end, and an interior; and a sharp;

wherein the on-body unit and the sharp are entirely disposed in the interior of the inserter,

wherein at least a portion of the glucose sensor is disposed in the sharp,

wherein the inserter is configured to advance the on-body unit and the sharp in a linear direction from a first position to a second position such that the sharp pierces skin of a user and the housing of the on-body unit is secured to the skin of the user in the second position,

wherein a distance between the housing when the on-body unit is in the first position and the housing when the on-body unit is in the second position is greater than a maximum height of the housing,

wherein a height profile of the housing is less than or equal to approximately 10 millimeters,

wherein the sharp is configured to pierce the skin of the user at an angle substantially perpendicular to the skin of the user,

wherein the sharp extends through the opening of the top surface and the opening of the bottom surface along the longitudinal axis when the on-body unit is in the first position,

wherein the distal end of the inserter is configured to be positioned on the skin of the user before advancement of the on-body unit and the sharp,

wherein the inserter is further configured to automatically retract the sharp from within the user and entirely into the interior of the inserter and leave a part of the glucose sensor in the skin of the user, and

wherein the distal end of the inserter is further configured to be removed from the skin of the user after automatic retraction of the sharp from within the user.

20. The insertion assembly of claim 19, further comprising an adhesive portion configured to secure the housing to the skin of the user, wherein the adhesive portion is configured to extend outwardly beyond the bottom surface of the housing along the skin in all directions when the housing is secured to the skin of the user.

21. The insertion assembly of claim 20, wherein the opening of the top surface is a first opening of the top

26

surface, wherein the top surface further comprises a second opening of the top surface, wherein the first opening of the top surface has a first maximum width, and wherein the second opening of the top surface has a second maximum width less than the first maximum width.

22. The insertion assembly of claim 21, wherein the sensor electronics further comprise an opening of the sensor electronics along the longitudinal axis, and wherein the sharp extends through the opening of the sensor electronics when the on-body unit is in the first position.

23. The insertion assembly of claim 22, wherein the distal end of the inserter defines a plane, and wherein the bottom surface of the housing is parallel to the plane when the on-body unit is in the first position.

24. The insertion assembly of claim 23, wherein the inserter further comprises an inserter base, wherein the proximal end of the inserter is configured to move in a downward direction toward the skin of the user relative to the inserter base in response to an application of force on the proximal end of the inserter, and wherein the inserter is configured to advance the on-body unit and the sharp from the first position to the second position after the application of force on the proximal end of the inserter.

25. The insertion assembly of claim 23, wherein the sensor electronics are in a sleep mode or an idle mode when the on-body unit is in the first position.

26. The insertion assembly of claim 23, wherein the sensor electronics are configured to be activated when the on-body unit is at or near the second position.

27. The insertion assembly of claim 23, wherein the on-body unit further comprises a side wall of the housing, wherein the side wall is located between the top surface and the bottom surface, wherein the side wall comprises a first portion and a second portion, and wherein the second portion of the side wall defines a non-orthogonal angle relative to both the first portion of the side wall and the top surface of the housing.

28. The insertion assembly of claim 23, further comprising a sensor hub,

wherein the glucose sensor comprises a distal sensor portion and a proximal sensor portion,

wherein the distal sensor portion is configured to sense a glucose level of the user,

wherein the proximal sensor portion is engaged with the sensor hub, and

wherein the distal sensor portion is substantially orthogonal to the proximal sensor portion.

29. The insertion assembly of claim 23, further comprising a cap removably attached to a distal portion of the inserter by a plurality of threads, and wherein the cap comprises an interior space comprising a sterile environment.

30. The insertion assembly of claim 29, wherein the cap further comprises a plurality of vertically extending grooves spaced apart around an outer perimeter surface of the cap.

* * * * *