

US009763716B2

(12) United States Patent Terrill et al.

(54) BONE PLATE WITH A TRANSFIXATION SCREW HOLE

- (71) Applicant: OsteoMed LLC, Addison, TX (US)
- (72) Inventors: Lance Nathan Terrill, Dallas, TX (US); Bruce R. Werber, Scottsdale, AZ (US)
- (73) Assignee: OsteoMed LLC, Addison, TX (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

- (21) Appl. No.: 15/147,828
- (22) Filed: May 5, 2016

(65) Prior Publication Data

US 2016/0242830 A1 Aug. 25, 2016

Related U.S. Application Data

- (63) Continuation of application No. 14/015,900, filed on Aug. 30, 2013, now Pat. No. 9,351,776, which is a (Continued)
- (51) Int. Cl.

A61B 17/80	(2006.01)
A61B 17/88	(2006.01)
A61B 17/84	(2006.01)

- (52) U.S. Cl.
 - CPC A61B 17/8057 (2013.01); A61B 17/8061 (2013.01); A61B 17/88 (2013.01); (Continued)
- (58) Field of Classification Search CPC A61B 17/80; A61B 17/861 See application file for complete search history.

(10) Patent No.: US 9,763,716 B2 (45) Date of Patent: *Sep. 19, 2017

(56) **References Cited**

U.S	. PATENT	DOCUMENTS

1,025,008 A	4/1912 Miner
1,105,105 A	7/1914 Sherman
	(Continued)

FOREIGN PATENT DOCUMENTS

EP	1468655 A2	10/2004
EP	1897509 A1	9/2007
	(Cont	inued)

OTHER PUBLICATIONS

PCT Invitation to Pay Additional Fees and, Where Applicable, Protest Fee; International Application No. PCT/US2010/031328, International Filing Date Apr. 16, 2010. (Continued)

Primary Examiner — Nicholas Woodall

(74) Attorney, Agent, or Firm - Norton Rose Fulbright US LLP

(57) ABSTRACT

A system for securing bones together across a joint includes a transfixation screw and a plate. The plate includes an elongate spine having a transfixation screw hole disposed along the spine. The transfixation screw hole includes an inner surface configured to direct the transfixation screw through the transfixation screw hole such that the transfixation screw extends alongside the bridge portion at a trajectory configured to pass through a first position on the first bone and a second position on the second bone once the plate is placed across the joint. The transfixation screw includes a head configured to abut the inner surface of the transfixation screw hole and a shaft configured to contiguously extend through the first bone, across the joint, and into the second bone.

21 Claims, 3 Drawing Sheets



Related U.S. Application Data

continuation of application No. $12/431,\!017,\,filed$ on Apr. 28, 2009, now Pat. No. $8,\!529,\!608.$

- (52) U.S. Cl.

(56) References Cited

U.S. PATENT DOCUMENTS

1,869,726	Α	8/1932	Youngren
2.133.859	A	10/1938	Hawley
2.398.915	Α	4/1946	Bell
2.443.363	Α	6/1948	Townsend et al.
2,489,870	Ā	11/1949	Dzus
2.501.978	A	3/1950	Wichman
2 561 550	A	7/1951	Wright
2 737 835	Δ	3/1956	Herz
3 463 148	Δ	8/1969	Treace
3 534 731	<u>A</u>	10/1070	Muller
3 552 380	7	1/1071	Allower et al
3 503 700	<u>л</u>	7/1071	Halloran
3,393,709	A .	6/1072	Allgower et al
2,605,250	A	10/1072	Aligower et al.
3,093,239	A	2/1072	10st Laborata a
3,710,030	A	2/19/3	Jonnston Markalf at al
3,741,203	A	12/1072	Markon et al.
3,779,240	A	12/19/3	Kondo
3,807,394	A	4/19/4	Attenborougn
4,219,015	A	8/1980	Steinemann
4,338,921	A	7/1982	Harder et al.
4,338,926	A	7/1982	Kummer et al.
4,364,382	A	12/1982	Mennen
4,408,601	А	10/1983	Wenk
4,484,570	Α	11/1984	Sutter et al.
4,488,543	Α	12/1984	Tornier
4,493,317	Α	1/1985	Klaue
4,503,848	Α	3/1985	Caspar et al.
4,513,744	Α	4/1985	Klaue
4,565,193	Α	1/1986	Streli
4,573,458	Α	3/1986	Lower
4,651,724	Α	3/1987	Berentey et al.
4,683,878	Α	8/1987	Carter
4,794,918	Α	1/1989	Wolter
4,800,874	Α	1/1989	David et al.
4,838,252	Α	6/1989	Klaue
4.867.144	Α	9/1989	Karas et al.
4.955.886	Α	9/1990	Pawluk
4.959.065	A	9/1990	Arnett et al.
5.002.544	A	3/1991	Klaue et al.
5.006.120	A	4/1991	Carter
5.015.249	Ā	5/1991	Nakao et al.
5.021.056	Â	6/1991	Hoffmann et al.
5 041 113	Ā	8/1991	Biedermann et al
5 0 53 0 36	Δ	10/1991	Perren et al
5,053,030	Δ	10/1001	Hofmann et al
5,057,111	Δ	10/1991	Park
5.085.660	<u>A</u>	2/1002	Lin
5,085,000	<u>^</u>	7/1002	Lubr at al
5,129,903	A	0/1002	Tapic et al
5,100,544	A .	2/1002	Chapman at al
5,190,344	A	3/1993	Chapman et al.
5,254,451	A	0/1993	Kener Maat
5,209,784	A	12/1993	Niast
5,304,180	A	4/1994	Slocum
5,330,535	A	7/1994	Moser et al.
5,344,421	A	9/1994	Crook
5,380,327	A	1/1995	Eggers et al.
5,387,102	A	2/1995	wagner et al.
5,443,467	A	8/1995	Biedermann et al.
5,474,553	A	12/1995	Baumgart
5,486,176	А	1/1996	Hildebrand et al.
5,487,741	A	1/1996	Maruyama et al.
5,501,684	А	3/1996	Schlapfer et al.
5,531,746	А	7/1996	Errico et al.
5,549,612	А	8/1996	Yapp et al.

5,578,034 A	. 11/1996	Estes
5,591,166 A	. 1/1997	Bernhardt et al.
5,601,553 A	. 2/1997 2/1997	Aust et al
5.607.426 A	3/1997	Ralph et al.
5,607,428 A	3/1997	Lin
5,620,448 A	4/1997	Puddu
5,643,265 A	. 7/1997	Errico et al.
5,662,655 A	. 9/1997	Laboureau et al.
5 676 667 A	10/1997	Hausman
5,681,311 A	10/1997	Foley et al.
5,709,686 A	1/1998	Talos et al.
5,725,588 A	3/1998	Errico et al.
5,733,287 A	. 3/1998	Tepic et al.
5,735,853 A	. 4/1998 //1008	Olerud Klaue et al
5.746.742 A	5/1998	Runciman et al.
5,749,872 A	5/1998	Kyle et al.
5,749,875 A	5/1998	Puddu
5,810,823 A	. 9/1998	Klaue et al.
5,931,838 A	. 8/1999	Vito Win quiet et al
5,958,004 A	0/1999	Fiz
5.954.722 A	9/1999	Bono
5,964,762 A	10/1999	Biedermann et al.
6,001,099 A	. 12/1999	Huebner
6,093,188 A	7/2000	Murray
6,117,173 A	. 9/2000	Taddia et al.
6 1 5 2 9 2 7 A	11/2000	Farris et al
6.183.475 B	1 2/2001	Lester et al.
6,193,721 B	1 2/2001	Michelson
6,206,881 B	1 3/2001	Frigg et al.
6,224,602 B	1 5/2001	Hayes
6,228,085 B	1 5/2001	Theken et al.
6 235 033 B	1 5/2001	Brace et al
6.235.034 B	1 5/2001	Brav
6,241,731 B	1 6/2001	Fiz
6,261,291 B	1 7/2001	Talaber et al.
6,302,883 B	1 10/2001	Bono
6,309,393 B	1 10/2001	Morrison et al
6.322.562 B	1 11/2001	Wolfer
6,342,055 B	1 1/2002	Eisermann et al.
6,348,052 B	1 2/2002	Sammarco
6,383,186 B	1 5/2002	Michelson
6,413,259 B	1 7/2002	Lyons et al.
6,454,770 B	1 9/2002 2 1/2003	Riaue
6.527.776 B	1 3/2003	Michelson
6,533,789 B	1 3/2003	Hall, IV et al.
6,575,975 B	2 6/2003	Brace et al.
6,595,993 B	2 7/2003	Donno et al.
6,602,255 B	1 8/2003	Campbell et al.
0,023,480 B	1 9/2005	Wessen at al
6 682 531 B	2 12/2003	Weaver et al.
	2 12/2003 2 1/2004	Weaver et al. Steiner et al. Winquist et al.
6,695,846 B	2 12/2003 2 1/2004 2 2/2004	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al.
6,695,846 B 6,719,759 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al.
6,695,846 B 6,719,759 B 6,755,832 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 1/2004	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Paul et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,821,278 B 6,821,278 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 11/2004 2 5/2005	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Paul et al. Frigg et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,821,278 B 6,890,334 B 6,945,973 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 11/2004 2 5/2005 2 9/2005	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Frigg et al. Brace et al. Brav
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,821,278 B 6,890,334 B 6,945,973 B 7,001,389 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 11/2004 2 5/2005 2 9/2005 1 2/2006	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Frigg et al. Brace et al. Bray Navarro et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,821,278 B 6,800,334 B 6,945,973 B 7,001,389 B 7,128,744 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 11/2004 2 5/2005 2 9/2005 1 2/2006 2 10/2006	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Paul et al. Brage et al. Brace et al. Bray Navarro et al. Weaver et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,821,278 B 6,890,334 B 6,945,973 B 7,001,389 B 7,128,744 B 7,175,624 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 2 6/2004 2 11/2004 2 5/2005 2 9/2005 2 9/2005 2 9/2005 2 10/2006 2 10/2006	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Paul et al. Braue et al. Brace et al. Bray Navarro et al. Weaver et al. Konieczynski et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,821,278 B 6,890,334 B 6,945,973 B 7,001,389 B 7,128,744 B 7,175,624 B 7,179,260 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 11/2004 2 11/2004 2 5/2005 2 9/2005 1 2/2005 2 10/2006 2 2/2007 2 2/2007	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Happonen et al. Paul et al. Frigg et al. Brace et al. Bray Navarro et al. Weaver et al. Konieczynski et al. Gerlach et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,890,334 B 6,890,334 B 7,001,389 B 7,128,744 B 7,175,624 B 7,175,624 B 7,175,624 B 7,179,260 B 7,273,481 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 2 6/2004 2 11/2004 2 11/2004 2 11/2004 2 12/2005 2 9/2005 2 9/2005 2 2/2007 2 2/2007 2 2/2007 2 9/2007	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Happonen et al. Paul et al. Frigg et al. Brace et al. Bray Navarro et al. Weaver et al. Gerlach et al. Lombardo et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,821,278 B 6,890,334 B 7,001,389 B 7,128,744 B 7,175,624 B 7,179,260 B 7,273,481 B 7,288,095 7 300 340 P	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 2 6/2004 2 11/2004 2 5/2005 2 9/2005 1 2/2006 2 10/2006 2 2/2007 2 2/2007 2 9/2007 2 10/2007	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Happonen et al. Paul et al. Frigg et al. Brace et al. Bray Navarro et al. Konieczynski et al. Gerlach et al. Lombardo et al. Baynham et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,821,278 B 6,890,334 B 7,001,389 B 7,102,8748 B 7,175,624 B 7,175,624 B 7,273,481 B 7,288,095 B 7,309,340 B 7,311,712 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 11/2004 2 5/2005 1 2/2005 1 2/2006 2 2/2007 2 2/2007 2 9/2007 2 12/2007 2 12/2007	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Happonen et al. Paul et al. Frigg et al. Bray Navarro et al. Weaver et al. Konieczynski et al. Gerlach et al. Lombardo et al. Baynham et al. Fallin et al. Dalton
6,695,846 B 6,719,759 B 6,755,833 B 6,821,278 B 6,890,334 B 6,890,334 B 7,001,389 B 7,102,8744 B 7,175,624 B 7,175,624 B 7,179,660 B 7,273,481 B 7,288,095 B 7,309,340 B 7,311,712 B 7,311,961 B	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 5/2005 1 2/2005 1 2/2007 2 2/2007 2 9/2007 2 10/2007 2 12/2007 2 12/2007 2 12/2007 2 2/2007 2 12/2007	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Praul et al. Frigg et al. Bray Navarro et al. Weaver et al. Konieczynski et al. Gerlach et al. Lombardo et al. Baynham et al. Fallin et al. Dalton Abdou
6,695,846 B 6,719,759 B 6,755,833 B 6,821,278 B 6,890,334 B 6,459,73 B 7,001,389 B 7,128,744 B 7,175,624 B 7,175,624 B 7,179,260 B 7,273,481 B 7,288,095 B 7,309,340 B 7,311,712 B 7,311,712 B 7,331,961 B 2001/0037112 A	2 12/2003 2 1/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 11/2004 2 5/2005 2 9/2005 1 2/2006 2 10/2006 2 2/2007 2 9/2007 2 9/2007 2 10/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 1 11/2001	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Prigg et al. Brace et al. Bray Navarro et al. Weaver et al. Konieczynski et al. Gerlach et al. Lombardo et al. Baynham et al. Fallin et al. Dalton Abdou Brace et al.
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,821,278 B 6,890,334 B 7,001,389 B 7,001,389 B 7,128,744 B 7,175,624 B 7,175,624 B 7,273,481 B 7,273,481 B 7,288,095 B 7,309,340 B 7,311,712 B 7,311,961 B 2001/0037112 A 2002/0082606 A	2 12/2003 2 1/2004 2 2/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 1 6/2005 2 9/2005 1 2/2006 2 10/2006 2 2/2007 2 9/2007 2 9/2007 2 10/2007 2 12/2007 2 12/2007 2 2/2008 1 11/2001 1 11/2001 1 6/2002	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Paul et al. Frigg et al. Brace et al. Bray Navarro et al. Weaver et al. Konieczynski et al. Gerlach et al. Lombardo et al. Baynham et al. Fallin et al. Dalton Abdou Brace et al. Suddaby
6,695,846 B 6,719,759 B 6,755,832 B 6,755,833 B 6,821,278 B 6,890,334 B 7,001,389 B 7,001,389 B 7,128,744 B 7,175,624 B 7,175,624 B 7,175,624 B 7,273,481 B 7,288,095 B 7,309,340 B 7,311,712 B 7,311,712 B 2001/0037112 A 2002/0082606 A 2003/0040749 A	2 12/2003 2 1/2004 2 2/2004 2 2/2004 2 4/2004 2 6/2004 1 6/2004 2 1/2004 2 5/2005 2 9/2005 1 2/2006 2 10/2006 2 2/2007 2 9/2007 2 10/2007 2 10/2007 2 10/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 2 12/2007 3 1/2/2017 3 1/2/2017 4 1/2/2017 4 1/2/2003	Weaver et al. Steiner et al. Winquist et al. Richelsoph et al. Wagner et al. Happonen et al. Paul et al. Brace et al. Bray Navarro et al. Weaver et al. Konieczynski et al. Gerlach et al. Lombardo et al. Baynham et al. Fallin et al. Dalton Abdou Brace et al. Suddaby Grabowski et al.

STRYKER Exhibit 1001 Page 2 of 14 IPR2022-00191

(56) References Cited

U.S. PATENT DOCUMENTS

2003/0187440	A1	10/2003	Richelsoph et al.
2003/0187442	A1	10/2003	Richelsoph et al.
2003/0199876	A1	10/2003	Brace et al.
2004/0015169	A1	1/2004	Gause
2004/0034354	A1	2/2004	Paul
2004/0059334	A1	3/2004	Weaver et al.
2004/0059335	A1	3/2004	Weaver et al.
2004/0087951	A1	5/2004	Khalili
2004/0127901	A1	7/2004	Huebner et al.
2005/0010226	A1	1/2005	Grady et al.
2005/0065521	A1	3/2005	Steger et al.
2005/0070904	A1	3/2005	Gerlach et al.
2005/0080421	A1	4/2005	Weaver et al.
2005/0131413	A1	6/2005	O'Driscoll et al.
2005/0234455	A1	10/2005	Binder et al.
2006/0015102	A1	1/2006	Toullec et al.
2006/0036249	A1	2/2006	Baynham et al.
2006/0173459	A1	8/2006	Kay et al.
2006/0235396	A1	10/2006	Sanders et al.
2006/0235397	A1	10/2006	Sanders et al.
2006/0241592	A1	10/2006	Myerson et al.
2006/0241607	A1	10/2006	Myerson et al.
2006/0241608	A1	10/2006	Myerson et al.

2007/0055253	A1	3/2007	Orbay et al.
2007/0088360	A1	4/2007	Orbay et al.
2007/0123880	A1	5/2007	Medoff
2007/0162020	A1	7/2007	Gerlach et al.
2007/0233115	A1	10/2007	Sixto et al.
2007/0239163	A1	10/2007	Strnad et al.
2007/0260244	A1	11/2007	Wolter
2007/0276383	A1	11/2007	Rayhack
2007/0276386	A1	11/2007	Gerlach et al.
2008/0015591	A1	1/2008	Castaneda et al.
2008/0015592	A1	1/2008	Long et al.

FOREIGN PATENT DOCUMENTS

JP	2007-500069 A	A 1/2007
WO	WO-2007/131287 A	1 11/2007

OTHER PUBLICATIONS

PCT Notification of Transmittal of the International Search Report and the Written Opinion of the International Searching Authority, or the Declaration; International Application No. PCT/US2010/ 031328; International Filing Date: Apr. 16, 2010.

Office Action issued for Japanese Patent Application No. 2012-508524, dated Dec. 3, 2013, 10 pages with English language translation.



STRYKER Exhibit 1001 Page 4 of 14 IPR2022-00191



STRYKER Exhibit 1001 Page 5 of 14 IPR2022-00191



FIG. 4

BONE PLATE WITH A TRANSFIXATION SCREW HOLE

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of co-pending, commonly assigned, patent application Ser. No. 14/015,900 entitled "BONE PLATE WITH A TRANSFIXATION SCREW HOLE," filed Aug. 30, 2013, which is a continuation of patent application Ser. No. 12/431,017 entitled "BONE PLATE WITH A TRANSFIXATION SCREW HOLE," filed Apr. 28, 2009, the disclosures of which are hereby incorporated herein by reference in their entirety.

TECHNICAL FIELD

The present disclosure relates to a device for securing bones together, and more particularly, to a bone plate with a transfixation screw hole.

BACKGROUND OF THE INVENTION

When performing certain medical procedures, such as reconstructing a joint that has been damaged due to bone or ²⁵ soft tissue trauma, a surgeon may need to fuse the bones of the joint together in a configuration that approximates the natural geometry of the joint. One way to achieve this objective is to attach the bones of the joint to a plate that holds the bones in alignment with one another while they ³⁰ fuse together.

BRIEF SUMMARY OF THE INVENTION

The present disclosure relates generally to orthopedic 35 devices. More specifically, the present disclosure relates to a bone plate with a transfixation screw hole for securing the bones of a joint together and a method for using the same.

In particular embodiments, a system for securing bones together across a joint includes a transfixation screw and a 40 plate. The plate includes an elongate spine having a first end that includes at least one attachment point for attaching the first end to a first bone on a first side of a joint, a second end that includes at least one attachment point for attaching the second end to a second bone on a second side of the joint. 45 and a bridge portion disposed between the first end and the second end configured to span across the joint. The plate further includes a transfixation screw hole disposed along the spine. The transfixation screw hole includes an inner surface configured to direct the transfixation screw through 50 the transfixation screw hole such that the transfixation screw extends alongside the bridge portion at a trajectory configured to pass through a first position on the first bone and a second position on the second bone once the plate is placed across the joint. The transfixation screw comprises a head 55 configured to abut the inner surface of the transfixation screw hole and a shaft configured to contiguously extend through the first bone, across the joint, and into the second bone.

Depending upon design, a central axis of the inner surface 60 of the transfixation screw hole may define the trajectory, and the trajectory may be configured to cross a neutral bending axis of the joint once the plate is placed across the joint.

In particular embodiments, a plate for securing bones together may include an elongate spine having a first end 65 that includes at least one attachment point for attaching the first end to a first bone on a first side of a joint, a second end 2

that includes at least one attachment point for attaching the second end to a second bone on a second side of the joint, and a bridge portion disposed between the first end and the second end configured to span across the joint. The plate may further include a transfixation screw hole disposed along the spine. The transfixation screw hole includes an inner surface configured to direct a transfixation screw through the transfixation screw hole such that the transfixation screw extends alongside the bridge portion at a trajectory configured to pass through a first position on the first bone and a second position on the second bone once the plate is placed across the joint.

In particular embodiments, a method for securing bones together across a joint includes placing a plate over a first bone on a first side of a joint and a second bone on a second side of the joint. The plate may include an elongate spine having a first end that includes at least one attachment point for attaching the first end to the first bone, a second end that includes at least one attachment point for attaching the second end to the second bone, and a bridge portion disposed between the first end and the second end configured to span across the joint. The plate may further include a transfixation screw hole disposed along the spine. The transfixation screw hole includes an inner surface configured to direct the transfixation screw through the transfixation screw hole such that the transfixation screw extends alongside the bridge portion at a trajectory configured to pass through a first position on the first bone and a second position on the second bone once the plate is placed across the joint. The method may further include attaching the plate to the first bone and the second bone, and inserting a transfixation screw into the first bone and the second bone through the transfixation screw hole. The transfixation screw may include a head configured to abut the inner surface of the transfixation screw hole and a shaft configured to contiguously extend through the first bone, across the joint, and into the second bone.

Particular embodiments of the present disclosure may provide a number of technical advantages, including for example, the ability to tightly couple the bones of a joint together by inserting a transfixation screw across the joint through a bone plate. In particular embodiments, the transfixation screw may have a "lag effect" that enables the bones of the joint to be approximated with one another by rotation of the transfixation screw. For example, the transfixation screw may include an unthreaded portion configured to rotate freely within the first bone and a threaded portion configured to threadably engage the second bone. When the transfixation screw is rotated, the unthreaded portion of the transfixation screw may rotate freely within the first bone while the threaded portion of the transfixation screw advances into the second bone, drawing the second bone toward the first bone and compressing the joint. These technical advantages (e.g., the presence of the transfixation screw across the joint, and the lag effect of the transfixation screw) may increase the contact pressure on the bony interface of the joint, increasing the probability of a positive fusion.

Depending upon design, the inner surface of the transfixation screw hole in the plate may direct the transfixation screw along a trajectory that crosses a neutral bending axis of the joint as the transfixation screw passes from the first bone to the second bone. This technical advantage may create a "tension band" construct that enables the transfixation screw to absorb a portion of the mechanical stress that would otherwise be imposed upon the plate above the joint when a load is applied to the joint. This technical advantage

> STRYKER Exhibit 1001 Page 7 of 14 IPR2022-00191

15

30

may enhance the integrity and reliability of the plate and increase the load that the plate may support without increasing plate thickness. Other technical advantages of the present disclosure will be readily apparent to one skilled in the art from the following figures, descriptions, and claims. 5 Moreover, while specific advantages have been enumerated above, various embodiments may include all, some, or none of the enumerated advantages.

BRIEF DESCRIPTION OF THE DRAWINGS

For a more complete understanding of the present disclosure and its advantages, reference is now made to the following descriptions, taken in conjunction with the accompanying drawings, in which:

FIG. 1 illustrates a failed metatarso-phalangeal joint in the big toe of a human foot;

FIG. 2 illustrates a bone plate being used in conjunction with a transfixation screw to repair the failed metatarsophalangeal joint of FIG. 1 according to an example embodi- 20 ment of the present disclosure;

FIG. 3 illustrates a more detailed isometric view of the bone plate of FIG. 2; and

FIG. 4 illustrates a bone plate adapted for use on a tarso-metatarsal joint according to an example embodiment 25 of the present disclosure.

DETAILED DESCRIPTION OF THE INVENTION

The metatarso-phalangeal joint is a joint between a metatarsal bone of the foot and the proximal phalanx of a toe. It is common, particularly in sports, for the first metatarsophalangeal joint (e.g., the metatarso-phalangeal joint of the big toe) to be injured as a result of trauma to or hyper extension 35 of the big toe. In other scenarios, degradation of the metatarsophalangeal joint may be caused by arthritis. Minor injuries to the metatarso-phalangeal joint, such as a sprain, may often be treated using conservative measures such as immobilization and icing of the toe, accompanied by rest 40 and anti-inflammatory medication. These measures may be followed by taping or splinting of the injured joint to help prevent recurrent hyperextensions of the toe.

In more severe cases involving major trauma to the bone or soft tissue of the metatarso-phalangeal joint, as illustrated 45 in FIGURE I, conservative measures may be ineffective, and surgery may be required. One procedure for reconstructing a severely damaged metatarso-phalangeal joint involves fusing the bones of the joint together using plates and/or screws. More particularly, a fusion procedure may involve 50 reducing the opposing faces of the bones of the joint to a bleeding bone bed, approximating the bones with one another, and screwing the bones together to promote fusion. In some cases, the bones may be screwed together without the use of a plate. However, this option may not provide 55 adequate lateral support for the bones, possibly allowing them to shift out of alignment, resulting in a malunion or a nonunion of the joint.

Another option for surgically repairing a severely damaged metatarso-phalangeal joint involves securing the bones 60 of the joint together using a plate. In this procedure, after the bones of the joint have been approximated next to one another, the plate may be laid across the joint. The plate may then be screwed to the bones of the joint to hold them in alignment next to one another, enabling the joint fuse. 65 However, when a load is placed upon the joint (e.g., when weight is placed upon the foot) it is possible for the plate to

bend or break above the joint. This may cause the bones of the joint to fall out of approximation, resulting in a nonunion (e.g., a failed fusion of the joint). Consequently, the ability to rigidly hold the bones of a joint in tight approximation without bending or breaking is one metric for judging the effectiveness of a joint-fixation plate.

One way to increase the durability and reliability of a joint-fixation plate is to include a transfixation screw hole in the plate that enables a transfixation screw to transfix the 10 joint through the plate. As explained in more detail below, once the transfixation screw is screwed across the joint, it may absorb some of the stress that would otherwise be exerted on the plate when a load is placed upon the joint. This may reduce the strain on the plate, increasing its reliability and durability. Additionally, while the plate may provide lateral support for the joint, the transfixation screw may hold the bones of the joint in tight approximation, increasing the likelihood of a positive fusion of the joint. This may be particularly important on the plantar side of the joint due to tensile stresses exerted on that side of the joint when loaded.

FIGS. 2-3 illustrate an example embodiment of a bone plate 100 that includes a transfixation screw hole 102 in accordance with the present disclosure. More particularly, FIG. 2 illustrates bone plate 100 being used in conjunction with a transfixation screw 150 to repair the failed metatarsophalangeal joint of FIGURE I. FIG. 3 illustrates a more detailed isometric view of bone plate 100. For reference purposes, bone plate 100 and its various features may be referred to as having a top surface intended to face away from the bones of joint 106 and a bottom surface intended to face toward the bones of joint 106 (e.g., to be placed upon the bones of joint 106). Though particular features of bone plate 100 may be explained using such intended placement as a point of reference, this method of explanation is not meant to limit the scope of the present disclosure to any particular configuration or orientation of bone plate 100.

As shown in FIG. 2, bone plate 100 is being used to reconstruct a failed joint 106 of a human foot. In particular, FIG. 2 illustrates transfixation screw 150 being inserted through bone plate 100 into a first bone 104a and a second bone 104b (collectively, bones 104) in order to fuse joint 106 (show collapsed in FIG. 1). Bone 104a refers to the bone positioned directly beneath transfixation screw hole 102 (e.g., touching the bottom surface of transfixation screw hole 102) while bone 104b refers to the bone positioned on the opposite side of joint 106. Although bone 104a is illustrated and described as the first metatarsal, bone 104b is illustrated and described as the first proximal phalanx, and joint 106 is illustrated and described as the metatarso-phalangeal joint 106 of the big toe, one of ordinary skill in the art will appreciate those specific examples are presented for the sake of explanatory clarification and will further appreciate that bones 104 and joint 106 may generically refer to any suitable set of bones forming any suitable joint in the body.

In a typical procedure, a surgeon may use bone plate 100 to fuse joint 106 according to the following example surgical procedure. To begin the procedure, the surgeon may create an incision over joint 106 to expose bones 104. After exposing bones 104, the surgeon may perform any prefusion steps such as removing cartilage from joint 106 and reducing the opposing faces of bones 104 to a bleeding bone bed. Following the pre-fusion steps, the surgeon may approximate bones 104 by positioning them next to one in a desired configuration for fusion. The surgeon may then secure bones 104 together by placing bone plate 100 across joint 106 such that transfixation screw hole 102 overlies

> STRYKER Exhibit 1001 Page 8 of 14 IPR2022-00191

bone 104a. The surgeon may screw bone plate 100 to bones 104, for example by inserting one or more bone screws 134 into one or more screw holes located on either end of bone plate 100, after which, the surgeon may create a path for transfixation screw 150. To create a path for transfixation 5 screw 150, the surgeon may drill a pilot hole into bones 104 through transfixation screw hole 102. In particular embodiments, the surgeon may use the central axis 116 of transfixation screw hole 102 as a guide to establish the trajectory for the pilot hole. Once the pilot hole has been created, 10 transfixation screw 150 may be inserted into the pilot hole through transfixation screw hole 102 and screwed into bones 104 until the head of transfixation screw 150 abuts the inner surface of transfixation screw hole 102. After bones 104 have been secured together using transfixation screw 150, 15 the surgeon may close the incision, leaving bones 104 to fuse together.

To facilitate the process of aligning bones **104**, bone plate **100** may include one or more joint-specific characteristics that may conform to the natural geometry of joint **106** or 20 bones **104**. For example, in the case of the metatarsophalangeal joint, bone plate **100** may include a rise (similar to rise **210** in FIG. **4**) that fits over the head on the dorsal section of metatarsal **104***a*. This may enable bone plate **100** to be seated firmly against the head of metatarsal **104***a* and 25 provide a natural footing for bone plate **100** against metatarsal **104***a*. In other embodiments, the rise may be eliminated from bone plate **100** and the dorsal head of metatarsal **104***a* may be ground down to enable bone plate **100** to be laid flush against bones **104**. 30

Depending upon design, bone plate 100 may further include a dorsiflexion angle (of approximately 10 degrees) between the first end 126b of the plate and the second end 126a of the plate that mimics the natural elevation of the first metatarsal 104a relative to the first proximal phalanx 104b. 35 The inclusion of a dorsiflexion angle between first end 126b and second end 126a may reduce the force on bone plate 100 during activities such as walking. Furthermore, bone plate 100 may include a valgus angle (of approximately 10 degrees) between the first end 126b of the plate and the 40 second end 126a of the plate that mimics the natural lateral alignment of the first metatarsal 104a relative to the first proximal phalanx 104b. The inclusion of a valgus angle in bone plate 100 may further help to reduce the force on bone plate 100 during activities such as walking. In particular 45 embodiments, to provide lateral support for joint 106, the ends of plate 100 may be may be curved around the medial side of bones 104. One of ordinary skill in the art will appreciate that above-described characteristics of bone plate 100 were described with respect to the metatarso-phalangeal 50 joint for the sake of explanatory simplicity and will further appreciate that particular embodiments of bone plate 100 may be adapted equally as well to approximate the natural geometry of virtually any joint 106 in the body without departing from the scope of the present disclosure.

As mentioned above, transfixation screw 150, once inserted across joint 106, may absorb a portion of the stress that would otherwise be exerted on the portion of bone plate 100 spanning across joint 106 when a load is placed upon joint 106. For example, in the case of the metatarso-phalangeal joint 106, activities that place weight on the foot, such as walking or standing, may cause metatarso-phalangeal joint 106 to flex. Due to the biomechanics of the foot, when the metatarso-phalangeal joint 106 flexes, the upper or "dorsal" side of joint 106 will compress together, while the 65 bottom or "plantar" side of joint 106 will draw apart under tension. This is generally true for any hinge-type joint. The 6

line about which the force on joint **106** transitions from tension to compression may be referred to as the neutral bending axis **118** of the joint **106**. In other words, neutral bending axis **118** defines the boundary line that separates the tension side of joint **106** from the compression side of joint **106**.

When transfixation screw 150 is screwed into joint 106 along a trajectory that crosses neutral bending axis 118 (as show in FIG. 2), a "tension band" construct is created that puts transfixation screw 150 under tension when joint 106 flexes. Normally, the plantar side of bone 104a (e.g., the portion of bone 104a on the tension side of joint 106) will draw away from the plantar side of bone 104b when a load is applied to joint 106. However, when transfixation screw 150 is screwed across joint 106 such that the head 152 of transfixation screw 150 abuts the inner surface of transfixation screw hole 102, the portion of transfixation screw 150 engaged with bone 104b will pull against the head 152 of transfixation screw 150 when a load is applied to joint 106. Since the head of transfixation screw 150 is braced against the inner surface of transfixation screw hole 102, it will absorb the tension forces transmitted up the shaft of transfixation screw 150, preventing the plantar side of bone 104bfrom drawing away from the plantar side of bone 104a.

In particular embodiments, the interface between bone 104a and transfixation screw 150 may provide another mechanism for absorbing the tension forces transmitted up the shaft of transfixation screw 150. For example, if transfixation screw 150 is threadably engaged with bone 104a, the threading on transfixation screw 150 may provide a footing against bone 104a which may also absorb a portion of the tension forces transmitted up the shaft of transfixation screw 150 from bone 104b when a load is applied to joint 106. In either case, once transfixation screw 150 has been screwed into joint 106 along a trajectory that crosses the neutral bending axis 118 of joint 106, a tension band construct may be created that enables transfixation screw 150 to absorb the tension forces that would otherwise draw the tension side of joint 106 apart when a load is placed on ioint 106.

In particular embodiments, transfixation screw hole 102 may be used to establish the trajectory for transfixation screw 150. For example, bone plate 100 may be configured such that, once bones 104 have been approximated and bone plate 100 has been placed across joint 106, the central axis 116 of transfixation screw hole 102 may align along a trajectory that crosses the neutral bending axis 118 of joint 106. For example, the central axis 116 of transfixation screw hole 102 may be configured to pass through joint 106 at a transfixation angle 114 of about 30 degrees to about 70 degrees relative to neutral bending axis 118 to achieve the desired tension band construct once bone plate 100 is secured across joint 106. In one example embodiment, central axis 116 may be configured to pass through joint 106 at a transfixation angle 114 of about 50 degrees. Consequently, by drilling a pilot hole along central axis 116, a surgeon may create a path for transfixation screw 150 that spans from a first position 120 on bone 104a located on the compression side of joint 106 to a second position 122 on bone 104b located on the tension side of joint 106, creating the desired tension band construct for transfixation screw 150. Alternatively. a surgeon may forgo drilling a pilot hole and may instead use a transfixation screw 150 having a self drilling feature. In that case, the surgeon could achieve a tension band construct by screwing the transfixation screw 150 directly into joint 106 along the trajectory of central axis 116

Transfixation screw 150 may be any component of hardware having a head 152 configured to abut the surface of bone plate 100 and a shaft 154 operable to secure bones 104 together in a fixed configuration. For example, transfixation screw 150 may be a nut and bolt assembly, a pin assembly, 5 or a bone screw. As another example and not by way of limitation, transfixation screw 150 may be a lag screw that includes a head 152 coupled to a shaft 154 having an unthreaded portion 156 and a threaded portion 158 that ends at a tip 156. Once transfixation screw 150 is screwed into 10 bones 104 through transfixation screw hole 102, this configuration of transfixation screw 150 may result in a lag effect that may tighten the interface between bones 104 when transfixation 150 is rotated. In particular embodiments, the length of shaft 154 may be less than the length of 15 the portion of central axis 116 that passes through bones 104 in order to keep tip 156 from protruding out of bone 104b (e.g., out of the plantar aspect of first proximal phalanx 104b) when transfixation screw 150 screwed into bones 104.

To achieve a lag effect, a surgeon, after affixing bone plate 20 100 across joint 106 and drilling a pilot hole for transfixation screw 150 as described above, may screw transfixation screw 150 into joint 106 until unthreaded portion 156 extends completely through bone 104a and threaded portion 158 threadably engages bone 104b. At this point, further 25 rotation of transfixation screw 150 may cause threaded portion 158 to advance further into bone 104b, causing bone 104b to ride up further onto shaft 154 and press against bone 104a while unthreaded portion 156 spins freely within bone 104a. Transfixation screw 150 may be further rotated under 30 these conditions until head 152 comes to bear on the inner surface of transfixation screw hole 102, cinching bone 104a between the bottom surface of bone plate 100 and bone 104b. This may create a tight interface between bones 104, increasing the chance of a positive fusion. In another 35 example procedure, a lag effect may be achieved by drilling a pilot hole in bone 104a that is larger in diameter than shaft 154. This may enable transfixation screw 150 to spin freely within bone 104a to achieve the desired lag effect, even if the entirety of shaft 154 is threaded.

FIG. 3 illustrates an external view of the top surface of bone plate 100. In particular embodiments, bone plate 100 may be characterized by a substantially thin construction that generally includes an elongate spine 124 having a first end 126*a* that includes at least one attachment point 128 for 45 attaching first end 126*a* to bone 104*a*, a second end 126*b* comprising at least one attachment point 128 for attaching second end 126*b* to bone 104*b*, and a bridge portion 130 disposed between ends 126 configured to span across joint 106. Bone plate 100 may further include a transfixation 50 screw hole 102, and a compression hole 132 which may be used to cinch bones 104 together using a bone screw 134.

Each attachment point **128** may be any mechanism or fixture operable to serve as a rigid point of attachment between bone plate **100** and a bone **104**. As one example and 55 not by way of limitation, an attachment point **128** may be an unthreaded screw hole in bone plate **100** configured to accept a bone screw **134**. As another example and not by way of limitation, an attachment point **128** may be a threaded screw hole that provides a locking interface 60 between bone screw **134** and bone plate **100**. To accomplish this locking interface, the underside of the head of screw **134** may include threads that interfere with the threading on the inside of the threaded screw hole to lock bone screw **134** into bone plate **100**. Consequently, once bone screw **134** is 65 screwed into bone **104** through the threaded screw hole, bone screw **134** may be prevented from loosening or back8

ing out of bone **104**. An example system for providing a locking interface between a screw hole and a screw is presented in U.S. Provisional Application No. 61/106,511, entitled, "Angulated Locking Plate/Screw Interface." In particular embodiments, the inner surface of transfixation screw hole **102** may also be threaded to provide a locking interface between transfixation screw **150** and bone plate **100**. In this case, the head of transfixation screw **150** may also be threaded.

As another example and not by way of limitation, an attachment point **128** may be any type of clip or clamp included on bone plate **100** operable to rigidly affix bone plate **100** to a bone. One of ordinary skill in the art will appreciate that the above-described embodiments of attachment points **128** were presented for the sake of explanatory clarification and will further appreciate that the present disclosure contemplates each attachment point **128** being any suitable mechanism or fixture operable to serve as a rigid point of attachment between bone plate **100** and bone **104**.

Spine 124 may generally define the central portion of bone plate 100 spanning along the length of bone plate 100. As an example and not by way of limitation, spine 124 may include a contiguous linear or curvilinear section of bone plate 100 spanning from the tip of first end 126a to the tip of second end 126b. As mentioned above, spine 124 includes a bridge portion 130 configured to span across joint 106. Since bridge portion 130 is configured to span across joint 106, it is typically defined by an unbroken section of spine 124 that is free of voids such as positioning holes or screw holes that could potentially reduce the bending strength of bridge portion 130. Depending upon design, bridge portion 130 may include a thickened section 136 of bone plate 100 to increase the bending strength of bridge portion 130. This may lessen the risk of bridge portion 130 bending or breaking above joint 106 when a load is applied to joint 106.

In particular embodiments, thickened section 136 may be defined by a thickened ridge of material in bone plate 100 having its greatest thickness along bridge portion 130 and gradually decreasing in thickness as one moves away from bridge portion 130 along the length of bone plate 100 toward ends 126. The increased material thickness may provide central section 130 with a higher section modulus than the proximal and distal areas of the plate located at ends 126. In a typical design, thickened section 136 may be about 100% to 200% thicker than the adjacent portions of bone plate 100. Including thickened section 136 in bone plate 100 may confer a number of advantages over plates of uniform thickness, one of which is the ability to efficiently increase the section modulus (and strength) of bridge portion 130 without adding material thickness to the entirety of bone plate 100.

Transfixation screw hole 102 may be defined by an inner surface of bone plate 100 surrounding a generally circular opening in bone plate 100. As an example and not by way of limitation, transfixation screw hole 102 may be disposed along the center line 138 of spine 124, immediately adjacent to bridge portion 130. In the case of a bone plate 100designed for use on the first metatarso-phalangeal joint, the placement of transfixation screw hole 102 adjacent to bridge portion 130 may enable transfixation screw 102 to penetrate the first metatarsal 104a on the dorsal aspect of the metatarsal head and pass into the plantar cortex of the first medial phalanx 104b, transfixing the metatarso-phalangeal joint 106.

In particular embodiments, the portion of bone plate 100 that includes transfixation screw hole 102 may be thicker

STRYKER Exhibit 1001 Page 10 of 14 IPR2022-00191 than other portions of bone plate 100. For example, transfixation screw hole 102 may be included in thickened section 136, adjacent to bridge portion 130. This may enable a countersink to be created around transfixation screw hole 102 so that the head 152 of transfixation screw 150 may rest flush with the top surface of bone plate 100 once transfixation screw 150 is screwed into transfixation screw hole 102. The increased plate thickness around transfixation screw hole 102 may also enable transfixation screw hole 102 to be machined into bone plate 100 at an angle relative to the top 10 surface of bone plate 100 (e.g., other than perpendicular to the top surface of bone plate 100).

As mentioned above, in particular embodiments, bone plate 100 may include a compression hole 132 for tightening bones 104 together using a bone screw 134. Compression hole 132 may be defined by an inner surface of bone plate 100 surrounding a generally oblong opening in bone plate 100. More particularly, the inner surface of compression hole 132 may have a narrow end 131a, and a wide end 131b that includes a horse-shoe-shaped countersink 133. To com- 20 press bones 104 together using compression hole 132, a surgeon may use the following example procedure. The surgeon may begin by attaching the second end 126b of bone plate 100 to bone 104b using the attachment points 128 located on end 126b. The surgeon may then manually 25 approximate bone 104a against bone 104b, placing bone 104a under compression hole 132. While holding bone 104a against the bottom surface of compression hole 132, either by hand or using a clamp, the surgeon may drill a pilot hole for bone screw 134 into bone 104a. The trajectory of the 30 pilot hole may be generally perpendicular to the top surface of bone plate 100 and be located approximately in the center of narrow end 131 a (e.g., located at the focus of narrow end 131a).

After creating the pilot hole, the surgeon may then screw 35 bone screw 134 into the pilot hole until the head of bone screw 134 comes into contact with countersink 133 near the tips 135 of countersink 133. To facilitate the compression feature, the underside of the head of bone screw 134 may be generally conical, having a taper angle approximately equal 40 to the taper angle of countersink 133. Once the head of bone screw 135 is in contact with counter sink 133 near tips 135, further rotation of bone screw 135 may cause the head of bone screw 134 to ride down into countersink 133, drawing bone plate 100 further up onto bone 104a and causing bones 45 104 to press together at the interface of joint 106. After approximating bones 104 by screwing bone screw 134 into compression hole 132 as just described, the surgeon may use other attachment points 128 to further secure bone plate 100 to bone 104a. The surgeon may also screw transfixation 50 screw 150 into joint 106 through transfixation screw hole 102 after tightening bones 104 together using compression hole 132. Depending upon design, compression hole 132 may be threaded to provide a locking interface for bone screw 134.

In particular embodiments, bone plate 100 may comprise one or more positioning holes 140 that may be used to position bone plate 100 relative to the bones 104 of joint 106. To position bone plate 100 using a positioning hole 140, a surgeon may insert a K-wire into one of the bones 104, 60 after which the surgeon may position bone plate 100 on bone 104 by inserting the K-wire through positioning hole 140 and sliding bone plate 100 down onto bone 104. Additionally, the surgeon may rotate bone plate 100 about the K-wire using positioning hole 140 to achieve a desired orientation 65 of bone plate 100 relative to bone 104. To ensure that bone plate 100 may be precisely positioned on bone 104 using a

K-wire, the diameter of positioning hole 140 may be approximately equal to the diameter of the K-wire. Once bone plate 100 has been properly positioned, the surgeon may secure bone plate 100 to bone 104, temporarily for example, by inserting another K-wire into another one of positioning holes 140, or more permanently, using attachment points 128.

In particular embodiments, the bottom surface of bone plate 100 may include one or more contact reduction features 146 which may reduce the amount of surface area of bone plate 100 that contacts bones 104 when bone plate 100 is secured across joint 106. As an example and not by way of limitation, the bottom surface of bone plate 100 may include one or more channels, notches, or other recessions which may reduce (e.g., minimize) the amount of bone plate 100 that contacts bones 104. This may lessen the amount of vascular impingement caused by bone plate 100, promoting blood flow to bones 104 and bone growth. In particular embodiments, each of the screw holes in bone plate 100 (e.g., attachment points 128, compression hole 132, or transfixation screw hole 102) may include a countersink capable of seating the head of a screw flush with the top surface of bone plate 100. This feature may provide several benefits such as lessening the chance of uncomfortable impingement on the surrounding soft tissue, and reducing patient palpation and visualization of bone plate 100.

In particular embodiments, bone plate 100 may further include flared hips 148 adjacent to transfixation screw hole 102. Flared hips may generally be defined by a widened section of bone plate 100. As an example and not by way of limitation, flared hips 148 may include two generally parabolic wings extending laterally from spine 124, symmetrically opposed to one another about transfixation screw hole 102. As will be appreciated by one of skill in the art, the entry point for transfixation screw 150 into bone 104a may be generally be located at the center of the bottom side of transfixation screw hole 102 when transfixation screw is inserted into transfixation screw hole 102 along central axis 116. Consequently, in embodiments where transfixation screw hole 102 is formed into bone plate 100 at an angle, the entry point for transfixation screw 150 may be out of sight (e.g., covered up by the top of transfixation screw hole 102) when bone plate 100 is viewed from above. Therefore, to help a surgeon precisely position the entry point for transfixation screw 150 onto a desired location on bone 104a, the entry point for transfixation screw 150 (e.g., the center of the bottom side of transfixation screw hole 102) may reside directly in between the widest portion of flared hips 148. Accordingly, by positioning the widest portion of hips 148 directly adjacent to the desired location for transfixation screw 150 on bone 104a, the surgeon may confidently position the entry point for transfixation screw 150 at the desired location, even when the entry point is out of sight. Flared hips 148 may also increase the strength of bone plate 100 around transfixation screw hole 102, lessening the chance of plate deformation or breakage.

Depending upon design, bone plate **100** may be formed from any material or combination of materials suitable for forming medical implants. Such materials may have high strength-to-weight ratios and may be inert to human body fluids. As an example and not by way of limitation, bone plate **100** may be formed from a forged titanium alloy. Titanium may provide several benefits as a material for bone plate **100** such as being relatively lightweight, providing adequate strength for withstanding forces typically experienced by a bone plate, and being visible in radiographs of the implant region.

> STRYKER Exhibit 1001 Page 11 of 14 IPR2022-00191

FIG. 4 illustrates an example embodiment of a bone plate 200 adapted for use in a Lapidus procedure where bone plate 200 may be secured across the first tarso-metatarsal (TMT) joint 206, located between the first metatarsal 204a and the first cuneiform 204b. Though bone plate 200 is adapted for 5 placement over the TMT joint, particular embodiments of bone plate 200 may include some or all of the features of bone plate 100 described above, appropriately adapted to conform to the TMT joint 206. For example, when used on TMT joint 206, transfixation screw hole 202 may be con- 10 figured to guide a transfixation screw 250 from the dorsal aspect of metatarsal 204a to the plantar aspect of first cuneiform 204b in order to transfix TMT joint 206. Likewise, bone plate 100 may include some or all of the features described with respect to bone plate 200, appropriately 15 adapted to conform to the MPJ joint 106. For reference purposes, like numbers may be used to refer to like features between bone plate 100 and bone plate 200.

Bone plate 200 may generally be "H-shaped", and include and it is an elongate spine 224 having a plurality of flanges 242 20 change extending laterally therefrom. Each flange 242 may further include one or more attachment points 228 (similar or identical to attachment points 128 described above) for attaching bone plate 200 to a bone 204. Flanges 242 may serve as a primary mechanism for attaching bone plate 200 zo to bones 204, although particular embodiments of bone plate 200 across a jo 200 may further include one or more additional attachment points 228 disposed along spine 224 for attaching bone plate 200.

Each flange 242 may be any type of rigid lateral extension 30 from spine 224. As an example and not by way of limitation, each flange 242 may be a rigid rounded tab extending laterally from the side of spine 224. Depending upon design, each flange 242 may be separated from the next by a gap 244, which may enable a surgeon to independently contour 35 each flange 242 to a desired position (e.g., to conform flanges 242 to match the geometry of bones 204). Furthermore, each flange 242 may be relatively thinner than spine 224 to reduce the mechanical force needed to contour flanges 242 up or down relative to spine 224. This thinning 40 of flanges 242 may confer a number of advantages over plates having uniform thickness, such as for example, providing a surgeon with the ability to easily contour flanges 242 to a desired position. In particular embodiments, flanges 242 may enable a surgeon to contour bone plate 200 such 45 that attachments points 242 are located on both the medial and dorsal aspects of bones 204. Once a flange 242 has been contoured to a desired position, it may be affixed to bone 204 using an attachment point 228

To facilitate the process of aligning bones 204, bone plate 50 200 may include one or more features which mimic the natural geometry of the TMT joint 206. For example, bone plate 200 may include a rise 210 of approximately 0 mm to 5 mm (e.g., 2 mm) that mimics the natural elevation of the first metatarsal 204*a* relative to the first cuneiform 204*b*. As 55 another example and not by way of limitation, bone plate 200 may include a varus angle of about 0 degrees to about 30 degrees (e.g., 15 degrees) between the first end 226*a* of the plate and the second end 226*b* of the plate that mimics the natural elevation of first metatarsal 204*a* relative to first 60 cuneiform 204*b*. In particular embodiments, bone plate 200 may be symmetric about center line 238 to enable bone plate 200 to be applied to either the left foot or the right foot, without substantial modification.

The particular embodiments disclosed above are illustra-65 tive only, as particular embodiments of the present disclosure may be modified and practiced in different but equiva-

lent manners apparent to those skilled in the art having the benefit of the teachings herein. Furthermore, no limitations are intended to the details of construction or design herein shown, other than as described in the claims below. It is therefore evident that the particular illustrative embodiments disclosed above may be altered or modified and all such variations are considered within the scope and spirit of the present disclosure. In particular, every range of values (e.g., "from about a to about b," or, equivalently, "from approximately a to b," or, equivalently, "from approxinately a to b," or, equivalently, "from approxinately a to b," or, equivalently, the patente.

Although the present disclosure has been described in several embodiments, a myriad of changes, substitutions, and modifications may be suggested to one skilled in the art, and it is intended that the present disclosure encompass such changes, substitutions, and modifications as fall within the scope of the present appended claims.

What is claimed is:

1. A system for securing two discrete bones together ross

- a joint between the two bones, comprising:
 - an elongate spine having:
 - a first end comprising:
 - at least one fixation point for attaching the first end to a first discrete bone on a first side of an intermediate joint; and
 - a first inner surface configured to substantially conform with a geometry of the first discrete bone;

a second end comprising:

- at least one fixation point for attaching the second end to a second discrete bone on a second side of the joint; and
- a second inner surface configured to substantially conform with a geometry of the second discrete bone; and
- a bridge portion disposed between the first end and the second end, at least a portion of said bridge portion having a depth greater than at least a portion of the depth of either the first end or the second end; and
- a transfixation screw hole disposed along the spine, the transfixation screw hole comprising an inner surface configured to direct the transfixation screw through the transfixation screw hole such that the transfixation screw extends the bridge portion at a trajectory configured to pass through a first position on the first discrete bone, a portion of the joint, and a second position on the second discrete bone; and
- a transfixation screw comprising a head configured to abut the inner surface of the transfixation screw hole and a shaft configured to contiguously extend through the first discrete bone, through the joint, and into the second discrete bone is loaded relative to the first discrete bone thereby transferring the tensile load from the second discrete bone, through the screw into said head and said bridge portion.
- **2**. The system of claim **1**, wherein:
- a central axis of the inner surface of the transfixation screw hole defines the trajectory; and

STRYKER Exhibit 1001 Page 12 of 14 IPR2022-00191 the trajectory is configured to cross a neutral bending axis of the joint.

3. The system of claim 2, wherein the first position resides on a compression side of the joint and the second position resides on a tension side of the joint.

4. The system of claim 2, wherein the trajectory is configured to pass through the joint at a transfixation angle between about 30 degrees and about 70 degrees measured from the neutral bending axis.

10 5. The system of claim 2, wherein the trajectory is configured to pass through the joint at a transfixation angle of about 50 degrees measured from the neutral bending axis.

6. The system of claim 1, wherein the inner surface of the transfixation screw hole is configured to lockably engage the head of the transfixation screw.

7. The system of claim 1, wherein the spine further includes a compression hole defined by an inner surface in the plate surrounding an oblong opening, the inner surface of the compression hole including, at one end, a horse-shoe- 20 an intermediate joint, comprising: shaped countersink.

8. The system of claim 1, wherein at least one attachment point comprises a threaded screw hole defined by a threaded inner surface configured to lockably engage one of a plu-25 rality of locking bone screws.

9. The system of claim 1, wherein the transfixation screw comprises a lag screw having:

at a first end of the shaft adjacent to the head, an unthreaded portion configured to extend through the 30 first bone: and

at a second end of the shaft adjacent to the tip, a threaded portion configured to extend into the second bone.

10. A plate for securing two discrete bones together across an intermediate joint, comprising: 35

an elongate spine having: a first end comprising:

- at least one fixation point for attaching the first end to a first discrete bone on a first side of a joint; and a first inner surface configured to substantially con- 40
- form with a geometry of the first bone;
- a second end comprising:
 - at least one fixation point for attaching the second end to a second discrete bone on a second side of the joint: and 45
- a second inner surface configured to substantially conform with a geometry of the second bone; and a bridge portion disposed between the first end and the

second end; and

- a transfixation screw hole disposed along the spine, the 50 transfixation screw hole comprising an inner surface configured to direct a transfixation screw through the transfixation screw hole such that the transfixation screw extends alongside the bridge portion at a trajectory configured to pass through a first position on the first bone and a second position on the second bone, enabling said screw to absorb tensile load when the second bone is loaded permitting transfer of the tensile load through said screw into said bridge, wherein at least a portion of said bridge portion and said transfix- 60 ation screw hole has a depth greater than at least a portion of said first and second ends.
- 11. The plate of claim 10, wherein:
- a central axis of the inner surface of the transfixation screw hole defines the trajectory; and
- the trajectory is configured to cross a neutral bending axis of the joint.

14

12. The plate of claim 11, wherein the first position resides on a compression side of the joint and the second position resides on a tension side of the joint.

13. The plate of claim 10, wherein the trajectory is configured to pass through the joint at a transfixation angle of about 50 degrees measured from the neutral bending axis.

14. The plate of claim 10, wherein the plate further includes a compression hole defined by an inner surface in the plate surrounding an oblong opening, the inner surface of the compression hole including, at one end, a horse-shoeshaped countersink.

15. The plate of claim 10, further comprising a first flared hip on a first side of the plate and a second flared hip on a second side of the plate, the flared hips comprising two generally parabolic wings extending laterally from the spine and being symmetrically opposed to one another about the transfixation screw hole.

16. A plate for securing two discrete bones together across

an elongate spine having:

- a first end comprising:
 - at least one fixation point for attaching the first end to a first discrete bone on a first side of a joint; and a first inner surface configured to substantially con-
 - form with a geometry of the first bone;

a second end comprising:

- at least one fixation point for attaching the second end to a second discrete bone on a second side of the joint; and
- a second inner surface configured to substantially conform with a geometry of the second bone; and
- a bridge portion disposed between the first end and the second end: and
- a transfixation screw hole disposed along the spine, the transfixation screw hole comprising an inner surface configured to direct a transfixation screw through the transfixation screw hole such that the transfixation screw extends alongside the bridge portion at a trajectory configured to pass through a first position on the first bone and a second position on the second bone, enabling said screw to absorb tensile load when the second bone is loaded permitting transfer of the tensile load through said screw into said bridge, wherein at least a portion of said bridge portion and said transfixation screw hole has a thickness greater than at least a portion of said first and second ends.

17. The plate of claim 16, wherein:

- a central axis of the inner surface of the transfixation screw hole defines the trajectory; and
- the trajectory is configured to cross a neutral bending axis of the joint.

18. The plate of claim 17, wherein the first position 55 resides on a compression side of the joint and the second position resides on a tension side of the joint.

19. The plate of claim 16, wherein the trajectory is configured to pass through the joint at a transfixation angle of about 50 degrees measured from the neutral bending axis.

20. The plate of claim 16, wherein the plate further includes a compression hole defined by an inner surface in the plate surrounding an oblong opening, the inner surface of the compression hole including, at one end, a horse-shoeshaped countersink.

21. The plate of claim 16, further comprising a first flared hip on a first side of the plate and a second flared hip on a second side of the plate, the flared hips comprising two

> STRYKER Exhibit 1001 Page 13 of 14 IPR2022-00191

generally parabolic wings extending laterally from the spine and being symmetrically opposed to one another about the transfixation screw hole.

* * * * *

STRYKER Exhibit 1001 Page 14 of 14 IPR2022-00191